

Package ‘METAAB’

February 9, 2019

Type Package

Title Multi Environment Trials Analysis using AMMI and BLUP

Version 1.0.0

Author Tiago Olivoto

Date 2019-01-05

Maintainer Tiago Olivoto <tiagoolivoto@gmail.com>

Description This package compute has useful functions for computing stability analysis using AMMI and BLUP methods. Several procedures, including cross-validation, prediction, and stability parameters for AMMI and BLUP models are available. Tools for personalized graphics is also provided.

Depends R (>= 3.5.0)

License GPL (>=3)

Encoding UTF-8

LazyData true

Imports dplyr, plyr, data.table, dendextend, heatmaply, gplots, ggExtra, grid, ggplot2, ggrepel, lme4, lmerTest, gtools, magrittr, methods, MASS

RoxygenNote 6.0.1

Suggests knitr, rmarkdown, testthat, xlsx, readxl, rJava, ReporteRs, cowplot

URL <https://github.com/TiagoOlivoto/METAAB>

VignetteBuilder knitr

RemoteType github

RemoteHost api.github.com

RemoteRepo METAAB

RemoteUsername TiagoOlivoto

RemoteRef master

RemoteSha 2d339b81389b07a5a7163e624d7727a44561dbde

GithubRepo METAAB

GithubUsername TiagoOlivoto

GithubRef master

GithubSHA1 2d339b81389b07a5a7163e624d7727a44561dbde

NeedsCompilation no

R topics documented:

| | |
|---------------------------------|-----------|
| AMMI_indexes | 2 |
| autoplot | 4 |
| FAI.BLUP | 5 |
| int.effects | 6 |
| meansGxE | 6 |
| MTSI | 6 |
| performs_ammi | 7 |
| plot.blup | 8 |
| plot.eigen | 9 |
| plot.FAI.BLUP | 10 |
| plot.MTSI | 11 |
| plot.scores | 11 |
| plot.validation.AMMIF | 14 |
| plot.WAASBY | 15 |
| plot.WAASBYratio | 17 |
| predict.WAAS.AMMI | 18 |
| resca | 19 |
| Resende_indexes | 19 |
| summary.WAAS.AMMI | 21 |
| summary.WAASB | 22 |
| theme_waasb | 22 |
| validation.AMMI | 23 |
| validation.AMMIF | 24 |
| validation.blup | 25 |
| WAAS.AMMI | 26 |
| WAASB | 29 |
| WAASBdata | 31 |
| WAASBYratio | 32 |
| WAASratio.AMMI | 33 |
| Index | 35 |

AMMI_indexes

AMMI-based indexes for stability and simultaneous selection

Description

This function computes the following AMMI-based stability indexes: ASV, AMMI stability value (Purchase et al., 2000); SIPC, sums of the absolute value of the IPCA scores (Sneller et al. 1997); EV, averages of the squared eigenvector values (Sneller et al. 1997); and Za, absolute value of the relative contribution of IPCAs to the interaction (Zali et al. 2012).

Usage

```
AMMI_indexes(x, order.y = NULL)
```

Arguments

| | |
|----------------------|---|
| <code>x</code> | An object of class WAAS.AMMI |
| <code>order.y</code> | A vector of the same length of <code>x</code> used to order the response variable. Each element of the vector must be one of the "h" or "l". If "h" is used, the response variable will be ordered from maximum to minimum. If "l" is used the response variable will be ordered from minimum to maximum. |

Details

The ASV index is computed as follows:

$$ASV_i = \left[\left[\frac{r \lambda_1^2}{r \lambda_2^2} \times (\lambda_1^{0.5} a_{i1} t_{j1}) \right]^2 + (\lambda_2^{0.5} a_{i2} t_{j2})^2 \right]^{0.5}$$

where r is the number of replications included in the analysis,

The SIPC index is computed as follows:

$$SIPC_i = \sum_{k=1}^P \left| \lambda_k^{0.5} a_{ik} \right|$$

where P is the number of IPCA retained via F-tests.

The EV index is computed as follows:

$$EV_i = \sum_{k=1}^P a_{ik}^2 / P$$

The ZA index is computed as follows:

$$Za_i = \sum_{k=1}^P \theta_k a_{ik}$$

where θ_k is the percentage sum of squares explained by the k th IPCA.

Four simultaneous selection indexes (ssi) are also computed by summation of the ranks of the ASV, SIPC, EV and Za indexes and the ranks of the mean yields (Farshadfar, 2008), which results in ssiASV, ssiSIPC, ssiEV, and ssiZa, respectively.

Value

A dataframe containing the indexes

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

References

- Purchase, J.L., H. Hatting, and C.S. van Deventer. 2000. Genotype vs environment interaction of winter wheat (*Triticum aestivum* L.) in South Africa: II. Stability analysis of yield performance. South African J. Plant Soil 17:101-107. doi:10.1080/02571862.2000.10634878
- Sneller, C.H., L. Kilgore-Norquest, and D. Dombek. 1997. Repeatability of Yield Stability Statistics in Soybean. Crop Sci. 37:383-390. doi:10.2135/cropsci1997.0011183X003700020013x
- Zali, H., E. Farshadfar, S.H. Sabaghpour, and R. Karimizadeh. 2012. Evaluation of genotype vs environment interaction in chickpea using measures of stability from AMMI model. Ann. Biol. Res. 3:3126-3136. http://eprints.icrisat.ac.in/id/eprint/7173

Examples

```
library(METAAB)
model = WAAS.AMMI(WAASBdata, GY, GEN, ENV, REP)
model_indexes = AMMI_indexes(model)
```

autoplot

Set of plots residuals for models of class WAAS.AMMI and WAASB

Description

Residual plots for a output model of class "WAAS.AMMI" and "WAASB". Six sets of plots are produced: (1) Residuals vs fitted, (2) normal Q-Q plot for the residuals, (3) scale-location plot (standardized residuals vs Fitted Values), (4) standardized residuals vs Factor-levels, (5) Histogram of raw residuals and (6) standardized residuals vs observation order. For a "WAASB" object, normal Q-Q plot for random effects may also be obtained declaring type = "re"

Usage

```
## S3 method for class 'WAAS.AMMI'
autoplot(x, conf = 0.95, labels = FALSE, theme = theme_waasb(),
         alpha = 0.2, fill.hist = "gray", col.hist = "black",
         col.point = "black", col.line = "red", col.lab.out = "red",
         size.lab.out = 2.5, size.tex.lab = 10, size.shape = 1.5,
         bins = 30, which = c(1:4), mfrow = c(2, 2), ...)

## S3 method for class 'WAASB'
autoplot(x, type = "res", conf = 0.95, labels = FALSE, theme = theme_waasb(),
         alpha = 0.2, fill.hist = "gray", col.hist = "black",
         col.point = "black", col.line = "red", col.lab.out = "red",
         size.lab.out = 2.5, size.tex.lab = 10, size.shape = 1.5,
         bins = 30, which = c(1:4), mfrow = c(2, 2), ...)
```

Arguments

| | |
|-------------|---|
| x | An object of class WAAS.AMMI or WAASB. |
| type | If type = "re", normal Q-Q plots for the random effects are obtained. |
| conf | Level of confidence interval to use in the Q-Q plot (0.95 by default). |
| labels | Logical argument. If TRUE labels the points outside confidence interval limits. |
| theme | The theme to use in the graphics. Default is theme = theme_waasb(). |
| alpha | The transparency of confidence band in the Q-Q plot. Must be a number between 0 (opaque) and 1 (full transparency). |
| fill.hist | The color to fill the histogram. Default is "gray". |
| col.hist | The color of the border of the the histogram. Default is "black". |
| col.point | The color of the points in the graphic. Default is "black". |
| col.line | The color of the lines in the graphic. Default is "red". |
| col.lab.out | The color of the labels for the "outlying" points. |

| | |
|---------------------------|--|
| <code>size.tex.lab</code> | The size of the text in axis text and labels. |
| <code>size.shape</code> | The size of the shape in the plots. |
| <code>bins</code> | The number of bins to use in the histogram. Default is 30. |
| <code>which</code> | Which graphics should be plotted. Default is <code>which = c(1:4)</code> that means that the first four graphics will be plotted. |
| <code>mfrow</code> | Allow creating a simple multi-paneled plot. Must be a vector of length 2. The first argument is the number of rows and the second the number of columns. Default is <code>mfrow = c(2, 2)</code> . |
| <code>...</code> | Additional parameter for the function |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

Examples

```
library(METAAB)
model = WAAS.AMMI(WAASBdata, GY, GEN, ENV, REP)
autoplot(model)

model2 = WAASB(WAASBdata, GY, GEN, ENV, REP)
autoplot(model2)
```

FAI.BLUP

Multitrait index based on factor analysis and ideotype-design

Description

Multitrait index based on factor analysis and ideotype-design proposed by Rocha et al. (2018).

Usage

```
FAI.BLUP(x, DI, UI, show = TRUE, SI = NULL, mineval = 1)
```

Arguments

| | |
|----------------------|---|
| <code>x</code> | An object of class WAASB |
| <code>DI, UI</code> | A vector of the same length of <code>x</code> to construct the desirable/undesirable ideotype. For each element of the vector, allowed values are "max", "min", "mean", or a numeric value. |
| <code>show</code> | Logical value. If TRUE the results are shown in console. |
| <code>SI</code> | An integer [0-100]. The selection intensity in percentage of the total number of genotypes. |
| <code>mineval</code> | The minimum value so that an eigenvector is retained in the factor analysis. |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

References

Rocha, J.R.A.S.C.R, J.C. Machado, and P.C.S. Carneiro. 2018. Multitrait index based on factor analysis and ideotype-design: proposal and application on elephant grass breeding for bioenergy. GCB Bioenergy 10:52-60. doi: [doi:10.1111/gcbb.12443](https://doi.org/10.1111/gcbb.12443).

int.effects

Dataset with genotype-by-environment interaction effects

Description

This dataset contains a matrix with interaction effects of 10 genotypes cultivated in 5 environments.

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[meansGxE](#)

meansGxE

A dataset with means of 10 genotypes cultivated in 5 environments

Description

This dataset contains the means for grain yield of 10 genotypes cultivated in 5 environments. The interaction effects for this data is found in [int.effects](#)

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

MTSI

Multitrait stability index

Description

Multitrait stability index in analysis of multi-environment trials using AMMI or BLUP methods.

Usage

```
MTSI(x, index = "WAASB", show = TRUE, SI = 15, mineval = 1)
```

Arguments

| | |
|---------|--|
| x | An object of class WAASB or WAAS.AMMI. |
| index | If index = "WAASB" (Default) the multitrait index will be computed considering the stability of genotypes only. If index = "WAASBY" both stability and mean performance are considered. More details can be seen in WAASB and WAAS.AMMI functions. |
| show | If show = TRUE (Default) some results are shown in the console. |
| SI | An integer [0-100]. The selection intensity in percentage of the total number of genotypes. |
| mineval | The minimum value so that an eigenvector is retained in the factor analysis. |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

performs_amm

Performs Additive Main effects and Multiplicative Interaction

Description

Compute the Additive Main effects and Multiplicative interaction. This is a helper function for other procedures performed in the WAASB package.

Usage

```
performs_amm(ENV, GEN, REP, Y)
```

Arguments

| | |
|-----|--|
| ENV | The name of the collum that contains the levels of the environments |
| GEN | The name of the collum that contains the levels of the genotypes |
| REP | The name of the collum that contains the levels of the replications/blocks |
| Y | The response variable |

Value

| | |
|----------|--|
| ANOVA | The analysis of variance for the AMMI model. |
| analysis | The principal component analysis |
| means | means of genotype vs environment |
| biplot | escores for genotypes and environments in all the possible axes. |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

Examples

```
amm_model = with(WAASBdata, performs_amm(ENV, GEN, REP, GY))
```

plot.blup

*Plot the BLUPs for genotypes***Description**

Plot the predicted BLUP of the genotypes.

Usage

```
## S3 method for class 'blup'
plot(x, prob = 0.95, export = FALSE, file.type = "pdf",
      file.name = NULL, theme = theme_waasb(), width = 6,
      height = 6, size.err.bar = 0.5, size.shape = 3.5,
      size.tex.lab = 12, height.err.bar = 0.3, x.lim = NULL,
      x.breaks = waiver(), col.shape = c("blue", "red"),
      y.lab = "Genotypes", x.lab = "Predicted Grain Yield",
      resolution = 300, ...)
```

Arguments

| | |
|----------------|--|
| x | The WAASB object |
| prob | The probability to be considered in confidence interval prediction. |
| export | Export (or not) the plot. Default is TRUE. |
| file.type | If export = TRUE, define the type of file to be exported. Default is pdf, Graphic can also be exported in *.tiff format by declaring file.type = "tiff". |
| file.name | The name of the file for exportation, default is NULL, i.e. the files are automatically named. |
| theme | The graphical theme of the plot. Default is 'theme = theme_waasb()'. Please, see '?WAASB::theme_waasb'. An own theme can be applied using the arguments: 'theme = theme_waasb() + theme(some stuff here)'. For more details, please, see '?ggplot2::theme' |
| width | The width "inch" of the plot. Default is 6. |
| height | The height "inch" of the plot. Default is 6. |
| size.err.bar | The size of the error bar for the plot. Default is 0.5. |
| size.shape | The size of the shape (both for genotypes and environments). Default is 3.5. |
| size.tex.lab | The size of the text in axis text and labels. |
| height.err.bar | The height for error bar. Default is 0.3. |
| x.lim | The range of x-axis. Default is NULL (maximum and minimum values of the data set). New arguments can be inserted as x.lim = c(x.min, x.max). |
| x.breaks | The breaks to be plotted in the x-axis. Default is automatic breaks. New arguments can be inserted as x.breaks = c(breaks) |
| col.shape | A vector of length 2 that contains the color of shapes for genotypes above and below of the mean, respectively. Default is c("blue", "red"). |
| x.lab | The label of the x-axis in the plot. Default is "Predicted Grain Yield". |
| y.lab | The label of the y-axis in the plot. Default is "Genotypes". |
| resolution | The resolution of the plot. Parameter valid if file.type = "tiff" is used. Default is 300 (300 dpi) |
| ... | Other arguments of the function |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[plot.scores](#), [plot.WAASBY](#)

Examples

```
library(METAAB)
model = WAASB(WAASBdata, resp = "GY", weight.response = 50, weight.WAAS = 50)
plot.blup(model)
```

plot.eigen

Plot the eigenvalues

Description

Plot the eigenvalues for from singular value decomposition of BLUP interaction effects matrix.

Usage

```
## S3 method for class 'eigen'
plot(x, export = FALSE, theme = theme_waasb(),
     file.type = "pdf", file.name = NULL, width = 6, height = 6,
     size.shape = 3.5, size.line = 1, size.tex.lab = 12,
     y.lab = "Eigenvalue", y2.lab = "Accumulated variance",
     x.lab = "Number of multiplicative terms", resolution = 300, ...)
```

Arguments

| | |
|--------------|--|
| x | The WAASB object |
| export | Export (or not) the plot. Default is TRUE. |
| theme | The graphical theme of the plot. Default is 'theme = theme_waasb()'. Please, see '?WAASB::theme_waasb'. An own theme can be applied using the arguments: 'theme = theme_waasb() + theme(some stuff here)'. For more details, please, see '?ggplot2::theme' |
| file.type | If export = TRUE, define the type of file to be exported. Default is pdf, Graphic can also be exported in *.tiff format by declaring file.type = "tiff". |
| file.name | The name of the file for exportation, default is NULL, i.e. the files are automatically named. |
| width | The width "inch" of the plot. Default is 6. |
| height | The height "inch" of the plot. Default is 6. |
| size.shape | The size of the shape. Default is 3.5. |
| size.line | The size of the line. Default is 1. |
| size.tex.lab | The size of the text in axis text and labels. |

| | |
|------------|---|
| y.lab | The label of the y-axis in the plot. Default is "Eigenvalue". |
| y2.lab | The label of the second y-axis in the plot. Default is "Accumulated variance". |
| x.lab | The label of the x-axis in the plot. Default is "Number of multiplicative terms". |
| resolution | The resolution of the plot. Parameter valid if file.type = "tiff" is used. Default is 300 (300 dpi) |
| ... | Other arguments of the function |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[plot.scores](#), [plot.WAASBY](#)

Examples

```
library(METAAB)
model = WAASB(WAASBdata, GY, GEN, ENV, REP)
plot.eigen(model)
```

plot.FAI.BLUP

Multitrait index based on factor analysis and ideotype-design

Description

Plot the multitrait index based on factor analysis and ideotype-design proposed by Rocha et al. (2018).

Usage

```
## S3 method for class 'FAI.BLUP'
plot(x, ideotype = 1, SI = 15, radar = TRUE, ...)
```

Arguments

| | |
|----------|---|
| x | An object of class WAASB |
| ideotype | The ideotype to be plotted. Default is 1. |
| SI | An integer [0-100]. The selection intensity in percentage of the total number of genotypes. |
| radar | Logical argument. If true (default) a radar plot is generated after using coord_polar(). |
| ... | Other arguments of the function |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

References

Rocha, J.R.A.S.C.R, J.C. Machado, and P.C.S. Carneiro. 2018. Multitrait index based on factor analysis and ideotype-design: proposal and application on elephant grass breeding for bioenergy. GCB Bioenergy 10:52-60. doi: [doi:10.1111/gcbb.12443](https://doi.org/10.1111/gcbb.12443).

| | |
|-----------|--|
| plot.MTSI | <i>Plot the multitrait stability index</i> |
|-----------|--|

Description

Plot the multitrait stability index using ggplot-generated graphics. .

Usage

```
## S3 method for class 'MTSI'
plot(x, SI = 15, radar = TRUE, ...)
```

Arguments

| | |
|-------|---|
| x | An object of class MTSI |
| SI | An integer [0-100]. The selection intensity in percentage of the total number of genotypes. |
| radar | Logical argument. If true (default) a radar plot is generated after using coord_polar(). |
| ... | Other arguments of the function |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

| | |
|-------------|---|
| plot.scores | <i>Plot scores in different graphical interpretations</i> |
|-------------|---|

Description

Plot scores of genotypes and environments in different graphics. 1 = PC1 x PC2, 2 = GY x PC1, 3 = GY x WAASB, and 4 = Nominal yield x EPCA1.

Usage

```
## S3 method for class 'scores'
plot(x, type = 1, polygon = FALSE, file.type = "pdf",
     export = FALSE, file.name = NULL, theme = theme_waasb(),
     axis.expand = 1.1, width = 8, height = 7, x.lim = NULL,
     x.breaks = waiver(), x.lab = NULL, y.lab = NULL,
     y.lim = NULL, y.breaks = waiver(), shape.gen = 21,
     shape.env = 23, size.shape = 2.5, size.tex.lab = 12,
     size.tex.pa = 3.5, size.line = 0.5, size.segm.line = 0.5,
     leg.lab = c("Gen", "Env"), line.type = "solid", line.alpha = 0.9,
     col.line = "gray", col.gen = "blue", col.env = "darkgreen",
     col.alpha = 0.9, col.segm.gen = "transparent",
     col.segm.env = "darkgreen", resolution = 300, ...)
```

Arguments

| | |
|-----------------------------|--|
| <code>x</code> | The object WAASB or WAAS.AMMI |
| <code>type</code> | Three types of graphics can be generated: 1 = PC1 x PC2, default, to make inferences related to the interaction effects; 2 = GY x PC1 to make inferences related to stability and productivity; 3 = GY x WAASB, and 4 = Nominal yield x Environment PC1. |
| <code>polygon</code> | Logical argument. If TRUE, a polygon is drawn when type 1. |
| <code>file.type</code> | The type of file to be exported. Valid parameter if <code>export = T TRUE</code> . Default is "pdf". The graphic can also be exported in *.tiff format by declaring <code>file.type = "tiff"</code> . |
| <code>export</code> | Export (or not) the plot. Default is FALSE. |
| <code>file.name</code> | The name of the file for exportation, default is NULL, i.e. the files are automatically named. |
| <code>theme</code> | The graphical theme of the plot. Default is 'theme = theme_waasb()'. Please, see '?WAASB::theme_waasb'. An own theme can be applied using the arguments: 'theme = theme_waasb() + theme(some stuff here)'. For more details, please, see '?ggplot2::theme' |
| <code>axis.expand</code> | Multiplication factor to expand the axis limits by to enable fitting of labels. Default is 1.1. |
| <code>width</code> | The width "inch" of the plot. Default is 8. |
| <code>height</code> | The height "inch" of the plot. Default is 7. |
| <code>x.lim</code> | The range of x-axis. Default is NULL (maximum and minimum values of the data set). New arguments can be inserted as <code>x.lim = c(x.min, x.max)</code> . |
| <code>x.breaks</code> | The breaks to be plotted in the x-axis. Default is automatic breaks. New arguments can be inserted as <code>x.breaks = c(breaks)</code> |
| <code>x.lab</code> | The label of x-axis. Each plot has a default value. New arguments can be inserted as <code>x.lab = "my label"</code> . |
| <code>y.lab</code> | The label of y-axis. Each plot has a default value. New arguments can be inserted as <code>y.lab = "my label"</code> . |
| <code>y.lim</code> | The range of x-axis. Default is NULL. The same arguments than <code>x.lim</code> can be used. |
| <code>y.breaks</code> | The breaks to be plotted in the x-axis. Default is automatic breaks. The same arguments than <code>x.breaks</code> can be used. |
| <code>shape.gen</code> | The shape for genotype indication in the biplot. Default is 21 (circle). Values must be between 21-25: 21 (circle), 22 (square), 23 (diamond), 24 (up triangle), and 25 (low triangle). |
| <code>shape.env</code> | The shape for environment indication in the biplot. Default is 23 (diamond). The same arguments than "shape.gen". |
| <code>size.shape</code> | The size of the shape (both for genotypes and environments). Default is 2.5. |
| <code>size.tex.lab</code> | The size of the text in the axes text and labels. Default is 12. |
| <code>size.tex.pa</code> | The size of the text of the plot area. Default is 3.5. |
| <code>size.line</code> | The size of the line that indicate the means in the biplot. Default is 0.5. |
| <code>size.segm.line</code> | The size of the segment that start in the origin of the biplot and end in the scores values. Default is 0.5. |
| <code>leg.lab</code> | The labs of legend. Default is Gen and Env. |


```

plot.scores(model, 3, col.gen = "blue", col.env = "red",
  theme = theme_waasb() + theme(axis.title = element_text(size = 14)))
# GY x WAAS.pdf

plot.scores(model, 4)
# no file exported

```

plot.validation.AMMIF *Plot the RMSPD of all AMMI-family tested models*

Description

Boxplot showing the Root Means Square Prediction Difference of all AMMI family models obtained in a cross-validation procedure.

Usage

```

## S3 method for class 'validation.AMMIF'
plot(x, violin = FALSE, export = FALSE, x.lab = NULL,
  y.lab = NULL, size.tex.lab = 12, file.type = "pdf",
  file.name = NULL, theme = theme_waasb(), width = 6,
  height = 6, resolution = 300, col.violin = "gray90",
  col.boxplot = "gray70", width.boxplot = 0.2,
  x.lim = NULL, x.breaks = waiver(), ...)

```

Arguments

| | |
|---------------------------|---|
| <code>x</code> | An object of class <code>validation.AMMIF</code> . |
| <code>violin</code> | Define if a violine plot is used with boxplot. Default is "TRUE" |
| <code>export</code> | Export (or not) the plot. Default is T. |
| <code>x.lab</code> | The label of x-axis. New arguments can be inserted as <code>x.lab = "my x label"</code> . |
| <code>y.lab</code> | The label of y-axis. New arguments can be inserted as <code>y.lab = "my y label"</code> . |
| <code>size.tex.lab</code> | The size of the text in axis text and labels. |
| <code>file.type</code> | The type of file to be exported. Default is pdf, Graphic can also be exported in *.tiff format by declaring <code>file.type = "tiff"</code> . |
| <code>file.name</code> | The name of the file for exportation, default is NULL, i.e. the files are automatically named. |
| <code>theme</code> | The graphical theme of the plot. Default is <code>'theme = theme_waasb()'</code> . Please, see <code>'?WAASB::theme_waasb'</code> . An own theme can be applied using the arguments: <code>'theme = theme_waasb() + theme(some stuff here)'</code> . For more details, please, see <code>'?ggplot2::theme'</code> |
| <code>width</code> | The width "inch" of the plot. Default is 6. |
| <code>height</code> | The height "inch" of the plot. Default is 6. |
| <code>resolution</code> | The resolution of the plot. Parameter valid if <code>file.type = "tiff"</code> is used. Default is 300 (300 dpi) |

| | |
|---------------|--|
| col.violin | Parameter valid if violin = T. Define the color of the violin plot. Default is "gray90. |
| col.boxplot | Define the color for boxplot. Default is "gray70". |
| width.boxplot | The width of boxplots. Default is 0.2. |
| x.lim | The range of x-axis. Default is NULL (maximum and minimum values of the data set). New arguments can be inserted as x.lim = c(x.min, x.max). |
| x.breaks | The breaks to be plotted in the x-axis. Default is automatic breaks. New arguments can be inserted as x.breaks = c(breaks) |
| ... | Other arguments of the function |

Details

Five statistics are shown in this type of plot. The lower and upper hinges correspond to the first and third quartiles (the 25th and 75th percentiles). The upper whisker extends from the hinge to the largest value no further than $1.5 * \text{IQR}$ from the hinge (where IQR is the inter-quartile range). The lower whisker extends from the hinge to the smallest value at most $1.5 * \text{IQR}$ of the hinge. Data beyond the end of the whiskers are considered outlying points.

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[plot.scores](#), [plot.WAASBY](#)

Examples

```
library(METAAB)
validation = validation.AMMIF(WAASBdata, GY, GEN, ENV, REP,
                              nboot = 100, nrepval = 2)

#A plot without a violin plot exported to a *.pdf file
plot(validation, violin = F, export = T)
```

plot.WAASBY

Plot WAASBY values for genotype ranking

Description

Plot heat maps with genotype ranking in two ways.

Usage

```
## S3 method for class 'WAASBY'
plot(x, export = F, file.type = "pdf", file.name = NULL,
     theme = theme_waasb(), width = 6, height = 6, size.shape = 3.5,
     size.tex.lab = 12, col.shape = c("blue", "red"), y.lab = "Genotypes",
     x.breaks = waiver(), resolution = 300, ...)
```

Arguments

| | |
|---------------------------|---|
| <code>x</code> | The WAASBY object |
| <code>export</code> | Export (or not) the plot. Default is T. |
| <code>file.type</code> | The type of file to be exported. Default is pdf, Graphic can also be exported in *.tiff format by declaring <code>file.type = "tiff"</code> . |
| <code>file.name</code> | The name of the file for exportation, default is NULL, i.e. the files are automatically named. |
| <code>theme</code> | The graphical theme of the plot. Default is <code>'theme = theme_waasb()'</code> . Please, see <code>'?WAASB::theme_waasb'</code> . An own theme can be applied using the arguments: <code>'theme = theme_waasb() + theme(some stuff here)'</code> . For more details, please, see <code>'?ggplot2::theme'</code> |
| <code>width</code> | The width "inch" of the plot. Default is 8. |
| <code>height</code> | The height "inch" of the plot. Default is 7. |
| <code>size.shape</code> | The size of the shape in the plot. Default is 3.5. |
| <code>size.tex.lab</code> | The size of the text in axis text and labels. |
| <code>col.shape</code> | A vector of length 2 that contains the color of shapes for genotypes above and below of the mean, respectively. Default is <code>c("blue", "red")</code> . |
| <code>y.lab</code> | The label of the y-axis in the plot. Default is "Genotypes". |
| <code>x.breaks</code> | The breaks to be plotted in the x-axis. Default is automatic breaks. New arguments can be inserted as <code>x.breaks = c(breaks)</code> |
| <code>resolution</code> | The resolution of the plot. Parameter valid if <code>file.type = "tiff"</code> is used. Default is 300 (300 dpi) |
| <code>...</code> | Other arguments of the function |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[plot.scores](#)

Examples

```
library(METAAB)
# plotting the WAASBY values based on blup procedure
#model = WAASBYratio(WAASBdata, resp = "GY", increment = 5, saveWAASY = 60)
#plot.WAASBY(model)

# plotting the WAASY value based on traditional AMMI model
#model2 = WAASratio.AMMI(WAASBdata, resp = "GY", increment = 5, saveWAASY = 60)
#plot.WAASBY(model2)
```

| | |
|------------------|---|
| plot.WAASBYratio | <i>Plot heat maps with genotype ranking</i> |
|------------------|---|

Description

Plot heat maps with genotype ranking in two ways.

Usage

```
## S3 method for class 'WAASBYratio'
plot(x, type, export = FALSE, file.type = "pdf",
      file.name = NULL, width = 6, height = 5, size.lab = 1,
      margins = c(5, 4), y.lab = NULL, x.lab = NULL,
      key.lab = "Genotype ranking", resolution = 300, ...)
```

Arguments

| | |
|------------|--|
| x | The WAASYratio object |
| type | 1 = Heat map Ranks: this graphic shows the genotype ranking considering the WAAS estimated with different numbers of Principal Components; 2 = Heat map WAASY-GY ratio: this graphic shows the genotype ranking considering the different combinations in the WAAS/GY ratio. |
| export | Export (or not) the plot. Default is TRUE. |
| file.type | If export = TRUE define the type of file to be exported. Default is pdf, Graphic can also be exported in *.tiff format by declaring file.type = "tiff". |
| file.name | The name of the file for exportation, default is NULL, i.e. the files are automatically named. |
| width | The width "inch" of the plot. Default is 8. |
| height | The height "inch" of the plot. Default is 7. |
| size.lab | The label size of the plot. It is suggested attribute 1 |
| margins | Numeric vector of length 2 containing the margins for column and row names, respectively. Default is c(5, 4). |
| y.lab | The label of y axis. Default is "Genotypes". |
| x.lab | The label of x axis. Default is "Number of axes". |
| key.lab | The label of color key. Default is "Genotype ranking". |
| resolution | Valid parameter if file.type = "tiff". Define the resolution of the plot. Default is "300". |
| ... | Other arguments of the function |

Details

The first type of heatmap shows the genotype ranking depending on the number of principal component axis used for estimating the WAASB index. An euclidian distance-based dendrogram is used for grouping the genotype ranking for both genotypes and principal component axis. The second type of heatmap shows the genotype ranking depending on the WAASB/GY ratio. The ranks obtained with a ratio of 100/0 considers exclusively the stability for the genotype ranking. On the other hand, a ratio of 0/100 considers exclusively the productivity for the genotype ranking. Four clusters are estimated (1) unproductive and unstable genotypes; (2) productive, but unstable genotypes; (3) stable, but unproductive genotypes; and (4), productive and stable genotypes.

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[plot.scores](#)

Examples

```
library(METAAB)
model = WAASBYratio(WAASBdata, resp = "GY")

# plot the heatmap considering the ranks in different number of PC axis.
plot.WAASBYratio(model, type = 1)

# plot the heatmap considering the ranks in WAASY/GY ratio and export to a *.tiff file
plot.WAASBYratio(model, type = 2, export = TRUE, file.type = "tiff")
```

| | |
|-------------------|--|
| predict.WAAS.AMMI | <i>Predict the means of a WAAS.AMMI object</i> |
|-------------------|--|

Description

Predict the means of a WAAS.AMMI object considering a specific number of axis.

Usage

```
## S3 method for class 'WAAS.AMMI'
predict(object, naxis, ...)
```

Arguments

| | |
|--------|--|
| object | An object of class WAAS.AMMI |
| naxis | The the number of axis to be use in the prediction. If object has more than one variable, then naxis must be a vector. |
| ... | Additional parameter for the function |

Details

This function is used to predict the response variable of a two-way table (for examples the yielding of the i -th genotype in the j -th environment) based on AMMI model. This prediction is based on the number of multiplicative terms used. If `naxis = 0`, only the main effects (AMMI0) are used. In this case, the predicted mean will be the predicted value from OLS estimation. If `naxis = 1` the AMMI1 (with one multiplicative term) is used for predicting the response variable. If `naxis = min(gen-1; env-1)`, the AMMIF is fitted and the predicted value will be the cell mean, i.e. the mean of R-replicates of the i -th genotype in the j -th environment. The number of axis to be used must be carefully chosen. Precures based on Postdictive sucess (such as Gollob's d.f.) or Predictive sucess (such as cross-validation) should be used to do this. This package provide both. [WAAS.AMMI](#) function compute traditional AMMI analysis showing the number of significant axis. On the other hand, [validation.AMMIF](#) function provide a cross-validation, estimating the RMSE of all AMMI-family models, based on resampling procedure.

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

Examples

```
library(METAAB)
model = WAAS.AMMI(WAASBdata, GY, GEN, ENV, REP)
predict = predict.AMMI(model, naxis = 3)
```

| | |
|-------|---|
| resca | <i>Rescale a continuous vector to have specified minimum and maximum values</i> |
|-------|---|

Description

Helper function used in the WAASB package. It rescales a continuous vector to have specified minimum and maximum values. Missing values are not allowed.

Usage

```
resca(values, new_min = 0, new_max = 100)
```

Arguments

| | |
|---------|--|
| values | continuous vector of values to manipulate. |
| new_min | The minimum value of the new scale. Default is 0. |
| new_max | The maximum value of the new scale. Default is 100 |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

Examples

```
resca(1:10)
resca(c(20, 30, 40), new_min = 5, new_max = 10)
```

| | |
|-----------------|---|
| Resende_indexes | <i>Stability indexes proposed by Resende based on a mixed-effect model.</i> |
|-----------------|---|

Description

This function computes the following indexes proposed by Resende (2007): the harmonic mean of genotypic values (HMGV), the relative performance of the genotypic values (RPGV) and the harmonic mean of the relative performance of genotypic values (HMRPGV).

Usage

```
Resende_indexes(x)
```

Arguments

x An object of class WAASB

Details

The indexes computed with this function have been used to select genotypes with stability performance in a mixed-effect model framework. Some examples are in Alves et al (2018), Azevedo Peixoto et al. (2018), Dias et al. (2018) and Colombari Filho et al. (2013).

The HMGV index is computed as

$$HMGV_i = \frac{1}{E} \sum_{j=1}^E \frac{1}{Gv_{ij}}$$

where E is the number of environments included in the analysis, Gv_{ij} is the genotypic value (BLUP) for the i th genotype in the j th environment.

The RPGV index is computed as

$$RPGV_i = \frac{1}{e} \sum_{j=1}^e BLUP_{ij} / \mu_j$$

The HMRPGV index is computed as

$$HMRPGV_i = \frac{1}{E} \sum_{j=1}^E \frac{1}{Gv_{ij} / \mu_j}$$

Value

A dataframe containing the indexes

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

References

- Alves, R.S., L. de Azevedo Peixoto, P.E. Teodoro, L.A. Silva, E.V. Rodrigues, M.D.V. de Resende, B.G. Laviola, and L.L. Bhering. 2018. Selection of *Jatropha curcas* families based on temporal stability and adaptability of genetic values. *Ind. Crops Prod.* 119:290-293. doi:10.1016/J.INDCROP.2018.04.029.
- Colombari Filho, J.M., M.D.V. de Resende, O.P. de Moraes, A.P. de Castro, E.P. Guimaraes, J.A. Pereira, M.M. Utumi, and F. Breseghello. 2013. Upland rice breeding in Brazil: a simultaneous genotypic evaluation of stability, adaptability and grain yield. *Euphytica* 192:117-129. doi:10.1007/s10681-013-0922-2
- Dias, P.C., A. Xavier, M.D.V. de Resende, M.H.P. Barbosa, F.A. Biernaski, R.A. Estopa. 2018. Genetic evaluation of *Pinus taeda* clones from somatic embryogenesis and their genotype x environment interaction. *Crop Breed. Appl. Biotechnol.* 18:55-64. doi:10.1590/1984-70332018v18n1a8
- Azevedo Peixoto, L. de, P.E. Teodoro, L.A. Silva, E.V. Rodrigues, B.G. Laviola, and L.L. Bhering. 2018. *Jatropha* half-sib family selection with high adaptability and genotypic stability. *PLoS One* 13:e0199880. doi:10.1371/journal.pone.0199880.
- Resende MDV (2007) *Matematica e estatistica na analise de experimentos e no melhoramento genetico*. Embrapa Florestas, Colombo

Examples

```
library(METAAB)
model = WAASB(WAASBdata, GY, GEN, ENV, REP)
model_indexes = Resende_indexes(model)
```

| | |
|-------------------|-----------------------------------|
| summary.WAAS.AMMI | <i>Summary a WAAS.AMMI object</i> |
|-------------------|-----------------------------------|

Description

Summary the WAAS.AMMI object in two ways. By default, the results are shown in the R console. The results can also be exported to the directory.

Usage

```
## S3 method for class 'WAAS.AMMI'
summary(object, export = FALSE, file.name = NULL, digits = 4, ...)
```

Arguments

| | |
|-----------|--|
| object | The WAAS.AMMI object |
| export | A logical argument. If TRUE T, a *.txt file is exported to the working directory |
| file.name | The name of the file if export = TRUE |
| digits | The significant digits to be shown. |
| ... | Other arguments of the function |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

Examples

```
library(METAAB)
model = WAAS.AMMI(WAASBdata, GY, GEN, ENV, REP)
summary(model, digits = 2)
summary(model, export = T, file.name = "my results")
```

| | |
|---------------|-------------------------------|
| summary.WAASB | <i>Summary a WAASB object</i> |
|---------------|-------------------------------|

Description

Summary the WAASB object in two ways. By default, the results are shown in the R console. The results can also be exported to the directory.

Usage

```
## S3 method for class 'WAASB'
summary(object, export = FALSE, file.name = NULL, digits = 4, ...)
```

Arguments

| | |
|-----------|--|
| object | The WAASB object |
| export | A logical argument. If TRUE T, a *.txt file is exported to the working directory |
| file.name | The name of the file if export = TRUE |
| digits | The significant digits to be shown. |
| ... | Other arguments of the function |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

Examples

```
library(METAAB)
model = WAASB(WAASBdata, GY, GEN, ENV, REP)
summary(model, digits = 2)
summary(model, export = T, file.name = "my results")
```

| | |
|-------------|--|
| theme_waasb | <i>A personalized theme for the WAASB ggplot2-based graphics</i> |
|-------------|--|

Description

The function theme_waasb() is a personalized theme for the WAASB ggplot2-based graphics. An own theme can be applied in all graphics by using the following arguments in the plot. functions of the package: theme = theme_waasb() + theme(some stuff here...). See ?ggplot2::theme for more details.

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

validation.AMMI

*Cross-validation for estimation of AMMI model***Description**

Cross-validation for estimation of AMMI models

Usage

```
validation.AMMI(data, resp, gen, env, rep, design = "RCBD",
               nboot, nrepval, naxis, progbar = TRUE)
```

Arguments

| | |
|---------|---|
| data | The dataset containing the columns related to Environments, Genotypes, replication/block and response variable(s). |
| resp | The response variable, for example resp = "RG". |
| gen | The name of the column that contains the levels of the genotypes. |
| env | The name of the column that contains the levels of the environments. |
| rep | The name of the column that contains the levels of the replications/blocks. |
| design | The experimental design to be considered. Default is RCBD (Randomized complete Block Design). For Completely Randomized Designs inform design = "CRD". |
| nboot | The number of resamples to be used in the cross-validation |
| nrepval | The number of replicates (r) from total number of replicates (R) to be used in the modeling dataset. Only one replicate is used as validating data each step, so, Nrepval must be equal R-1 |
| naxis | The number of axis to be considered for estimation of GE effects. |
| progbar | A logical argument to define if a progress bar is shown. Default is TRUE. |

Details

For each iteration, the original dataset is split into two datasets: modeling and validating data. The dataset "modeling" has all combinations (genotype x environment) with the number of replications informed in nrepval. The dataset "validating" has one replication. The splitting of the dataset into modeling and validating data depends on the design informed. For Completely Randomized Block Design (default), completely blocks are selected within environments. The remained block serves validation data. If design = "RCD" is informed, completely randomly samples are made for each genotype-by-environment combination. The estimated values (depending on NAXIS informed) are compared with the "validating" data. the Root Means Square error is computed. At the end of boots, a list is returned with the following values.

Value

| | |
|-----------|---|
| RMSE | A vector with Nboot-estimates of the root mean squared error estimated with the difference between predicted and validating data. |
| RSMEmean | The mean of RMSE estimates. |
| Estimated | A data frame that contain the values (predicted, observed, validation) of the last loop. |
| Modeling | The dataset used as modeling data in the last loop. |
| Testing | The dataset used as testing data in the last loop. |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[validation.AMMIF](#)

Examples

```
library(METAAB)
validation = validation.AMMI(WAASBdata, GY, GEN, ENV, REP,
                             nboot = 100, nrepval = 2, naxis = 4)
```

validation.AMMIF

Cross-validation for estimation of all AMMI-family models

Description

Cross-validation for estimation of all AMMI-family models

Usage

```
validation.AMMIF(data, resp, gen, env, rep, design = "RCBD",
                  nboot, nrepval, progbar = TRUE)
```

Arguments

| | |
|---------|---|
| data | The dataset containing the columns related to Environments, Genotypes, replication/block and response variable(s). |
| resp | The response variable, for example <code>resp = GY</code> . |
| gen | The name of the column that contains the levels of the genotypes. |
| env | The name of the column that contains the levels of the environments. |
| rep | The name of the column that contains the levels of the replications/blocks. |
| design | The experimental design to be considered. Default is RCBD (Randomized complete Block Design). For Completely Randomized Designs inform <code>design = "CRD"</code> . |
| nboot | The number of resamples to be used in the cross-validation |
| nrepval | The number of replicates (r) from total number of replicates (R) to be used in the modeling dataset. Only one replicate is used as validating data each step, so, Nrepval must be equal R-1 |
| progbar | A logical argument to define if a progress bar is shown. Default is TRUE. |

Details

This function provides a complete cross-validation of replicate-based data using AMMI-family models. Automatically the first validation is carried out considering the AMMIF (all possible axis used). Considering this model, the original dataset is split into two datasets: modeling and validating data. The dataset "modeling" has all combinations (genotype x environment) with the number of replications informed in nrepval. The dataset "validating" has one replication. The splitting of the dataset into modeling and validating data depends on the design informed. For Completely Randomized Block Design (default), completely blocks are selected within environments. The remained block serves validation data. If design = "RCD" is informed, completely randomly samples are made for each genotype-by-environment combination. The estimated values (depending on naxis informed) are compared with the "validating" data. the Root Means Square error is computed. At the end of boots, a list is returned with the following values.

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[validation.AMMI](#)

Examples

```
library(METAAB)
validation = validation.AMMIF(WAASBdata, GY, GEN, ENV, REP,
                             nboot = 100, nrepval = 2)
```

| | |
|-----------------|---|
| validation.blup | <i>Cross-validation for blup prediction</i> |
|-----------------|---|

Description

Cross-validation for blup prediction.

Usage

```
validation.blup(data, resp, gen, env, rep,
                nboot, nrepval, progbars = TRUE)
```

Arguments

| | |
|-------|--|
| data | The dataset containing the columns related to Environments, Genotypes, replication/block and response variable(s). |
| resp | The response variable, for example resp = GY. |
| gen | The name of the column that contains the levels of the genotypes. |
| env | The name of the column that contains the levels of the environments. |
| rep | The name of the column that contains the levels of the replications/blocks. |
| nboot | The number of resamples to be used in the cross-validation |

| | |
|---------|---|
| nrepval | The number of replicates (r) from total number of replicates (R) to be used in the modeling dataset. Only one replicate is used as validating data each step, so, Nrepval must be equal R-1 |
| progbar | A logical argument to define if a progress bar is shown. Default is TRUE. |

Details

This function provides a cross-validation of replicate-based data using mixed models. By default, complete blocks are randomly selected each environment. In each iteration, the original dataset is split into two datasets: modeling and validating data. The dataset "modeling" has all combinations (genotype x environment) with the number of replications informed in nrepval. The dataset "validating" has one replication. The estimated values are compared with the "validating" data. the Root Means Square error is computed. At the end of boots, a list is returned.

Value

| | |
|------|--|
| RMSE | The root mean squared error estimated with the difference between predicted and validating data. |
|------|--|

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[plot.scores](#), [plot.WAASBY](#)

Examples

```
library(METAAB)
validation = validation.blup(WAASBdata, GY, GEN, ENV, REP,
                             nboot = 100, nrepval = 2)
```

WAAS.AMMI

Weighted Average of Absolute Scores for AMMI analysis

Description

Compute the Weighted Average of Absolute Scores for AMMI analysis.

Usage

```
WAAS.AMMI(data, resp, gen, env, rep, mresp = NULL,
           prob = 0.05, naxis = NULL,
           wresp = 50, verbose = TRUE)
```

Arguments

| | |
|-------|---|
| data | The dataset containing the columns related to Environments, Genotypes, replication/block and response variable(s). |
| resp | The response variable(s). To analyze multiple variables in a single procedure a vector of variables may be used. For example <code>resp = c(var1, var2, var3)</code> . |
| gen | The name of the column that contains the levels of the genotypes. |
| env | The name of the column that contains the levels of the environments. |
| rep | The name of the column that contains the levels of the replications/blocks. |
| mresp | A numeric vector of the same length of <code>resp</code> . The <code>mresp</code> will be the new maximum value after reescalating. By default, all variables in <code>resp</code> are rescaled so that the maximum value is 100 and the minimum value is 0. |
| prob | The p-value for considering a IPCA significant. |
| naxis | The number of IPCAs to be used for computing the WAAS index. Default is NULL (Significant IPCAs are used). If values are informed, the number of IPCAs will be used independently on its significance. Note that if two or more variables are included in <code>resp</code> , then <code>naxis</code> must be a vector. |
| wresp | The weight for the response variable(s) for computing the WAASBY index. Must be a numeric vector of the same length of <code>resp</code> . Default is 50, i.e., equal weights for stability and mean performance. |

Details

This function compute the weighted average of absolute scores, estimated as follows:

$$WAAS_i = \sum_{k=1}^p |IPCA_{ik} \times EP_k| / \sum_{k=1}^p EP_k$$

where $WAAS_i$ is the weighted average of absolute scores of the i th genotype; $IPCA_{ik}$ is the score of the i th genotype in the k th IPCA; and EP_k is the explained variance of the k th IPCA for $k = 1, 2, \dots, p$, considering p the number of significant PCAs, or a declared number of PCAs. For example if `prob = 0.05`, all axis that are significant considering this probability level are used. The number of axis can be also informed by declaring `naxis = x`. This command ignores the `p.valuePC` command.

Value

| | |
|------------|--|
| individual | A within-environments ANOVA considering a fixed-effect model. |
| model | A data frame with the response variable, the scores of all Principal Components, the estimates of Weighted Average of Absolute Scores, and WAASY (the index that consider the weights for stability and productivity in the genotype ranking). |
| MeansGxE | The means of genotypes in the environments, with observed, predicted and residual values. |
| PCA | Principal Component Analysis. |
| anova | Joint analysis of variance for the main effects and Principal Component analysis of the interaction effect. |
| Details | A list summarizing the results. The following information are showed. <code>WgtResponse</code> , the weight for the response variable in estimating WAASB, <code>WgtWAAS</code> the weight for stability, <code>Ngen</code> the number of genotypes, <code>Nenv</code> the number of environments, <code>OVmean</code> the overall mean, <code>Min</code> the minimum observed (returning the genotype |

and environment), Max the maximum observed, Max the maximum observed, MinENV the environment with the lower mean, MaxENV the environment with the larger mean observed, MinGEN the genotype with the lower mean, MaxGEN the genotype with the larger.

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[WAAS.AMMI](#)

Examples

```
library(METAAB)

# Considering p-value <= 0.05 to compute the WAAS

model <- WAAS.AMMI(WAASBdata,
  resp = GY,
  gen = GEN,
  env = ENV,
  rep = REP)

# Declaring the number of axis to be used for computing WAAS
# and assigning a larger weight for the response variable when
# computing the WAASBY index.

model2 <- WAAS.AMMI(WAASBdata,
  resp = GY,
  gen = GEN,
  env = ENV,
  rep = REP,
  naxis = 3,
  wresp = 60)

# Analyzing multiple variables (GY and HM) at the same time
# considering that smaller values of HM are better and higher
# values of GY are better, assigning a larger weight for the GY
# and a smaller weight for HM when computing WAASBY index.

model3 <- WAAS.AMMI(WAASBdata,
  resp = c(GY, HM),
  gen = GEN,
  env = ENV,
  rep = REP,
  mresp = c(100, 0)
  wresp = c(60, 40))
```

WAASB

Weighted Average of Absolute Scores for the BLUP'S GxE effects matrix generated by a mixed-effect model

Description

Compute the Weighted Average of Absolute Scores for quantifying the stability in multienvironment trials using mixed-effect models.

Usage

```
WAASB(data, resp, gen, env, rep, mresp = NULL,
       wresp = NULL, random = "gen", prob = 0.95,
       verbose = TRUE)
```

Arguments

| | |
|--------|--|
| data | The dataset containing the columns related to Environments, Genotypes, replication/block and response variable(s). |
| resp | The response variable(s). To analyze multiple variables in a single procedure a vector of variables may be used. For example <code>resp = c(var1, var2, var3)</code> . |
| gen | The name of the column that contains the levels of the genotypes. |
| env | The name of the column that contains the levels of the environments. |
| rep | The name of the column that contains the levels of the replications/blocks. |
| mresp | A numeric vector of the same length of <code>resp</code> . The <code>mresp</code> will be the new maximum value after reescalating. By default, all variables in <code>resp</code> are rescaled so that the maximum value is 100 and the minimum value is 0. |
| wresp | The weight for the response variable(s) for computing the WAASBY index. Must be a numeric vector of the same length of <code>resp</code> . Default is 50, i.e., equal weights for stability and mean performance. |
| random | The effects of the model assumed to be random. Default is <code>random = "gen"</code> (genotype and genotype-vs-environment as random effects. Other values allowed are <code>random = "env"</code> (environment, genotype-vs-environment and block-within-environment random effects) or <code>random = "all"</code> all effects except the intercept are assumed to be random effects. |
| prob | The probability for estimating confidence interval for BLUP's prediction. |

Details

This function compute the weighted average of absolute scores considering all principal component axis from the Singular Value Decomposition (SVD) of the BLUP'S GxE effects matrix generated by a linear mixed-effect model. The main advantage of this procedure in relation to the `WAAS.AMMI` function is that random effects can be included in the model. In addition, unbalanced datasets can also be modeled.

Value

The function returns the results in a list for each analyzed variable. For each variable, the following objects are returned.

| | |
|------------|---|
| individual | A within-environments ANOVA considering a fixed-effect model. |
| fixed | Test for fixed effects. |
| random | Variance components for random effects. |
| LRT | The Likelihood Ratio Test for the random effects. |
| model | A data frame with the response variable, the scores of all Principal Components, the estimates of Weighted Average of Absolute Scores, and WAASY (the index that consider the weights for stability and productivity in the genotype ranking). |
| blupGEN | The estimated BLUPS for genotypes (If random = "gen" or random = "all") |
| BLUPenv | The estimated BLUPS for environments, (If random = "env" or random = "all"). |
| BLUPge | The estimated BLUPS of all genotypes in all environments "BLUPij". |
| PCA | The results of Principal Component Analysis with eigenvalues and explained variance of BLUP-interaction matrix. |
| MeansGxE | The phenotypic means of genotypes in the environments, with observed, predicted and OLS residual prediction. |
| Details | A list summarizing the results. The following information are showed. WgtResponse, the weight for the response variable in estimating WAASB, WgtWAAS the weight for stability, Ngen the number of genotypes, Nenv the number of environments, OVmean the overall mean, Min the minimum observed (returning the genotype and environment), Max the maximum observed, Max the maximum observed, MinENV the environment with the lower mean, MaxENV the environment with the larger mean observed, MinGEN the genotype with the lower mean, MaxGEN the genotype with the larger. |
| ESTIMATES | A list with the following values: GEV the genotype-by-environment variance (and percentage of phenotypic variance); GV the genotypic variance (and percentage of phenotypic variance); EV the environmental variance; RV the residual variance (and percentage of phenotypic variance); FV the phenotypic variance; h2g the heritability of the trait; GER2 the coefficient of determination of the interaction effects; h2mg the heritability of the mean; AccuGen the selective accuracy; rge the genotype-environment correlation; CVg the genotypic coefficient of variation; CVr the residual coefficient of variation; CVratio the ratio between genotypic and residual coefficient of variation. |
| residuals | The residuals of the model. |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

See Also

[WAAS.AMMI](#)

Examples

```

library(METAAB)

# Genotypes as random effects and equal weights for both

# response variable and stability

model <- WAASB(WAASBdata,
               resp = GY,
               gen = GEN,
               env = ENV,
               rep = REP,
               wresp = 70)

# Higher weight for response variable

model2 <- WAASB(WAASBdata,
                resp = GY,
                gen = GEN,
                env = ENV,
                rep = REP,
                wresp = 65)

# Environment as random effects analyzing more than one variables
# considering that smaller values of HM are better and higher
# values of GY are better, assigning a larger weight for the GY
# and a smaller weight for HM when computing WAASBY index.

model3 <- WAASB(WAASBdata,
                random = "env",
                resp = c(GY, HM)
                gen = GEN,
                env = ENV,
                rep = REP,
                mresp = c(100, 0)
                wresp = c(60, 40))

```

WAASBdata

A replicate-based data of 10 genotypes cultivated in 11 environments

Description

This dataset contain the observed grain yield of 10 genotypes cultivated in 11 environments. The experimental design was a RCBD with 3 replicates(blocks). This data provide examples for several functions of WAAS package.

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

| | |
|-------------|---|
| WAASBYratio | <i>Weighted Average of Absolute Scores from SVD of BLUP-interaction effects matrix in different scenarios of WAASB/GY ratio</i> |
|-------------|---|

Description

Compute the Weighted Average of Absolute Scores for AMMI analysis in different combinations of weights for stability and productivity.

Usage

```
WAASBYratio(data, resp, gen, env, rep, increment = 5,
             saveWAASY = 50, progbars = TRUE)
```

Arguments

| | |
|-----------|--|
| data | The dataset containing the columns related to Environments, Genotypes, replication/block and response variable(s). |
| resp | The response variable, for example <code>resp = RG</code> . |
| gen | The name of the column that contains the levels of the genotypes. |
| env | The name of the column that contains the levels of the environments. |
| rep | The name of the column that contains the levels of the replications/blocks. |
| increment | The range of the increment for WAASB/GY ratio. Default is 5. The function compute the WAASBY values starting with a weight of 100 for stability and 0 for response variable. With the default, the first scenario will be a WAASB/GY ratio = 100/0. In the next scenario, the WAASBY values are computed based on a WAASB/GY ratio = 95/5. |
| saveWAASY | Automatically save the WAASY values when the weight for WAAS (stability) in the WAAS/GY ratio is "saveWAASY". Default is 100. The value of "saveWAASY" must be multiple of "Increment". If this assumption is not valid, an error will occur. |
| progbars | A logical argument to define if a progress bar is shown. Default is TRUE. |

Details

This function considers both stability (weighted average of absolute scores based on SVD of BLUP-interaction effects matrix) and productivity for genotype ranking. This function provides the option of attributing weights for stability and productivity in genotype ranking. This is important depending on the goal of a selection strategy. For example, if a goal of a breeding program is to select a genotype with high yielding (independently on the stability performance), that genotype with the first rank in an WAASB/GY = 0/100 ratio should be selected. The reciprocal is true. Aiming at selecting a high-stable genotype (independently on the productivity), that genotype with the first rank in an WAASB/GY = 100/0 ratio should be selected. By default, the increment on the WAASB/GY ratio is equal to 5. In other words, twenty one different combinations are computed. Each combination, the genotypes are ranked regarding the WAASY value.

Value

| | |
|--------------|--|
| anova | Joint analysis of variance for the main effects and Principal Component analysis of the interaction effect. |
| PC | Principal Component Analysis. |
| MeansGxE | The means of genotypes in the environments, with observed, predicted and residual values. |
| WAAS | A data frame with the response variable, the scores of all Principal Components, the estimates of Weighted Average of Absolute Scores, and WAASY (the index that consider the weights for stability and productivity in the genotype ranking). |
| WAASY | The values of the WAASY estimated when the weight for the stability in the loop match with argument "saveWAASY". |
| WAASY.values | All the values of WAASY estimated in the different scenarios of WAAS/GY weighting ratio. |

Author(s)

Tiago Olivoto <tiagoolivoto@gmail.com>

Examples

```
# Default, with increment of 5 and saving the WAASY values when weight is 50
library(METAAB)
model = WAASBYratio(WAASBdata, GY, GEN, ENV, REP)

# Incrementing 2-by-2 and saving the WAASY values when weight is 70

model2 = WAASBYratio(WAASBdata, GY, GEN, ENV, REP,
                     increment = 2, saveWAASY = 70)
```

| | |
|----------------|--|
| WAASratio.AMMI | <i>Weighted Average of Absolute Scores for AMMI analysis in different scenarios of WAAS/GY ratio</i> |
|----------------|--|

Description

Compute the Weighted Average of Absolute Scores for AMMI analysis in different combinations of weights for stability and productivity.

Usage

```
WAASratio.AMMI(data, resp, gen, env, rep, p.valuePC = 0.05,
               increment = 5, saveWAASY = 50, progbar = TRUE)
```

Arguments

| | |
|------|--|
| data | The dataset containing the columns related to Environments, Genotypes, replication/block and response variable(s). |
| resp | The response variable, for example resp = RG. |
| gen | The name of the column that contains the levels of the genotypes. |

Index

AMMI_indexes, [2](#)
autoplot, [4](#)

FAI.BLUP, [5](#)

int.effects, [6](#), [6](#)

meansGxE, [6](#), [6](#)
MTSI, [6](#)

performs_ammi, [7](#)
plot.blup, [8](#)
plot.eigen, [9](#)
plot.FAI.BLUP, [10](#)
plot.MTSI, [11](#)
plot.scores, [9](#), [10](#), [11](#), [15](#), [16](#), [18](#), [26](#)
plot.validation.AMMIF, [14](#)
plot.WAASBY, [9](#), [10](#), [13](#), [15](#), [15](#), [26](#)
plot.WAASBYratio, [17](#)
predict.WAAS.AMMI, [18](#)

resca, [19](#)
Resende_indexes, [19](#)

summary.WAAS.AMMI, [21](#)
summary.WAASB, [22](#)

theme_waasb, [22](#)

validation.AMMI, [23](#), [25](#)
validation.AMMIF, [18](#), [24](#), [24](#)
validation.blup, [25](#)

WAAS.AMMI, [7](#), [18](#), [26](#), [28](#), [30](#)
WAASB, [7](#), [29](#)
WAASBdata, [31](#)
WAASBYratio, [32](#)
WAASratio.AMMI, [33](#)