General Description

The LY25XX series are a group of positive voltage output,three –pin regulator,that provide a high current even when the input/output Voltage differerntial is small.Low power consumption and high accuracy is achieved through CMOS technology.They allow input voltages as high as 18V.

Features

- Ultra low quienscent current: 3.0uA(typ)
- High input voltage (up to 18v)
- Low dropout voltage :80mV@Iout=40mA (Vout=3.3v)
- Output voltage accuracy： ±2%
- Maximum output current：300mA (within max.power dissipation,Vout=3.3V)
- Low temperature coefficient
- Package：SOT23-3、TO-92、SOT89-3

Selection Guide



Typical Application

- Cameras, video recorders
- Voltage regulator for microprocessor
- Voltage regulator for LAN cards
- Wireless communication equipment
- Audio/Video equipment

Typical Application Circuit



Pin Configuration



SOT23-3 **SOT89-3** **TO-92**

Pin Assignment

LY25XX

Pin Number		Pin Name	Functions
SOT89-3/TO-92	SOT23-3		
1	1	V_{SS}	Ground
2	3	V_{IN}	Input
3	2	V_{OUT}	Output

Absolute Maximum Ratings

Parameter		Symbol	Ratings	Units
Input Voltage		V_{IN}	18	V
Output Voltage		V_{OUT}	Vss-0.3～V_{IN} +0.3	V
Output Current		Iout	500	mA
Operating Temperature Range		T_{OPR}	-40～+85	℃
Storage Temperature Range		T_{STG}	−40～+125	℃
Power Dissipation	SOT89-3	P_D	500	mW
	TO-92		500	
	SOT23-3		300	

Block Diagram



Electrical Characteristics

LY2533

(V_{IN}= V_{OUT}+1.0V，C_{IN}=C_L=10uF，Ta=25^{O}C, unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Output Voltage	V_{OUT}(E) (Note 2)	I_{OUT}=40mA, V_{IN}=Vout+1V	X 0.98	V_{OUT} (T) (Note 1)	X 1.02	V
Input Voltage	V_{IN}				18	V
Maximum Output Voltage	I_{OUT} _max	V_{IN}=Vout+1V	250			mA
Load Regulation	**Δ**V_{OUT}	V_{IN}=Vout+1V, 1mA≤I_{OUT}≤60mA		15	40	mV
Dropout Voltage (Note 3)	V_{dif}	I_{OUT} =40mA		80		mV
Supply Current	I_{SS}	V_{IN}=Vout+1V		3	4	**μ**A
Line Regulations	$\frac{\Delta V_{OUT}}{\Delta V_{IN} \times V_{OUT}}$	I_{OUT} =40mA Vout+1V ≤V_{IN}≤18V		0.1	0.2	%/V
△VOUT/△Ta	Temperature Coefficient	V_{IN}=Vout+1V, I_{OUT} =40mA -40℃<Ta<85℃		±0.7		mV/℃

LY2540

(V_{IN}= V_{OUT}+1.0V，$C_{IN=}C_L$=10uF，Ta=25^{O}C, unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Output Voltage	V_{OUT}(E) (Note 2)	I_{OUT}=40mA, V_{IN}=Vout+1V	X 0.98	V_{OUT} (T) (Note 1)	X 1.02	V
Input Voltage	V_{IN}				18	V
Maximum Output Voltage	I_{OUT} _max	V_{IN}=Vout+1V	250			mA
Load Regulation	**Δ**V_{OUT}	V_{IN}=Vout+1V, 1mA≤I_{OUT}≤60mA		15	40	mV
Dropout Voltage (Note 3)	V_{dif}	I_{OUT} =40mA		70		mV
Supply Current	I_{SS}	V_{IN}=Vout+1V		3	4	μA
Line Regulations	$\frac{\Delta V_{OUT}}{\Delta V_{IN} \times V_{OUT}}$	I_{OUT} =40mA Vout+1V ≤V_{IN}≤18V		0.1	0.2	%/V
△VOUT/△Ta	Temperature Coefficient	V_{IN}=Vout+1V, I_{OUT} =40mA -40℃<Ta<85℃		±0.7		mV/℃

Note ：

1. V_{OUT} (T) ：Specified Output Voltage

2.V_{OUT} (E) ：Effective Output Voltage (ie. The output voltage when "V_{OUT} (T)+1.0V"is provided at the Vin pin while maintaining a certain Iout value.)

3.V_{DIF}：V_{IN1} –V_{OUT} (E)'

V_{IN1} ：The input voltage when V_{OUT}(E)' appears as input voltage is gradually decreased.

V_{OUT} (E)'=A voltage equal to 98% of the output voltage whenever an amply stabilized Iout and {V_{OUT} (T)+1.0V} is input.

Precautions

- During the test, if AC/DC power supply and the ceramic chip capacitors collocation are used, there may be serious voltage spike phenomenon instantaneously. When the power supply access to 16V, the voltage is rushed to about 30V instantaneously. Because of exceeding the limit voltage of chip, the chip is damaged. If you string a small resistance of 1 ohm in the input end during the test, the peak phenomenon can be avoided.
- In the test, there is serious burr phenomenon only when the AC/DC power is used with ceramic chip capacitors. But electrolytic capacitors and tantalum capacitance won't appear above phenomenon. Please be sure to pay attention to this point when you use AC/DC power.
- In normal use, when any type of capacitor is used with battery or the supply of fire power, the above phenomenon doesn't occur.

Packaging Information:

● SOT23-3



● SOT89-3



● TO-92


4.65 +0.35 -0.45
3.7±0.3
4.8 +0.4 -0.5
1.6±0.1
10.0min
0.45±0.1
0.4±0.05
2.5 +0.4 -0.1
2.5 +0.4 -0.1

- The information described herein is subject to change without notice.
- Shenzhen LIANYIWEI Electronics Inc is not responsible for any problems caused by circuits or diagrams described herein whose related industrial properties, patents, or other rights belong to third parties. The application circuit examples explain typical applications of the products, and do not guarantee the success of any specific mass-production design.
- Use of the information described herein for other purposes and/or reproduction or copying without the express permission of Shenzhen LIANYIWEI Electronics Inc is strictly prohibited.
- The products described herein cannot be used as part of any device or equipment affecting the human body, such as exercise equipment, medical equipment, security systems, gas equipment, or any apparatus installed in airplanes and other vehicles, without prior written permission of Shenzhen LIANYIWEI Electronics Inc.
- Although Shenzhen LIANYIWEI Electronics Inc exerts the greatest possible effort to ensure high quality and reliability, the failure or malfunction of semiconductor products may occur. The user of these products should therefore give thorough consideration to safety design, including redundancy, fire-prevention measures, and malfunction prevention, to prevent any accidents, fires, or community damage that may ensue.