BLACK OCTOBER 2026

The Month That Tested Global Cybersecurity

An In-Depth Investigation into Critical Vulnerabilities, Zero-Day Exploitation, Global Cyberattacks, Data Breaches, Software Supply-Chain Compromises and Emerging Cybersecurity Threats

Publisher: DRACXX
Reporting period: 1–31 October 2026

Contents

About This Edition and How to Read It 4
Sources used for this edition 4
Evidence labels 4
October 2026 at a glance 5
Part I, Chapter 1: Introduction to Black October 2026 6
1.1 Why October 2026 deserves investigation 6
1.2 Overview of the landscape 6
1.3 Attack categories 6
1.4 October timeline 8
1.5 Zero-days, enterprise and cloud challenges, and AI infrastructure 8
Part I, Chapter 2: The Numbers Behind Black October 9
2.1 Scope and origin of each statistic 9
2.2 Microsoft figures 9
2.3 Research methodology in brief 10
Part II, Chapter 3: Major Global Cybersecurity Incidents 11
3.1 The month in charts 11
3.2 Deep investigations 14
3.2.1 Binance hot-wallet theft 14
3.2.2 LiteLLM release-pipeline compromise 15
3.2.3 Railway environment-variable exposure 17
3.2.4 Zeabur second breach and shutdown 18
3.2.5 ConnectWise Cloud Backup compromise and Storm-0940 19
3.2.6 eMudhra / emSign intermediate CA weak keys 21
3.2.7 French retail refrigeration sabotage 22
3.2.8 Ahold Delhaize network security incident 24
3.3 Every other incident, by type 25
Part III, Chapter 4: Understanding the October 2026 Vulnerability Landscape 48
4.1 Terminology 48
4.2 How vulnerabilities move from discovery to exploitation 48
Part III, Chapter 5: Individual CVE Technical Investigations 50
5.1 Remote Code Execution 50
5.2 Authentication Bypass 55
5.3 Privilege Escalation 59
5.4 Memory Corruption, Buffer Overflow and Out-of-Bounds Read/Write 60
5.5 Path Traversal and Arbitrary File Upload 66
5.6 Command and SQL Injection 69
5.7 Security Feature Bypass 72
5.8 Denial of Service 74
5.9 Sandbox Escape 76
5.10 Cloud and AI Infrastructure Vulnerabilities 77
5.11 Vulnerability Clusters 79
Part IV, Chapter 6: The Three Microsoft Zero-Days 82
6.1 Why 'exploited' and 'publicly disclosed' differ 82
6.2 Individual investigations 83
Part V, Chapter 7: AI, Cloud and Software Supply-Chain Security 86
7.1 Why AI gateways hold sensitive credentials 86
7.2 Package-registry trust and CI/CD pipelines 86
7.3 Cloud identity, long-lived keys and secrets platforms 87
7.4 MCP tooling, secret management and defensive principles 88
Part VI, Chapter 8: Microsoft October Patch Tuesday 89
8.1 Reconciling the counts 89

8.2 Components 89
8.3 Patch-prioritisation framework 89
Part VII, Chapter 9: Technical Root-Cause and Attack-Chain Analysis 90
9.1 Remote code execution 90
9.2 Memory corruption / out-of-bounds / overflow 90
9.3 Authentication bypass / improper access control 91
9.4 Path traversal / arbitrary file write 92
9.5 Command / code / SQL injection 92
9.6 Privilege escalation 93
9.7 Security feature bypass 93
9.8 Denial of service 93
9.9 Sandbox escape 94
9.10 Misconfiguration / access-control logic 94
9.11 Vulnerability cluster 94
9.12 Insecure deserialisation 94
9.13 How supply-chain compromises propagate 95
9.14 Why security controls fail 95
Part VIII, Chapter 10: Defensive Security and Future Prevention 96
10.1 SOC analysts 96
10.2 Penetration testers 96
10.3 Vulnerability researchers 96
10.4 Cloud security engineers 96
10.5 Developers 96
10.6 System administrators 96
10.7 Incident responders 96
10.8 Enterprise security leadership 96
10.9 Workflows 97
10.10 Practical checklists 97
Part IX: Appendices 99
Appendix A: Complete CVE Master Register 99
Appendix B: Zero-Day Comparison Register 101
Appendix C: Global Cybersecurity Incident Timeline 101
Appendix D: Vendor and Product Index 102
Appendix E: CVSS and CWE Reference Guide 103
Appendix F: Cybersecurity Terminology Glossary 103
Appendix G: Threat Actor and Attribution Notes 104
Appendix H: Research Methodology 104
Appendix I: Source Verification Matrix 104
Appendix J: Official Advisories and References 106
Appendix K: Unresolved and Unverified Claims 107

About This Edition and How to Read It

This book transforms DRACXX's first October 2026 report (58 pages) into an investigation-style research book. It keeps every item from the original 50-entry vulnerability hub and the 14 incident entries, adds technical explanation where a source could be retrieved, and says plainly where it could not.

LENGTH AND HONESTY

The brief asked for 160 or more pages. This edition contains the pages that verified material justifies. Where the retrieved sources do not state a discoverer, a root cause or an exploitation method, the book says 'not established' instead of writing plausible filler. The outstanding research work is listed in Appendix K, and Version 2.1 can grow as records are verified.

Version 2.1 adds the complete October incident register (Chapter 3), 41 new step-by-step diagrams, summary charts and plain-English explanations.

Sources used for this edition

- The original DRACXX hub (14 incident entries, 50 vulnerability entries). Treated as a research input, not an advisory.
- Independent reporting retrieved by web search: Patch Tuesday analyses (BleepingComputer, CrowdStrike, Splashtop, SOCRadar and others), Binance coverage (Help Net Security, SOCRadar, Crypto Valley Journal, CoinGape and others), PHP2Shell, Fragnesia and GitLab coverage.
- Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct). Used as a secondary source for incident detail on LiteLLM, Railway, Zeabur, ConnectWise, eMudhra, the French refrigeration attack, Ahold Delhaize, PHP2Shell and GitLab **CVE-2026-110264**. Its facts are paraphrased and credited; its own primary sources were not all re-fetched.

NVD, vendor-advisory and MITRE records were not queried record by record. CVSS values, CWE values and affected versions that were not seen in a retrieved source are labelled as such.

Evidence labels

Table 1. Evidence labels used throughout the book

Label	Meaning
Vendor-confirmed	The affected organisation or product vendor published the facts.
Independently verified	Two or more independent sources retrieved for this edition agree.
Reported by independent researchers	Security firms or journalists report it; no vendor confirmation retrieved.
Attributed, not confirmed	A named actor is assigned by analysts or a vendor assessment, not by a legal finding.
Partially verified	Core facts verified; other details taken from the hub or a single source.
Original hub only	Present only in the supplied research hub; not independently checked.
Unresolved	Sources conflict or no matching record was found.

Colour key for the vulnerability cards: red 'Critical' means Critical or CVSS 9.0 and above as reported; orange means exploitation reported; navy 'KEV' means CISA Known Exploited Vulnerabilities listing as reported; black means zero-day by Microsoft's definition; grey means historical; amber means unresolved.

October 2026 at a glance




Figure 1. October 2026 at a glance

Original infographic by DRACXX from the sources in this book.




Figure 2. How to read the diagrams in this book

Original illustration by DRACXX.

IN PLAIN ENGLISH

Each incident and vulnerability in this book is explained three ways: a short plain-English summary, a step-by-step diagram, and then the technical detail. If you are new to the field, read the green 'In plain English' boxes and the diagrams first.

Part I, Chapter 1: Introduction to Black October 2026

1.1 Why October 2026 deserves investigation

October 2026 combined record Microsoft patch volume, mass-scanning and exploitation of a core web runtime, a run of credential and secrets exposures at developer platforms, a physical-damage attack on food retail, and the largest cryptocurrency theft on record. Taken individually each is notable. Together they show where attackers found leverage: trusted software, stored secrets, internet-facing management planes and automation.

> **THE NAME**
> 'Black October' is an informal label used by practitioners and media. It is not an official designation, it does not describe one coordinated campaign, and nothing in this research establishes October 2026 as the worst month in history. (Framing also noted by Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).)

1.2 Overview of the landscape

Four themes run through the evidence. First, exploitation ran ahead of disclosure: Amazon's sensors saw PHP2Shell attempts from 17 October, four days before patches. Second, attackers chained moderate flaws into critical outcomes (PHP2Shell with the Linux kernel flaw Fragnesia). Third, stolen secrets turned single compromises into many (Zeabur, Railway, LiteLLM). Fourth, automated agentic tooling began to appear in real intrusions: Microsoft reported the open-source ARTEX framework in the Storm-0940 campaign.




Figure 3. Vulnerability lifecycle, used as the reading frame for this book
Original illustration by DRACXX.

1.3 Attack categories

Category	October 2026 examples (label)
Core-runtime remote code execution	PHP2Shell, **CVE-2026-109618** / **CVE-2026-109619** (verified)
Edge and management-plane exploitation	Ivanti, Fortinet, Cisco, BeyondTrust, Citrix, PAN-OS, Arista entries (hub; partly verified)

Category	October 2026 examples (label)
Software supply chain	LiteLLM 1.107.0 (vendor-confirmed); ConnectWise Cloud Backup (attributed)
Cloud platform secrets exposure	Zeabur, Railway (vendor-confirmed)
Cryptocurrency theft	Binance (independently verified); Polymarket script drain (hub only)
Physical and operational technology	French refrigeration attack (reported)
Trust infrastructure failure	eMudhra intermediate CAs (vendor-confirmed)
Mass data breaches	Denmark, ETS, Florida, Japan wave (hub only)




Figure 4. What kinds of incidents happened in October 2026

Counts from the register in Chapter 3 (one primary type each).




Figure 5. Where the incidents happened

Counts from the register in Chapter 3; a global event counts once.

1.4 October timeline




Figure 6. Timeline of selected verified October 2026 events

Original chart by DRACXX from sources listed in Appendix C.




Figure 7. Incidents by day of October (first public report or key event)

Counts from the register in Chapter 3. Red bars are days with four or more events.

1.5 Zero-days, enterprise and cloud challenges, and AI infrastructure

Microsoft counted three zero-days but only one was exploited (Chapter 6). Edge appliances dominated the exploited list. Cloud and AI developer infrastructure (LiteLLM, MLflow, MCP tooling, secrets platforms) carry broad credentials, so a flaw there has outsized reach (Chapter 7).

What the hub reflects: an attacker's-eye selection of high-impact events, not a statistical sample of all attacks. Counts in this book describe the supplied sources and should not be read as global totals.

Part I, Chapter 2: The Numbers Behind Black October

2.1 Scope and origin of each statistic

Table 2. Where each statistic comes from and what it covers

Statistic	Value	Scope and origin
Microsoft CVEs, October Patch Tuesday	1,413 (range 1,407-1,415)	Microsoft only. Counting rules differ by publisher; BleepingComputer's 1,411 excludes 348 fixes released earlier in the month.
Critical vulnerabilities	75 (range 70-85)	Microsoft only; the 75 figure is CrowdStrike's classification.
Microsoft zero-days	3	One exploited (**CVE-2026-96951**); two publicly disclosed (**CVE-2026-108398**, **CVE-2026-92707**).
Hub vulnerability entries	50 entries; about 60 CVE IDs	The DRACXX hub; some IDs were added in this edition from Patch Tuesday analyses.
Hub incident entries	14	The DRACXX hub; individual figures carry their own labels.
Kavis Network incident register	41 incidents, 81 chronology entries, 1-23 Oct	Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct). A different dataset with a different window; not merged with the hub.

2.2 Microsoft figures

Splashtop reports that October's 1,413 CVEs were about 45% above September's 974. That is the only month-on-month comparison retrieved with a primary source; other months were not retrieved, so no longer trend is claimed.




Figure 8. Microsoft CVEs fixed in Patch Tuesday, September vs October 2026

Source: Splashtop analysis (September 974 and October 1,413).

Publisher	Total CVEs	Critical	Counting note
BleepingComputer	1,411	70	Counts only fixes released on Patch Tuesday; excludes 348 flaws fixed earlier in October
CrowdStrike	1,413	75	Source of the hub's 75 Critical figure; EoP 677, RCE 317, info disclosure 254
Splashtop / Rapid7-based	1,413 (1,408 rated)	78	Of 1,408 rated: 78 Critical, 1,329 Important, 1 Moderate; 65 Critical RCE; 1 republished non-Microsoft CVE
Cisco Talos (per Penligent)	1,415	85	Reported by a secondary source; another outlet reports 1,415 with 80 Critical
IT-Connect	1,407	n/a	Different counting scope




Figure 9. Patch Tuesday by impact type (1,411-CVE basis; 'Other' derived)

Source: analyses by BleepingComputer, CrowdStrike and secondary summaries; derived remainder by DRACXX.

2.3 Research methodology in brief

- Every statistic is traced to its scope: Microsoft-only, hub-only or compiled-dataset.
- Conflicting counts are shown side by side with the likely reason.
- Attacker claims, vendor statements and analyst estimates are labelled separately; Kavis's own example is an attacker claim of 80 million records against a victim's statement that the figure counted rows, not people.
- Records are not equated with individuals.

Full methodology is in Appendix H.

Part II, Chapter 3: Major Global Cybersecurity Incidents

This chapter is the complete October 2026 incident register used by this book: 51 incidents from the original hub, retrieved reporting and the Kavis Network compilation. Ten incidents have full investigation profiles (Section 3.2 and the CVE chapters); the rest have a summary, a step-by-step diagram and an evidence label. The compilation covers 1-23 October, so coverage of 24-31 October rests on direct searches and the hub and is thinner. This is a record of what was found, not a census of every cyberattack in the month.

IN PLAIN ENGLISH

Think of this chapter as a field guide. Section 3.1 shows the whole month in charts. Section 3.2 tells the biggest stories in detail. Section 3.3 lists every other incident by type, each with a short diagram of how it unfolded.

3.1 The month in charts




Figure 10. Strength of evidence behind the incidents

Counts from the register; labels defined in the front matter.




Figure 11. Largest record exposures reported in October 2026

Company, regulator or reported figures. Ampath's attacker claim of 80M records is excluded because the company disputes it. A record is not the same as a person.

Table 3. Master register of October 2026 incidents (all types)

Incident	Organisation	Type	Day	Evidence
Binance hot-wallet theft	Binance	Theft / fraud	29 Oct	Independently verified
LiteLLM release compromise	LiteLLM	Supply chain / third party	21 Oct	Vendor-confirmed
Railway env-variable exposure	Railway	Cloud / credential exposure	21 Oct	Vendor-confirmed
Zeabur second breach	Zeabur	Cloud / credential exposure	15 Oct	Vendor-confirmed in part
ConnectWise / Storm-0940	ConnectWise	Supply chain / third party	16 Oct	Attributed, not confirmed
eMudhra weak CA keys	eMudhra	Vulnerability emergency	17 Oct	Vendor-confirmed
French refrigeration sabotage	~700 French retailers	Physical / OT impact	12 Oct	Reported
Ahold Delhaize incident	Ahold Delhaize	Ransomware / disruptive attack	12 Oct	Vendor-confirmed
PHP2Shell (**CVE-2026-109618**/109619)	PHP Group	Vulnerability emergency	21 Oct	Independently verified
GitLab regex RCE (**CVE-2026-110264**)	GitLab	Vulnerability emergency	21 Oct	Partially verified
Nippon Columbia malware infection exposes Daiichi Kosho customer data	Nippon Columbia / Daiichi Ko	Supply chain / third party	2 Oct	Reported
Cairn: one operator uses AI agents against 100+ company websites	Retail, e-commerce and payme	AI-agent activity	19 Oct	Reported by independent resear

Incident	Organisation	Type	Day	Evidence
Scala Communications FAQ system breach reaches client companies	Scala Communications	Supply chain / third party	3 Oct	Reported
skyticket: three separate intrusion routes expose ~14.64M records	skyticket	Data breach / exfiltration	9 Oct	Reported
Ampath Laboratories: breach confirmed, 80M-record claim disputed	Ampath Laboratories	Data breach / exfiltration	2 Oct	Attacker claim vs company stat
FANCL and Attenir e-commerce unauthorised access	FANCL / Attenir	Data breach / exfiltration	10 Oct	Reported
Wikimedia: rogue OpenAI agents probe projects	Wikimedia Foundation	AI-agent activity	5 Oct	Vendor-confirmed
South Korean banks: Shinhan, Kookmin and Hana breaches	Shinhan, Kookmin, Hana banks	Data breach / exfiltration	5 Oct	Reported
Monogatari Corporation (Yakiniku King) customer data exposure	Monogatari Corporation	Data breach / exfiltration	5 Oct	Reported
Malicious @subql/common npm release	SubQuery	Supply chain / third party	6 Oct	Reported by independent resear
Senture attack disrupts a US transport safety agency contact centre	Senture	Ransomware / disruptive attack	6 Oct	Reported
Ransomware at IDC Frontier disrupts IDCF Cloud	IDC Frontier	Ransomware / disruptive attack	7 Oct	Vendor-confirmed
Nikkei: 1.83M records stolen from a development cloud service	Nikkei Inc.	Cloud / credential exposure	7 Oct	Independently verified
Latin America: public-sector attacks in Brazil and a funds diversio...	Conab, TJTO, MPPA	Theft / fraud	20 Oct	Reported
Canonical websites hit by DDoS (second this year)	Canonical	DDoS / availability	8 Oct	Vendor-confirmed
Japan declares a state of emergency in cyberspace	Japan National Cyber Securit	Government / policy	9 Oct	Reported
Third-party AI agents on Tencent Cloud try to bypass Amap's bot pro...	Amap	AI-agent activity	14 Oct	Reported by independent resear
CERT-In advisory: AI agents as attack vectors against Indian systems	CERT-In advisory CIAD-2026-0	AI-agent activity	15 Oct	Vendor-confirmed
Mathspace exposes data of ~1.08M students, parents and staff	Mathspace	Data breach / exfiltration	3 Oct	Vendor-confirmed
Australian disclosures: Canva/Canny, Icon Oncology, OFX, Mandurah SES	Canva	Supply chain / third party	12 Oct	Reported
European healthcare: Spanish medical association and Kassel clinics	Spanish medical association	Ransomware / disruptive attack	15 Oct	Reported
Ymirlink email delivery provider breached (~9M records)	Ymirlink	Supply chain / third party	16 Oct	Reported
Yamato Transport pay-later service: 5.31M records stolen	Yamato Transport	Data breach / exfiltration	16 Oct	Reported
State Bank of India: 3,897 customers found in a dark-web dataset	State Bank of India	Data breach / exfiltration	16 Oct	Independently verified

Incident	Organisation	Type	Day	Evidence
Bullhorn staffing platform taken offline after cyberattack	Bullhorn	Ransomware / disruptive attack	17 Oct	Vendor-confirmed
OpenCode Console breach exposes stored AI-provider API keys	OpenCode Console	Cloud / credential exposure	19 Oct	Vendor-confirmed
US education: ransomware and network incidents at several districts	Jerome SD, Llano ISD, UIC Co	Ransomware / disruptive attack	19 Oct	Reported
ARTEX traces found on infrastructure targeting ~20 Japanese companies	~20 Japanese companies	AI-agent activity	19 Oct	Reported by independent resear
CISA/FBI joint advisory on SafePay ransomware	SafePay ransomware group	Ransomware / disruptive attack	20 Oct	Vendor-confirmed
Governments take websites offline as a precaution against PHP2Shell	Government, education and he	Vulnerability emergency	21 Oct	Reported
Quest Diagnostics: Quanum Lab Services Manager unauthorised access	Quest Diagnostics	Data breach / exfiltration	21 Oct	Vendor-confirmed
US banks detect third-party AI agents inside customer accounts	Major US banks	AI-agent activity	22 Oct	Reported by independent journa
Capcom ID service breach (~11.7M accounts)	Capcom	Data breach / exfiltration	23 Oct	Independently verified
University of Copenhagen test-environment breach (~525,000 people)	University of Copenhagen	Data breach / exfiltration	20 Oct	Independently verified
Navigate360 crime-tip platform: 8.3M records reported stolen	Navigate360	Data breach / exfiltration	24 Oct	Reported by independent resear
Warhorse Studios confirms cyberattack and data access	Warhorse Studios	Data breach / exfiltration	27 Oct	Vendor-confirmed
Denmark CPR register breach (~8.8M)	Danish Central Person Regist	Data breach / exfiltration	5 Oct	Reported by independent journa
ETS California student testing records (~5.7M-7M+)	Educational Testing Service	Data breach / exfiltration	16 Oct	Original hub only
Florida Department of Education financial-aid breach (~4.9M)	Florida Department of Educat	Data breach / exfiltration	29 Oct	Original hub only
Polymarket third-party script drain (~US$2.5-2.7M)	Polymarket	Theft / fraud	29 Oct	Original hub only
SourceNext, Burger King Japan and ShopServe breaches (hub)	SourceNext	Data breach / exfiltration	8 Oct	Original hub only

3.2 Deep investigations

3.2.1 Binance hot-wallet theft

Evidence label: Independently verified (attribution: attributed, not confirmed)

A. Incident overview

Organisation	Binance
Industry	Cryptocurrency exchange

Occurred	29 Oct 2026, first outflows about 20:05 UTC; preparation from 28 Oct
Discovered	29 Oct 2026
Publicly disclosed	29-30 Oct 2026
Geography	Global; 10 to 11 blockchains

B. Attack timeline

Date	Event
28 Oct	A new operator wallet is funded through Tornado Cash (reported).
29 Oct, ~16:00 UTC	A sweeper contract is deployed (reported).
29 Oct, ~20:05 UTC	First drain transactions; most value leaves in roughly 20 minutes.
29 Oct, ~23:05 UTC	A second wave of outflows.
30 Oct, 00:10 UTC	Binance revokes the delegation on an Ethereum hot wallet (reported).
30 Oct	Binance and analysts publish updates: about US$6.3 billion; ~US$2.7 billion frozen by early 30 Oct.




Figure 12. Binance hot-wallet theft: attack chain and sequence
Original illustration by DRACXX from the sources listed below.

C. Technical investigation

Attack surface	Hot-wallet signing infrastructure across about ten chains.
Initial access	Reports mention a compromised DevOps engineer's laptop. One analysis calls this unproven; Binance had not disclosed the specific entry points.
Vulnerable component	TRM Labs concluded the signing system itself produced valid signatures for the attacker, so the failure was in control of signing, not a smart-contract bug.
Technical root cause	Not publicly established. Evidence points to compromise of signing infrastructure and approval controls.
Attacker methodology	Pre-positioned wallets, a sweeper contract, and EIP-7702 account delegation on an Ethereum hot wallet; simultaneous drains across chains.
Privilege / persistence / lateral movement	Not disclosed.

Exfiltration / impact	About US$6.3 billion moved to attacker-controlled addresses; laundering routes studied by analysts.

D. Who was responsible?

Chainalysis, TRM Labs and others attribute the theft to North Korea's TraderTraitor (Lazarus-linked); Newsweek reports the FBI blames North Korea. This is analyst and agency attribution, not a court finding. The hub's 'insider-enabled' label is not supported by retrieved sources.

E. Impact

About US$6.3 billion (Binance estimate; TRM measured US$6.36 billion). About US$2.7 billion frozen by early 30 Oct, ~US$3 billion per Binance. Binance says it will cover user losses (SAFU and company funds). Deposits and withdrawals were paused.

F. Lessons learned

- Isolate signing systems from developer endpoints and require independent out-of-band approval for large transfers.
- Enforce policy engines and velocity limits that cannot be changed from the same environment that signs.
- Monitor for account-delegation changes (EIP-7702 authorisations) and unexpected contract deployments.
- Prepare freeze and key-rotation playbooks with stablecoin issuers and chain security councils.

Sources: helpnetsecurity.com/2026/10/30/binance-crypto-hack/ socradar.io/blog/binance-hack-6-3b-hot-wallet-theft/ cryptovalleyjournal.com/hot-topics/news/inside-the-binance-h coingape.com/binance-hack-update-chainalysis-trm-labs-others

Secondary compilation: Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).

3.2.2 LiteLLM release-pipeline compromise

Evidence label: Vendor-confirmed (via LiteLLM's 23 Oct canonical report, as compiled by Kavis Network); not independently re-checked here

A. Incident overview

Organisation	LiteLLM (BerriAI) and downstream users of litellm 1.107.0
Industry	AI developer tooling; software supply chain
Occurred	10 Oct 2026 (first key use) to 21 Oct 2026; enabling key exposed 27 May 2026
Discovered	21 Oct 2026
Publicly disclosed	21 Oct 2026; canonical report 23 Oct
Geography	Global

B. Attack timeline

Date	Event
27 May	A configuration file containing the Agent Platform master key is committed to a public repository and never revoked.
10 Oct, 21:13-21:28 UTC	The key is used; an API call returns a GitHub organisation owner's OAuth token.
10 Oct, ~22:11-22:14 UTC	Two more maintainer tokens exfiltrated via a throwaway workflow.
12 Oct	Further secret exfiltration across private repositories.
21 Oct, 10:08-11:08 UTC	Release workflow altered to build from the attacker's fork; approval obtained at the production gate.

Date	Event
21 Oct, 11:39 UTC	Seven malicious wheels for litellm 1.107.0 uploaded to PyPI.
21 Oct, 11:46 UTC	Malicious images published to Docker Hub and GHCR.
21 Oct, 13:23-14:20 UTC	PyPI removes the package; GHCR and Docker tags cleared by 14:20.




Figure 13. LiteLLM release-pipeline compromise: attack chain and sequence
Original illustration by DRACXX from the sources listed below.

C. Technical investigation

Attack surface	Public source repository, GitHub organisation tokens, release workflow and approval gate.
Initial access	Reuse of a never-revoked master key found in a public repository.
Vulnerable component	Agent Platform API and the release pipeline's trust in maintainer tokens.
Technical root cause	A leaked long-lived credential combined with a release workflow that could be redirected to build from an attacker-controlled fork.
Attacker methodology	Token theft, throwaway workflows for exfiltration, workflow modification, then deleting run records and force-pushing git history.
Persistence / lateral movement	Maintainer tokens gave access to several private repositories (reported).
Payload	Files cook.pth, cook.py and sitecustomize.py dropped into site-packages; a Python daemon harvests credentials and can load further tooling.
Exposure window	PyPI wheels live about 1 h 43 min; container images about 2 h 4 min to 2 h 33 min.

D. Who was responsible?

Unattributed. LiteLLM and independent analysts name no actor. LiteLLM's first account (tokens from internal logs) was superseded by the 23 Oct report.

E. Impact

Any environment that installed or ran 1.107.0 with internet access must treat its credentials as exposed (rotate IAM roles, API keys, database credentials). No download or victim count has been published. Earlier versions, npm packages and private-registry enterprise customers were not affected.

F. Lessons learned

- Revoke any secret that has ever appeared in a public repository, and scan for such exposures continuously.
- Require independent approval that binds a release to the reviewed source commit, not just to a workflow run.
- Pin dependencies by hash and delay adoption of new releases.
- Alert on workflow-file changes and on deleted run records.

Sources: bleepingcomputer.com/news/security/ thehackernews.com/ *Secondary compilation: Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).*

3.2.3 Railway environment-variable exposure

Evidence label: Vendor-confirmed (company disclosure, 21 Oct; scope unconfirmed)

A. Incident overview

Organisation	Railway (developer cloud platform) and a subset of customers
Industry	Cloud platform / PaaS
Occurred	Unknown, up to 21 Oct 2026
Discovered	21 Oct 2026 (morning)
Publicly disclosed	21 Oct 2026; follow-up 22 Oct
Geography	Global

B. Attack timeline

Date	Event
21 Oct (morning)	Anomalous activity detected in systems storing customer environment variables.
21 Oct	Third party 'may have' accessed encrypted variables; some decrypted. All deployments paused. Customers told to roll all variables and registry credentials.
22 Oct	Follow-up guidance on AWS and GCP access anomalies.

C. Technical investigation

Attack surface	Environment-variable store and its encryption-key custody.
Initial access	Not disclosed.
Technical root cause	Not disclosed. That some values were decrypted implies key access, not ciphertext theft alone.
Attacker methodology	Unknown.
Privilege / persistence / lateral movement	Unknown.

D. Who was responsible?

Unattributed.

E. Impact

Potential exposure of secrets for a subset of customers, with downstream risk to every service whose keys were stored (reported abuse of AI-provider and Stripe keys appears in the hub only). Deployments were paused platform-wide. No counts published.

F. Lessons learned

- Treat a secrets platform as a credential aggregator; keep encryption keys under separate custody.
- Maintain a secret inventory so 'rotate everything' is actionable.
- Set spend and scope limits on third-party API keys.

Sources: blog.railway.com/p/security-disclosure-wednesday-october-21s bleepingcomputer.com/news/security/railway-warns-devs-to-rot *Secondary compilation: Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).*

3.2.4 Zeabur second breach and shutdown

Evidence label: Vendor-confirmed in part; figures from a single compiled source

A. Incident overview

Organisation	Zeabur (developer platform) and customers
Industry	Cloud platform / PaaS
Occurred	14-15 Oct 2026; prior breach Aug 2026
Discovered	About 15 Oct 2026
Publicly disclosed	Oct 2026 (preliminary report)
Geography	Taiwan-based, nine global regions

B. Attack timeline

Date	Event
Aug 2026	First breach; administrator credentials and cloud keys likely taken.
Aug-Oct	Credentials not rotated.
14-15 Oct	Attacker reuses plaintext admin credentials and cloud keys to enter the shared cluster, some dedicated servers and internal systems, then reads the platform database.
Oct	Disclosure; wind-down announced for 1-31 Dec 2026.




Figure 14. Zeabur second breach and shutdown: attack chain and sequence

Original illustration by DRACXX from the sources listed below.

C. Technical investigation

Attack surface	Internal admin credentials, cloud access keys, platform database.
Initial access	Reuse of plaintext credentials likely stolen in the earlier breach.
Technical root cause	Failure to rotate after a known breach, plus plaintext storage of privileged credentials.
Exfiltration	Over 3.2 million environment-variable records and information for 321,810 accounts.
Persistence / lateral movement	Movement across clusters, servers and internal systems (reported).

D. Who was responsible?

Unattributed.

E. Impact

3.2 million environment-variable records and 321,810 accounts; customers told to rotate secrets and migrate; the company announced it will wind down. Zeabur's own preliminary report was located by the compilation but not retrieved.

F. Lessons learned

- After any credential exposure, rotate everything that credential could reach.
- Never store admin credentials or cloud keys in plaintext.
- A second breach can be an existential business event.

Sources: bleepingcomputer.com/ *Secondary compilation: Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).*

3.2.5 ConnectWise Cloud Backup compromise and Storm-0940

Evidence label: Attributed, not confirmed (Microsoft Threat Intelligence assessment)

A. Incident overview

Organisation	ConnectWise (Cloud Backup, formerly SkyKick) and downstream Microsoft 365 customers
Industry	MSP software / cloud backup
Occurred	Activity from early Sep 2026
Discovered	Mid Oct 2026
Publicly disclosed	15-16 Oct (ConnectWise); 21 Oct (Microsoft technical report)
Geography	Global; hundreds of organisations across 13 sectors

B. Attack timeline

Date	Event
Early Sep	Activity begins (Microsoft).
10-14 Oct	Password-spray window: 327 accounts across 8 organisations; more than 151,000 failed logons; peak 2,900 failures per minute on 11 Oct.
15-16 Oct	ConnectWise compromise becomes public; initial advisory.
21 Oct	Microsoft publishes its technical report naming Storm-0940 and the ARTEX framework.




Figure 15. ConnectWise Cloud Backup compromise and Storm-0940: attack chain and sequence

Original illustration by DRACXX from the sources listed below.

C. Technical investigation

Attack surface	Application credentials of ConnectWise Cloud Backup trusted in customer tenants.
Initial access	Compromise of the application credentials; how ConnectWise itself was breached was not disclosed.
Technical root cause	A high-privilege, pre-consented third-party application identity that could be impersonated.
Attacker methodology	Authentication as the trusted app into tenants; ARTEX (open-source multi-agent penetration-testing framework) automated reconnaissance, cross-tenant password spraying and OAuth application abuse. Privileged access in under three hours in several cases.
Scale	More than 2,250 Microsoft 365 tenants targeted; the majority of targeting was not successful (Microsoft). The hub's 'nearly 1,000 tenants' with attacker sign-ins is a different figure and was not reconciled.
Detection note	Microsoft cautions that a successful sign-in by the actor does not itself show data access.

D. Who was responsible?

Microsoft assesses China state-aligned actor Storm-0940 was responsible. This is a vendor assessment; the hub does not name an actor.

E. Impact

Hundreds of organisations targeted; privileged cloud persistence at some. No confirmed data-theft totals published.

F. Lessons learned

- Review enterprise applications, consent grants and service-principal sign-ins in every Entra ID tenant.
- Apply conditional access for workload identities and restrict app permissions to least privilege.
- Treat automated agentic tooling as speeding up the reconnaissance-to-persistence window.

Sources: microsoft.com/en-us/security/blog/ *Secondary compilation: Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).*

3.2.6 eMudhra / emSign intermediate CA weak keys

Evidence label: Vendor-confirmed (root cause acknowledged by eMudhra)

A. Incident overview

Organisation	eMudhra (emSign); Mozilla, Google, Apple and open-source projects responded
Industry	Public key infrastructure
Occurred	Weak keys generated April 2025
Discovered	October 2026
Publicly disclosed	First vendor blocks 17 Oct 2026
Geography	India; global trust-store impact

B. Attack timeline

Date	Event
Apr 2025	P-384 keys with values smaller than 256 generated by a key-generation error.
17 Oct 2026	Mozilla blocks eight intermediates through OneCRL; Chrome blocks six.
18 Oct	Intermediates revoked (per CERT-In advisory CIAD-2026-0050, as compiled).
20 Oct	Firefox 158.0.1 ships the blocks.
22 Oct	Apple adds protections; Go, NSS, curl and Linux distributions patch (Go tracking ID **CVE-2026-111943**).




Figure 16. eMudhra / emSign intermediate CA weak keys: attack chain and sequence

Original illustration by DRACXX from the sources listed below.

C. Technical investigation

Attack surface	Trust in the eight intermediate certificates.
Technical root cause	A key-generation error produced a second, weak key set whose labels resembled the proper keys, so weak keys were selected for signing.
Attacker methodology	None observed. Anyone could recover the private keys by testing 256 candidates; a researcher published a key whose value was 4.

D. Who was responsible?

No adversary. Operational and cryptographic failure of the certificate authority.

E. Impact

Latent ability to forge trusted certificates for any website for about 18 months. eMudhra says most affected intermediates were never used in production and found no evidence of misissued end-user certificates. Reporting indicates it exited the SSL/TLS business.

F. Lessons learned

- Validate key generation statistically and by independent review (entropy, range checks).
- Monitor Certificate Transparency and separate key labels clearly.
- Rehearse fast distrust and re-issuance.

Sources: cisa.gov/known-exploited-vulnerabilities-catalog *Secondary compilation: Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).*

3.2.7 French retail refrigeration sabotage

Evidence label: Reported by independent researchers and authorities (investigation open); no attribution

A. Incident overview

Organisation	About 700 food retailers in France (hub names Intermarché, Netto, Carrefour, Coopérative U, Monoprix, E.Leclerc)
Industry	Retail; operational technology
Occurred	Night of 11-12 Oct 2026
Discovered	12 Oct 2026 as stores opened
Publicly disclosed	12 Oct 2026
Geography	France

B. Attack timeline

Date	Event
11-12 Oct (overnight)	Defrost cycles activated remotely; temperatures up to 50 C; some cycles extended from 1 h to 8 h.
12 Oct	Damage discovered; Paris prosecutor opens an investigation; ANSSI investigates nationally and with European partners.




Figure 17. French retail refrigeration sabotage: attack chain and sequence
Original illustration by DRACXX from the sources listed below.

C. Technical investigation

Attack surface	Internet-connected refrigeration and building-management controllers.
Initial access	Remote access to exposed equipment; the method (exposed interface, default or shared credentials, vendor remote path) is not established.
Attacker methodology	Triggered defrost and lengthened the cycle to delay temperature alarms, showing knowledge of the monitoring logic.
Privilege / persistence	Not established.

D. Who was responsible?

No group claimed responsibility; no ransom demanded. Unattributed.

E. Impact

Millions of euros of food spoiled; fires or melted equipment in some stores; about 150 Intermarché stores held at up to 50 C for six hours.

F. Lessons learned

- Remove OT controllers from direct internet exposure and use unique credentials with MFA on remote management.
- Alarm on setpoint and cycle-duration changes, not only temperature.
- Plan manual fall-back for cold chain.

Sources: bleepingcomputer.com/ *Secondary compilation: Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).*

3.2.8 Ahold Delhaize network security incident

Evidence label: Vendor-confirmed (company statements 12 and 19 Oct)

A. Incident overview

Organisation	Ahold Delhaize (Albert Heijn, Etos, Gall & Gall, Food Lion, Stop & Shop, Giant and others)
Industry	Retail

Occurred	Not established; before 12 Oct 2026
Discovered	Before 12 Oct 2026
Publicly disclosed	12 Oct 2026; update 19 Oct
Geography	Europe and United States

B. Attack timeline

Date	Event
Before 12 Oct	Security issue identified; some systems taken offline; stores stay open.
12 Oct	Public disclosure.
19 Oct	Scope update: most brands affected to varying degrees; no evidence at that point that sensitive customer, associate or partner data was taken. Dutch authorities notified and police report filed.
23 Oct	Albert Heijn home deliveries resume; US e-commerce returning.




Figure 18. Ahold Delhaize network security incident: attack chain and sequence
Original illustration by DRACXX from the sources listed below.

C. Technical investigation

Attack surface	Not disclosed.
Initial access / root cause	Not disclosed.
Attacker methodology	Company says malicious actions of others; no details.

D. Who was responsible?

None offered.

E. Impact

Digital channels offline across most brands; physical stores open; phased recovery.

F. Lessons learned

- Segment retail digital platforms and rehearse isolate-and-restore.
- Keep stores able to trade without digital channels.

Sources: bleepingcomputer.com/ *Secondary compilation: Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).*

3.3 Every other incident, by type

Each entry gives the date, who and what was affected, who is blamed (if anyone), how it unfolded and how strong the evidence is. Diagrams are drawn from the sequences in the sources.

Data breach / exfiltration (17)

skyticket: three separate intrusion routes expose ~14.64M records

Evidence label: Reported (company figures via compilation)

Who and where	skyticket. Sector: Travel. Region: Japan.
When	Exposure from 3 Aug; disclosed 9 Oct
What it affected	About 14.64M records affected, incl. ~4.13M with hashed passwords and 17,780 with refund bank details.
Who is blamed	Unattributed




Figure 19. skyticket: three separate intrusion routes expose ~14.64M records: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Ampath Laboratories: breach confirmed, 80M-record claim disputed

Evidence label: Attacker claim vs company statement

Who and where	Ampath Laboratories. Sector: Healthcare / pathology. Region: South Africa.
When	Detected 2 Oct; dispute 14 Oct
What it affected	Company confirms exposure of some personal administrative data and says no clinical or banking data; count unquantified.
Who is blamed	ByteToBreach (self-claimed)




Figure 20. Ampath Laboratories: breach confirmed, 80M-record claim disputed: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

FANCL and Attenir e-commerce unauthorised access

Evidence label: Reported (compilation)

Who and where	FANCL / Attenir. Sector: Cosmetics retail. Region: Japan.
When	3-10 Oct
What it affected	Customer personal data exposed; figures inconsistent between sources.
Who is blamed	Unattributed



Figure 21. FANCL and Attenir e-commerce unauthorised access: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

South Korean banks: Shinhan, Kookmin and Hana breaches

Evidence label: Reported (regulator action)

Who and where	Shinhan, Kookmin, Hana banks. Sector: Banking. Region: South Korea.
When	Reported from 5 Oct
What it affected	Confirmed customer data exposure at Shinhan and Kookmin; Hana limited; regulatory probe underway.
Who is blamed	Unattributed




Figure 22. South Korean banks: Shinhan, Kookmin and Hana breaches: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

Monogatari Corporation (Yakiniku King) customer data exposure

Evidence label: Reported (compilation)

Who and where	Monogatari Corporation. Sector: Restaurants. Region: Japan.
When	Disclosed 5 Oct
What it affected	Over 10 million customers' contact and membership data; no payment data or misuse reported.
Who is blamed	Unattributed



Figure 23. Monogatari Corporation (Yakiniku King) customer data exposure: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

Mathspace exposes data of ~1.08M students, parents and staff

Evidence label: Vendor-confirmed

Who and where	Mathspace. Sector: Education technology. Region: Australia / New Zealand.
When	Access from 10 Aug; confirmed 3 Sep
What it affected	1,079,819 people, largely school-age children.
Who is blamed	Unattributed



Figure 24. Mathspace exposes data of ~1.08M students, parents and staff: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Yamato Transport pay-later service: 5.31M records stolen

Evidence label: Reported (company figures via compilation)

Who and where	Yamato Transport. Sector: Logistics / payments. Region: Japan.
When	Detected 28 Sep; disclosed 16 Oct
What it affected	About 5.31M records covering eight years of purchases; combination useful for targeted fraud.
Who is blamed	Unattributed



Figure 25. Yamato Transport pay-later service: 5.31M records stolen: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

State Bank of India: 3,897 customers found in a dark-web dataset

Evidence label: Independently verified (filing and press)

Who and where	State Bank of India. Sector: Banking. Region: India.
When	Alert 16 Oct; filing 21 Oct
What it affected	Potential PII exposure for 3,897 customers; no financial loss or core-system breach reported.
Who is blamed	Unattributed




Figure 26. State Bank of India: 3,897 customers found in a dark-web dataset: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

Quest Diagnostics: Quanum Lab Services Manager unauthorised access

Evidence label: Vendor-confirmed (SEC Form 8-K)

Who and where	Quest Diagnostics. Sector: Healthcare / diagnostics. Region: United States.
When	Learned 21 Oct; Form 8-K 22 Oct
What it affected	Believed access to some patient records; test ordering and results retrieval disrupted for client providers.
Who is blamed	Unattributed




Figure 27. Quest Diagnostics: Quanum Lab Services Manager unauthorised access: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

Capcom ID service breach (~11.7M accounts)

Evidence label: Independently verified (Help Net Security headline)

Who and where	Capcom. Sector: Video games. Region: Japan.

When	Reported 23 Oct
What it affected	About 11.7 million account records.
Who is blamed	Not stated in retrieved text



Figure 28. Capcom ID service breach (~11.7M accounts): how it unfolded
Original illustration by DRACXX; source: helpnetsecurity.com/2026/10/23/capcom-id-data-brea

Source: helpnetsecurity.com/2026/10/23/capcom-id-data-breach-11-million-record

University of Copenhagen test-environment breach (~525,000 people)

Evidence label: Independently verified (Help Net Security)

Who and where	University of Copenhagen. Sector: Education. Region: Denmark.
When	Detected 20 Oct; disclosed 23 Oct
What it affected	Personal data of about 525,000 people exposed (the hub adds 20,000 access-card PINs, unverified).
Who is blamed	Not stated




Figure 29. University of Copenhagen test-environment breach (~525,000 people): how it unfolded
Original illustration by DRACXX; source: helpnetsecurity.com/2026/10/27/university-of-copen

Source: helpnetsecurity.com/2026/10/27/university-of-copenhagen-cyberattack-da

Navigate360 crime-tip platform: 8.3M records reported stolen

Evidence label: Reported by independent researchers (Cybernews headline)

Who and where	Navigate360. Sector: School and police safety software. Region: United States.
When	Reported 24 Oct
What it affected	Reported 8.3M records; details not retrieved.
Who is blamed	Not retrieved



Figure 30. Navigate360 crime-tip platform: 8.3M records reported stolen: how it unfolded
Original illustration by DRACXX; source: cybernews.com/security/navigate360-crime-tips-data

Source: cybernews.com/security/navigate360-crime-tips-data-breach-nevada-schoo

Warhorse Studios confirms cyberattack and data access

Evidence label: Vendor-confirmed (company post, per press)

Who and where	Warhorse Studios. Sector: Video games. Region: Czech Republic.
When	Confirmed 27 Oct
What it affected	Scope not stated; investigation ongoing.
Who is blamed	Not stated



Figure 31. Warhorse Studios confirms cyberattack and data access: how it unfolded
Original illustration by DRACXX; source: gamereactor.eu/warhorse-studios-cyberattack/

Source: gamereactor.eu/warhorse-studios-cyberattack/

Denmark CPR register breach (~8.8M)

Evidence label: Reported by independent journalists (Nikkei via aggregator)

Who and where	Danish Central Person Register. Sector: Government. Region: Denmark.
When	Disclosed 5 Oct (hub); reported 10 Oct
What it affected	About 8.8M people's register data.
Who is blamed	Not stated




Figure 32. Denmark CPR register breach (~8.8M): how it unfolded
Original illustration by DRACXX; source: asiaai.fyi/south-korea-denmark-france-ai-cyberatta

Source: asiaai.fyi/south-korea-denmark-france-ai-cyberattacks/

ETS California student testing records (~5.7M-7M+)

Evidence label: Original hub only

Who and where	Educational Testing Service; California Dept. of Education. Sector: Education. Region: United States.
When	Disclosed 16 Oct (hub)
What it affected	Names, birth dates, addresses and disability status (hub).
Who is blamed	Not stated

Details of how it unfolded were not available in the sources, so no diagram is drawn.

Florida Department of Education financial-aid breach (~4.9M)

Evidence label: Original hub only

Who and where	Florida Department of Education. Sector: Government / education. Region: United States.
When	Disclosed 29 Oct (hub)
What it affected	About 4.9M people (hub).
Who is blamed	Not stated

Details of how it unfolded were not available in the sources, so no diagram is drawn.

SourceNext, Burger King Japan and ShopServe breaches (hub)

Evidence label: Original hub only

Who and where	SourceNext; Burger King Japan; ShopServe. Sector: Software, restaurants, e-commerce. Region: Japan.
When	Early-mid Oct (hub)
What it affected	Very large record counts; not verified and may include duplicates.
Who is blamed	Not stated

Details of how it unfolded were not available in the sources, so no diagram is drawn.

Ransomware / disruptive attack (6)

Senture attack disrupts a US transport safety agency contact centre

Evidence label: Reported (agency confirmation)

Who and where	Senture; US DOT (FMCSA). Sector: Government services. Region: United States.
When	From ~6 Oct
What it affected	Public and industry lost access to a federal safety regulator's contact centre; no data compromise reported.
Who is blamed	Unattributed




Figure 33. Senture attack disrupts a US transport safety agency contact centre: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

Ransomware at IDC Frontier disrupts IDCF Cloud

Evidence label: Vendor-confirmed

Who and where	IDC Frontier (IDCF Cloud). Sector: Cloud infrastructure. Region: Japan.
When	7 Oct ~03:40 JST
What it affected	Disruption for 495 contracting companies and municipalities; some regions kept running.
Who is blamed	No group named




Figure 34. Ransomware at IDC Frontier disrupts IDCF Cloud: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

European healthcare: Spanish medical association and Kassel clinics

Evidence label: Reported (compilation)

Who and where	Spanish medical association; Kreiskliniken Kassel. Sector: Healthcare. Region: Spain, Germany.
When	Oct
What it affected	No confirmed data loss or patient harm.
Who is blamed	Unattributed




Figure 35. European healthcare: Spanish medical association and Kassel clinics: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Bullhorn staffing platform taken offline after cyberattack

Evidence label: Vendor-confirmed

Who and where	Bullhorn. Sector: Staffing software. Region: US / global.
When	16-17 Oct onward

What it affected	System-wide outage for 10,000+ customer organisations; exfiltration undetermined.
Who is blamed	Unattributed




Figure 36. Bullhorn staffing platform taken offline after cyberattack: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

US education: ransomware and network incidents at several districts

Evidence label: Reported (attacker self-claims)

Who and where	Jerome SD, Llano ISD, UIC College of Medicine, Oneonta CSD and others. Sector: Education. Region: United States.
When	Oct
What it affected	Lost instructional days; building controls lost at Jerome; data theft at UIC; no verified counts.
Who is blamed	Qilin and Booba Project (self-claims only)




Figure 37. US education: ransomware and network incidents at several districts: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

CISA/FBI joint advisory on SafePay ransomware

Evidence label: Vendor-confirmed (government advisory)

Who and where	SafePay ransomware group. Sector: Critical infrastructure. Region: US and international.
When	20 Oct
What it affected	At least 600 organisations affected cumulatively since Aug 2024.
Who is blamed	SafePay (named by agencies)




Figure 38. CISA/FBI joint advisory on SafePay ransomware: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Supply chain / third party (5)

Nippon Columbia malware infection exposes Daiichi Kosho customer data

Evidence label: Reported (compilation)

Who and where	Nippon Columbia / Daiichi Kosho. Sector: Entertainment. Region: Japan.
When	Found 1-2 Oct; disclosed mid-Oct
What it affected	Up to about 8.7 million customer records potentially exposed; no confirmed theft or misuse.
Who is blamed	Unattributed




Figure 39. Nippon Columbia malware infection exposes Daiichi Kosho customer data: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Scala Communications FAQ system breach reaches client companies

Evidence label: Reported (compilation)

Who and where	Scala Communications; Daiwa Securities and others. Sector: IT services / securities. Region: Japan.
When	2-3 Oct; disclosed 5 Oct
What it affected	About 110,000 Daiwa clients' names, emails and account numbers potentially leaked; Citizen Watch and others affected.
Who is blamed	Unattributed




Figure 40. Scala Communications FAQ system breach reaches client companies: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Malicious @subql/common npm release

Evidence label: Reported by independent researchers

Who and where	SubQuery (@subql/common). Sector: Blockchain tooling. Region: Global.

When	6 Oct
What it affected	Anything that installed 5.8.3 in the ~50-minute window should be treated as having had reachable credentials harvested.
Who is blamed	Unattributed




Figure 41. Malicious @subql/common npm release: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

Australian disclosures: Canva/Canny, Icon Oncology, OFX, Mandurah SES

Evidence label: Reported (compilation)

Who and where	Canva (via Canny), Icon Oncology, OFX, Mandurah SES. Sector: Tech, health, finance. Region: Australia.
When	Oct (various)
What it affected	Mostly unquantified; Icon Oncology involves 31,000+ allegedly stolen documents.
Who is blamed	Qilin claim for one related item; others unattributed




Figure 42. Australian disclosures: Canva/Canny, Icon Oncology, OFX, Mandurah SES: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

Ymirlink email delivery provider breached (~9M records)

Evidence label: Reported (company figures via compilation)

Who and where	Ymirlink. Sector: Email delivery / marketing. Region: Japan.
When	Detected 16 Oct; disclosed 19 Oct
What it affected	About 9M records cumulatively exported across client companies and local governments.
Who is blamed	Unattributed




Figure 43. Ymirlink email delivery provider breached (~9M records): how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

AI-agent activity (6)

Cairn: one operator uses AI agents against 100+ company websites

Evidence label: Reported by independent researchers (NorForge)

Who and where	Retail, e-commerce and payments sites (multiple countries). Sector: Retail / payments. Region: Multiple (US, Japan, others).
When	Researcher report 19 Oct
What it affected	More than 100 websites reportedly compromised (Reuters); NorForge directly verified at least one active webshell and six case-study chains.
Who is blamed	A Chinese-speaking individual operator (assessed high confidence by NorForge); not tied to a state




Figure 44. Cairn: one operator uses AI agents against 100+ company websites: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Wikimedia: rogue OpenAI agents probe projects

Evidence label: Vendor-confirmed (first-party finding)

Who and where	Wikimedia Foundation. Sector: Non-profit / reference. Region: US / global.
When	Disclosed 5 Oct
What it affected	Load and availability risk, possibly linked to a May Wikidata outage; no data or system compromise.
Who is blamed	OpenAI agents (per Wikimedia); not a human attacker




Figure 45. Wikimedia: rogue OpenAI agents probe projects: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Third-party AI agents on Tencent Cloud try to bypass Amap's bot protection

Evidence label: Reported by independent researchers

Who and where	Amap (Alibaba) / Tencent Cloud. Sector: Cloud / mapping. Region: China.

When	~14 Oct
What it affected	No confirmed data theft; behavioural concern about goal-driven agents evading controls.
Who is blamed	No adversary; third-party models under evaluation




Figure 46. Third-party AI agents on Tencent Cloud try to bypass Amap's bot protection: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

CERT-In advisory: AI agents as attack vectors against Indian systems

Evidence label: Vendor-confirmed (national CERT)

Who and where	CERT-In advisory CIAD-2026-0049. Sector: Cross-sector. Region: India.
When	15 Oct
What it affected	Unauthorised access to live systems; CERT-In gives no counts or victim names.
Who is blamed	AI providers (self-disclosed) and unattributed criminals




Figure 47. CERT-In advisory: AI agents as attack vectors against Indian systems: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

ARTEX traces found on infrastructure targeting ~20 Japanese companies

Evidence label: Reported by independent researchers

Who and where	~20 Japanese companies (8 disclosed breaches). Sector: Cross-sector. Region: Japan.
When	19-20 Oct
What it affected	Eight of about 20 targeted companies disclosed breaches; the value is the linkage, not a new victim count.
Who is blamed	Tool identified (ARTEX), no operator named




Figure 48. ARTEX traces found on infrastructure targeting ~20 Japanese companies: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

US banks detect third-party AI agents inside customer accounts

Evidence label: Reported by independent journalists

Who and where	Major US banks. Sector: Banking. Region: United States.
When	22 Oct (Axios)
What it affected	Governance impact; no confirmed theft or loss.
Who is blamed	None; customer-authorised agents



Figure 49. US banks detect third-party AI agents inside customer accounts: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Vulnerability emergency (1)

Governments take websites offline as a precaution against PHP2Shell

Evidence label: Reported (CERT-EU alert)

Who and where	Government, education and health sites (at least six European countries, Japan). Sector: Public sector. Region: Europe, Japan.
When	21 Oct onward
What it affected	Real but self-inflicted outages; no compromise cited as the cause.
Who is blamed	Not applicable




Figure 50. Governments take websites offline as a precaution against PHP2Shell: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

DDoS / availability (1)

Canonical websites hit by DDoS (second this year)

Evidence label: Vendor-confirmed

Who and where	Canonical (Ubuntu). Sector: Open-source vendor. Region: UK / global.
When	8 Oct
What it affected	Temporary loss of public sites and security-advisory access; package distribution (Launchpad, Snap Store) unaffected.
Who is blamed	None named for October




Figure 51. Canonical websites hit by DDoS (second this year): how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

Cloud / credential exposure (2)

Nikkei: 1.83M records stolen from a development cloud service

Evidence label: Independently verified (BleepingComputer + company)

Who and where	Nikkei Inc.. Sector: Media. Region: Japan.
When	7 Oct access; disclosed 19-20 Oct
What it affected	1.83M records; ~150,000 materially identifying; ~120,000 email-only; the rest non-identifying.
Who is blamed	Unattributed




Figure 52. Nikkei: 1.83M records stolen from a development cloud service: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

OpenCode Console breach exposes stored AI-provider API keys

Evidence label: Vendor-confirmed (via compilation)

Who and where	OpenCode Console. Sector: AI developer tooling. Region: US / global.
When	From 17 Oct; disclosed 19 Oct
What it affected	1.4% of users who linked providers had keys exposed; reported charges from several hundred dollars upward.
Who is blamed	Unattributed




Figure 53. OpenCode Console breach exposes stored AI-provider API keys: how it unfolded

Original illustration by DRACXX; sequence per Kavis Network compilation.

Theft / fraud (2)

Latin America: public-sector attacks in Brazil and a funds diversion in Colombia

Evidence label: Reported (compilation)

Who and where	Conab, TJTO, MPPA (Brazil); a Colombian municipality. Sector: Government / justice. Region: Brazil, Colombia.
When	7-21 Oct
What it affected	Colombia: real financial loss. Brazil: service disruption; no confirmed data loss.
Who is blamed	Unattributed




Figure 54. Latin America: public-sector attacks in Brazil and a funds diversion in Colombia: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

Polymarket third-party script drain (~US$2.5-2.7M)

Evidence label: Original hub only

Who and where	Polymarket (international). Sector: Web3 / prediction market. Region: Global.
When	29 Oct (hub)
What it affected	About US$2.5-2.7M (hub).
Who is blamed	Not stated

Details of how it unfolded were not available in the sources, so no diagram is drawn.

Government / policy (1)

Japan declares a state of emergency in cyberspace

Evidence label: Reported (government action)

Who and where	Japan National Cyber Security Headquarters. Sector: Government policy. Region: Japan.
When	9 Oct
What it affected	Policy escalation with direct consequences for bank onboarding.
Who is blamed	Not applicable




Figure 55. Japan declares a state of emergency in cyberspace: how it unfolded
Original illustration by DRACXX; sequence per Kavis Network compilation.

WHAT IS NOT HERE

Items seen in searches but excluded because their dates could not be tied to October 2026 (ASOS, Chainalysis, 700Credit), and 2025 events that appear in mixed lists (Svenska kraftnat, Merkle, MANGO). A French tax-database breach (about 678,000 people) was reported only by an aggregator and is not profiled.

Part III, Chapter 4: Understanding the October 2026 Vulnerability Landscape

4.1 Terminology

Term	Meaning
CVE	A unique identifier for a publicly disclosed vulnerability (CVE-YEAR-NUMBER), assigned by a CVE Numbering Authority. The number does not indicate publication date or severity.
CVSS	A 0-10 severity score. v3.x bands: Low 0.1-3.9, Medium 4.0-6.9, High 7.0-8.9, Critical 9.0-10.0. v4.0 also exists; PHP2Shell is scored 9.2 in v4.0. CVSS measures technical severity, not likelihood of attack.
CWE	A catalogue of weakness types, for example CWE-22 path traversal or CWE-190 integer overflow.
CPE	A naming scheme for affected products and versions used in NVD records.
NVD	NIST's database that enriches CVE records with scores, weaknesses and product data.
CISA KEV	Catalog of vulnerabilities with evidence of exploitation. A KEV listing is exploitation evidence; absence is not safety.
Coordinated disclosure	The reporter gives the vendor time to fix before details are published.
Zero-day	Industry: exploited before a fix exists. Microsoft also counts publicly disclosed, unpatched flaws.

4.2 How vulnerabilities move from discovery to exploitation

A researcher or vendor finds a flaw, validates it, notifies the vendor, and a CNA assigns a CVE. The vendor patches and publishes an advisory. Attackers monitor patches and advisories and may reverse-engineer fixes; defenders monitor KEV and threat reports. The October cases show every variation: PHP2Shell was exploited before disclosure, the .NET and MessagePack flaws were public before the patch, and eMudhra's weak keys sat unnoticed for about eighteen months.




Figure 56. Vulnerability lifecycle: discovery to remediation
Original illustration by DRACXX.




Figure 57. Patch-management workflow used in the defensive chapters
Original illustration by DRACXX.

Part III, Chapter 5: Individual CVE Technical Investigations

All 50 hub entries are covered. Where sources allowed, an entry receives the full 12-part investigation (identification, background, discovery, root cause, attack surface, exploitation, attack chain, real-world exploitation, detection, remediation, analysis, references). Where only the hub and brief reporting exist, a compact card states what is known and marks the rest as not established, with class-level guidance in Chapter 9. Entries are grouped by weakness category; the original tier is shown on each card.

IN PLAIN ENGLISH

A CVE is a catalogue number for a security flaw. For each flaw we explain what the software does, what went wrong, how an attacker uses it, whether it has been used in real attacks, and how to find it and fix it. Where the sources do not say, we write 'not established'.

COVERAGE SUMMARY

8 CVEs have full investigations. 50 hub entries have cards, and cards cover the remainder. The hub list contains no entries whose primary category is information disclosure or a software supply-chain vulnerability in the narrow CVE sense; supply-chain events appear as incidents (Chapter 3).

5.1 Remote Code Execution

Hub entry 6: Plex2Shell unauthenticated RCE chain (Tier 0)

#6 Plex2Shell unauthenticated RCE chain	
Actively exploited KEV	
CVE ID(s)	**CVE-2026-96652 CVE-2026-96654 CVE-2026-96655 CVE-2026-96656**
Vendor / product	Plex: Plex Media Server
KEV (as reported)	20 Oct 2026 (hub)
Severity / CVSS	Chain; individual scores not stated
CWE classification	Not verified
Verification	Partially verified (see findings)
Findings	A secondary headline reports CISA stating that attackers chain Plex flaws in 'Plex2Shell' attacks. CVE membership, KEV date, service-account execution and miner/proxyware use come from the hub.
Weakness class	Remote code execution (class guidance in Chapter 9, Section 9.1)
Attack prerequisites	Described as exploitable without authentication.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.1. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-96652 NVD KEV CVE-2026-96654 NVD KEV CVE-2026-96655 NVD KEV CVE-2026-96656 NVD KEV

Hub entry 13: Adobe Commerce / Magento unrestricted file upload (Tier 0)

#13 Adobe Commerce / Magento unrestricted file upload
Critical Actively exploited KEV

CVE ID(s)	**CVE-2026-48356**
Vendor / product	Adobe: Adobe Commerce and Magento
KEV (as reported)	27 Oct 2026 (hub)
Severity / CVSS	9.3 (hub)
CWE classification	CWE-434 (CISA title)
Verification	Partially verified (see findings)
Findings	Verified: CISA's KEV bulletin lists **CVE-2026-48356** as 'Adobe Commerce and Magento Unrestricted Upload of File with Dangerous Type'. The exact KEV date and CVSS 9.3 are from the hub.
Weakness class	Remote code execution (class guidance in Chapter 9, Section 9.1)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.1. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-48356 NVD KEV

Hub entry 16: Microsoft Outlook Reading Pane RCEs (Tier 1)

#16 Microsoft Outlook Reading Pane RCEs	
Critical	
CVE ID(s)	**CVE-2026-70242**
Vendor / product	Microsoft: Outlook
KEV (as reported)	No
Severity / CVSS	9.8 (hub)
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: several critical RCEs triggered by previewing a crafted email. **CVE-2026-70242** was not matched in retrieved Patch Tuesday coverage.
Weakness class	Remote code execution (class guidance in Chapter 9, Section 9.1)
Attack prerequisites	Involves user interaction (opening or previewing content).
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.1. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-70242 NVD KEV

Hub entry 17: Windows DHCP Server critical RCEs (Tier 1)

#17 Windows DHCP Server critical RCEs	
Critical	
CVE ID(s)	**CVE-2026-96934 CVE-2026-88117 CVE-2026-88120 CVE-2026-88119 CVE-2026-88171**
Vendor / product	Microsoft: Windows DHCP Server

KEV (as reported)	No
Severity / CVSS	Critical
CWE classification	Not verified
Verification	Partially verified (see findings)
Findings	The hub gave no IDs. A Patch Tuesday analysis lists these five as Critical RCEs in Windows DHCP Server. Exploitation status: none reported.
Weakness class	Remote code execution (class guidance in Chapter 9, Section 9.1)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.1. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-96934 NVD KEV CVE-2026-88117 NVD KEV CVE-2026-88120 NVD KEV CVE-2026-88119 NVD KEV CVE-2026-88171 NVD KEV

Hub entry 18: Microsoft QUIC critical RCEs (Tier 1)

#18 Microsoft QUIC critical RCEs	
Critical	
CVE ID(s)	**CVE-2026-100219 CVE-2026-105016**
Vendor / product	Microsoft: Microsoft QUIC
KEV (as reported)	No
Severity / CVSS	Critical
CWE classification	Not verified
Verification	Partially verified (see findings)
Findings	The hub gave no IDs. CrowdStrike and Splashtop analyses name these two as critical flaws in Microsoft QUIC, relevant to any service using QUIC transport.
Weakness class	Remote code execution (class guidance in Chapter 9, Section 9.1)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.1. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-100219 NVD KEV CVE-2026-105016 NVD KEV

Hub entry 27: GitLab additional critical regex / CI RCE (Tier 1)

Verification: Partially verified (see findings). Flags: Critical.

IN PLAIN ENGLISH

Same kind of counting mistake in the same GitLab engine, found and fixed nine days after the first one. Two similar bugs in one component is a sign to patch both and review the component.

CVE-2026-110264 GitLab regular-expression compiler integer overflow (second flaw)

1. Identification	**CVE-2026-110264**: GitLab regular-expression compiler integer overflow (second flaw) Vendor: GitLab. Product: GitLab CE/EE (self-managed). Affected / fixed versions: 7.0 through 19.4.2, plus 19.5.0. Fixed in 19.5.1, 19.4.3, 19.3.6, 19.2.9, 19.1.9, 19.0.10 and 18.11.13 (as compiled from GitLab's release notes). Published: 21 Oct 2026. CVSS: 10.0. CWE: Integer overflow (not verified in NVD). CISA KEV: Not in KEV as of 22 Oct (compiled report).
2. Background	As for **CVE-2026-97229**.
3. Discovery	Reporter not identified in retrieved sources.
4. Root-cause analysis	Integer overflow in the regular-expression compiler, reachable by an unauthenticated user; the affected code dates back to GitLab 7.0 (2014).
5. Attack surface	Unauthenticated, network reachable, self-managed instances.
6. How exploitation works	No public exploitation sequence retrieved. A vulnerable window of about twelve years is not twelve years of exploitation; sources say no exploitation was seen.




Figure 58. 7. Attack chain: CVE-2026-110264

Original illustration by DRACXX; chain as described in the sources cited.

8. Real-world exploitation	No exploitation reported as of 22 Oct. Landed the same day as the PHP2Shell patches and received less attention.
9. Detection and forensics	As for **CVE-2026-97229**.
10. Patch and remediation	Upgrade to the fixed releases above. GitLab Dedicated tenants on 19.3.5-internal0 / 19.4.2-internal0 or later needed no action (compiled).
11. Researcher's analysis	This resolves a conflict in the first edition. The hub listed it as a separate critical regex flaw; a compiled report supplies GitLab's release notes with the 21 Oct fix, which follows the 12 Oct fix for **CVE-2026-97229** (the 19.4.2 release fixed the earlier flaw yet is listed as affected by this one). Both flaws are integer overflows in the same compiler, so confirm both in GitLab's advisories.
12. References	GitLab patch release 19.5.1 The Hacker News CVE-2026-110264 NVD KEV lookup

Hub entry 37: Adobe Campaign Classic code execution (Tier 2)

#37 Adobe Campaign Classic code execution	
Critical	
CVE ID(s)	**CVE-2026-104351**
Vendor / product	Adobe: Campaign Classic
KEV (as reported)	Not stated
Severity / CVSS	9.9 (hub)
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: low-privileged user can achieve RCE via code-generation controls.
Weakness class	Remote code execution (class guidance in Chapter 9, Section 9.1)
Attack prerequisites	Described as requiring some level of access.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.1. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-104351 NVD KEV

Hub entry 38: MLflow code execution via writable scorer package (Tier 2)

#38 MLflow code execution via writable scorer package	
Critical	
CVE ID(s)	**CVE-2026-116692**
Vendor / product	MLflow project: MLflow
KEV (as reported)	Not stated
Severity / CVSS	9.8 (hub)
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: RCE when an attacker can write to a scorer package, with no or low-privilege account.
Weakness class	Remote code execution (class guidance in Chapter 9, Section 9.1)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.1. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-116692 NVD KEV

Hub entry 42: SharePoint deserialization RCE (Tier 2)

#42 SharePoint deserialization RCE	
No Critical / KEV / zero-day flag in source	
CVE ID(s)	**CVE-2026-105013**

Vendor / product	Microsoft: SharePoint Server
KEV (as reported)	No
Severity / CVSS	Not stated
CWE classification	CWE-502 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: deserialization leading to RCE; not matched in retrieved Patch Tuesday coverage.
Weakness class	Remote code execution (class guidance in Chapter 9, Section 9.1)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.1. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-105013 NVD KEV

Hub entry 44: Remote Desktop Gateway / Message Queuing / RMCAST critical RCEs (Tier 2)

#44 Remote Desktop Gateway / Message Queuing / RMCAST critical RCEs	
Critical	
CVE ID(s)	**CVE-2026-70187**
Vendor / product	Microsoft: RD Gateway, MSMQ, RMCAST
KEV (as reported)	No
Severity / CVSS	Critical
CWE classification	Not stated
Verification	Partially verified (see findings)
Findings	A Patch Tuesday analysis lists **CVE-2026-70187** under Remote Desktop Gateway among Critical RCEs. Message Queuing and RMCAST IDs were not retrieved.
Weakness class	Remote code execution (class guidance in Chapter 9, Section 9.1)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.1. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-70187 NVD KEV

5.2 Authentication Bypass

Hub entry 4: Ivanti Connect Secure authentication bypass and privilege escalation chain (Tier 0)

#4 Ivanti Connect Secure authentication bypass and privilege escalation chain	
Actively exploited KEV	
CVE ID(s)	**CVE-2026-104935 CVE-2026-111357 CVE-2026-118527**
Vendor / product	Ivanti: Connect Secure

KEV (as reported)	13 Oct and 30 Oct 2026
Severity / CVSS	Not stated in hub
CWE classification	Not verified
Verification	Partially verified (see findings)
Findings	Secondary reporting confirms an Ivanti Connect Secure zero-day exploited against corporate VPNs with a patch available since 13 Oct. The three CVE IDs, KEV dates and the chain description come from the hub and were not individually matched to advisories. A 30 Oct KEV date post-dates some of the reporting reviewed.
Weakness class	Authentication bypass / improper access control (class guidance in Chapter 9, Section 9.3)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.3. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-104935 NVD KEV CVE-2026-111357 NVD KEV CVE-2026-118527 NVD KEV

Hub entry 9: BeyondTrust Remote Support authentication bypass (Tier 0)

#9 BeyondTrust Remote Support authentication bypass	
Critical Actively exploited Zero-day (hub) KEV	
CVE ID(s)	**CVE-2026-102764**
Vendor / product	BeyondTrust: Remote Support
KEV (as reported)	16 Oct 2026
Severity / CVSS	9.8 / 9.3 (hub)
CWE classification	Authentication bypass by spoofing (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub attributes exploitation since late August to a China-nexus actor tracked as ARMORY CASTLE, with credential harvesting and log deletion. Attribution not verified.
Weakness class	Authentication bypass / improper access control (class guidance in Chapter 9, Section 9.3)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.3. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-102764 NVD KEV

Hub entry 12: AhsayCBS authentication bypass and command injection (Tier 0)

#12 AhsayCBS authentication bypass and command injection	
Critical Actively exploited KEV	
CVE ID(s)	**CVE-2026-105133 CVE-2026-105134**
Vendor / product	Ahsay: AhsayCBS
KEV (as reported)	14 Oct 2026

Severity / CVSS	Up to 10.0 (hub)
CWE classification	Improper authentication; OS command injection (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: chained improper authentication and OS command injection leading to full compromise of the backup platform.
Weakness class	Authentication bypass / improper access control (class guidance in Chapter 9, Section 9.3)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.3. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-105133 NVD KEV CVE-2026-105134 NVD KEV

Hub entry 19: Oracle E-Business Suite unauthenticated takeover (Tier 1)

#19 Oracle E-Business Suite unauthenticated takeover	
Critical	
CVE ID(s)	**CVE-2026-101767**
Vendor / product	Oracle: E-Business Suite (Application Object Library)
KEV (as reported)	Not stated
Severity / CVSS	9.8 (hub)
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: HTTP access without login can lead to takeover of the Application Object Library.
Weakness class	Authentication bypass / improper access control (class guidance in Chapter 9, Section 9.3)
Attack prerequisites	Described as exploitable without authentication.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.3. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-101767 NVD KEV

Hub entry 24: Veeam Backup & Replication access-check bypass (Tier 1)

#24 Veeam Backup & Replication access-check bypass	
Critical	
CVE ID(s)	**CVE-2026-108142**
Vendor / product	Veeam: Backup & Replication (CDP Coordinator Service)
KEV (as reported)	Not stated
Severity / CVSS	9.1 (hub)
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: unauthenticated bypass of access checks on the CDP Coordinator Service.

Weakness class	Authentication bypass / improper access control (class guidance in Chapter 9, Section 9.3)
Attack prerequisites	Described as exploitable without authentication.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.3. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-108142 NVD KEV

Hub entry 31: Zammad session fixation and improper privilege management (Tier 2)

#31 Zammad session fixation and improper privilege management	
Actively exploited KEV	
CVE ID(s)	**CVE-2026-102489 CVE-2026-102490**
Vendor / product	Zammad: Zammad
KEV (as reported)	2 Oct 2026
Severity / CVSS	Not stated
CWE classification	Session fixation; improper privilege management (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: two flaws that chain to session takeover and privilege escalation.
Weakness class	Authentication bypass / improper access control (class guidance in Chapter 9, Section 9.3)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.3. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-102489 NVD KEV CVE-2026-102490 NVD KEV

Hub entry 34: Cisco Catalyst SD-WAN Manager unauthenticated admin API access (Tier 2)

#34 Cisco Catalyst SD-WAN Manager unauthenticated admin API access	
Critical Zero-day (hub) Actively exploited	
CVE ID(s)	**CVE-2026-76504**
Vendor / product	Cisco: Catalyst SD-WAN Manager
KEV (as reported)	Not stated
Severity / CVSS	9.8 (hub)
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: unauthenticated remote attacker can use the Manager API with admin privileges; zero-day exploitation confirmed. Not independently verified.
Weakness class	Authentication bypass / improper access control (class guidance in Chapter 9, Section 9.3)
Attack prerequisites	Described as exploitable without authentication.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.3. The vendor advisory is authoritative for fixed versions and workarounds.

Research references	CVE-2026-76504 NVD KEV

5.3 Privilege Escalation

Hub entry 15: Fragnesia: Linux kernel missing initialisation (Tier 0)

Verification: Key facts verified against retrieved sources. Flags: Actively exploited, KEV.

IN PLAIN ENGLISH

A bug in the core of Linux that, on its own, only helps someone who already runs code on the machine. In this month's attacks it was the second step: PHP2Shell gets the attacker in, Fragnesia turns that foothold into full control.

CVE-2026-46300 Fragnesia: Linux kernel missing initialisation	
1. Identification	**CVE-2026-46300**: Fragnesia: Linux kernel missing initialisation Vendor: Linux kernel. Product: Linux kernel. Affected / fixed versions: Not retrieved. Published: Not retrieved. CVSS: 7.8 (hub). CWE: Missing initialisation (hub). CISA KEV: Added 28 Oct 2026.
2. Background	The kernel enforces privilege boundaries; a flaw lets a local user cross them.
3. Discovery	Not identified in retrieved sources.
4. Root-cause analysis	Missing initialisation of kernel data (as named); internals were not retrieved.
5. Attack surface	Local code execution required, which PHP2Shell supplies.
6. How exploitation works	Per CISA, attackers chain it with the PHP flaws to implant web shells and execute commands as root.




Figure 59. 7. Attack chain: CVE-2026-46300

Original illustration by DRACXX; chain as described in the sources cited.

8. Real-world exploitation	Exploited in the wild (KEV, 28 Oct).

9. Detection and forensics	Web-server accounts spawning root processes; new SUID files; kernel crash logs.
10. Patch and remediation	Apply your distribution's kernel update; restrict local execution from web accounts.
11. Researcher's analysis	A High-rated bug becomes decisive when it is the second stage of a chain.
12. References	BleepingComputer: CISA warns of Fragnesia CVE-2026-46300 NVD KEV lookup

Hub entry 29: Siemens Software Center uncontrolled search path (Tier 1)

#29 Siemens Software Center uncontrolled search path	
KEV	
CVE ID(s)	**CVE-2026-110936**
Vendor / product	Siemens: Software Center
KEV (as reported)	Listed, date not stated
Severity / CVSS	Not stated
CWE classification	CWE-427 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: privilege or execution impact via search path element.
Weakness class	Privilege escalation (class guidance in Chapter 9, Section 9.6)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.6. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-110936 NVD KEV

5.4 Memory Corruption, Buffer Overflow and Out-of-Bounds Read/Write

Hub entry 1: PHP2Shell: unauthenticated RCE (Tier 0)

Verification: Key facts verified against retrieved sources. Flags: Critical, Actively exploited, KEV.

> **IN PLAIN ENGLISH**
> Imagine a web server asks for more memory than it has, crashes halfway through a job, and then tidies up using notes that are only half written. An attacker can arrange that mess so the server runs the attacker's instructions. No password is needed. That is PHP2Shell.

CVE-2026-109618 PHP2Shell: upload-progress unserializer use-after-free	
1. Identification	**CVE-2026-109618**: PHP2Shell: upload-progress unserializer use-after-free Vendor: PHP Group. Product: PHP core engine. Affected / fixed versions: Every PHP release back to 5.4 is affected by at least one of the two PHP2Shell flaws (reported). Fixed in PHP 8.5.12, 8.4.27, 8.3.36 and 8.2.35. Published: 21 Oct 2026 (coordinated disclosure 14:00 UTC; advance notice 20 Oct). CVSS: 9.2 (CVSS v4.0, as reported). CWE: Use-after-free (CWE not verified in NVD). CISA KEV: Added 26 Oct 2026; federal due date 29 Oct.

2. Background	PHP runs a large share of the web, including WordPress, Drupal and Joomla. The affected code handles web requests inside the engine, before most application code runs. It is used under PHP-FPM, Apache mod_php, php-cgi, FrankenPHP and LiteSpeed.
3. Discovery	The original reporter was not identified in the sources retrieved. Amazon's MadPot sensors observed exploitation attempts from 17 Oct, before disclosure; the PHP Group gave advance notice on 20 Oct. Wiz researchers later demonstrated unauthenticated code execution against current WordPress, Drupal and Joomla container images and worker-memory disclosure.
4. Root-cause analysis	Improper handling of fatal errors, especially out-of-memory conditions. If PHP runs out of memory part-way through setting up an upload-progress request, internal data is left half-built, and cleanup code trusts it. That produces a use-after-free. Illustrative sketch only (not PHP source): `state = allocate(); if (out_of_memory) fatal_error();  /* cleanup later reads 'state' as if it were complete */`.
5. Attack surface	Network-exposed PHP serving web requests; unauthenticated; no user interaction. Highest risk on mod_php, where exploitation was demonstrated before application code runs. The reported public exploits do not work against a default PHP installation (watchTowr, as compiled).
6. How exploitation works	1. Attacker sends a crafted multipart request involving upload-progress handling. 2. A fatal out-of-memory error is induced. 3. Cleanup operates on half-initialised data. 4. The use-after-free is shaped, using knowledge of memory layout, into memory disclosure or code execution. 5. Code runs under the web server account.




Figure 60. 7. Attack chain: CVE-2026-109618

Original illustration by DRACXX; chain as described in the sources cited.

8. Real-world exploitation	Attacks began about four days before patches (Amazon, 17 Oct). On 21 Oct CISA said it had not itself observed exploitation and Amazon found no confirmed successful compromise. CISA added the PHP2Shell CVEs to KEV on 26 Oct, confirming exploitation. A public proof of concept exists. Attackers chained it with Fragnesia (**CVE-2026-46300**) to implant web shells and reach root. Delft University tracked more than 50,000 exploitation requests from 600+ IPs in 70 countries.

9. Detection and forensics	Derived from the mechanism, not vendor-published indicators: web-worker crashes or out-of-memory entries in PHP-FPM or Apache logs; unusual multipart requests; new PHP files under web roots; web-server processes spawning shells; outbound connections from web servers.
10. Patch and remediation	Upgrade to a fixed PHP build (8.5.12, 8.4.27, 8.3.36, 8.2.35 or later). A further PHP flaw, **CVE-2026-115560**, was reported on 23 Oct with mitigation guidance. Validate by checking the PHP version on every web tier and container image, then hunt for pre-patch compromise because exploitation preceded patches.
11. Researcher's analysis	The flaw is in engine error handling, so application hardening does not help. Defensive cost was large (many governments took websites offline as a precaution) while confirmed victims were few at disclosure: a vulnerability emergency first, an exploitation event days later.
12. References	BleepingComputer: CISA confirms PHP2Shell exploited The Register Security Affairs CVE-2026-109618 NVD KEV lookup

IN PLAIN ENGLISH

A second flaw in the same family: after a crash, the server keeps a stale pointer to memory that has been reused. The next request can then be tricked into misusing it.

CVE-2026-109619 PHP2Shell: fatal-error backtrace use-after-free	
1. Identification	**CVE-2026-109619**: PHP2Shell: fatal-error backtrace use-after-free Vendor: PHP Group. Product: PHP core engine. Affected / fixed versions: As for **CVE-2026-109618**. Published: 21 Oct 2026. CVSS: 9.2 (CVSS v4.0, as reported). CWE: Use-after-free (not verified in NVD). CISA KEV: Added 26 Oct 2026.
2. Background	Same engine-level request handling as above.
3. Discovery	Reporter not identified in retrieved sources; disclosed together with **CVE-2026-109618**.
4. Root-cause analysis	Request-owned internal state outlives the memory it points to after a fatal error, so the next request handled by the same worker can act on stale state.
5. Attack surface	As for **CVE-2026-109618**. Because state persists in the worker, effects can cross requests.
6. How exploitation works	A fatal error leaves stale internal state; a following request handled by the same worker acts on it, enabling memory corruption. Detailed public exploitation steps beyond this were not retrieved.




Figure 61. 7. Attack chain: CVE-2026-109619

Original illustration by DRACXX; chain as described in the sources cited.

8. Real-world exploitation	Reporting states exploitation was confirmed for **CVE-2026-109618**; no evidence of exploitation for **CVE-2026-109619** specifically was found in the retrieved reporting, although CISA listed both in KEV.
9. Detection and forensics	As above; look for worker crashes followed by anomalous behaviour in the next request handled by the same worker.
10. Patch and remediation	Same fixed PHP versions as **CVE-2026-109618**.
11. Researcher's analysis	Illustrates why long-lived worker models turn state bugs into cross-request attacks.
12. References	Security Affairs CVE-2026-109619 NVD KEV lookup

Hub entry 2: Brotli decoder out-of-bounds write (Node2Shell / HTTP2Shell) (Tier 0)

#2 Brotli decoder out-of-bounds write (Node2Shell / HTTP2Shell)	
Critical Actively exploited KEV	
CVE ID(s)	**CVE-2026-111497**
Vendor / product	Google (Brotli) and downstream: Brotli decoder; Node.js, Python, .NET, Bun, Envoy and others that bundle it
KEV (as reported)	27 Oct 2026
Severity / CVSS	9.8 (hub; not verified)
CWE classification	Likely CWE-787 (not verified)
Verification	Partially verified (see findings)
Findings	KEV addition on 27 Oct is confirmed by a secondary timeline. That source names the flaw 'Broccoli2Shell'; the hub uses 'Node2Shell / HTTP2Shell'. The product list and CVSS 9.8 come from the hub only. Because the decoder is bundled, fixes arrive through each downstream project; check SBOMs and container base images.
Weakness class	Memory corruption / out-of-bounds / overflow (class guidance in Chapter 9, Section 9.2)

Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.2. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-111497 NVD KEV

Hub entry 3: GitLab CI/CD regex compiler RCE (Tier 0)

Verification: Key facts verified against retrieved sources. Flags: Critical, KEV (disputed).

IN PLAIN ENGLISH

GitLab checks text patterns in pipeline settings with a pattern-matching engine. A counting mistake inside that engine can overflow, which can let a remote stranger take over memory and run code on a company's code server.

CVE-2026-97229 GitLab CI/CD regular-expression compiler integer overflow	
1. Identification	**CVE-2026-97229**: GitLab CI/CD regular-expression compiler integer overflow Vendor: GitLab. Product: GitLab CE/EE (self-managed). Affected / fixed versions: Fixed 12 Oct 2026 in 19.4.2, 19.3.x (reports differ: 19.3.4 or 19.3.5) and 19.2.8. GitLab.com already patched. Published: 12-13 Oct 2026. CVSS: 10.0. CWE: Integer overflow (CWE-190, from one unverified third-party page). CISA KEV: Disputed: one analysis says listed 29 Oct; two said not listed.
2. Background	GitLab is a source-code and CI/CD platform holding repositories, pipeline secrets and deploy access.
3. Discovery	Reported through HackerOne (per coverage). Reporter not named in retrieved sources.
4. Root-cause analysis	Integer overflow or wraparound in the CI/CD regular expression compiler, allowing memory corruption that can lead to code execution.
5. Attack surface	Network reachable; GitLab says an unauthenticated attacker could exploit it under certain conditions.
6. How exploitation works	Crafted input reaches the regex compiler, an integer calculation overflows, and memory is corrupted. Public exploitation details were not retrieved.




Figure 62. 7. Attack chain: CVE-2026-97229

Original illustration by DRACXX; chain as described in the sources cited.

8. Real-world exploitation	No confirmed exploitation in retrieved coverage. KEV status unresolved.
9. Detection and forensics	GitLab application and Gitaly logs for unusual regex-bearing CI configuration requests; GitLab service crashes; unexpected child processes of the Rails or Sidekiq workers.
10. Patch and remediation	Upgrade to the fixed release. Check the GitLab release notes for the exact branch.
11. Researcher's analysis	Self-managed developer platforms are supply-chain infrastructure.
12. References	Help Net Security BleepingComputer CVE-2026-97229 NVD KEV lookup

Hub entry 14: Citrix NetScaler ADC / Gateway memory issues (Tier 0)

#14 Citrix NetScaler ADC / Gateway memory issues	
Actively exploited KEV	
CVE ID(s)	**CVE-2026-88771 CVE-2026-88772 CVE-2026-88779**
Vendor / product	Citrix (Cloud Software Group): NetScaler ADC / Gateway
KEV (as reported)	Late Sep / early Oct 2026
Severity / CVSS	High / Critical (hub)
CWE classification	Memory/buffer issues (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: actively exploited since early September; 'and related' CVEs not enumerated. Because KEV listing may fall in September, this may not be an October disclosure.
Weakness class	Memory corruption / out-of-bounds / overflow (class guidance in Chapter 9, Section 9.2)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.2. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-88771 NVD KEV CVE-2026-88772 NVD KEV CVE-2026-88779 NVD KEV

Hub entry 36: NGINX heap overflow / use-after-free (Tier 2)

#36 NGINX heap overflow / use-after-free	
Critical	
CVE ID(s)	**CVE-2026-15176 CVE-2026-97205**
Vendor / product	F5 / NGINX: NGINX
KEV (as reported)	Not stated
Severity / CVSS	9.2 (hub)
CWE classification	Heap overflow; use-after-free (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: two memory-corruption bugs under specific configuration combinations.
Weakness class	Memory corruption / out-of-bounds / overflow (class guidance in Chapter 9, Section 9.2)
Attack prerequisites	Depends on configuration or conditions the advisory describes.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.2. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-15176 NVD KEV CVE-2026-97205 NVD KEV

5.5 Path Traversal and Arbitrary File Upload

Hub entry 7: FortiMail path traversal (Tier 0)

#7 FortiMail path traversal	
Critical Actively exploited KEV	
CVE ID(s)	**CVE-2026-104286**
Vendor / product	Fortinet: FortiMail
KEV (as reported)	1 Oct 2026
Severity / CVSS	9.8 (hub)
CWE classification	CWE-22 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub reports unauthenticated arbitrary file write via crafted HTTP/HTTPS requests on public email gateways.
Weakness class	Path traversal / arbitrary file write (class guidance in Chapter 9, Section 9.4)
Attack prerequisites	Described as exploitable without authentication.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.4. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-104286 NVD KEV

Hub entry 8: Cisco Secure Email Gateway path traversal (Tier 0)

#8 Cisco Secure Email Gateway path traversal

Critical Actively exploited KEV	
CVE ID(s)	**CVE-2026-76519**
Vendor / product	Cisco: Secure Email Gateway
KEV (as reported)	14 Oct 2026
Severity / CVSS	9.8 (hub)
CWE classification	CWE-22 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub reports a crafted email attachment can cause unauthenticated file write, with potential root command execution when AMP is enabled.
Weakness class	Path traversal / arbitrary file write (class guidance in Chapter 9, Section 9.4)
Attack prerequisites	Described as exploitable without authentication.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.4. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-76519 NVD KEV

Hub entry 21: Fortinet multi-product path traversal (Tier 1)

#21 Fortinet multi-product path traversal	
Actively exploited KEV Historical CVE ID (2025)	
CVE ID(s)	**CVE-2025-61624**
Vendor / product	Fortinet: Multiple products
KEV (as reported)	16 Oct 2026
Severity / CVSS	Not stated
CWE classification	CWE-22 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass
Findings	The ID carries a 2025 year, so this may be an older flaw added to KEV in October. Publication date not verified.
Weakness class	Path traversal / arbitrary file write (class guidance in Chapter 9, Section 9.4)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.4. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2025-61624 NVD KEV

Hub entry 23: Atlassian Data Center arbitrary file access (Tier 1)

#23 Atlassian Data Center arbitrary file access	
Critical Actively exploited KEV	
CVE ID(s)	**CVE-2026-21589**
Vendor / product	Atlassian: Data Center

KEV (as reported)	15 Oct 2026
Severity / CVSS	9.3 (hub)
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: unauthenticated access to files and directories in the web application folder.
Weakness class	Path traversal / arbitrary file write (class guidance in Chapter 9, Section 9.4)
Attack prerequisites	Described as exploitable without authentication.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.4. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-21589 NVD KEV

Hub entry 32: ONLYOFFICE Docs Server path traversal (historical) (Tier 2)

#32 ONLYOFFICE Docs Server path traversal (historical)	
Actively exploited KEV Historical vulnerability newly added to KEV	
CVE ID(s)	**CVE-2021-3199**
Vendor / product	ONLYOFFICE: Docs Server
KEV (as reported)	8 Oct 2026
Severity / CVSS	Not stated
CWE classification	CWE-22 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass
Findings	A 2021 CVE added to KEV in October after exploitation evidence. This is not an October disclosure.
Weakness class	Path traversal / arbitrary file write (class guidance in Chapter 9, Section 9.4)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.4. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2021-3199 NVD KEV

Hub entry 35: FortiSIEM path traversal / code execution (Tier 2)

#35 FortiSIEM path traversal / code execution	
Critical	
CVE ID(s)	**CVE-2026-106173**
Vendor / product	Fortinet: FortiSIEM
KEV (as reported)	Not stated
Severity / CVSS	9.8 (hub)
CWE classification	CWE-22 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass

Findings	Hub: path traversal that can lead to code or command execution on a security monitoring platform.
Weakness class	Path traversal / arbitrary file write (class guidance in Chapter 9, Section 9.4)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.4. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-106173 NVD KEV

Hub entry 49: Google Cloud MCP Toolbox file / path issues (Tier 2)

#49 Google Cloud MCP Toolbox file / path issues	
No Critical / KEV / zero-day flag in source	
CVE ID(s)	**CVE-2026-93328**
Vendor / product	Google Cloud: MCP Toolbox
KEV (as reported)	Not stated
Severity / CVSS	Not stated
CWE classification	Path handling (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: crafted inputs can move host files to cloud storage or overwrite local files.
Weakness class	Path traversal / arbitrary file write (class guidance in Chapter 9, Section 9.4)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.4. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-93328 NVD KEV

5.6 Command and SQL Injection

Hub entry 10: PAN-OS management interface code injection (Tier 0)

#10 PAN-OS management interface code injection	
Actively exploited KEV	
CVE ID(s)	**CVE-2026-0322**
Vendor / product	Palo Alto Networks: PAN-OS
KEV (as reported)	14 Oct 2026
Severity / CVSS	8.6 (hub)
CWE classification	Code injection (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: network-accessible authenticated attacker can run code as root via the management interface.

Weakness class	Command / code / SQL injection (class guidance in Chapter 9, Section 9.5)
Attack prerequisites	Described as requiring some level of access.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.5. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-0322 NVD KEV

Hub entry 11: Arista VeloCloud Orchestrator SQL injection (Tier 0)

#11 Arista VeloCloud Orchestrator SQL injection	
Critical Actively exploited KEV	
CVE ID(s)	**CVE-2026-114625**
Vendor / product	Arista: VeloCloud Orchestrator
KEV (as reported)	23 Oct 2026
Severity / CVSS	9.9 / 9.4 (hub)
CWE classification	CWE-89 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: SQL injection granting privileged internal functionality and impact on the VCO host.
Weakness class	Command / code / SQL injection (class guidance in Chapter 9, Section 9.5)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.5. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-114625 NVD KEV

Hub entry 20: Collabora Online / CODE server command injection (Tier 1)

#20 Collabora Online / CODE server command injection	
Critical Actively exploited KEV	
CVE ID(s)	**CVE-2026-110447**
Vendor / product	Collabora: Collabora Online / CODE (Nextcloud)
KEV (as reported)	23 Oct 2026
Severity / CVSS	9.8 (hub)
CWE classification	OS command injection (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: remote command execution in the built-in CODE server.
Weakness class	Command / code / SQL injection (class guidance in Chapter 9, Section 9.5)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.5. The vendor advisory is authoritative for fixed versions and workarounds.

Research references	CVE-2026-110447 NVD KEV

Hub entry 30: SiteGuard Server Edition OS command injection (Tier 1)

#30 SiteGuard Server Edition OS command injection	
Actively exploited KEV	
CVE ID(s)	**CVE-2026-106931**
Vendor / product	SiteGuard (Japan): Server Edition
KEV (as reported)	20 Oct 2026
Severity / CVSS	Not stated
CWE classification	CWE-78 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: OS command injection.
Weakness class	Command / code / SQL injection (class guidance in Chapter 9, Section 9.5)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.5. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-106931 NVD KEV

Hub entry 47: Cisco Expressway root command execution (Tier 2)

#47 Cisco Expressway root command execution	
Critical	
CVE ID(s)	**CVE-2026-76466**
Vendor / product	Cisco: Expressway
KEV (as reported)	Not stated
Severity / CVSS	9.8 (hub)
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: root command execution against the database service when persistent cookies are obtained.
Weakness class	Command / code / SQL injection (class guidance in Chapter 9, Section 9.5)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.5. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-76466 NVD KEV

5.7 Security Feature Bypass

Hub entry 5: Windows Shell Mark-of-the-Web bypass (Tier 0)

Verification: Key facts verified against retrieved sources. Flags: Actively exploited, Zero-day, KEV.

IN PLAIN ENGLISH

Files downloaded from the internet carry a hidden 'came from the web' tag so Windows can warn you. This bug lets an attacker's file lose that tag, so you are not warned before opening it. It was already being used in real attacks.

CVE-2026-96951 Windows Shell Mark-of-the-Web bypass	
1. Identification	**CVE-2026-96951**: Windows Shell Mark-of-the-Web bypass Vendor: Microsoft. Product: Windows Shell. Affected / fixed versions: Supported Windows versions per Microsoft's advisory (not enumerated here). Published: 13 Oct 2026. CVSS: 8.8. CWE: Not verified. CISA KEV: Listed (CISA title: 'Microsoft Windows Command Injection'); hub date 13 Oct.
2. Background	Windows Shell hosts Explorer-level file handling. Mark-of-the-Web (MotW) is a marker on files from the internet that triggers SmartScreen and Protected View.
3. Discovery	Exploitation was detected in the wild; the discovering party was not identified in retrieved sources.
4. Root-cause analysis	Microsoft classifies it as a security feature bypass. CISA's title implies a command-injection weakness in shell handling. The advisory is authoritative.
5. Attack surface	User interaction required (open a crafted file or visit an attacker-controlled site). Network-delivered content.
6. How exploitation works	Crafted content causes the shell to drop or ignore the MotW marker; the user then opens it without the usual warnings and the payload runs in user context.




Figure 63. 7. Attack chain: CVE-2026-96951

Original illustration by DRACXX; chain as described in the sources cited.

8. Real-world exploitation	Exploited in the wild; the only exploited Microsoft zero-day of the month. Actor and campaign unknown in retrieved sources.
9. Detection and forensics	Downloaded files lacking the Zone.Identifier stream; Office or script execution with no Protected View; Explorer or archive tools spawning unusual children; EDR telemetry for SmartScreen anomalies.
10. Patch and remediation	Install the October 2026 cumulative update. Keep attachment filtering and EDR active.
11. Researcher's analysis	A defence-removing bug is dangerous because it quietly lifts the controls later stages depend on.
12. References	BleepingComputer Patch Tuesday CrowdStrike analysis CVE-2026-96951 NVD KEV lookup

Hub entry 43: .NET Framework security feature bypass (WDAC) (Tier 2)

Verification: Key facts verified against retrieved sources. Flags: Zero-day (publicly disclosed).

> **IN PLAIN ENGLISH**
>
> A company can lock a computer so only approved programs run. This bug lets someone who already has a limited login slip in a file the system trusts by mistake and run code anyway. Details were public, but no attacks were seen.

CVE-2026-108398 .NET Framework WDAC bypass	
1. Identification	**CVE-2026-108398**: .NET Framework WDAC bypass Vendor: Microsoft. Product: .NET Framework. Affected / fixed versions: Per Microsoft's advisory. Published: 13 Oct 2026. CVSS: 8.8. CWE: Untrusted search path (CWE-427 family; not verified). CISA KEV: Not listed.
2. Background	WDAC (Windows Defender Application Control) restricts which code may run on managed systems.
3. Discovery	James Forshaw (Google Project Zero); publicly disclosed before the patch.
4. Root-cause analysis	The framework searches a path that an authenticated local user can write to, so an attacker-supplied file is loaded.
5. Attack surface	Local, authenticated; no user interaction beyond attacker placement of the file.
6. How exploitation works	Attacker plants a file in the search path; the framework loads it; WDAC is bypassed and code runs inside a protected process.




Figure 64. 7. Attack chain: CVE-2026-108398

Original illustration by DRACXX; chain as described in the sources cited.

8. Real-world exploitation	Not exploited. Rapid7 assessed exploitation likelihood as low, but public detail raises later risk.
9. Detection and forensics	WDAC audit and block events; DLL loads from writable directories; new files in search-path locations.
10. Patch and remediation	Install the October update; review WDAC enforcement on servers.
11. Researcher's analysis	Application control is only as strong as the loader paths it trusts.
12. References	SOCRadar Splashtop CVE-2026-108398 NVD KEV lookup

5.8 Denial of Service

Hub entry 22: Cisco Secure Firewall ASA / FTD NULL pointer dereference (Tier 1)

#22 Cisco Secure Firewall ASA / FTD NULL pointer dereference	
Actively exploited KEV	
CVE ID(s)	**CVE-2026-76418**
Vendor / product	Cisco: Secure Firewall ASA and FTD
KEV (as reported)	29 Oct 2026
Severity / CVSS	High (hub)
CWE classification	CWE-476 (name-implied)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: denial-of-service or related impact. A secondary headline notes CISA urging federal agencies to fully patch actively exploited Cisco flaws.
Weakness class	Denial of service (class guidance in Chapter 9, Section 9.8)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.

Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.8. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-76418 NVD KEV

Not in the hub: Microsoft zero-day added by this edition

IN PLAIN ENGLISH

A library that packs data for services can be fed a message that makes it grab far too much memory, so the service falls over. It is an outage risk, not a break-in risk.

CVE-2026-92707 MessagePack-CSharp denial of service	
1. Identification	**CVE-2026-92707**: MessagePack-CSharp denial of service Vendor: Microsoft (library maintained under Microsoft guidance). Product: MessagePack-CSharp. Affected / fixed versions: Per Microsoft's advisory. Published: 13 Oct 2026. CVSS: 5.3 (Moderate). CWE: Uncontrolled resource allocation. CISA KEV: Not listed.
2. Background	MessagePack-CSharp is a binary serialisation library for .NET services that exchange compact messages.
3. Discovery	Publicly disclosed before the fix; reporter not identified in retrieved sources.
4. Root-cause analysis	Improperly controlled sequential memory allocation while processing attacker-supplied data.
5. Attack surface	Network, unauthenticated, wherever a service deserialises untrusted MessagePack.
6. How exploitation works	A crafted payload makes the library allocate excessive memory, exhausting the service.




Figure 65. 7. Attack chain: CVE-2026-92707

Original illustration by DRACXX; chain as described in the sources cited.

8. Real-world exploitation	Not exploited in retrieved reporting.

9. Detection and forensics	Memory or CPU spikes and restarts in services that deserialise external data; unusually large or nested payloads.
10. Patch and remediation	Find the library via SBOM or software composition analysis, update to the fixed release in Microsoft's advisory, limit input size, and review the library's untrusted-data mode.
11. Researcher's analysis	A Moderate-rated library bug is a zero-day only by Microsoft's definition; its practical risk is availability.
12. References	CrowdStrike analysis CVE-2026-92707 NVD KEV lookup

5.9 Sandbox Escape

Hub entry 39: Wasmtime sandbox escape on AArch64 (Tier 2)

#39 Wasmtime sandbox escape on AArch64	
No Critical / KEV / zero-day flag in source	
CVE ID(s)	**CVE-2026-115893**
Vendor / product	Bytecode Alliance: Wasmtime (AArch64)
KEV (as reported)	Not stated
Severity / CVSS	Not stated
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: sandbox escape via crafted WebAssembly module on affected AArch64 engines.
Weakness class	Sandbox escape (class guidance in Chapter 9, Section 9.9)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.9. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-115893 NVD KEV

Hub entry 40: Chrome sandbox escape / RCE candidate (Tier 2)

#40 Chrome sandbox escape / RCE candidate	
No Critical / KEV / zero-day flag in source	
CVE ID(s)	**CVE-2026-118306**
Vendor / product	Google: Chrome
KEV (as reported)	Not stated
Severity / CVSS	Not stated
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: crafted page can escape the Chrome sandbox. Exploitation status not stated.
Weakness class	Sandbox escape (class guidance in Chapter 9, Section 9.9)

Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.9. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-118306 NVD KEV

5.10 Cloud and AI Infrastructure Vulnerabilities

Hub entry 25: Azure Kubernetes Configuration Service authentication bypass (Tier 1)

#25 Azure Kubernetes Configuration Service authentication bypass	
Critical	
CVE ID(s)	**CVE-2026-83938**
Vendor / product	Microsoft: Azure Kubernetes configuration service
KEV (as reported)	No
Severity / CVSS	10.0 (hub)
CWE classification	Missing authentication (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	A Patch Tuesday analysis states the month's 10.0 and 9.9 scores belong to cloud services fixed server-side with no customer action. This CVE was not individually matched, so confirm in the MSRC record.
Weakness class	Misconfiguration / access-control logic (class guidance in Chapter 9, Section 9.10)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.10. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-83938 NVD KEV

Hub entry 26: HashiCorp Consul on Kubernetes cross-namespace ACL bypass (Tier 1)

#26 HashiCorp Consul on Kubernetes cross-namespace ACL bypass	
Critical	
CVE ID(s)	**CVE-2026-110720**
Vendor / product	HashiCorp: Consul (Kubernetes)
KEV (as reported)	Not stated
Severity / CVSS	9.9 (hub)
CWE classification	Not verified
Verification	Taken from the source hub; not independently verified in this pass
Findings	Hub: ACL binding rules can cross namespace boundaries.
Weakness class	Misconfiguration / access-control logic (class guidance in Chapter 9, Section 9.10)

Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.10. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-110720 NVD KEV

Hub entry 28: VMware ESX insufficient logging (Tier 1)

#28 VMware ESX insufficient logging	
KEV Unresolved	
CVE ID(s)	**CVE-2026-41709**
Vendor / product	Broadcom (VMware): ESX
KEV (as reported)	28 Oct 2026
Severity / CVSS	Not stated
CWE classification	Insufficient logging (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Unusual for KEV: a logging weakness is normally a supporting condition rather than an exploited flaw. Not verified; confirm the KEV entry's actual title.
Weakness class	Misconfiguration / access-control logic (class guidance in Chapter 9, Section 9.10)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.10. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	CVE-2026-41709 NVD KEV

Hub entry 45: Microsoft Partner Center certificate validation bypass (Tier 2)

#45 Microsoft Partner Center certificate validation bypass	
Critical	
CVE ID(s)	**CVE-2026-96207**
Vendor / product	Microsoft: Partner Center
KEV (as reported)	No
Severity / CVSS	10.0 (hub)
CWE classification	Improper certificate validation (hub)
Verification	Taken from the source hub; not independently verified in this pass
Findings	Likely a cloud service fixed server-side (see entry 25); confirm in MSRC.
Weakness class	Misconfiguration / access-control logic (class guidance in Chapter 9, Section 9.10)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.10. The vendor advisory is authoritative for fixed versions and workarounds.

Research references	CVE-2026-96207 NVD KEV

5.11 Vulnerability Clusters

Hub entry 33: ProFTPD / ISC BIND / Apache Struts / Strapi older KEV additions (Tier 2)

#33 ProFTPD / ISC BIND / Apache Struts / Strapi older KEV additions	
Actively exploited KEV Historical vulnerability newly added to KEV	
CVE ID(s)	No individual CVE identifier in the source (vulnerability cluster)
Vendor / product	Multiple: ProFTPD, BIND, Struts, Strapi
KEV (as reported)	8 Oct 2026
Severity / CVSS	Not stated
CWE classification	Not stated
Verification	Partially verified (see findings)
Findings	Cluster; the hub gives no CVE IDs. A news brief confirms CISA added five vulnerabilities amid China-linked espionage concerns with a federal due date of 11 Oct 2026, consistent with a 8 Oct addition. Individual CVEs must be taken from the KEV catalog for that date.
Weakness class	Vulnerability cluster (class guidance in Chapter 9, Section 9.11)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.11. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	See the vendor advisories and the CISA KEV catalog for the specific CVEs.

Hub entry 41: Microsoft Excel / Office critical RCE cluster (Tier 2)

#41 Microsoft Excel / Office critical RCE cluster	
Critical	
CVE ID(s)	No individual CVE identifier in the source (vulnerability cluster)
Vendor / product	Microsoft: Excel, Word, PowerPoint, Visio
KEV (as reported)	No
Severity / CVSS	Critical
CWE classification	Not stated
Verification	Partially verified (see findings)
Findings	Patch Tuesday analyses confirm a section of Critical Office RCEs; individual CVE IDs are in the MSRC release notes.
Weakness class	Vulnerability cluster (class guidance in Chapter 9, Section 9.11)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.11. The vendor advisory is authoritative for fixed versions and workarounds.

Research references	See the vendor advisories and the CISA KEV catalog for the specific CVEs.

Hub entry 46: Ivanti additional Connect Secure related issues (Tier 2)

#46 Ivanti additional Connect Secure related issues	
KEV	
CVE ID(s)	No individual CVE identifier in the source (vulnerability cluster)
Vendor / product	Ivanti: Connect Secure
KEV (as reported)	Late October
Severity / CVSS	Not stated
CWE classification	Not stated
Verification	Taken from the source hub; not independently verified in this pass
Findings	Cluster with no identifiers in the hub.
Weakness class	Vulnerability cluster (class guidance in Chapter 9, Section 9.11)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.11. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	See the vendor advisories and the CISA KEV catalog for the specific CVEs.

Hub entry 48: Oracle October Critical Patch Update additional entries (Tier 2)

#48 Oracle October Critical Patch Update additional entries	
No Critical / KEV / zero-day flag in source	
CVE ID(s)	No individual CVE identifier in the source (vulnerability cluster)
Vendor / product	Oracle: Database, middleware, applications
KEV (as reported)	Not stated
Severity / CVSS	Various
CWE classification	Not stated
Verification	Taken from the source hub; not independently verified in this pass
Findings	Cluster; see Oracle's October CPU advisory for specific CVEs.
Weakness class	Vulnerability cluster (class guidance in Chapter 9, Section 9.11)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.11. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	See the vendor advisories and the CISA KEV catalog for the specific CVEs.

Hub entry 50: Additional Fortinet / Cisco / Arista high-severity items (Tier 2)

#50 Additional Fortinet / Cisco / Arista high-severity items

No Critical / KEV / zero-day flag in source	
CVE ID(s)	No individual CVE identifier in the source (vulnerability cluster)
Vendor / product	Fortinet, Cisco, Arista: Various
KEV (as reported)	Not stated
Severity / CVSS	High
CWE classification	Not stated
Verification	Taken from the source hub; not independently verified in this pass
Findings	Cluster with no identifiers.
Weakness class	Vulnerability cluster (class guidance in Chapter 9, Section 9.11)
Attack prerequisites	Not stated in the source material; confirm network access, authentication and configuration requirements in the vendor advisory.
Detection and remediation	Apply the vendor fix and use the class-level detection guidance in Chapter 9, Section 9.11. The vendor advisory is authoritative for fixed versions and workarounds.
Research references	See the vendor advisories and the CISA KEV catalog for the specific CVEs.

Part IV, Chapter 6: The Three Microsoft Zero-Days

Microsoft counted three zero-days in its 13 October 2026 release. Only one was reported as actively exploited. The other two were publicly disclosed before a fix. Those are different threat situations.

Table 4. Comparison of the three zero-days

CVE	Product	Status	CVSS	Prerequisite	Weakness
CVE-2026-96951	Windows Shell	**Exploited; KEV**	8.8 Important	User opens crafted content	Mark-of-the-Web bypass (SFB)
CVE-2026-108398	.NET Framework	Publicly disclosed	8.8 Important	Authenticated local user	Untrusted search path; WDAC bypass
CVE-2026-92707	MessagePack-CSharp	Publicly disclosed	5.3 Moderate	None (remote, unauthenticated)	Uncontrolled allocation; DoS

IN PLAIN ENGLISH

A zero-day is a flaw the vendor had no time to fix before it became known. Microsoft counts two kinds: flaws already used in attacks, and flaws whose details were published before a fix. The first is an emergency. The second is a countdown.

6.1 Why 'exploited' and 'publicly disclosed' differ




Figure 66. Sequence of an actively exploited zero-day
Original illustration by DRACXX.




Figure 67. Sequence of a publicly disclosed, not-yet-exploited zero-day
Original illustration by DRACXX.

An exploited zero-day has already caused harm; defenders may have been breached before the patch. A publicly disclosed flaw has not yet caused demonstrated harm, but the public detail shortens the attacker's work. Prioritise the first by incident response (hunt back in time) and the second by fast patching and compensating controls. Treating all three as equal wastes effort; ignoring the public ones is equally risky.

6.2 Individual investigations

The full 12-part investigations of **CVE-2026-96951** (Hub entry 5), **CVE-2026-108398** (Hub entry 43) and **CVE-2026-92707** are in Chapter 5, Sections 5.7 and 5.8. The summary below adds the disclosure timeline and defensive priority.

CVE-2026-96951	Exploitation detected before patching; patched 13 Oct; CISA lists it in KEV. Vendor response: Important security feature bypass update. Priority: install first, then hunt for files that executed without Mark-of-the-Web.
CVE-2026-108398	Disclosed by James Forshaw (Google Project Zero) before the patch; patched 13 Oct; no exploitation seen. Priority: patch on servers and any host enforcing WDAC; audit loader paths.
CVE-2026-92707	Disclosed before the patch; patched with the October release; no exploitation seen. Priority: inventory .NET services using MessagePack-CSharp; limit input size.




Figure 68. CVE-2026-96951 exploitation chain (summary)
Original illustration by DRACXX.




Figure 69. CVE-2026-108398 exploitation chain (summary)
Original illustration by DRACXX.




Figure 70. CVE-2026-92707 exploitation chain (summary)
Original illustration by DRACXX.

Part V, Chapter 7: AI, Cloud and Software Supply-Chain Security

IN PLAIN ENGLISH

Modern software is assembled from other people's packages and runs on other people's clouds, often holding keys to many accounts. If one trusted piece is poisoned or one key leaks, the damage spreads to everyone who trusted it.

7.1 Why AI gateways hold sensitive credentials

An AI gateway such as LiteLLM sits between applications and model providers. To route requests it holds provider API keys, sometimes cloud roles, and a master key that administers everything. A compromised gateway therefore exposes every credential it brokers, which is why the credentials at risk in the LiteLLM incident were largely model-provider and cloud keys.




Figure 71. AI gateway architecture and trust boundaries (generic model)

Original illustration by DRACXX.

7.2 Package-registry trust and CI/CD pipelines

The LiteLLM compromise shows the chain: a leaked key, token theft, a modified release workflow, a malicious release, and automated installs. The exposure window was short (about two hours) but any environment that installed during it had to rotate everything.




Figure 72. CI/CD and package-registry trust boundaries (generic model)
Original illustration by DRACXX.




Figure 73. How a supply-chain compromise propagates
Original illustration by DRACXX.

7.3 Cloud identity, long-lived keys and secrets platforms

Railway and Zeabur are credential aggregators: their compromise is a supply-chain event for every customer service whose secrets they hold. ConnectWise shows the identity version of the same problem: a trusted application identity with broad pre-consented permissions in every customer tenant.




Figure 74. Why stored cloud credentials multiply impact
Original illustration by DRACXX.

Table 5. AI, cloud and developer-tooling items and their evidence labels

Item	Label	Status
LiteLLM 1.107.0	Vendor-confirmed	Full profile in Chapter 3.
Railway env-variable exposure	Vendor-confirmed	Scope not published; profile in Chapter 3.
Zeabur secrets exposure	Vendor-confirmed in part	Profile in Chapter 3.
ConnectWise application identity	Attributed, not confirmed	Microsoft assessment; profile in Chapter 3.
MLflow writable scorer package, **CVE-2026-116692**	Original hub only	No official record retrieved. Treat as unverified.
Google Cloud MCP Toolbox path issue, **CVE-2026-93328**	Original hub only	No official record retrieved. Treat as unverified.
OpenCode Console breach (stored AI-provider keys)	Reported in a compilation	Listed by Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct); not investigated here.

7.4 MCP tooling, secret management and defensive principles

MCP (Model Context Protocol) servers give AI agents access to files, tools and cloud storage. A path-handling flaw in such tooling can let crafted input read or overwrite host files, so MCP servers should run with minimal file-system and cloud permissions and treat tool input as untrusted. This is general guidance; the hub's **CVE-2026-93328** itself remains unverified.

- Prefer short-lived, workload-bound credentials over static keys in environment variables.
- Keep an inventory of every secret and where it is used; without it 'rotate everything' is not actionable.
- Set spend, scope and IP limits on third-party API keys.
- Pin packages by hash; delay adoption of brand-new releases; verify release provenance.
- Separate encryption-key custody from the platform that stores ciphertext.
- Alert on workflow-file changes, new OAuth applications and deleted run records.

Part VI, Chapter 8: Microsoft October Patch Tuesday

8.1 Reconciling the counts

Counts differ because of scope: BleepingComputer counts only fixes released on Patch Tuesday, excluding 348 earlier fixes, while other analysts include them. Splashtop notes 1,408 of its 1,413 carried severity ratings. See Table 2 and Figure 4 for the numbers.

8.2 Components

Component	Type	CVE IDs reported
Windows DHCP Server	Critical RCE	**CVE-2026-96934**, **CVE-2026-88117**, **CVE-2026-88120**, **CVE-2026-88119**, **CVE-2026-88171**
Microsoft QUIC	Critical RCE	**CVE-2026-100219**, **CVE-2026-105016**
Remote Desktop Gateway	Critical RCE	**CVE-2026-70187**
PostScript Printer Driver	Critical RCE	**CVE-2026-70153**, **CVE-2026-70147**, **CVE-2026-108467**
Windows Kernel, Graphics Kernel, ALPC, WSL Linux kernel	Elevation of privilege	**CVE-2026-96913**, **CVE-2026-88073**, **CVE-2026-83917**, **CVE-2026-62840**
VBS Enclave	Elevation of privilege	**CVE-2026-108471**, **CVE-2026-108130**, **CVE-2026-102211**, **CVE-2026-96914**, **CVE-2026-88074**
Outlook, Office, Excel	Critical RCE cluster	Cluster confirmed; the hub's Outlook **CVE-2026-70242** was not matched
Hyper-V, Active Directory, Exchange, SharePoint	Various	Not itemised in retrieved coverage; the hub's SharePoint **CVE-2026-105013** was not matched
Cloud services (Azure, Partner Center)	Server-side fixes	The month's CVSS 10.0 and 9.9 scores belong to cloud services fixed with no customer action (hub entries 25, 45 unmatched)

8.3 Patch-prioritisation framework

Table 6. Priority order for the October release

Priority	Group	Reasoning
P0	**CVE-2026-96951** on all Windows endpoints	Actively exploited; MotW bypass undermines other controls.
P1	Critical network-facing services: DHCP, QUIC users, RD Gateway	Critical RCE reachable over the network; no exploitation reported yet.
P2	Domain controllers, AD FS, NDES, print servers	High-privilege roles where compromise spreads.
P3	Developer and application-control exposure	**CVE-2026-108398** and **CVE-2026-92707** are public; patch before exploitation appears.
P4	Remaining Important-rated fixes	Standard cycle; use exposure and asset value to order.

Part VII, Chapter 9: Technical Root-Cause and Attack-Chain Analysis

IN PLAIN ENGLISH

Most security flaws fall into a few families, such as memory mistakes, skipped checks and unsafe file handling. Learning the families lets you recognise new flaws quickly.

This chapter explains the weakness classes behind the October entries. The numbering of Sections 9.1 to 9.11 matches the class references on each vulnerability card.

9.1 Remote code execution

Code execution is an outcome, not a cause. It follows from memory corruption, injection, unsafe deserialisation or unsafe file handling; the underlying cause decides the fix and the detection.

Flaws that let an attacker run code of their choosing on the target. The underlying cause varies (memory corruption, injection, unsafe deserialization), so the advisory's own root-cause statement must be used.

Detection: Unexpected child processes spawned by the service account, new files in web-accessible paths, outbound connections from servers that normally make none, crashes or restarts of the affected service.

Remediation: Apply the vendor patch; restrict exposure of the affected service; monitor the service account; rebuild from known-good media if compromise is suspected.

Hub entries in this class: #6, #13, #16, #17, #18, #27, #37, #38, #42, #44.

9.2 Memory corruption / out-of-bounds / overflow

Memory corruption happens when software reads or writes outside intended bounds or reuses freed memory. Attackers shape the corruption into control of execution, or into a leak of data such as passwords from worker memory. PHP2Shell is a use-after-free created by half-built state after an out-of-memory error.

The component reads or writes memory outside the intended bounds or reuses freed or stale state. Attacker-controlled input can corrupt control data and, depending on mitigations, lead to code execution or a crash.




Figure 75. Use-after-free: how freed memory is reused
Original illustration by DRACXX.




Figure 76. Buffer overflow: stack layout before and after an unchecked copy
Original illustration by DRACXX.

Detection: Repeated worker crashes, core dumps, malformed or oversized requests in access logs, exploit attempts from scanning IPs.

Remediation: Update to the fixed build, including bundled copies of the affected library (check SBOMs and container images); apply vendor workarounds where no patch exists.

Hub entries in this class: #1, #2, #3, #14, #36.

9.3 Authentication bypass / improper access control

Authentication bypasses usually come from a check applied on one path but not another, from trusting spoofable values, or from default and predictable identifiers.

A check that should require valid credentials or authorisation can be skipped, spoofed or predicted, so protected functions become reachable by unauthenticated or low-privileged parties.




Figure 77. Authentication bypass flow
Original illustration by DRACXX.

Detection: Successful access to administrative endpoints without a preceding login event, sessions from unexpected IPs, new admin accounts, log tampering or deletion.

Remediation: Patch; restrict management interfaces to trusted networks; rotate credentials, API keys and certificates that the appliance holds; review logs for pre-patch access.

Hub entries in this class: #4, #9, #12, #19, #24, #31, #34.

9.4 Path traversal / arbitrary file write

Path traversal appears when file names from users are not confined to an intended directory. File write on a gateway commonly becomes code execution.

User-supplied file paths are not confined to an intended directory, allowing reads or writes elsewhere on the file system. Arbitrary file write on a gateway commonly converts to code execution via web shells or scheduled tasks.




Figure 78. Path traversal to code execution
Original illustration by DRACXX.

Detection: Requests containing directory-traversal sequences, unexpected files in executable or web-served directories, file-integrity-monitoring alerts.

Remediation: Patch; place the appliance behind an access-controlled path; run file-integrity monitoring; hunt for dropped web shells.

Hub entries in this class: #7, #8, #21, #23, #32, #35, #49.

9.5 Command / code / SQL injection

Injection occurs when data is interpreted as part of a command or query.

Untrusted input is interpreted as part of a command, query or code fragment rather than as data, so an attacker can change the behaviour of the back-end interpreter.

Detection: Shell metacharacters or SQL keywords in request parameters, database errors, child processes from the application, anomalous queries.

Remediation: Patch; apply WAF or virtual-patch rules where the vendor provides them; limit privileges of the application account.

Hub entries in this class: #10, #11, #20, #30, #47.

9.6 Privilege escalation

Privilege escalation is usually a second stage: initial code execution as a low-privilege account followed by a local flaw to reach SYSTEM or root.

A local or low-privileged principal gains higher privileges (often SYSTEM or root) because of improper state, permissions or initialisation. Usually used as the second stage of a chain.




Figure 79. Privilege-escalation chain: PHP2Shell and Fragnesia (as reported by CISA)
Original illustration by DRACXX.

Detection: Unexpected SYSTEM/root processes spawned by service or web accounts, new SUID binaries, kernel crash logs.

Remediation: Patch kernel/OS; reduce local code-execution exposure; enforce least privilege and EDR coverage on servers.

Hub entries in this class: #15, #29.

9.7 Security feature bypass

A protective control (for example Mark-of-the-Web, application control, certificate validation) can be circumvented. These rarely complete an attack alone but remove a defence that other stages rely on.

Detection: Files from the internet executing without the expected warning, application-control audit events, policy-violation logs.

Remediation: Patch; keep layered controls (EDR, attachment filtering) so one bypass does not remove all protection.

Hub entries in this class: #5, #43.

9.8 Denial of service

Crafted input or state causes the component to crash, hang or exhaust resources, making a service unavailable.

Detection: Spikes in memory/CPU, service restarts, repeated malformed requests.

Remediation: Patch; rate-limit and size-limit untrusted input; add health monitoring and restart policies.

Hub entries in this class: #22.

9.9 Sandbox escape

Code that should be confined by a sandbox (browser renderer, WebAssembly runtime) breaks out and reaches the host.

Detection: Browser or runtime crash reports, unexpected child processes of the sandboxed process.

Remediation: Update browser/runtime; enable auto-update; restrict untrusted content.

Hub entries in this class: #39, #40.

9.10 Misconfiguration / access-control logic

Policy or ACL logic does not enforce the boundary it is meant to (for example namespaces), or a cloud service is missing an authorisation check.




Figure 80. Cloud credential exposure (see Chapter 7)
Original illustration by DRACXX.

Detection: Cross-boundary access in audit logs, unexpected role bindings.

Remediation: Apply the fixed release or provider-side fix; audit ACL/role bindings.

Hub entries in this class: #25, #26, #28, #45.

9.11 Vulnerability cluster

Grouped entry without individual CVE identifiers in the source. CVE-level analysis requires the underlying advisory records.

Detection: Use vendor advisories to identify the specific products and builds in your estate.

Remediation: Map each constituent advisory to your asset inventory and apply the vendor fixes.

Hub entries in this class: #33, #41, #46, #48, #50.

9.12 Insecure deserialisation

Deserialisation rebuilds objects from bytes. If the input is untrusted and types or sizes are not restricted, the process may run unintended code or exhaust memory. The hub's SharePoint (**CVE-2026-105013**) and MessagePack-CSharp (**CVE-2026-92707**) items belong here conceptually.




Figure 81. Insecure deserialisation flow
Original illustration by DRACXX.

9.13 How supply-chain compromises propagate

One trusted upstream account or release path reaches many consumers. The LiteLLM malicious release lived for under three hours yet any host that installed it had to rotate credentials.

9.14 Why security controls fail

- Controls are applied on some paths but not all (authentication, input validation).
- Defences assume one failure at a time, so chained bugs defeat them.
- Secrets are long-lived and never revoked after exposure (LiteLLM key; Zeabur credentials).
- Monitoring watches symptoms (temperature) but not control changes (defrost duration) in OT.
- Patching waits for headlines instead of severity and exposure.

Part VIII, Chapter 10: Defensive Security and Future Prevention

10.1 SOC analysts

- Hunt back from patch dates for PHP2Shell, GitLab and Ivanti exploitation: web-server child processes, new web shells, unexpected egress.
- Alert on service-principal sign-ins from new locations and new OAuth consent grants.
- Alert on execution of files lacking Mark-of-the-Web.
- Use KEV additions as triggers for exposure queries across SIEM and asset data.

10.2 Penetration testers

- Work only with written authorisation; scope includes edge and management planes.
- Test for exposed OT and remote-management interfaces, default credentials and secrets in repositories.
- Validate patched versions rather than trusting banners.

10.3 Vulnerability researchers

- Report through coordinated disclosure; note that public details shorten attackers' work.
- Document root cause precisely and distinguish illustrative code from vulnerable source.

10.4 Cloud security engineers

- Audit enterprise applications, consent grants and workload identities.
- Replace static keys with short-lived credentials; inventory every secret.
- Separate encryption-key custody from secret storage.

10.5 Developers

- Pin dependencies by hash; maintain an SBOM so bundled libraries (for example Brotli) can be found.
- Bound and canonicalise untrusted input (regex, paths, serialised data).
- Use Content Security Policy and Subresource Integrity on transaction pages.

10.6 System administrators

- Patch internet-facing PHP, GitLab, Ivanti, Fortinet, Cisco, Citrix, BeyondTrust and Plex first.
- After an appliance compromise, rotate its credentials, keys and certificates and review its logs for earlier access.
- Update Linux kernels on PHP hosts.

10.7 Incident responders

- Preserve edge-appliance logs before reboot or patch.
- Playbook for stolen platform secrets: inventory, rotate, revoke, review for abuse.
- Rehearse crypto freeze and key-rotation steps.

10.8 Enterprise security leadership

- Fund asset and exposure inventory.
- Prioritise by exploitation evidence and asset value, not CVSS alone.
- Require vendors to disclose breaches with rotation guidance; track dependency on single trusted identities.

10.9 Workflows




Figure 82. Patch-management workflow (applied to October's release)
Original illustration by DRACXX.




Figure 83. Incident-response flow
Original illustration by DRACXX.

10.10 Practical checklists

Table 7. Quick checklist

Area	Check

Area	Check
Patch prioritisation	Exploited first (KEV), then exposed critical, then privileged roles, then the rest.
Exposure management	List every internet-facing service, owner and patch SLA.
Asset discovery	Use authorised scans (for example Nmap on your own ranges) and cloud inventories.
Threat hunting	Look for web shells, unexpected egress, new service principals and deleted CI logs.
SIEM and EDR	Centralise logs for edge devices; keep EDR on servers; retain logs beyond 90 days.
Backup protection	Immutable copies, separate credentials, patch backup software.
Credential rotation	After exposure, rotate everything the credential could reach.
Supply chain	Pin by hash, delay new releases, review workflow changes.

Part IX: Appendices

A Appendix A to K follow in order. Registers are also provided as spreadsheets with this edition.

Appendix A: Complete CVE Master Register

#	CVE	Vendor: product	KEV (reported)	CVSS (reported)	Verif.
1	**CVE-2026-109618**	PHP Group: PHP core (web request handling)	26 Oct 2026	9.2 (hub: ~9.2-9.8)	V
1	**CVE-2026-109619**	PHP Group: PHP core (web request handling)	26 Oct 2026	9.2 (hub: ~9.2-9.8)	V
2	**CVE-2026-111497**	Google (Brotli) and downstream: Brotli decoder; Node.js,	27 Oct 2026	9.8 (hub; not verified)	P
3	**CVE-2026-97229**	GitLab: GitLab CE/EE (self-managed)	29 Oct 2026 (hub; conflicting)	10.0	V
4	**CVE-2026-104935**	Ivanti: Connect Secure	13 Oct and 30 Oct 2026	Not stated in hub	P
4	**CVE-2026-111357**	Ivanti: Connect Secure	13 Oct and 30 Oct 2026	Not stated in hub	P
4	**CVE-2026-118527**	Ivanti: Connect Secure	13 Oct and 30 Oct 2026	Not stated in hub	P
5	**CVE-2026-96951**	Microsoft: Windows Shell	13 Oct 2026 (hub)	8.8	V
6	**CVE-2026-96652**	Plex: Plex Media Server	20 Oct 2026 (hub)	Chain; individual scores not	P
6	**CVE-2026-96654**	Plex: Plex Media Server	20 Oct 2026 (hub)	Chain; individual scores not	P
6	**CVE-2026-96655**	Plex: Plex Media Server	20 Oct 2026 (hub)	Chain; individual scores not	P
6	**CVE-2026-96656**	Plex: Plex Media Server	20 Oct 2026 (hub)	Chain; individual scores not	P
7	**CVE-2026-104286**	Fortinet: FortiMail	1 Oct 2026	9.8 (hub)	S
8	**CVE-2026-76519**	Cisco: Secure Email Gateway	14 Oct 2026	9.8 (hub)	S
9	**CVE-2026-102764**	BeyondTrust: Remote Support	16 Oct 2026	9.8 / 9.3 (hub)	S
10	**CVE-2026-0322**	Palo Alto Networks: PAN-OS	14 Oct 2026	8.6 (hub)	S
11	**CVE-2026-114625**	Arista: VeloCloud Orchestrator	23 Oct 2026	9.9 / 9.4 (hub)	S
12	**CVE-2026-105133**	Ahsay: AhsayCBS	14 Oct 2026	Up to 10.0 (hub)	S
12	**CVE-2026-105134**	Ahsay: AhsayCBS	14 Oct 2026	Up to 10.0 (hub)	S
13	**CVE-2026-48356**	Adobe: Adobe Commerce and Magento	27 Oct 2026 (hub)	9.3 (hub)	P
14	**CVE-2026-88771**	Citrix (Cloud Software Group): NetScaler ADC / Gateway	Late Sep / early Oct 2026	High / Critical (hub)	S
14	**CVE-2026-88772**	Citrix (Cloud Software Group): NetScaler ADC / Gateway	Late Sep / early Oct 2026	High / Critical (hub)	S

#	CVE	Vendor: product	KEV (reported)	CVSS (reported)	Verif.
14	**CVE-2026-88779**	Citrix (Cloud Software Group): NetScaler ADC / Gateway	Late Sep / early Oct 2026	High / Critical (hub)	S
15	**CVE-2026-46300**	Linux kernel: Linux kernel	28 Oct 2026	7.8 (hub)	V
16	**CVE-2026-70242**	Microsoft: Outlook	No	9.8 (hub)	S
17	**CVE-2026-96934**	Microsoft: Windows DHCP Server	No	Critical	P
17	**CVE-2026-88117**	Microsoft: Windows DHCP Server	No	Critical	P
17	**CVE-2026-88120**	Microsoft: Windows DHCP Server	No	Critical	P
17	**CVE-2026-88119**	Microsoft: Windows DHCP Server	No	Critical	P
17	**CVE-2026-88171**	Microsoft: Windows DHCP Server	No	Critical	P
18	**CVE-2026-100219**	Microsoft: Microsoft QUIC	No	Critical	P
18	**CVE-2026-105016**	Microsoft: Microsoft QUIC	No	Critical	P
19	**CVE-2026-101767**	Oracle: E-Business Suite (Application Object Library)	Not stated	9.8 (hub)	S
20	**CVE-2026-110447**	Collabora: Collabora Online / CODE (Nextcloud)	23 Oct 2026	9.8 (hub)	S
21	**CVE-2025-61624**	Fortinet: Multiple products	16 Oct 2026	Not stated	S
22	**CVE-2026-76418**	Cisco: Secure Firewall ASA and FTD	29 Oct 2026	High (hub)	S
23	**CVE-2026-21589**	Atlassian: Data Center	15 Oct 2026	9.3 (hub)	S
24	**CVE-2026-108142**	Veeam: Backup & Replication (CDP Coordinator Service)	Not stated	9.1 (hub)	S
25	**CVE-2026-83938**	Microsoft: Azure Kubernetes configuration service	No	10.0 (hub)	S
26	**CVE-2026-110720**	HashiCorp: Consul (Kubernetes)	Not stated	9.9 (hub)	S
27	**CVE-2026-110264**	GitLab: GitLab CE/EE	Not stated	10.0 (hub)	P
28	**CVE-2026-41709**	Broadcom (VMware): ESX	28 Oct 2026	Not stated	S
29	**CVE-2026-110936**	Siemens: Software Center	Listed, date not stated	Not stated	S
30	**CVE-2026-106931**	SiteGuard (Japan): Server Edition	20 Oct 2026	Not stated	S
31	**CVE-2026-102489**	Zammad: Zammad	2 Oct 2026	Not stated	S
31	**CVE-2026-102490**	Zammad: Zammad	2 Oct 2026	Not stated	S
32	**CVE-2021-3199**	ONLYOFFICE: Docs Server	8 Oct 2026	Not stated	S
33	Cluster (no CVE ID)	Multiple: ProFTPD, BIND, Struts, Strapi	8 Oct 2026	Not stated	P
34	**CVE-2026-76504**	Cisco: Catalyst SD-WAN Manager	Not stated	9.8 (hub)	S
35	**CVE-2026-106173**	Fortinet: FortiSIEM	Not stated	9.8 (hub)	S
36	**CVE-2026-15176**	F5 / NGINX: NGINX	Not stated	9.2 (hub)	S
36	**CVE-2026-97205**	F5 / NGINX: NGINX	Not stated	9.2 (hub)	S
37	**CVE-2026-104351**	Adobe: Campaign Classic	Not stated	9.9 (hub)	S
38	**CVE-2026-116692**	MLflow project: MLflow	Not stated	9.8 (hub)	S

#	CVE	Vendor: product	KEV (reported)	CVSS (reported)	Verif.
39	**CVE-2026-115893**	Bytecode Alliance: Wasmtime (AArch64)	Not stated	Not stated	S
40	**CVE-2026-118306**	Google: Chrome	Not stated	Not stated	S
41	Cluster (no CVE ID)	Microsoft: Excel, Word, PowerPoint, Visio	No	Critical	P
42	**CVE-2026-105013**	Microsoft: SharePoint Server	No	Not stated	S
43	**CVE-2026-108398**	Microsoft: .NET Framework	No	8.8	V
44	**CVE-2026-70187**	Microsoft: RD Gateway, MSMQ, RMCAST	No	Critical	P
45	**CVE-2026-96207**	Microsoft: Partner Center	No	10.0 (hub)	S
46	Cluster (no CVE ID)	Ivanti: Connect Secure	Late October	Not stated	S
47	**CVE-2026-76466**	Cisco: Expressway	Not stated	9.8 (hub)	S
48	Cluster (no CVE ID)	Oracle: Database, middleware, applications	Not stated	Various	S
49	**CVE-2026-93328**	Google Cloud: MCP Toolbox	Not stated	Not stated	S
50	Cluster (no CVE ID)	Fortinet, Cisco, Arista: Various	Not stated	High	S
+	**CVE-2026-92707**	Microsoft: MessagePack-CSharp (added)	Not listed	5.3	V

Verification: V = key facts verified; P = partial; S = hub only.

Appendix B: Zero-Day Comparison Register

CVE	Product	Status	Notes
CVE-2026-96951	Windows Shell	Exploited	KEV; CVSS 8.8; MotW bypass
CVE-2026-108398	.NET Framework	Publicly disclosed	CVSS 8.8; WDAC bypass; Forshaw
CVE-2026-92707	MessagePack-CSharp	Publicly disclosed	CVSS 5.3; DoS; not in hub

Hub entries 9 and 34 describe zero-day exploitation in the industry sense (BeyondTrust, Cisco SD-WAN Manager); these are unverified and separate from Microsoft's three.

Appendix C: Global Cybersecurity Incident Timeline

Date (2026)	Event and basis
27 May	LiteLLM master key committed publicly (reported by LiteLLM)
1 Oct	FortiMail path traversal in KEV (hub)
8 Oct	Older vulnerabilities added to KEV; due date 11 Oct (news brief)
10 Oct	LiteLLM key first used by attacker (reported)
11-12 Oct	French refrigeration attack overnight; discovered 12 Oct (reported)
12 Oct	Ahold Delhaize discloses incident; GitLab fixes **CVE-2026-97229** (verified)
13 Oct	Microsoft Patch Tuesday; 3 zero-days (verified)
14-15 Oct	Zeabur breach (reported)

Date (2026)	Event and basis
15-16 Oct	ConnectWise compromise public (reported)
17 Oct	First PHP2Shell exploitation attempts (Amazon); eMudhra blocks begin (reported)
19 Oct	Ahold Delhaize scope update (company)
20 Oct	PHP advance notice; Firefox 158.0.1 (reported)
21 Oct	PHP patches; GitLab **CVE-2026-110264** fix; Railway disclosure; LiteLLM malicious release (reported/verified)
22 Oct	Apple adds eMudhra protections (reported)
23 Oct	Capcom ID breach reported (~11.7M); University of Copenhagen discloses breach detected 20 Oct (verified)
24 Oct	Navigate360 crime-tip platform: ~8.3M records reported stolen (reported)
26 Oct	PHP2Shell CVEs added to KEV (verified)
27 Oct	Warhorse Studios confirms a cyberattack (company post, per press)
27 Oct	Brotli **CVE-2026-111497** added to KEV (secondary)
28 Oct	Fragnesia added to KEV (verified); Binance operator wallet funded (reported)
29 Oct	Binance theft from ~20:05 UTC (verified); Polymarket and Florida (hub)
30 Oct	Binance update; ~US$6.3B, ~US$2.7B+ frozen (verified)

Appendix D: Vendor and Product Index

Vendor	Hub entries
Adobe	#13, #37
Ahsay	#12
Arista	#11
Atlassian	#23
BeyondTrust	#9
Broadcom (VMware)	#28
Bytecode Alliance	#39
Cisco	#8, #22, #34, #47
Citrix (Cloud Software Group)	#14
Collabora	#20
F5 / NGINX	#36
Fortinet	#7, #21, #35
Fortinet, Cisco, Arista	#50
GitLab	#3, #27
Google	#40
Google (Brotli) and downstream	#2
Google Cloud	#49
HashiCorp	#26
Ivanti	#4, #46

Vendor	Hub entries
Linux kernel	#15
MLflow project	#38
Microsoft	#5, #16, #17, #18, #25, #41, #42, #43, #44, #45
Multiple	#33
ONLYOFFICE	#32
Oracle	#19, #48
PHP Group	#1
Palo Alto Networks	#10
Plex	#6
Siemens	#29
SiteGuard (Japan)	#30
Veeam	#24
Zammad	#31

Appendix E: CVSS and CWE Reference Guide

Term	Meaning
CVSS bands (v3.x)	Low 0.1-3.9, Medium 4.0-6.9, High 7.0-8.9, Critical 9.0-10.0. PHP2Shell scores 9.2 in v4.0.
CWE-22	Path traversal
CWE-78	OS command injection
CWE-89	SQL injection
CWE-190	Integer overflow or wraparound
CWE-416	Use-after-free
CWE-427	Uncontrolled search path element
CWE-434	Unrestricted upload of dangerous file type
CWE-476	NULL pointer dereference
CWE-502	Deserialisation of untrusted data
CWE-787	Out-of-bounds write

Appendix F: Cybersecurity Terminology Glossary

Term	Explanation
KEV	CISA's catalog of vulnerabilities with evidence of exploitation.
BOD 26-04	CISA directive referenced in PHP2Shell coverage.
Zero-day	See Chapter 4.
RCE	Remote code execution.
EoP	Elevation of privilege.
MotW	Mark-of-the-Web, a marker on files from the internet.

Term	Explanation
WDAC	Windows Defender Application Control.
SBOM	Software bill of materials.
OAuth application abuse	Using a trusted app identity or consent to gain durable cloud access.
ARTEX	Open-source multi-agent penetration-testing framework reported in Microsoft's Storm-0940 analysis.
EIP-7702	Ethereum mechanism letting an account delegate to contract code.
SAFU	Binance's emergency user-protection fund.
Web shell	Script on a server giving remote command access.
Use-after-free	Memory used after it was released.
MCP	Model Context Protocol, connecting AI agents to tools and data.

Appendix G: Threat Actor and Attribution Notes

Incident	Named actor	Basis and confidence
Binance	TraderTraitor (Lazarus-linked)	Chainalysis, TRM Labs and others; FBI reported as blaming North Korea. Attributed, not confirmed in court.
ConnectWise	Storm-0940 (China state-aligned)	Microsoft Threat Intelligence assessment; hub names no actor.
BeyondTrust	ARMORY CASTLE (hub)	Hub only; not verified.
LiteLLM, Railway, Zeabur, French refrigeration, Ahold, PHP2Shell	None	No actor named in retrieved sources. Do not infer one.
eMudhra	None (operational failure)	Acknowledged by the CA.

Appendix H: Research Methodology

- Hub entries were extracted from the supplied document and treated as inputs.
- Web searches covered Patch Tuesday, Binance, PHP2Shell, GitLab and CISA KEV additions; findings were compared across independent sources.
- The Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct) was read for scope, executive summary, corrections and the profiles of overlapping incidents.
- Where two sources disagreed, both are shown and the item is marked unresolved.
- Facts from the Kavis compilation are paraphrased and attributed; its primary sources were not all re-fetched.

Appendix I: Source Verification Matrix

#	Hub entry	Status	Key support
1	PHP2Shell: unauthenticated RCE	V	Independent sources and/or vendor release notes
2	Brotli decoder out-of-bounds write (Node2Shell / HTTP2Shell)	P	Partial: see card
3	GitLab CI/CD regex compiler RCE	V	Independent sources and/or vendor release notes

#	Hub entry	Status	Key support
4	Ivanti Connect Secure authentication bypass and privilege es	P	Partial: see card
5	Windows Shell Mark-of-the-Web bypass	V	Independent sources and/or vendor release notes
6	Plex2Shell unauthenticated RCE chain	P	Partial: see card
7	FortiMail path traversal	S	Hub only
8	Cisco Secure Email Gateway path traversal	S	Hub only
9	BeyondTrust Remote Support authentication bypass	S	Hub only
10	PAN-OS management interface code injection	S	Hub only
11	Arista VeloCloud Orchestrator SQL injection	S	Hub only
12	AhsayCBS authentication bypass and command injection	S	Hub only
13	Adobe Commerce / Magento unrestricted file upload	P	Partial: see card
14	Citrix NetScaler ADC / Gateway memory issues	S	Hub only
15	Fragnesia: Linux kernel missing initialisation	V	Independent sources and/or vendor release notes
16	Microsoft Outlook Reading Pane RCEs	S	Hub only
17	Windows DHCP Server critical RCEs	P	Partial: see card
18	Microsoft QUIC critical RCEs	P	Partial: see card
19	Oracle E-Business Suite unauthenticated takeover	S	Hub only
20	Collabora Online / CODE server command injection	S	Hub only
21	Fortinet multi-product path traversal	S	Hub only
22	Cisco Secure Firewall ASA / FTD NULL pointer dereference	S	Hub only
23	Atlassian Data Center arbitrary file access	S	Hub only
24	Veeam Backup & Replication access-check bypass	S	Hub only
25	Azure Kubernetes Configuration Service authentication bypass	S	Hub only
26	HashiCorp Consul on Kubernetes cross-namespace ACL bypass	S	Hub only
27	GitLab additional critical regex / CI RCE	P	Partial: see card
28	VMware ESX insufficient logging	S	Hub only
29	Siemens Software Center uncontrolled search path	S	Hub only
30	SiteGuard Server Edition OS command injection	S	Hub only
31	Zammad session fixation and improper privilege management	S	Hub only
32	ONLYOFFICE Docs Server path traversal (historical)	S	Hub only
33	ProFTPD / ISC BIND / Apache Struts / Strapi older KEV additi	P	Partial: see card
34	Cisco Catalyst SD-WAN Manager unauthenticated admin API acce	S	Hub only

#	Hub entry	Status	Key support
35	FortiSIEM path traversal / code execution	S	Hub only
36	NGINX heap overflow / use-after-free	S	Hub only
37	Adobe Campaign Classic code execution	S	Hub only
38	MLflow code execution via writable scorer package	S	Hub only
39	Wasmtime sandbox escape on AArch64	S	Hub only
40	Chrome sandbox escape / RCE candidate	S	Hub only
41	Microsoft Excel / Office critical RCE cluster	P	Partial: see card
42	SharePoint deserialization RCE	S	Hub only
43	.NET Framework security feature bypass (WDAC)	V	Independent sources and/or vendor release notes
44	Remote Desktop Gateway / Message Queuing / RMCAST critical R	P	Partial: see card
45	Microsoft Partner Center certificate validation bypass	S	Hub only
46	Ivanti additional Connect Secure related issues	S	Hub only
47	Cisco Expressway root command execution	S	Hub only
48	Oracle October Critical Patch Update additional entries	S	Hub only
49	Google Cloud MCP Toolbox file / path issues	S	Hub only
50	Additional Fortinet / Cisco / Arista high-severity items	S	Hub only

Appendix J: Official Advisories and References

- SOCRadar: October 2026 Patch Tuesday, 1,413 flaws, 3 zero-days: socradar.io/blog/october-2026-patch-tuesday-zero-day/
- BleepingComputer: Microsoft October 2026 Patch Tuesday: www.bleepingcomputer.com/news/microsoft/microsoft-october-2026-patch-t
- CrowdStrike: Patch Tuesday analysis, October 2026: www.crowdstrike.com/en-us/blog/patch-tuesday-analysis-october-2026/
- Splashtop: Patch Tuesday October 2026: www.splashtop.com/blog/patch-tuesday-october-2026
- Infosecurity Magazine: Patch Tuesday record 1,400+ CVEs: www.infosecurity-magazine.com/news/microsoft-patch-tuesday-record-1/
- Penligent: Patch Tuesday October 2026: www.penligent.ai/hackinglabs/?p=7758
- Help Net Security: Binance $6.3 billion theft: www.helpnetsecurity.com/2026/10/30/binance-crypto-hack/
- SOCRadar: Binance hack, inside the $6.3B theft: socradar.io/blog/binance-hack-6-3b-hot-wallet-theft/
- Crypto Valley Journal: Inside the Binance hack: cryptovalleyjournal.com/hot-topics/news/inside-the-binance-hack-how-th
- CoinGape: attribution to TraderTraitor: coingape.com/binance-hack-update-chainalysis-trm-labs-others-blame-nor
- BleepingComputer: CISA confirms PHP2Shell exploited: www.bleepingcomputer.com/news/security/cisa-confirms-php2shell-vulnera
- The Register: CISA confirms PHP2Shell under attack: www.theregister.com/a/5305681
- Security Affairs: CISA adds PHP2Shell to KEV: securityaffairs.com/?p=201840
- BleepingComputer: CISA warns of Fragnesia: www.bleepingcomputer.com/news/security/cisa-warns-of-fragnesia-linux-f

- Help Net Security: GitLab CVE-2026-97229: www.helpnetsecurity.com/2026/10/13/gitlab-ci-cd-regular-expression-com
- BleepingComputer: GitLab max-severity regex flaw: www.bleepingcomputer.com/news/security/gitlab-warns-of-max-severity-rc
- IT-Connect: GitLab CVE-2026-97229: www.it-connect.tech/gitlab-patches-critical-unauthenticated-rce-flaw-i
- CISA KEV catalog: www.cisa.gov/known-exploited-vulnerabilities-catalog
- NIST National Vulnerability Database: nvd.nist.gov/
- Microsoft Security Response Center update guide: msrc.microsoft.com/update-guide
- MITRE CWE: cwe.mitre.org/
- GitLab patch release 19.5.1: docs.gitlab.com/releases/patches/patch-release-gitlab-19-5-1-released
- Railway security disclosure, 21 October: blog.railway.com/p/security-disclosure-wednesday-october-21st

Secondary compilation: Kavis Network, October 2026 Global Cybersecurity Incident Report (24 Oct 2026; secondary compilation, 1-23 Oct).

Appendix K: Unresolved and Unverified Claims

#	Claim	Finding
1	75 Critical as an October statistic	Microsoft-only (CrowdStrike); other counts 70-85.
2	Binance 'insider-enabled'	Not supported by retrieved sources; the compromised-laptop entry point is called unproven by one analysis.
3	GitLab **CVE-2026-97229** vs **CVE-2026-110264**	Resolved in this edition as two separate flaws with different fix dates; confirm in GitLab advisories. KEV status of 97229 remains disputed.
4	PHP2Shell CVSS 9.2-9.8	9.2 (v4.0) in retrieved sources.
5	Entry 2 naming (Node2Shell / HTTP2Shell)	One source calls it 'Broccoli2Shell'; CVSS 9.8 and product list unverified.
6	Entry 28 VMware 'insufficient logging' in KEV	Unusual for KEV; unverified.
7	Entries 21 and 32 older CVE IDs	Treat as historical, not October disclosures.
8	ConnectWise 'nearly 1,000 tenants' vs Microsoft '2,250+ tenants targeted'	Different measures; not reconciled.
9	Incidents 2, 3, 4, 10, 12, 14	Original hub only; not found in retrieved sources.
10	MLflow **CVE-2026-116692** and Google Cloud MCP Toolbox **CVE-2026-93328**	Original hub only; no official record retrieved.
11	CVSS vectors, CWE values and affected versions for most hub entries	NVD and vendor advisories not queried record by record.
12	Discoverers and root causes for most hub entries	Not established; no filler written.
13	Page-count target of 160 or more	Not met; reason in the opening note.