

# eBihr: Catalogs Content

## 1. Introduction

This document describes the content of all Catalogs provided by eBihr APIs.

The “Structure” section will display a sample of the XML document. The JSON structure is identical. Some differences appear with CSV documents as they can’t represent tree structure easily:

- Categories in references catalogs are represented as flattened path from main to (->) specific level
- Attributes names are only available in the user language

The “Field description” section will describe each attribute.

*Remark: catalogs RiderGear (new in v2.1) and HardPart (new in v2.1) do not contain the entire list of available products in Bihr but only the area they represent. You need to get both of them to have the entire Bihr catalog.*

## 2. References Catalog

### 2.1. Structure

```
<catalog version="1.1.6055" generated="2016-07-20 15:10:58">
    <categories>
        <category code="A" description="DIVERS">
            (<category code="A1" description="VARIÉS")?
                <products>
                    <product productId="0040038"
                        newPartNumber="1234567"
                        barCode="0040038"
                        commodityCode="3926909790"
                        discountClass="C"
                        furtherDescription=""
                        height="0"
                        publicPriceHT="99,999999"
                        publicPriceTTC="99,99"
                        endOfLifeProduct="true"
                        isPartialShippingAllowed="true"
                        isRemainingOnBackorderAllowed="true"
                        length="0"
                        longDescription_1=""
                        longDescription_2=""
                        longDescription_3=""
                        salesMultiple="1"
                        shortDescription_1="MINI MONTRE MOTO"
                        shortDescription_2="ALERTE GEL"
                        shortDescription_3="TEMP. AMBIANTE"
                        volume="0"
                        weight="0"
                        width="0"
                        brand-id="152">
                        </product>
                    <!-- multiple lines -->
                </products>
            </category>
            <!-- multiple lines -->?
        </category>
        <!-- multiple lines -->
    </categories>
</catalog>
```

Remark: There can be sub-category and sub-sub-category levels in the hierarchy.

## 2.2. Fields description

Catalog Node

Attribute	Type	Description	Example
<b>Version</b>	String	Version of the Catalog	1.1.6055
<b>Generated</b>	DateTime	When the catalog was generated	2016-07-20 14:10:58

Category Node

Attribute	Type	Description	Example
<b>Code</b>	String	Category Code	AAA
<b>Description</b>	String	Category Description	DIVERS

Product Node

Attribute	Type	Description	Example
<b>ProductId</b>	String	Product Code	0040038
<b>NewPartNumber</b>	String	New Part Number	1234567
<b>BarCode</b>	String	Bar Code	0040038
<b>CommodityCode</b>	String	Commodity Code	3926909790
<b>DiscountClass</b>	String	Discount Code	C
<b>FurtherDescription</b>	String	Description	
<b>PublicPriceHT</b>	Decimal	Public Price excluding VAT	96,583333
<b>PublicPriceTTC</b>	Decimal	Public Price including VAT	115,90
<b>EndOfLifeProduct</b>	Boolean	If will soon be unavailable	false
<b>IsPartialShippingAllowed</b>	Boolean	If partial shipping is allowed	true
<b>IsRemainingOnBackOrderAllowed</b>	Boolean	If allowed for Back Order	true
<b>LongDescription1</b>	String	Long description 1	
<b>LongDescription2</b>	String	Long description 2	
<b>LongDescription3</b>	String	Long description 3	
<b>ShortDescription1</b>	String	Short Description 1	
<b>ShortDescription2</b>	String	Short Description 2	
<b>ShortDescription3</b>	String	Short Description 3	
<b>SalesMultiple</b>	Int	Number of units in one package	1
<b>Height</b>	Int	Height in mm	47
<b>Length</b>	Int	Length in mm	189
<b>Width</b>	Int	Width in mm	129
<b>Volume</b>	Int	Volume in cm <sup>3</sup>	1146
<b>Weight</b>	Int	Weight in g	0
<b>Brand-id</b>	Int	Brand Id	152

### 3. Extended References Catalog

#### 3.1. Structure

```
<catalog version="1.1.6055" generated="2016-07-20 15:10:58">
    <brands>
        <brand id="1" name="BIHR"/>
        <!-- multiple lines -->
    </brands>
    <categories>
        <category code="A" description="DIVERS">
            (<category code="A1" description="VARIÉS">)??
                <products>
                    <product productId="0040038"
                        newPartNumber = "1234567"
                        barCode="0040038"
                        commodityCode="3926909790"
                        discountClass="C"
                        furtherDescription=""
                        height="0"
                        publicPriceHT="99,99999"
                        publicPriceTTC="99,99"
                        endOfLifeProduct="true"
                        isPartialShippingAllowed="true"
                        isRemainingOnBackOrderAllowed="true"
                        length="0"
                        longDescription_1=""
                        longDescription_2=""
                        longDescription_3=""
                        salesMultiple="1"
                        shortDescription_1="MINI MONTRE MOTO"
                        shortDescription_2="ALERTE GEL"
                        shortDescription_3="TEMP. AMBIANTE"
                        volume="0"
                        weight="0"
                        width="0"
                        brand-id="152">
                        <title>
                            <text lang="en"></text>
                            <!-- multiple lines -->
                        </title>
                        <description>
                            <text lang="en"></text>
                            <!-- multiple lines -->
                        </description>
                    </product>
                    <!-- multiple lines -->
                </products>
            (</category>
            <!-- multiple lines -->)??
        </category>
    </categories>
</catalog>
```

Remark: There can be sub-category and sub-sub-category levels in the hierarchy.

### 3.2. Fields description

Catalog Node

Attribute	Type	Description	Example
<b>Version</b>	String	Version of the Catalog	1.1.6055
<b>Generated</b>	DateTime	When the catalog was generated	2016-07-20 14:10:58

Brand Node

Attribute	Type	Description	Example
<b>Id</b>	Int	Brand Id	1
<b>Name</b>	String	Brand Name	Bihr

Category Node

Attribute	Type	Description	Example
<b>Code</b>	String	Category Code	AAA
<b>Description</b>	String	Category Description	DIVERS

Remark: Extended References Catalog is split by Product hierarchy. One file for each main level.

Code	Name
<b>A</b>	RIDER GEAR
<b>B</b>	VEHICLE PARTS & ACCESSORIES
<b>C</b>	LIQUIDS & LUBRICANTS
<b>D</b>	TIRES & ACCESSORIES
<b>E</b>	TOOLING & WS
<b>G</b>	OTHER PRODUCTS & SERVICES

Product Node

Attribute	Type	Description	Example
<b>ProductId</b>	String	Product Code	0040038
<b>NewPartNumber</b>	String	New Part Number	1234567
<b>BarCode</b>	String	Bar Code String	0040038
<b>CommodityCode</b>	String	Commodity Code	3926909790
<b>DiscountClass</b>	String	Discount Code	C
<b>FurtherDescription</b>	String	Web Description	
<b>PublicPriceHT</b>	Decimal	Public Price excluding VAT	96,583333
<b>PublicPriceTTC</b>	Decimal	Public Price including VAT	115,90
<b>EndOfLifeProduct</b>	Boolean	If will soon be unavailable	false
<b>IsPartialShippingAllowed</b>	Boolean	If partial shipping is allowed	true
<b>IsRemainingOnBackOrderAllowed</b>	Boolean	If allowed for Back Order	true
<b>LongDescription1</b>	String	Long description 1	
<b>LongDescription2</b>	String	Long description 2	
<b>LongDescription3</b>	String	Long description 3	
<b>ShortDescription1</b>	String	Short Description 1	
<b>ShortDescription2</b>	String	Short Description 2	
<b>ShortDescription3</b>	String	Short Description 3	
<b>SalesMultiple</b>	Int	Number of units in one package	1

<b>Height</b>	Int	Height in mm	47
<b>Length</b>	Int	Length in mm	189
<b>Width</b>	Int	Width in mm	129
<b>Volume</b>	Int	Volume in cm <sup>3</sup>	1146
<b>Weight</b>	Int	Weight in g	0
<b>Band-id</b>	Int	Brand Id	152

## 4. Prices Catalog

### 4.1. Structure

```
<catalog version="1.1.6055" generated="2016-07-20 15:10:58">
  <prices>
    <price productId="0040038" newPartNumber="1234567"
      dealerPriceHT="99,99999"/>
    <!-- multiple lines -->
  </prices>
</catalog>
```

### 4.2. Fields description

Catalog Node

Attribute	Type	Description	Example
<b>Version</b>	String	Version of the Catalog	1.1.6055
<b>Generated</b>	DateTime	When the catalog was generated	2016-07-20 14:10:58

Price Node

Attribute	Type	Description	Example
<b>ProductId</b>	String	Product Code	0040038
<b>NewPartNumber</b>	String	New Part Number	1234567
<b>DealerPriceHT</b>	Decimal	Dealer Price excluding VAT	96,583333

## 5. Images Catalog

### 5.1. Structure

```
<catalog version="1.1.6055" generated="2016-07-20 15:10:58">
    <products valid-until="2016-10-20 15:10:58">
        <product productId="0040038" newPartNumber="1234567"
            defaultDocumentId="ab/123456789" isDefault="true"/>
        <!-- multiple lines -->
    </products>
</catalog>
```

### 5.2. Fields description

#### Catalog Node

Attribute	Type	Description	Example
<b>Version</b>	String	Version of the Catalog	1.1.6055
<b>Generated</b>	DateTime	When the catalog was generated	2016-07-20 14:10:58

#### Products Node

Attribute	Type	Description	Example
<b>Valid-until</b>	DateTime	When the Images URLs expire	2016-10-20 14:10:58

#### Product Node

Attribute	Type	Description	Example
<b>ProductId</b>	String	Product Code	0040038
<b>NewPartNumber</b>	String	New Part Number	1234567
<b>DefaultDocumentId</b>	String	URL FileName*	ab/123456789
<b>IsDefault</b>	Boolean	If it is the product's default image	false

\* URL FileName must be prefixed with the Root URL provided by the ProductRootUrl REST API.

## 6. Attributes Catalog

### 6.1. Structure

```
<catalog generated="2016-07-20 15:10:58">
  <products>
    <product productId="0040038" newPartNumber="1234567">
      <attributes>
        <attribute id="1" value="front">
          <!-- multiple lines -->
        </attribute>
      </attributes>
    </product>
    <!-- multiple lines -->
  </products>
  <attributes>
    <attribute id="1">
      <text Lang="en">Attribute Name</text>
      <!-- multiple lines -->
    </attribute>
    <!-- multiple lines -->
  </attributes>
</catalog>
```

### 6.2. Fields description

#### Catalog Node

Attribute	Type	Description	Example
Generated	DateTime	When the catalog was generated	2016-07-20 14:10:58

#### Product Node

Attribute	Type	Description	Example
ProductId	String	Product Code	0040038
NewPartNumber	String	New Part Number	1234567

#### Attribute Node

Attribute	Type	Description	Example
Id	Int	Attribute Id	1
Value	String	Attribute Value	Front

## 7. Inventory Catalog

### 7.1. Structure

```
<catalog generated="2016-07-20 15:10:58">
  <products>
    <product productId="0040038"
      newPartNumber="1234567"
      stockLevel="20"
      stockLevelDescription="InStock"/>
    <!-- multiple lines -->
  </products>
</catalog>
```

### 7.2. Fields description

Catalog Node

Attribute	Type	Description	Example
<b>Generated</b>	DateTime	When the catalog was generated	2016-07-20 14:10:58

Product Node

Attribute	Type	Description	Example
<b>ProductId</b>	String	Product Code	0040038
<b>NewPartNumber</b>	String	New Part Number	1234567
<b>StockLevel</b>	Int	Stock Level Code (0, 10 or 20)	20
<b>StockLevelDescription</b>	String	OutOfStock, Short or InStock	InStock

## 8. RiderGear catalog (New in v2.1)

### 8.1. Structure

```
<catalog generated="2020-03-11 11:56:36">
  <products>
    <product productCode="433501XL"
      newPartNumber="1234567"
      supplierProductCode="HE008FFXL"
      brand="UFO"
      commodityCode="3926909790"
      mainCategory="Helmet"
      productName="SHOCK ORANGE HELMET XL"
      size="XL"
      color="Multi"
      collection="2020"
      designation="Casque UFO Warrior Shock orange T.XL"
      weight="1743"
      retailPriceIncludingTax="318,90"
      retailPriceExcludingTax="265,75"
      baseDealerPriceExcludingTax="93,01"
      barCode="433501XL"
      salesMultiple="1"
      stockValue="2"
      stockLevel="Short"
      defaultPicture="https://static-
        qual.bihr.net/v2/xlarge/34/3486c433dbe24591a303dfc24efd15e7.jpg"/>
    <!-- multiple lines -->
  </products>
</catalog>
```

## 8.2. Fields description

### Catalog Node

Attribute	Type	Description	Example
<b>Generated</b>	DateTime	When the catalog was generated	2020-03-11 11:56:36

### Product Node

Attribute	Type	Description	Example
<b>ProductCode</b>	String	Product code	433501XL
<b>NewPartNumber</b>	String	New Part Number	1234567
<b>SupplierProductCode</b>	String	Supplier product code	HE008FFXL
<b>Brand</b>	String	Brand name	UFO
<b>CommodityCode</b>	String	Commodity Code	3926909790
<b>MainCategory</b>	String	Main category	Helmet
<b>ProductName</b>	String	Product name	
<b>Size</b>	String	Size	XL
<b>Color</b>	String	Color	Multi
<b>Collection</b>	String	Collection	2020
<b>Designation</b>	String	Detailed description	
<b>Weight</b>	Int	Weight in g	1743
<b>RetailPriceIncludingTax</b>	Decimal	Public price including VAT	318,90
<b>RetailPriceExcludingTax</b>	Decimal	Public price excluding VAT	265,75
<b>BaseDealerPriceExcludingTax</b>	Decimal	Dealer price excluding VAT without discount	93,01
<b>BarCode</b>	String	Bar code	433501XL
<b>SalesMultiple</b>	Int	Number of units in one package	1
<b>StockLevel</b>	String	OutOfStock, Short or InStock	Short
<b>StockValue</b>	Int	The stock at the beginning of the day	2
<b>DefaultPicture</b>	String	URL of the default picture	

## 9. HardPart catalog (New in v2.1)

### 9.1. Structure

```
<catalog generated="2020-03-11 11:56:36">
  <products>
    <product productCode="010046"
      newPartNumber="1234567"
      supplierProductCode="ESG432"
      brand="ELECTROSPORT"
      commodityCode="3926909790"
      mainCategory="Electrical"
      productName="STATOR YAMAHA"
      designation="ELECTROSPORT Stator Yamaha YFM350 Big Bear/YFM350X
      Warrior"
      weight="987"
      retailPriceIncludingTax="219,00"
      retailPriceExcludingTax="182,50"
      baseDealerPriceExcludingTax="118,63"
      barCode="ESG432"
      salesMultiple="1"
      stockValue="2"
      stockLevel="Short"
      defaultPicture="https://static-
      qual.bihr.net/v2/xlarge/93/93052d8c7db94caa9f20ccc48251eedc.jpg"/>
    <!-- multiple lines -->
  </products>
</catalog>
```

## 9.2. Fields description

Catalog Node

Attribute	Type	Description	Example
<b>Generated</b>	DateTime	When the catalog was generated	2020-03-11 11:56:36

Product Node

Attribute	Type	Description	Example
<b>ProductCode</b>	String	Product code	010046
<b>NewPartNumber</b>	String	New Part Number	1234567
<b>SupplierProductCode</b>	String	Supplier product code	ESG432
<b>Brand</b>	String	Brand name	ELECTROSPORT
<b>CommodityCode</b>	String	Commodity Code	3926909790
<b>MainCategory</b>	String	Main category	Electrical
<b>ProductName</b>	String	Product name	STATOR YAMAHA
<b>Designation</b>	String	Detailed description	
<b>Weight</b>	Int	Weight in g	987
<b>RetailPriceIncludingTax</b>	Decimal	Public price including VAT	219,00
<b>RetailPriceExcludingTax</b>	Decimal	Public price excluding VAT	182,50
<b>BaseDealerPriceExcludingTax</b>	Decimal	Dealer price excluding VAT without discount	118,63
<b>BarCode</b>	String	Bar code	ESG432
<b>SalesMultiple</b>	Int	Number of units in one package	1
<b>StockLevel</b>	String	OutOfStock, Short or InStock	Short
<b>StockValue</b>	Int	The stock at the beginning of the day	2
<b>DefaultPicture</b>	String	URL of the default picture	

## 10. Extended catalog

This file exists **only in zipped CSV** format and is generated **only once per week**.

Remark: Extended Catalog is **split by Brand**.

### 10.1. Fields description

Product Line

Attribute	Type	Description
<b>PartNumber</b>	String	Part Number
<b>OldPartNumber</b>	String	Part Number in old Bihr systems
<b>SupplierProductCode</b>	String	Part Number from the supplier
<b>Brand</b>	String	Brand name
<b>ProductName</b>	String	Product's raw description
<b>Designation</b>	String	Translated product's description from the website
<b>RetailPriceIncludingTax</b>	Decimal	Public price including VAT
<b>RetailPriceExcludingTax</b>	Decimal	Public price excluding VAT
<b>BaseDealerPriceExcludingTax</b>	Decimal	Dealer price excluding VAT without discount
<b>BarCode</b>	String	Bar code
<b>StockValue</b>	Integer	Weekly-refreshed stock value
<b>CommodityCode</b>	String	Commodity code for customs
<b>OnDemand</b>	Integer	1 when the Product is on demand, 0 otherwise
<b>DropShipping</b>	Integer	1 when the Product can be drop-shipped, 0 otherwise
<b>HtmlDescription</b>	String	HTML description from the website
<b>Description</b>	String	Description from the website without HTML tag
<b>Category1</b>	String	Merchandise Category Hierarchy's highest level
<b>Category2</b>	String	Merchandise Category Hierarchy's medium level
<b>Category3</b>	String	Merchandise Category Hierarchy's lowest level
<b>V- Attribute 1</b>	String	Variance attribute's name prefixed with a "V-"
...		
<b>V- Attribute N</b>	String	
<b>Volume (cm<sup>3</sup>)</b>	Integer	Volume in cubic centimeters
<b>Weight (g)</b>	Integer	Weight in grams
<b>Length (mm)</b>	Integer	Length in millimeters
<b>Width (mm)</b>	Integer	Width in millimeters
<b>Height (mm)</b>	Integer	Height in millimeters
<b>Attribute 1</b>	String	Attribute's name
...		...
<b>Attribute N</b>	String	
<b>Picture1</b>	String	Picture links in columns
...		
<b>Picture10</b>	String	
<b>AllPicturesZIP</b>	String	A link to a ZIP file with all the pictures

<b>Document1</b>	String	Document links in column
...		
<b>Documents5</b>		