


Lecture 8 – Effective network inference

Dr. Joseph Lizier



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of the **University of Sydney** pursuant to Part VB of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.


Do not remove this notice

Effective network inference: session outcomes

- Understand different options for network inference from time-series data, complexities and subtleties involved in effective network inference.
- Able to use JIDT for simple effective network inference (pairwise)
- Understand advantages of more advanced techniques in the IDTxI toolkit
- Primary references:
 - Bossomaier, Barnett, Harré, Lizier, "An Introduction to Transfer Entropy: Information Flow in Complex Systems", Springer, Cham, 2016; section 7.2

Network inference

- Key question: *given only time series for each of a set of variables, can we describe a network which represents the relationships between these variables?*




Options:

1. Functional networks
2. Effective networks
3. Structural networks

Complex system as a **multivariate time-series** of states

Effective network inference

- Hybrid approach between structural and functional
- Seeks to infer **directed** relationships and “*minimal neuronal circuit model*” which can replicate and indeed explain the time series of the nodes



Not structural (causal) but:


- May be best that can be done with data. (Causality often impossible)
- Reflect dynamic **changes in regime** of the system.
- Model the **computation** taking place in the system, revealing **emergent structure**.

What can we use effective network inference for?

- Infer underlying information network for the system
- Examine how network changes over time
- Examine how network changes with condition

- Application areas:

- Neuroimaging
- Financial market data sets
- Gene regulatory networks
- Social media analysis
- Sport analytics
- ...




J. T. Lizier, J. Heinzle, A. Horstmann, J.-D. Haynes, and M. Prokopenko.. *Journal of Computational Neuroscience*, 30(1):85–107, 2011

O. M. Cliff, J. T. Lizier, X. R. Wang, P. Wang, O. Obst, and M. Prokopenko. In S. Behnke, M. Veloso, A. Visser, and R. Xiong, editors, *RoboCup 2013: Robot World Cup XVII*, volume 8371 of *Lecture Notes in Computer Science*, pages 1–12. Springer, Berlin/Heidelberg, 2014

Effective network inference

- Hybrid approach between structural and functional
- Seeks to infer **directed** relationships and “*minimal neuronal circuit model*” which can replicate and indeed explain the time series of the nodes



Not structural (causal) but:

- May be best that can be done with data. (Causality often impossible)
- Reflect dynamic **changes in regime** of the system.
- Model the **computation** taking place in the system, revealing **emergent structure**.

Transfer entropy is a natural fit!

TE for effective network inference: basic approach



1. Measure **pairwise TE** between all pairs of variables in the system;
 2. **Threshold** the TE values to select connections for the network
- Let's try this in JIDT
 - What is the first problem we encounter?

TE for effective network inference: standard approach

1. Measure **pairwise TE** between all pairs of variables in the system;
 2. For each source-target pair, obtain the **p-value** for measuring the observed TE under the null distribution; (see lec. 5)
 3. **Threshold the p-values** to select connections for the network.
- More principled approach: threshold is statistically derived, robust, suitable for small data sets.
 - Let's try this in JIDT

Notes on standard approach

1. Need to correct for **multiple comparisons** using either:
 - family-wise error rates
 - e.g. Bonferroni correction \rightarrow drop threshold α by a factor of M , where M is the number of tests we make. Normally $M=G.(G-1)$ for network of size G , which gives a very small threshold!
 - false discovery rates.
2. Need to properly set **TE parameters**, else can get false positives/negatives:
 - Set embeddings;
 - Set source-target delay
3. Does not handle **redundancies or synergies** between sources.




M. Wibral, R. Vicente, and M. Lindner. "Transfer entropy in neuroscience". In M. Wibral, R. Vicente, and J. T. Lizier, editors, *Directed Information Measures in Neuroscience*, pp. 3–36. Springer, Berlin/Heidelberg, 2014.

Bossomaier, Barnett, Harré, Lizier, "An Introduction to Transfer Entropy: Information Flow in Complex Systems", Springer, Cham, 2016; section 7.2

Effective network inference beyond pairwise TE

- What could we do to address redundancy and synergy?
- Recall that conditional TE does this
 - But what to condition on ...?

Recall: Information regression/model



- **Modelling** the information processing in X .
- Consider two sources to X . (General case in Lizier 2010):

Real goal here: to infer this **parent set** $\{Y, Z\}$ for X

$$H(X_{n+1}) = I(\mathbf{X}_n^{(k)}; X_{n+1}) + I(Y_n, Z_n; X_{n+1} | \mathbf{X}_n^{(k)}) + H(X_{n+1} | \mathbf{X}_n^{(k)}, Y_n, Z_n)$$

$$H(X_{n+1}) = I(\mathbf{X}_n^{(k)}; X_{n+1}) + I(Y_n; X_{n+1} | \mathbf{X}_n^{(k)}) + I(Z_n; X_{n+1} | \mathbf{X}_n^{(k)}, Y_n) + H(X_{n+1} | \mathbf{X}_n^{(k)}, Y_n, Z_n)$$

$$H(X_{n+1}) = I(\mathbf{X}_n^{(k)}; X_{n+1}) + I(Z_n; X_{n+1} | \mathbf{X}_n^{(k)}) + I(Y_n; X_{n+1} | \mathbf{X}_n^{(k)}, Z_n) + H(X_{n+1} | \mathbf{X}_n^{(k)}, Y_n, Z_n)$$

1. Active information storage

2-. Collective transfer entropy


2. Pairwise/apparent transfer entropy

3+. Conditional transfer entropy

J. T. Lizier, M. Prokopenko, & A. Y. Zomaya. "Local information transfer as a spatiotemporal filter for complex systems". Physical Review E, 77(2):026110, 2008.

J. T. Lizier, M. Prokopenko, & A. Y. Zomaya. "Information modification and particle collisions in distributed computation", Chaos, 20(3), 037109, 2010.

Iterative/greedy approaches



- Consider two sources to X . (General case in Lizier 2010):

Real goal: to infer this **parent set** $\{Y, Z\}$ for X

$$H(X_{n+1}) = I(\mathbf{X}_n^{(k)}; X_{n+1}) + I(Y_n, Z_n; X_{n+1} | \mathbf{X}_n^{(k)}) + H(X_{n+1} | \mathbf{X}_n^{(k)}, Y_n, Z_n)$$


- Inferring whole parent set at once is combinatorially difficult.
- Instead, infer parents one by one in a **greedy** fashion:
 1. Evaluate TE from each source to target, **conditioning on previously selected sources**.
 2. Add the source with max conditional TE if p-value is statistically significant.
 3. Go back to step 1 if a new parent was added, else terminate.

$$H(X_{n+1}) = I(\mathbf{X}_n^{(k)}; X_{n+1}) + I(Y_n; X_{n+1} | \mathbf{X}_n^{(k)}) + I(Z_n; X_{n+1} | \mathbf{X}_n^{(k)}, Y_n) + H(X_{n+1} | \mathbf{X}_n^{(k)}, Y_n, Z_n)$$

J. T. Lizier and M. Rubinov. "Multivariate construction of effective computational networks from observational data". Technical Report Preprint 25/2012, Max Planck Institute for Mathematics in the Sciences, 2012.

Bossomaier, Barnett, Harré, Lizier, "An Introduction to Transfer Entropy: Information Flow in Complex Systems", Springer, Cham, 2016; section 7.2

Iterative/greedy approaches



- Instead, infer parents one by one in a **greedy** fashion:
 1. Evaluate TE from each source to target, conditioning on previously selected sources.
 2. Add the source with max TE if p-value is statistically significant.
 3. Go back to step 1 if a new parent was added, else terminate.

$$H(X_{n+1}) = I\left(\mathbf{X}_n^{(k)}; X_{n+1}\right) + I\left(Y_n; X_{n+1} \mid \mathbf{X}_n^{(k)}\right) + I\left(Z_n; X_{n+1} \mid \mathbf{X}_n^{(k)}, Y_n\right) + H\left(X_{n+1} \mid \mathbf{X}_n^{(k)}, Y_n, Z_n\right)$$

Notes:

- More **efficient** than brute force search for parent set.
- Handles **redundancies** and **synergies** between parents.
- Statistical tests provide “**automatic brake**” when statistical power of data is exhausted
- End result is the **parent set**. Order that nodes were inferred in is no longer relevant.

Using iterative/greedy approaches

- IDTxI (which uses JIDT as an internal information-theoretic engine) implements the greedy algorithm, including:
 - “Max statistics” for parent selection (more rigorous, yet not as harsh as Bonferroni);
 - Handles TE parameter selection, non-uniform embedding / delay selection of sources.
 - Adds additional steps (pruning step) and statistical tests.

Information dynamics Part II: summary

- We've looked at different options for network inference from time-series data, complexities and subtleties involved in effective network inference.
- Able to use JIDT for simple effective network inference (pairwise)
- Understand advantages of more advanced techniques in the IDTxl toolkit

Questions



THE UNIVERSITY OF
SYDNEY