


Lecture 2 – What is information?

Dr. Joseph Lizier



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of the **University of Sydney** pursuant to Part VB of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice

What is Information: session outcomes

- Ability to express ideas about information and relate that to uncertainty.
- Understand further fundamental measures of information theory including: entropy, joint entropy, conditional entropy, mutual information, conditional mutual information.
- Ability to partially construct Matlab code to compute such measures, and apply that code to examples.
- Primary references:
 - Cover and Thomas, "Elements of Information Theory", Hoboken, New Jersey: John Wiley and Sons, Inc., 2006 (2nd ed.); section 2.2-2.5, 2.6, 2.8
 - Mackay, "Information Theory, Inference, and Learning Algorithms", Cambridge: Cambridge University Press, 2003; sections 2.6, chapter 8.
 - Bossomaier, Barnett, Harré, Lizier, "An Introduction to Transfer Entropy: Information Flow in Complex Systems", Springer, Cham, 2016; section 3.2.1-3.2.4.
 - Lizier, "JIDT: An information-theoretic toolkit for studying the dynamics of complex systems", Frontiers in Robotics and AI, 1:11, 2014; Appendix A.1 and A.3

Joint Entropy

- We can consider **joint entropy** of a multivariate, e.g. $\{X, Y\}$:

$$H(X, Y) = \sum_{x \in A_x} \sum_{y \in A_y} p(x, y) \log_2 \frac{1}{p(x, y)}$$

$$H(X, Y) = \sum_{x \in A_x} \sum_{y \in A_y} -p(x, y) \log_2 p(x, y)$$

$$H(X, Y) = \langle h(x, y) \rangle$$

- Surprise $h(x, y)$ / Uncertainty $H(X, Y)$ for the joint sample $\{x, y\}$
- Same properties as for $H(X)$, only now X is multivariate!
- $H(X, Y) \geq H(X)$
- We refer to $H(X)$ or $H(Y)$ as *marginal* entropies to distinguish them
- Is $H(X, Y) = H(X) + H(Y)$?
 - Only for *independent* variables where $p(x, y) = p(x)p(y)$!

T. M. Cover and J. A. Thomas. Elements of Information Theory. Wiley-Interscience, New York, 1991. Section 2.2

D. J. C. MacKay. Information Theory, Inference, and Learning Algorithms. Cambridge University Press, Cambridge, 2003. Section 8.1

Joint Entropy

- We can consider **joint entropy** of a multivariate, e.g. $\{X, Y\}$:

$$H(X, Y) = \sum_{x \in A_x} \sum_{y \in A_y} p(x, y) \log_2 \frac{1}{p(x, y)}$$

$$H(X, Y) = \sum_{x \in A_x} \sum_{y \in A_y} -p(x, y) \log_2 p(x, y)$$

$$H(X, Y) = \langle h(x, y) \rangle$$

- **Exercise:** How to code $H(X, Y)$?

1. Edit the Matlab function `jointentropy(p)` to return the joint Shannon entropy for the joint probability p .
 - a. You can assume p is 2D ($p(x, y)$) for now.
 - b. Can you simply alter your `entropy(p)` code?
 - c. Try some test cases that you come up with yourself.
 - d. *Challenge:* try dropping the assumption that p is 2D. Does your code change?

Joint Entropy

- We can consider **joint entropy** of a multivariate, e.g. $\{X, Y\}$:

$$H(X, Y) = \sum_{x \in A_x} \sum_{y \in A_y} -p(x, y) \log_2 p(x, y)$$

- **Exercise:** Let's code it assuming we don't have $P(X, Y)$ given, but are given empirical data to compute $P(X, Y)$ from:
 1. Edit the Matlab function `jointentropyempirical(xn)` to return the Shannon entropy for the given samples x_n of X (n is sample index)
 - a. Input is x_n as a matrix of samples, where each row is a vector of samples of each variable (e.g. $[0, 1]$)
 - b. Trick: can we use our existing `entropyempirical()` by combining $\{x, y\}$ into a joint variable?

Aside: Shannon entropy – derivation

- **Shannon entropy** of a random variable X :

$$H(X) = \sum_{x \in A_x} -p(x) \log_2 p(x)$$

- Is a **unique** form that satisfies three axioms (Ash, 1965; Shannon, 1948):
 - **Continuity** w.r.t. $p(x)$
 - **Monotony** – $H(X) \uparrow$ as $|A_x| \uparrow$, for $p(x) = 1/|A_x|$
 - **Grouping** – For independent variables X and Y , $H(X, Y) = H(X) + H(Y)$

C. E. Shannon. A mathematical theory of communication. Bell System Technical Journal, 27(3–4):379–423, 623–656, 1948.

R. B. Ash. Information Theory. Dover Publications Inc., New York, 1965. p. 5-12.

Conditional entropy

- What if we already know something that may pertain to X ? Does this change our surprise/uncertainty?
- **Conditional entropy**: (average) surprise remaining about sample x of X if we already know the sample y of Y

$$H(X|y) = \sum_{x \in A_x} p(x|y) \log_2 \frac{1}{p(x|y)}$$


$$H(X|Y) = \sum_{y \in A_y} p(y) H(X|y)$$

$$H(X|Y) = \sum_{x \in A_x} \sum_{y \in A_y} p(x, y) \log_2 \frac{1}{p(x|y)}$$

$$H(X|Y) = H(X, Y) - H(Y)$$

$$h(x|y) = h(x, y) - h(y)$$

$$h(x|y) = -\log_2 p(x|y)$$



Venn
diagram

Properties:


- $0 \leq H(X|Y) \leq H(X)$
- $H(X|Y) = H(X)$ iff X and Y are independent
- $H(X|Y) = 0$ means there is no surprise left in X once we know Y .

Conditional entropy

- **Conditional entropy**: (average) surprise remaining about sample x of X if we already know the sample y of Y

$$h(x|y) = h(x, y) - h(y)$$

$$H(X|Y) = H(X, Y) - H(Y)$$



Venn diagram

Coding interpretation of $H(X|Y)$?

Example 1:


- Coding characters in English text – what variable Y would drop $H(X)$ to some $H(X|Y)$ and therefore the code length for a **conditional** encoding of incoming character X ?
- Context of previous character(s) Y changes the probability of the next character X – Markov chains

i	a_i	p_i	$h(p_i)$
1	a	.0575	4.1
2	b	.0128	6.3
3	c	.0263	5.2
4	d	.0285	5.1
5	e	.0913	3.5
6	f	.0173	5.9
7	g	.0133	6.2
8	h	.0313	5.0
9	i	.0599	4.1
10	j	.0006	10.7
11	k	.0084	6.9
12	l	.0335	4.9
13	m	.0235	5.4
14	n	.0596	4.1
15	o	.0689	3.9
16	p	.0192	5.7
17	q	.0008	10.3
18	r	.0508	4.3
19	s	.0567	4.1
20	t	.0706	3.8
21	u	.0334	4.9
22	v	.0069	7.2
23	w	.0119	6.4
24	x	.0073	7.1
25	y	.0164	5.9
26	z	.0007	10.4
27	-	.1928	2.4

$$\sum_i p_i \log_2 \frac{1}{p_i} \quad 4.1$$

Table 2.9. Shannon information contents of the outcomes a–z.

Conditional entropy



- **Conditional entropy:** (average) surprise remaining about sample x of X if we already know the sample y of Y


$$h(x|y) = h(x, y) - h(y)$$

$$H(X|Y) = H(X, Y) - H(Y)$$

- **Exercise:** Let's code it!

1. Edit the Matlab function `conditionalentropy(p)` to return the conditional entropy for X given Y for the joint probability p .
 - a. You can assume p is 2D ($p(x, y)$); this is the input.
 - b. Trick: can we use our existing `entropy()` and `jointentropy()`?
 - c. Test: `conditionalentropy([0.5, 0; 0, 0.5]) = 0`
 - d. Test: `conditionalentropy([0.25, 0.25; 0.25, 0.25]) = 1`
 - e. Guess Who? $H(\text{sex}|\text{earrings})$? Construct $p(\text{sex}, \text{earrings})$ first. Is $p(\text{earrings}|\text{sex})$ the same?

Conditional entropy



- **Conditional entropy:** (average) surprise remaining about sample x of X if we already know the sample y of Y

$$h(x|y) = h(x, y) - h(y)$$

$$H(X|Y) = H(X, Y) - H(Y)$$

- **Exercise:** Let's code it!

1. Edit the Matlab function

`conditionalentropyempirical(xn, yn)` to return the conditional entropy for X given Y from empirical samples x_n, y_n :

- Input is samples x_n, y_n .
- Trick: can we use our existing `entropyempirical()` and `jointentropyempirical()`?
- Test: `conditionalentropyempirical([0,0,1,1], [0,1,0,1]) = 1`
- Test: `conditionalentropyempirical([0,0,1,1], [0,0,1,1]) = 0`

Chain rule for entropy and information content

- Chain rule for entropy:
 - $H(X, Y) = H(X) + H(Y|X)$
 - $H(X, Y) = H(Y) + H(X|Y)$
 - $H(X_1, X_2, \dots, X_n) = \sum_{i=1}^n H(X_i|X_1 \dots X_{i-1})$
 - Same applies for $h(x, y)$, $H(X, Y|Z)$ and $h(x, y|z)$.

Cross entropy and Kullback-Leibler divergence

– Cross-entropy:

$$G(p||q) = \sum_{x \in A_x} p(x) \log_2 \frac{1}{q(x)}$$

- Average code length if using the PDF $q(x)$ to optimally encode x , which has actual PDF $p(x)$


– Kullback-Leibler (KL) divergence:

$$D(p||q) = \sum_{x \in A_x} p(x) \log_2 \frac{p(x)}{q(x)}$$

- Average coding penalty from using the PDF $q(x)$ to optimally encode x , which has actual PDF $p(x)$
- $D(p||q) \geq 0$ with equality iff $q=p$
 - You always incur a cost for using incorrect PDF!

Mutual information (MI)

- Mutual information $I(X;Y)$ is the **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y
- Interpretation 1: from Venn diagrams –



$$I(X;Y) = H(X) + H(Y) - H(X,Y)$$

$$I(X;Y) = H(X) - H(X|Y)$$

$$I(X;Y) = H(Y) - H(Y|X)$$


$$I(X;Y) = I(Y;X)$$

Properties:

- $0 \leq I(X;Y) \leq \min(H(X), H(Y))$
- Is symmetric in X and Y
- $I(X;Y) = H(X) \rightarrow H(X|Y) = 0$

Mutual information (MI)

- Mutual information $I(X;Y)$ is the **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y
- Interpretation 2: KL divergence / Bayesian view –



$$I(X; Y) = \sum_{x \in A_x, y \in A_y} p(x, y) \log_2 \frac{p(x, y)}{p(x)p(y)}$$

$$I(X; Y) = \sum_{x \in A_x, y \in A_y} p(x, y) \log_2 \frac{p(x|y)}{p(x)}$$


Properties:

- $I(X; Y) = D(p(x, y) || p(x)p(y))$
- MI is code length penalty for coding $\{x, y\}$ assuming x and y are independent, or for coding x without using knowledge of y .

Mutual information (MI)

- Mutual information $I(X;Y)$ is the **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y
- Interpretation 3: statistical view –

$$I(X;Y) = \sum_{x \in A_x, y \in A_y} p(x,y) \log_2 \frac{p(x|y)}{p(x)}$$



Properties:


- $I(X;Y) = 0 \Leftrightarrow X$ is independent of Y
- MI is a non-linear form of correlation

Mutual information (MI)

- Mutual information $I(X;Y)$ is the **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y
- Interpretation 4: self-information and uncertainty –

$$I(X; X) = H(X) + H(X) - H(X, X)$$

$$I(X; X) = H(X)$$



$H(X)$

$I(X;X)$

Properties:

- Entropy $H(X)$ (**uncertainty**) is equivalent to the self-information $I(X;X)$ (**uncertainty reduction**) obtained from that variable about itself.
- Entropy and information are complementary quantities!

Local or pointwise Mutual information

- Mutual information $i(x;y)$ is the **reduction in uncertainty** or surprise about one sample x of variable X that we obtain from one sample y of another variable Y

$$i(x; y) = h(x) + h(y) - h(x, y)$$

$$i(x; y) = h(x) - h(x|y)$$

$$i(x; y) = h(y) - h(y|x)$$

$$i(x; y) = \log_2 \frac{p(x|y)}{p(x)}$$

$$I(X; Y) = \langle i(x; y) \rangle$$

- $i(x;y) > 0$ means $p(x | y) > p(x)$, so y increased our expectation that x would occur, **positively informing** us.
- $i(x;y) < 0$ means $p(x | y) < p(x)$, so y reduced our expectation that x would occur, **misinforming** us.
 - e.g. when the weather report says 'sunshine' but it actually rains, we may have $p(\text{rain} | \text{sunny_forecast}) = 0.05$ whilst $p(\text{rain})=0.2$.
 - But: *on average* over all samples Y provides $I(X;Y) \geq 0$.

Local or pointwise Mutual information

- Mutual information $i(x;y)$ is the **reduction in uncertainty** or surprise about one sample x of variable X that we obtain from one sample y of another variable Y
- Interpretation 5: information comes from effect of *exclusions* –





Fig. 1. Probability mass diagrams, which use length to represent the probability mass of each joint event (x, y) (summing to 1 over all (x, y) of course). These illustrate: a. (left) starting from the joint distribution $P(X, Y)$; b. (middle) the occurrence of the event $Y = y_1$ leads to exclusions of $\bar{y}_1 = \{Y \setminus y_1\} = \{y_2, y_3\}$ to leave $P(X, y_1)$; c. (right) and the remaining space is then normalised into $P(X|y_1)$.

1. Learning the value $Y=y_1$ leads to exclusions in the joint space $P(X, y_1)$. The potential “value” of the exclusions is $h(y_1)$.
 2. Renormalise the probability space to get $P(X|y_1)$.
 3. Compare $P(x_1)$ and $P(x_1|y_1)$ for the event x_1 which occurred.
- Consider how exclusions in Guess Who provide information in this way ...

Mutual information (MI) – code



- The **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y


$$i(x; y) = h(x) + h(y) - h(x, y)$$

$$I(X; Y) = H(X) + H(Y) - H(X, Y)$$

- **Exercise:** Let's code it!

1. Edit the Matlab function `mutualinformation(p)` to return the MI between X and Y for the joint probability p .
 - a. You can assume p is 2D ($p(x, y)$); this is the input.
 - b. Trick: can we use our existing `entropy()` and `jointentropy()`?
 - c. Test: `mutualinformation([0.5, 0; 0, 0.5]) = 1`
 - d. Test: `mutualinformation([0.25, 0.25; 0.25, 0.25]) = 0`
 - e. Guess Who? $I(\text{sex}; \text{earrings})$? Construct $p(\text{sex}, \text{earrings})$ first. Why is there MI here?

Mutual information (MI) – code



- The **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y

$$i(x; y) = h(x) + h(y) - h(x, y)$$

$$I(X; Y) = H(X) + H(Y) - H(X, Y)$$

- **Exercise:** Let's code it!





1. Edit the Matlab function

`mutualinformationempirical(xn, yn)` to return the MI between X and Y from empirical samples x_n, y_n :

- a. Input is samples x_n, y_n .
- b. Trick: can we use our existing `jointentropyempirical()`?
- c. **Test:** `mutualinformationempirical([0,0,1,1], [0,1,0,1]) = 0`
- d. **Test:** `mutualinformationempirical([0,0,1,1], [0,0,1,1]) = 1`

Mutual information (MI)

- Is a great model-free tool to:
 - detect relationships between variables;
 - reveal patterns;
 - show how such relationships and patterns fluctuate in time.
- Example uses:
 - Feature selection in machine learning
 - Space-time characterisation of information processing in complex systems – lectures 4,5
 - Inferring relationships (i.e. networks) in multivariate time-series data (e.g. brain imaging) – lecture 6



J. T. Lizier. "Measuring the dynamics of information processing on a local scale in time and space". In M. Wibral, R. Vicente, and J. T. Lizier, editors, "Directed Information Measures in Neuroscience", Springer, Berlin/Heidelberg, 2014; pp. 161–193.

J. T. Lizier, J. Heinze, A. Horstmann, J.-D. Haynes, & M. Prokopenko. "Multivariate information-theoretic measures reveal directed information structure and task relevant changes in fMRI connectivity". J. Computational Neuroscience, 30 (1):85–107, 2011.

O.M. Cliff, J.T. Lizier, P. Wang, X.R. Wang, O. Obst, M. Prokopenko, "Quantifying Long-Range Interactions and Coherent Structure in Multi-Agent Dynamics", Artificial Life, vol. 23, no. 1, pp. 34-57, 2017.

Conditional mutual information (CMI)

- $I(X; Y | Z)$ is the **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y , **given** the value of another variable Z .

- Interpretation 1: in the **context** of Z –

$$I(X; Y | Z) = H(X | Z) + H(Y | Z) - H(X, Y | Z)$$

$$I(X; Y | Z) = H(X | Z) - H(X | Y, Z)$$

$$I(X; Y | Z) = H(Y | Z) - H(Y | X, Z)$$

$$I(X; Y | Z) = I(Y; X | Z)$$

$$I(X; Y | Z) = I(X; Y, Z) - I(X; Z) \leftarrow \text{Ok this one is new!}$$


All maths changes to be conditional on Z

Properties:

- $0 \leq I(X; Y | Z) \leq \min(H(X | Z), H(Y | Z))$
 - e.g. if Z explains X ($H(X | Z) = 0$), then $I(X; Y | Z) = 0$
- Is symmetric in X and Y
- $I(X; Y | Z) = H(X | Z) \rightarrow H(X | Y, Z) = 0$

Conditional mutual information (CMI)

- $I(X;Y|Z)$ is the **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y , given the value of another variable Z .
- Be warned against using Venn diagrams to interpret 3-term entropies!
 - Areas in the diagram add up correctly **but** the diagram gives the misleading impression that all areas are positive! (They aren't!)



- Mackay emphasises that there are no other well-defined “3-term entropies”

Conditional mutual information (CMI)

- $I(X; Y | Z)$ is the **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y , given the value of another variable Z .
- Interpretation 2: KL divergence / Bayesian view –

$$I(X; Y | Z) = \sum_{x \in A_x, y \in A_y, z \in A_z} p(x, y, z) \log_2 \frac{p(x, y | z)}{p(x | z)p(y | z)}$$

$$I(X; Y | Z) = \sum_{x \in A_x, y \in A_y, z \in A_z} p(x, y, z) \log_2 \frac{p(x | y, z)}{p(x | z)}$$

Properties:

- $I(X; Y | Z) = D(p(x, y | z) || p(x | z)p(y | z))$
- CMI is code length penalty for coding $\{x, y\}$ assuming x and y are conditionally independent (on z), or for coding x without using knowledge of y *in addition* to knowledge of z .

Conditional mutual information (CMI)

- $I(X; Y | Z)$ is the **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y , given the value of another variable Z .
- Interpretation 3: statistical view –

$$I(X; Y | Z) = \sum_{x \in A_x, y \in A_y, z \in A_z} p(x, y, z) \log_2 \frac{p(x | y, z)}{p(x | z)}$$

Properties:

- $I(X; Y | Z) = 0 \iff X$, conditional on Z , is independent of Y
- CMI is a non-linear form of partial correlation

Local or pointwise Conditional Mutual information

- $i(x;y|z)$ is the **reduction in uncertainty** or surprise about one sample x of variable X that we obtain from one sample y of another variable Y , given the sample z of another variable Z .

$$i(x;y|z) = h(x|z) + h(y|z) - h(x,y|z)$$

$$i(x;y|z) = h(x|z) - h(x|y,z)$$

$$i(x;y|z) = h(y|z) - h(y|x,z)$$

$$i(x;y|z) = \log_2 \frac{p(x|y,z)}{p(x|z)}$$

$$I(X;Y|Z) = \langle i(x;y|z) \rangle$$

- $i(x;y|z)$ may be positive or negative (as per $i(x;y)$)

Conditional Mutual information (CMI) – code

- $I(X;Y|Z)$ is the **reduction in uncertainty** or surprise about one variable X that we obtain from another variable Y , given the value of another variable Z .

$$i(x; y|z) = h(x|z) + h(y|z) - h(x, y|z)$$

$$I(X;Y|Z) = H(X|Z) + H(Y|Z) - H(X, Y|Z)$$

- **Exercise:** Let's code it! (empirical only)

1. Edit the Matlab function `conditionalmutualinformationempirical(xn, yn, zn)` to return the CMI between X and Y given Z from empirical samples

x_n, y_n, z_n :

- a. Input is samples x_n, y_n, z_n .
- b. Trick: can we use our existing `conditionalentropyempirical()`?
- c. Test: `CMI([0,0,1,1], [0,1,0,1], [0,1,0,1]) = 0`
- d. Test: `CMI([0,0,1,1], [0,0,1,1], [0,1,1,0]) = 1`
- e. Challenge: compute using $I(X;Y|Z) = I(X;Y,Z) - I(X;Z)$
- f. Challenge: write `conditionalmutualinformation(p)` (p is a 3D matrix!)

Conditional and unconditional mutual information

Conditioning on Z in $I(X;Y|Z)$, as compared to $I(X;Y)$ can:

- Have no effect (if all variables are independent)
- Serve to **decrease** $I(X;Y|Z)$ compared to $I(X;Y)$
 - Y and Z carry **redundant** information about X .
 - Z explained away some of what could be detected by Y
 - e.g. If $X=Y=Z$ are iid random bits, $I(X;Y|Z)=0$ although $I(X;Y)=1$
- Serve to increase $I(X;Y|Z)$ compared to $I(X;Y)$
 - Y and Z together provide **synergistic** information about X , which cannot be detected by examining either alone.
 - e.g. If $X=Y \oplus Z$, iid random bits, $I(X;Y|Z)=1$ although $I(X;Y)=0$.
- $I(X;Y|Z) - I(X;Y)$ being positive implies presence of synergy, or being negative implies presence of redundancy.
- But you can have both redundancy and synergy at once!
- Cannot measure redundancy and synergy with traditional info theory ...

Williams and Beer, "Nonnegative decomposition of multivariate information". arXiv:1004.2515, 2010.

Bossomaier, Barnett, Harré, Lizier, "An Introduction to Transfer Entropy: Information Flow in Complex Systems", Springer, Cham, 2016; section 3.2.3.1

Chain rule for mutual information

- Chain rule for information:

- $I(X; Y, Z) = I(X; Y) + I(X; Z|Y)$

- $I(X; Y, Z) = I(X; Z) + I(X; Y|Z)$

$$I(X_1, X_2, \dots, X_n; Y) = \sum_{i=1}^n I(X_i; Y | X_1 \dots X_{i-1})$$

- This is an **information regression**!

- Same applies for $i(x;y)$, $I(X;Y|Z)$ and $i(x;y|z)$.

Aside: Mutual information – derivation

- Local mutual information between X and Y :

$$i(x; y) = \log_2 \frac{p(x|y)}{p(x)}$$

and by implication $I(X; Y) = \langle i(x; y) \rangle$

- Is a **unique** form that satisfies four axioms:
 - **Once-differentiability** w.r.t. $p(x)$ and $p(x|y)$
 - **Conditional form** $i(x; y|z)$ matches $i(x; y)$ but with all PDFs conditioned on z
 - **Additivity** – $i(x; y, z) = i(x; z) + i(x; y|z)$
 - **Separation** for independent ensembles:
 - $p(x, y, u, v) = p(x, y)p(u, v) \rightarrow i(x, u; y, v) = i(x; y) + i(u, v)$

What is information: summary

- We've been introduced to the ideas of uncertainty and surprise.
- Understand the meaning of information as uncertainty reduction
- Know how to calculate fundamental measures of information theory, from PDFs and empirically from data.
- *Next lecture:* Move onto using a more advanced toolkit, and dealing with continuous-valued variables using a number of different estimators.

Questions



THE UNIVERSITY OF
SYDNEY