

# Spring 2022 Data 100/200 Midterm 2 Reference Sheet

## Ordinary Least Squares

Multiple Linear Regression Model:  $\hat{\mathbb{Y}} = \mathbb{X}\theta$  with design matrix  $\mathbb{X}$ , response vector  $\mathbb{Y}$ , and predicted vector  $\hat{\mathbb{Y}}$ . If there are  $p$  features plus a bias/intercept, then the vector of parameters  $\theta = [\theta_0, \theta_1, \dots, \theta_p]^T \in \mathbb{R}^{p+1}$ . The vector of estimates  $\hat{\theta}$  is obtained from fitting the model to the sample  $(\mathbb{X}, \mathbb{Y})$ .

Concept	Formula	Concept	Formula
Mean squared error	$R(\theta) = \frac{1}{n}   Y - X\theta  _2^2$	Normal equation	$\mathbb{X}^T \mathbb{X} \hat{\theta} = \mathbb{X}^T \mathbb{Y}$
Least squares estimate, if $\mathbb{X}$ is full rank	$\hat{\theta} = (\mathbb{X}^T \mathbb{X})^{-1} \mathbb{X}^T \mathbb{Y}$	Residual vector, $e$	$e = \mathbb{Y} - \hat{\mathbb{Y}}$
		Multiple $R^2$ (coefficient of determination)	$R^2 = \frac{\text{variance of fitted values}}{\text{variance of } y}$
Ridge Regression L2 Regularization	$\frac{1}{n}   Y - X\theta  _2^2 + \alpha   \theta  _2^2$	Squared L2 Norm of $\theta \in \mathbb{R}^d$	$  \theta  _2^2 = \sum_{j=1}^d \theta_j^2$
Ridge regression estimate (closed form)	$\hat{\theta}_{\text{ridge}} = (\mathbb{X}^T \mathbb{X} + n\alpha I)^{-1} \mathbb{X}^T \mathbb{Y}$		
LASSO Regression L1 Regularization	$\frac{1}{n}   Y - X\theta  _2^2 + \alpha   \theta  _1$	L1 Norm of $\theta \in \mathbb{R}^d$	$  \theta  _1 = \sum_{j=1}^d  \theta_j $

## Scikit-Learn

Suppose `sklearn.model_selection` and `sklearn.linear_model` are both imported packages.

Package	Function(s)	Description
<code>sklearn.linear_model</code>	<code>LinearRegression()</code>	Returns an ordinary least squares Linear Regression model.
	<code>LassoCV()</code> , <code>RidgeCV()</code>	Returns a Lasso (L1 Regularization) or Ridge (L2 regularization) linear model, respectively, and picks the best model by cross validation.
	<code>model.fit(X, y)</code>	Fits the scikit-learn <code>model</code> to the provided <code>X</code> and <code>y</code> .
	<code>model.predict(X)</code>	Returns predictions for the <code>X</code> passed in according to the fitted <code>model</code> .
<code>sklearn.model_selection</code>	<code>train_test_split(*arrays, test_size=0.2)</code>	Returns two random subsets of each array passed in, with 0.8 of the array in the first subset and 0.2 in the second subset.

## Probability

Let  $X$  have a discrete probability distribution  $P(X = x)$ .  $X$  has expectation  $\mathbb{E}[X] = \sum_x P(X = x)$  over all possible values  $x$ , variance  $\text{Var}(X) = \mathbb{E}[(X - \mathbb{E}[X])^2]$ , and standard deviation  $\text{SD}(X) = \sqrt{\text{Var}(X)}$ .

The covariance of two random variables  $X$  and  $Y$  is  $\mathbb{E}[(X - \mathbb{E}[X])(Y - \mathbb{E}[Y])]$ . If  $X$  and  $Y$  are independent, then  $\text{Cov}(X, Y) = 0$ .

Notes	Property of Expectation	Property of Variance
$X$ is a random variable. $a, b \in \mathbb{R}$ are scalars.	$\mathbb{E}[aX + b] = a\mathbb{E}[X] + b$	$\text{Var}(aX + b) = a^2\text{Var}$
$X, Y$ are random variables.	$\mathbb{E}[X + Y] = \mathbb{E}[X] + \mathbb{E}[Y]$	$\text{Var}(X + Y) = \text{Var}(X) + \text{Var}(Y) + 2\text{Cov}(X, Y)$
$X$ is a Bernoulli random variable that takes on value 1 with probability $p$ and 0 otherwise.	$\mathbb{E}[X] = p$	$\text{Var}(X) = p(1 - p)$
$Y$ is a Binomial random variable representing the number of ones in $n$ independent Bernoulli trials with probability $p$ of 1.	$E[Y] = np$	$\text{Var}(Y) = np(1 - p)$

**Central Limit Theorem:** Let  $(X_1, \dots, X_n)$  be a sample of independent and identically distributed random variables drawn from a population with mean  $\mu$  and standard deviation  $\sigma$ . The sample mean  $\overline{X}_n = \sum_{i=1}^n X_i$  is normally distributed, where  $\mathbb{E}[\overline{X}_n] = \mu$  and  $\text{SD}(\overline{X}_n) = \sigma/\sqrt{n}$ .

Parameter Estimation

Suppose for each individual with fixed input  $x$ , we observe a random response  $Y = g(x) + \epsilon$ , where  $g$  is the true relationship and  $\epsilon$  is random noise with zero mean and variance  $\sigma^2$ .

For a new individual with fixed input  $x$ , define our random prediction  $\hat{Y}(x)$  based on a model fit to our observed sample  $(\mathbb{X}, \mathbb{Y})$ . The model risk is the mean squared prediction error between  $Y$  and  $\hat{Y}(x)$ :

$$\mathbb{E}[(Y - \hat{Y}(x))^2] = \sigma^2 + \left(\mathbb{E}[\hat{Y}(x)] - g(x)\right)^2 + \text{Var}(\hat{Y}(x))$$

Suppose that input  $x$  has  $p$  features and the true relationship  $g$  is linear with parameter  $\theta \in \mathbb{R}^{p+1}$ . Then  $Y = f_\theta(x) = \theta_0 + \sum_{j=1}^p \theta_j x_j + \epsilon$  and  $\hat{Y} = f_{\hat{\theta}}(x)$  for a parameter estimate  $\hat{\theta}$  fit to the observed sample  $(\mathbb{X}, \mathbb{Y})$ .

SQL

SQLite syntax:

```
SELECT [DISTINCT]
  { * | expr [[AS] c_alias]
    {, expr [[AS] c_alias] ...} }
FROM tableref {, tableref}
[[INNER | LEFT ] JOIN table_name
  ON qualification_list]
[WHERE search_condition]
[GROUP BY colname {, colname...}]
[HAVING search_condition]
[ORDER BY column_list]
[LIMIT number]
[OFFSET number of rows];
```

Syntax	Description
SELECT column_expression_list	List is comma-separated. Column expressions may include aggregation functions (MAX, FIRST, COUNT, etc). AS renames columns. DISTINCT selects only unique rows.
FROM s INNER JOIN t ON cond	Inner join tables s and t using cond to filter rows; the INNER keyword is optional.
FROM s LEFT JOIN t ON cond	Left outer join of tables s and t using cond to filter rows.
FROM s, t	Cross join of tables s and t: all pairs of a row from s and a row from t
WHERE a IN cons_list	Select rows for which the value in column a is among the values in a cons_list.
ORDER BY RANDOM LIMIT n	Draw a simple random sample of n rows.
ORDER BY a, b DESC	Order by column a (ascending by default) , then b (descending).
CASE WHEN pred THEN cons ELSE alt END	Evaluates to cons if pred is true and alt otherwise. Multiple WHEN/THEN pairs can be included, and ELSE is optional.
WHERE s.a LIKE 'p'	Matches each entry in the column a of table s to the text pattern p. The wildcard % matches at least zero characters.
LIMIT number	Keep only the first number rows in the return result.
OFFSET number	Skip the first number rows in the return result.