

# Iteration Guide — Site Inspection App

## How to update, extend and redeploy the app

App v1.3 · Form 4.2 · Project 2.1 — Site Assessment Live app: <https://ds-js1.github.io/dryspace-inspect/>

**What changed in v1.3.** The app is now in a **git repository** with an **automated test suite**, so "save as a new version folder" and the manual test checklist are both retired. Governance moved out of this document into three that are loaded automatically — see §0.

## 0. Read these first

This guide covers **how to change the code**. It deliberately no longer covers what *else* must be updated when you do — that drifted, and now lives elsewhere:

| Document               | Covers                                                                         |
|------------------------|--------------------------------------------------------------------------------|
| CLAUDE.md              | The non-negotiables. <b>Loaded automatically at the start of every session</b> |
| 05_Release Protocol.md | What to update and when, tiered by change size                                 |
| docs/DECISION-LOG.md   | What was decided and why — <b>read before proposing anything architectural</b> |

The decision log matters most. Many questions that look open are already settled, and §3 of it lists decisions that were *reversed* — reverting to any of those reintroduces a known bug.

## 1. Where everything lives

Source of truth is the repository working folder:

```
01_Contact to Contract\Dryspace Inspection App v1.3\  
  index.html          the app – form content, record layer, UI  
  ds-media-sync.js    renditions, naming, upload queue, state machine  
  ds-sharepoint.js    Microsoft Graph transport  
  ds-auth.js          OAuth 2.0 PKCE sign-in  
  sw.js               offline caching + update detection  
  tests.html          237 assertions – run before and after any change  
  manifest.webmanifest, icons
```

Git internals live **outside** this folder at `C:\Users\jamie\dev\.git-dryspace-inspect`, because the folder sits in a OneDrive-synced SharePoint library and syncing `.git` corrupts it. The `.git` entry here is a pointer file — do not delete it.

Deployment: GitHub account **DS-JS1**, repository **dryspace-inspect**, live via GitHub Pages from `main`.

**Folder naming changed in v1.3.** The folder matches the **minor** version (`v1.3`), not every patch. Git holds each version and tags each release, so copying the whole folder for a typo fix creates snapshots nobody reads.

## 2. Starting an update session

Point the session at the v1.3 folder so `CLAUDE.md` loads automatically. If that is awkward, start with:

```
Read CLAUDE.md and docs/DECISION-LOG.md in <path>, then ...
```

State the change in your usual list format. Reference fields by their on-form reference number (e.g. 03.4) and their label.

### Example prompt

```
In index.html:
(1) Section 05 – add checkbox "Perched water table confirmed by scan" to
    Contributing structural / design factors;
(2) Section 01 – add a B2C/B2B client type dropdown after Client name(s).

Assign data-fid values to the new controls, run tests.html before and after,
update the changelog, bump the versions, and commit.
```

## 3. The structural rules

### Every control needs a permanent `data-fid`

```
<input type="text" data-fid="s3.internal-ceiling-height">
```

That id is what answers are stored against. Set once, when the field is created, and never changed.

- **Renaming a label is safe.** The id does not change.
- **Moving a field is safe.** Same reason.
- **Adding fields, options or sections is safe.**
- **Deleting a field still loses its data** — expected. If it is being *replaced*,

add a migration rule instead.

**A control without a `data-fid` is silently excluded from saved data.** No error, no warning — the answer simply never saves. `tests.html` fails if any control is missing one.

### Every file input needs a permanent `data-mfid`

```
<input type="file" data-mfid="m.s4.wall-moisture-signs" id="wall-signs-media">
```

Added in v1.3. Photos were previously keyed by the input's DOM `id`, so renaming an id orphaned every photo attached to it — the one place the v1.2 fix had been skipped.

### Naming convention

| Control type           | Pattern                               | Example                                 |
|------------------------|---------------------------------------|-----------------------------------------|
| Text, select, textarea | <code>sNN.slug-of-label</code>        | <code>s3.internal-ceiling-height</code> |
| Checkbox               | <code>sNN.slug::slug-of-option</code> | <code>s3.slab-design::raft-slab</code>  |
| Radio group            | <code>r.groupname</code>              | <code>r.grade</code>                    |
| "Other" free text      | <code>sNN.slug-of-label-other</code>  | <code>s3.retaining-wall-other</code>    |
| File input             | <code>m.sNN.purpose</code>            | <code>m.s4.wall-moisture-signs</code>   |

Lowercase, hyphenated, derived from the label as it reads when the field is created.

### Migration rules — when a field is replaced

Four mechanisms exist. Use them rather than accepting data loss:

1. `data-legacy` — put the old key on the new control to redirect its data.

Multiple rules can be given, separated by `;;`.

2. `VALUE_RULES` — declared as `data-legacy="oldKey=oldValue"`. Ticks a checkbox when an old dropdown held a particular value.

3. `MERGE_RULES` — appends old free text into another field rather than overwriting, and can tick a companion checkbox.

4. `VALUE_REMAP` — rewrites a stored answer when the *wording of an option* changes.

Anything unmatched is preserved under an `unmapped:` prefix rather than discarded.

**The trap.** Field ids protect against renaming a **label**. They do **not** protect against rewording an **option** in a radio or checkbox group — those are stored as their text. Reword one without a `VALUE_REMAP` and the answer is orphaned on the next autosave.

The record schema number tracks this: 1 is label-keyed, 2 introduced field ids, 3 applied the BS8102:2022 grade remap. Bump it whenever a migration step is added.

## 4. Versioning — required on every change

- `index.html`: update `APP_VER`, `VER_DATE`, and `FORM_VER` if form content changed.
- `sw.js`: bump `CACHE_VERSION`. **\*\*This is what makes installed devices pick up the update.\*\*** `tests.html` fails if it does not contain `APP_VER`.
- `CHANGELOG.txt`: write the entry as you make the change, not afterwards.
- If field ids changed or were added, say so explicitly — Project 3.0 maps against them.
- If any radio or checkbox option was reworded, add a `VALUE_REMAP` and bump the schema.
- Commit, and tag the release (v1.3.2).

The home-screen footer and form header read their version from these constants — no separate text edit is needed.

## 5. Testing

**Automated.** Serve the folder over HTTP and open `tests.html`. 237 assertions covering field-id integrity, the full v1.1.1 migration chain, the grade remap, media identity, update detection, naming, the upload queue, the Graph transport and sign-in. **Expect zero failures before you start and zero when you finish.**

Serving matters — `file://` blocks iframe access and IndexedDB.

**Still needs a person.** The tests cannot tell you whether the app *feels* right:

1. Create a test inspection and enter data in every changed field.
2. Close the tab, reopen, confirm it reloads intact — including dynamic reveals, Other boxes and the measurement schedule.
3. Export a draft, re-import it, confirm the changed fields survive.
4. Open a record created on the previous version and confirm the migration message appears and old answers are present.

5. Change the stage; confirm the audit trail grows and the exported filename picks it up.
6. Attach a photo; confirm the chip turns green and the count increments.
7. Mark complete, download the report, check the changed fields and measurement totals appear.
8. Delete the test inspection.

**Development caching will bite you.** The service worker serves cache-first, so an edit can appear to do nothing. Load `index.html?nosw=1` for a guaranteed fresh copy. This has twice caused the test suite to grade stale code.

## 6. Redeploying

The repository **is** the deployment. Pushing to `main` publishes the app.

1. Confirm tests pass and version stamps agree.
2. Commit and tag.
3. Merge `release/v1.x` into `main` and push.
4. **Verify the served file actually changed** — fetch the live `index.html` and confirm `APP_VER` moved. Not that the push succeeded; that the app did.
5. From v1.3 devices announce the update themselves. Before that, staff must fully close and reopen the app.

**If devices do not update**, it is almost always a missed `CACHE_VERSION` bump. Check that first. The tests now catch it, which is why the check exists.

**v1.2.0 and v1.2.1 were completed and never deployed**, and nobody noticed for two versions because nothing checked that live matched intent. Step 4 is that check.

## 7. Downstream connection (Project 3.0)

Every report contains a hidden machine-readable JSON block with all answers, section labels, the measurement schedule with totals, per-section completion counts, and the audit trail.

**Action required in Project 3.0.** From v1.2 the `rawData` block is keyed by permanent **field id** (e.g. `s3.slab-design`) rather than label text. The Proposal Builder must map against these ids.

`docs/FIELD-APP-TEMPLATE.md` describes the whole architecture, written so a sibling app (progress inspections, completion reports, competency assessments, equipment damage) can be built from it. Roughly 80% of the code moves across unchanged — the form is the only part that genuinely differs.

## 8. Ideas parked for future versions

- **SharePoint List + Power Apps** — the agreed destination for the handover problem. One record per inspection, per-field versioning, no baton discipline needed. Trigger is headcount and volume, not time.
- **B2C/B2B client type indicator** — required by 4.0 for quote type selection.

- **Required-field prompts** — better as stage-transition gates than a blocking check on *Mark complete*.
- **Update the Dryspace Guide to BS8102:2022** — the form moved in v1.2.1 and the Guide now disagrees with it.
- **SOP alignment** — Section 01 corresponds to the New Enquiry SOP, Section 02 to the Discovery Call SOP.
- **Sample photos on fields** — note that hover does not exist on touch devices.
- **App icons rebuilt from the official logo mark** — the current icons are a generic droplet.
- **Document freshness check** — compare each document's modified date against `index.html` and flag any older than the code it describes. The largest remaining manual gap in the release process.
- **Google Photos secondary backup** — scheduled sync reading from SharePoint, for its map-based search. Needs a custom connector.

### Done since this list was last written

- ~~Direct SharePoint upload via Microsoft Graph~~ — built in v1.3.