

26.Jun.2022

OracleTalk#06

By : Mohammed Arshad

<u>#</u>	<u>Incident/Question</u>	<u>OPERATING LAYER</u>	<u>Solution/Answer</u>
37	Command to get package version / form version/ Sql script version		<code>strings -a xlajelns.pkb grep '\$Header'</code> <code>strings -a xlajelns.pls grep '\$Header'</code> <code>strings -a xlajelns.sql grep '\$Header'</code> > <code>strings -a apxpawkb.fmb grep '\$Header'</code>
38	To work with R12 E Business services.		<code>Common_top\admins\scripts\</code>
39	Dos command to kill an OS process	APP LEVEL USUALLY / ANY PROCESS.	<code>C:\>PSKILL -9 PROCESSID</code>
40	Command to search for processes running at the OS level for a utility , FND, for example.		<code>C:\>PS -EF GREP [FND,]</code>

26.Jun.2022

OracleTalk#06

By : Mohammed Arshad

41	Query to check the validation of the GUEST/Oracle user.		<pre>select fnd_web_sec.validate_login('GUEST',' <GuestPassword>') from dual;</pre>
42	To run PYUPIP trace		Open a DOS box and run the following PAY_TOP\BIN_PATH\pyupip.exe APPS_USER/APPS_PWD PID > LOGFILE
43	a) Query to refresh materialized view. b) View the materialized views created.		<pre>exec dbms_mview.refresh('dtl_budget_mv');</pre> <pre>select * from user_mviews;</pre>
44	To connect to an instance without a password using the		<pre>i. Add "ORACLE_HOME = <Oracle installation Directory" in Environment variable</pre> <pre>ii. Open a command prompt</pre> <pre>iii. Change the directory to %ORACLE_HOME%\bin</pre>

26.Jun.2022

OracleTalk#06

By : Mohammed Arshad

	SYS account		<pre>iv. type the command "sqlplus /nolog "</pre> <pre>v. SQL> connect /as sysdba</pre> <pre>vi. SQL> alter user SYS identified by</pre> <pre>"newpassword"</pre>
45	TO check for data file offline\co rrupt.		<pre>select</pre> <pre>node_name,target_node,control_code,</pre> <pre>from fnd_concurrent_queues</pre> <pre>select * from v\$recover_file</pre> <pre>select * from v\$datafile where file# in</pre> <pre>('1','2','5','7')</pre>
46	How to run import for jpximporte r.		<pre>java</pre> <pre>oracle.jrad.tools.xml.importer.JPXImport</pre> <pre>er <jpxpath> -username apps -</pre> <pre>password appspwd -dbconnection</pre> <pre>"(DESCRIPTION=(ADDRESS_LIST=(ADDRESS=(P</pre> <pre>ROTOCOL=TCP)(HOST=server.domain)(PORT=p</pre> <pre>ort))) (CONNECT_DATA=(SERVICE_NAME =</pre> <pre>DB_Service)))"</pre> <pre>Note: source the environment before.</pre>
47	What is ad_splicer		<pre>ad splicer utility is used to register</pre> <pre>a product with the E business suite.</pre>