From the theory of vulnerability to verified policy advice

Nicola Botta with P. Jansson and C. Ionescu

Part 2, Background: climate science, climate policy under uncertainty, 2024-05-06

Botta FPClimate 55/98

Plan

Done:

- The computational structure of *possible*: Monadic dynamical systems
- Background: climate science, climate policy under uncertainty
 - Basic notions
 - Example 1: emission reduction policies
 - Optimality, policies

Today:

- Background: climate science, climate policy under uncertainty
 - Example 2: a generation dilemma (Heitzig et al. 2018)
 - Examples 1 and 2: common traits
 - Towards sequential decision problems
- Sequential decision problems

Botta FPClimate 56 / 98

Plan

Today:

- Background: climate science, climate policy under uncertainty
 - Example 2: a generation dilemma (Heitzig et al. 2018)
 - Examples 1 and 2: common traits
 - Towards sequential decision problems
- Sequential decision problems

Next week:

- Bellman's equation, backward induction
- Verified policy advice in a nutshell

Botta FPClimate 57 / 98

Optimality, policies

- With the <u>understanding</u> that what can be optimal under uncertainty are <u>policies</u> and with a notion of optimality, we can formulate the questions from the emission reduction example consistently
- How do optimal policies change if we account for the fact that technological innovation could become available later or earlier?
- How do optimal policies change if there is a non-zero probability of exceeding critical thresholds even if we stay within the IPCC emission corridor?
- How do optimal policies change if we account for the fact that climate decisions may not be implemented, for example, because of political instability or because of external shocks?

Botta FPClimate 58 / 98


Example 2: a generation dilemma (Heitzig et al. 2018)

- The world can be in one of four states: GU, GS, B and BT
- B is a bad state, one in which resources are depleted and the wealth of the societies is low
- GS is a good, safe state. In GS, plenty of resources are available, societies are wealthy and there is no risk to turn into B, GU or BT
- GU is a good but unsafe state. In GU, plenty of resources are available, societies are wealthy but there is a significant risk to turn into B
- BT is a bad but temporary state
- In BT, societies are poor but it is certain that the next state will be good and safe: GS

Botta FPClimate 59 / 98

Example 2: a generation dilemma (Heitzig et al. 2018)


- A generation in B, BT or GS has no options: the next states will be B, GS and GS
- A generation in GU has two options: a and b
- If it picks a, the next generation will possibly be in GU again. But it can also end up in B
- If it picks b, the next generation will be in BT with certainty



• What should a generation in GU do? a or b?

Botta FPClimate 60 / 98

Example 2: a generation dilemma (Heitzig et al. 2018)



Exercise 5.5

Should a generation in GU do a or b? The answer is: it depends. Explain on what it might depend.

Exercise 5.6

Put consistent probabilities on the edges of the transition graph above.

Botta FPClimate 61 / 98

Examples 1 and 2: common traits

- Both decision problems have the form of a dilemma
- In both cases, the consequences of decisions are uncertain
- Decisions are taken sequentially, one after the other, see *Incorporating path dependency into decision-analytic methods: an application to global climate-change policy*
- Can we exploit these similarities? Can we develop a method for specifying and solving these and similar decisions problems rigorously? What does this mean?

Botta FPClimate 62 / 98

• We tackle these questions in three steps:

- Abstract away the details of specific decision problems
- 2 Formulate a class of decision problems rigorously
- 1 Derive generic, verified solution methods for this class

Botta **FPClimate** 63 / 98

Botta FPClimate 64/98

There are n + 1 decision steps to go . . .

$$\circ \circ \circ$$
 $n+1$ steps left


65 / 98 Botta **FPClimate**

... here is the current state,




66 / 98 **FPClimate**

...here are your options.




Botta FPClimate 67 / 98

Pick one!




Botta FPClimate 68 / 98

Move to a new state and ...




Botta FPClimate 69 / 98

... collect rewards and face the next decision step!




Botta FPClimate 70 / 98

What if there are more than one next possible states?



Botta FPClimate 71 / 98

Apply monadic systems theory!



Botta FPClimate 72 / 98

Next week

- Steps 1-3: Sequential decision problems
- Bellman's equation, backward induction
- Verified policy advice in a nutshell

Exercise 5.7

Try to formalize the cartoon of step 1 (abstract away the details of specific decision problems) in Agda

Botta FPClimate 73 / 98

From the theory of vulnerability to verified policy advice

Nicola Botta with P. Jansson and C. Ionescu

Part 3, 2024-05-06

Plan

Done:

- The computational structure of possible: Monadic dynamical systems
- Background: climate science, climate policy under uncertainty

Today:

- Sequential decision problems
- Bellman's equation, backward induction
- Verified policy advice in a nutshell

Sequential decision problems

Sequential decision problems

- As in the vulnerability theory, we build a theory for specifying and solving finite horizon sequential decision problems (SDP) in terms of a number of postulates or partial definitions
- These are the problem specification components of the theory/library
- The rest are problem solution components
- The theory is applied by fully defining the specification components

Specification: monadic uncertainty, number of decision steps

• The problem is affected by monadic uncertainty

```
\begin{array}{lll} \textit{M} & : \textit{Set} \rightarrow \textit{Set} \\ \textit{fmap}_{\textit{M}} & : \{\textit{A} \textit{B} : \textit{Set}\} \rightarrow (\textit{A} \rightarrow \textit{B}) \rightarrow \textit{M} \textit{A} \rightarrow \textit{M} \textit{B} \\ \eta_{\textit{M}} & : \{\textit{A} : \textit{Set}\} \rightarrow \textit{A} \rightarrow \textit{M} \textit{A} \\ \mu_{\textit{M}} & : \{\textit{A} : \textit{Set}\} \rightarrow \textit{M} (\textit{M} \textit{A}) \rightarrow \textit{M} \textit{A} \end{array}
```

• We want to make *n* decision steps

$$n: \mathbb{N}$$

• At decision step $t : \mathbb{N}$, we have already taken t decisions

Specification: states, controls, transition function

• The set of states of the problem can be different at different decision steps

$$X: \mathbb{N} \to Set$$

The set of controls can be different at different decision steps and in different states


$$Y: (t: \mathbb{N}) \rightarrow X t \rightarrow Set$$

• Selecting a control $y: Y t \times in \times X t$ yields an M-structure of possible next states

$$next: (t: \mathbb{N}) \rightarrow (x: X t) \rightarrow Y t x \rightarrow M (X (suc t))$$

• next describes an infinite, layered DAG with states in the nodes

Specification: states, controls, transition function



Specification: values, reward function

• Each decision step yields a reward in a value set Val

• As in vulnerability theory, we require Val to be a preorder, here a total one

$$\begin{array}{l} _ \leqslant _ : Val \rightarrow Val \rightarrow Set \\ refl_\leqslant : (x : Val) \rightarrow x \leqslant x \\ trans_\leqslant : (x \ y \ z : Val) \rightarrow x \leqslant y \rightarrow y \leqslant z \rightarrow x \leqslant z \\ total_\leqslant : (x \ y : Val) \rightarrow Either (x \leqslant y) (y \leqslant x) \end{array}$$

We will also need Val to have a reference "zero" element and an "addition"

$$0_{Val}$$
 : Val \rightarrow Val \rightarrow Val

Specification: reward function, solving a SDP

• Different combinations of current state, control and next state can lead to different rewards

reward :
$$(t : \mathbb{N}) \rightarrow (x : X t) \rightarrow Y t x \rightarrow X (suc t) \rightarrow Val$$

• Solving a SDP means finding a sequence of policies that maximizes a measure of the ⊕-sum of the rewards along all possible trajectories

Exercise 6.1

Make sure that you fully understand what solving a SDP means.

Exercise 6.2

Define M, X, Y and next for the generation dilemma. What could be Val and reward for this problem?

Botta FPClimate Part 3, 2024-05-06 82 / 98

Solution: policies, policy sequences

- ... finding a sequence of policies that maximizes a measure of the ⊕-sum of the rewards along all possible trajectories
- We need to formulate the problem precisely
- We start with policies and policy sequences

```
Policy : (t : \mathbb{N}) \to Set

Policy t = (x : X t) \to Y t x

data PolicySeq : (t n : \mathbb{N}) \to Set where

Nil : \{t : \mathbb{N}\} \to PolicySeq t zero

_::_ : \{t n : \mathbb{N}\} \to Policy t \to PolicySeq (suc t) n \to PolicySeq t (suc n)

infixr 5 _::_
```

Exercise 6.3

Explain the $(suc\ t)\ n$ - $t\ (suc\ n)$ pattern in the definition of *PolicySeq*.

Solution: state-control sequences

- ...a pol. seq. that max. a meas of the ⊕-sum of the rewards along all possible trajectories
- We want the possible trajectories of a policy sequence to be sequences of state-control pairs

```
data XYSeq : (t n : \mathbb{N}) \rightarrow Set where

Last : \{t : \mathbb{N}\} \rightarrow X t \rightarrow XYSeq t (suc zero)

_(1) = (t n : \mathbb{N}) \rightarrow \Sigma (X t) (Y t) \rightarrow XYSeq (suc t) (suc n) \rightarrow XYSeq t (suc (suc n))
```

Exercise 6.4

A value of type $XYSeq\ t\ n$ is like a vector. What is its length? Can n be zero? Why is the first constructor of $XYSeq\ called\ Last$?

Botta FPClimate Part 3, 2024-05-06 84 / 98

Solution: possible trajectories

- ...a pol. seq. that max. a meas of the \oplus -sum of the rewards along all possible trajectories
- We compute the possible trajectories of a policy sequence as we did for monadic systems

$$trj: \{t \ n : \mathbb{N}\} \rightarrow PolicySeq \ t \ n \rightarrow X \ t \rightarrow M \ (XYSeq \ t \ (suc \ n))$$
 $trj \{t\} \ Nil \qquad x = \eta_M \ (Last \ x)$
 $trj \{t\} \ (p :: ps) \ x = \mathbf{let} \ y = p \ x \mathbf{in}$

$$\mathbf{let} \ mx' = next \ t \ x \ y \mathbf{in}$$

$$fmap_M \ ((x \ , y) \ ||_{-}) \ (mx' \ \gg =_M trj \ ps)$$

Exercise 6.5

Make sure that you understand the computation of possible trajectories. What are the types of y, mx' in the **let-in** clauses?

Botta FPClimate Part 3, 2024-05-06 85 / 98

Solution: possible trajectories

- ...a pol. seq. that max. a meas of the ⊕-sum of the rewards along all possible trajectories
- Now we can compute the ⊕-sum of the rewards along all possible trajectories . . .

```
\begin{array}{lll} sumR : \{t \ n : \mathbb{N}\} & \rightarrow XYSeq \ t \ n \rightarrow Val \\ sumR \{t\} \ (Last \ x) & = \ 0_{Val} \\ sumR \{t\} \ ((x \ , y) \ || \ xys) & = \ reward \ t \ x \ y \ (head \ xys) \ \oplus \ sumR \ xys \end{array}
```

• ... and the value of taking n decisions according to a policy sequence in an initial state

```
val: \{t \ n: \mathbb{N}\} \rightarrow (ps: PolicySeq \ t \ n) \rightarrow (x: X \ t) \rightarrow Val \ val \ ps = measure \circ fmap_M \ sumR \circ trj \ ps
```

Exercise 6.6

Notice that val ps is a vulnerability measure! What are possible and harm here?