Handling Imbalanced Data in Binary Classification: A Review and Comparative Experimental Study

Chi-Wei, PENG
National Central University
Student ID: 114423004
Zhongli, Taiwan
114423004@cc.ncu.edu.tw

Ting-Chun, Lin
National Central University
Student ID: 114423009
Zhongli, Taiwan
Tinalin@g.ncu.edu.tw

Chiu-Hsiang, Lin
National Central University
Student ID: 114423049
Zhongli, Taiwan
114423049@cc.ncu.edu.tw

Chia-Chen, Lee
National Central University
Student ID: 114423050
Zhongli, Taiwan
cclee@g.ncu.edu.tw

Abstract

A clear and well-documented LaTeX document is presented as an article formatted for publication by ACM in a conference proceedings or journal publication. Based on the "acmart" document class, this article presents and explains many of the common variations, as well as many of the formatting elements an author may use in the preparation of the documentation of their work.

CCS Concepts

• **Do Not Use This Code → Generate the Correct Terms for Your Paper**; *Generate the Correct Terms for Your Paper*; Generate the Correct Terms for Your Paper; Generate the Correct Terms for Your Paper.

Keywords

Do, Not, Use, This, Code, Put, the, Correct, Terms, for, Your, Paper

1 Introduction

1.1 Background and Problem Definition

In recent years, the rapid expansion of data availability across large-scale, complex, and networked systems has propelled machine learning to prominent roles in numerous application domains [1].

However, real-world data distributions are inherently complex and frequently exhibit a significant class imbalance. The class imbalance problem arises when the number of instances belonging to one class (the majority class) substantially outnumbers those of another (the minority class), resulting in a severely skewed training distribution [1, 2].

This phenomenon is pervasive in many high-stakes domains, including financial fraud detection, network intrusion detection, and the diagnosis of rare diseases such as diabetes and stroke, where the minority class—despite its low frequency of occurrence—typically constitutes the primary target of predictive interest [3, 4].

1.2 Challenges and the Pitfalls of Evaluation Metrics

Standard machine learning models are generally designed under the implicit assumption of an approximately balanced class distribution. Consequently, when applied to skewed data, these models exhibit a systematic bias toward the majority class, yielding poor predictive performance for minority instances—precisely those of greatest practical concern [1].

This issue is further compounded by the widespread use of conventional evaluation metrics. Overall accuracy, in particular, is highly misleading under class imbalance: a naive classifier that assigns all instances to the majority class can attain superficially high accuracy while entirely failing to identify any minority-class example [5].

To overcome this limitation, the research community has advocated the adoption of more discriminative metrics, including the F1-Score, the Area Under the Receiver Operating Characteristic Curve (AUC-ROC) [6], and the Geometric Mean (G-Mean) [7], which collectively provide a more faithful assessment of model performance across both classes.

1.3 Taxonomy of Imbalanced Learning Techniques

To address the challenges posed by imbalanced datasets, a rich body of literature has proposed numerous techniques, which are broadly categorized into three main families: data-level methods, algorithmic-level methods, and hybrid strategies [1, 8].

Data-level approaches modify the training data distribution prior to model induction, either by oversampling the minority class—most notably through the Synthetic Minority Over-sampling Technique (SMOTE) [2] and its variants—or by undersampling the majority class through methods such as Random Under-Sampling (RUS).

Algorithmic-level approaches, by contrast, leave the data distribution unchanged and instead modify the learning procedure itself; representative techniques include cost-sensitive learning and ensemble-based methods such as weighted classifiers and boosting frameworks [9].

Finally, hybrid strategies combine the complementary strengths of both data resampling and algorithmic robustness, with methods

such as SMOTEBoost and RUSBoost serving as prominent examples [9].

1.4 Research Gap and Objectives

Despite the substantial volume of existing work, many comparative studies evaluate imbalanced learning techniques across heterogeneous datasets that vary simultaneously in multiple dimensions—including class overlap, feature complexity, and sample size—making it difficult to isolate the independent effect of the Imbalance Ratio (IR) on classifier performance [1]. Confounding factors of this nature limit the interpretability of empirical findings and reduce their practical utility as guidelines for practitioners.

To address this gap, this study proposes a rigorous empirical framework grounded in controlled experimental design. Rather than relying solely on a diverse collection of independent datasets, we systematically vary the IR within a curated set of benchmark datasets spanning a wide range of imbalance severity—from mild (IR ≈ 2.4) to extreme (IR ≈ 41.4)—thereby enabling direct, controlled comparisons across escalating levels of class imbalance.

Within this framework, we conduct a systematic evaluation of representative methods from all three technique families—data-level, algorithmic-level, and hybrid—using three established base classifiers (SVM, Random Forest, and XGBoost) and a comprehensive set of evaluation metrics (F1-Score, AUC-ROC, and G-Mean). By analyzing the performance degradation trajectories of each strategy as class imbalance worsens, this study aims to provide both a nuanced empirical understanding of the strengths and limitations of existing approaches and actionable practical guidance for selecting appropriate imbalanced learning techniques in binary classification tasks.

2 Template Overview

As noted in the introduction, the "`acmart`" document class can be used to prepare many different kinds of documentation — a double-anonymous initial submission of a full-length technical paper, a two-page SIGGRAPH Emerging Technologies abstract, a "camera-ready" journal article, a SIGCHI Extended Abstract, and more — all by selecting the appropriate *template style* and *template parameters*.

This document will explain the major features of the document class. For further information, the *LaTeX User's Guide* is available from https://www.acm.org/publications/proceedings-template.

2.1 Template Styles

The primary parameter given to the "`acmart`" document class is the *template style* which corresponds to the kind of publication or SIG publishing the work. This parameter is enclosed in square brackets and is a part of the `documentclass` command:

```
\documentclass[STYLE]{acmart}
```

Journals use one of three template styles. All but three ACM journals use the `acmsmall` template style:

- `acmsmall`: The default journal template style.
- `acmlarge`: Used by JOCCH and TAP.
- `acmtog`: Used by TOG.

The majority of conference proceedings documentation will use the `acmconf` template style.

- `sigconf`: The default proceedings template style.
- `sigchi`: Used for SIGCHI conference articles.
- `sigplan`: Used for SIGPLAN conference articles.

2.2 Template Parameters

In addition to specifying the *template style* to be used in formatting your work, there are a number of *template parameters* which modify some part of the applied template style. A complete list of these parameters can be found in the *LaTeX User's Guide.*

Frequently-used parameters, or combinations of parameters, include:

- `anonymous,review`: Suitable for a "double-anonymous" conference submission. Anonymizes the work and includes line numbers. Use with the `\acmSubmissionID` command to print the submission's unique ID on each page of the work.
- `authorversion`: Produces a version of the work suitable for posting by the author.
- `screen`: Produces colored hyperlinks.

This document uses the following string as the first command in the source file:

```
\documentclass[sigconf]{acmart}
```

3 EXPERIMENTAL SETUP

3.1 Datasets

To rigorously investigate the effect of varying Imbalance Ratios (IR) on classifier performance, this study employs eight benchmark datasets sourced from the KEEL (Knowledge Extraction based on Evolutionary Learning) repository [**?**], a widely adopted resource for imbalanced classification research. The selected datasets span a broad spectrum of imbalance severity—from mild to extreme—and originate from diverse real-world domains, thereby enabling controlled cross-IR comparisons while maintaining ecological validity.

The Imbalance Ratio is defined formally as:

$$\mathrm{IR} = \frac{|S_{\mathrm{maj}}|}{|S_{\mathrm{min}}|}, \tag{1}$$

where $|S_{\mathrm{maj}}|$ and $|S_{\mathrm{min}}|$ denote the cardinalities of the majority and minority classes, respectively. Following the severity categorization proposed in the imbalanced learning literature [**?**], the datasets are stratified into four levels: *mild* (IR < 3), *moderate* ($3 \leq$ IR < 15), *severe* ($15 \leq$ IR < 30), and *extreme* (IR ≥ 30).

All experiments employ **stratified 5-fold cross-validation** to ensure that the class distribution is preserved in every fold. The complete characteristics of the benchmark suite are summarised in Table 1.

The inclusion of four Yeast variants (Yeast-1, -3, -4, and -6) sharing an identical feature space and sample size ($n = 1{,}484$) is a deliberate methodological choice: by holding feature complexity and data size constant while varying only the IR, these four datasets allow the direct isolation of class imbalance severity as the sole experimental variable, effectively controlling for confounds that commonly hinder cross-dataset comparisons [**?**].

Table 1: Summary of Benchmark Datasets.

Dataset	Instances	Features	Minority	Majority	Imbalance Ratio	Severity
Yeast-1	1,484	8	429	1,055	2.46	Mild
Yeast-3	1,484	8	163	1,321	8.10	Moderate
Yeast-4	1,484	8	51	1,433	28.10	Severe
Yeast-6	1,484	8	35	1,449	41.40	Extreme

3.2 Evaluation Metrics

A central challenge in evaluating classifiers on imbalanced datasets is metric selection. As demonstrated by He and Garcia [?] and mathematically formalised by Luque et al. [?], overall *Accuracy* is a fundamentally flawed metric under class imbalance: a degenerate classifier that assigns every instance to the majority class can attain superficially high accuracy while entirely failing to detect any minority-class example. Accordingly, this study excludes Accuracy as a primary performance measure and instead adopts a suite of imbalance-aware metrics grounded in the binary confusion matrix, whose elements are defined as follows: True Positives (TP), True Negatives (TN), False Positives (FP), and False Negatives (FN), where the *positive* class denotes the minority class throughout.

Precision and Recall. Precision measures the proportion of predicted positive instances that are truly positive; Recall (Sensitivity) measures the proportion of actual positive instances that are correctly identified. Both metrics are defined over the minority class and are expressed as [?]:

$$\text{Precision} = \frac{TP}{TP + FP}, \tag{2}$$

$$\text{Recall} = \frac{TP}{TP + FN}. \tag{3}$$

F1-Score. The F1-Score is the harmonic mean of Precision and Recall, providing a single scalar that penalises severe imbalances between the two [?]:

$$F_1 = 2 \cdot \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}} = \frac{2\,TP}{2\,TP + FP + FN}. \tag{4}$$

Because the harmonic mean is strictly lower than the arithmetic mean whenever Precision and Recall diverge, F_1 constitutes a conservative and informative composite measure for imbalanced classification tasks.

AUC-ROC.. The Area Under the Receiver Operating Characteristic Curve (AUC-ROC) is a threshold-independent metric that quantifies a classifier's ability to discriminate between classes across all possible decision thresholds [?]. Let the False Positive Rate (FPR) and True Positive Rate (TPR) be defined as:

$$\text{FPR} = \frac{FP}{FP + TN}, \qquad \text{TPR} = \frac{TP}{TP + FN}. \tag{5}$$

The AUC-ROC is then computed as:

$$\text{AUC}_{\text{ROC}} = \int_0^1 \text{TPR}\big(\text{FPR}^{-1}(x)\big)\, dx. \tag{6}$$

A value of 0.5 corresponds to random classification, while 1.0 denotes a perfect classifier. As noted by Saito and Rehmsmeier [?], however, ROC-based metrics can present an overly optimistic picture under extreme class imbalance, because the large pool of true negatives in the majority class suppresses the FPR, thereby inflating the apparent curve.

G-Mean. The Geometric Mean (G-Mean), originally proposed by Kubat and Matwin [?] for imbalanced learning, is the square root of the product of Sensitivity (Recall) and Specificity. It provides a balanced assessment of performance across both classes simultaneously: poor performance on *either* class leads to a sharp decline in the overall score. Specificity and G-Mean are defined as:

$$\text{Specificity} = \frac{TN}{TN + FP}, \tag{7}$$

$$\text{G-Mean} = \sqrt{\text{Recall} \times \text{Specificity}} = \sqrt{\frac{TP}{TP + FN} \cdot \frac{TN}{TN + FP}}. \tag{8}$$

Metric Selection Rationale. Although this study reports all metrics described above for completeness, the **primary evaluation metrics are F1-Score, AUC-ROC, and G-Mean**. These three are selected because they collectively capture complementary dimensions of classifier performance under imbalance: the F1-Score reflects the precision–recall trade-off for the minority class; the AUC-ROC captures threshold-independent ranking ability across all decision boundaries; and the G-Mean ensures that majority-class performance is not sacrificed for minority-class gains. Metrics including overall Accuracy and Balanced Accuracy (BAcc) are reported as supplementary references but are not used as the basis for primary comparisons, in accordance with the limitations identified in prior literature [? ? ?].

4 Typefaces

The "`acmart`" document class requires the use of the "Libertine" typeface family. Your TEX installation should include this set of packages. Please do not substitute other typefaces. The "`lmodern`" and "`ltimes`" packages should not be used, as they will override the built-in typeface families.

5 Title Information

The title of your work should use capital letters appropriately - https://capitalizemytitle.com/ has useful rules for capitalization. Use the `title` command to define the title of your work. If your work has a subtitle, define it with the `subtitle` command. Do not insert line breaks in your title.

If your title is lengthy, you must define a short version to be used in the page headers, to prevent overlapping text. The `title` command has a "short title" parameter:

```
\title[short title]{full title}
```

6 Authors and Affiliations

Each author must be defined separately for accurate metadata identification. As an exception, multiple authors may share one affiliation. Authors' names should not be abbreviated; use full first names wherever possible. Include authors' e-mail addresses whenever possible.

Grouping authors' names or e-mail addresses, or providing an "e-mail alias," as shown below, is not acceptable:

```
\author{Brooke Aster, David Mehldau}
\email{dave,judy,steve@university.edu}
\email{firstname.lastname@phillips.org}
```

The `authornote` and `authornotemark` commands allow a note to apply to multiple authors — for example, if the first two authors of an article contributed equally to the work.

If your author list is lengthy, you must define a shortened version of the list of authors to be used in the page headers, to prevent overlapping text. The following command should be placed just after the last `\author{}` definition:

```
\renewcommand{\shortauthors}{McCartney, et al.}
```

Omitting this command will force the use of a concatenated list of all of the authors' names, which may result in overlapping text in the page headers.

The article template's documentation, available at https://www.acm.org/publications/proceedings-template, has a complete explanation of these commands and tips for their effective use.

Note that authors' addresses are mandatory for journal articles.

7 Rights Information

Authors of any work published by ACM will need to complete a rights form. Depending on the kind of work, and the rights management choice made by the author, this may be copyright transfer, permission, license, or an OA (open access) agreement.

Regardless of the rights management choice, the author will receive a copy of the completed rights form once it has been submitted. This form contains LaTeX commands that must be copied into the source document. When the document source is compiled, these commands and their parameters add formatted text to several areas of the final document:

- the "ACM Reference Format" text on the first page.
- the "rights management" text on the first page.
- the conference information in the page header(s).

Rights information is unique to the work; if you are preparing several works for an event, make sure to use the correct set of commands with each of the works.

The ACM Reference Format text is required for all articles over one page in length, and is optional for one-page articles (abstracts).

8 CCS Concepts and User-Defined Keywords

Two elements of the "acmart" document class provide powerful taxonomic tools for you to help readers find your work in an online search.

The ACM Computing Classification System — https://www.acm.org/publications/class-2012 — is a set of classifiers and concepts that describe the computing discipline. Authors can select entries from this classification system, via https://dl.acm.org/ccs/ccs.cfm, and generate the commands to be included in the LaTeX source.

User-defined keywords are a comma-separated list of words and phrases of the authors' choosing, providing a more flexible way of describing the research being presented.

CCS concepts and user-defined keywords are required for for all articles over two pages in length, and are optional for one- and two-page articles (or abstracts).

Table 2: Frequency of Special Characters

Non-English or Math	Frequency	Comments
Ø	1 in 1,000	For Swedish names
π	1 in 5	Common in math
$	4 in 5	Used in business
Ψ_1^2	1 in 40,000	Unexplained usage

9 Sectioning Commands

Your work should use standard LaTeX sectioning commands: `\section`, `\subsection`, `\subsubsection`, `\paragraph`, and `\subparagraph`. The sectioning levels up to `\subsubsection` should be numbered; do not remove the numbering from the commands.

Simulating a sectioning command by setting the first word or words of a paragraph in boldface or italicized text is **not allowed.**

Below are examples of sectioning commands.

9.1 Subsection

This is a subsection.

9.1.1 Subsubsection. This is a subsubsection.

Paragraph. This is a paragraph.
Subparagraph This is a subparagraph.

10 Tables

The "`acmart`" document class includes the "`booktabs`" package — https://ctan.org/pkg/booktabs — for preparing high-quality tables.

Table captions are placed *above* the table.

Because tables cannot be split across pages, the best placement for them is typically the top of the page nearest their initial cite. To ensure this proper "floating" placement of tables, use the environment **table** to enclose the table's contents and the table caption. The contents of the table itself must go in the **tabular** environment, to be aligned properly in rows and columns, with the desired horizontal and vertical rules. Again, detailed instructions on **tabular** material are found in the *LaTeX User's Guide*.

Immediately following this sentence is the point at which Table 2 is included in the input file; compare the placement of the table here with the table in the printed output of this document.

To set a wider table, which takes up the whole width of the page's live area, use the environment **table*** to enclose the table's contents and the table caption. As with a single-column table, this wide table will "float" to a location deemed more desirable. Immediately following this sentence is the point at which Table 3 is included in the input file; again, it is instructive to compare the placement of the table here with the table in the printed output of this document.

Table 3: Some Typical Commands

Command	A Number	Comments
`\author`	100	Author
`\table`	300	For tables
`\table*`	400	For wider tables

Always use midrule to separate table header rows from data rows, and use it only for this purpose. This enables assistive technologies to recognise table headers and support their users in navigating tables more easily.

11 Math Equations

You may want to display math equations in three distinct styles: inline, numbered or non-numbered display. Each of the three are discussed in the next sections.

11.1 Inline (In-text) Equations

A formula that appears in the running text is called an inline or in-text formula. It is produced by the **math** environment, which can be invoked with the usual `\begin . . . \end` construction or with the short form `$ . . . $`. You can use any of the symbols and structures, from α to ω, available in LaTeX [25]; this section will simply show a few examples of in-text equations in context. Notice how this equation: $\lim_{n\rightarrow \infty}x=0$, set here in in-line math style, looks slightly different when set in display style. (See next section).

11.2 Display Equations

A numbered display equation—one set off by vertical space from the text and centered horizontally—is produced by the **equation** environment. An unnumbered display equation is produced by the **displaymath** environment.

Again, in either environment, you can use any of the symbols and structures available in LaTeX; this section will just give a couple of examples of display equations in context. First, consider the equation, shown as an inline equation above:

$$\lim_{n\rightarrow \infty}x=0 \tag{9}$$

Notice how it is formatted somewhat differently in the **displaymath** environment. Now, we'll enter an unnumbered equation:

$$\sum_{i=0}^{\infty} x + 1$$

and follow it with another numbered equation:

$$\sum_{i=0}^{\infty}x_i=\int_{0}^{\pi+2} f \tag{10}$$

just to demonstrate LaTeX's able handling of numbering.

12 Figures

The "`figure`" environment should be used for figures. One or more images can be placed within a figure. If your figure contains third-party material, you must clearly identify it as such, as shown in the example below.

Figure 1: 1907 Franklin Model D roadster. Photograph by Harris & Ewing, Inc. [Public domain], via Wikimedia Commons. (https://goo.gl/VLCRBB).

Your figures should contain a caption which describes the figure to the reader.

Figure captions are placed *below* the figure.

Every figure should also have a figure description unless it is purely decorative. These descriptions convey what's in the image to someone who cannot see it. They are also used by search engine crawlers for indexing images, and when images cannot be loaded.

A figure description must be unformatted plain text less than 2000 characters long (including spaces). **Figure descriptions should not repeat the figure caption - their purpose is to capture important information that is not already provided in the caption or the main text of the paper.** For figures that convey important and complex new information, a short text description may not be adequate. More complex alternative descriptions can be placed in an appendix and referenced in a short figure description. For example, provide a data table capturing the information in a bar chart, or a structured list representing a graph. For additional information regarding how best to write figure descriptions and why doing this is so important, please see https://www.acm.org/publications/taps/describing-figures/.

12.1 The "Teaser Figure"

A "teaser figure" is an image, or set of images in one figure, that are placed after all author and affiliation information, and before the body of the article, spanning the page. If you wish to have such a

figure in your article, place the command immediately before the `\maketitle` command:

```
\begin{teaserfigure}
  \includegraphics[width=\textwidth]{sampleteaser}
  \caption{figure caption}
  \Description{figure description}
\end{teaserfigure}
```

13 Citations and Bibliographies

The use of BibTEX for the preparation and formatting of one's references is strongly recommended. Authors' names should be complete — use full first names ("Donald E. Knuth") not initials ("D. E. Knuth") — and the salient identifying features of a reference should be included: title, year, volume, number, pages, article DOI, etc.

The bibliography is included in your source document with these two commands, placed just before the `\end{document}` command:

```
\bibliographystyle{ACM-Reference-Format}
\bibliography{bibfile}
```

where "`bibfile`" is the name, without the "`.bib`" suffix, of the BibTEX file.

Citations and references are numbered by default. A small number of ACM publications have citations and references formatted in the "author year" style; for these exceptions, please include this command in the **preamble** (before the command "`\begin{document}`") of your LATEX source:

```
\citestyle{acmauthoryear}
```

Some examples. A paginated journal article [2], an enumerated journal article [11], a reference to an entire issue [10], a monograph (whole book) [24], a monograph/whole book in a series (see 2a in spec. document) [18], a divisible-book such as an anthology or compilation [13] followed by the same example, however we only output the series if the volume number is given [14] (so Editor00a's series should NOT be present since it has no vol. no.), a chapter in a divisible book [37], a chapter in a divisible book in a series [12], a multi-volume work as book [23], a couple of articles in a proceedings (of a conference, symposium, workshop for example) (paginated proceedings article) [3, 16], a proceedings article with all possible elements [36], an example of an enumerated proceedings article [15], an informally published work [17], a couple of preprints [6, 8], a doctoral dissertation [9], a master's thesis: [4], an online document / world wide web resource [1, 29, 38], a video game (Case 1) [28] and (Case 2) [27] and [26] and (Case 3) a patent [35], work accepted for publication [32], 'YYYYb'-test for prolific author [33] and [34]. Other cites might contain 'duplicate' DOI and URLs (some SIAM articles) [22]. Boris / Barbara Beeton: multi-volume works as books [20] and [19]. A presentation [31]. An article under review [7]. A couple of citations with DOIs: [21, 22]. Online citations: [38–40]. Artifacts: [30] and [5].

14 Acknowledgments

Identification of funding sources and other support, and thanks to individuals and groups that assisted in the research and the preparation of the work should be included in an acknowledgment section, which is placed just before the reference section in your document.

This section has a special environment:

```
\begin{acks}
...
\end{acks}
```

so that the information contained therein can be more easily collected during the article metadata extraction phase, and to ensure consistency in the spelling of the section heading.

Authors should not prepare this section as a numbered or unnumbered `\section`; please use the "`acks`" environment.

15 Appendices

If your work needs an appendix, add it before the "`\end{document}`" command at the conclusion of your source document.

Start the appendix with the "`appendix`" command:

```
\appendix
```

and note that in the appendix, sections are lettered, not numbered. This document has two appendices, demonstrating the section and subsection identification method.

16 Multi-language papers

Papers may be written in languages other than English or include titles, subtitles, keywords and abstracts in different languages (as a rule, a paper in a language other than English should include an English title and an English abstract). Use `language=...` for every language used in the paper. The last language indicated is the main language of the paper. For example, a French paper with additional titles and abstracts in English and German may start with the following command

```
\documentclass[sigconf, language=english, language=german,
               language=french]{acmart}
```

The title, subtitle, keywords and abstract will be typeset in the main language of the paper. The commands `\translatedXXX`, `XXX` begin title, subtitle and keywords, can be used to set these elements in the other languages. The environment `translatedabstract` is used to set the translation of the abstract. These commands and environment have a mandatory first argument: the language of the second argument. See `sample-sigconf-i13n.tex` file for examples of their usage.

17 SIGCHI Extended Abstracts

The "`sigchi-a`" template style (available only in LATEX and not in Word) produces a landscape-orientation formatted article, with a wide left margin. Three environments are available for use with the "`sigchi-a`" template style, and produce formatted output in the margin:

`sidebar:` Place formatted text in the margin.
`marginfigure:` Place a figure in the margin.
`margintable:` Place a table in the margin.

Acknowledgments

To Robert, for the bagels and explaining CMYK and color spaces.

References

[1] Rafal Ablamowicz and Bertfried Fauser. 2007. *CLIFFORD: a Maple 11 Package for Clifford Algebra Computations, version 11.* Retrieved February 28, 2008 from http://math.tntech.edu/rafal/cliff11/index.html

[2] Patricia S. Abril and Robert Plant. 2007. The patent holder's dilemma: Buy, sell, or troll? *Commun. ACM* 50, 1 (Jan. 2007), 36–44. doi:10.1145/1188913.1188915

[3] Sten Andler. 1979. Predicate Path expressions. In *Proceedings of the 6th. ACM SIGACT-SIGPLAN symposium on Principles of Programming Languages (POPL '79).* ACM Press, New York, NY, 226–236. doi:10.1145/567752.567774

[4] David A. Anisi. 2003. *Optimal Motion Control of a Ground Vehicle.* Master's thesis. Royal Institute of Technology (KTH), Stockholm, Sweden.

[5] Sam Anzaroot and Andrew McCallum. 2013. *UMass Citation Field Extraction Dataset.* Retrieved May 27, 2019 from http://www.iesl.cs.umass.edu/data/data-umasscitationfield

[6] Sam Anzaroot, Alexandre Passos, David Belanger, and Andrew McCallum. 2014. *Learning Soft Linear Constraints with Application to Citation Field Extraction.* arXiv:1403.1349 doi:10.48550/arXiv.1403.1349

[7] R. Baggett, M. Simecek, C. Chambellan, K. Tsui, and M. Fraune. 2025. Fluidity in the Phased Framework of Technology Acceptance: Case Study to Gain a Holistic Understanding of (Older Adult) Participant Advancement Through Acceptance Phases with Mobile Telepresence Robots. *Robotics Aut. Systems.* Manuscript submitted for review.

[8] Lutz Bornmann, K. Brad Wray, and Robin Haunschild. 2019. *Citation concept analysis (CCA)—A new form of citation analysis revealing the usefulness of concepts for other researchers illustrated by two exemplary case studies including classic books by Thomas S. Kuhn and Karl R. Popper.* arXiv:1905.12410 [cs.DL]

[9] Kenneth L. Clarkson. 1985. *Algorithms for Closest-Point Problems (Computational Geometry).* Ph. D. Dissertation. Stanford University, Palo Alto, CA. UMI Order Number: AAT 8506171.

[10] Jacques Cohen (Ed.). 1996. Special issue: Digital Libraries. *Commun. ACM* 39, 11 (Nov. 1996).

[11] Sarah Cohen, Werner Nutt, and Yehoshua Sagic. 2007. Deciding equivalances among conjunctive aggregate queries. *J. ACM* 54, 2, Article 5 (April 2007), 50 pages. doi:10.1145/1219092.1219093

[12] Bruce P. Douglass, David Harel, and Mark B. Trakhtenbrot. 1998. Statecarts in use: structured analysis and object-orientation. In *Lectures on Embedded Systems*, Grzegorz Rozenberg and Frits W. Vaandrager (Eds.). Lecture Notes in Computer Science, Vol. 1494. Springer-Verlag, London, 368–394. doi:10.1007/3-540-65193-4_29

[13] Ian Editor (Ed.). 2007. *The title of book one* (1st. ed.). The name of the series one, Vol. 9. University of Chicago Press, Chicago, Chapter The title of the chapter, 127–238. doi:10.1007/3-540-09237-4

[14] Ian Editor (Ed.). 2008. *The title of book two* (2nd. ed.). University of Chicago Press, Chicago, Chapter 100, 25–137. doi:10.1007/3-540-09237-4

[15] Matthew Van Gundy, Davide Balzarotti, and Giovanni Vigna. 2007. Catch me, if you can: Evading network signatures with web-based polymorphic worms. In *Proceedings of the first USENIX workshop on Offensive Technologies (WOOT '07).* USENIX Association, Berkley, CA, Article 7, 9 pages.

[16] Torben Hagerup, Kurt Mehlhorn, and J. Ian Munro. 1993. Maintaining Discrete Probability Distributions Optimally. In *Proceedings of the 20th International Colloquium on Automata, Languages and Programming (Lecture Notes in Computer Science, Vol. 700).* Springer-Verlag, Berlin, 253–264.

[17] David Harel. 1978. *LOGICS of Programs: AXIOMATICS and DESCRIPTIVE POWER.* MIT Research Lab Technical Report TR-200. Massachusetts Institute of Technology, Cambridge, MA.

[18] David Harel. 1979. *First-Order Dynamic Logic.* Lecture Notes in Computer Science, Vol. 68. Springer-Verlag, New York, NY. doi:10.1007/3-540-09237-4

[19] Lars Hörmander. 1985. *The analysis of linear partial differential operators. III.* Grundlehren der Mathematischen Wissenschaften [Fundamental Principles of Mathematical Sciences], Vol. 275. Springer-Verlag, Berlin, Germany. viii+525 pages. Pseudodifferential operators.

[20] Lars Hörmander. 1985. *The analysis of linear partial differential operators. IV.* Grundlehren der Mathematischen Wissenschaften [Fundamental Principles of Mathematical Sciences], Vol. 275. Springer-Verlag, Berlin, Germany. vii+352 pages. Fourier integral operators.

[21] IEEE 2004. IEEE TCSC Executive Committee. In *Proceedings of the IEEE International Conference on Web Services (ICWS '04).* IEEE Computer Society, Washington, DC, USA, 21–22. doi:10.1109/ICWS.2004.64

[22] Markus Kirschmer and John Voight. 2010. Algorithmic Enumeration of Ideal Classes for Quaternion Orders. *SIAM J. Comput.* 39, 5 (Jan. 2010), 1714–1747. doi:10.1137/080734467

[23] Donald E. Knuth. 1997. *The Art of Computer Programming, Vol. 1: Fundamental Algorithms (3rd. ed.).* Addison Wesley Longman Publishing Co., Inc., Boston.

[24] David Kosiur. 2001. *Understanding Policy-Based Networking* (2nd. ed.). Wiley, New York, NY.

[25] Leslie Lamport. 1986. *LaTeX: A Document Preparation System.* Addison-Wesley, Reading, MA.

[26] Newton Lee. 2005. Interview with Bill Kinder: January 13, 2005. Video. *Comput. Entertain.* 3, 1, Article 4 (Jan.-March 2005). doi:10.1145/1057270.1057278

[27] Dave Novak. 2003. Solder man. Video. In *ACM SIGGRAPH 2003 Video Review on Animation theater Program: Part I - Vol. 145 (July 27–27, 2003).* ACM Press, New York, NY, 4. doi:10.945/woot07-S422 http://video.google.com/videoplay?docid=6528042696351994555

[28] Barack Obama. 2008. A more perfect union. Video. Retrieved March 21, 2008 from http://video.google.com/videoplay?docid=6528042696351994555

[29] Poker-Edge.Com. 2006. Stats and Analysis. Retrieved June 7, 2006 from http://www.poker-edge.com/stats.php

[30] R Core Team. 2019. *R: A Language and Environment for Statistical Computing.* R Foundation for Statistical Computing, Vienna, Austria. https://www.R-project.org/

[31] Brian J. Reiser. 2014. Designing coherent storylines aligned with NGSS for the K-12 classroom. Presentation at National Science Education Leadership Association Meeting, Boston, MA, USA. https://www.academia.edu/6884962/

[32] Bernard Rous. 2008. The Enabling of Digital Libraries. *Digital Libraries* 12, 3, Article 5 (July 2008). To appear.

[33] Mehdi Saeedi, Morteza Saheb Zamani, and Mehdi Sedighi. 2010. A library-based synthesis methodology for reversible logic. *Microelectron. J.* 41, 4 (April 2010), 185–194.

[34] Mehdi Saeedi, Morteza Saheb Zamani, Mehdi Sedighi, and Zahra Sasanian. 2010. Synthesis of Reversible Circuit Using Cycle-Based Approach. *J. Emerg. Technol. Comput. Syst.* 6, 4 (Dec. 2010), 12 pages.

[35] Joseph Scientist. 2009. The fountain of youth. Patent No. 12345, Filed July 1st., 2008, Issued Aug. 9th., 2009.

[36] Stan W. Smith. 2010. An experiment in bibliographic mark-up: Parsing metadata for XML export. In *Proceedings of the 3rd. annual workshop on Librarians and Computers (LAC '10, Vol. 3)*, Reginald N. Smythe and Alexander Noble (Eds.). Paparazzi Press, Milan Italy, 422–431.

[37] Asad Z. Spector. 1990. Achieving application requirements. In *Distributed Systems* (2nd. ed.), Sape Mullender (Ed.). ACM Press, New York, NY, 19–33. doi:10.1145/90417.90738

[38] Harry Thornburg. 2001. *Introduction to Bayesian Statistics.* Retrieved March 2, 2005 from http://ccrma.stanford.edu/~jos/bayes/bayes.html, archived at [https://web.archive.org/web/20240505055615/https://ccrma.stanford.edu/~jos/bayes/bayes.html]

[39] TUG 2017. *Institutional members of the TEX Users Group.* Retrieved May 27, 2017 from http://wwtug.org/instmem.html

[40] Boris Veytsman. 2017. *acmart—Class for typesetting publications of ACM.* Retrieved May 27, 2017 from http://www.ctan.org/pkg/acmart

A Research Methods

A.1 Part One

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Morbi malesuada, quam in pulvinar varius, metus nunc fermentum urna, id sollicitudin purus odio sit amet enim. Aliquam ullamcorper eu ipsum vel mollis. Curabitur quis dictum nisl. Phasellus vel semper risus, et lacinia dolor. Integer ultricies commodo sem nec semper.

A.2 Part Two

Etiam commodo feugiat nisl pulvinar pellentesque. Etiam auctor sodales ligula, non varius nibh pulvinar semper. Suspendisse nec lectus non ipsum convallis congue hendrerit vitae sapien. Donec at laoreet eros. Vivamus non purus placerat, scelerisque diam eu, cursus ante. Etiam aliquam tortor auctor efficitur mattis.

B Online Resources

Nam id fermentum dui. Suspendisse sagittis tortor a nulla mollis, in pulvinar ex pretium. Sed interdum orci quis metus euismod, et sagittis enim maximus. Vestibulum gravida massa ut felis suscipit congue. Quisque mattis elit a risus ultrices commodo venenatis eget dui. Etiam sagittis eleifend elementum.

Nam interdum magna at lectus dignissim, ac dignissim lorem rhoncus. Maecenas eu arcu ac neque placerat aliquam. Nunc pulvinar massa et mattis lacinia.

C Experimental Results Summary

This section provides a comprehensive summary of the experimental results across all evaluated methods and datasets.

Received 20 February 2007; revised 12 March 2009; accepted 5 June 2009

Table 4: Experimental Results Summary across all methods and datasets.

Type	Method	Dataset	Acc.	Prec.	Rec.	F1	AUC	PR-AUC	G-Mean	BAcc.
data level	Baseline	yeast1	0.7581	0.6410	0.4025	0.4850	0.7881	0.5887	0.5976	0.6526
		yeast3	0.9477	0.8106	0.6848	0.7412	0.9570	0.7924	0.8184	0.8325
		yeast4	0.9661	0.3556	0.0970	0.1403	0.8561	0.3739	0.2219	0.5470
		yeast6	0.9798	0.4556	0.2952	0.3445	0.8999	0.5656	0.4296	0.6458
	oversampling	yeast1	0.7280	0.5356	0.6596	0.5841	0.7835	0.5737	0.7021	0.7077
		yeast3	0.9292	0.6479	0.8488	0.7290	0.9509	0.7530	0.8920	0.8940
		yeast4	0.9261	0.3308	0.4897	0.3022	0.8732	0.3626	0.6272	0.7157
		yeast6	0.9537	0.3796	0.6857	0.4355	0.9080	0.4895	0.7952	0.8230
	SMOTE	yeast1	0.7201	0.5209	0.6760	0.5831	0.7834	0.5747	0.7029	0.7070
		yeast3	0.9328	0.6561	0.8551	0.7391	0.9571	0.7664	0.8971	0.8988
		yeast4	0.9115	0.2465	0.6152	0.3315	0.8801	0.3527	0.7406	0.7686
		yeast6	0.9452	0.3202	0.7333	0.4155	0.9240	0.4788	0.8248	0.8418
	SMOTE-ENN	yeast1	0.6734	0.4657	0.7948	0.5846	0.7803	0.5666	0.7011	0.7094
		yeast3	0.9216	0.6028	0.8938	0.7177	0.9533	0.7438	0.9089	0.9094
		yeast4	0.8821	0.1900	0.6921	0.2928	0.8881	0.3371	0.7769	0.7905
		yeast6	0.9306	0.2587	0.7810	0.3724	0.9324	0.4875	0.8468	0.8576
algorithm level	RandomForest	yeast1	0.7783	0.6650	0.4803	0.5553	0.8133	0.6435	0.6561	0.6899
		yeast3	0.9447	0.7870	0.6805	0.7275	0.9706	0.8316	0.8134	0.8289
		yeast4	0.9677	0.6000	0.1364	0.2062	0.9206	0.4073	0.3206	0.5668
		yeast6	0.9831	0.7667	0.4000	0.5054	0.8997	0.5629	0.6088	0.6986
	Cost-Sensitive+ RandomForest	yeast1	0.7891	0.6979	0.4825	0.5688	0.8114	0.6420	0.6632	0.6981
		yeast3	0.9461	0.7896	0.6992	0.7396	0.9726	0.8479	0.8254	0.8379
		yeast4	0.9650	0.3333	0.1164	0.1655	0.9269	0.4298	0.2572	0.5557
		yeast6	0.9838	0.8667	0.4286	0.5305	0.8965	0.5907	0.6350	0.7129
	XGBoost	yeast1	0.7648	0.6122	0.5151	0.5569	0.7847	0.6034	0.6662	0.6907
		yeast3	0.9434	0.7567	0.7176	0.7354	0.9612	0.7726	0.8338	0.8444
		yeast4	0.9629	0.4503	0.2764	0.3241	0.9165	0.3767	0.5024	0.6319
		yeast6	0.9771	0.5267	0.4857	0.4992	0.9246	0.5340	0.6875	0.7373
	Cost-Sensitive+ XGBoost	yeast1	0.7561	0.5765	0.5989	0.5861	0.7859	0.6012	0.6998	0.7094
		yeast3	0.9468	0.7482	0.7852	0.7649	0.9615	0.7895	0.8709	0.8760
		yeast4	0.9582	0.4230	0.3945	0.3932	0.9107	0.4053	0.6066	0.6865
		yeast6	0.9764	0.4984	0.5714	0.5294	0.9242	0.5515	0.7399	0.7788
	AdaBoost (depth=1)	yeast1	0.7601	0.6293	0.4219	0.5045	0.7878	0.5760	0.6152	0.6598
		yeast3	0.9508	0.7891	0.7725	0.7770	0.9721	0.7808	0.8664	0.8726
		yeast4	0.9623	0.3500	0.1945	0.2439	0.9217	0.3758	0.3814	0.5920
		yeast6	0.9831	0.7000	0.4857	0.5655	0.9380	0.5549	0.6836	0.7404
	Cost-Sensitive+ AdaBoost	yeast1	0.6658	0.4496	0.6922	0.5449	0.6736	0.4009	0.6729	0.6736
		yeast3	0.8956	0.5169	0.9203	0.6610	0.9470	0.7058	0.9061	0.9064
		yeast4	0.8922	0.2093	0.7436	0.3251	0.9190	0.2352	0.8154	0.8205
		yeast6	0.8956	0.1608	0.8000	0.2655	0.8972	0.2441	0.8374	0.8489
Hybrid Method	AdaBoost (depth=5)	yeast1	0.7540	0.5853	0.5196	0.5470	0.7821	0.5880	0.6612	0.6845
		yeast3	0.9421	0.7577	0.6928	0.7231	0.9591	0.7695	0.8199	0.8328
		yeast4	0.9650	0.5500	0.1964	0.2727	0.9312	0.4115	0.3923	0.5943
		yeast6	0.9778	0.5500	0.3714	0.4392	0.8979	0.4859	0.6043	0.6819
	SMOTEBoost	yeast1	0.7473	0.5560	0.6294	0.5903	0.7718	0.5543	0.7074	0.7123
		yeast3	0.9468	0.7530	0.7725	0.7611	0.9596	0.7989	0.8641	0.8704
		yeast4	0.9535	0.3799	0.3946	0.3730	0.9147	0.4122	0.6148	0.6840
		yeast6	0.9778	0.5101	0.6286	0.5539	0.9147	0.5500	0.7704	0.8074
	RUSBoost	yeast1	0.7156	0.5171	0.6085	0.5498	0.7558	0.5147	0.6728	0.6839
		yeast3	0.9003	0.5325	0.9203	0.6731	0.9348	0.5969	0.9090	0.9090
		yeast4	0.8255	0.1469	0.8418	0.2499	0.8847	0.1846	0.8321	0.8333
		yeast6	0.7864	0.0856	0.8286	0.1548	0.8265	0.0983	0.8009	0.8070
	RHSBoost	yeast1	0.7507	0.5613	0.6456	0.5993	0.7910	0.5896	0.7148	0.7195
		yeast3	0.9191	0.5901	0.9015	0.7115	0.9546	0.6852	0.9111	0.9114
		yeast4	0.8396	0.1545	0.8036	0.2584	0.8824	0.1807	0.8210	0.8223
		yeast6	0.8679	0.1359	0.8571	0.2340	0.8675	0.1328	0.8580	0.8627
	SUBoost	yeast1	0.7224	0.5297	0.5408	0.5277	0.7571	0.5586	0.6512	0.6685
		yeast3	0.9394	0.7743	0.6267	0.6877	0.9548	0.7286	0.7778	0.8024
		yeast4	0.9589	0.4417	0.2746	0.3146	0.8879	0.3961	0.4581	0.6289
		yeast6	0.9771	0.5343	0.4286	0.4462	0.8706	0.4566	0.6227	0.7095
	SMOTECSL	yeast1	0.5492	0.3855	0.9416	0.5470	0.7931	0.5956	0.6053	0.6656
		yeast3	0.8538	0.4260	0.9510	0.5883	0.9688	0.8093	0.8947	0.8964
		yeast4	0.6874	0.0877	0.8618	0.1591	0.8535	0.1488	0.7648	0.7715
		yeast6	0.7540	0.0865	0.9429	0.1573	0.9100	0.3574	0.8363	0.8462