

Assessing GNSS-derived displacements at the near and far-field of the 2023 Turkey earthquake doublet



Panagiotis Psimoulis^a, Dimitrios Anastasiou^b, Xanthos Papanikolaou^b, Maria Tsakiri^b

^a Faculty of Engineering, University of Nottingham

^b School of Rural, Surveying & Geoinformatics Engineering, National Technical University of Athens

39th GENERAL ASSEMBLY OF THE EUROPEAN SEISMOLOGICAL COMMISSION (ESC2024)
Corfu - Greece | September 22-27, 2024



Introduction

Processing & Analysis

Current Status & Future Work

Currently

References

Contact Information

- Web: dionysos.survey.ntua.gr
- Email: danastasiou@mail.ntua.gr

test

Network & Data processing

57 continuously operating GNSS stations in distances ranging from 900km to 1400km from the epicenter Receiver type: LEICA

- most of them GR30

- also GRX1200GGPRO / GRX1200+GNSS

Antenna type LEICA

- LEIAR10 / LEIAS10

- few stations: LEIAX1202GG

Observation interval: 1s

Precise Point Positioning w Ambiguity Resolution

Sat systems:

GPS / GLO / GAL / BDS-2/3

Elevation angle: 7 deg

–Kinematic mode

Reference Frame: IGS20

Final IGS Products for satellite:

- Orbits (.SP3)

- Clocks (.CLK)

- Earth Orientation Parameters (.ERP)

- Attitude (.OBX)

- Bias (.BIA)

ANTEX File: IGS20_2247

For Tropospheric modeling: VMF1




Figure 1:Processed stations.

