

## rightTo3.java

```
* Generated by SAE Prolog - www.opal-project.de
package predicates;

import saere.*;

public final class rightTo3 implements Goal {
    // variables to control/manage the execution this predicate
    private int clauseToExecute/* = 0; */;
    private int goalToExecute/* = 0; */;
    private GoalStack goalStack = GoalStack.EMPTY_GOAL_STACK;
    // variables related to the predicate's state
    private Term arg0;
    private Term arg1;
    private Term arg2;
    final private State initialArg0state;
    final private State initialArg1state;
    final private State initialArg2state;
    // variables to store clause local information
    private Term clv0;

    public rightTo3(final Term arg0, final Term arg1, final Term arg2) {
        this.arg0 = arg0;
        this.arg1 = arg1;
        this.arg2 = arg2;
        this.initialArg0state = (arg0).manifestState();
        this.initialArg1state = (arg1).manifestState();
        this.initialArg2state = (arg2).manifestState();
    }

    public void abort() {
        if (this.initialArg0state != null)
            this.initialArg0state.reincarnate();
        if (this.initialArg1state != null)
            this.initialArg1state.reincarnate();
        if (this.initialArg2state != null)
            this.initialArg2state.reincarnate();
        this.goalStack = goalStack.abortPendingGoals();
    }

    public boolean choiceCommitted() {
        return false;
    }

    public boolean next() {
```

rightTo3.java

```
eval_clauses: do {
    switch (this.clauseToExecute) {
    case 0: {
        if (this.clause0()) {
            return true;
        }
        // this clause contains no "cut"
        // prepare the execution of the next clause
        this.goalToExecute = 0;
        this.clauseToExecute = 1;
    }
    case 1: {
        // tail recursive clause with last call optimization
        if (this.clause1()) {
            this.clv0 = null;
            this.goalToExecute = 0;
            this.clauseToExecute = 0;
            continue eval_clauses;
        }
        this.abort();
        return false;
    }
    }
} while (true);
}

private boolean clause0() {
    switch (this.goalToExecute) {

    case 0: {
        this.goalStack = goalStack.put(UndoGoal.create
(arg0,arg1,arg2));
        if (arg2.unify(list(arg0, list(arg1, variable())))) {
            this.goalToExecute = 1;
            return true;
        }
    }
    case 1: {
        this.goalStack = goalStack.abortTopLevelGoal();
        return false;
    }

    // case 0: {
    //     this.goalStack = goalStack.put(new Unify2(arg2, list(arg0,
```

## rightTo3.java

```
list(arg1, variable()))));
//      }
//      case 1: {
//          boolean succeeded = this.goalStack.peek().next();
//          if (!succeeded) {
//              this.goalStack = goalStack.drop();
//              return false;
//          }
//          this.goalToExecute = 1;
//          return true;
//      }
//      default:
//          // should never be reached
//          throw new Error("internal compiler error");
//      }
}

private boolean clause1() {
    eval_goals: do {
        switch (this.goalToExecute) {
            case 0: {
                // [arg(2), clv(0)]
                this.clv0 = variable();
                this.goalStack = goalStack.put(new Unify2(arg2, list
(variable(), clv0)));
            }
            case 1: {
                boolean succeeded = this.goalStack.peek().next();
                if (!succeeded) {
                    this.goalStack = goalStack.drop();
                    return false;
                }
                // fall through ... 2
            }
            case 2: {
                // tail call with last call optimization
                this.arg0 = arg0;
                this.arg1 = arg1;
                this.arg2 = clv0;
                this.goalStack = GoalStack.EMPTY_GOAL_STACK;
                return true;
            }
        }
    } while (true);
}
```

rightTo3.java

```
}  
}
```