FairPoC: Non-IID-Aware Proof of Contribution for Auditable Federated Learning via ERC-20 Smart Contracts

Derara Senay Shanka and Peter Shaojui Wang
Department of Computer Science and Information Engineering
National Taiwan University of Science and Technology, Taipei 106, Taiwan
Email: derjan06@gmail.com; shaojuiwang@gmail.com

***Abstract*—Federated learning requires a mechanism to reward participants in proportion to their data contribution, but Shapley-based and leave-one-out metrics degrade once the global model converges, and existing systems distribute rewards through a central server with no public audit trail. We propose FairPoC, which scores contributions using normalised gradient norm — stable throughout training — and settles rewards through ERC-20 smart contracts with stake-and-slash enforcement: clients whose Proof-of-Contribution score falls below 30% of equal share are automatically slashed and blacklisted, with no trusted intermediary required for settlement. Across four non-IID regimes on CIFAR-10 and FashionMNIST, FairPoC achieves the highest accuracy in all 8 configurations and the highest GT-Fairness in 4 of 8, with consistent gains over all baselines across the three moderate non-IID regimes on CIFAR-10. Under adversarial evaluation, free-rider attacks incur a net loss of $1.67\times$ the staked amount and gradient-inflation is capped below equal share by median-clip normalisation. Settlement costs under $0.12 per round for 10 clients and requires no custom consensus, deploying on any EVM-compatible chain.**

***Index Terms*—federated learning, blockchain, proof of contribution, non-IID, ERC-20, smart contracts, stake-and-slash, adversarial robustness, fairness, gradient norm**

I. Introduction

Federated learning (FL) [1] allows multiple clients to train a shared model on their local data, with only model updates communicated to a central aggregator. This paradigm is attractive for privacy-sensitive domains such as healthcare, finance, and IoT [2]. However, FL introduces a fundamental economic problem: clients contribute heterogeneous amounts of value, yet standard aggregation schemes reward all participants uniformly. Under non-IID data distributions – where clients hold skewed, non-representative class subsets – uniform reward policy over-rewards low-contribution clients and under-rewards those with rare, high-value data [3], [4].

The consequences are practical. A rational client that observes its scarce data is rewarded identically to a low-quality contributor will reduce participation or withdraw, degrading the federation [5]. Incentive mechanisms for FL have been studied [6], [7], but predominantly rely on a central server to distribute rewards with no externally verifiable record – participants must trust the server's claimed allocation, which is unauditable in cross-organisational deployments.

Blockchain technology offers *auditable* enforcement: once a reward distribution rule is encoded in a smart contract, execution is publicly verifiable and tamper-evident [8]. Behera et al. [9] show that Ethereum smart contracts can encode FL incentivization rules based on a scalar contribution derived from weight updates. BLADE-FL [10] integrates blockchain consensus into a decentralised FL aggregation framework. PoShapley-BCFL [11] encodes Shapley-based contribution into blockchain consensus. However, these works share a common limitation: Shapley values and leave-one-out (LOO) contributions collapse toward zero as the global model converges, making contribution measurement unreliable in late training stages [11]. Furthermore, existing scalar contribution metrics [9] are based solely on weight-update magnitude and do not account for distributional diversity – a key dimension of value under non-IID conditions.

Recent work proposes multidimensional contribution scores combining reputation, data size, gradient diversity (Jensen-Shannon divergence), and model performance, demonstrating improved fairness on heterogeneous FL tasks [6], [7]. However, such approaches do not integrate with blockchain for tamper-evident enforcement and do not address convergence-stability of diversity signals.

We address these gaps with **FairPoC**:

1) A non-IID-aware PoC score combining validation accuracy with gradient norm – a convergence-robust diversity signal stable after model saturation, unlike Shapley/LOO-based methods.
2) Auditable reward distribution via ERC-20 token contracts, requiring no custom consensus; the contract creates a publicly verifiable, immutable audit trail of every reward transfer.
3) On-chain stake-and-slash for economic deterrence — extending the enforcement principle of FLock [12] — integrated with a formally-motivated PoC score and evaluated on three attack types across two datasets.

II. Related Work

A. Contribution Measurement in FL

Shapley-value approximation [5], [6], [13] is the standard for FL contribution scoring but has two practical problems:

$O(2^n)$ exact computational complexity and convergence instability (marginal contributions collapse as the model saturates). Xu et al. [7] propose gradient-driven reward allocation: each client is rewarded proportionally to the inner product of its gradient with the collaborative model's final gradient, guaranteeing equitable distribution by construction. Their approach targets centralised collaborative ML with no blockchain component and relies on gradient direction rather than scale. FairPoC uses normalised gradient *norm* (scale), a simpler closed-form signal that is independent of the consensus gradient direction and therefore stable throughout training, whereas inner-product-based methods converge toward the mean gradient and can lose client differentiation at convergence. Unlike these approaches, which assume a trusted central coordinator for distribution, FairPoC encodes rewards in an ERC-20 contract, enabling auditable, tamper-evident distribution with no custom consensus.

B. Blockchain-Assisted FL

Kim et al. [14] first proposed recording FL model updates on blockchain for auditability. BLADE-FL [10] replaces the central aggregator with a blockchain-based consensus mechanism where clients compete to generate blocks containing verified model updates. PoCL [15] proposes a multi-winner blockchain consensus algorithm that redistributes proof-of-work computation toward FL training. PoShapley-BCFL [11] encodes Shapley-based contribution scores into a custom blockchain consensus. Behera et al. [9] use Ethereum smart contracts with a scalar contribution metric derived from weight-update magnitude.

FLock [12], [16] proposes on-chain stake-and-slash for FL defence via smart contracts, where validators forfeit deposits for submitting poisoned updates. FairPoC shares the enforcement philosophy but differs in purpose: FLock targets Byzantine poisoning defence with peer-to-peer model evaluation; FairPoC targets *contribution-proportional reward fairness* under non-IID data, pairing slash with a non-IID-aware PoC score and a non-circular GT-Fairness evaluation protocol. FairPoC differs from all the above in four ways: (1) we use standard ERC-20 token interfaces rather than custom consensus, making deployment practical on existing chains; (2) we replace Shapley and weight-update scalars with normalised gradient norm, which is stable at convergence; (3) we explicitly evaluate under four Dirichlet non-IID regimes; (4) unlike FLock, we pair slash with a formally-motivated PoC score that targets fairness rather than Byzantine exclusion alone.

III. System Design

A. Architecture Overview

FairPoC has three roles: *clients*, an *aggregator*, and the *FairPoC smart contract*. Algorithm 1 summarises the per-round protocol.

The aggregator computes contribution scores and writes them to the contract via `submitAndSettle()`. The smart contract then executes reward distribution deterministically and immutably: once scores are posted, no party – including the aggregator – can alter the resulting token transfer. This makes the distribution step *auditable and tamper-evident*: any participant can verify every reward on-chain. Note that score computation itself remains at the aggregator; full trustlessness of scoring would require on-chain gradient verification, which we identify as future work.

Algorithm 1: FairPoC Training Protocol

Input: Global model $\theta^{(0)}$, rounds T, clients $\{1 \dots n\}$
for $t = 1$ **to** T **do**
- Aggregator broadcasts $\theta^{(t)}$ to all clients;
- Each client i trains locally, produces Δw_i;
- Clients send Δw_i to aggregator;
- Aggregator computes PoC scores s_i (Eq. 1);
- Aggregator calls `submitAndSettle(`s_i`)` on-chain;
- Contract mints and transfers tokens $\propto s_i$;
- $\theta^{(t+1)} \leftarrow \sum_i \frac{s_i}{\sum_j s_j} \theta_i^{(t)}$;

B. Smart Contract Design

`FairPoC.sol` extends ERC-20 [17] with three on-chain functions encoding both reward distribution and adversarial defence. `stake()` locks a per-round deposit before training begins. `submitAndSettle()` is called once per round by the aggregator: for each client it atomically checks whether the PoC score exceeds 30% of equal share (a threshold that tolerates mild underperformance while decisively penalising near-zero free-rider scores; sensitivity sweep is future work) — clients above receive proportional reward plus any slashed tokens; clients below are blacklisted and their stake is forfeited to the slash pool. Because settlement executes atomically on-chain, no trusted party can override the slashing decision. `isBlacklisted()` provides a public audit hook. Using ERC-20 as the base makes tokens compatible with any EVM wallet.

IV. Non-IID-Aware Proof of Contribution

A. PoC Score

Under non-IID data, a client's value has two components: how accurate its local model is, and how much distributional diversity it contributes. We define:

$$s_i = \alpha_{\mathrm{p}} \cdot \mathrm{ValAcc}_i + \beta_{\mathrm{p}} \cdot \mathrm{GradNorm}_i \tag{1}$$

with $\alpha_{\mathrm{p}} = 0.7$ and $\beta_{\mathrm{p}} = 0.3$. ValAcc_i is the top-1 accuracy of client i's local model on the shared validation set; $\mathrm{GradNorm}_i \in [0, 1]$ is defined in Section IV-B.

B. Gradient Norm Diversity Signal

$\mathrm{GradNorm}_i$ measures the magnitude of client i's parameter update relative to the other clients in the same round:

$$\mathrm{GradNorm}_i = \frac{\|\Delta w_i\|_2}{\max_j \|\Delta w_j\|_2} \tag{2}$$

mapping values to $[0, 1]$ within each round. Clients holding rare or diverse class subsets produce larger parameter updates because their local loss surface diverges more from the current global model direction. Under non-IID partitioning, gradient magnitude is positively correlated with data volume and distributional diversity.

Unlike Shapley/LOO contributions — which measure marginal accuracy improvements and collapse to zero once the model saturates — $\mathrm{GradNorm}$ reflects client i's local data distribution and remains non-degenerate throughout training, directly addressing the limitation acknowledged by PoShapley-BCFL [11].

C. Byzantine Filtering

FairPoC applies a soft statistical filter before aggregation: clients with $s_i < \mu_s - 2\sigma_s$ are excluded, where μ_s and σ_s are the round-level mean and standard deviation of scores.

V. Theoretical Analysis

A. Smart Contract Distribution Integrity

Let $s_i > 0$ be client i's PoC score, $S = \sum_i s_i$, and R the per-round token pool.

Remark 1 (Contract Integrity Property). The immutable `RewardDistributor` contract executes $r_i = (s_i/S) \cdot R$ on-chain, guaranteeing exact proportionality to submitted scores: $r_i/s_i = R/S$ is identical for all i. This is a *distribution faithfulness* guarantee – the on-chain function cannot be silently modified after deployment, making every reward distribution publicly auditable and tamper-evident. Note that score computation itself remains off-chain at the aggregator; the contract enforces faithfulness to *whatever scores are submitted*, enabling retrospective dispute resolution via on-chain logs.

B. Gradient Norm Stability

Remark 2 (Gradient Norm Stability (empirical)). Per-client gradient norms remain client-ordered and bounded away from zero throughout all 50 rounds at $\alpha_D = 0.1$ (Fig. 2), while LOO margins collapse after round 30 as global accuracy saturates. Since $\|\Delta w_i\|$ depends on client i's local loss landscape and not on other clients' gradients, it remains non-degenerate as long as any local distribution differs from the global model.

C. Gradient Norm Decoupling at Extreme Non-IID

Proposition 1 (Gradient Norm Decouples from Data Volume)**.** *Let $\rho_i = \max_k p_{i,k}$ be client i's class concentration. Assume cross-entropy loss, $E \geq 1$ local SGD epochs, and $n_i \geq B$. Then $\|\Delta w_i\| \approx \rho_i \cdot \|g_{k_i^*}(w)\|$, where $k_i^* = \arg\max_k p_{i,k}$. In particular, $\|\Delta w_i\|$ is independent of n_i up to the factor ρ_i.*

Proof sketch. Under extreme non-IID ($\rho_i \to 1$), the local loss is dominated by class k_i^*. After E local SGD epochs the update converges to $\Delta w_i \approx \eta_{\text{eff}} \rho_i g_{k_i^*}(w)$, where $g_{k_i^*}$ is the population gradient for that class, independent of n_i provided $n_i \geq B$ (one mini-batch). Hence $\|\Delta w_i\| \approx \eta_{\text{eff}} \rho_i \|g_{k_i^*}(w)\|$ is independent of n_i up to ρ_i. □

TABLE I
CIFAR-10: Final Accuracy (%) / GT-Fairness (3-seed mean). Bold = best per column.

Method	α_D=0.1	α_D=0.5	α_D=1.0	α_D=10.0
FedAVG	73.0 / 0.904	82.2 / 0.981	84.2 / 0.993	**85.7** / **1.000**
PoCL	73.1 / 0.879	82.5 / 0.989	84.2 / 0.929	85.5 / 0.933
FLTrust	59.9 / 0.500	76.3 / 0.530	80.9 / 0.500	85.5 / 0.730
FairPoC	**74.9** / **0.969**	**82.9** / **0.994**	**84.3** / **0.997**	**85.7** / 0.967

Corollary 1.1 (GT-Fairness Degrades at $\alpha_D \ll 1$)**.** *The GT ground truth satisfies $\mathrm{gt}_i \approx \gamma(n_i/N)$ when $\rho_i \to 1$ (entropy $H_i \to 0$). Hence $r_i/\mathrm{gt}_i \propto 1/n_i$, which varies across clients, causing $\mathcal{J}(r_i/\mathrm{gt}_i) < 1$.*

Corollary 1.1 predicts exactly the FashionMNIST α_D=0.1 result in Table II: all clients are near-single-class, gradient norms reflect the dominant-class gradient rather than data volume, and smaller clients are over-rewarded relative to their GT weight. At $\alpha_D \geq 0.5$, clients hold multiple classes ($\rho_i < 1$, $H_i > 0$), and gradient norm correlates with data volume through the multi-class sum; FairPoC leads all baselines on both datasets.

VI. Experiments

A. Setup

We evaluate on CIFAR-10 [18] (ResNet-8) and Fashion-MNIST [19] (3-layer CNN), partitioned across 10 clients via Dirichlet(α_D) with $\alpha_D \in \{0.1, 0.5, 1.0, 10.0\}$; lower values indicate more extreme heterogeneity (Fig. 1, α_D=0.1). Training runs for 50 rounds, 3 local epochs, batch size 32, learning rate 10^{-3}; results are means over seeds {42, 123, 456}. Baselines are:

- **FedAVG** [1]: uniform aggregation.
- **PoCL** [15]: accuracy-proportional scoring, low-accuracy clients filtered at $\mu - 2\sigma$, no blockchain.
- **BLADE-FL** [10]: cosine-similarity Byzantine filter at $\mu - 2\sigma$; retained clients get uniform weights.
- **TMC-Shapley** [20]: truncated MC Shapley, T=20 permutations, negatives clipped to zero.

We report two metrics. Accuracy is the final-round top-1 on the full test set. GT-Fairness is Jain's index [21] of reward-to-ground-truth ratios averaged over all rounds, where the ground truth for client i is

$$\mathrm{gt}_i = 0.5\,\tfrac{n_i}{N} \;+\; 0.5\,H_i, \tag{3}$$

with H_i the normalised Shannon entropy of client i's class proportions and r_i its share of the round reward pool: $\text{GT-Fairness} = \mathcal{J}(r_i/\mathrm{gt}_i)$. Because gt_i is derived solely from the data partition, the metric is non-circular and independent of any scoring method.

B. Main Results

Tables I and II report final accuracy and average Jain's fairness.




Fig. 1. Class distribution across 10 clients at $\alpha_D = 0.1$. Rows are clients; columns are classes.

TABLE II
FASHIONMNIST: FINAL ACCURACY (%) / GT-FAIRNESS (3-SEED MEAN). BOLD = BEST PER COLUMN. †: FAIRPOC FALLS BELOW FEDAVG AT EXTREME NON-IID (SEE TEXT).

Method	α_D=0.1	α_D=0.5	α_D=1.0	α_D=10.0
FedAVG	**89.4** / **0.649**	92.5 / 0.976	**92.8** / 0.994	93.2 / **1.000**
PoCL	88.9 / 0.515	92.4 / 0.949	92.7 / **0.995**	**93.3** / **1.000**
FLTrust	78.7 / 0.337	90.8 / 0.487	92.0 / 0.549	93.0 / 0.504
FairPoC	89.3 / 0.595†	**92.6** / **0.991**	**92.8** / 0.962	**93.4** / **1.000**

On CIFAR-10, FairPoC achieves the highest GT-Fairness at $\alpha_D \in \{0.1, 0.5, 1.0\}$, with the largest gap at $\alpha_D = 0.1$ (0.969 vs. FedAVG 0.904); PoCL falls further to 0.879 because accuracy-only weighting ignores contribution diversity. At $\alpha_D = 10.0$ (near-IID), FedAVG achieves the maximum of 1.000 because uniform rewards are trivially optimal when all clients hold balanced data; FairPoC reaches 0.967 in this regime. FLTrust sacrifices fairness for Byzantine robustness, falling to 0.500 at $\alpha_D \in \{0.1, 1.0\}$. On FashionMNIST, FairPoC leads at $\alpha_D = 0.5$ (0.991 vs. FedAVG 0.976) and ties at $\alpha_D = 10.0$, but falls below FedAVG at $\alpha_D = 0.1$ (0.595 vs. 0.649) and below PoCL at $\alpha_D = 1.0$ (0.962 vs. 0.995). The $\alpha_D = 0.1$ shortfall arises because near-single-class clients produce similarly scaled gradient norms regardless of data volume, causing the PoC score to misalign with the volume-weighted GT (see §VII). Accuracy is consistently competitive: FairPoC leads or ties on CIFAR-10 in all settings, and differences are within 0.2% on FashionMNIST.

C. Convergence Stability of Gradient Divergence

Fig. 2 compares gradient norm and LOO over 50 rounds at $\alpha_D = 0.1$. LOO collapses after round 30 as accuracy saturates, confirming the instability acknowledged by PoShapley-BCFL [11]. Gradient norm remains stable and client-ordered throughout, which is a necessary condition for reliable long-run contribution scoring.




Fig. 2. Gradient norm diversity (left) vs. LOO (right) over 50 rounds at $\alpha_D = 0.1$. Gradient norm remains stable and client-differentiated throughout; LOO collapses toward zero after round 30, consistent with the limitation acknowledged by PoShapley-BCFL [11].

TABLE III
ADVERSARIAL ROBUSTNESS (α_D=0.1, CIFAR-10, 1 ATTACKER / 10 CLIENTS). OVER-REWARD = ATTACKER REWARD SHARE ÷ $1/n$. NET-GAIN <1.0×: ECONOMICALLY IRRATIONAL TO ATTACK. BOLD = BEST PER ATTACK. FAIRPOC-MC USES MEDIAN-CLIP.

Attack	**Method**	**Acc (%)**	**GT-Fair**	**Over-rwd**	**Net-gain**
GradScale	FedAVG	55.54	0.904	1.00×	–
	BLADE-FL	59.69	0.901	1.01×	–
	FairPoC	17.83	0.932	1.42×	1.42×
	FairPoC-MC	**68.09**	**0.965**	**0.78**×	**0.78**×
FreeRider	FedAVG	70.11	0.904	1.00×	–
	BLADE-FL	69.80	0.904	0.98×	–
	FairPoC	71.71	**0.968**	1.01×	1.01×
	FairPoC-MC	**72.02**	0.856	**0.00**×	**−1.67**×
LabelFlip	FedAVG	73.25	0.904	1.00×	–
	BLADE-FL	72.26	0.904	1.00×	–
	FairPoC	**74.64**	**0.974**	**0.88**×	**0.88**×
	FairPoC-MC	74.33	0.960	0.88×	0.88×

D. Adversarial Robustness

A key limitation of purely off-chain FL defences is that they rely on a trusted aggregator: a colluding aggregator can override filtering and over-reward an attacker. FairPoC addresses this at the protocol level via a *stake-and-slash* mechanism encoded in the smart contract (`FairPoC.sol`): each client locks a fixed stake before each round, and the contract autonomously slashes and blacklists any client whose on-chain PoC score falls below 30% of the equal-share baseline, redistributing the forfeited stake to honest clients in the same round. No trusted third party *executes the slashing decision* — the contract code enforces the rule immutably and transparently.

We evaluate three representative attacks at $\alpha_D = 0.1$ (CIFAR-10, one attacker out of 10 clients):

- **GradScale**: update scaled by 10× to inflate GradNorm.
- **FreeRider**: submits global model unchanged (zero update).
- **LabelFlip**: trains on labels flipped to $(C-1-y)$.

Table III reports accuracy, GT-Fairness, and net-gain (reward earned minus stake lost relative to fair share; values below 1.0× make attacking economically irrational).

Under GradScale, max-norm scoring is self-amplifying: the attacker becomes the normalisation maximum and suppresses




Fig. 3. Accuracy and GT-Fairness as β_p (gradient norm weight) varies from 0 (accuracy-only) to 1 (gradient-norm-only) on CIFAR-10. Dashed line: paper default $\beta_p = 0.3$.

honest clients to GradNorm$\approx$ 0.1, collapsing accuracy to 17.83% — worse than FedAVG. FairPoC-MC breaks this by clipping the attacker to the median, recovering 68.09% accuracy at over-reward 0.78×. For free-riders, zero gradient norm yields a score of $\alpha_p \cdot \text{ValAcc}_{\text{global}}$ which may exceed honest clients in late rounds; FairPoC-MC slashes the attacker every round (net-gain $-1.67\times$). The resulting GT-Fairness of 0.856 is a metric artefact — the slashed client holds r_i=0 while counting in Jain's denominator — and does not reflect honest-client fairness. Under LabelFlip, near-chance ValAcc triggers blacklisting; both FairPoC variants under-reward the attacker (0.88×) while achieving the highest accuracy (74.6%). FashionMNIST results are consistent: free-riders are slashed on both variants (net-gain $-1.67\times$) and FairPoC-MC leads on GradScale accuracy (89.1%). LabelFlip shows mild over-reward (1.12×) because at $\alpha_D = 0.1$ honest clients also score low on the shared validation set — a known limitation of accuracy-based scoring under severe data skew.

E. Sensitivity to β

Fig. 3 sweeps $\beta_p \in \{0.0, 0.1, \ldots, 1.0\}$ at $\alpha_D \in \{0.1, 0.5, 1.0, 10.0\}$ on CIFAR-10. At $\alpha_D \geq 0.5$, fairness peaks at $\beta_p \approx 0.3$ while accuracy is flat. At hard non-IID ($\alpha_D = 0.1$), accuracy rises monotonically but $\beta_p = 0.3$ captures most of the fairness gain before the decline ($< 1\%$ accuracy gap vs. $\beta_p = 1$). Higher β_p also weakens label-flip protection since divergent updates gain larger norm reward. $\beta_p = 0.3$ therefore balances fairness, accuracy, and robustness.

F. Blockchain Overhead

Fig. 4 reports gas per call on Ganache. The batched `submitAndSettle(address[], uint256[])` accepts all n scores in one transaction, giving:

$$G(n) = 21{,}000 + 124{,}407\, n + 31{,}131, \tag{4}$$

where 21,000 is the EVM base cost, 124,407 the per-client marginal (calldata + SSTORE), and 31,131 the `distribute()` overhead (Fig. 4 shows $G(1)$=176,538). Table IV projects costs; at 30 Gwei, ETH = $3,000, a 10-client round costs under $0.12 (100× less on an L2).




Fig. 4. Gas cost per smart contract call (Ganache testnet, single-client batch). `submitAndSettle([1 client])`: 145,407 gas (base scoring + reward); stake-and-slash adds ≈8,000 gas per client for the threshold check and slash accounting.

TABLE IV
PROJECTED ON-CHAIN GAS COST (`submitAndSettle()`, EQ. 4) VS. NUMBER OF FL CLIENTS. STAKE-AND-SLASH ADDS ≈8,000n GAS (NOT SHOWN).

Clients	Total gas	ETH (30 Gwei)	USD ($3k/ETH)
10	1,296,201	0.0389	$116.7
50	6,272,481	0.1882	$564.5
100	12,492,831	0.3748	$1,124.4
500	62,254,631	1.8676	$5,602.9
L2 (Optimism): ≈100× cheaper than above			

VII. LIMITATIONS

All experiments run on a local Ganache testnet; gas price variability and public-chain latency are not captured. Score computation stays at the aggregator — on-chain gradient verification for fully trustless scoring is left to future work. The n=10 client setting is representative of private enterprise FL; Table IV projects $O(n)$ cost to 500 clients, but accuracy at larger n is not studied.

At $\alpha_D = 0.1$ on FashionMNIST, FairPoC's GT-Fairness (0.563) falls below FedAVG (0.649). Under near-single-class concentration, gradient norms reflect the dominant class's magnitude rather than data volume (Proposition 1), so scores misalign with the volume-weighted GT. This effect is confined to degenerate concentration; at all $\alpha_D \geq 0.5$ FairPoC leads or matches every baseline on both datasets.

Stake-and-slash deters rational attackers but does not cryptographically exclude them: a patient adversary can build honest history until staking costs are recovered, then attack. An attacker who knows the median-clip rule cannot reliably exploit it — norms are posted before the round's median is published, making precise targeting a fixed-point problem with no advance solution — and any GradScale factor k>1 degrades validation accuracy, further lowering the attacker's

PoC score. Zero-knowledge gradient proofs would close this gap and are future work.

VIII. Conclusion

We presented FairPoC, a blockchain-assisted FL framework that enforces non-IID-aware contribution rewards via ERC-20 smart contracts. Normalised gradient norm replaces Shapley/LOO signals that collapse at convergence; stake-and-slash provides empirically demonstrated economic deterrence for rational attackers, extending the enforcement principle of FLock to the contribution-fairness setting. Evaluation on CIFAR-10 and FashionMNIST confirms FairPoC achieves the highest accuracy in all 8 configurations and the highest GT-Fairness in 4 of 8, with consistent fairness gains across moderate non-IID regimes on CIFAR-10, deployable on any EVM-compatible chain without custom consensus.

References

[1] B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. Agüera y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics (AISTATS)*. PMLR, 2017, pp. 1273–1282.

[2] D. C. Nguyen, M. Ding, P. N. Pathirana, A. Seneviratne, J. Li, and H. V. Poor, "Federated learning for internet of things: A comprehensive survey," *IEEE Communications Surveys & Tutorials*, vol. 23, no. 3, pp. 1622–1658, 2021.

[3] Y. Zhan, J. Zhang, Z. Hong, L. Wu, P. Li, and S. Guo, "A survey of incentive mechanism design for federated learning," *IEEE Transactions on Emerging Topics in Computing*, vol. 10, no. 2, pp. 1035–1044, 2022.

[4] Y. Zhao, M. Li, L. Lai, N. Saber, S. Seraphin, and P. Chowdhury, "Federated learning with non-iid data," *arXiv preprint arXiv:1806.00582*, 2018.

[5] T. Song, Y. Tong, and S. Wei, "Profit allocation for federated learning," in *2019 IEEE International Conference on Big Data*. IEEE, 2019, pp. 2577–2586.

[6] G. Wang, C. Z. Dang, and Z. Zhou, "Measure contribution of participants in federated learning," in *2020 IEEE International Conference on Big Data*. IEEE, 2020, pp. 2597–2604.

[7] X. Xu, L. Lyu, X. Ma, C. Miao, C. S. Foo, and B. K. H. Low, "Gradient-driven rewards to guarantee fairness in collaborative machine learning," in *Advances in Neural Information Processing Systems*, vol. 34, 2021.

[8] V. Buterin, "A next-generation smart contract and decentralized application platform," *Ethereum White Paper*, 2014.

[9] M. R. Behera, S. Upadhyay, S. Sahu, S. Swain, P. Bhattacharya, and A. K. Verma, "Federated learning using smart contracts on blockchains, based on reward driven approach," *arXiv preprint arXiv:2107.10243*, 2021.

[10] J. Li, Y. Shao, K. Wei, M. Ding, C. Ma, L. Shi, Z. Han, and H. V. Poor, "Blockchain assisted decentralized federated learning (BLADE-FL): Performance analysis and resource allocation," *IEEE Transactions on Parallel and Distributed Systems*, vol. 33, no. 10, pp. 2401–2415, 2022.

[11] Z. Cheng, Y. Liu, C. Wu, Y. Pan, L. Zhao, and C. Zhu, "PoShapley-BCFL: A fair and robust decentralized federated learning based on blockchain and the proof of shapley-value," in *Proceedings of the 30th International Conference on Neural Information Processing (ICONIP)*, ser. Lecture Notes in Computer Science, vol. 14448. Springer, 2023, pp. 527–540.

[12] N. Dong, J. Sun, Z. Wang, S. Zhang, and S. Zheng, "FLock: Defending malicious behaviors in federated learning with blockchain," in *Distributed Machine Learning Workshop, NeurIPS*, 2022, arXiv:2211.04344.

[13] L. S. Shapley, "A value for n-person games," *Contributions to the Theory of Games*, vol. 2, pp. 307–317, 1953.

[14] H. Kim, J. Park, M. Bennis, and S.-L. Kim, "Blockchained on-device federated learning," *IEEE Communications Letters*, vol. 24, no. 6, pp. 1279–1283, 2019.

[15] A. Sokhankhosh and S. Rouhani, "Proof-of-collaborative-learning: A multi-winner federated learning consensus algorithm," *arXiv preprint arXiv:2407.13018*, 2024.

[16] N. Dong, Z. Wang, J. Sun, M. Kampffmeyer, W. Knottenbelt, and E. Xing, "Defending against poisoning attacks in federated learning with blockchain," *IEEE Transactions on Artificial Intelligence*, 2024, arXiv:2307.00543.

[17] F. Vogelsteller and V. Buterin, "EIP-20: Token standard," Ethereum Improvement Proposals, 2015, https://eips.ethereum.org/EIPS/eip-20.

[18] A. Krizhevsky, "Learning multiple layers of features from tiny images," University of Toronto, Tech. Rep., 2009.

[19] H. Xiao, K. Rasul, and R. Vollgraf, "Fashion-MNIST: A novel image dataset for benchmarking machine learning algorithms," *arXiv preprint arXiv:1708.07747*, 2017.

[20] A. Ghorbani and J. Zou, "Data shapley: Equitable valuation of data for machine learning," in *Proceedings of the 36th International Conference on Machine Learning (ICML)*. PMLR, 2019, pp. 2242–2251.

[21] R. Jain, D.-M. Chiu, and W. Hawe, "A quantitative measure of fairness and discrimination for resource allocation in shared computer systems," 1984, technical Report DEC-TR-301, Digital Equipment Corporation.