

Borked3DS-rpi optimizations since the letters bug (v146 → v394)

Raspberry Pi 5, V3DV / Mesa 26.1.2, RetroPie. This lists the **kept** changes that improve the emulator.

Legend

Mark	Meaning
✓	Applies. It was measured, or the code is shared and active in that renderer.
(✓)	The code is shared by both renderers, so it probably applies. It was never measured under OpenGL/GLES.
—	Does not apply (Vulkan-only code).

- **Speed gain:** given as % of speed (frames per second), computed from the project's measurements.
- **Cold loading time:** given as % less time.
- All % values are **approximate**. They depend on the game and scene measured.
- Speed gains do not add up. Each one was measured on a different game and version.

1. In-game speed

Version	Improvement	Measured gain	≈ %	Vulkan	OpenGL (GLES)
v149c / v150	Scheduler mode C: no GPU <i>Finish</i> after each software draw (EmuThread was blocked 60-69 % of the time)	Metroid 37-40 % → 60 % speed	+55 % speed	✓	—
TB33	Removed the image copy (CopyImageView) on every draw	Metroid 49.3 % → 88.7 %	+80 % speed	✓	—
TB34	Heavy traces made opt-in (off by default)	88.7 % → ~95 %	+7 % speed	✓	—
v158 / v389	Lighter log filter (*:Trace → *:Warning by default)	+5 speed points	≈ +5 % speed	✓	✓
v160	Environment variables read once instead of on every draw (pica_core, rasterizer, pipeline cache)	EmuThread CPU 68.1 % → 54.5 %	-20 % CPU (no fps gain; the CPU was not the bottleneck then)	✓	—
v148	SAFE_PICA_HW budgets raised (1/6 → 9999/65536): every draw goes through the GPU	Render bottleneck removed	not quantified	✓	—
v388	Robustness disabled on the fragment shader only (VK_EXT_pipeline_robustness): 1278 → 839 instructions, spills 16:27 → 2:2	Luigi's Mansion 2: 54 → 37.8 ms per frame	+43 % speed	✓	—

Version	Improvement	Measured gain	≈ %	Vulkan	OpenGL (GLES)
v391	Reduced lighting for Luigi's Mansion 2 only (title 0004000000076500): 6 of the 8 per-pixel lights are computed. All other games are untouched.	Luigi's Mansion 2: ~40 → 26 ms per frame (census method, see note in section 7); slow pipeline compiles 0.9-3.4 s → up to 1.7 s	+50 % speed (Luigi only)	✓	—

2. Freezes, stutter and smoothness

Version	Improvement	Measured gain	≈ %	Vulkan	OpenGL (GLES)
v151	Extended Dynamic State (EDS) enabled: fewer pipeline variants	Kid Icarus worst compile 12,993 → ~51 ms; poisons 43 → 0	-99.6 % of worst freeze	✓	—
v326 / v329	No blocking wait on BindPipeline, plus fix for is_pending never being reset	8-20 s freezes removed	freezes removed	✓	—
v331 / v342	Asynchronous compile pool, pool-inversion fix, 6 worker threads	Compilation = 0.8 % of the session; no shader waits	not quantified	✓	—
v361	glslang internal optimizer turned off (unbounded exhaustive inlining)	Major freeze removed (12 GiB runaway allocation on EmuThread, frozen console)	major freeze removed	✓	—
v371	Short wait for the first pipeline instead of skipping the draw	Frames with skipped draws 28 → 4; early 2D flash fixed	-86 % damaged frames	✓	—
v372	In-memory and on-disk SPIR-V cache (38 % of conversions were redundant)	Warm: ~1 s 3D freeze removed; frames > 100 ms 8 → 2	-75 % warm stutter	✓	—
v390	Compile threads at background priority (nice 19), 3 threads by default: compiling never steals CPU time from emulation	Kid Icarus cold: 31 → 18 s of compile time, 12 frames > 80 ms; Luigi: frames > 80 ms 117 → 8 during compiles	-42 % cold compile (Kid Icarus)	✓	—
v392	Vulkan shader caches (pipelines + SPIR-V) are kept across rebuilds ; only the SPIR-V part is purged if the GLSL → SPIR-V conversion itself changes	Areas already visited never recompile, even after an emulator update	no repeated cold start	✓	—
v383 / v384	GPU lead bounded, pipeline cache saved during gameplay	Luigi flicker removed; cache stays warm even after a crash	not quantified	✓	—

3. Cold shader loading time

Version	Improvement	Measured gain	≈ %	Vulkan	OpenGL (GLES)
v377	Acyclic PICA decompiler (state machines without poison loops)	Sonic poisons 77 → 11 s	-86 % loading	✓	(✓)
v385	Vertex-shader boolean and loop specialization, cap 64	Sonic 62 → 9 s	-85 % loading	✓	(✓)

Version	Improvement	Measured gain	≈ %	Vulkan	OpenGL (GLES)
		Kid Icarus 319 → 19-31 s	-90 to -94 % loading	✓	(✓)
		Zelda 68 → 12 s	-82 % loading	✓	(✓)
		Metroid 12 → 5 s	-58 % loading	✓	(✓)

4. Games made playable or fixed

Version	Improvement	Measured gain	Vulkan	OpenGL (GLES)
v379 / v380	Backward jumps and specialized JMPU jumps in the decompiler	Luigi's Mansion 2: 98.6 s black screen then crash → playable	✓	(✓)
v313 / v335	HIGH_SWITCH / DIRA removed: avoids the software vertex path	Sonic 3D runs on the GPU	✓	—
v394	Logic op NoOp honoured in Vulkan: under strict-compat the hardware logic op is off and emulated in the shader, but NoOp ("leave the color alone") cannot be emulated there. It now sets the color write mask to 0, keeping depth and stencil writes.	Super Mario 3D Land: shadows drawn as long black spikes → correct shadows (TB97). No speed cost (TB98: Luigi 32.5 ms with and without).	✓	— (GLES was already correct through glColorMask)

5. System and settings

Version	Improvement	Measured gain	Vulkan	OpenGL (GLES)
v324	cpu_clock_percentage 60 → 100	Games run at their nominal pace	✓	✓
v376	Mesa 26.1.2 kept (rather than 26.1.6)	Better of the two drivers tested	✓	(✓)
v378	Official 27 W power supply	Pi crashes removed	✓	✓
v389	Optimal settings built into the code. Vulkan and disk cache on by default, fullscreen on. The 17 V3DV variables are set automatically, in Vulkan only. <code>emulators.cfg</code> reduced to 3 lines.	Same speed, simple setup	✓	✓ (Vulkan is the default; GL can still be selected)

6. Tried, then removed (no gain or a regression)

Version	Attempt	Why it was removed	Vulkan	OpenGL (GLES)
—	opt_compile_time	Halved compile time. With the non-robust FS it gave 1336 instructions and Luigi at 126 ms.	✓	—
v382	TEXSYNC	Superseded by v383/v384	✓	—
v386	Forced early-Z	52.9 → 52.1 ms, negligible gain	✓	—
v386	SKIP_DARK (skip dark lights)	Slower, and the bottom screen broke	✓	(✓)
—	Looped or grouped lighting	1356 to 1760 instructions vs 839	✓	(✓)
—	glslang -Os	Identical after NIR	✓	—
v351	optimize_spirv_output modes 1 to 3	34 s poisons and GPU hangs; stays at 0	✓	—
TB87	Geometry shader turned off (geometry_shader=false)	No gain: the fragment lighting shader is the cost, not the GS	✓	—
TB88	2 compile threads (normal priority)	Smooth, but the compile queue never caught up (most draws skipped); replaced by v390	✓	—
TB91a	Luigi with 4 lights	Barely faster than 6 lights (CPU-bound) and far too dark	✓	—
v393	PICA shadow maps rendered in Vulkan (atomic writes to an r32ui image, Shadow2D/ShadowCube reads)	Did not fix Mario 3D Land, which never uses PICA shadow maps. Luigi's Mansion 2 (flashlight shadow pass every frame) went from 32.5 to 35.4 ms. Kept in the code but off by default since v394; BORKED3DS_V3DV_V393_SHADOWS=1 turns it on.	✓	—

7. Final result (v394, Vulkan; 60 fps = 16.7 ms per frame, warm caches)

Game	ms per frame	Cold shader loading
Kid Icarus Uprising	16.6 (full speed)	~18 s of compile time, 0 poisons
Metroid	16.7 (full speed)	< 1 s
Zelda	16.7 (full speed)	12.5 s
Smash Bros	16.8 (full speed)	7-10 s
Sonic	16.7 (full speed)	~5 s
Luigi's Mansion 2 (6 lights)	26.0 by census, 32.5 in real time (~51 % speed)	1-2 s per new pipeline in unvisited areas
Super Mario 3D Land	shadows correct since v394	—

Luigi's Mansion 2 has reached its CPU floor: with lighting removed entirely (TB90 probe) it still runs at 25.9 ms per frame. Going further would require reducing the CPU cost of emulation.

Measurement note (TB98). The 26 ms figures for Luigi come from the census `frame_us`, which samples only one frame in sixty. Measured from real elapsed time over 60 frames (V383_LAG timestamps), the same garden scene runs at **32.5 ms per frame**. Both are correct for what they measure, but only the real-time figure matches what the player sees; future Luigi measurements use it. The relative gains above (v388, v391) were each measured with a single method and remain valid.

Known defect: small flashes on Smash's bottom screen. They existed before v388.

8. Validation at stock clocks (TB92: 2.4 GHz CPU, 960 MHz GPU)

Most Pi 5 owners do not overclock. The reference Pi runs `arm_freq=3000`, `v3d_freq=1000` and `over_voltage_delta=50000`; these were disabled for this test (`arm_boost=1`, a stock Raspberry Pi OS setting, was kept).

Game	3.0 GHz / 1000 MHz	2.4 GHz / 960 MHz	Reading
Luigi's Mansion 2 (6 lights)	26.0 ms (census)	33.8 ms (~49 % speed)	CPU and GPU both slower; GPU busy 93 %
Kid Icarus	16.6 ms	16.6 ms	Full speed, no loss
Smash Bros	16.8 ms	median 16.6 ms , mean 19.1 ms	Full speed most of the time; ~10 % of frames above 22 ms

No throttling (`throttled=0x0`), 49-51 °C, official 27 W power supply. Overclocking gives Luigi's Mansion 2 about +30 % speed; the other games do not need it.

9. Cold run and warm run

A **cold run** is the first time a game (or a new area of a game) is played after installation. The 3DS shaders must first be translated and compiled for the Pi's GPU. This happens in the background, so the game keeps running, but while a shader is not ready you may see minor glitches: an object appearing a moment late, a brief flash, a short stutter or a frame that looks frozen for an instant. In Luigi's Mansion 2, each unvisited room can take a few seconds to settle.

A **warm run** is every run after that. The compiled shaders are saved on disk and loaded instantly, so the same scenes play smoothly from the start. Since v392 these caches are also kept when the emulator is rebuilt or updated, so the warm-up only happens once per game area.

In short: the first minutes of a new game may look a little rough; play on, and it settles.

OpenGL (GLES) note

All measurements were taken in Vulkan. v390, v391, v392, v393 and v394 are Vulkan-only. Mario 3D Land shadows were already correct under GLES. Under OpenGL, only the shader generator changes (PICA decompiler, v385 specialization, v379/v380 jumps) and the general settings apply. No figures were taken under GLES. The GL driver compiles GLSL itself, so the SPIR-V cache, robustness, EDS and the compile pool do not concern it.