

PlastFormance Products



Compounds

Plastic compounds combine the properties of a filler (e.g., ceramic or metallic) and a plastic in a single material. The inheritance of the filler characteristics by the respective compound becomes more pronounced the higher the filler content in the finished material.



Challenge

In existing compounds, processability, especially flowability in injection molding, decreases rapidly with increasing filler content. The full performance range often cannot be achieved because the limits of processability have been reached.

The solution

The patented PlastFormance technology enables injection molding capability to be maintained even at very high fill levels (80% vol.). This results in lower injection pressures, longer flow paths, and more complex component geometries.



Product portfolio

Our current standard product range includes high-quality compounds, each leading in its physical properties and price-performance ratio. A particular strength lies in the combination of thermal conductivity and high electrical resistance.
Submit an inquiry directly for one or more of our products. We are happy to supply test quantities so you can test their compatibility for your further processing. If you require compounds with specific properties for special applications, we also offer customized products .

Thermally Conductive Series

Product	Thermal Conductivity (W/mK)	Electrical Resistance (Ωcm)	Properties	Applications
TC4-1624-PA6	4.0	$>1\times10^{12}$	high thermal conductivity, electrically insulating	- Heat sinks - Electronics overmolding - Thermal management of power electronics - Potting housings - Heat spreaders - Sensor overmolding - Functional housings - Aluminum housing replacement - Thermal management of connectors
TC2-4424-PA12-FR	2.2	$>1\times10^{12}$	high thermal conductivity, excellent chemical resistance, flame retardant, electrically insulating	
TC3-4524-PA12	3.0	$>1\times10^{12}$	high thermal conductivity, excellent chemical resistance, electrically insulating	
TC2-6222-PBT	2.3	$>1\times10^{12}$	thermally conductive, electrically insulating	
TC1-2623-LCP-FR	1.2	$>1\times10^{12}$	thermally conductive, flame retardant, electrically insulating	
TC3-2723-LCP-FR	3.1	$>1\times10^{12}$	high thermal conductivity, flame retardant, electrically insulating	
TC8-1412-LCP-FR	8.5	$>1\times10^{12}$	very high thermal conductivity, flame retardant, electrically insulating	
TC2-2424-TPE	2.1	$>4\times10^{10}$	high elongation, thermally conductive, electrically insulating	
TC3-316-SEBS	2.9	1×10^{9}	extremely soft, high thermal conductivity, electrically insulating	

Radiation Shielding Series

Product	Density (g/cm³)	Electrical Resistance (Ωcm)	Properties	Applications
M10-001-PA6-RS	10.6	0.5	gamma ray shielding, very high density, non-magnetic, electrically conductive	- Application for radiation protection products - Lead replacement - Alternative to conventional tungsten products
M14-001-PA6-RS	14.2	0.2	gamma ray shielding, very high density, non-magnetic, electrically conductive	
M11-3024-PA12-RS	11.0	0.5	gamma ray shielding, very high density, non-magnetic, electrically conductive	

EMI Series

Product	Thermal Conductivity (W/mK)	Electrical Resistance (Ωcm)	Properties	Applications

EMV-2824-PA6	1.5	0.1-0.6	high electromagnetic shielding effectiveness, highly electrically conductive, high tensile strength	
EMV-2924-PA6	2.0	0.1-0.4	high electromagnetic shielding effectiveness, highly electrically conductive, high tensile strength	- EMI protection for electronic components
EMV-3024-LCP	3.0	0.3-1.0	high electromagnetic shielding effectiveness, highly electrically conductive, high media resistance	

Electrically Conductive Series

Product	Thermal Conductivity (W/mK)	Electrical Resistance (Ωcm)	Properties	Applications
EC1-GP56-305-PP	30.0	0.25	highly electrically conductive, very high thermal conductivity	
EC1-GP60-PP	40.0	0.12	highly electrically conductive, very high thermal conductivity	
EC1-6723-PP	20.0	0.06	highly electrically conductive, very high thermal conductivity	- Fuel cell - Redox flow battery
EC3-NC-1561-PC	0.3	1×10^{5}	electrically conductive, good elasticity	
EC3-CB-TPU R06-24	0.3	$<1\times10^{7}$	electrically conductive	

Heavy Plastic Series

Product	Density (g/cm³)	Electrical Resistance (Ωcm)	Properties	Applications
M3.0-0724-PA6	3.0	$<1\times10^{3}$	high density, electrically conductive, thermally conductive	
M6.3-CP-PA12	6.3	5×10^{11}	high density, electrically insulating, thermally conductive	- Design plastics - Balancing / trim weights
M2.5-MP-ABS-MG	2.5	4.5×10^{11}	high density, electrically conductive	- Metallic haptics
M3.3-MP-ABS-MG	3.3	2×10^{4}	high density, electrically conductive	

Didn't find what you were looking for?

Contact us

contact **menu**

PlastFormance GmbH
Warisloh 10
83317 Teisendorf

T +49 8666 989 29 152
M info@plastformance.com

Home
Products
Applications
News
About Us
Contact
Legal Notice & Privacy Policy

©2025, PlastFormance GmbH