

# Bill of Materials (BOM) Explanation

Pontus Svensson / RoboCup

October 14, 2024

## Introduction

This document provides an explanation of the Bill of Materials (BOM) we want to use in the project. Each component listed in the BOM is described in detail, including its purpose and other relevant specifications.

## Component Overview

The table below outlines the components used in this project along with their purpose and additional information.

Table 1: Component Descriptions for the Project

| Component                       | Description   | Purpose  | # | á price<br>(price per<br>robot)<br>SEK |
|---------------------------------|---|--|---|--|
| DF45L024048-A                   | Brushless direct current (BLDC) motor with integrated hall sensors for the wheels | Used to spin the wheels of the robot.  | 4 | 830.4<br>(3273.60)                     |
| Hobbywing FPV XRotor 3110 900KV | Brushelss DC motor  | High revolutions per minute (RPM) motor used to control the dribbler.  | 1 | 175.20<br>(175.20)                     |
| B-G431B-ESC1                    | BLDC motor driver   | Motor driver with embedded $\mu$ Controller current sensing and hall sensing to form a closed-loop control algorithm | 5 | 208.96<br>(1044.8)                     |

Table 1: Component Descriptions for the Project

| Component                       | Description  | Purpose   | #  | price<br>(price per<br>robot)<br>SEK |
|---------------------------------|--|---|----|--------------------------------------|
| NUCLEO-H723ZG                   | $\mu$ Controller                                     | Computational power and real-time processing capabilities, supports $\mu$ ROS | 1  | 322.58<br>(322.58)                   |
| Raspberry Pi 4 Model B/8GB      | Single-board computer                                | Processing camera input and performing local path planning                    | 1  | 979 (979)                            |
| SX1280IMLTRT                    | Radio frequency (RF) transceiver                     | Used to transmit data over 2.4Ghz network                                     | 1  | 75.44<br>(75.44)                     |
| SKY66122-11                     | Integrated front-end-moduel (FEM)                    | Simplified integration with the RF circuit                                    | 1  | 40.48<br>(40.48)                     |
| 6s 1300mAh - 120C - GNB HV XT60 | LiPo-battery   | Used to power the robot   | 1  | 351.20<br>(351.20)                   |
| LT3750                          | Charging controller for the capacitors of the kicker | Charge controller for the kicker circuit                                      | 1  | 146.93<br>(146.93)                   |
| iC-PX2604 + PX01S 26-30         | Wheel encoders                                       | Will be used for odometry of the robot  | 4  | 224.40<br>(897.60)                   |
| WSEN-ISDS 6 Axis IMU            | 6-DoF IMU  | Will be used for odometry of the robot  | 10 | N/A                                  |
| Raspberry Pi Kameramodul 3      | Camera   | Provide images in front of the robot to detect the ball and obstacles         | 1  | 369 (369)                            |
| IR Break Beam Sensor - 5mm LEDs | Infrared (IR) sensor                                 | Used to detect if the ball is close to the robot                              | 1  | 99 (99)                              |
| JST 6B-PH-K-S                   | Connector  | Hall sensor connector from the motor  | 4  | 3.85 (15.4)                          |
| JST B5P-VH                      | Connector  | Motor connector   | 4  | 4.06<br>(16.24)                      |

Table 1: Component Descriptions for the Project

| Component                           | Description                 | Purpose  | #   | price<br>(price per<br>robot)<br>SEK |
|-------------------------------------|-----------------------------|--|-----|--------------------------------------|
| Connectors                          | Passive component           | Supplied by Würth                                | N/A | N/A                                  |
| Shaft hub with clamping bracket 4mm | Coupler                     | Couple the wheels with the motor shaft           | 4   | 139 (556)                            |
| Bearings                            | Bearings                    | Make the roller spin (dribbler)                  | 2   | 18 (36)                              |
| Resistors                           | Passive component           | Supplied by Würth or 326                         | N/A | N/A                                  |
| Capacitors                          | Passive component           | Supplied by Würth or 326                         | N/A | N/A                                  |
| Voltage regulators                  | DC/DC buck converters       | Supplied by Würth                                | N/A | N/A                                  |
| Solenoid                            | Solenoid                    | Supplied by MDU                                  | 1   | N/A                                  |
| PCB                                 | Printed circuit board (PCB) | The students will supply any custom PCB designed | 2   | N/A                                  |
| <b>Total price for 1 robot</b>      | <b>8398.47</b>              |  |     |                                      |

## Reason for component choice

### DF45L024048-A

During competition a SSL-robot is most of the time accelerating [1]. Having a motor which can provide sufficient torque at any given speed is crucial.

The DF45L024048-A BLDC motors provides a good tradeoff between torque and RPM, with integrated hall sensors. The sensors detect the position of the rotor relative to the stator which gives the ability to control the motors using commutation. The motor controller uses the signals from the hall sensors to determine the exact timing for switching the current in the stator windings. This gives a smooth motor operation while maximizing torque output.

We also have to take the size of the motor into account. Having too large footprint on the motors would cause the kicker (solenoid) to not fit in the chassis. Using a general 5010 sensorless drone motor could be used as demonstrated by [2] but this motor would require a more sophisticated ESC which would take a lot of time to develop and manufacture.

Using hall sensors is a common method utilized by several teams and proven to be a winning concept [3] [4] [5] [1].

## Hobbywing FPV XRotor 3110 900KV

The requirements for the dribbler motor is that it can reach high RPM (around 10000 RPM).

### B-G431B-ESC1

A sensorless controller requires that the BLDC motor produce a measurable back electromotive force (EMF) so the controller can determine the position of the rotor and therefore cannot provide smooth commutation at start up and low speeds. [6]

The chosen electronics speed controller (ESC) has an STSPIN32F0A system in package chip which has an integrated STM32 processor with hall sensor decoding logic and current sensing capabilities. This makes this ESC a good fit with the DF45L024048-A BLDC motor.

The STSPIN32F0A chip is a common choice for controlling BLDC motors in the SSL competitions which has been proven to be reliable and succesful [3] [7]

A PID system can be implemented on the chip to allow for precise movement and rapid acceleration which is critical to make fast directions changes.

The B-G431B-ESC1 will receive a desired velocity, to use this with in a PID system the RPM of each motor is required. The RPM will be retrieved by measuring the number of pulses from the hall sensors and calculate the time between them.

The size and weight of the ESC does also have to be taken in consideration, the B-G431B-ESC1 has a small footprint with a relatively low weight 286g. With all the components integrated on one board will make the assembly process easier and reduce any external components e.g. hall sensing or mosfets. The programming for the integrated STM32 is done using STM32 Motor Control Software Development Kit which is a graphical programming envirotnment from ST.

### NUCLEO-H723ZG Microcontroller

The NUCLEO-H723ZG is a development board based on the STM32H723ZG chip, it comes with all necessary peripheral communication UART, SPI, I2C and CAN. The STM32H723ZG features an ARM Cortex-M7 core operating at up to 480 MHz, providing good processing power for handling multiple real-time tasks required in our application.

Additionally, the STM32 series is widely adopted in RoboCup competitions, including the **Small Size League (SSL)** [3] [8] [5]. This widespread use underscores its reliability and effectiveness in competitions.

To manage the various tasks and ensure smooth operation of our robot, we will implement a control architecture using **micro-ROS** in combination with **FreeRTOS** on the NUCLEO-H723ZG.

**FreeRTOS** is a real-time operating system that provides task scheduling and resource management. Implementing FreeRTOS on the NUCLEO-H723ZG allows us to handle multiple concurrent tasks efficiently, such as sensor data processing, motor control, and communication with other system components.

This also aligns with the collaboration with Universidad de Antioquia, since they will use FreeRTOS to program the ESP32-S3.

## **Raspberry Pi 4 Model B/8GB**

It is important to accurately detect the ball and other robots in a timely manner, therefore we have decided to use a camera which image input will be processed by the Raspberry Pi 4. The Raspberry pi has been extensively used in the SSL competitions for this purpose [9] [10]

## **SX1280IMLTRT + SKY66122-11**

To obtain a reliable connection to the team server, we have opted to use the SX1280IMLTRT RF transceiver with the SKY66122-11 front-end-module.

This implementation has been proven succesful by several teams [3] [11]. However, one drawback is that the components require a custom made PCB. This will be solved by creating one mainboard with connectors to our components, battery, motors, sensors and the NUCLEO-H723ZG. This will enable a modular design where components can be swapped.

## **iC-PX2604 + PX01S 26-30**

This wheel encoder comes as a complete module which will be easy to integrate and in combination with the NUCLEO-H723ZG the resolution of the encoder is increased. Since we also have a quotation at a reasonable price we have chosen to use this encoder.

## **WSEN-ISDS 6 Axis IMU**

Ther IMU we have chosen is supplied free of charge from Würth electronics. It communicates using I2C or SPI which both are available on the NUCLEO-H723ZG.

## **Raspberry Pi Kameramodul 3**

The Raspberry Pi camera-module 3 is chosen because its seamless integration with the Raspberry Pi 4.

## **IR Break Beam Sensor - 5mm LEDs**

The IR Break Beam sensor will be connected using GPIO pins on the NUCLEO-H723ZG with a pull-up resistor.

## **Connectors**

Connectors for the main PCB board will be supplied by Würth electronics.

## **Shaft hub with clamping bracket 4mm**

From our research teams have noticed that if the coupling between the motorshaft and wheels does not have a good fit, the shaft will start to release tiny metal dust which will be collected by the hub of the BLDC motor.

Therefore we have chosen to use this clamp to ensure the coupling is secure.

## **Bearings**

## **Resistors**

Any Passive components required will be supplied by Würth electronics or if we can find it in 326.

## **Capacitors**

Any Passive components required will be supplied by Würth electronics or if we can find it in 326.

## **Voltage regulators**

The voltage regulators will be used to ensure our components receive the correct voltages, 3.3V, 5V, 12V will be integrated on the custom PCB.

The voltage regulators was supplied by Würth electronics.

## **Solenoid**

A custom made solenoid would be preferred, but due to time the solenoid we will use is a generic solenoid for starting car engines. Supplied by MDU.

## **PCB**

As some of our components require a custom PCB, we will design two PCBs. A main-board and a kicker-board, the main board will host connectors for the battery, motors, NUCLEO-H723ZG and pin headers for powering the Raspberry Pi. The mainboard will also host the RF transceiver, IMU and voltage regulators.

## **Hardware Architecture**

## **Hardware Interface**

## **Conclusion**

This document serves as a reference for understanding the role of each component in the project. For any further technical details, please refer to the respective datasheets provided by the manufacturers.

## **References**

- [1] A. Franca, B. Barros, C. Gomes, C. Silva, C. M. Alves, D. C. Barbosa, D. Xavier, E. Araujo, F. Pereira, L. H. Cavalcanti, M. Asfora, M. Alves, M. Paixao, M. Vasconcelos, M. Vimcius, J. G. Melo, J. R. Silva, J. Leite, P. H. Santana, P. P. Oliveira, R. Rodrigues, T. Teobaldo, V. Dutra, V. Araujo, and E. Barros, “RoboCup In Small Size League Extended Team Description Paper for RoboCup 2024.”

- [2] A. Veeraghanta, H. Bryant, S. Zheng, M. MacDougall, S. Guido, and L. Bontkes, “2024 Team Description Paper: The Bots.”
- [3] A. Ryll and S. Jut, “Extended Team Description for RoboCup 2020.”
- [4] D. R. H. Abiyev, N. Akkaya, T. Yirtici, E. Aytac, G. Burge, S. Abizada, A. Turk, and G. Say, “NEUIslanders Team Description Paper RoboCup 2022.”
- [5] Y. Wu, K. Liu, J. Fan, H. Zhang, J. L. Minghe, Q. Li, and J. Li, “Compilation Error Team Description Paper for Small Size League of Robocup 2024.”
- [6] A. Rowe, G. Sen Gupta, and S. Demidenko, “Instrumentation and control of a high power BLDC motor for small vehicle applications,” in *2012 IEEE International Instrumentation and Measurement Technology Conference Proceedings*. Graz, Austria: IEEE, May 2012, pp. 559–564.
- [7] A. Abousaleh, A. Balamurali, B. Blair, R. Cao, M. Charara, L. Chee, J. Coffin, J. Guo, W. Ha, F. Haas, T. Kong, R. Khan, C. Lee, O. Levy, R. Nedjbat, M. Phung, A. Sidhu, D. Sturn, M. Tong, B. Vasilchikov, K. Wakaba, N. Zareian, S. Banna, P. Zhou, and Y. B. Zhou, “2024 Team Description Paper: UBC Thunderbots.”
- [8] A. Zhao, P. Yu, Z. Huang, N. Shen, J. Yang, J. Yu, Z. Chen, L. Wang, and R. Xiong, “ZJUNlict Extended Team Description Paper.”
- [9] N. Ommer, A. Ryll, M. Ratzel, and M. Geiger, “Extended Team Description for RoboCup 2024.”
- [10] H. Sato, N. Okamoto, A. Ito, S. Kayaki, T. Nakao, Y. Nishimura, Y. Hara, and R. Yuri, “GreenTea 2024 Team Description Paper.”
- [11] H. Barreto, L. E. Horie, E. G. Frese, de Freitas, M. C. Antunes, E. Baldi, and E. H. V. Melo, “RoboIME: Igniting Innovation, Shaping the Future in RoboCup 2024.”