

Introduction to model validation

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

What is model validation?

Model validation consists of:

- Ensuring your model performs as expected on new data
- Testing model performance on holdout datasets
- Selecting the best model, parameters, and accuracy metrics
- Achieving the best accuracy for the data given

scikit-learn modeling review

Basic modeling steps:

```
model = RandomForestRegressor(n_estimators=500, random_state=1111)
model.fit(X=X_train, y=y_train)
```

```
RandomForestRegressor(bootstrap=True, criterion='mse', max_depth=None,
                        max_features='auto', max_leaf_nodes=None,
                        min_impurity_decrease=0.0, min_impurity_split=None,
                        min_samples_leaf=1, min_samples_split=2,
                        min_weight_fraction_leaf=0.0, n_estimators=500, n_jobs=1,
                        oob_score=False, random_state=1111, verbose=0, warm_start=False)
```

Modeling review continued

```
predictions = model.predict(X_test)
print("{0:.2f}".format(mae(y_true=y_test, y_pred=predictions)))
```

10.84

Mean Absolute Error Formula

$$\frac{\sum_{i=1}^n |y_i - \hat{y}_i|}{n}$$

Review prerequisites

- Intermediate Python
- Supervised Learning with scikit-learn

How often did a fun-sized candy of a given type win its matchups against the rest of the field?

Search...

RK	CANDY	WIN PERCENTAGE	
1	Reese's Peanut Butter Cup	84.2%	<div></div>
2	Reese's Miniatures	81.9	<div></div>
3	Twix	81.6	<div></div>
4	Kit Kat	76.8	<div></div>
5	Snickers	76.7	<div></div>

Seen vs. unseen data

Training data = seen data

```
model = RandomForestRegressor(n_estimators=500, random_state=1111)
model.fit(X_train, y_train)
train_predictions = model.predict(X_train)
```

Testing data = unseen data


```
model = RandomForestRegressor(n_estimators=500, random_state=1111)
model.fit(X_train, y_train)
test_predictions = model.predict(X_test)
```

Let's begin!

MODEL VALIDATION IN PYTHON

Regression models

MODEL VALIDATION IN PYTHON




Kasey Jones
Data Scientist

Random forests in scikit-learn

```
from sklearn.ensemble import RandomForestRegressor  
from sklearn.ensemble import RandomForestClassifier
```

```
rfr = RandomForestRegressor(random_state=1111)  
rfc = RandomForestClassifier(random_state=1111)
```

Decision Tree Example:
Predicted Amount of Debt




Decision Tree #1: \$4k

Decision Tree #2: \$4k

Decision Tree #3: \$3k

Decision Tree #4: \$5k

Decision Tree #5: \$5k


$$(4 + 4 + 3 + 5 + 5) / 5 = 4.2$$

Random forest parameters

`n_estimators` : the number of trees in the forest

`max_depth` : the maximum depth of the trees

`random_state` : random seed

```
from sklearn.ensemble import RandomForestRegressor  
rfr = RandomForestRegressor(n_estimators=50, max_depth=10)
```

```
rfr = RandomForestRegressor(random_state=1111)  
rfr.n_estimators = 50  
rfr.max_depth = 10
```

Feature importance

Print how important each column is to the model

```
for i, item in enumerate(rfr.feature_importances_):  
    print("{0:s}: {1:.2f}".format(X.columns[i], item))
```

```
weight: 0.50  
height: 0.39  
left_handed: 0.72  
union_preference: 0.05  
eye_color: 0.03
```

Let's begin

MODEL VALIDATION IN PYTHON

Classification models

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

Classification models

- Categorical Responses:
 - Newborn's hair color
 - Winner of a basketball game
 - Genre of the next song on the radio

The Tic-Tac-Toe dataset

...	Bottom-Left	Bottom-Middle	Bottom-Right	Class
...	X	O	O	positive
...	O	X	O	positive
...	O	O	X	positive
...	X	X	O	negative
...

▼ Medium




X

-

O

-

X Turn



RESTART GAME

Using `.predict()` for classification

```
from sklearn.ensemble import RandomForestClassifier
rfc = RandomForestClassifier(random_state=1111)
rfc.fit(X_train, y_train)
rfc.predict(X_test)
```

```
array([1, 1, 1, 1, 0, 1, ...])
```

```
pd.Series(rfc.predict(X_test)).value_counts()
```

```
1    627
0    331
```

Predicting probabilities

```
rfc.predict_proba(X_test)
```

```
array([[0. , 1. ],  
       [0.1, 0.9],  
       [0.1, 0.9],  
       ...])
```

```
rfc = RandomForestClassifier(random_state=1111)
rfc.get_params()
```

```
{'bootstrap': True,
 'class_weight': None,
 'criterion': 'gini',
 ...}
```

```
rfc.fit(X_train, y_train)
rfc.score(X_test, y_test)
```

```
0.8989
```

Let's classify Tic-Tac-Toe end-game scenarios

MODEL VALIDATION IN PYTHON

Creating train, test, and validation datasets


MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

Traditional train/test split

- Seen data (used for training)
- Unseen data (unavailable for training)



Dataset definitions and ratios

Dataset	Definition
Train	The sample of data used when fitting models
Test (holdout sample)	The sample of data used to assess model performance

Ratio Examples

- 80:20
- 90:10 (used when we have little data)
- 70:30 (used when model is computationally expensive)

The X and y datasets

```
import pandas as pd

tic_tac_toe = pd.read_csv("tic-tac-toe.csv")
X = pd.get_dummies(tic_tac_toe.iloc[:,0:9])
y = tic_tac_toe.iloc[:, 9]
```

Python courses covering dummy variables:

- [Supervised Learning](#)
- [Preprocessing for Machine Learning](#)

Creating holdout samples

```
X_train, X_test, y_train, y_test =\n    train_test_split(X, y, test_size=0.2, random_state=1111)
```

Parameters:

- `test_size`
- `train_size`
- `random_state`

Dataset for preliminary testing?


What do we do when testing different model parameters?

- 100 *versus* 1000 trees

Available Data



New Available Data



Train, validation, test continued

```
X_temp, X_test, y_temp, y_test =\  
    train_test_split(X, y, test_size=0.2, random_state=1111)
```


```
X_train, X_val, y_train, y_val =\  
    train_test_split(X_temp, y_temp, test_size=0.25, random_state=11111)
```

It's holdout time

MODEL VALIDATION IN PYTHON

Accuracy metrics: regression models

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

Regression models

12.2 points

15 gallons of gas

\$1,323,492

6 new puppies

4,320 people

Mean absolute error (MAE)

$$MAE = \frac{\sum_{i=1}^n |y_i - \hat{y}_i|}{n}$$

- Simplest and most intuitive metric
- Treats all points equally
- Not sensitive to outliers

Mean squared error (MSE)

$$MSE = \frac{\sum_{i=1}^n (y_i - \hat{y}_i)^2}{n}$$

- Most widely used regression metric
- Allows outlier errors to contribute more to the overall error
- Random family road trips could lead to large errors in predictions

MAE vs. MSE

- Accuracy metrics are always application specific
- MAE and MSE error terms are in different units and should not be compared

Mean absolute error

```
rfr = RandomForestRegressor(n_estimators=500, random_state=1111)
rfr.fit(X_train, y_train)
test_predictions = rfr.predict(X_test)
sum(abs(y_test - test_predictions))/len(test_predictions)
```

9.99

```
from sklearn.metrics import mean_absolute_error
mean_absolute_error(y_test, test_predictions)
```

9.99

Mean squared error

```
sum(abs(y_test - test_predictions)**2)/len(test_predictions)
```

```
141.4
```

```
from sklearn.metrics import mean_squared_error  
mean_squared_error(y_test, test_predictions)
```

```
141.4
```

Accuracy for a subset of data

```
chocolate_preds = rfr.predict(X_test[X_test[:, 1] == 1])  
mean_absolute_error(y_test[X_test[:, 1] == 1], chocolate_preds)
```

8.79

```
nonchocolate_preds = rfr.predict(X_test[X_test[:, 1] == 0])  
mean_absolute_error(y_test[X_test[:, 1] == 0], nonchocolate_preds)
```


10.99

Let's practice

MODEL VALIDATION IN PYTHON

Classification metrics

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

Classification metrics

- Precision
- Recall (also called sensitivity)
- Accuracy
- Specificity
- F1-Score, and its variations
- ...

Classification metrics

- **Precision**
- **Recall** (also called sensitivity)
- **Accuracy**
- Specificity
- F1-Score, and its variations
- ...

Confusion matrix

		Predicted Values	
		0	1
Actual Values	0	23 (TN)	7 (FP)
	1	8 (FN)	62 (TP)

True Positive: Predict/Actual are both 1

True Negative: Predict/Actual are both 0

False Positive: Predicted 1, actual 0

False Negative: Predicted 0, actual 1

```
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, test_predictions)
print(cm)
```

```
array([[ 23,   7],
       [   8,  62]])
```

```
cm[<true_category_index>, <predicted_category_index>]
cm[1, 0]
```

```
8
```

Accuracy

		Predicted Values	
		0	1
Actual Values	0	23	7
	1	8	62

$$\frac{23(\text{TN}) + 62(\text{TP})}{23 + 7 + 8 + 62} = .85$$

Precision

Predicted Values			
		0	1
Actual Values	0	23	7
	1	8	62

$$\frac{62(\text{TP})}{62(\text{TP})+7(\text{FP})} = .90$$

Recall

Predicted Values			
		0	1
Actual Values	0	23	7
	1	8	62

$$\frac{62(\text{TP})}{62(\text{TP})+8(\text{FN})} = .885$$

Accuracy, precision, recall

```
from sklearn.metrics import accuracy_score, precision_score, recall_score  
accuracy_score(y_test, test_predictions)
```

.85

```
precision_score(y_test, test_predictions)
```

.8986

```
recall_score(y_test, test_predictions)
```

.8857

Practice time

MODEL VALIDATION IN PYTHON

The bias-variance tradeoff

MODEL VALIDATION IN PYTHON




Kasey Jones
Data Scientist

Variance

- Variance: following the training data too closely
 - Fails to generalize to the test data
 - Low training error but high testing error
 - Occurs when models are overfit and have high complexity


Overfitting models (high variance)




Bias

- Bias: failing to find the relationship between the data and the response
 - High training/testing error
 - Occurs when models are underfit

Underfitting models (high bias)



Optimal performance



- Bias-Variance Tradeoff

Parameters causing over/under fitting

```
rfc = RandomForestClassifier(n_estimators=100, max_depth=4)
rfc.fit(X_train, y_train)

print("Training: {0:.2f}".format(accuracy_score(y_train, train_predictions)))
```

```
Training: .84
```

```
print("Testing: {0:.2f}".format(accuracy_score(y_test, test_predictions)))
```

```
Testing: .77
```

```
rfc = RandomForestClassifier(n_estimators=100, max_depth=14)
rfc.fit(X_train, y_train)

print("Training: {0:.2f}".format(accuracy_score(y_train, train_predictions)))
```

```
Training: 1.0
```

```
print("Testing: {0:.2f}".format(accuracy_score(y_test, test_predictions)))
```

```
Testing: .83
```

```
rfc = RandomForestClassifier(n_estimators=100, max_depth=10)
rfc.fit(X_train, y_train)

print("Training: {0:.2f}".format(accuracy_score(y_train, train_predictions)))
```

```
Training: .89
```

```
print("Testing: {0:.2f}".format(accuracy_score(y_test, test_predictions)))
```

```
Testing: .86
```

**Remember, only you
can prevent
overfitting!**

MODEL VALIDATION IN PYTHON


The problems with holdout sets

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

Transition validation



Model 1

```
X_train, X_val, y_train, y_val =  
    train_test_split(X, y,  
                    test_size=0.2)
```

```
rf = RandomForestRegressor()
```

```
rf.fit(X_train, y_train)  
out_of_sample = rf.predict(X_test)  
print(mae(y_test, out_of_sample))
```

10.24

Traditional training splits

```
cd = pd.read_csv("candy-data.csv")  
s1 = cd.sample(60, random_state=1111)  
s2 = cd.sample(60, random_state=1112)
```

Overlapping candies:

```
print(len([i for i in s1.index if i in s2.index]))
```

39

Traditional training splits

Chocolate Candies:

```
print(s1.chocolate.value_counts()[0])  
print(s2.chocolate.value_counts()[0])
```

34

30

The split matters

Sample 1 Testing Error

```
print('Testing error: {0:.2f}'.format(mae(s1_y_test, rfr.predict(s1_X_test))))
```

10.32

Sample 2 Testing Error

```
print('Testing error: {0:.2f}'.format(mae(s2_y_test, rfr.predict(s2_X_test))))
```

11.56

Train, validation, test

```
X_temp, X_val, y_temp, y_val = train_test_split(..., random_state=1111)
X_train, X_test, y_train, y_test = train_test_split(..., random_state=1111)

rfr = RandomForestRegressor(n_estimators=25, random_state=1111, max_features=4)
rfr.fit(X_train, y_train)
print('Validation error: {0:.2f}'.format(mae(y_test, rfr.predict(X_test))))
```

9.18

```
print('Testing error: {0:.2f}'.format(mae(y_val, rfr.predict(X_val))))
```

8.98

Round 2

```
X_temp, X_val, y_temp, y_val = train_test_split(..., random_state=1171)
X_train, X_test, y_train, y_test = train_test_split(..., random_state=1171)

rfr = RandomForestRegressor(n_estimators=25, random_state=1111, max_features=4)
rfr.fit(X_train, y_train)
print('Validation error: {0:.2f}'.format(mae(y_test, rfr.predict(X_test))))
```

8.73

```
print('Testing error: {0:.2f}'.format(mae(y_val, rfr.predict(X_val))))
```


10.91

Holdout set exercises

MODEL VALIDATION IN PYTHON


Cross-validation

MODEL VALIDATION IN PYTHON





Kasey Jones
Data Scientist

Cross-validation



Cross-validation



`n_splits` : number of cross-validation splits

`shuffle` : boolean indicating to shuffle data before splitting

`random_state` : random seed

```
from sklearn.model_selection import KFold
```

```
X = np.array(range(40))
```

```
y = np.array([0] * 20 + [1] * 20)
```

```
kf = KFold(n_splits=5)
```

```
splits = kf.split(X)
```

```
kf = KFold(n_splits=5)
splits = kf.split(X)
for train_index, test_index in splits:
    print(len(train_index), len(test_index))
```

```
32 8 32 8 32 8 32 8 32 8
```

```
# Print one of the index sets:
print(train_index, test_index)
```

```
[ 0  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 ...]
[32 33 34 35 36 37 38 39]
```

```
rfr = RandomForestRegressor(n_estimators=25, random_state=1111)
errors = []
for train_index, val_index in splits:
    X_train, y_train = X[train_index], y[train_index]
    X_val, y_val = X[val_index], y[val_index]

    rfr.fit(X_train, y_train)
    predictions = rfr.predict(X_test)
    errors.append(<some_accuracy_metric>)
print(np.mean(errors))
```

4.25

Practice time

MODEL VALIDATION IN PYTHON

sklearn's `cross_val_score()`

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

cross_val_score()

```
from sklearn.model_selection import cross_val_score
from sklearn.ensemble import RandomForestClassifier
rfc = RandomForestClassifier()
```

estimator : the model to use

X : the predictor dataset

y : the response array

cv : the number of cross-validation splits

```
cross_val_score(estimator=rfc, X=X, y=y, cv=5)
```

Using scoring and make_scorer

The cross_val_score `scoring` parameter:

```
# Load the Methods
from sklearn.metrics import mean_absolute_error, make_scorer
```

```
# Create a scorer
mae_scorer = make_scorer(mean_absolute_error)
```

```
# Use the scorer
cross_val_score(<estimator>, <X>, <y>, cv=5, scoring=mae_scorer)
```

Load all of the `sklearn` methods

```
from sklearn.ensemble import RandomForestRegressor
from sklearn.model_selection import cross_val_score
from sklearn.metrics import mean_squared_error, make_scorer
```

Create a model and a scorer

```
rfc = RandomForestRegressor(n_estimators=20, max_depth=5, random_state=1111)
mse = make_scorer(mean_squared_error)
```

Run `cross_val_score()`

```
cv_results = cross_val_score(rfc, X, y, cv=5, scoring=mse)
```


Accessing the results

```
print(cv_results)
```

```
[196.765, 108.563, 85.963, 222.594, 140.942]
```

Report the mean and standard deviation:

```
print('The mean: {}'.format(cv_results.mean()))  
print('The std: {}'.format(cv_results.std()))
```

```
The mean: 150.965
```

```
The std: 51.676
```

Let's practice!
MODEL VALIDATION IN PYTHON


Leave-one-out- cross-validation (LOOCV)

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

LOOCV



When to use LOOCV?

Use when:

- The amount of training data is limited
- You want the absolute best error estimate for new data

Be cautious when:

- Computational resources are limited
- You have a lot of data
- You have a lot of parameters to test

LOOCV Example

```
n = X.shape[0]
mse = make_scorer(mean_squared_error)
cv_results = cross_val_score(estimator, X, y, scoring=mse, cv=n)
```

```
print(cv_results)
```

```
[5.45, 10.52, 6.23, 1.98, 11.27, 9.21, 4.65, ... ]
```

```
print(cv_results.mean())
```

```
6.32
```

Let's practice

MODEL VALIDATION IN PYTHON

Introduction to hyperparameter tuning

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

Model parameters

Parameters are:

- Learned or estimated from the data
- The result of fitting a model
- Used when making future predictions
- Not manually set

Linear regression parameters

Parameters are created by fitting a model:

```
from sklearn.linear_model import LinearRegression
lr = LinearRegression()
lr.fit(X, y)
print(lr.coef_, lr.intercept_)
```

```
[[0.798, 0.452]] [1.786]
```

Linear regression parameters

Parameters do not exist before the model is fit:

```
lr = LinearRegression()  
print(lr.coef_, lr.intercept_)
```

```
AttributeError: 'LinearRegression' object has no attribute 'coef_'
```

Model hyperparameters

Hyperparameters:

- Manually set *before* the training occurs
- Specify how the training is supposed to happen

Random forest hyperparameters

Hyperparameter	Description	Possible Values (default)
n_estimators	Number of decision trees in the forest	2+ (10)
max_depth	Maximum depth of the decision trees	2+ (None)
max_features	Number of features to consider when making a split	See documentation
min_samples_split	The minimum number of samples required to make a split	2+ (2)

What is hyperparameter tuning?

Hyperparameter tuning:

- Select hyperparameters
- Run a single model type at different value sets
- Create ranges of possible values to select from
- Specify a single accuracy metric

Specifying ranges

```
depth = [4, 6, 8, 10, 12]
samples = [2, 4, 6, 8]
features = [2, 4, 6, 8, 10]
# Specify hyperparameters
rfc = RandomForestRegressor(
    n_estimators=100, max_depth=depth[0],
    min_samples_split=samples[3], max_features=features[1])
rfr.get_params()
```

```
{'bootstrap': True,
 'criterion': 'mse'
 ...
}
```

Too many hyperparameters!

```
rfr.get_params()
```

```
{'bootstrap': True,  
 'criterion': 'mse',  
 'max_depth': 4,  
 'max_features': 4,  
 'max_leaf_nodes': None,  
 'min_impurity_decrease': 0.0,  
 'min_impurity_split': None,  
 'min_samples_leaf': 1,  
 'min_samples_split': 8,  
 ...  
}
```


General guidelines

- Start with the basics
- Read through the documentation
- Test practical ranges

Let's practice!
MODEL VALIDATION IN PYTHON


RandomizedSearchCV

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

Grid searching hyperparameters



Grid searching continued

Benefits:

- Tests every possible combination

Drawbacks:

- Additional hyperparameters increase training time exponentially

Better methods

- Random searching
- Bayesian optimization

Random search

```
from sklearn.model_selection import RandomizedSearchCV

random_search = RandomizedSearchCV()
```

Parameter Distribution:

```
param_dist = {"max_depth": [4, 6, 8, None],
              "max_features": range(2, 11),
              "min_samples_split": range(2, 11)}
```

Random search parameters

Parameters:

- `estimator` : the model to use
- `param_distributions` : dictionary containing hyperparameters and possible values
- `n_iter` : number of iterations
- `scoring` : scoring method to use

Setting RandomizedSearchCV parameters

```
param_dist = {"max_depth": [4, 6, 8, None],  
              "max_features": range(2, 11),  
              "min_samples_split": range(2, 11)}
```

```
from sklearn.ensemble import RandomForestRegressor  
from sklearn.metrics import make_scorer, mean_absolute_error  
  
rfr = RandomForestRegressor(n_estimators=20, random_state=1111)  
scorer = make_scorer(mean_absolute_error)
```

RandomizedSearchCV implemented

Setting up the random search:

```
random_search =\
    RandomizedSearchCV(estimator=rfr,
                       param_distributions=param_dist,
                       n_iter=40,
                       cv=5)
```

- We cannot do hyperparameter tuning without understanding model validation
- Model validation allows us to compare multiple models and parameter sets

RandomizedSearchCV implemented

Setting up the random search:

```
random_search =\
    RandomizedSearchCV(estimator=rfr,
                       param_distributions=param_dist,
                       n_iter=40,
                       cv=5)
```

Complete the random search:

```
random_search.fit(X, y)
```

Let's explore some examples!

MODEL VALIDATION IN PYTHON

Selecting your final model

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

```
# Best Score  
rs.best_score_
```

```
5.45
```

```
# Best Parameters  
rs.best_params_
```

```
{'max_depth': 4, 'max_features': 8, 'min_samples_split': 4}
```

```
# Best Estimator  
rs.best_estimator_
```

Other attributes

```
rs.cv_results_  
rs.cv_results_['mean_test_score']
```

```
array([5.45, 6.23, 5.87, 5.91, 5.67])
```

```
# Selected Parameters:  
rs.cv_results_['params']
```

```
[{'max_depth': 10, 'min_samples_split': 8, 'n_estimators': 25},  
 {'max_depth': 4, 'min_samples_split': 8, 'n_estimators': 50},  
 ...]
```

Using .cv_results_

Group the max depths:

```
max_depth = [item['max_depth'] for item in rs.cv_results_['params']]
scores = list(rs.cv_results_['mean_test_score'])
d = pd.DataFrame([max_depth, scores]).T
d.columns = ['Max Depth', 'Score']
d.groupby(['Max Depth']).mean()
```

Max Depth	Score
2.0	0.677928
4.0	0.753021
6.0	0.817219
8.0	0.879136
10.0	0.896821

Other attributes continued

Uses of the output:

- Visualize the effect of each parameter
- Make inferences on which parameters have big impacts on the results

Max Depth	Score
2.0	0.677928
4.0	0.753021
6.0	0.817219
8.0	0.879136
10.0	0.896821

Selecting the best model

`rs.best_estimator_` contains the information of the best model

```
rs.best_estimator_
```

```
RandomForestRegressor(bootstrap=True, criterion='mse', max_depth=8,  
                        max_features=8, max_leaf_nodes=None, min_impurity_decrease=0.0,  
                        min_impurity_split=None, min_samples_leaf=1,  
                        min_samples_split=12, min_weight_fraction_leaf=0.0,  
                        n_estimators=20, n_jobs=1, oob_score=False, random_state=1111,  
                        verbose=0, warm_start=False)
```

Comparing types of models

Random forest:

```
rfr.score(X_test, y_test)
```

6.39

Gradient Boosting:

```
gb.score(X_test, y_test)
```

6.23

Using `.best_estimator_`

Predict new data:

```
rs.best_estimator_.predict(<new_data>)
```

Check the parameters:

```
random_search.best_estimator_.get_params()
```

Save model for use later:

```
from sklearn.externals import joblib  
  
joblib.dump(rfr, 'rfr_best_<date>.pkl')
```

Let's practice!
MODEL VALIDATION IN PYTHON

Course completed!

MODEL VALIDATION IN PYTHON



Kasey Jones
Data Scientist

Course recap

Some topics covered:

- Accuracy/evaluation metrics
- Splitting data into train, validation, and test sets
- Cross-validation and LOOCV
- Hyperparameter tuning

Next steps

Check out [Kaggle](#)

Next steps

- [Hyperparameter Tuning in Python](#)
- [Introduction to Deep Learning in Python](#)

Thank you!

MODEL VALIDATION IN PYTHON