

CSM Berkeley 61B, Spring 2015: Week 3

What's wrong with these sum functions?

File: [BuggySums.java](#)

```
class BuggySums {

    public static int buggySum1(int[] a) {
        int total = 0;
        for (int i = 1; i < a.length; i++) {
            total += a[i];
        }
        return total;
    }

    public static int buggySum2(int[] a) {
        int total = 0;
        for (int i = 0; i <= a.length; i++) {
            total += a[i];
        }
        return total;
    }

    public static int buggySum3(int[] a) {
        int i = 0;
        int total = 0;
        while (i < a.length) {
            total += a[i];
        }
        return total;
    }
}
```

Write `middle`, which takes in array of ints and returns the middle element.

If not element is in the exact middle, return the one to the left of the middle. Don't overthink this.

File: `ArrayExample.java`

```
import java.util.Arrays;

class ArrayExample {
    public static int middle(int[] arr) {

    }
}
```

Write `reverse`, which takes in an array of ints and reverses its elements in-place.

```
    public static void reverse(int[] arr) {

    }

    public static void main(String[] args) {
        int[] test1 = {1, 3, 3, 7, 42};
        System.out.println(Arrays.toString(test1));
        reverse(test1);
        System.out.println(Arrays.toString(test1));
    }
}
```

Write middle, for SLists.

Hint: why are our pointers called slow and fast?

If not element is in the exact middle, return the one to the left of the middle.

File: [SList.java](#)

```
public class SList {
    private SListNode head;
    public SList(SListNode head) {
        this.head = head;
    }
    public SList() {
        this(null);
    }

    public static Object middle(SList list) {

        while (
            ) {

        }
        return
    }

    public String toString() {
        String result = "";
        for (SListNode cur = head; cur != null; cur = cur.next)
            result += cur.item.toString() + " ";
        return result;
    }

    public static void main(String[] args) {
        SList l = new SList(new SListNode(1, new SListNode(2, new SListNode(3))));
        System.out.println("l = " + l);
        System.out.println("l middle: " + middle(l));
    }
}

class SListNode {
    Object item; SListNode next;
    SListNode(Object item, SListNode next) {
        this.item = item; this.next = next;
    }
    SListNode(Object item) {
        this(item, null);
    }
}
```

Spot the bug! (extra time)

File: `IntListBug.java`

```
// TODO: This file contains (unintentional) errors.

class IntListBug {

    /**
     * Returns a list consisting of the elements of A followed by the
     * elements of B. May NOT modify items of A.
     */
    public static IntList buggyCatenate(IntList A, IntList B) {
        IntList C = new IntList(A.head, A.tail);

        IntList list2 = C;
        while (list2.tail != null) {
            list2 = list2.tail;
        }
        current.tail = B;
        return C;
    }

    public static void main(String[] args) {
        IntList A = IntList.list(1, 2, 3);
        IntList B = IntList.list(4, 5, 6);
        IntList C = buggyCatenate(A, B);
    }
}

class IntList {
    public int head;
    public IntList tail;

    public IntList(int head, IntList tail) {
        this.head = head;
        this.tail = tail;
    }
}
```