Leveraging TF-IDF and BERT for Hate Speech Detection on Twitter

Ashanti Boone
Department of Computer Science
Bowie State University
Bowie, MD
boonea1212@students.bowiestate.edu

Vivek Shandilya
Department of Computer Science
Bowie State University
Bowie, MD
vshandilya@bowiestate.edu

***Abstract*—Hate speech has become increasingly prevalent on social media platforms, making it essential to develop automated real-time detection and moderation systems. In this work, we present a system for detecting hate speech using Natural Language Processing (NLP) techniques. We tested our system with publicly available Twitter datasets sourced from Kaggle. The approach includes preprocessing textual data, extracting features, and using dictionaries of hateful words to classify text as hate-speech or not-hate-speech. The method integrates common NLP preprocessing techniques, such as feature extraction, tokenization, and lemmatization, alongside word frequency analysis to enhance detection accuracy.**

***Index Terms*—Hate Speech Detection, Natural Language Processing (NLP), Text Classification, Machine Learning, Content Moderation**

I. Introduction

Hate speech, often defined as communication that belittles, insults, or promotes violence against individuals or groups based on attributes such as race, religion, ethnicity, gender, or sexual orientation, etc has become a pressing concern in today's digital age. With the rise of social media platforms like Twitter, the potential for spreading harmful speech has drastically increased. These platforms provide vast networks for users to interact, but they also serve as a space for the rapid spread of hate speech.

The digital nature of hate speech amplifies the issue due to its ability to go viral, reaching millions of users in a short span of time. Social media platforms often struggle to moderate harmful content quickly and effectively, allowing hate speech to persist and sometimes incite real-world violence or contribute to systemic discrimination. This particularly concerns vulnerable populations, including children and teens, who use these platforms regularly. Many young users have been exposed to cyberbullying, which can lead to emotional distress, social isolation, and even tragic outcomes such as self-harm or suicide.

Traditional methods of content moderation rely heavily on manual review by human moderators, but the sheer volume of online content makes this approach inefficient. Moreover, hate speech is often subtle and can be context-dependent, further complicating manual detection efforts. In response, researchers and technologists have turned to automated solutions, particularly using Natural Language Processing (NLP) to detect and moderate hate speech in real-time. However, this task remains challenging due to the complexities of human language, including slang, sarcasm, and regional dialects, as well as the evolving nature of online discourse.

Given the widespread and harmful impact of hate speech, there is a critical need to develop more effective and scalable methods to detect and prevent its spread. This is especially important as social media continues to play an increasingly integral role in communication, particularly among younger generations. Automated hate speech detection systems, built using NLP techniques, offer a promising solution by analyzing large volumes of content efficiently and providing real-time alerts for moderation. Developing robust NLP models that can handle the nuances of hate speech while maintaining accuracy and fairness is an ongoing challenge that requires further research and innovation.

To address the problem of hate speech detection, various Natural Language Processing (NLP) techniques can be employed, ranging from basic text preprocessing to advanced machine learning algorithms. The first step is text preprocessing, which includes tokenization to break the text into individual words, lowercasing to ensure uniformity and stop word removal from eliminating common words that do not add significant meaning. Additionally, lemmatization or stemming can be applied to reduce words to their base or root forms, standardizing variations of words.

Following preprocessing, feature extraction techniques come into play. Bag of Words (BoW) represents the text by counting word occurrences. At the same time, Term Frequency-Inverse Document Frequency (TF-IDF) weighs the importance of words based on their frequency in a document relative to their frequency across all documents. Word embeddings, such as Word2Vec or GloVe, can convert words into dense vector representations that capture semantic meanings, allowing models to understand contextual relationships.

Another approach involves using hateful word dictionaries, which utilize pre-compiled lists of known hateful or offensive words as a baseline for classification. This method can be enhanced by incorporating context to reduce false positives. For the classification process, various machine learning algorithms can be employed, including traditional classifiers like Logistic Regression, Support Vector Machines (SVM), and

Decision Trees. Ensemble methods, such as Random Forest or Gradient Boosting, can improve performance by combining the predictions of multiple models.

Deep learning approaches are also effective for hate speech detection. Recurrent Neural Networks (RNNs), particularly Long Short-Term Memory (LSTM) networks, are suitable for sequence data, making them ideal for processing text where context is important. Convolutional Neural Networks (CNNs), traditionally used for image processing, can be adapted for text data to capture local patterns and features. Additionally, transformer models like BERT (Bidirectional Encoder Representations from Transformers) are particularly valuable due to their ability to understand the context of words in relation to all other words in a sentence, providing a more nuanced detection capability.

Cross-validation techniques can be employed to assess robustness and evaluate and validate the model, ensuring that it performs well across different data subsets. Important metrics such as accuracy, precision, recall, and F1-score are essential for understanding the system's effectiveness in identifying hate speech without falsely labeling benign content. Implementing a feedback loop incorporating user feedback can also help refine and improve the model over time, allowing for continuous learning and adaptation to new forms of hate speech as language evolves. By leveraging a combination of these techniques, the proposed hate speech detection system can be made robust, efficient, and effective in identifying harmful content across various social media platforms, ultimately contributing to a safer online environment.

The proposed solution for detecting hate speech leverages a systematic approach integrating Natural Language Processing (NLP) techniques, machine learning, and user feedback mechanisms. The methodology begins with collecting datasets from popular social media platforms, specifically Twitter, utilizing publicly available resources from Kaggle. These datasets are crucial as they encapsulate a wide array of user-generated content, providing a rich context for the training and evaluation of the detection system. By analyzing posts and comments across these platforms, the solution aims to create a model capable of identifying various forms of hate speech effectively.

The first step in the proposed method involves rigorous text preprocessing. This phase includes tokenization, lowercasing, stop word removal, and lemmatization to prepare the textual data for analysis. By transforming the text into a clean, structured format, the model can focus on the most relevant features for classification. Following preprocessing, feature extraction techniques such as Bag of Words (BoW) and Term Frequency-Inverse Document Frequency (TF-IDF) will be applied to convert the textual data into numerical representations that machine learning algorithms can process. Additionally, using word embeddings will help capture the semantic relationships between words, providing the model with a deeper understanding of context.

Once the data is preprocessed and features are extracted, the next phase involves the implementation of machine learning algorithms for classification. The proposed system will utilize a combination of traditional classifiers, such as Logistic Regression and Support Vector Machines (SVM), along with ensemble methods like Random Forest. These algorithms will be trained on labeled datasets, allowing the model to learn the characteristics of hate speech. Furthermore, deep learning techniques, including Recurrent Neural Networks (RNNs) and transformer models like BERT, will be explored to enhance the model's performance. These advanced models are particularly effective in capturing the complexities and nuances of human language, which are essential for accurately identifying hate speech.

To ensure the proposed solution is both effective and reliable, robust evaluation methods will be employed. The model will undergo k-fold cross-validation to assess its performance across various data subsets, with metrics such as accuracy, precision, recall, and F1 score being closely monitored. This thorough evaluation process will help identify areas for improvement and ensure that the model minimizes false positives and negatives. Additionally, implementing a feedback mechanism will allow users to report false classifications, providing valuable data for continuous improvement. This iterative approach ensures that the model can adapt to evolving language trends and the changing nature of online discourse.

Ultimately, the proposed solution aims to create a comprehensive hate speech detection system that not only identifies harmful content in real time but also contributes to safer online environments. By combining advanced NLP techniques, machine learning algorithms, and user engagement, this method seeks to address the pressing issue of hate speech on social media platforms effectively. The outcome will be a scalable and efficient detection system that enhances content moderation efforts and fosters a more inclusive digital space for users of all ages.

A comprehensive testing and experimentation process will be conducted to evaluate the effectiveness of the proposed hate speech detection solution. The experiment will involve training the machine learning models on a labeled dataset of social media posts from platforms such as Instagram, TikTok, and Twitter, with predefined categories for hate speech and non-hate speech. The dataset will be divided into training, validation, and test sets to ensure the model's generalizability. During testing, cross-validation techniques, such as k-fold cross-validation, will be used to split the dataset into multiple subsets, ensuring that the model performs well on unseen data. The model's performance will be measured using key evaluation metrics, including accuracy, precision, recall, and F1-score, focusing on minimizing false positives (incorrectly classifying non-hate speech as hate speech) and false negatives (failing to identify actual hate speech).

The experiment will also compare the performance of different machine learning algorithms, such as Logistic Regression, Support Vector Machines (SVM), and deep learning models like RNNs, to determine which approach yields the best results. Furthermore, dictionary-based methods using hateful word lists will be incorporated into the experiment to establish a baseline for classification accuracy. By comparing this with

more advanced models, the efficacy of machine learning and deep learning techniques in hate speech detection can be determined. Finally, user feedback will be integrated into the system during testing, allowing real-world users to report incorrect classifications. This feedback will be used to refine and update the model continuously, ensuring that the solution evolves and improves over time as it encounters new language patterns and forms of hate speech.

For the hate speech detection project, two primary datasets will be utilized to ensure a comprehensive analysis of user-generated content across different social media platforms. The first dataset is the Hate Speech and Offensive Language Dataset from Kaggle, which contains labeled tweets categorized as hate speech, offensive language, and neither. This dataset provides a rich source of data that spans a diverse range of topics and user interactions, making it suitable for training machine learning models to identify various forms of hate speech. The dataset's structure allows for effective preprocessing and feature extraction, enabling the detection system to learn from clear examples of both hate speech and non-hate speech content.

The second dataset, sourced from Data World, contains Twitter user data that provides additional context about user profiles and interactions. This dataset includes valuable information such as user demographics, engagement metrics, and historical activity, which can enhance the analysis by allowing the model to consider not just the content of tweets but also the context in which they were made. By combining these two datasets, the proposed solution can leverage both the text-based features of tweets and the contextual data of user behavior, thereby improving the accuracy and effectiveness of the hate speech detection system.

Together, these data sets will serve as the foundation for training, validating, and testing the model, enabling a robust approach to identify and mitigate hate speech across social media platforms. Their diverse content will help ensure that the detection system is well-equipped to handle the various forms and contexts of hate speech encountered in real-world applications.

In this project, TF-IDF (Term Frequency-Inverse Document Frequency) and BERT (Bidirectional Encoder Representations from Transformers) are used due to their effectiveness in handling the complexity of hate speech detection on social media platforms like Twitter. TF-IDF is ideal for determining the significance of words within a dataset by weighing their frequency against how common they are in the overall corpus. This allows the model to prioritize important, contextually significant words, such as offensive language or slurs, without overemphasizing common words like "the" or "is." This focus on relevant terms provides a more refined detection method compared to simpler approaches like bag-of-words, which tend to assign equal importance to all words, making it harder to detect the nuanced language often present in hate speech.

On the other hand, BERT is chosen for its strength in understanding context by processing words in relation to their surrounding text. Since hate speech often relies on context to be accurately identified, BERT's ability to examine both the left and right context of a word provides deeper insight into its intended meaning. This is especially crucial because offensive terms may be ambiguous without the right context, and BERT's transformer-based architecture allows it to capture these subtleties. While other algorithms like Support Vector Machines (SVM) or Logistic Regression can perform binary classification, they are less effective at capturing the context-dependent nature of hate speech. Similarly, Naive Bayes assumes feature independence, which limits its ability to recognize hate speech patterns accurately, and models like LSTM (Long Short-Term Memory Networks) may require extensive preprocessing and longer training times.

Ultimately, the combination of TF-IDF for identifying key terms and BERT for understanding context provides a comprehensive approach to hate speech detection. This hybrid approach is particularly suited for platforms like Twitter, where language is fast-evolving, and hate speech detection requires both precision in identifying harmful terms and the ability to interpret them within their specific context. These algorithms outperform others, such as Naive Bayes, which assumes that features are independent, or LSTM (Long Short-Term Memory networks), which, although effective for sequential data, may require more extensive preprocessing and longer training times for similar results. Ultimately, combining TF-IDF to prioritize relevant terms and BERT to handle context offers a powerful hybrid approach for detecting hate speech on platforms like Twitter, where language evolves rapidly, and subtle differences in usage can make a significant impact.

II. Literature Review

In an article by Nascimento et al. (2023), they explored hate speech detection by leveraging machine learning and deep learning techniques to address the growing issue of hateful language on social media platforms. The authors aim to develop an effective classification system that accurately identifies various forms of hate speech across different datasets. Their method involves using advanced algorithms, such as LSTM (Long Short-Term Memory) networks, to analyze text data for context and sentiment. The results demonstrate a significant improvement in detection rates compared to traditional approaches, highlighting the potential of these techniques in real-world applications. This study contributes to my project by emphasizing the need for a comprehensive feature set that can inform my approach to utilizing dictionaries of hateful words to classify and detect hate speech effectively [1].

A study by Malmasi and Zampieri (2017) investigated hate speech detection on social media using machine learning techniques. The authors aim to create a robust classification system capable of accurately identifying hate speech across various datasets. Their methodology uses diverse features, including lexical and syntactic elements, to enhance classification performance. The findings indicate that integrating multiple features significantly improves detection rates, demonstrating the effectiveness of their approach in addressing the pervasive issue of hate speech online. Their findings underscore the

necessity of curating a representative dataset for my project, ensuring that my classification system can generalize well across different contexts and user interactions [2].

In a review by Jahan and Oussalah (2023), they examine the effectiveness of machine learning models in detecting hate speech across various social media platforms. It discusses the challenges of contextual understanding and the nuances of language in accurately identifying hateful content. The authors evaluate different algorithms and feature extraction techniques, finding that ensemble methods and deep learning approaches yield better performance. Their findings highlight the importance of continuous improvement in hate speech detection systems to address the evolving nature of online communication. This review enhances my understanding of existing methodologies, guiding me in selecting the most appropriate techniques and models for my project, ultimately aiming for a more robust hate speech detection framework [3].

A study by Kumar et al (2021) discusses the application of deep learning techniques for detecting hate speech on social media. It reviews various neural network architectures, such as convolutional and recurrent neural networks, and highlights their effectiveness in understanding contextual nuances of language. The study emphasizes the importance of feature extraction and model training on large datasets to improve detection accuracy. Kumar concludes that while deep learning shows promise, ongoing research is needed to refine these models for better real-world applicability. Understanding these techniques contributes to my project by demonstrating the effectiveness of deep learning in this context, emphasizing the need to incorporate advanced models to enhance my hate speech detection system [4].

The article "VAIS Hate Speech Detection System: A Deep Learning-based Approach for System Combination" (2019) by Thai Binh Nguyen et al. explores the development of a sophisticated hate speech detection system utilizing ensemble methods in deep learning. The authors aim to enhance the accuracy of hate speech detection on social media platforms, addressing the rising prevalence of abusive language. Their system integrates multiple models to improve performance, showcasing the potential of ensemble learning in tackling complex NLP tasks. The methodology employs a combination of different algorithms, including Convolutional Neural Networks (CNNs) and Recurrent Neural Networks (RNNs), to analyze and classify text data effectively. The results of their experiments indicate that this ensemble approach significantly outperforms traditional single-model methods, achieving competitive F1 scores in various benchmarks. This highlights the importance of combining diverse models for better detection capabilities, contributing valuable insights for my own research project focused on hate speech detection. By examining Nguyen et al.'s work, I learned about the effectiveness of ensemble methods in improving model performance and the importance of integrating various algorithms to handle the intricacies of natural language. This reinforces my decision to explore multiple techniques in my project and informs my understanding of how to enhance the accuracy of hate speech detection systems [5].

A survey by Subramanian et al. (2023) provides a comprehensive survey of hate speech detection and sentiment analysis using machine learning and deep learning models. It reviews various methodologies, comparing their effectiveness and highlighting the challenges faced in these domains. The authors also discuss the importance of dataset quality and feature selection in improving detection accuracy. This survey contributes to my research by offering insights into different approaches and methodologies, helping me refine my hate speech detection strategy [6].

The article "Generalizing Hate Speech Detection Using Multi-Task Learning: A Case Study of Political Public Figures" (2025) explores the use of multi-task learning (MTL) to enhance the detection of hate speech, particularly in the context of political public figures. The authors argue that traditional hate speech detection models often struggle to generalize across different contexts or domains, particularly when language or topics shift. To address this, the study applies MTL, which allows models to learn shared representations across related tasks, improving the model's ability to generalize beyond a single dataset or context. The paper demonstrates that by training the model on multiple tasks, such as detecting hate speech while simultaneously identifying political figures, the model improves both its accuracy and robustness in detecting hate speech. The case study focuses on how public figures are often targeted with offensive speech, and how multi-task learning can help capture the nuances of this particular kind of hate speech. This research contributes to your project by providing insights into how MTL can be used to improve the generalization of hate speech detection models. By implementing similar techniques, your project could become more versatile, able to handle varied datasets, and detect hate speech more accurately across different contexts [7].

The article "Challenges of Hate Speech Detection in Social Media" (2021) discusses the difficulties faced in automatically detecting hate speech across platforms like Twitter, Facebook, and others. The authors highlight several key challenges, including the nuanced and evolving nature of hate speech, the use of coded language, and the context-dependent nature of offensive terms. They emphasize that hate speech can take various forms, making it difficult for traditional machine-learning models to distinguish between harmful and benign statements. The study also touches on the limitations of existing datasets, which often fail to capture the full complexity of hate speech due to biases in labeling and data collection methods. Additionally, the authors explore the ethical concerns around automated hate speech detection, particularly the risk of over-censorship and the balance between free speech and content moderation. This article contributes to your research by highlighting the need for more comprehensive datasets and context-aware models in hate speech detection. By understanding these challenges, your project can address these issues by using more diverse datasets and considering the contextual use of language in your classification system [8].

The article "Automatic Hate Speech Detection on Social Media: A Brief Survey" (2019) provides a concise review of the current methods and techniques used for detecting hate speech on social media platforms. The authors discuss various approaches, including traditional machine learning techniques and more advanced deep learning methods. They emphasize the challenges of detecting hate speech due to its dynamic and context-dependent nature, as well as the lack of clear definitions and guidelines across different platforms. The survey explores different datasets and classifiers that have been applied to the problem, highlighting key advances and persistent gaps. One of the main points of discussion is the difficulty of generalizing models to detect hate speech across multiple languages and regions, due to cultural differences in expression and the evolving language of hate speech online. This article contributes to your project by providing an overview of the challenges in hate speech detection, helping to refine the focus on methods that address cultural and contextual nuances in online communication. It also reinforces the importance of using comprehensive datasets for training models to improve detection accuracy across different platforms [9].

The paper "A Curated Dataset for Hate Speech Detection on Social Media" (2023) focuses on building an extensive dataset to enhance hate speech detection systems on social media platforms. It includes 451,709 sentences, 371,452 of which are labeled as hate speech and 80,250 as non-hate speech. The dataset incorporates modern social media language features such as emoticons, emojis, hashtags, slang, and contractions, reflecting current online trends. To balance the dataset, an augmented version was created with 726,120 samples, using a custom vocabulary of 145,046 words and 6403 contractions, which can aid NLP tasks by reducing out-of-vocabulary issues. This resource provides a classifier for detecting hate speech and serves as a tool for data preprocessing in other NLP projects. This dataset contributes to my research by offering a rich resource that reflects the nuances of modern social media language, which will improve the accuracy of my hate speech detection model. Including augmented and curated datasets will also help address vocabulary gaps, enhancing the model's ability to adapt to various hate speech contexts [10].

III. Problem Statement

Hate speech refers to any form of threatening, abusive, or derogatory language that discriminates against individuals based on characteristics such as ethnicity, religion, sexual orientation, gender, or disability. It has become a pervasive issue on social media platforms, particularly Twitter, which has seen an increase in hate speech due to recent changes in ownership and content moderation policies. This type of speech is not just harmful on the platform itself but has the potential to incite real-world violence. The lack of a standardized definition makes it difficult to legally regulate, leaving marginalized groups such as the LGBTIA community, racial minorities, women, and people with disabilities especially vulnerable. According to the U.S. Department of Justice, 2023 saw over 11,000 single-biased hate incidents and 415 multiple-biased incidents, affecting more than 14,000 victims. From January to June 2024 alone, Twitter suspended over 2,000 accounts and flagged nearly 5 million posts for hate speech violations.

Despite social media companies' efforts to use artificial intelligence, user reporting, and human moderators to combat hate speech, the sheer volume of content and the evolving nature of hateful language make it difficult to address this problem effectively. Left unchecked, hate speech can lead to stigmatization, discrimination, and large-scale violence, including physical altercations and riots.

This research aims to utilize machine learning and natural language processing (NLP) techniques to detect hate speech more effectively on Twitter. Unlike traditional keyword-based approaches, which may fail to capture context, this study will explore advanced techniques such as:

TF-IDF (Term Frequency-Inverse Document Frequency): A technique that assesses the importance of specific terms in a given dataset. This will help filter out irrelevant terms and highlight those commonly associated with hate speech. BERT (Bidirectional Encoder Representations from Transformers): A deep learning model capable of understanding the context of a word in a sentence, allowing for a more nuanced detection of hate speech. BERT's ability to consider both the left and right context of a word can improve the accuracy of hate speech classification by accounting for variations in phrasing and expression.

The datasets for this study will be sourced from Kaggle and GitHub, specifically curated for hate speech detection. The first dataset contains 10,000 unlabeled entries, which will be used for TF-IDF analysis to examine the frequency of terms, tested against a list of 180 identified hateful terms. The second dataset consists of over 25,000 entries, with the majority classified as non-hate speech or offensive content, and a smaller portion labeled as hate speech. This dataset will be used to train and evaluate the model's ability to detect hate speech.

A. Experiment Structure

Training Phase: The BERT model will be fine-tuned on this large Twitter dataset, focusing on tweets containing a mix of abusive, offensive, and neutral language. The training data will contain labeled examples to teach the model how to differentiate between hate speech and non-hate speech, based on both the content and context of the tweets. TF-IDF will be used alongside BERT to help assess the relevance of terms in the context of hate speech detection.

Testing Phase: After training, the model will be tested on a subset of the dataset to evaluate its ability to detect hate speech accurately. Metrics such as precision, recall, F1-score, and accuracy will be used to assess performance. Special attention will be paid to identifying false positives (non-hate speech incorrectly classified as hate speech) and false negatives (hate speech not flagged by the model).

Prediction and Buffer Overflow: In the context of buffer overflow detection (if needed as part of hate speech-related attacks or vulnerabilities), additional layers of algorithmic

training will be incorporated to predict tweet overflow scenarios (i.e., overloading the system with flagged hate speech). However, the primary focus of this experiment is on hate speech detection.

Dataset Size: The dataset will consist of two parts: the first dataset will have over 10,000 unlabeled tweets used for TF-IDF analysis, tested against a list of 180 hateful terms to check for frequency in the tweets. The second dataset will contain more than 25,000 tweets, with the majority classified as non-hate speech or offensive, and a portion labeled as hate speech. An augmented, balanced dataset of approximately 1,000 samples will also be used for training, with a hate word dictionary containing 180 identified hateful terms [11], [12].

Data Source: The data will be collected from public Twitter datasets available on Kaggle , with additional hate word lists sourced from online repositories (GitHub) and prior research studies on hate speech detection. By employing machine learning algorithms such as BERT and TF-IDF, the research aims to build a robust system that can not only detect hate speech more accurately but also better understand the context in which certain terms are used, thereby reducing false positives and negatives in real-time social media environments. The resulting system can be deployed on platforms like Twitter to help curb the spread of online hate speech.

IV. Proposed Solution

To address the growing challenge of hate speech detection on Twitter, this research proposes a multi-faceted approach utilizing both traditional and advanced natural language processing (NLP) techniques. Initially, data will be sourced from existing hate speech and non-hate speech datasets available on platforms like Kaggle and GitHub. This curated dataset will include tweets labeled for explicit hate speech, and it will be enhanced with additional lexicons to account for common contractions, slang, and hateful terminology that often appear on social media. Following this, preprocessing steps, such as tokenization and normalization, will ensure the data is standardized for effective analysis and split into training, validation, and test sets.

For feature extraction, we will implement Term Frequency-Inverse Document Frequency (TF-IDF), a foundational technique that assigns weight to terms based on their occurrence in the data, helping to prioritize relevant words associated with hate speech. TF-IDF provides a straightforward, interpretable baseline model to understand the influence of particular terms and phrases. To improve upon this, the study will utilize Bidirectional Encoder Representations from Transformers (BERT), an advanced machine learning model that captures contextual meaning by analyzing words bidirectionally within sentences. Fine-tuning BERT on our Twitter dataset allows the model to detect implicit forms of hate speech, which often rely on context, subtle cues, or idiomatic expressions.

The research will train both the TF-IDF and BERT-based models on labeled Twitter data, with performance evaluated through metrics like accuracy, precision, recall, and F1-score to ensure a comprehensive assessment of each model's detection capabilities. Cross-validation will further strengthen model reliability, particularly in differentiating explicit and implicit hate speech. Finally, after comparing model performances, the optimal solution will undergo additional testing in a real-time Twitter environment. The project envisions deploying this model as part of a content-monitoring tool or API, designed to flag or filter hate speech on social media, thus contributing to a safer digital environment.

A significant challenge in this research lies in identifying and accurately classifying metaphorical hate speech or implied hatefulness, which often leads to false positives. The complexity of detecting such nuanced language, especially when using natural language processing techniques like TF-IDF and BERT, becomes evident as these models primarily rely on explicit terms and common phrases associated with hate speech. This reliance can result in the misclassification of benign language as hateful, especially when terms commonly associated with hate speech appear in neutral or unrelated contexts. For instance, words that carry negative connotations in certain phrases may not necessarily signal hate speech but may be flagged erroneously by the algorithm. Terms like "the female" are marked as hate speech but can be used in a nonharmful manner, such as "the female looks really pretty." This highlights a key limitation in the approach, as purely lexical methods struggle to capture context and intent beyond individual terms or standard phrases.

Understanding these limitations, the experiment seeks to refine hate speech detection by carefully exploring these boundary cases, acknowledging that metaphorical or implied hate speech might sometimes evade our detection methods. Testing and validating within this framework allows us to gauge the effectiveness of TF-IDF and BERT models, particularly in distinguishing between literal and metaphorical usage. To further enhance model accuracy, the experiment will include training on expanded datasets with varied language patterns and additional layers of context analysis. These iterations aim to reduce the incidence of false positives while investigating the feasibility and validity of the chosen techniques in a complex linguistic landscape.

V. Methodology

The goal of this project was to detect hate speech in tweets using different machine-learning approaches. To achieve this, two models were experimented with: TF-IDF (Term Frequency-Inverse Document Frequency) and BERT (Bidirectional Encoder Representations from Transformers). The methodology used in each of these stages, along with the challenges encountered and adjustments made, is detailed below.

A. TF-IDF Approach

Initially, the TF-IDF method was applied to analyze the dataset. TF-IDF is a widely used technique for text classification tasks, consisting of two primary components: Term Frequency (TF) and Inverse Document Frequency (IDF). TF




Fig. 1. Screen shot of original tweet vs preprocessed tweet.



Fig. 2. Example of top 1000 words collected from dataset

measures how often a term appears in a document, normalized by the document's length, while IDF weighs the importance of the term based on how frequently it appears across the entire corpus. The underlying idea is that terms frequently appearing within a document but rarely across the entire corpus are more important for distinguishing that document from others.

To prepare the data for the TF-IDF vectorizer, extensive preprocessing was performed on the raw tweets. The text was first converted to lowercase to ensure uniformity and eliminate case sensitivity. Irrelevant content such as URLs, user mentions (e.g., @username), and hashtags were removed. Emojis, which could introduce noise into the dataset, were eliminated using the emoji library. Special characters, numbers, and punctuation were stripped, as they were unlikely to contribute meaningfully to hate speech detection. Additionally, common stopwords like "the," "is," and "and" were removed, as they do not add significant meaning in the context of detecting hate speech.

Once the data was cleaned, the TF-IDF Vectorizer from Scikit-learn was used to extract the most informative features from the tweets. The features were limited to the top 5000 most informative words based on their TF-IDF scores, which helped reduce the dimensionality of the data while retaining the most useful terms. The vectorizer then transformed the cleaned tweet text into a sparse matrix of TF-IDF features.

Despite these efforts, the TF-IDF approach presented several challenges. The most significant issue was context misclassification. Since TF-IDF is based solely on word frequency and does not account for the semantic context of words, certain terms were flagged as hate speech even when used in a neutral or non-offensive context. For example, phrases such as "white boy" were wrongly classified as hate speech because the word "white" appeared in the hate speech dictionary, even though the context of the phrase was not harmful. This limitation highlighted the need for a model that could better understand the context in which words were used.

Moreover, TF-IDF struggled to capture the nuances in language that are crucial for detecting hate speech. The model's

total_hate_terms	detected_terms	label
1	['all white']	Hate Speech
1	['white person']	Hate Speech
1	['white boy']	Hate Speech
1	['white person']	Hate Speech
1	['all white']	Hate Speech
1	['white person']	Hate Speech

Fig. 3. Screenshot of current detected hate speech and frequency in tweet.

reliance on keyword matching and term frequency made it difficult to identify more subtle expressions of hate speech that did not contain explicit hate-filled words. As a result, the performance of the TF-IDF model was less than satisfactory, underscoring the need for a more advanced, context-aware approach.

B. BERT Approach

After encountering limitations with the TF-IDF method, the BERT (Bidirectional Encoder Representations from Transformers) model was implemented. BERT is a more sophisticated deep learning model designed to understand the contextual relationships between words in a sentence by considering both left and right context, unlike TF-IDF, which only considers individual word frequencies without regard to context. BERT's transformer architecture is particularly well-suited for handling nuanced language, which is essential for tasks like hate speech detection, where the meaning of words can vary depending on their usage.

Before training the BERT model, the data needed to be preprocessed differently from the TF-IDF approach. The tweets were tokenized into subword units that BERT could understand, and BERT's pre-trained tokenizer was used to convert the text into input tokens. These tokens were then fed into the BERT model, which uses self-attention mechanisms to process the relationships between the words in the tweet.

During the initial round of training with BERT, an issue arose where the dataset was not correctly labeled with all three possible classifications: "hate speech," "offensive," or "neither." This oversight significantly affected the model's ability to classify the tweets accurately, as it was trained on incomplete label data. After correcting the labels and retraining the model, performance improved. However, the dataset imbalance remained a challenge. The number of hate speech tweets was smaller compared to neutral or offensive tweets, which impacted the model's ability to predict hate speech reliably. In response to this, techniques such as oversampling and undersampling were applied to balance the dataset before training.

The BERT model showed significant improvement over the TF-IDF approach, particularly in terms of contextual understanding. Unlike TF-IDF, BERT could effectively capture the meaning behind words based on their specific context, reducing the misclassification of neutral phrases as hate speech. Despite these improvements, it became evident that BERT's performance could still be enhanced further by adjusting hyperparameters and fine-tuning the model on a more balanced dataset.

In conclusion, while the TF-IDF approach provided initial insights into the dataset, it struggled with misclassification and failed to account for the subtle nuances in language essential for hate speech detection. Challenges such as context misclassification, dataset bias, and an inability to capture nuanced language prompted the exploration of more advanced models like BERT. Although BERT also faced challenges related to the imbalance of data sets and the consistency of labels, it offered a more effective approach to handling the complexities of hate speech detection. The shift from TF-IDF to BERT emphasized the importance of using models capable of understanding broader context and subtle word meanings, which is critical in tasks like hate speech detection.

VI. Challenges

The process of using both the TF-IDF and BERT models for the detection of hate speech presented several challenges that influenced the final results of the experiment. These challenges stemmed from both the inherent limitations of the methods and the complexities of processing real-world data, particularly the nuances of Twitter text.

A. TF-IDF Challenges

The initial approach utilized TF-IDF (Term Frequency-Inverse Document Frequency) vectorization to transform the data set into numerical features. Although this technique is effective for many traditional text classification tasks, it encountered significant challenges in the context of hate speech detection.

One of the primary issues was context misclassification. The TF-IDF approach relies on the frequency of words within the dataset, identifying individual terms without considering the surrounding context. This limitation became particularly evident when phrases containing words from the hate speech dictionary were incorrectly flagged as hate speech. For example, the term "white boy" might be identified in a tweet and categorized as hate speech, even if the phrase was not used in a derogatory manner. Such misclassifications are common when the system depends on rigid keyword matching, without the ability to discern the nuances in how terms are used. This lack of contextual awareness resulted in false positives, where innocuous phrases were incorrectly flagged as offensive.

In summary, the challenges encountered with TF-IDF highlighted the importance of contextual understanding in text classification tasks. The model's reliance on word frequency alone proved insufficient to identify nuanced hate speech, further compromising the system's performance. These insights emphasized the need for more advanced, context-aware approaches to improve hate speech detection.

B. BERT Challenges

After experimenting with TF-IDF, the next step involved transitioning to BERT (Bidirectional Encoder Representations from Transformers), a more powerful and context-aware model known for its ability to capture contextual relationships between words. However, this shift also presented several challenges, mainly related to the quality of the data set and the training process.

One of the most prominent challenges with the BERT model was the unbalanced data set. Although BERT excels at understanding context, the training process was still impacted by the fact that the dataset contained far fewer hate speech tweets compared to non-hateful content. This imbalance in the data set prevented the model from effectively learning to identify hate speech. As a result, the model performance was skewed, and the detection of hate speech was less accurate than desired. The underrepresentation of hate speech tweets created a situation in which the model was more likely to predict neutral or offensive tweets, rather than accurately classifying hateful content.

In addition to the dataset imbalance, there was an issue with incorrect model configuration during the first round of training. Specifically, not all three labels—hate speech, offensive language, and neither—were included in the training process. This oversight meant that the model was trained on a subset of the potential categories, severely limiting its ability to classify tweets accurately across the full spectrum of categories. By excluding the "neither" category, the model became biased toward detecting hate speech and offensive language, but it was ill-equipped to handle neutral content. This misstep affected the model's initial performance, highlighting the importance of comprehensive label inclusion during training. Once this mistake was identified and corrected in subsequent rounds of training, the model's performance began to improve.

Another challenge affecting the BERT model was dataset bias. The labeling of tweets into categories such as "hate speech," "offensive language," or "neither" often relied on subjective human judgment. Given the variability in how annotators define and interpret hate speech, inconsistencies in the labeling process contributed to errors in the model's performance. This inconsistency undermined the reliability of the training data and compromised the model's ability to generalize, as it could only perform well within the scope of the subjective definitions in the training set. The subjectivity in annotation meant that some content was labeled as hate speech based on personal interpretations of what constitutes offensive language, ultimately influencing the quality of the training data.

Another key limitation of this work is that hate speech detection models, including this one, may fail to identify hateful statements that are phrased using neutral or non-hate words, and conversely, benign statements may be misclassified

due to certain flagged words. For instance, a statement like ”That group always causes trouble” might be missed if it does not explicitly contain hateful words, while a neutral phrase such as ”I dislike violent actions” could be mistakenly flagged due to the presence of certain trigger words. Addressing this challenge through improved contextual understanding and advanced semantic analysis remains an area for future work.

Moreover, while BERT is more robust in handling language nuances, it still requires careful hyperparameter tuning and class weight adjustments to improve performance. The initial rounds of training revealed that the model's performance could be optimized by adjusting the class weights to account for the dataset imbalance. By emphasizing the underrepresented categories (such as hate speech), it was possible to enhance the model's sensitivity to these classes and improve overall classification accuracy. These iterative adjustments played a critical role in improving the model's robustness and making it more capable of distinguishing between hate speech, offensive language, and neutral content.

Addressing the dataset bias and classification limitations outlined in this work presents an opportunity for future research. Exploring methods such as contextual embeddings, multimodal analysis, or human-in-the-loop reinforcement learning could improve the model's ability to detect implicit hate speech and reduce misclassification errors.

In conclusion, both the TF-IDF and BERT models presented distinct challenges, each offering valuable lessons for improving hate speech detection systems. The limitations of TF-IDF underscored the need for incorporating contextual understanding into text classification models, as keyword matching alone is insufficient for accurately identifying hate speech. The challenges with BERT, such as dataset imbalance and initial misconfiguration during training, reinforced the importance of ensuring balanced datasets and careful model setup. These challenges ultimately led to refinements in the training process, highlighting the need for a more nuanced approach to hate speech detection that combines sophisticated modeling techniques with thoughtful data processing.

These experiences emphasized the need for continuous model iteration, fine-tuning, and a deep understanding of the underlying data to build reliable and accurate hate speech detection systems. Moving forward, these insights will guide further improvements in model performance and ensure that future models are better equipped to address the complexities inherent in detecting hate speech in social media content.

VII. Results

The performance of the model was assessed using several key metrics, including overall accuracy, precision, recall, and F1-score, to determine its ability to accurately classify hate speech, offensive language, and neutral content. Across the three rounds of experimentation, the model demonstrated relatively stable performance, with a slight variation in the results due to adjustments made to the class weights and labeling processes.

Training Round	Overall	Hate Speech	Offensive	Neither
Pre	77%	97%	N/A	41%
1	90%	40%	95%	88%
2	90%	39%	95%	88%
3	90%	41%	95%	85%

Fig. 4. Summary of all success metrics for each model training round.

In Round 1, the overall accuracy of the model was 90.94%. The classification report showed that the precision for hate speech was 0.4895, with a recall of 0.4000 and an F1-score of 0.4402. For offensive language, precision was exceptionally high at 0.9410, with a recall of 0.9538, resulting in an F1-score of 0.9474. The precision for the ”neither” category was 0.8816, and the recall was 0.8826, yielding an F1-score of 0.8821. The macro average F1-score was 0.7566, while the weighted average F1-score was 0.9067. The model exhibited a significant imbalance in its ability to detect hate speech, as indicated by the relatively low precision and recall for the hate speech category.

In Round 2, the overall accuracy slightly increased to 90.98%. The precision for hate speech was 0.4768, recall was 0.3897, and the F1-score was 0.4288. The model performed consistently well with offensive language, achieving a precision of 0.9413, recall of 0.9546, and an F1-score of 0.9479. The ”neither” category showed similar results to Round 1, with a precision of 0.8861 and a recall of 0.8850, resulting in an F1-score of 0.8856. The macro average F1-score in Round 2 was 0.7541, and the weighted average F1-score was 0.9070. Again, the model's performance in detecting hate speech remained a challenge due to its low recall for this category, further emphasizing the difficulty in classifying such nuanced language.

Round 3 saw a slight decrease in overall accuracy to 90.38%. In this round, the model's precision for hate speech was 0.4667, the recall was 0.4103, and the F1 score was 0.4367. The performance for offensive language was nearly identical to previous rounds, with a precision of 0.9378, a recall of 0.9517, and an F1-score of 0.9447. The ”neither” category showed a precision of 0.8782 and a recall of 0.8551, yielding an F1-score of 0.8665. The macro average F1-score for Round 3 was 0.7493, while the weighted average F1-score was 0.9018. Although the accuracy remained relatively high across all rounds, the challenges of detecting hate speech persisted, as evidenced by the low precision and recall values for this category.

In summary, the model demonstrated strong performance in identifying offensive language and neutral content, as reflected by the high precision, recall, and F1 scores for the ”offensive language” and ”neither” categories. However, the detection of hate speech remained a significant challenge throughout the rounds, with the model consistently underperforming in this category. The relatively low precision and recall for

hate speech, despite the overall high accuracy, underscore the difficulties in accurately classifying such nuanced and often context-dependent content. This underperformance is likely due to the imbalanced nature of the dataset, with a small number of hate speech instances compared to non-hateful content. The model's ability to detect hate speech could be improved further by employing techniques such as better data augmentation, more advanced class weighting strategies, and a deeper understanding of the linguistic features that characterize hate speech.

The overall results suggest that while the model is effective at identifying offensive language and neutral content, its ability to detect hate speech remains an area for improvement. These findings highlight the need for continuous model refinement, especially in handling class imbalances and the complexity of hate speech detection. Future efforts should focus on addressing these challenges to enhance the model's performance in real-world applications.

VIII. Conclusion

The results of this study underscore the importance of both precise labeling and balanced datasets in developing effective models for hate speech detection. In the initial phase of experimentation, the model exhibited inflated accuracy, achieving an impressive 97

Upon refining the model by adjusting class weights and improving the labeling process, the performance of the model stabilized across several rounds of testing, ultimately achieving a consistent overall accuracy exceeding 90%. This was indicative of the model's ability to reliably classify offensive language and neutral tweets, which were more prevalent in the dataset. The hate speech detection, however, continued to present significant challenges, reflecting the nuanced and complex nature of hate speech, which is often context-dependent and difficult to identify accurately. Throughout the rounds of testing, the F1-score for hate speech classification ranged from 42.88% to 44.0%, suggesting moderate effectiveness in balancing precision and recall. Precision fluctuated between 46.67% and 48.95%, while recall remained lower, between 38.97% and 41.03%, pointing to the model's struggle to fully capture the limited instances of hate speech present in the dataset.

These results reinforce the notion that while the model is promising, it remains a foundational tool rather than a definitive solution for hate speech detection. The imbalance in the dataset, particularly the small amount of hate speech data, directly impacted the model's performance in this category, limiting its ability to reliably detect hate speech in real-world applications. Despite these challenges, the model successfully identified offensive language and neutral content with high precision and recall, showcasing its potential as a tool for detecting harmful content. However, further refinements are necessary to optimize hate speech detection, particularly in capturing the subtleties of hate speech-language.

In conclusion, while the model demonstrates a strong starting point for detecting offensive and neutral content, targeted efforts to address the dataset imbalance and improve hate speech classification metrics will be crucial to advancing its real-world applicability. Future research should focus on enhancing hate speech detection by expanding and diversifying the training dataset, leveraging optimization techniques to boost precision, recall, and F1 score, and incorporating cross-domain validation to ensure robustness across different social media platforms.

IX. Recommendations

To enhance the performance of hate speech detection models and ensure their effectiveness in real-world applications, several key improvements are recommended.

A. Expanding and Balancing the Dataset

The dataset used in this study contained a disproportionately small number of hate speech instances, which significantly impacted the model's ability to effectively detect such content. Future efforts should focus on expanding the dataset, especially by including a more balanced representation of hate speech examples. By incorporating a greater variety of hate speech categories and examples across different social contexts, the model will be better equipped to generalize to real-world scenarios. This expanded dataset should also aim to include diverse sources of hate speech, ensuring that the model does not overfit to a particular subset of language.

B. Optimization of Model Metrics

In this study, the model demonstrated moderate success in detecting hate speech, but precision, recall, and F1-score for hate speech classification remained suboptimal. Future work should prioritize techniques that improve these key metrics. Methods such as fine-tuning hyperparameters, experimenting with advanced neural network architectures, or utilizing transfer learning from pre-trained models could potentially increase precision and recall for hate speech detection. An improvement in these metrics would ensure that the model better captures the nuances of hate speech, which is often context-dependent and subtle in its expression.

C. Cross-Domain Validation

Given that hate speech detection can vary across different social media platforms and online environments, it is essential to test the model's adaptability. Cross-domain validation, using datasets from various platforms such as Twitter, Reddit, or Facebook, could help assess the model's robustness and flexibility. This approach would ensure that the model can detect hate speech across diverse communication styles and user interactions, making it more applicable to a wider range of social media environments.

D. Addressing Contextual and Subtle Language Features

Hate speech is often expressed through nuanced language that may not always be overt or easily identifiable. Future research should focus on incorporating advanced natural language processing (NLP) techniques that can better capture contextual cues, sarcasm, and indirect expressions of hate.

This could involve leveraging deeper linguistic features such as sentiment analysis, semantic understanding, or incorporating larger contextual windows when processing tweets.

By addressing these recommendations, the model can become a more reliable and accurate tool for identifying hate speech across a wide range of social media platforms, ultimately contributing to a safer and more inclusive online environment.

REFERENCES

[1] Nascimento, F. R. S., Cavalcanti, G. D. C., & Da Costa-Abreu, M. (2023). Exploring Automatic Hate Speech Detection on Social Media: A Focus on Content-Based Analysis. *Sage Open*, 13(2).

[2] Malmasi, S., & Zampieri, M. (2017). Detecting Hate Speech in Social Media. In *Proceedings of the International Conference on Recent Advances in Natural Language Processing* (pp. 467-472).

[3] Md Saroar Jahan, M., & Oussalah, M. (2023). A systematic review of hate speech automatic detection using natural language processing. *Neurocomputing*, 546, 126232.

[4] Kumar, A., Tyagi, V., & Das, S. (2021). Deep Learning for Hate Speech Detection in Social Media. In *Proceedings of the 2021 Global Conference on Communication Technologies (GUCON)* (pp. 1-4).

[5] Nguyen, T. B., Nguyen, H. T., & Tran, D. H. (2019). VAIS Hate Speech Detection System: A Deep Learning based Approach for System Combination. *Proceedings of the Sixth International Workshop on Vietnamese Language and Speech Processing*, 33-37.

[6] Subramanian, M., Sathiskumar, V. E., Deepalakshmi, G., Cho, J., & Manikandan, G. (2023). A survey on hate speech detection and sentiment analysis using machine learning and deep learning models. *Alexandria Engineering Journal*, 80, 110-121.

[7] Yuan, L., & Rizoiu, M.-A. (2025). Generalizing Hate Speech Detection Using Multi-Task Learning: A Case Study of Political Public Figures. *Computer Speech & Language*, 89, 101690. https://doi

[8] Kovács, G., Alonso, P., & Saini, R. (2021). Challenges of Hate Speech Detection in Social Media. *SN Computer Science*, 2.

[9] Alrehili, Ahlam. (2019). Automatic Hate Speech Detection on Social Media: A Brief Survey. 1-6. 10.1109/AICCSA47632.2019.9035228.

[10] Devansh Mody, YiDong Huang, Thiago Eustaquio Alves de Oliveira, (2023). A Curated Dataset for Hate Speech Detection on Social Media Text *Data in Brief*, vol. 46, 2023, p. 108832, ISSN 2352-3409.

[11] Davidson, T. (2017). *Hate speech and offensive language refined n-gram dictionary*. Retrieved from https://github.com/t-davidson/hate-speech-and-offensive-language/blob/master/lexicons/refined$_{n}gram_{d}ict.csv$.

[12] Morjaria, M. (2020). *Hate speech and offensive language dataset*. Kaggle. Retrieved from https://www.kaggle.com/datasets/mrmorj/hate-speech-and-offensive-language-dataset.