

Date: 12-02-2021

Hashing with Chaining

Done By : Rohit Karunakaran

Roll no: 58

Aim: Implementation of Hash table with chaining as the collision

Data Structure Used: Hash table

Algorithm for Inserting an element (insert)

Input: Element to be inserted, v. The hash table to which the element is inserted HT, and the hash function h(v)

Output: The element inserted in the hash table

Data Structure: Hash table

Steps:

Step 1: Start
Step 2: key = h(v)
Step 3: new = GetNode(Node)
Step 4: new→data = v
Step 5: new →next = NULL
Step 6: if(HT[key]!=NULL) then
 Step 4: HT[key] = new
Step 7: else
 Step 1: ptr = HT[key]
 Step 2: while(ptr→next != NULL) do
 Step 1: ptr = ptr→ next
 Step 3: EndWhile
 Step 4: ptr →next = new
Step 8: endif
Step 9: Stop

Program Code:

```
/******  
* Implementing of Hashing with  
* chaining  
* Done By: Rohit Karunakaran  
* *****/  
  
#include<stdio.h>  
#include<stdlib.h>  
  
#define SIZE 10  
  
typedef struct hash_node{  
    int data;  
    struct hash_node *next;  
} node;  
  
void insert(node ***ht, int e){  
    int pos = e%SIZE;
```

```

node **hash_table = *ht;

node *new_node = (node*)malloc(sizeof(node));
if(new_node !=NULL){
    new_node->data = e;
    new_node->next=NULL;
    if(hash_table[pos]==NULL){
        hash_table[pos] = new_node;
    }
    else{
        node *ptr = hash_table[pos];
        while(ptr->next!=NULL)ptr = ptr->next;
        ptr->next=new_node;
    }
}
}

void show_the_hash_table(node **ht){
    int i;
    for(i=0;i<SIZE;i++){
        node *ptr = ht[i];
        if(ptr!=NULL){
            while(ptr->next!=NULL){
                printf("%d -> ",ptr->data);
                ptr = ptr->next;
            }
            printf("%d\n",ptr->data);
        }
    }
}

int main(){
    node **hash_table=(node**)calloc(sizeof(node),SIZE);
    int RUN=1;
    int elem;
    int c;

    while(RUN){
        printf("\nMENU\n");
        printf("1.Insert to hash table\n");
        printf("2.Display the hash table\n");
        printf("3.Exit\n");
        printf("Enter yout choice: ");

        scanf("%d",&c);

        switch(c){

            case 1:
                printf("Enter the element you want to enter : ");
                scanf("%d",&elem);
                insert(&hash_table, elem);
                break;

```

```
        case 2:
            printf("The hash table is : \n");
            show_the_hash_table(hash_table);
            break;
        case 3:
            RUN=0;
            break;
    }
}
return 0;
}
```

Result:

The program was successfully compiled and the required output was obtained.

Screenshot:

Date: 12-02-2021

Hashing with Linear Probing

Done By : Rohit Karunakaran

Roll no: 58

Aim: Implementation of Hash table with linear probing as the collision resolution method

Data Structure Used: Hash table

Algorithm for Inserting an element (insert)

Input: Element to be inserted, v. The hash table to which the element is inserted HT with the hash function $h(v)$

Output: The element inserted in the hash table

Data Structure: Hash table

Steps:

Step 1: Start

Step 2: $key = h(v)$

Step 3: $new = \text{GetNode}(\text{Node})$

Step 4: $new \rightarrow \text{value} = v$

Step 6: if ($HT[key] \neq \text{NULL}$) then

 Step 4: $HT[key] = new$

Step 7: else

 Step 1: $new_key = key + 1$

 Step 2: while ($new_key \neq key$ and $HT[new_key] \neq \text{NULL}$) do

 Step 1: $new_key = new_key + 1$

 Step 3: EndWhile

 Step 4: if ($new_key == key$) then

 Step 1: Print "Insertion not possible"

 Step 2: Exit

 Step 5: else

$HT[new_key] = new$

 Step 6: endif

Step 8: endif

Step 9: Stop

Program Code:

```
/*  
 * Hashing with linear probing as the  
 * collision resolution method  
 *  
 * Done By: Rohit Karunakaran  
 */
```

```
#include<stdio.h>  
#include<stdlib.h>
```

```
#define SIZE 10
```

```

void insert(int ***hash_table, int e,int i){
    if(i<=SIZE){
        int pos = (e%SIZE+i)%SIZE;
        int **ht = *hash_table;

        if(ht[pos]==NULL){
            int* node = (int*) malloc(sizeof(int));
            *node = e;
            ht[pos] = node;
        }
        else{
            insert(hash_table,e,i+1);
        }
    }
    else{
        printf("INSERTION NOT POSSIBLE!!!!!!\nThe Hash Table is full\n");
        return;
    }
}

void show_the_hash_table(int **ht){
    int i;
    for(i=0;i<SIZE;i++){
        int *ptr = ht[i];
        if(ptr!=NULL){
            printf("(%d) - %d\n",i,*ptr);
        }
    }
}

int main(){
    int **hash_table=(int**)calloc(sizeof(int*),SIZE);
    int RUN=1;
    int elem;
    int c;

    while(RUN){
        printf("\nMENU\n");
        printf("1.Insert to hash table\n");
        printf("2.Display the hash table\n");
        printf("3.Exit\n");
        printf("Enter yout choice: ");

        scanf("%d",&c);

        switch(c){

            case 1:
                printf("Enter the element you want to enter : ");
                scanf("%d",&elem);
                insert(&hash_table, elem,0);
                break;

```

```
        case 2:
            printf("The hash table is : \n");
            show_the_hash_table(hash_table);
            break;
        case 3:
            RUN=0;
            break;
    }

}

for(int i = 0; i<SIZE;i++){
    free(*(hash_table+i));
}
free(hash_table);

return 0;
}
```