

Optimization Methods

Introduction

Jean-Louis Bouquard



Beijing Institute of Technology

- 1 Introduction
- 2 A scheduling problem
- 3 Local search
- 4 Experimentation

Thanks to Prof. Li Dongni

Jean-Louis Bouquard
Graduate School of Engineering
University of Tours (France)
jean-louis.bouquard@univ-tours.fr

Thanks to Prof. Li Dongni

Jean-Louis Bouquard
Graduate School of Engineering
University of Tours (France)
jean-louis.bouquard@univ-tours.fr

1 Introduction

Introduction

Optimization problems

- Optimization problems
- Find X such that $f(X)$ is minimal subject to $\mathcal{C}(X)$
- $f(X)$ is the **Objective function** or the **Criterion**
- defines you are looking for
- $\mathcal{C}(X)$ is the set of constraints on X
- defines where you are looking for
- Ex: Traveling Salesman Problem
- Ex: Shortest path in a graph
- Ex: Knapsack problem

Introduction

Optimization problems

- Optimization problems
- Find X such that $f(X)$ is minimal subject to $\mathcal{C}(X)$
- $f(X)$ is the **Objective function** or the **Criterion**
- defines **what** you are looking for
- $\mathcal{C}(X)$ is the set of constraints on X
- defines **where** you are looking for
- Ex: Traveling Salesman Problem
- Ex: Shortest path in a graph
- Ex: Knapsack problem

Introduction

Optimization problems

- Optimization problems
- Find X such that $f(X)$ is minimal subject to $\mathcal{C}(X)$
- $f(X)$ is the **Objective function** or the **Criterion**
- defines **what** you are looking for
- $\mathcal{C}(X)$ is the set of **constraints** on X
- defines **where** you are looking for
- Ex: Traveling Salesman Problem
- Ex: Shortest path in a graph
- Ex: Knapsack problem

Introduction

Optimization problems

- Optimization problems
- Find X such that $f(X)$ is minimal subject to $\mathcal{C}(X)$
- $f(X)$ is the **Objective function** or the **Criterion**
- defines **what** you are looking for
- $\mathcal{C}(X)$ is the set of **constraints** on X
- defines **where** you are looking for
- Ex: Traveling Salesman Problem
- Ex: Shortest path in a graph
- Ex: Knapsack problem

Introduction

Optimization problems

- Optimization problems
- Find X such that $f(X)$ is minimal subject to $\mathcal{C}(X)$
- $f(X)$ is the **Objective function** or the **Criterion**
- defines **what** you are looking for
- $\mathcal{C}(X)$ is the set of **constraints** on X
- defines **where** you are looking for
- Ex: Traveling Salesman Problem
- Ex: Shortest path in a graph
- Ex: Knapsack problem

Introduction

Optimization problems

- Optimization problems
- Find X such that $f(X)$ is minimal subject to $\mathcal{C}(X)$
- $f(X)$ is the **Objective function** or the **Criterion**
- defines **what** you are looking for
- $\mathcal{C}(X)$ is the set of **constraints** on X
- defines **where** you are looking for
- Ex: Traveling Salesman Problem
- Ex: Shortest path in a graph
- Ex: Knapsack problem

Introduction

Optimization problems

- Optimization problems
- Find X such that $f(X)$ is minimal subject to $\mathcal{C}(X)$
- $f(X)$ is the **Objective function** or the **Criterion**
- defines **what** you are looking for
- $\mathcal{C}(X)$ is the set of **constraints** on X
- defines **where** you are looking for
- Ex: Traveling Salesman Problem
- Ex: Shortest path in a graph
- Ex: Knapsack problem

Introduction

Optimization problems

- Optimization problems
- Find X such that $f(X)$ is minimal subject to $\mathcal{C}(X)$
- $f(X)$ is the **Objective function** or the **Criterion**
- defines **what** you are looking for
- $\mathcal{C}(X)$ is the set of **constraints** on X
- defines **where** you are looking for
- Ex: Traveling Salesman Problem
- Ex: Shortest path in a graph
- Ex: Knapsack problem

Introduction

Optimization problems

- Optimization problems
- Find X such that $f(X)$ is minimal subject to $\mathcal{C}(X)$
- $f(X)$ is the **Objective function** or the **Criterion**
- defines **what** you are looking for
- $\mathcal{C}(X)$ is the set of **constraints** on X
- defines **where** you are looking for
- Ex: Traveling Salesman Problem
- Ex: Shortest path in a graph
- Ex: Knapsack problem

Introduction

Algorithm Complexity

- Complexity of algorithms
- With the Θ and the O notations
- Ex: the complexity of “brute force” sort is $\Theta(n!)$
- the complexity of the merge sort (or heap sort) is $\Theta(n \log n)$
- the complexity of the insertion sort (or selection sort) is $\Theta(n^2)$
- Moore-Dijkstra algorithm: $O(V^2)$
- Matrix Multiplication with the “usual” algorithm: $\Theta(n^3)$
- Matrix Multiplication with the Strassen algorithm: $\Theta(n^{2.7})$
- TSP with B&B procedure: $O(n!)$

Introduction

Algorithm Complexity

- Complexity of algorithms
- With the Θ and the O notations
- Ex: the complexity of “brute force” sort is $\Theta(n!)$
- the complexity of the merge sort (or heap sort) is $\Theta(n \log n)$
- the complexity of the insertion sort (or selection sort) is $\Theta(n^2)$
- Moore-Dijkstra algorithm: $O(V^2)$
- Matrix Multiplication with the “usual” algorithm: $\Theta(n^3)$
- Matrix Multiplication with the Strassen algorithm: $\Theta(n^{2.7})$
- TSP with B&B procedure: $O(n!)$

Introduction

Algorithm Complexity

- Complexity of algorithms
- With the Θ and the O notations
- Ex: the complexity of “brute force” sort is $\Theta(n!)$
- the complexity of the merge sort (or heap sort) is $\Theta(n \log n)$
- the complexity of the insertion sort (or selection sort) is $\Theta(n^2)$
- Moore-Dijkstra algorithm: $O(V^2)$
- Matrix Multiplication with the “usual” algorithm: $\Theta(n^3)$
- Matrix Multiplication with the Strassen algorithm: $\Theta(n^{\log 7})$
- TSP with B&B procedure: $O(n!)$

Introduction

Algorithm Complexity

- Complexity of algorithms
- With the Θ and the O notations
- Ex: the complexity of “brute force” sort is $\Theta(n!)$
- the complexity of the merge sort (or heap sort) is $\Theta(n \log n)$
- the complexity of the insertion sort (or selection sort) is $\Theta(n^2)$
- Moore-Dijkstra algorithm: $O(V^2)$
- Matrix Multiplication with the “usual” algorithm: $\Theta(n^3)$
- Matrix Multiplication with the Strassen algorithm: $\Theta(n^{\log 7})$
- TSP with B&B procedure: $O(n!)$

Introduction

Algorithm Complexity

- Complexity of algorithms
- With the Θ and the O notations
- Ex: the complexity of “brute force” sort is $\Theta(n!)$
- the complexity of the merge sort (or heap sort) is $\Theta(n \log n)$
- the complexity of the insertion sort (or selection sort) is $\Theta(n^2)$
- Moore-Dijkstra algorithm: $O(V^2)$
- Matrix Multiplication with the “usual” algorithm: $\Theta(n^3)$
- Matrix Multiplication with the Strassen algorithm: $\Theta(n^{2.7})$
- TSP with B&B procedure: $O(n!)$

Introduction

Algorithm Complexity

- Complexity of algorithms
- With the Θ and the O notations
- Ex: the complexity of “brute force” sort is $\Theta(n!)$
- the complexity of the merge sort (or heap sort) is $\Theta(n \log n)$
- the complexity of the insertion sort (or selection sort) is $\Theta(n^2)$
- Moore-Dijkstra algorithm: $O(V^2)$
- Matrix Multiplication with the “usual” algorithm: $\Theta(n^3)$
- Matrix Multiplication with the Strassen algorithm: $\Theta(n^{\log 7})$
- TSP with B&B procedure: $O(n!)$

Introduction

Algorithm Complexity

- Complexity of algorithms
- With the Θ and the O notations
- Ex: the complexity of “brute force” sort is $\Theta(n!)$
- the complexity of the merge sort (or heap sort) is $\Theta(n \log n)$
- the complexity of the insertion sort (or selection sort) is $\Theta(n^2)$
- Moore-Dijkstra algorithm: $O(V^2)$
- Matrix Multiplication with the “usual” algorithm: $\Theta(n^3)$
- Matrix Multiplication with the Strassen algorithm: $\Theta(n^{\lg 7})$
- TSP with B&B procedure: $O(n!)$

Introduction

Algorithm Complexity

- Complexity of algorithms
- With the Θ and the O notations
- Ex: the complexity of “brute force” sort is $\Theta(n!)$
- the complexity of the merge sort (or heap sort) is $\Theta(n \log n)$
- the complexity of the insertion sort (or selection sort) is $\Theta(n^2)$
- Moore-Dijkstra algorithm: $O(V^2)$
- Matrix Multiplication with the “usual” algorithm: $\Theta(n^3)$
- Matrix Multiplication with the Strassen algorithm: $\Theta(n^{\lg 7})$
- TSP with B&B procedure: $O(n!)$

Introduction

Algorithm Complexity

- Complexity of algorithms
- With the Θ and the O notations
- Ex: the complexity of “brute force” sort is $\Theta(n!)$
- the complexity of the merge sort (or heap sort) is $\Theta(n \log n)$
- the complexity of the insertion sort (or selection sort) is $\Theta(n^2)$
- Moore-Dijkstra algorithm: $O(V^2)$
- Matrix Multiplication with the “usual” algorithm: $\Theta(n^3)$
- Matrix Multiplication with the Strassen algorithm: $\Theta(n^{\lg 7})$
- TSP with B&B procedure: $O(n!)$

Introduction

Algorithm Complexity

- Complexity of algorithms usually easy to evaluate
- for the same problem, several algorithms
- We look for *good* (i.e. low complexity) algorithms
- Is it possible to design a sort in $\Theta(n)$?

Introduction

Algorithm Complexity

- Complexity of algorithms usually easy to evaluate
- for the same problem, several algorithms
- We look for *good* (i.e. low complexity) algorithms
- Is it possible to design a sort in $\Theta(n)$?

Introduction

Algorithm Complexity

- Complexity of algorithms usually easy to evaluate
- for the same problem, several algorithms
- We look for *good* (i.e. low complexity) algorithms
- Is it possible to design a sort in $\Theta(n)$?

Introduction

Algorithm Complexity

- Complexity of algorithms usually easy to evaluate
- for the same problem, several algorithms
- We look for *good* (i.e. low complexity) algorithms
- Is it possible to design a sort in $\Theta(n)$?

Introduction

Problem Complexity

- Complexity of problems
- Polynomial problems: there exists a $\Theta(n^k)$ algorithm
- Considered as **easy** or **tractable**
- Superpolynomial problems: e.g. in $\Omega(a^n)$ ($a > 1$)
- Considered as **hard** or **untractable**
- *NP*-complete problems: $P \neq NP$ question since 1971
!!!
- Called *NP*-hard
- Any comparison sort algorithm is $\Omega(n \log n)$

Introduction

Problem Complexity

- Complexity of problems
- Polynomial problems: there exists a $\Theta(n^k)$ algorithm
- Considered as easy or tractable
- Superpolynomial problems: e.g. in $\Omega(a^n)$ ($a > 1$)
- Considered as hard or untractable
- *NP*-complete problems: $P \neq NP$ question since 1971
!!!
- Called *NP*-hard
- Any comparison sort algorithm is $\Omega(n \log n)$

Introduction

Problem Complexity

- Complexity of problems
- Polynomial problems: there exists a $\Theta(n^k)$ algorithm
- Considered as **easy** or **tractable**
- Superpolynomial problems: e.g. in $\Omega(a^n)$ ($a > 1$)
- Considered as **hard** or **untractable**
- *NP*-complete problems: $P \neq NP$ question since 1971
!!!
- Called *NP*-hard
- Any comparison sort algorithm is $\Omega(n \log n)$

Introduction

Problem Complexity

- Complexity of problems
- Polynomial problems: there exists a $\Theta(n^k)$ algorithm
- Considered as **easy** or **tractable**
- Superpolynomial problems: e.g. in $\Omega(a^n)$ ($a > 1$)
- Considered as **hard** or **untractable**
- *NP*-complete problems: $P \neq NP$ question since 1971
!!!
- Called *NP*-hard
- Any comparison sort algorithm is $\Omega(n \log n)$

Introduction

Problem Complexity

- Complexity of problems
- Polynomial problems: there exists a $\Theta(n^k)$ algorithm
- Considered as **easy** or **tractable**
- Superpolynomial problems: e.g. in $\Omega(a^n)$ ($a > 1$)
- Considered as **hard** or **untractable**
- *NP*-complete problems: $P \neq NP$ question since 1971
!!!
- Called *NP-hard*
- Any comparison sort algorithm is $\Omega(n \log n)$

Introduction

Problem Complexity

- Complexity of problems
- Polynomial problems: there exists a $\Theta(n^k)$ algorithm
- Considered as **easy** or **tractable**
- Superpolynomial problems: e.g. in $\Omega(a^n)$ ($a > 1$)
- Considered as **hard** or **untractable**
- NP -complete problems: $P \neq NP$ question since 1971
!!!
- Called **NP -hard**
- Any comparison sort algorithm is $\Omega(n \log n)$

Introduction

Problem Complexity

- Complexity of problems
- Polynomial problems: there exists a $\Theta(n^k)$ algorithm
- Considered as **easy** or **tractable**
- Superpolynomial problems: e.g. in $\Omega(a^n)$ ($a > 1$)
- Considered as **hard** or **untractable**
- NP -complete problems: $P \neq NP$ question since 1971
!!!
- Called **NP -hard**
- Any comparison sort algorithm is $\Omega(n \log n)$

Introduction

Problem Complexity

- Complexity of problems
- Polynomial problems: there exists a $\Theta(n^k)$ algorithm
- Considered as **easy** or **tractable**
- Superpolynomial problems: e.g. in $\Omega(a^n)$ ($a > 1$)
- Considered as **hard** or **untractable**
- NP -complete problems: $P \neq NP$ question since 1971
!!!
- Called **NP -hard**
- Any comparison sort algorithm is $\Omega(n \log n)$

Introduction

Problem Complexity

As an effective conclusion:

- For *NP*-hard problems
- it is not possible to get an optimal solution in a “reasonable” time
- Exact methods used only for small data
- For other (real, realistic) instances, we use
- Approximation methods or
- Heuristics

Introduction

Problem Complexity

As an effective conclusion:

- For *NP*-hard problems
- it is not possible to get an optimal solution in a “reasonable” time
- Exact methods used only for small data
- For other (real, realistic) instances, we use
- Approximation methods or
- Heuristics

Introduction

Problem Complexity

As an effective conclusion:

- For *NP*-hard problems
- it is not possible to get an optimal solution in a “reasonable” time
- **Exact methods** used only for small data
- For other (real, realistic) instances, we use
- Approximation methods or
- Heuristics

Introduction

Problem Complexity

As an effective conclusion:

- For *NP*-hard problems
- it is not possible to get an optimal solution in a “reasonable” time
- **Exact methods** used only for small data
- For other (real, realistic) instances, we use
 - Approximation methods or
 - Heuristics

Introduction

Problem Complexity

As an effective conclusion:

- For *NP*-hard problems
- it is not possible to get an optimal solution in a “reasonable” time
- **Exact methods** used only for small data
- For other (real, realistic) instances, we use
- Approximation methods or
- **Heuristics**

Introduction

Problem Complexity

As an effective conclusion:

- For *NP*-hard problems
- it is not possible to get an optimal solution in a “reasonable” time
- **Exact methods** used only for small data
- For other (real, realistic) instances, we use
- Approximation methods or
- **Heuristics**

2 A scheduling problem

A two-machine flowshop problem

- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
- on machine 1: **processing time** is $p_{1,j}$
- then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
- then it is **early**: $T_j = 0$
- else it is **tardy**: $T_j = C_{2,j} - d_j$
- The sum of tardinesses \bar{T} is to be minimized

A two-machine flowshop problem

- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
 - on machine 1: processing time is $p_{1,j}$
 - then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
 - then it is early: $T_j = 0$
 - else it is tardy: $T_j = C_{2,j} - d_j$
- The sum of tardinesses \bar{T} is to be minimized

A two-machine flowshop problem

- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
- on machine 1: processing time is $p_{1,j}$
- then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
- then it is early: $T_j = 0$
- else it is tardy: $T_j = C_{2,j} - d_j$
- The sum of tardinesses \bar{T} is to be minimized

A two-machine flowshop problem

- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
- on machine 1: processing time is $p_{1,j}$
- then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
- then it is early: $T_j = 0$
- else it is tardy: $T_j = C_{2,j} - d_j$
- The sum of tardinesses \bar{T} is to be minimized

A two-machine flowshop problem

- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
- on machine 1: processing time is $p_{1,j}$
- then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
- then it is early: $T_j = 0$
- else it is tardy: $T_j = C_{2,j} - d_j$
- The sum of tardinesses T is to be minimized

A two-machine flowshop problem

- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
- on machine 1: processing time is $p_{1,j}$
- then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
- then it is early: $T_j = 0$
- else it is tardy: $T_j = C_{2,j} - d_j$
- The sum of tardinesses T is to be minimized

A two-machine flowshop problem

- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
- on machine 1: processing time is $p_{1,j}$
- then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
 - then it is early: $T_j = 0$
 - else it is tardy: $T_j = C_{2,j} - d_j$
- The sum of tardinesses T is to be minimized

A two-machine flowshop problem


- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
- on machine 1: processing time is $p_{1,j}$
- then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
- then it is early: $T_j = 0$
- else it is tardy: $T_j = C_{2,j} - d_j$
- The sum of tardinesses \bar{T} is to be minimized

A two-machine flowshop problem

- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
- on machine 1: processing time is $p_{1,j}$
- then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
- then it is early: $T_j = 0$
- else it is tardy: $T_j = C_{2,j} - d_j$
- The sum of tardinesses \bar{T} is to be minimized

A two-machine flowshop problem

- There are n jobs
- Each job j ($1 \leq j \leq n$) has to be processed
- on machine 1: processing time is $p_{1,j}$
- then on machine 2: processing time is $p_{2,j}$
- Each machine can process only one job at a time
- For each job, operation 2 cannot begin before operation 1 is completed
- If the completion time of a job is before its due date d_j ,
- then it is early: $T_j = 0$
- else it is tardy: $T_j = C_{2,j} - d_j$
- The sum of tardinesses \bar{T} is to be minimized


A two-machine flowshop problem: $F2//T$ Job 3 early: $C_{2,3} \leq d_3, T_3 = 0$ Job 2 early: $C_{2,2} \leq d_2, T_2 = 0$ Job 5 tardy: $C_{2,5} > d_5, T_5 = C_{2,5} - d_5 > 0$ 


A two-machine flowshop problem: $F2//T$


Job 3 early: $C_{2,3} \leq d_3, T_3 = 0$


Job 2 early: $C_{2,2} \leq d_2, T_2 = 0$

Job 5 tardy: $C_{2,5} > d_5, T_5 = C_{2,5} - d_5 > 0$



A two-machine flowshop problem: $F2//T$ Job 3 early: $C_{2,3} \leq d_3, T_3 = 0$ Job 2 early: $C_{2,2} \leq d_2, T_2 = 0$ Job 5 tardy: $C_{2,5} > d_5, T_5 = C_{2,5} - d_5 > 0$ 

A two-machine flowshop problem: $F2//T$ Job 3 early: $C_{2,3} \leq d_3$, $T_3 = 0$ Job 2 early: $C_{2,2} \leq d_2$, $T_2 = 0$ Job 5 tardy: $C_{2,5} > d_5$, $T_5 = C_{2,5} - d_5 > 0$ 


A two-machine flowshop problem: $F2//T$ Job 3 early: $C_{2,3} \leq d_3, T_3 = 0$ Job 2 early: $C_{2,2} \leq d_2, T_2 = 0$ Job 5 tardy: $C_{2,5} > d_5, T_5 = C_{2,5} - d_5 > 0$ 

A two-machine flowshop problem: $F2//T$

Job 3 early: $C_{2,3} \leq d_3$, $T_3 = 0$

Job 2 early: $C_{2,2} \leq d_2$, $T_2 = 0$

Job 5 tardy: $C_{2,5} > d_5$, $T_5 = C_{2,5} - d_5 > 0$




A two-machine flowshop problem: $F2//T$

Job 3 early: $C_{2,3} \leq d_3$, $T_3 = 0$

Job 2 early: $C_{2,2} \leq d_2$, $T_2 = 0$

Job 5 tardy: $C_{2,5} > d_5$, $T_5 = C_{2,5} - d_5 > 0$




A two-machine flowshop problem: $F2//T$

Job 3 early: $C_{2,3} \leq d_3, T_3 = 0$

Job 2 early: $C_{2,2} \leq d_2, T_2 = 0$

Job 5 tardy: $C_{2,5} > d_5, T_5 = C_{2,5} - d_5 > 0$




A two-machine flowshop problem: $F2//T$

Job 3 early: $C_{2,3} \leq d_3$, $T_3 = 0$

Job 2 early: $C_{2,2} \leq d_2$, $T_2 = 0$

Job 5 tardy: $C_{2,5} > d_5$, $T_5 = C_{2,5} - d_5 > 0$




A two-machine flowshop problem: $F2//T$

Job 3 early: $C_{2,3} \leq d_3$, $T_3 = 0$

Job 2 early: $C_{2,2} \leq d_2$, $T_2 = 0$

Job 5 tardy: $C_{2,5} > d_5$, $T_5 = C_{2,5} - d_5 > 0$



$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- Do not confuse job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- Do not confuse job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- Do not confuse job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- Do not confuse job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- Do not confuse job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- Do not confuse job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- Do not confuse job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- Do not confuse job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- **Do not confuse** job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- The data are: n number of jobs
- $(p_{1,j}, p_{2,j}, d_j)$ for $j \in \{1, 2, \dots, n\}$
- We have to **decide** how to **schedule** the jobs
- What is the first job ?
- What is the second job ?
- What is the k^{th} job ? (for $1 \leq k \leq n$)
- A solution is given by a permutation of $\{1, 2, \dots, n\}$
- $s(1)$ is the first job, $s(2)$ is the second job, ...
- **Do not confuse** job $s(1)$, the job you decide to schedule first
- and job 1, the job numbered 1 in the data.

$F2//\bar{T}$ problem

- From s , we can compute:
 - The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
 - The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
 - Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
- Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
- Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
- Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
- Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
- Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
- Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
 - Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
 - Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
 - Then $\bar{T} = \sum_{j=1}^n T_j$

$F2//\bar{T}$ problem

- From s , we can compute:
- The completion times
 - $C_{1,s(1)} = p_{1,s(1)}$
 - $C_{1,s(2)} = C_{1,s(1)} + p_{1,s(2)} = p_{1,s(1)} + p_{1,s(2)}$
 - $C_{1,s(k)} = C_{1,s(k-1)} + p_{1,s(k)} = \sum_{j=1}^k p_{1,s(j)}$
 - $C_{2,s(1)} = C_{1,s(1)} + p_{2,s(1)} = p_{1,s(1)} + p_{2,s(1)}$
 - $C_{2,s(2)} = \max(C_{1,s(2)}, C_{2,s(1)}) + p_{2,s(2)}$
 - $C_{2,s(k)} = \max(C_{1,s(k)}, C_{2,s(k-1)}) + p_{2,s(k)}$
- The tardinesses
 - $T_{s(k)} = \max(0, C_{2,s(k)} - d_{s(k)})$
 - Then $\bar{T} = \sum_{j=1}^n T_j$

3 Local search

Iterative improvement algorithms

- Two families of algorithms for optimization problems:
 - Constructive methods: solutions are computed from the data
 - Iterative improvement algorithms:
 - Starting from one (or several) solution(s),
 - better solution(s) is (are) computed
 - iteratively, until no improvement is done
 - or until a time limit is reached

Iterative improvement algorithms

- Two families of algorithms for optimization problems:
- **Constructive methods**: solutions are computed from the data
- Iterative improvement algorithms:
 - Starting from one (or several) solution(s),
 - better solution(s) is (are) computed
 - iteratively, until no improvement is done
 - or until a time limit is reached

Iterative improvement algorithms

- Two families of algorithms for optimization problems:
- **Constructive methods**: solutions are computed from the data
- **Iterative improvement algorithms**:
 - Starting from one (or several) solution(s),
 - better solution(s) is (are) computed
 - iteratively, until no improvement is done
 - or until a time limit is reached

Iterative improvement algorithms

- Two families of algorithms for optimization problems:
- **Constructive methods**: solutions are computed from the data
- **Iterative improvement algorithms**:
 - Starting from one (or several) solution(s),
 - better solution(s) is (are) computed
 - iteratively, until no improvement is done
 - or until a time limit is reached

Iterative improvement algorithms

- Two families of algorithms for optimization problems:
- **Constructive methods**: solutions are computed from the data
- **Iterative improvement algorithms**:
 - Starting from one (or several) solution(s),
 - better solution(s) is (are) computed
 - iteratively, until no improvement is done
 - or until a time limit is reached

Iterative improvement algorithms

- Two families of algorithms for optimization problems:
- **Constructive methods**: solutions are computed from the data
- **Iterative improvement algorithms**:
 - Starting from one (or several) solution(s),
 - better solution(s) is (are) computed
 - iteratively, until no improvement is done
 - or until a time limit is reached

Iterative improvement algorithms

- Two families of algorithms for optimization problems:
- **Constructive methods**: solutions are computed from the data
- **Iterative improvement algorithms**:
 - Starting from one (or several) solution(s),
 - better solution(s) is (are) computed
 - iteratively, until no improvement is done
 - or until a time limit is reached

Local search

- **Local Search** is an Iterative improvement algorithm
- From a solution, “slight modifications” are tried with the hope it will improve it
- These modifications are called **moves**
- The solutions obtained are called **neighbors**
- They form a neighborhood of the current solution

Local search

- **Local Search** is an Iterative improvement algorithm
- From a solution, “slight modifications” are tried with the hope it will improve it
- These modifications are called **moves**
- The solutions obtained are called **neighbors**
- They form a neighborhood of the current solution

Local search

- **Local Search** is an Iterative improvement algorithm
- From a solution, “slight modifications” are tried with the hope it will improve it
- These modifications are called **moves**
 - The solutions obtained are called **neighbors**
 - They form a **neighborhood** of the current solution

Local search

- **Local Search** is an Iterative improvement algorithm
- From a solution, “slight modifications” are tried with the hope it will improve it
- These modifications are called **moves**
- The solutions obtained are called **neighbors**
- They form a **neighborhood** of the current solution

Local search

- **Local Search** is an Iterative improvement algorithm
- From a solution, “slight modifications” are tried with the hope it will improve it
- These modifications are called **moves**
- The solutions obtained are called **neighbors**
- They form a **neighborhood** of the current solution

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- **Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- **Move 2:** swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- **Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
 - $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
 - For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
 - For $k = 1, \dots, n - 1$
 - The neighborhood has $(n - 1)$ elements
- Move 2: swap the jobs $s(k_1)$ and $s(k_2)$
 - $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
 - For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
 - For $1 \leq k_1 < k_2 \leq n$
 - The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- **Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- Move 2: swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- **Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- Move 2: swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- **Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- **Move 2:** swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- **Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- **Move 2:** swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- Move 2:** swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- **Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- **Move 2:** swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- Move 2:** swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- Move 2:** swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- Here a solution is a permutation of $\{1, 2, \dots, n\}$
- **Move 1:** swap the consecutive jobs $s(k)$ and $s(k + 1)$
- $t(k) = s(k + 1)$, $t(k + 1) = s(k)$
- For all $j \neq k$ and $j \neq k + 1$, $t(j) = s(j)$
- For $k = 1, \dots, n - 1$
- The neighborhood has $(n - 1)$ elements
- **Move 2:** swap the jobs $s(k_1)$ and $s(k_2)$
- $t(k_1) = s(k_2)$, $t(k_2) = s(k_1)$
- For all $j \neq k_1$ and $j \neq k_2$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 3:** rotate the jobs $s(k_1)$, $s(k_2)$ and $s(k_3)$
 - $t_1(k_1) = s(k_2)$, $t_1(k_2) = s(k_3)$, $t_1(k_3) = s(k_1)$
 - For all $j \notin \{k_1, k_2, k_3\}$, $t_1(j) = s(j)$
 - $t_2(k_1) = s(k_3)$, $t_2(k_2) = s(k_1)$, $t_2(k_3) = s(k_2)$
 - For all $j \notin \{k_1, k_2, k_3\}$, $t_2(j) = s(j)$
 - 2 neighbors for the same (k_1, k_2, k_3)
 - For $1 \leq k_1 < k_2 < k_3 \leq n$
 - The neighborhood has $2 \binom{n}{3} = \frac{n(n-1)(n-2)}{3}$ elements

Local search for the $F2//T$

- **Move 3:** rotate the jobs $s(k_1)$, $s(k_2)$ and $s(k_3)$
- $t_1(k_1) = s(k_2)$, $t_1(k_2) = s(k_3)$, $t_1(k_3) = s(k_1)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_1(j) = s(j)$
- $t_2(k_1) = s(k_3)$, $t_2(k_2) = s(k_1)$, $t_2(k_3) = s(k_2)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_2(j) = s(j)$
- 2 neighbors for the same (k_1, k_2, k_3)
- For $1 \leq k_1 < k_2 < k_3 \leq n$
- The neighborhood has $2 \binom{n}{3} = \frac{n(n-1)(n-2)}{3}$ elements

Local search for the $F2//T$

- **Move 3**: rotate the jobs $s(k_1)$, $s(k_2)$ and $s(k_3)$
- $t_1(k_1) = s(k_2)$, $t_1(k_2) = s(k_3)$, $t_1(k_3) = s(k_1)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_1(j) = s(j)$
- $t_2(k_1) = s(k_3)$, $t_2(k_2) = s(k_1)$, $t_2(k_3) = s(k_2)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_2(j) = s(j)$
- 2 neighbors for the same (k_1, k_2, k_3)
- For $1 \leq k_1 < k_2 < k_3 \leq n$
- The neighborhood has $2 \binom{n}{3} = \frac{n(n-1)(n-2)}{3}$ elements

Local search for the $F2//T$

- **Move 3**: rotate the jobs $s(k_1)$, $s(k_2)$ and $s(k_3)$
- $t_1(k_1) = s(k_2)$, $t_1(k_2) = s(k_3)$, $t_1(k_3) = s(k_1)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_1(j) = s(j)$
- $t_2(k_1) = s(k_3)$, $t_2(k_2) = s(k_1)$, $t_2(k_3) = s(k_2)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_2(j) = s(j)$
- 2 neighbors for the same (k_1, k_2, k_3)
- For $1 \leq k_1 < k_2 < k_3 \leq n$
- The neighborhood has $2 \binom{n}{3} = \frac{n(n-1)(n-2)}{3}$ elements

Local search for the $F2//T$

- **Move 3**: rotate the jobs $s(k_1)$, $s(k_2)$ and $s(k_3)$
- $t_1(k_1) = s(k_2)$, $t_1(k_2) = s(k_3)$, $t_1(k_3) = s(k_1)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_1(j) = s(j)$
- $t_2(k_1) = s(k_3)$, $t_2(k_2) = s(k_1)$, $t_2(k_3) = s(k_2)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_2(j) = s(j)$
- 2 neighbors for the same (k_1, k_2, k_3)
- For $1 \leq k_1 < k_2 < k_3 \leq n$
- The neighborhood has $2 \binom{n}{3} = \frac{n(n-1)(n-2)}{3}$ elements

Local search for the $F2//T$

- **Move 3**: rotate the jobs $s(k_1)$, $s(k_2)$ and $s(k_3)$
- $t_1(k_1) = s(k_2)$, $t_1(k_2) = s(k_3)$, $t_1(k_3) = s(k_1)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_1(j) = s(j)$
- $t_2(k_1) = s(k_3)$, $t_2(k_2) = s(k_1)$, $t_2(k_3) = s(k_2)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_2(j) = s(j)$
- 2 neighbors for the same (k_1, k_2, k_3)
- For $1 \leq k_1 < k_2 < k_3 \leq n$
- The neighborhood has $2 \binom{n}{3} = \frac{n(n-1)(n-2)}{3}$ elements

Local search for the $F2//T$

- **Move 3**: rotate the jobs $s(k_1)$, $s(k_2)$ and $s(k_3)$
- $t_1(k_1) = s(k_2)$, $t_1(k_2) = s(k_3)$, $t_1(k_3) = s(k_1)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_1(j) = s(j)$
- $t_2(k_1) = s(k_3)$, $t_2(k_2) = s(k_1)$, $t_2(k_3) = s(k_2)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_2(j) = s(j)$
- 2 neighbors for the same (k_1, k_2, k_3)
- For $1 \leq k_1 < k_2 < k_3 \leq n$
- The neighborhood has $2 \binom{n}{3} = \frac{n(n-1)(n-2)}{3}$ elements

Local search for the $F2//T$

- **Move 3**: rotate the jobs $s(k_1)$, $s(k_2)$ and $s(k_3)$
- $t_1(k_1) = s(k_2)$, $t_1(k_2) = s(k_3)$, $t_1(k_3) = s(k_1)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_1(j) = s(j)$
- $t_2(k_1) = s(k_3)$, $t_2(k_2) = s(k_1)$, $t_2(k_3) = s(k_2)$
- For all $j \notin \{k_1, k_2, k_3\}$, $t_2(j) = s(j)$
- 2 neighbors for the same (k_1, k_2, k_3)
- For $1 \leq k_1 < k_2 < k_3 \leq n$
- The neighborhood has $2 \binom{n}{3} = \frac{n(n-1)(n-2)}{3}$ elements

Local search for the $F2//T$

- **Move 4:** shift backward the job $s(k_2)$ in position k_1
 - $t(k_1) = s(k_2)$
 - For all j , $(k_1 + 1 \leq j \leq k_2)$, $t(j) = s(j - 1)$
 - For all j , $(1 \leq j \leq k_1 - 1)$ and $(k_2 + 1 \leq j \leq n)$, $t(j) = s(j)$
 - For $1 \leq k_1 < k_2 \leq n$
 - The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 4:** shift backward the job $s(k_2)$ in position k_1
- $t(k_1) = s(k_2)$
- For all j , $(k_1 + 1 \leq j \leq k_2)$, $t(j) = s(j - 1)$
- For all j , $(1 \leq j \leq k_1 - 1)$ and $(k_2 + 1 \leq j \leq n)$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 4:** shift backward the job $s(k_2)$ in position k_1
- $t(k_1) = s(k_2)$
- For all j , $(k_1 + 1 \leq j \leq k_2)$, $t(j) = s(j - 1)$
- For all j , $(1 \leq j \leq k_1 - 1)$ and $(k_2 + 1 \leq j \leq n)$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 4:** shift backward the job $s(k_2)$ in position k_1
- $t(k_1) = s(k_2)$
- For all j , $(k_1 + 1 \leq j \leq k_2)$, $t(j) = s(j - 1)$
- For all j , $(1 \leq j \leq k_1 - 1)$ and $(k_2 + 1 \leq j \leq n)$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 4:** shift backward the job $s(k_2)$ in position k_1
- $t(k_1) = s(k_2)$
- For all j , $(k_1 + 1 \leq j \leq k_2)$, $t(j) = s(j - 1)$
- For all j , $(1 \leq j \leq k_1 - 1)$ and $(k_2 + 1 \leq j \leq n)$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 4:** shift backward the job $s(k_2)$ in position k_1
- $t(k_1) = s(k_2)$
- For all j , $(k_1 + 1 \leq j \leq k_2)$, $t(j) = s(j - 1)$
- For all j , $(1 \leq j \leq k_1 - 1)$ and $(k_2 + 1 \leq j \leq n)$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 5:** shift forward the job $s(k_1)$ in position k_2
- $t(k_2) = s(k_1)$
- For all j , $k_1 \leq j \leq k_2 - 1$, $t(j) = s(j + 1)$
- For all j , $1 \leq j \leq k_1 - 1$ and $k_2 + 1 \leq j \leq n$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 5:** shift forward the job $s(k_1)$ in position k_2
- $t(k_2) = s(k_1)$
- For all j , $k_1 \leq j \leq k_2 - 1$, $t(j) = s(j + 1)$
- For all j , $1 \leq j \leq k_1 - 1$ and $k_2 + 1 \leq j \leq n$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 5:** shift forward the job $s(k_1)$ in position k_2
- $t(k_2) = s(k_1)$
- For all j , $k_1 \leq j \leq k_2 - 1$, $t(j) = s(j + 1)$
- For all j , $1 \leq j \leq k_1 - 1$ and $k_2 + 1 \leq j \leq n$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 5:** shift forward the job $s(k_1)$ in position k_2
- $t(k_2) = s(k_1)$
- For all j , $k_1 \leq j \leq k_2 - 1$, $t(j) = s(j + 1)$
- For all j , $1 \leq j \leq k_1 - 1$ and $k_2 + 1 \leq j \leq n$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 5:** shift forward the job $s(k_1)$ in position k_2
- $t(k_2) = s(k_1)$
- For all j , $k_1 \leq j \leq k_2 - 1$, $t(j) = s(j + 1)$
- For all j , $1 \leq j \leq k_1 - 1$ and $k_2 + 1 \leq j \leq n$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- **Move 5:** shift forward the job $s(k_1)$ in position k_2
- $t(k_2) = s(k_1)$
- For all j , $k_1 \leq j \leq k_2 - 1$, $t(j) = s(j + 1)$
- For all j , $1 \leq j \leq k_1 - 1$ and $k_2 + 1 \leq j \leq n$, $t(j) = s(j)$
- For $1 \leq k_1 < k_2 \leq n$
- The neighborhood has $\binom{n}{2} = \frac{n(n-1)}{2}$ elements

Local search for the $F2//T$

- These moves can be used with every problem the solution is a permutation
- Move 1: consecutive swap k and $k + 1$
- Move 2: any swap k_1 and k_2 : 2-opt
- Move 3: rotation (k_1, k_2, k_3) : 3-opt
- Move 4: Extraction and Backward Shift Reinsertion: EBSR
- Move 5: Extraction and Forward Shift Reinsertion: EFSR

Local search for the $F2//T$

- These moves can be used with every problem the solution is a permutation
- Move 1: **consecutive swap** k and $k + 1$
- Move 2: any swap k_1 and k_2 : **2-opt**
- Move 3: rotation (k_1, k_2, k_3) : **3-opt**
- Move 4: Extraction and Backward Shift Reinsertion: **EBSR**
- Move 5: Extraction and Forward Shift Reinsertion: **EFSR**

Local search for the $F2//T$

- These moves can be used with every problem the solution is a permutation
- Move 1: **consecutive swap** k and $k + 1$
- Move 2: any swap k_1 and k_2 : **2-opt**
- Move 3: rotation (k_1, k_2, k_3) : **3-opt**
- Move 4: Extraction and Backward Shift Reinsertion: **EBSR**
- Move 5: Extraction and Forward Shift Reinsertion: **EFSR**

Local search for the $F2//T$

- These moves can be used with every problem the solution is a permutation
- Move 1: **consecutive swap** k and $k + 1$
- Move 2: any swap k_1 and k_2 : **2-opt**
- Move 3: rotation (k_1, k_2, k_3) : **3-opt**
- Move 4: Extraction and Backward Shift Reinsertion: **EBSR**
- Move 5: Extraction and Forward Shift Reinsertion: **EFSR**

Local search for the $F2//T$

- These moves can be used with every problem the solution is a permutation
- Move 1: **consecutive swap** k and $k + 1$
- Move 2: any swap k_1 and k_2 : **2-opt**
- Move 3: rotation (k_1, k_2, k_3) : **3-opt**
- Move 4: Extraction and Backward Shift Reinsertion: **EBSR**
- Move 5: Extraction and Forward Shift Reinsertion: **EFSR**

Local search for the $F2//T$

- These moves can be used with every problem the solution is a permutation
- Move 1: **consecutive swap** k and $k + 1$
- Move 2: any swap k_1 and k_2 : **2-opt**
- Move 3: rotation (k_1, k_2, k_3) : **3-opt**
- Move 4: Extraction and Backward Shift Reinsertion: **EBSR**
- Move 5: Extraction and Forward Shift Reinsertion: **EFSR**

Algorithm of exploring a neighborhood

Neighborhood

function *Neighbor*(*s*)

Require: *s* is a solution of the problem

Ensure: The neighborhood of *s* is explored and *bestneighbor* is returned. A boolean value *Improved* is also returned.

```
1: currentvalue  $\leftarrow f(s)$ 
2: bestvalue  $\leftarrow$  currentvalue
3: bestneighbor  $\leftarrow s$ 
4: for t in neighborhood(s) do
5:   if (f(t) < bestvalue) then
6:     bestvalue  $\leftarrow f(t)$ 
7:     bestneighbor  $\leftarrow t$ 
8:   end if
9: end for
10: Improved  $\leftarrow$  (bestvalue < currentvalue)
11: return (Improved, bestneighbor)
```

Algorithm of the Iterated Local Search

Iterated Local Search

function *IteratedLS*(s)

Require: s is a solution of the problem

Ensure: The neighborhood of s is explored as long as an improvement is proved. Then the current best solution is returned.

```
1: Improved  $\leftarrow$  true
2: while (Improved) do
3:   (Improved, bestneighbor)  $\leftarrow$  Neighbor( $s$ )
4: end while
5: return bestneighbor
```