

# Matheuristics

Jean-Louis Bouquard



Beijing Institute of Technology

Optimization Methods

- 1 Generalities
- 2 Usual neighborhood
- 3 Other neighborhoods
  - The Shake model
  - The Swap model
  - The extended swap model
  - The EBSR and EFSR models
  - The Random model
- 4 Conclusion

# 1 Generalities

# Matheuristics

- **Matheuristics**
- reference to Metaheuristics
- or Math + Heuristics
- First papers: 2009, Hybridizing Metaheuristics and Mathematical programming (V. Maniezzo, T. Stützle, S. Voß, Annals of Information Systems, Springer)

# Matheuristics

- Matheuristics
- reference to Metaheuristics
- or Math + Heuristics
- First papers: 2009, Hybridizing Metaheuristics and Mathematical programming (V. Maniezzo, T. Stützle, S. Voß, Annals of Information Systems, Springer)

# Matheuristics

- Matheuristics
- reference to Metaheuristics
- or Math + Heuristics
- First papers: 2009, Hybridizing Metaheuristics and Mathematical programming (V. Maniezzo, T. Stützle, S. Voß, Annals of Information Systems, Springer)

# Matheuristics

- Matheuristics
- reference to Metaheuristics
- or Math + Heuristics
- First papers: 2009, Hybridizing Metaheuristics and Mathematical programming (V. Maniezzo, T. Stützle, S. Voß, Annals of Information Systems, Springer)

# Matheuristics

- In Iterated Local Search (ILS)
- Neighborhoods are searched by enumeration
- that is (local) brute force
- we could use MILP to do it!



# Matheuristics

- In Iterated Local Search (ILS)
- Neighborhoods are searched by enumeration
  - that is (local) brute force
  - we could use MILP to do it!

# Matheuristics

- In Iterated Local Search (ILS)
- Neighborhoods are searched by enumeration
- that is (local) brute force
- we could use MILP to do it!

# Matheuristics

- In Iterated Local Search (ILS)
- Neighborhoods are searched by enumeration
- that is (local) brute force
- we could use MILP to do it!

## 2 Usual neighborhood

# Defining a neighborhood

- Back to our  $F2/\Sigma T_j$  problem
- Restrict the search to a reasonable amount of jobs
- Given a solution  $s = (s_1, \dots, s_n)$
- and an interval  $[h..h + w - 1] \subset [1..n]$ , the width is  $w$
- let us consider the neighborhood defined by:
- all the solutions that are equal to  $s$  except on  $[h..h + w - 1]$
- $\mathcal{N}_{h,w}(s) = \{\sigma / \sigma_j = s_j \text{ for } j \notin [h..h + w - 1]\}$

# Defining a neighborhood

- Back to our  $F2//\Sigma T_j$  problem
- Restrict the search to a reasonable amount of jobs
- Given a solution  $s = (s_1, \dots, s_n)$
- and an interval  $[h..h + w - 1] \subset [1..n]$ , the width is  $w$
- let us consider the neighborhood defined by:
- all the solutions that are equal to  $s$  except on  $[h..h + w - 1]$
- $\mathcal{N}_{h,w}(s) = \{\sigma / \sigma_j = s_j \text{ for } j \notin [h..h + w - 1]\}$

# Defining a neighborhood

- Back to our  $F2//\Sigma T_j$  problem
- Restrict the search to a reasonable amount of jobs
- Given a solution  $s = (s_1, \dots, s_n)$ 
  - and an interval  $[h..h + w - 1] \subset [1..n]$ , the width is  $w$
  - let us consider the neighborhood defined by:
  - all the solutions that are equal to  $s$  except on  $[h..h + w - 1]$
  - $\mathcal{N}_{h,w}(s) = \{\sigma / \sigma_j = s_j \text{ for } j \notin [h..h + w - 1]\}$

# Defining a neighborhood

- Back to our  $F2/\Sigma T_j$  problem
- Restrict the search to a reasonable amount of jobs
- Given a solution  $s = (s_1, \dots, s_n)$
- and an interval  $[h..h + w - 1] \subset [1..n]$ , the width is  $w$
- let us consider the neighborhood defined by:
- all the solutions that are equal to  $s$  except on  $[h..h + w - 1]$
- $\mathcal{N}_{h,w}(s) = \{s' / s'_j = s_j \text{ for } j \notin [h..h + w - 1]\}$



# Defining a neighborhood

- Back to our  $F2//\Sigma T_j$  problem
- Restrict the search to a reasonable amount of jobs
- Given a solution  $s = (s_1, \dots, s_n)$
- and an interval  $[h..h + w - 1] \subset [1..n]$ , the width is  $w$
- let us consider the neighborhood defined by:
  - all the solutions that are equal to  $s$  except on  $[h..h + w - 1]$
  - $\mathcal{N}_{h,w}(s) = \{\sigma / \sigma_j = s_j \text{ for } j \notin [h..h + w - 1]\}$

# Defining a neighborhood

- Back to our  $F2/\Sigma T_j$  problem
- Restrict the search to a reasonable amount of jobs
- Given a solution  $s = (s_1, \dots, s_n)$
- and an interval  $[h..h + w - 1] \subset [1..n]$ , the width is  $w$
- let us consider the neighborhood defined by:
- all the solutions that are equal to  $s$  except on  $[h..h + w - 1]$
- $\mathcal{N}_{h,w}(s) = \{\sigma / \sigma_j = s_j \text{ for } j \notin [h..h + w - 1]\}$

# Defining a neighborhood

- Back to our  $F2/\Sigma T_j$  problem
- Restrict the search to a reasonable amount of jobs
- Given a solution  $s = (s_1, \dots, s_n)$
- and an interval  $[h..h + w - 1] \subset [1..n]$ , the width is  $w$
- let us consider the neighborhood defined by:
- all the solutions that are equal to  $s$  except on  $[h..h + w - 1]$
- $\mathcal{N}_{h,w}(s) = \{\sigma / \sigma_j = s_j \text{ for } j \notin [h..h + w - 1]\}$

# Defining a neighborhood

- There are  $w!$  elements in this neighborhood
- We will search for the best solution of this neighborhood
- a best local solution
- Not using brute force, but MILP
- For the model, we can use the lesson 3 model
- and fix all the variables we know
- or we can build a dedicated model

# Defining a neighborhood

- There are  $w!$  elements in this neighborhood
- We will search for the best solution of this neighborhood
- a best local solution
- Not using brute force, but MILP
- For the model, we can use the lesson 3 model
- and fix all the variables we know
- or we can build a dedicated model

# Defining a neighborhood

- There are  $w!$  elements in this neighborhood
- We will search for the best solution of this neighborhood
- a best local solution
- Not using brute force, but MILP
- For the model, we can use the lesson 3 model
- and fix all the variables we know
- or we can build a dedicated model

# Defining a neighborhood

- There are  $w!$  elements in this neighborhood
- We will search for the best solution of this neighborhood
- a best local solution
- Not using brute force, but MILP
- For the model, we can use the lesson 3 model
- and fix all the variables we know
- or we can build a dedicated model

# Defining a neighborhood

- There are  $w!$  elements in this neighborhood
- We will search for the best solution of this neighborhood
- a best local solution
- Not using brute force, but MILP
- For the model, we can use the lesson 3 model
  - and fix all the variables we know
  - or we can build a dedicated model




# Defining a neighborhood

- There are  $w!$  elements in this neighborhood
- We will search for the best solution of this neighborhood
- a best local solution
- Not using brute force, but MILP
- For the model, we can use the lesson 3 model
- and fix all the variables we know
- or we can build a dedicated model


# Defining a neighborhood

- There are  $w!$  elements in this neighborhood
- We will search for the best solution of this neighborhood
- a best local solution
- Not using brute force, but MILP
- For the model, we can use the lesson 3 model
- and fix all the variables we know
- or we can build a dedicated model


# Defining a neighborhood




# Defining a neighborhood




# Defining a neighborhood




# Defining a neighborhood



# Defining a neighborhood




# Defining a neighborhood





# Defining a neighborhood



# A model for the neighborhood

## Variables



- Metadata: from  $s$  we compute useful values
- Variables are:
  - $X_{k,j}$  for  $k \in [0..w-1]$  and  $j \in [0..w-1]$ .  
 $X_{k,j} = 1$  if and only if the job  $s[h+j]$  is in position  $h+k$
  - $F1_k, F2_k$  and  $G_k$  for  $k \in [0..w-1]$ .  
 They correspond to the job in position  $h+k$
  - $C2_j, T_j$  for the jobs in position  $\in [h+w..n]$

# A model for the neighborhood

## Variables



- Metadata: from  $s$  we compute useful values
- Variables are:
  - •  $X_{k,j}$  for  $k \in [0..w-1]$  and  $j \in [0..w-1]$ .  
 $X_{k,j} = 1$  if and only if the job  $s[h+j]$  is in position  $h+k$
  - •  $F1_k, F2_k$  and  $G_k$  for  $k \in [0..w-1]$ .  
 They correspond to the job in position  $h+k$
  - •  $C2_j, T_j$  for the jobs in position  $\in [h+w..n]$

# A model for the neighborhood

## Variables



- Metadata: from  $s$  we compute useful values
- Variables are:
  - $X_{k,j}$  for  $k \in [0..w-1]$  and  $j \in [0..w-1]$ .  
 $X_{k,j} = 1$  if and only if the job  $s[h+j]$  is in position  $h+k$
  - $F1_k, F2_k$  and  $G_k$  for  $k \in [0..w-1]$ .  
 They correspond to the job in position  $h+k$
  - $C2_j, T_j$  for the jobs in position  $\in [h+w..n]$

# A model for the neighborhood

## Variables



- Metadata: from  $s$  we compute useful values
- Variables are:
  - $X_{k,j}$  for  $k \in [0..w-1]$  and  $j \in [0..w-1]$ .  
 $X_{k,j} = 1$  if and only if the job  $s[h+j]$  is in position  $h+k$
  - $F1_k, F2_k$  and  $G_k$  for  $k \in [0..w-1]$ .  
 They correspond to the job in position  $h+k$
  - $C2_j, T_j$  for the jobs in position  $\in [h+w..n]$

# A model for the neighborhood

## Variables



- Metadata: from  $s$  we compute useful values
- Variables are:
  - $X_{k,j}$  for  $k \in [0..w-1]$  and  $j \in [0..w-1]$ .  
 $X_{k,j} = 1$  if and only if the job  $s[h+j]$  is in position  $h+k$
  - $F1_k, F2_k$  and  $G_k$  for  $k \in [0..w-1]$ .  
 They correspond to the job in position  $h+k$
  - $C2_j, T_j$  for the jobs in position  $\in [h+w..n]$

# A model for the neighborhood

## Constraints



- Each rank is assigned to a unique job (rows of the matrix  $(X_{k,j})$ ):

$$\forall k \in [0..w-1] \quad \sum_{j=0}^{w-1} X_{k,j} = 1 \quad (1)$$

- Each job has got a unique rank (columns of the matrix  $(X_{k,j})$ ):

$$\forall j \in [0..w-1] \quad \sum_{k=0}^{w-1} X_{k,j} = 1 \quad (2)$$

# A model for the neighborhood

## Constraints



- Each rank is assigned to a unique job (rows of the matrix  $(X_{k,j})$ ):

$$\forall k \in [0..w-1] \quad \sum_{j=0}^{w-1} X_{k,j} = 1 \quad (1)$$

- Each job has got a unique rank (columns of the matrix  $(X_{k,j})$ ):

$$\forall j \in [0..w-1] \quad \sum_{k=0}^{w-1} X_{k,j} = 1 \quad (2)$$



# A model for the neighborhood

## Constraints



- Completion time on  $M1$  of the job in position  $h$  (first red job)

$$F1_0 = f1_{h-1} + \sum_{j=0}^{w-1} p1_{s_{(h+j)}} X_{0,j} \quad (3)$$

- Completion times on  $M1$  of the jobs in position  $h+1..h+w-1$  (other red jobs)

$$\forall k \in [1..w-1] \quad F1_k = F1_{k-1} + \sum_{j=0}^{w-1} p1_{s_{(h+j)}} X_{k,j} \quad (4)$$

# A model for the neighborhood

## Constraints



- Completion time on  $M1$  of the job in position  $h$  (first red job)

$$F1_0 = f1_{h-1} + \sum_{j=0}^{w-1} p1_{s(h+j)} X_{0,j} \quad (3)$$

- Completion times on  $M1$  of the jobs in position  $h + 1..h + w - 1$  (other red jobs)

$$\forall k \in [1..w-1] \quad F1_k = F1_{k-1} + \sum_{j=0}^{w-1} p1_{s(h+j)} X_{k,j} \quad (4)$$

# A model for the neighborhood

## Constraints



- Completion time on  $M2$  of the job in position  $h$  (first red job)

$$F2_0 \geq f2_{h-1} + \sum_{j=0}^{w-1} p2_{s_{(h+j)}} X_{0,j} \quad (5)$$

- Completion times on  $M2$  of the jobs in position  $h+1..h+w-1$  (other red jobs)

$$\forall k \in [1..w-1] \quad F2_k \geq F2_{k-1} + \sum_{j=0}^{w-1} p2_{s_{(h+j)}} X_{k,j} \quad (6)$$

# A model for the neighborhood

## Constraints



- Completion time on  $M2$  of the job in position  $h$  (first red job)

$$F2_0 \geq f2_{h-1} + \sum_{j=0}^{w-1} p2_{s(h+j)} X_{0,j} \quad (5)$$

- Completion times on  $M2$  of the jobs in position  $h + 1..h + w - 1$  (other red jobs)

$$\forall k \in [1..w-1] \quad F2_k \geq F2_{k-1} + \sum_{j=0}^{w-1} p2_{s(h+j)} X_{k,j} \quad (6)$$

# A model for the neighborhood

## Constraints



- Completion times on  $M2$  of the jobs in position  $h..h + w - 1$  (red jobs):  $M2$  is after  $M1$

$$\forall k \in [0..w-1] \quad F2_k \geq F1_k + \sum_{j=0}^{w-1} p2_{s_{(h+j)}} X_{k,j} \quad (7)$$

- Tardinesses of the jobs in position  $h..h + w - 1$  (red jobs):

$$\forall k \in [0..w-1] \quad G_k \geq F2_k - \sum_{j=0}^{w-1} d_{s_{(h+j)}} X_{k,j} \quad (8)$$

# A model for the neighborhood

## Constraints



- Completion times on  $M2$  of the jobs in position  $h..h + w - 1$  (red jobs):  $M2$  is after  $M1$

$$\forall k \in [0..w - 1] \quad F2_k \geq F1_k + \sum_{j=0}^{w-1} p2_{s_{(h+j)}} X_{k,j} \quad (7)$$

- Tardinesses of the jobs in position  $h..h + w - 1$  (red jobs):

$$\forall k \in [0..w - 1] \quad G_k \geq F2_k - \sum_{j=0}^{w-1} d_{s_{(h+j)}} X_{k,j} \quad (8)$$

# A model for the neighborhood

## Constraints



- Completion times on  $M2$  of the jobs in position  $h + w..n$  (yellow jobs):

$$\forall j \in [0..n - h - w] \quad C2_j \geq \pi_{h+w, h+w+j}^1 \quad (9)$$

$$C2_j \geq F2_{w-1} + \pi_{h+w, h+w+j}^2 \quad (10)$$

- Tardinesses of the jobs in position  $h + w..n$  (yellow jobs):

$$\forall j \in [0..n - h - w] \quad T_j \geq C2_j - d_{s(h+w+j)} \quad (11)$$

# A model for the neighborhood

## Constraints



- Completion times on  $M2$  of the jobs in position  $h + w..n$  (yellow jobs):

$$\forall j \in [0..n - h - w] \quad C2_j \geq \pi_{h+w, h+w+j}^1 \quad (9)$$

$$C2_j \geq F2_{w-1} + \pi_{h+w, h+w+j}^2 \quad (10)$$

- Tardinesses of the jobs in position  $h + w..n$  (yellow jobs):

$$\forall j \in [0..n - h - w] \quad T_j \geq C2_j - d_{s(h+w+j)} \quad (11)$$



# A model for the neighborhood

Constraint of improvement and objective function



- We want to improve the current solution:

$$\sum_{j=1}^{h-1} g_j + \sum_{k=0}^{w-1} G_k + \sum_{j=0}^{n-h-w} T_j \leq tbar(s) - 1 \quad (12)$$

- Objective function:

$$\text{Minimize} \quad \sum_{k=0}^{w-1} G_k + \sum_{j=0}^{n-h-w} T_j$$

# A model for the neighborhood

Constraint of improvement and objective function



- We want to improve the current solution:

$$\sum_{j=1}^{h-1} g_j + \sum_{k=0}^{w-1} G_k + \sum_{j=0}^{n-h-w} T_j \leq tbar(s) - 1 \quad (12)$$

- Objective function:

$$\text{Minimize} \quad \sum_{k=0}^{w-1} G_k + \sum_{j=0}^{n-h-w} T_j$$

# Running this model

## Function One-Pass( $w, step$ )

```

1: improved  $\leftarrow$  false
2: for  $h$  from 0 while ( $h + w \leq n$ ) by step do
3:   Run the model
4:   if (there is a solution news) then
5:      $s \leftarrow news$ 
6:     improved  $\leftarrow$  true
7:   end if
8: end for
9: return improved

```

- $w$ : width of the interval
- *step*: pace for the progression of the interval
- line 4: if there is a solution, then it is better than  $s$
- $s$  is modified by side **effect**

# Running this model

In the function One-pass, the model is launched  $\left\lfloor \frac{n-w}{step} \right\rfloor$  times.

The function One-Pass is used while the solution is improved.  
A fixed point is reached.

Function Several-Passes( $w, step$ )

```

1:  $s \leftarrow$  initial solution
2: while One-Pass( $w, step$ ) do
3:   Pass
4: end while
5: return  $s$ 

```

# Running this model

In the function One-pass, the model is launched  $\left\lfloor \frac{n-w}{step} \right\rfloor$  times.

The function One-Pass is used while the solution is improved.  
A fixed point is reached.

Function Several-Passes( $w, step$ )

```

1:  $s \leftarrow$  initial solution
2: while One-Pass( $w, step$ ) do
3:   Pass
4: end while
5: return  $s$ 

```

# Running this model

In the function One-pass, the model is launched  $\left\lfloor \frac{n-w}{step} \right\rfloor$  times.

The function One-Pass is used while the solution is improved.  
A fixed point is reached.

## Function Several-Passes(w,step)

```

1:  $s \leftarrow$  initial solution
2: while One-Pass(w,step) do
3:   Pass
4: end while
5: return  $s$ 

```

### 3 Other neighborhoods

- The Shake model
- The Swap model
- The extended swap model
- The EBSR and EFSR models
- The Random model

# A second neighborhood

- In the local search, we considered swapping consecutive jobs
- Now we can allow jobs to change their positions in a limited way
- for each job,  $\text{new-rank} \in [\text{old-rank} - \delta, \text{old-rank} + \delta]$
- This will be called the Shake model



# A second neighborhood

- In the local search, we considered swapping consecutive jobs
- Now we can allow jobs to change their positions in a limited way
  - for each job,  $\text{new-rank} \in [\text{old-rank} - \delta, \text{old-rank} + \delta]$
  - This will be called the **Shake model**

# A second neighborhood

- In the local search, we considered swapping consecutive jobs
- Now we can allow jobs to change their positions in a limited way
- for each job,  $\text{new-rank} \in [\text{old-rank} - \delta .. \text{old-rank} + \delta]$
- This will be called the **Shake model**

# A second neighborhood

- In the local search, we considered swapping consecutive jobs
- Now we can allow jobs to change their positions in a limited way
- for each job,  $\text{new-rank} \in [\text{old-rank} - \delta .. \text{old-rank} + \delta]$
- This will be called the **Shake model**

# Defining a second neighborhood

$s()$

	0	...	$\delta$										$n-1$
0	X	X	X										
...	X	X	X	X									
$\delta$	X	X	X	X	X								
		X	X	X	X	X							
			X	X	X	X	X						
				X	X	X	X	X					
					X	X	X	X	X				
						X	X	X	X	X			
							X	X	X	X	X		
								X	X	X	X	X	
$n-1$									X	X	X	X	

The **X** correspond to possible moves

thus to binary variables.

The ranks of the jobs are recomputed.


## Defining a second neighborhood

The **X** correspond to possible moves

thus to binary variables.


The parameters of the method are:

- $\delta$
- $w$ : width of the interval
- $step$




# A third neighborhood

- In the local search, we considered swapping any pairs of two jobs
- Now we can consider jobs within two (small) distinct intervals
- This will be called the **Swap model**




# A third neighborhood

- In the local search, we considered swapping any pairs of two jobs
- Now we can consider jobs within two (small) distinct intervals
- This will be called the **Swap model**



# A third neighborhood


- In the local search, we considered swapping any pairs of two jobs
- Now we can consider jobs within two (small) distinct intervals
- This will be called the **Swap model**





# A third neighborhood

- In the local search, we considered swapping any pairs of two jobs
- Now we can consider jobs within two (small) distinct intervals
- This will be called the **Swap model**



# Running the Swap model

## Function One-Pass( $w, \text{step}$ )

```


1: improved  $\leftarrow$  false
2: for  $h_1$  from 0 while ( $h_1 + 2w \leq n$ ) by  $\text{step}_1$  do
3:   for  $h_2$  from  $h_1 + w$  while ( $h_2 + w \leq n$ ) by  $\text{step}_2$  do
4:     Run the model
5:     if (there is a solution news) then
6:        $s \leftarrow \text{news}$ 
7:       improved  $\leftarrow$  true
8:     end if
9:   end for
10: end for
11: return improved

```

- $w$ : width of the interval
- $\text{step}_1, \text{step}_2$ : pace for the progression of  $h_1$  and  $h_2$
- the model is launched  $\approx \frac{(n-2w)^2}{2\text{step}_1\text{step}_2}$  **times**


# A variant of the Swap model

- In the Swap model, the (blue) jobs with the rank  $[1..h_1 - 1]$ ,  $[h_1 + w..h_2 - 1]$  and  $[h_2 + w..n]$  do not change
- Only the (red) jobs with the ranks within the intervals  $[h_1..h_1 + w - 1]$  and  $[h_2..h_2 + w - 1]$  are recomputed.




# A variant of the Swap model

- In the Swap model, the (blue) jobs with the rank  $[1..h_1 - 1]$ ,  $[h_1 + w..h_2 - 1]$  and  $[h_2 + w..n]$  do not change
- Only the (red) jobs with the ranks within the intervals  $[h_1..h_1 + w - 1]$  and  $[h_2..h_2 + w - 1]$  are recomputed.




# the Extended Swap model

- In the Extended Swap model, the (blue) jobs with the rank  $[1..h_1 - 1]$  and  $[h_2 + w..n]$  do not change
- The (red) jobs with the ranks within the intervals  $[h_1..h_1 + w - 1] \cup [h_2..h_2 + w - 1]$  are recomputed
- within the intervals  $[h_1..h_1 + w + v - 1] \cup [h_2 + v..h_2 + w - 1]$  where  $v$  is a small positive or negative variable.




# the Extended Swap model

- In the Extended Swap model, the (blue) jobs with the rank  $[1..h_1 - 1]$  and  $[h_2 + w..n]$  do not change
- The (red) jobs with the ranks within the intervals  $[h_1..h_1 + w - 1] \cup [h_2..h_2 + w - 1]$  are recomputed
- within the intervals  $[h_1..h_1 + w + v - 1] \cup [h_2 + v..h_2 + w - 1]$  where  $v$  is a small positive or negative variable.




# the Extended Swap model

- In the Extended Swap model, the (blue) jobs with the rank  $[1..h_1 - 1]$  and  $[h_2 + w..n]$  do not change
- The (red) jobs with the ranks within the intervals  $[h_1..h_1 + w - 1] \cup [h_2..h_2 + w - 1]$  are recomputed
- within the intervals  $[h_1..h_1 + w + v - 1] \cup [h_2 + v..h_2 + w - 1]$  where  $v$  is a small positive or negative **variable**.



# the Extended Swap model


- The subsequence of the (yellow) jobs in the interval  $[h_1 + w..h_2 - 1]$  is shifted of  $v$  positions
  - leftward or rightward, depending on the sign of  $v$
  - $HV$ 's are to be used in the model to enable this possibility (the price of the free  $v$ )






# the Extended Swap model

- The subsequence of the (yellow) jobs in the interval  $[h_1 + w..h_2 - 1]$  is shifted of  $v$  positions
- leftward or rightward, depending on the sign of  $v$
- $HV$ 's are to be used in the model to enable this possibility (the price of the free  $v$ )



# the Extended Swap model


- The subsequence of the (yellow) jobs in the interval  $[h_1 + w..h_2 - 1]$  is shifted of  $v$  positions
- leftward or rightward, depending on the sign of  $v$
- $HV$ 's are to be used in the model to enable this possibility (the price of the free  $v$ )



# The EBSR model

## Extraction and Backward Shifted Reinsertion


- The subsequence of the (red) jobs in the interval  $[h_2 - w..h_2 - 1]$  gives place to the intervals  $[h_1..h_1 + v - 1]$  and  $[h_2 + v - w..h_2 - 1]$
- The subsequence of the (yellow) jobs in the interval  $[h_1..h_2 - w - 1]$  is shifted rightward of  $v$  positions



# The EBSR model

## Extraction and Backward Shifted Reinsertion


- The subsequence of the (red) jobs in the interval  $[h_2 - w..h_2 - 1]$  gives place to the intervals  $[h_1..h_1 + v - 1]$  and  $[h_2 + v - w..h_2 - 1]$
- The subsequence of the (yellow) jobs in the interval  $[h_1..h_2 - w - 1]$  is shifted rightward of  $v$  positions



# The EFSR model

## Extraction and Forward Shifted Reinsertion


- The subsequence of the (red) jobs in the interval  $[h_1..h_1 + w - 1]$  gives place to the intervals  $[h_1..h_1 + w - v - 1]$  and  $[h_2 - v..h_2 - 1]$
- The subsequence of the (yellow) jobs in the interval  $[h_1 + w..h_2 - 1]$  is shifted leftward of  $(w - v)$  positions



# The EFSR model

## Extraction and Forward Shifted Reinsertion

- The subsequence of the (red) jobs in the interval  $[h_1..h_1 + w - 1]$  gives place to the intervals  $[h_1..h_1 + w - v - 1]$  and  $[h_2 - v..h_2 - 1]$
- The subsequence of the (yellow) jobs in the interval  $[h_1 + w..h_2 - 1]$  is shifted leftward of  $(w - v)$  positions



# The Random model

- We choose  $w$  jobs
- The other  $(n - w)$  jobs keep the same ranks
- We compute the optimal local solution

# The Random model

- We choose  $w$  jobs
- The other  $(n - w)$  jobs keep the same ranks
- We compute the optimal local solution



# The Random model

- We choose  $w$  jobs
- The other  $(n - w)$  jobs keep the same ranks
- We compute the optimal local solution

# The Random model

- $\binom{n}{w}$  is huge!
  - In practice impossible to enumerate
  - We use only a fixed number of randomly generated subsets
  - for this method, no fixed point to reach

# The Random model

- $\binom{n}{w}$  is huge!
- In practice impossible to enumerate
- We use only a fixed number of randomly generated subsets
- for this method, no fixed point to reach

# The Random model

- $\binom{n}{w}$  is huge!
- In practice impossible to enumerate
- We use only a fixed number of randomly generated subsets
- for this method, no fixed point to reach

# The Random model

- $\binom{n}{w}$  is huge!
- In practice impossible to enumerate
- We use only a fixed number of randomly generated subsets
- for this method, no fixed point to reach

## 4 Conclusion

# Various Matheuristic methods

- 1 The “classical” method
- 2 The Shake method
- 3 The Swap method
- 4 The Extended Swap method
- 5 The EBSR and EFSR methods
- 6 The Random method

# Various Matheuristic methods

- 1 The “classical” method
- 2 The Shake method
- 3 The Swap method
- 4 The Extended Swap method
- 5 The EBSR and EFSR methods
- 6 The Random method



# Various Matheuristic methods

- 1 The “classical” method
- 2 The Shake method
- 3 The Swap method
- 4 The Extended Swap method
- 5 The EBSR and EFSR methods
- 6 The Random method

# Various Matheuristic methods

- 1 The “classical” method
- 2 The Shake method
- 3 The Swap method
- 4 The Extended Swap method
- 5 The EBSR and EFSR methods
- 6 The Random method

# Various Matheuristic methods

- 1 The “classical” method
- 2 The Shake method
- 3 The Swap method
- 4 The Extended Swap method
- 5 The EBSR and EFSR methods
- 6 The Random method

# Various Matheuristic methods

- 1 The “classical” method
- 2 The Shake method
- 3 The Swap method
- 4 The Extended Swap method
- 5 The EBSR and EFSR methods
- 6 The Random method

# How to compare them?

- How to compare them?
- For each method
- How to choose the parameters?
- How to choose the way to make loops?
- Anyway, let's go!

# How to compare them?

- How to compare them?
- For each method
  - How to choose the parameters?
  - How to choose the way to make loops?
  - Anyway, let's go!

# How to compare them?

- How to compare them?
- For each method
- How to choose the parameters?
- How to choose the way to make loops?
- Anyway, let's go!

# How to compare them?

- How to compare them?
- For each method
- How to choose the parameters?
- How to choose the **way** to make **loops**?
- Anyway, let's go!



# How to compare them?

- How to compare them?
- For each method
- How to choose the parameters?
- How to choose the **way** to make **loops**?
- Anyway, let's go!

# What can we conclude from the experiment?

The ILS

- Beware of the *gray cat* theorem!
- EDD versus NEH ?
- Swap, EBSR or EFSR ?
- Compare with Edd23 and Neh23.
- Is it well worth it?

# What can we conclude from the experiment?

The ILS

- Beware of the *gray cat* theorem!
- EDD versus NEH ?
- Swap, EBSR or EFSR ?
- Compare with Edd23 and Neh23.
- Is it well worth it?

# What can we conclude from the experiment?

The ILS

- Beware of the *gray cat* theorem!
- EDD versus NEH ?
- Swap, EBSR or EFSR ?
- Compare with Edd23 and Neh23.
- Is it well worth it?

# What can we conclude from the experiment?

The ILS

- Beware of the *gray cat* theorem!
- EDD versus NEH ?
- Swap, EBSR or EFSR ?
- Compare with Edd23 and Neh23.
- Is it well worth it?

# What can we conclude from the experiment?

The ILS

- Beware of the *gray cat* theorem!
- EDD versus NEH ?
- Swap, EBSR or EFSR ?
- Compare with Edd23 and Neh23.
- Is it well worth it?

# What can we conclude from the experiment?

## The Matheuristics

- Classical, Swap, SwapEx, Shake, EBSR, EFSR, Random?
- Choice of the parameters!
- What should be done now?

# What can we conclude from the experiment?

## The Matheuristics

- Classical, Swap, SwapEx, Shake, EBSR, EFSR, Random?
- Choice of the parameters!
- What should be done now?



# What can we conclude from the experiment?

## The Matheuristics

- Classical, Swap, SwapEx, Shake, EBSR, EFSR, Random?
- Choice of the parameters!
- What should be done now?

# What can we conclude from the experiment?

## The Matheuristics

- Classical, Swap, SwapEx, Shake, EBSR, EFSR, Random?
- Choice of the parameters!
- What should be done now?