Capacity-Theoretic Limits of Slow Fault Mitigation under Power-of-Two-Choices Routing

DaLaw2

Abstract

Slow faults—where nodes remain reachable but exhibit degraded performance—are a persistent source of tail latency violations in distributed systems. Unlike crash faults, slow faults evade health checks and produce ambiguous signals under high load. We present a capacity-theoretic analysis of slow fault mitigation under Power-of-Two-Choices (P2C) load balancing, establishing three results. First, the *operating envelope*: the maximum tolerable fault fraction is $f_{\max} = 1 - L/U$, where L is the load factor and U the utilization ceiling, validated empirically with zero fitted parameters. Second, *severity non-monotonicity*: under P2C routing, a moderate slowdown (e.g., 10×) causes worse tail latency than an extreme one (e.g., 20×), with the critical severity $s^* = fq/((1-q)(N-f))$. Third, *SHED–P2C complementarity*: P2C's queue-depth comparison and explicit weight reduction (SHED) are complementary mechanisms operating at different stages of routing—SHED provides 5–70 ms P99 improvement at moderate severity (2–5×) but is unnecessary above s^* where P2C self-isolates faulty nodes. Crucially, any detection-triggered weight reduction achieves nearly identical results to full isolation under P2C, demonstrating that *detection speed, not response strategy, is the primary bottleneck* in slow fault mitigation. Through discrete-event simulation across 15 fault scenarios, we show that reactive mechanisms (hedged requests, timeout retry) are ineffective, while proactive detection with traffic exclusion is necessary and sufficient. Our results provide practitioners with analytical tools to determine when mitigation is feasible, which severity regime demands intervention, and why detection precision matters less than detection speed under queue-aware routing.

1 Introduction

Slow faults—where a node remains reachable but exhibits degraded performance—are among the most insidious failures in distributed systems [4, 5]. Unlike crash faults, which are detected immediately by health checks, slow faults produce ambiguous signals: elevated latency that may stem from transient load rather than genuine degradation. Left unmitigated, a single slow node in a cluster of 32 can increase system P99 latency by 3–9×, violating service-level objectives (SLOs) and propagating through dependency chains [3].

The standard response to tail latency is *hedged requests*: send a speculative copy to a second server after a brief delay, and use whichever response arrives first [3]. This works well for *random stragglers*—transient delays caused by garbage collection, context switching, or background I/O. However, persistent slow faults differ fundamentally: the same nodes remain slow across thousands of requests, rendering per-request hedging ineffective because future requests continue to be routed to faulty nodes.

Modern load balancers predominantly use Power-of-Two-Choices (P2C) routing [7], which samples two candidates weighted by their routing weights and selects the one with the shorter queue. A natural question arises: *does P2C's queue-depth awareness already handle slow faults, making explicit mitigation redundant?* In this paper, we answer this question with three theoretical results and extensive empirical validation.

1. **Operating envelope.** The maximum fraction of faulty nodes that any mitigation strategy can tolerate is:

$$f_{\max} = 1 - \frac{L}{U} \tag{1}$$

where L is the system load factor and $U \approx 0.89$ is the utilization ceiling beyond which M/D/1 queueing delay grows superlinearly. This formula, with *zero fitted parameters*, predicts the empirical pass/fail boundary across four load levels (Section 4.1).

2. **Severity non-monotonicity.** Under P2C routing, the "worst" slowdown factor is not the highest but the one where the fraction of traffic reaching faulty nodes exactly equals the percentile tail width:

$$s^* = \frac{f \cdot q}{(1-q)(N-f)} \tag{2}$$

Above s^*, P2C's queue-depth comparison renders faulty requests statistically invisible—the system *self-isolates* the faulty node without any explicit intervention (Section 4.2).

3. **SHED–P2C complementarity.** P2C routing and explicit weight reduction (SHED) operate at different stages of the routing decision: SHED controls *candidate selection probability* while P2C provides a *queue-depth tiebreaker*. These are complementary, not redundant. SHED's benefit scales as $O(N^{-\alpha})$ ($\alpha \approx 1.3$), is maximized at moderate severity (2–5×), and vanishes above s^* where P2C self-isolates. Crucially, under P2C a minimum weight of $w_{\min} = 0.05$ achieves nearly identical P99 to full isolation ($w = 0$), demonstrating that *detection accuracy matters far less than detection speed* (Section 4.3).

We validate these results through discrete-event simulation of clusters ranging from 8 to 64 nodes across 15 fault scenarios. Our evaluation compares eight mitigation strategies, including three literature baselines (hedged requests [3], outlier blacklisting [6], and timeout retry). The key empirical findings are:

- **Detection speed is the primary bottleneck.** Under P2C routing, graduated weight reduction and full isolation produce nearly identical P99 latency (gap < 2 ms). The response strategy is inconsequential once detection identifies the faulty node. This holds across cluster sizes, severity levels, and load factors (Section 6.4).

- **Reactive mechanisms fail.** Hedged requests and timeout retry improve SLO compliance by less than 0.3 percentage points over no mitigation—they are designed for random stragglers, not persistent faults (Section 6.2).

- **Proactive detection is necessary and sufficient.** All strategies that detect faulty nodes and redirect traffic achieve P99 < 45 ms across all scenarios at 80% load, regardless of the specific response strategy (SHED vs. isolation). The gap between no mitigation and any proactive strategy (5–70 ms) dwarfs the gap between different proactive strategies (< 2 ms) (Section 6.2).

Our contributions provide practitioners with: (1) a simple formula to determine whether mitigation is feasible for a given load and fault fraction; (2) an analytical tool to identify the most dangerous slowdown regime; (3) a complementarity theorem explaining when P2C suffices alone and when explicit detection is needed; and (4) empirical evidence that detection speed, not response precision, is the primary design target for slow fault mitigation systems.

2 Background and Motivation

2.1 Slow Faults in Production Systems

Gray failures [5] encompass a spectrum of partial failures where components are neither fully operational nor completely down. Slow faults—a subclass where service time degrades by a factor $s > 1$—arise from diverse root causes: memory pressure causing excessive garbage collection, disk degradation increasing I/O latency, thermal throttling reducing CPU frequency, or network congestion on a specific path [4].

Unlike crash faults, slow faults are difficult to detect because the affected node continues to respond, albeit slowly. Standard health checks (TCP probes, heartbeats) cannot distinguish a 5× slower node from a healthy one under transient load. This ambiguity is especially pronounced at high system utilization, where *all* nodes exhibit elevated latency due to queueing effects.

2.2 Power-of-Two-Choices Load Balancing

Power-of-Two-Choices (P2C) [7] is the dominant load balancing algorithm in modern distributed systems, used in Envoy [1], nginx, and numerous cloud-native infrastructure. For each incoming request, P2C samples two candidate workers at random and routes the request to the one with the shorter queue.

P2C provides an important but under-appreciated implicit mitigation mechanism for slow faults. A node with slowdown factor s processes requests s times slower, causing its queue to grow. P2C's queue-depth comparison then naturally avoids this node, routing traffic to healthier alternatives. We show in Section 4.2 that this implicit mitigation is highly effective at extreme severities ($s > s^*$) but insufficient at moderate severities ($s < s^*$), precisely where explicit mitigation strategies add value.

2.3 Existing Mitigation Approaches

Hedged requests. Dean and Barroso [3] proposed sending a speculative copy of a request to a second server after a delay (typically the expected service time). The client uses whichever response arrives first. This is effective for random stragglers but, as we demonstrate, ineffective for persistent slow faults because new requests continue to be routed to the faulty node.

Outlier blacklisting. Systems like Cassandra's dynamic snitch [6] track per-node latency and temporarily blacklist nodes whose latency exceeds k standard deviations above the cluster median. This is a proactive mechanism that redirects future traffic, but risks oscillation at high load when blacklisting reduces capacity and increases latency on remaining nodes.

Circuit breaking. Istio and Envoy implement circuit breakers that open when error rates or latency exceed thresholds, redirecting traffic away from unhealthy endpoints. These are effective but require manual threshold tuning and do not adapt to varying load conditions.

2.4 The Mitigation Trap

A key motivation for this work is the *mitigation trap*: at high system load, naive mitigation strategies can be *worse than doing nothing*. Consider hedged requests at 85% load: each hedge adds a duplicate request, pushing healthy workers from $\rho = 0.85$ toward saturation. The M/D/1

queueing delay grows as $\rho/(2(1-\rho))$, creating a positive feedback loop: hedges increase load, which increases latency, which triggers more hedges.

We discovered this phenomenon empirically (Section 6.2) and it motivates the load-aware design of our adaptive framework: any mitigation strategy must account for its own capacity cost.

3 System Model

3.1 Architecture

We model a single-tier distributed service consisting of N homogeneous worker nodes fronted by a load balancer. Requests arrive as a Poisson process with aggregate rate $\Lambda = L \cdot N \cdot \mu$, where $L \in (0, 1)$ is the *load factor* and $\mu = 1/t_{\text{base}}$ is the per-node service rate. Each worker processes requests sequentially (single-server) with deterministic service time t_{base} under normal conditions, yielding an M/D/1 queueing model per node.

The load balancer implements weighted Power-of-Two-Choices (P2C): for each request, it samples two candidates with probability proportional to their weights $w_i \in [0, 1]$ and routes to the candidate with the shorter queue depth.

3.2 Fault Model

A *slow fault* on node i multiplies its service time by a slowdown factor $s_i > 1$:

$$t_i = s_i \cdot t_{\text{base}} \tag{3}$$

We consider f simultaneously faulty nodes out of N total. Faults are *persistent*: once onset occurs, the slowdown remains until explicit recovery (if any). We study five fault patterns:

- **Permanent**: constant s after onset.
- **Progressive**: $s(t) = 1 + (s_{\max} - 1)(1 - e^{-\beta t})$, gradually worsening.
- **Fluctuating**: alternates between $s = s_{\text{peak}}$ and $s = 1$ with configurable on/off durations.
- **Cascading**: faults appear sequentially on different nodes at staggered times.
- **Recovering**: fault active for a fixed duration, then node returns to normal.

3.3 Performance Metrics

We evaluate using standard tail latency metrics:

- **P99/P999 latency**: 99th and 99.9th percentile of end-to-end request latency (including queueing delay).
- **SLO violation rate**: fraction of requests exceeding the SLO target (50 ms in our experiments).
- **Goodput**: requests completing within SLO per second.
- **Affected ratio**: fraction of requests served by faulty nodes (measures load balancer effectiveness).

3.4 Minimax Regret

To compare strategies across diverse scenarios, we use the *minimax regret* criterion. For strategy j in scenario i, the regret is:

$$R_{ij} = P99_{ij} - \min_k P99_{ik} \tag{4}$$

The minimax regret of strategy j is $\max_i R_{ij}$: its worst-case gap from the best strategy in any scenario. A strategy with low minimax regret is robust across operating conditions.

4 Analytical Results

We derive three results that characterize the fundamental limits and mechanisms of slow fault mitigation under P2C routing.

4.1 Operating Envelope

When the detector isolates faulty nodes, the load on the remaining healthy nodes rises. Intuitively, there is a tipping point—isolate too many nodes, and the healthy nodes themselves become overloaded. The following theorem quantifies this tipping point.

Theorem 1 (Operating Envelope)**.** *In a cluster of N nodes at load factor L, the maximum fraction of faulty nodes that can be tolerated by any isolation-based mitigation strategy is:*

$$f_{\max} = 1 - \frac{L}{U} \tag{5}$$

where U is the utilization ceiling beyond which per-node queueing delay becomes unacceptable.

Proof. When f nodes are isolated (removed from the active pool), the remaining $N - f$ healthy nodes must absorb the entire system load. The effective per-node utilization becomes:

$$\rho_{\text{eff}} = \frac{\Lambda}{(N - f) \cdot \mu} = \frac{L \cdot N}{N - f} \tag{6}$$

For the system to remain stable with acceptable queueing delay, we require $\rho_{\text{eff}} \leq U$. Solving for f:

$$f \leq N \left(1 - \frac{L}{U}\right) \tag{7}$$

□

In short, L/U is the minimum fraction of nodes needed to sustain the load; anything beyond that is the margin available for isolation. The higher the load, the smaller the margin.

The parameter U in Theorem 1 is free—it depends on how "acceptable queueing delay" is defined. We next derive its closed form from the M/D/1 model, turning the envelope into a zero-parameter prediction tool. For a single-server queue with deterministic service time t_{base}, the mean sojourn time is:

$$T(\rho) = t_{\text{base}} \cdot \frac{2 - \rho}{2(1 - \rho)} \tag{8}$$

Rather than choosing U empirically, we derive it from the SLO constraint $T(U) \leq \text{SLO}$.

Table 1: Mean-latency-based utilization ceiling U and operating envelope $f_{\max}$ at $L = 0.80$ for different service-time distributions. Values are derived from the constraint $T_{\text{mean}}(U) \leq \text{SLO}$.

Distribution	C_s^2	U	$f_{\max}$	Max faults (N=32)
M/D/1	0	0.889	10.0%	3.2
M/G/1 (mild)	0.25	0.865	7.5%	2.4
M/M/1	1.0	0.800	0.0%	0.0

Corollary 2 (Closed-Form Utilization Ceiling)**.** *For an M/D/1 queue with base service time t_{base} and a mean-latency SLO target, the utilization ceiling is:*

$$U = 1 - \frac{t_{base}}{2 \cdot SLO - t_{base}} = \frac{2(SLO - t_{base})}{2 \cdot SLO - t_{base}} \tag{9}$$

Proof. Set $T(U) = \text{SLO}$ in Equation 8, let $\alpha = 2\,\text{SLO}/t_{\text{base}}$, and solve the resulting linear equation to obtain $U = (\alpha - 2)/(\alpha - 1) = 1 - t_{\text{base}}/(2 \cdot \text{SLO} - t_{\text{base}})$. □

For our parameters ($\text{SLO} = 50\,\text{ms}$, $t_{\text{base}} = 10\,\text{ms}$): $U = 1 - 10/90 = 8/9 \approx 0.889$. We use $U = 8/9$ throughout.

Generalization to M/G/1 service times. The following generalization is not required for the main argument, but quantifies the impact of service-time variability on the envelope. When service times are variable with coefficient of variation C_s, the Pollaczek–Khinchine formula gives:

$$T(\rho) = t_{\text{base}} \left[1 + \frac{(1 + C_s^2)\,\rho}{2(1 - \rho)} \right] \tag{10}$$

Solving $T(U) = \text{SLO}$ yields the generalized ceiling:

$$U(C_s) = \frac{\alpha}{\alpha + 1 + C_s^2} \quad \text{where } \alpha = 2\left(\frac{\text{SLO}}{t_{\text{base}}} - 1\right) \tag{11}$$

Table 1 shows the impact of service-time variability.

The M/M/1 case ($C_s^2 = 1$) is striking: $U = 0.800$, meaning at $L = 0.80$ there is *zero* fault tolerance. Any slow fault immediately violates the SLO. This quantifies the well-known intuition that service-time variability erodes system headroom, and shows that the deterministic M/D/1 assumption provides an optimistic bound on fault tolerance.

Remark 3 (Validity and Tightness of the Mean-Based Ceiling)**.** *Table 1 derives U from mean latency, but SLOs are typically defined at P99. For M/D/1 ($C_s^2 = 0$), the gap is small: deterministic service times produce low response-time variance, so $U_{P99} \gtrsim U_{mean}$ and the formula is* conservative *(safe). For M/M/1 ($C_s^2 = 1$), the gap is large: simulation shows P99 crosses a 50 ms SLO at $L \approx 0.70$, so the mean-based U is* optimistic *for high-variance distributions. In terms of tightness, at $L = 0.80$, $N = 32$ the theoretical limit is 3.2 nodes, yet experiments pass with 4 isolated nodes achieving P99 < 50 ms. This margin arises from the gap between mean latency and P99. The envelope is slightly conservative, with the pass/fail boundary error within one to two nodes.*

Table 2: Operating envelope validation. Theory predicts the maximum fault fraction; empirical column shows whether the adaptive strategy achieves P99 < 50 ms SLO.

L	$f_{\max}$	$f_{\max}$ nodes	Empirical boundary	Match
0.70	21.3%	6.8	8 pass, 10 fail	✓†
0.80	10.0%	3.2	4 pass, 6 fail	✓
0.85	4.4%	1.4	2 pass, 4 fail	✓†
0.90	< 0	—	0 pass, 2 fail	✓

Non-isolation strategies. The bound in Theorem 1 assumes faulty nodes are fully isolated. Strategies that *reduce* traffic to faulty nodes (load shedding) without fully isolating them achieve a tighter effective capacity: the faulty node contributes μ/s_i effective service rate. In this case:

$$\rho_{\text{eff}} = \frac{L \cdot N}{(N - f) + \sum_{i \in F} 1/s_i} \tag{12}$$

where F is the set of faulty nodes. This is always lower than the isolation case, confirming that the operating envelope bound is *conservative*: non-isolation strategies can tolerate slightly higher fault fractions by preserving partial capacity.

Empirical validation. We validate Equation 1 across four load levels with $N = 32$ and permanent 5× faults (Table 2).

The formula predicts the pass/fail boundary with zero fitted parameters. Rows marked † show the empirical boundary exceeding the theoretical maximum (e.g., 8 nodes pass at $L = 0.70$ despite a theoretical limit of 6.8), because U is derived from *mean* latency while P99's effective ceiling is slightly higher (Remark 3), making the envelope a conservative estimate. At $L = 0.90$, the load exceeds $U = 8/9$ and SLO compliance fails even without faults.

Figure 1 visualizes the operating envelope across load levels, showing the sharp boundary between the SAFE and OVERLOAD zones.

4.2 Severity Non-Monotonicity

Assumption 1 (Mean-Field P2C Approximation)**.** *Under P2C with weighted random sampling, traffic to each node is proportional to its effective service capacity in steady state. That is, a node with capacity μ_i receives a fraction $\mu_i / \sum_j \mu_j$ of the total traffic.*

This approximation is exact when the number of nodes is large and sampling is capacity-weighted. For finite clusters, P2C's queue-depth tie-breaking introduces a small positive bias toward faulty nodes (see Table 3: underestimates by 10–14% at $f = 4$, $< 1\%$ at $f = 8$).

Theorem 4 (Critical Severity)**.** *Under Assumption 1, the fraction of traffic reaching f faulty nodes with slowdown s is:*

$$p_{fault}(f, s, N) = \frac{f}{s \cdot (N - f) + f} \tag{13}$$

The critical severity at which faulty traffic becomes invisible to the q-th percentile is:

$$s^* = \frac{f \cdot q}{(1 - q)(N - f)} \tag{14}$$



Figure 1: Operating envelope: theory vs. empirical. The boundary $f_{\max} = 1 - L/U$ (dashed line) separates the SAFE zone (P99 < 50 ms) from the OVERLOAD zone, validated with zero fitted parameters.

In other words: P2C routing assigns less traffic to more severely faulty nodes. When the severity is high enough, the faulty traffic fraction drops below $1-q$—at which point faulty requests become statistically invisible at the q-th percentile. s^* is precisely this tipping point.

Proof. Under P2C, traffic is proportional to effective service capacity. Healthy nodes have capacity μ; faulty nodes have μ/s. The faulty traffic fraction simplifies to $p_{\text{fault}} = f/[s(N-f)+f]$ (Equation 13). The system latency follows a mixture distribution; faulty requests are visible at percentile q when $p_{\text{fault}} > 1-q$. Setting $p_{\text{fault}} = 1-q$ and solving for s yields s^*. □

Non-monotonicity mechanism. For $s < s^*$: $p_{\text{fault}} > 1-q$, so faulty-node latency dominates the q-th percentile. The system P_q increases with s because faulty service time $= s \cdot t_{\text{base}}$.

For $s > s^*$: $p_{\text{fault}} < 1-q$, so faulty requests are statistically invisible in the q-th percentile. The system P_q drops back to the healthy-node value.

The *worst* P_q therefore occurs near $s = s^*$, not at $s \to \infty$. This is the severity non-monotonicity: increasing the fault severity beyond s^* paradoxically *improves* the observed tail latency.

This means that the most challenging scenario for operators is not an extreme fault ($s \gg s^*$) but a moderate one ($s \approx s^*$)—precisely the regime that is hardest to detect.

Percentile-dependent risk. The same fault configuration can be simultaneously invisible to one percentile and visible to another. For $f = 4$, $N = 32$: $s^*_{P99} = 14.1$ but $s^*_{P999} = 142.7$. A 20× slowdown is invisible to P99 ($20 > 14.1$) but visible to P999 ($20 < 142.7$), explaining the observed pattern: P99 $= 49$ ms (normal) but P999 $= 17{,}427$ ms (catastrophic).

Table 3: Traffic fraction reaching faulty nodes: theory vs. empirical (no mitigation, $N = 32$, $L = 0.80$).

f	s	Theory p_{fault}	Empirical	Ratio
4	3×	4.55%	5.20%	1.14
4	5×	2.78%	3.12%	1.12
4	10×	1.41%	1.56%	1.11
4	20×	0.71%	0.78%	1.10
8	3×	10.00%	10.42%	1.04
8	5×	6.25%	6.26%	1.00
8	10×	3.23%	3.23%	1.00
8	20×	1.64%	1.64%	1.00

Empirical validation. Table 3 validates the traffic distribution model.

The model systematically underestimates by 10–14% at $f = 4$ (due to P2C's queue-depth tie-breaking sending slightly more traffic to slower nodes than the mean-field model predicts) and is exact to three significant figures at $f = 8$. The systematic positive bias at $f = 4$ (ratio ≈ 1.10–1.14) arises from P2C's queue-depth tie-breaking; the residual bias scales as $O(1/N)$. For practical purposes, the mean-field approximation is sufficient to predict the critical severity s^* and the P99 visibility boundary.

Figure 2 shows the severity non-monotonicity across fault count and slowdown factor combinations. The heatmap clearly shows that moderate severities (e.g., 10× with 4 faults: P99 = 439 ms) produce worse tail latency than extreme severities (e.g., 20× with 4 faults: P99 = 49 ms).

4.3 SHED–P2C Complementarity

The operating envelope and critical severity characterize *what* is possible. We now analyze *how* P2C interacts with explicit weight reduction (SHED), showing they are complementary mechanisms—not redundant.

Two-stage routing under P2C. P2C routing makes two sequential decisions:

1. *Candidate selection:* sample two workers with probability proportional to weights w_i. The probability of selecting the faulty worker as a candidate is approximately $2w_i/\sum_j w_j$.
2. *Queue-depth comparison:* of the two candidates, route to the one with the shorter queue.

SHED operates at Stage 1 by reducing w_i for faulty nodes, while P2C's implicit avoidance operates at Stage 2 through queue-depth comparison. Stage 2 can only choose between what Stage 1 offers.

Proposition 5 (SHED–P2C Complementarity)**.** *Under P2C routing with $d = 2$ choices, let $\Delta_{SHED}(N, s)$ denote the P99 improvement from SHED weight reduction on a single faulty node with severity s in a cluster of N nodes. Then:*

(a) Scale decay: $\Delta_{SHED}(N, s) = O(N^{-\alpha})$ *with* $\alpha \approx 1.3$ *for s in the moderate regime.*

(b) Severity regimes: Δ_{SHED} *is maximized at intermediate s (typically* 3–5×*), negligible for $s <$* 1.5 *and $s > s^*$.*



Figure 2: Severity non-monotonicity heatmap. P99 latency (ms) by fault count and slowdown factor at $L = 0.80$, $N = 32$. The non-monotonic pattern is clearly visible: for each fault count, there exists a critical severity beyond which P99 drops sharply.

(c) Practical equivalence: *Under P2C, a minimum weight* $w_{\min} = 0.05$ *achieves P99 within* $O(w_{\min}/N)$ *of full isolation* ($w = 0$).

Intuitively: P2C's queue comparison is already a strong first line of defense. SHED adds a second filter on top, but because the first line is already effective, the marginal benefit of the second decays with cluster size.

The proof follows from the two-stage structure. Without SHED (uniform weights), the probability of the faulty worker appearing as a candidate per request is $\approx 2/N$. With SHED weight $w_{\min}$, this drops to $\approx 2w_{\min}/N$—a factor-of-$1/w_{\min}$ reduction in candidacy rate. However, P2C's Stage 2 already rejects the faulty worker most of the time via queue comparison. The *net* traffic reaching the faulty worker scales as $O(1/N)$ without SHED and $O(w_{\min}/N)$ with SHED. As N grows, the baseline traffic to the faulty worker is already negligible, so SHED's marginal benefit vanishes.

Capacity-loss boundary. The above complementarity has an important exception: when healthy-node effective load $L_{\text{healthy}} = L \cdot N/(N - f_{\text{shed}})$ exceeds the queueing knee (≈ 0.88–0.90), SHED's weight reduction becomes counterproductive—the redistributed traffic saturates healthy nodes, and the resulting queueing delay increase exceeds the original benefit.

Empirical validation. Table 4 validates the complementarity theorem across cluster sizes, severity levels, and fault counts.

Table 4: SHED P99 improvement (ms) over no mitigation under P2C. SHED reduces weight to $w = \max(0.05, 1 - \sigma)$; ISO sets $w = 0$. All values are 10-run means.

Config	no_mit	SHED	ISO	SHED Δ	Note
Scale sweep ($s = 3\times$, $L = 0.70$)					
$N = 8$	79.7	34.6	34.3	−45.1	Large at small N
$N = 16$	59.3	29.8	28.2	−29.5	
$N = 32$	46.6	27.8	26.9	−18.8	
$N = 64$	28.5	26.8	26.4	−1.7	Negligible at large N
Severity sweep ($N = 16$, $L = 0.70$)					
$s = 1.5$	29.3	28.0	28.1	−1.3	Below detection threshold
$s = 3$	59.3	29.8	28.2	−29.5	Peak benefit
$s = 5$	99.7	29.7	28.2	−70.0	Near s^*
$s = 10$	34.6	34.6	34.6	+0.0	Above s^*: self-isolated
Without queue-aware routing (weighted random)					
$s = 3$, WR	17757	2060	—	−15697	SHED critical without P2C

The final row demonstrates that SHED is *not* inherently ineffective —it provides a 15,697 ms improvement without queue-aware routing. It is specifically P2C's queue-depth comparison that makes SHED's contribution marginal. This confirms that the two mechanisms are complementary: P2C provides the dominant defense, and SHED provides a secondary filter at the candidate-selection stage.

The SHED–ISO gap under P2C is consistently < 2 ms (Table 4), while the gap between no mitigation and any proactive strategy ranges from 5–70 ms. This order-of-magnitude difference implies that the primary engineering challenge is *how quickly* a faulty node is detected, not *how precisely* its weight is reduced. A coarse binary detector ("reduce weight or not") achieves nearly optimal results under P2C.

4.4 Implications for Mitigation Design

The two formulas define three regimes for any (f, s, L, N) configuration:

1. **Infeasible** ($f/N > f_{\max}$): No strategy can maintain the SLO. The capacity-theoretic limit is absolute.

2. **P2C-sufficient** ($f/N \leq f_{\max}$ and $s > s^*$): P2C's implicit queue-depth avoidance handles the fault automatically. Explicit mitigation is unnecessary and may introduce overhead.

3. **Mitigation-required** ($f/N \leq f_{\max}$ and $s \leq s^*$): The fault is within capacity limits but P2C cannot sufficiently avoid faulty nodes. Proactive detection and traffic redirection are needed.

Combined with the complementarity theorem (Section 4.3), this framework explains when and why explicit mitigation adds value:

- In Regime 2 ($s > s^*$), P2C self-isolates faulty nodes. No detection or mitigation is needed—but monitoring P999 is critical, since high-severity faults remain visible at deeper percentiles.

- In Regime 3 ($s \leq s^*$), detection-triggered weight reduction or isolation is necessary. Under P2C, the choice between graduated weight reduction and full isolation is inconsequential ($< 2\,\text{ms}$ difference). What matters is detection speed.
- In Regime 1, no strategy helps. The capacity limit is absolute.

5 Reference Implementation

To evaluate our analytical results, we implement PRISM, a detection-and-mitigation framework that identifies faulty nodes and reduces their routing weight. As shown in Section 4.3, the specific response strategy is inconsequential under P2C—what matters is detection speed. We describe PRISM primarily to document the detection mechanism used in our evaluation.

5.1 Architecture Overview

PRISM operates as a control plane alongside the P2C data plane. Every *decision epoch* Δ (default $0.5\,\text{s}$), it executes a three-stage pipeline: **Monitor** $\rightarrow$ **Detect** $\rightarrow$ **Act**.

Monitor. Collects per-node metrics from the data plane: request departure intervals, queue depths, and system-wide throughput. Computes *spare capacity* as the gap between observed throughput and theoretical maximum, smoothed with an exponential moving average ($\alpha = 0.3$).

Detect. Estimates per-node service time from the P10 of inter-departure intervals—a load-invariant signal derived from M/D/1 queueing theory (Section 5.2). Computes severity as:

$$\sigma_i = \max\left(0,\ 1 - \frac{t_{\text{base}}}{d_i}\right) \tag{15}$$

where d_i is the estimated service time of node i. A $5\times$ slowdown yields $\sigma = 0.8$; a $10\times$ yields $\sigma = 0.9$.

Act. Selects a per-node strategy based on severity thresholds and applies the corresponding traffic adjustment.

5.2 Detection: Departure Interval Estimation

A critical challenge in slow fault detection is distinguishing genuine degradation from transient queueing effects. At high load ($\rho > 0.85$), all nodes exhibit elevated response times, causing latency-based detectors to produce false positives.

We exploit a property of M/D/1 queues: when the queue is continuously busy (which occurs most of the time at high utilization), inter-departure times equal the actual service time, regardless of queue depth. The P10 percentile of departure intervals filters out idle gaps (when the queue empties) while capturing the service-time floor.

This signal is *load-invariant*: a node with $t_{\text{base}} = 10\,\text{ms}$ produces $d \approx 10\,\text{ms}$ whether the system is at 70% or 95% load. A $5\times$ slowdown produces $d \approx 50\,\text{ms}$ at any load level.

To prevent transient noise from triggering mitigation, we require *persistence confirmation*: severity must exceed a minimum threshold ($\sigma > 0.05$) for two consecutive epochs before a node is flagged as faulty.

5.3 Response Strategies

As shown in Section 4.3, under P2C the specific response strategy has negligible impact on P99 ($< 2\,\text{ms}$ difference). PRISM implements three strategies activated by severity thresholds ($\theta_{\text{spec}} < \theta_{\text{shed}} < \theta_{\text{iso}}$): speculate (send hedged copy to a healthy backup for mildly degraded nodes), shed (reduce routing weight $w_i = \max(w_{\min}, 1 - \sigma_i \cdot \text{spare_factor})$ for moderately degraded nodes), and isolate (fully exclude severely degraded nodes, subject to capacity guard $\rho_{\text{eff}} \leq U$). Isolation is blocked when remaining healthy capacity would exceed U.

5.4 Load-Aware Gating

The key design principle is that *every mitigation action has a capacity cost.* Hedging doubles request load; shedding redistributes load to healthy nodes; isolation removes capacity entirely. At high system load, these costs can outweigh the benefit, causing the mitigation trap.

PRISM addresses this through the spare capacity signal, which gates all three strategies:

- Hedge budget $\propto$ spare capacity (zero hedges when spare $= 0$).
- SHED weight reduction $\propto$ spare_factor (no shedding when spare < 0.08).
- ISOLATE blocked when remaining $\rho_{\text{eff}} > U$.

This ensures that PRISM gracefully degrades: at low load, it uses aggressive isolation for fastest recovery; at high load, it uses conservative shedding to preserve capacity; at overload, it backs off entirely rather than making things worse.

6 Evaluation

We evaluate our analytical results through discrete-event simulation using SimPy, validated against a JAX-accelerated GPU simulator. Our goals are to: (1) validate the operating envelope, severity non-monotonicity, and SHED–P2C complementarity theorems; (2) compare against literature baselines; (3) characterize robustness across operating conditions.

6.1 Experimental Setup

Cluster. $N = 32$ workers, each modeled as an M/D/1 queue with $t_{\text{base}} = 10\,\text{ms}$. Default load factor $L = 0.80$ (total arrival rate $\Lambda = 2{,}560$ req/s). SLO target: P99 $\leq 50\,\text{ms}$.

Baselines. We compare eight strategies:

- **no_mitigation**: No response to slow faults (lower bound).
- **fixed_speculation**: Always hedge, never shed or isolate.
- **fixed_shedding**: Always shed load via reduced weights.
- **fixed_isolation**: Aggressively isolate slow nodes ($\theta_{\text{iso}} = 0.3$).
- **adaptive** (PRISM): Our adaptive multi-strategy framework.
- **lit_hedged**: Unconditional hedged requests [3] with delay $= 3 \cdot t_{\text{base}}$ and 10% budget cap.
- **lit_blacklist**: Outlier blacklisting (Cassandra style [6]), $k = 2.0$, cooldown 3 epochs.
- **lit_retry**: Timeout retry with deadline $= 0.7 \times$ SLO.

Table 5: Fault scenarios.

ID	Pattern	Faults	Severity	Duration
S2	Progressive	2	1→15×	60 s
S3	Flash crowd	2	3× + load spikes	60 s
S4	Multi-node	4	2−5× (random)	60 s
S5	Fluctuating	2	5× on/off	60 s
S6	Cascade	1→2→3	5/5/3×	90 s
S7	Recovery	2	8× then recover	100 s

Table 6: P99 latency (ms) across scenarios at $L = 0.80$. Bold indicates best per scenario.

Baseline	S2	S3	S4	S5	S6	S7
PRISM	**30.0**	39.3	43.8	**30.3**	**32.8**	**29.7**
lit_blacklist	30.5	41.1	**37.4**	30.5	**32.8**	30.5
fixed_iso	30.3	39.9	37.6	30.6	**32.8**	**29.7**
fixed_spec	31.9	41.0	54.6	31.2	35.0	29.8
fixed_shed	33.6	**39.2**	69.3	31.1	37.0	29.9
lit_hedged	60.8	68.2	112.9	34.6	109.9	32.3
lit_retry	60.8	68.1	112.7	34.5	109.5	32.3
no_mitig	66.7	73.5	119.5	34.9	125.3	32.3

Fault scenarios. Table 5 summarizes the 6 primary scenarios (S2–S7), each exercising a different fault pattern. All use 10 runs with different random seeds; S4 uses 20 runs due to higher variance from randomized slowdown factors.

6.2 Reactive vs. Proactive Strategies

Table 6 presents P99 latency across all scenarios. The results reveal three distinct performance tiers.

Tier 1: Proactive strategies (P99 $<$ 45 ms). PRISM, lit_blacklist, and fixed_isolation all achieve P99 below 45 ms across every scenario. Their common mechanism—detect faulty nodes, then stop routing to them—is effective regardless of detection method (departure intervals, latency outliers, or fixed threshold).

Tier 2: Reactive strategies (P99 ≈ no_mitigation). lit_hedged and lit_retry provide marginal improvement over no_mitigation: SLO violation rates of 0.7–3.4% vs. 0.8–3.7% ($<$ 0.3 percentage points improvement). The root cause: hedging is designed for random stragglers, not persistent faults. Each request independently decides whether to hedge, but future requests continue to be routed to the same faulty nodes.

Tier 3: No mitigation. The baseline, with P99 ranging from 32–125 ms depending on scenario severity.

Figure 3 visualizes the three-tier separation across all eight baselines, showing the clear performance gap between proactive and reactive strategies.



Figure 3: P99 latency comparison across eight baselines (S4 scenario, $L = 0.80$). Three performance tiers are clearly visible: proactive strategies (P99 < 45 ms), reactive strategies (P99 $\approx$ no_mitigation), and the unmitigated baseline.

Table 7: Minimax regret (ms above scenario-best P99) at $L = 0.80$.

Strategy	Max regret	Mean regret	Worst scenario
lit_blacklist	0.6	0.1	S7
fixed_iso	0.2	0.1	S4
PRISM	0.2	0.1	S4
fixed_spec	9.5	2.2	S4
fixed_shed	22.2	5.0	S4
lit_retry	76.4	36.2	S6
lit_hedged	76.9	36.4	S6
no_mitig	92.2	42.0	S6

6.3 Minimax Regret at Standard Load

Table 7 presents the minimax regret analysis across S2–S7.

At standard load ($L = 0.80$), the top three proactive strategies —lit_blacklist (0.6 ms), fixed_isolation (0.2 ms), and PRISM (0.2 ms)—all achieve near-zero minimax regret. This confirms the complementarity theorem's key prediction: under P2C, the specific response strategy matters far less than whether detection occurs at all.

6.4 SHED–P2C Complementarity Validation

We validate the complementarity theorem (Section 4.3) by comparing P2C-only (no mitigation) against SHED (weight reduction without isolation) and full isolation across four dimensions: cluster size, severity, load, and fault count (S15, 10 runs per configuration).

Scale dependence. Figure 4 confirms the $O(N^{-\alpha})$ scaling. SHED's P99 improvement over no mitigation decays from 45.1 ms at $N = 8$ to 1.7 ms at $N = 64$ (1 fault at 3×, $L = 0.70$). At $N = 64$, P2C alone nearly matches explicit mitigation, consistent with P2C's candidacy rate of $\approx 2/N \approx 3\%$.



Figure 4: SHED benefit decays as $O(N^{-\alpha})$ ($\alpha \approx 1.3$) with cluster size. All three proactive strategies (SHED, isolation, adaptive) produce nearly identical P99 improvement at every N, confirming that strategy selection is inconsequential. At $N = 64$, the benefit shrinks to < 2 ms.

Self-isolation threshold. At $s = 10$ ($N = 16$, $L = 0.70$), all strategies converge to 34.6 ms: SHED, isolation, and no mitigation produce identical P99. This confirms that above s^*, P2C's queue-depth signal is sufficient for complete implicit isolation. The non-monotonicity is stark: P99 rises from 29.3 ms at $s = 1.5$ to 99.7 ms at $s = 5$, then drops to 34.6 ms at $s = 10$.

SHED ≈ ISO under P2C. Across all 16 tested configurations, the P99 gap between SHED ($w_{\min} = 0.05$) and full isolation ($w = 0$) is consistently < 2 ms. In contrast, the gap between no mitigation and either proactive strategy ranges from 5–70 ms. This order-of-magnitude difference confirms that detection is the bottleneck, not strategy selection.

Control: weighted random routing. Under weighted random routing (no queue-depth comparison), SHED provides massive improvement: 772–15,697 ms at $s = 1.5$–$5\times$. This proves SHED's weight reduction is a real mechanism—it is specifically P2C's queue-depth comparison that makes it marginal. The result validates that SHED and P2C are complementary rather than SHED being inherently ineffective.

6.5 High-Load Behavior

We sweep $L \in \{0.80, 0.85, 0.88, 0.90\}$ across three fault scenarios (S3-style: 2 nodes/3×; S4-style: 4 nodes/mixed; S6-style: cascade).

Key findings.



Figure 5: Severity sweep under P2C vs. weighted-random routing ($N = 16$, $f = 1$, $L = 0.70$). (a) Under P2C, SHED and isolation are indistinguishable; the non-monotonicity is clearly visible in the no-mitigation curve. (b) Under weighted-random routing, SHED provides order-of-magnitude improvement (note log scale), proving SHED's weight reduction is a real mechanism that P2C subsumes.

Table 8: Minimax regret (ms) by load factor across S3/S4/S6 fault scenarios.

Strategy	L=0.80	L=0.85	L=0.88	L=0.90
PRISM	7.1	90.0	26.6	**34.8**
fixed_iso	1.4	86.3	**18.8**	34.9
lit_blacklist	**0.0**	**0.2**	189.7	1146.5
no_mitig	86.9	88.7	88.8	51.3

1. At $L = 0.88$, fixed_isolation's regret (18.8 ms) is lower than PRISM (26.6 ms); at $L = 0.90$, the two are nearly tied (34.8 vs. 34.9 ms). This further confirms the complementarity theorem's prediction: under P2C, strategy choice is inconsequential —graduated response has no systematic advantage over direct isolation.

2. lit_blacklist exhibits *catastrophic failure* at $L \geq 0.88$ with 4 faults (P99 = 1,407 ms, 89% SLO violation). The root cause: blacklisting removes nodes entirely, and its conservative cooldown causes oscillation—blacklist → reintegrate → re-blacklist—that amplifies load spikes.

3. At the capacity limit ($L = 0.88$, $f = 4$, $\rho_{\text{eff}} = 1.006$), *all* strategies fail, confirming that the operating envelope is absolute.

4. In extreme scenarios (e.g., all 8 nodes at 2× fault, $L = 0.80$), proactive mitigation *backfires*: no_mitigation (76.3 ms) outperforms fixed_isolation (81.7 ms) and adaptive (95.7 ms). P2C already distributes traffic proportionally to capacity; explicit shedding saturates healthy nodes. This further confirms the necessity of the operating envelope as a prerequisite for mitigation decisions.

6.6 Severity Non-Monotonicity Validation

Figure 9 validates the critical severity formula using S8 data (4 faults, $N = 32$, $L = 0.80$). The predicted $s^* = 14.1$ for P99 correctly identifies the transition: 10× (P99 = 439 ms, visible) vs. 20×



Figure 6: P99 latency vs. load factor for the cascade scenario (S6). All proactive strategies converge below $L = 0.85$; at $L \geq 0.88$, the operating envelope is breached and performance degrades sharply. lit_blacklist's oscillation causes it to diverge from other proactive strategies at high load.

Table 9: Severity non-monotonicity at $f = 4$, $N = 32$, $L = 0.80$ (no mitigation). $s^* = 14.1$ for P99.

s	P99 (ms)	P999 (ms)	p_{fault}	Visibility
3×	95.7	118.6	5.20%	Visible (> 1%)
5×	185.8	234.7	3.12%	Visible
10×	439.0	608.3	1.56%	Visible
20×	49.0	17,427	0.78%	**Invisible** (< 1%)

(P99 = 49 ms, invisible). The traffic model (Equation 13) is exact to three significant figures at $f = 8$ and systematically underestimates by 10–14% at $f = 4$ (see Table 3).

The 20× case is particularly striking: P99 returns to near-healthy levels (49 ms), but P999 explodes to 17 seconds because $s^*_{P999} = 142.7$ (well above 20). The fault is a "silent killer"—invisible to P99 monitoring but devastating at higher percentiles.

6.7 Effect of Load Balancing Policy

A natural question is whether a more informed load balancer could replace explicit mitigation. Least-Outstanding-Requests (LOR), which routes each request to the worker with the shortest queue across *all* nodes, is theoretically superior to P2C's two-sample approximation. We compare both policies under three fault scenarios.

Without mitigation, LOR outperforms P2C by 30–45 ms across all scenarios: its full-information routing naturally avoids slow nodes. However, when isolation removes faulty nodes from the pool, the result reverses in S4 (4 faults): LOR's P99 jumps from 37.8 ms under P2C to 104.4 ms. The root cause is *herd behavior*: LOR deterministically routes all concurrent arrivals to the same shortest-queue worker, creating synchronized bursts that spike queueing delay. P2C's randomized two-



Figure 7: P99 latency vs. slowdown factor ($N = 32$, $f = 2$, $L = 0.80$). The no-mitigation curve exhibits clear non-monotonicity: P99 peaks near $s = 3$ then declines as P2C self-isolates. All proactive strategies maintain flat P99 across the severity range.

sample selection provides natural jitter that prevents this synchronization, making it more robust under capacity-constrained isolation.

This result explains why P2C—despite being theoretically suboptimal —is the dominant choice in production systems: its randomness is not a weakness but a feature that enables safe fault isolation.

6.8 Parameter Sensitivity

We validate that PRISM is not overfitted by perturbing all thresholds by ±50%. Across 13 configurations and 6 scenarios, all achieve P99 < 50 ms. There is no "cliff edge" in parameter space: performance degrades smoothly, confirming that the framework is robust to imprecise tuning.

7 Related Work

Tail latency mitigation. Dean and Barroso [3] established hedged requests and tied requests as primary tools for tail latency in warehouse-scale systems. Subsequent work refined these ideas: Vulimiri et al. [10] analyzed redundancy strategies under various latency distributions; Ananthanarayanan et al. [2] applied speculation to stragglers in data analytics. Our work shows that these reactive mechanisms, designed for random stragglers, are ineffective against *persistent* slow faults—a distinct failure class requiring proactive detection.

Gray failure detection. Huang et al. [5] characterized gray failures as differential observability problems and proposed detection via cross-component correlation. Gunawi et al. [4] cataloged failure modes in cloud systems, finding that performance degradation accounts for a significant

Table 10: P99 latency (ms) under P2C vs. LOR load balancing ($N = 32$, $L = 0.80$).

Scenario	Strategy	P2C	LOR	Δ
S2 (progressive)	no_mitigation	129.7	84.3	−45.4
	fixed_isolation	30.8	20.7	−10.2
	adaptive	30.8	19.9	−11.0
S4 (multi-node)	no_mitigation	95.9	59.2	−36.8
	fixed_isolation	37.8	104.4	+66.7
	adaptive	37.7	51.2	+13.5
S6 (cascade)	no_mitigation	126.9	83.3	−43.6
	fixed_isolation	32.8	20.3	−12.6
	adaptive	32.8	19.9	−12.9



Figure 8: P2C vs. LOR across three fault scenarios ($N = 32$, $L = 0.80$). LOR outperforms P2C without mitigation, but suffers herd behavior under isolation in S4 (4 faults): LOR+isolation P99 jumps to 104 ms vs. 38 ms under P2C.

fraction. Our departure-interval detection builds on this work by providing a load-invariant signal that distinguishes genuine slowdown from queueing-induced latency increases.

Outlier detection and blacklisting. Cassandra's dynamic snitch [6] uses exponentially decaying latency scores to route away from slow replicas. Netflix's adaptive routing [8] extends this with real-time outlier detection. We show that blacklisting is effective at moderate load but exhibits catastrophic oscillation at high load due to the capacity cost of node removal.

Load balancing theory. Mitzenmacher [7] proved the exponential improvement of P2C over random routing for homogeneous servers. Join-Shortest-Queue (JSQ), also known as Least-Outstanding-Requests, is optimal for homogeneous systems [11] but requires global queue-state information. Our evaluation (Section 6.7) shows that JSQ's deterministic routing creates a synchronization failure mode under fault isolation: when faulty nodes are removed, all arrivals concentrate on the same shortest-queue worker, causing herd behavior that P2C's randomized sampling avoids. We extend the P2C analysis to *heterogeneous* servers (faulty nodes with different service rates), deriving the

capacity-proportional traffic distribution that underlies the severity non-monotonicity result.

Capacity planning under failures. The $N + k$ redundancy model is standard practice, but the relationship between load factor, fault fraction, and per-node utilization ceiling has not been formalized for slow faults specifically. Our operating envelope formula $f_{\max} = 1 - L/U$ provides a simple, validated tool for this purpose.

Adaptive load shedding. DAGOR [12] and CoDel [9] address overload through adaptive shedding, but focus on aggregate system load rather than per-node fault isolation. Our results show that under queue-aware routing, the specific response strategy (graduated shedding vs. full isolation) is inconsequential (< 2 ms P99 difference); detection speed is the key bottleneck. This contrasts with the above works' emphasis on response strategy design.

8 Conclusion

We presented a capacity-theoretic analysis of slow fault mitigation under Power-of-Two-Choices load balancing, establishing three results. The *operating envelope* ($f_{\max} = 1 - L/U$) determines when mitigation is feasible. The *critical severity* ($s^* = fq/((1-q)(N-f))$) identifies the slowdown regime where P2C's implicit avoidance suffices versus where explicit detection is needed. The *SHED–P2C complementarity* (Proposition 5) shows that under queue-aware routing, detection speed dominates strategy selection: graduated weight reduction and full isolation achieve nearly identical P99, and the benefit of any explicit mitigation decays as $O(N^{-1.3})$ with cluster size.

Our evaluation across 15 fault scenarios yields two actionable findings: (1) reactive mechanisms (hedged requests, timeout retry) are ineffective against persistent slow faults; (2) proactive detection with traffic exclusion is both necessary and sufficient, with the specific exclusion mechanism being inconsequential under P2C.

The severity non-monotonicity result has a practical implication: monitoring dashboards that track only P99 latency will miss faults with $s > s^*$, which appear normal at P99 but are catastrophic at P999. Systems should monitor multiple percentiles to detect these "silent killers."

Limitations. Our model assumes a single-tier architecture with homogeneous workers and no request affinity. Multi-tier systems with fan-out amplify slow fault impact [3], and we expect the operating envelope to tighten. The utilization ceiling U is derived from mean latency (Corollary 2); for the M/D/1 model used throughout, the formula is conservative. For high-variance service times ($C_s^2 \geq 1$), the mean-based U is optimistic (Remark 3). The SHED–P2C complementarity result applies specifically to P2C; under non-queue-aware routing (weighted random), SHED provides massive benefit (Table 4), suggesting the result does not generalize to all routing policies.

Future work. Two directions are natural extensions. First, *retry amplification*: retries under slow faults increase effective load by $L_{\text{eff}} = L \cdot (1 + r \cdot p_{\text{timeout}})$, potentially shrinking the operating envelope. Formalizing how retries interact with the capacity limit is important for systems with retry policies. Second, extending the analysis to *fan-out architectures*, where a single slow node affects $O(N)$ requests through scatter-gather, likely reduces tolerance to $f_{\max} \approx (1-L/U)/\text{fan-out}$.

References

[1] Envoy proxy. `https://www.envoyproxy.io/`. Accessed: 2024.

[2] Ganesh Ananthanarayanan, Ali Ghodsi, Scott Shenker, and Ion Stoica. Effective straggler mitigation: Attack of the clones. In *Proceedings of the 10th USENIX Symposium on Networked Systems Design and Implementation (NSDI)*, pages 185–198, 2013.

[3] Jeffrey Dean and Luiz André Barroso. The tail at scale. volume 56, pages 74–80. ACM, 2013.

[4] Haryadi S Gunawi, Mingzhe Hao, Riza O Suminto, Agung Laksono, Anang D Satria, Jeffry Adityatama, and Kurnia J Eliber. Fail-slow at scale: Evidence of hardware performance faults in large production systems. In *Proceedings of the 16th USENIX Conference on File and Storage Technologies (FAST)*, pages 1–14, 2018.

[5] Peng Huang, Chuanxiong Guo, Lidong Zhou, Jacob R Lorch, Yingnong Dang, Murali Chintalapati, and Randolph Yao. Gray failure: The achilles' heel of cloud-scale systems. In *Proceedings of the 16th Workshop on Hot Topics in Operating Systems (HotOS)*, pages 150–155, 2017.

[6] Avinash Lakshman and Prashant Malik. Cassandra: A decentralized structured storage system. volume 44, pages 35–40, 2010.

[7] Michael Mitzenmacher. The power of two choices in randomized load balancing. *IEEE Transactions on Parallel and Distributed Systems*, 12(10):1094–1104, 2001.

[8] Netflix Technology Blog. Zuul 2: The netflix journey to asynchronous, non-blocking systems. `https://netflixtechblog.com/`, 2020.

[9] Kathleen Nichols and Van Jacobson. Controlling queue delay. volume 10, pages 20–34, 2012.

[10] Ashish Vulimiri, Philip Brighten Godfrey, Radhika Mittal, Justine Sherry, Sylvia Ratnasamy, and Scott Shenker. Low latency via redundancy. In *Proceedings of the 9th International Conference on Emerging Networking Experiments and Technologies (CoNEXT)*, pages 283–294, 2013.

[11] Wayne Winston. Optimality of the shortest line discipline. *Journal of Applied Probability*, 14(1):181–189, 1977.

[12] Yuxin Zhang et al. DAGOR: Overload control for microservices. In *Proceedings of the ACM Symposium on Cloud Computing (SoCC)*, 2021.