
Machine Learning

Answer Sheet for Homework 7

Da-Min HUANG

R04942045

Graduate Institute of Communication Engineering, National Taiwan University

January 6, 2016

Problem 1

Set $\mu_- = 1 - \mu_+$, we have

$$1 - \mu_+^2 - \mu_-^2 = 1 - \mu_+^2 - (1 - \mu_+)^2 = (1 - \mu_+)(1 + \mu_+) - (1 - \mu_+)^2 \quad (1)$$

$$= 2\mu_+(1 - \mu_+) = -2\mu_+^2 + 2\mu_+ = -2\left(\mu_+ - \frac{1}{2}\right)^2 + \frac{1}{2} \quad (2)$$

$$\leq \frac{1}{2} \quad (3)$$

Hence, if $\mu_+ = 1/2 \in [0, 1]$, then the maximum value of Gini index is $1/2$.

□

Problem 2

The normalized Gini index is

$$\frac{(1 - \mu_+^2 - \mu_-^2)}{\left(\frac{1}{2}\right)} = 2(1 - \mu_+^2 - \mu_-^2) \quad (4)$$

The squared error can be rewritten as

$$\mu_+(1 - (\mu_+ - \mu_-))^2 + \mu_-(-1 - (\mu_+ - \mu_-))^2 = 4\mu_+(1 - \mu_+)^2 + 4\mu_+^2(1 - \mu_+) \quad (5)$$

$$= 4\mu_+(1 - \mu_+) \leq 4 \times \frac{1}{4} = 1 \quad (6)$$

Hence the normalized squared error is

$$4\mu_+(1 - \mu_+) = 2(2\mu_+(1 - \mu_+)) = 2((1 - \mu_+)(1 + \mu_+) - (1 - \mu_+)^2) \quad (7)$$

$$= 2(1 - \mu_+^2 - \mu_-^2) \quad (8)$$

which is equal to normalized Gini index.

□

Problem 3

The probability of one example not sampled is

$$\left(1 - \frac{1}{N}\right)^{pN} = \frac{1}{\left(\frac{N}{N-1}\right)^{pN}} = \frac{1}{\left(1 + \frac{1}{N-1}\right)^{pN}} = \left(\frac{1}{\left(1 + \frac{1}{N-1}\right)^N}\right)^p \quad (9)$$

As $N \rightarrow \infty$, we have

$$\lim_{N \rightarrow \infty} \left(\frac{1}{\left(1 + \frac{1}{N-1}\right)^N}\right)^p = \left(\lim_{N \rightarrow \infty} \frac{1}{\left(1 + \frac{1}{N-1}\right)^N}\right)^p = \left(\frac{1}{e}\right)^p = e^{-p} \quad (10)$$

So there approximately $e^{-p} \cdot N$ of the examples not sampled.

□

Problem 4

Since $G = \text{Uniform}(\{g_k\}_{k=1}^3)$, so if at least two of $\{g_k\}_{k=1}^3$ are wrong, then G outputs wrong result. Let $\{E_k\}_{k=1}^3$ be the set of examples that g_k got wrong results. Apparently $|E_3| > |E_2| > |E_1|$ and $|E_1| + |E_2| > |E_3|$. So

1. Maximum of $E_{\text{out}}(G)$ happens at $E_3 \subset (E_1 \cup E_2)$. Then G outputs wrong result in the region of E_3 with $E_{\text{out}}(G) = 0.35$.
2. Minimum of $E_{\text{out}}(G)$ happens at $E_i \cap E_j = \phi$, $i \neq j$ and $1 \leq i, j \leq 3$ with $i, j \in \mathbb{N}$. Then G always outputs the correct result since $(E_1 \cup E_2 \cup E_3) \subset \{\text{all examples}\}$.

Hence, $0 \leq E_{\text{out}}(G) \leq 0.35$.

□

Problem 5

☐

Problem 6

☐

Problem 7

☐

Problem 8

☐

Problem 9

☐

Problem 10

☐

Problem 11

☐

Problem 12

☐

Problem 13

☐

Problem 14

☐

Problem 15

☐

Problem 16

☐

Problem 17

☐

Problem 18

☐

Problem 19

☐

Problem 20

☐

Reference

- [1] Lecture Notes by Hsuan-Tien LIN, Department of Computer Science and Information Engineering, National Taiwan University, Taipei 106, Taiwan.