



Improving Generative Flow Networks with Path Regularization

Anh Do, Duy Dinh, Tan Nguyen, Khuong Nguyen, Stanley Osher, Nhat Ho University of Texas, Austin

University of California, Los Angeles

FPT Software AI Center

Fanmeng Wang

2023-6-21

Outline

- > Introduction
- ➤ Background: GFlowNets & Optimal Transport Distance
- ➤ Method: Path Regularization via Optimal Transport
- > Experiment
- > Conclusion




- ➤ Background: GFlowNets & Optimal Transport Distance
- > Method: Path Regularization via Optimal Transport
- > Experiment
- Conclusion







- ➤ Generative Flow Networks (GFlowNets) are recently proposed models for learning stochastic policies that generate compositional objects by sequences of actions with the probability proportional to a given reward function.
- The central problems of GFlowNets are how to improve **exploration** and **generalization**.
- In this paper, we propose to train the GFlowNets with an additional **path** regularization via OT to deal with above problems.






- ➤ Background: GFlowNets & Optimal Transport Distance
- > Method: Path Regularization via Optimal Transport
- > Experiment
- Conclusion



■ GFlowNets: some basic concepts

Compositional Space X, where each object $x \in X$ can be constructed from the source state s_0 and ends in the final state s_f by taking a sequence of discrete actions from the action space A (e.g. a molecule can generated fragment by fragment).



A directed acyclic graph G

node -> state

edge -> action

 \triangleright A complete trajectory τ , which is a sequence of transitions from s_0 to s_f .


$$\tau = (s_0 \to s_1 \to \dots \to s_n = x \to s_f)$$

^{*} Bengio E, Jain M, Korablyov M, et al. Flow network based generative models for non-iterative diverse candidate generation[J]. Advances in Neural Information Processing Systems, 2021, 34: 27381-27394.



■ GFlowNets: Flows

- \triangleright A **trajectory flow** is a nonnegative function, which represents the probability mass of each complete trajectory τ
- \triangleright The flow through each state: $F(s) = \sum_{\tau \in \mathcal{T}, s \in \tau} F(\tau)$
- \triangleright The flow through each edge: $F(s \to s') = \sum_{\tau \in T. s \to s' \in \tau} F(\tau)$
- \triangleright The forward transition probabilities (forward policy): $P_F(s'|s) := F(s \to s')/F(s)$
- \triangleright The backward transition probabilities (backward policy): $P_B(s|s') := F(s \to s')/F(s')$








■ GFlowNets: Learning Objective

- ➤ A GFlowNet can perfectly generate objects proportional to their rewards.
- \triangleright In other words, the probability from the source state s_0 to the final state s_f is proportional to the given reward.







■ Optimal Transport Distance

For two discrete probability measures α and β over some space X

The set of transportation plans or joint probability distributions can be defined as:

$$\Pi\left(\boldsymbol{\alpha},\boldsymbol{\beta}\right) = \left\{\boldsymbol{\pi} \in \mathbb{R}_{+}^{k \times l} : \boldsymbol{\pi} \mathbb{1}_{l} = \boldsymbol{\alpha}, \boldsymbol{\pi}^{\top} \mathbb{1}_{k} = \boldsymbol{\beta}\right\}$$


 \triangleright The Kantorovich **optimal transport** between α and β is defined as follows:

$$\mathrm{OT}_{\mathbf{C}}\left(oldsymbol{lpha},oldsymbol{eta}
ight):=\min_{\pi\in\Pi\left(oldsymbol{lpha},oldsymbol{eta}
ight)}\langle\mathbf{C},\pi
angle$$

where C is given cost matrix



- ➤ Background: GFlowNets & Optimal Transport Distance
- ➤ Method: Path Regularization via Optimal Transport







Discrete distance -> OT distance -> Path Regularization

■ Directed distance in the GFlowNet

- We define a new **directed distance** between two arbitrary states in the GFlowNet, which is used as **transportation cost** to compute OT distance.
- Note: the directed distance from a state s to another state s' is designed to be inversely proportional to the probability of going from s to s'
- Let $\tau = (s = s0 \rightarrow s1 \rightarrow ... \rightarrow sn = s')$ be the sequence of transitions from s to s' where $s_t \rightarrow s_{t+1}$ can be a **forward or backward transition** (i.e., the given DAG can be considered an undirected connected graph), the **directed distance** from s to s' is defined as follows:

$$d(s, s') := \min_{\tau = (s \to \dots \to s')} -\log(P(\tau \mid s))$$

i.e., the shortest path from s to s'

The length of the trajectory τ



Discrete distance -> OT distance -> Path Regularization

■ Optimal transport formulation of the path regularization

Give **two neighbor states** s and s' in trajectory τ , **the forward policy** $P_F(\cdot|s)$ is a discrete probability measure supported by Child(s) = $\{u_1, ..., u_k\}$ and $P_F(\cdot|s')$ is a discrete probability measure supported by Child(s') = $\{v_1, ..., v_l\}$.

 \triangleright The **OT distance** between $P_F(\cdot|s)$ and $P_F(\cdot|s')$ can be defined as:

$$OT_{\mathbf{C}}(P_{F}(\cdot|s), P_{F}(\cdot|s')) := \min_{\pi \in \prod(P_{F}(\cdot|s), P_{F}(\cdot|s'))} \langle \mathbf{C}, \pi \rangle
\Pi(P_{F}(\cdot|s), P_{F}(\cdot|s')) := \{ \pi \in \mathbb{R}_{+}^{k \times l} : \pi \mathbb{1}_{l} = P_{F}(\cdot|s), \pi^{\top} \mathbb{1}_{k} = P_{F}(\cdot|s') \}
C_{ij} = c(u_{i}, v_{j}) := d(u_{i}, v_{j}) = \min_{\tau = (u_{i} \to \dots \to v_{j})} -\log(P(\tau \mid u_{i}))$$

The cost matrix C can be calculated in practice by approximating as follows:

$$\mathbf{C}_{ij} = \begin{cases} 0, & \text{if } u_i \equiv v_j \\ \min\left(-\log(P_B(s\mid u_i)P_F(s'\mid s)P_F(v_j\mid s')), -\log(P(v_j\mid u_i))\right), & \text{else if } u_i \equiv v_j \\ -\log(P_B(s\mid u_i)P_F(s'\mid s)P_F(v_j\mid s')), & \text{otherwise.} \end{cases}$$





Discrete distance -> OT distance -> Path Regularization

■ Optimal transport formulation of the path regularization

Give **two neighbor states** s and s' in trajectory τ , **the forward policy** $P_F(\cdot|s)$ is a discrete probability measure supported by Child(s) = $\{u_1, ..., u_k\}$ and $P_F(\cdot|s')$ is a discrete probability measure supported by Child(s') = $\{v_1, ..., v_l\}$.

 \triangleright For any complete trajectory τ , we define the path regularization via OT as follows:

$$\mathcal{L}_{OT}(\tau) := \sum_{t=0}^{n-1} OT_{\mathbf{C}_{t;\theta}} \left(P_F(\cdot|s_t;\theta), P_F(\cdot|s_{t+1};\theta) \right)$$

 \triangleright If π_{θ} is the training policy, then **the trajectory loss** is updated:

$$\mathbb{E}_{\tau \sim \pi_{\theta}} \nabla_{\theta} (\mathcal{L}_{TB}(\tau) + \lambda \mathcal{L}_{OT}(\tau))$$

where $\lambda \in \mathbb{R}$, $\lambda > 0$ indicates that we want to **minimize** the path regularization to to improve the generalization and, $\lambda < 0$ indicates that we want to **maximize** the path regularization to generate more diverse and novel candidates.



Discrete distance -> OT distance -> Path Regularization

Upper bound of optimal transport distance

- \triangleright Our path regularization's definition requires computing the OT distances for all edges in the trajectory τ , which imposes a heavy burden on the computing
- To overcome this problem, we propose the **upper bound** of the OT distance:

$$\begin{split} \text{OT}_{\mathbf{C}}\left(P_{F}(\cdot|s_{t}), P_{F}(\cdot|s_{t+1})\right) &:= \min_{\pi \in \prod(P_{F}(\cdot|s_{t}), P_{F}(\cdot|s_{t+1}))} \langle \mathbf{C}, \pi \rangle \\ &\leq \sum_{i} \sum_{j} \pi_{ij} \mathbf{C}_{ij} \\ &\leq -\sum_{i} \sum_{j} \pi_{ij} \log\left(P_{B}(s_{t}|u_{i})P_{F}(s_{t+1}|s_{t})P_{F}(v_{j}|s_{t+1})\right) \\ &= -\sum_{i} \sum_{j} \pi_{ij} \log\left(P_{B}(s_{t}|u_{i})\right) - \sum_{i} \sum_{j} \pi_{ij} \log\left(P_{F}(s_{t+1}|s_{t})\right) - \sum_{i} \sum_{j} \pi_{ij} \log\left(P_{F}(v_{j}|s_{t+1})\right)\right) \\ &= -\sum_{i} \log\left(P_{B}(s_{t}|u_{i})\right) \sum_{j} \pi_{ij} - \log\left(P_{F}(s_{t+1}|s_{t})\right) \sum_{i} \sum_{j} \pi_{ij} - \sum_{i} \log\left(P_{F}(v_{j}|s_{t+1})\right) \sum_{j} \pi_{ij} \\ &= -\sum_{i} \log\left(P_{B}(s_{t}|u_{i})\right) P_{F}(u_{i}|s_{t}) - \log\left(P_{F}(s_{t+1}|s_{t})\right) - \sum_{j} \log\left(P_{F}(v_{j}|s_{t+1})\right) P_{F}(v_{j}|s_{t+1}) \\ &= \sum_{u \in \text{Child}(s_{t})} P_{F}(u|s_{t}) \log(P_{B}(s_{t}|u)) - \log(P_{F}(s_{t+1}|s_{t})) + \mathbf{H}(P_{F}(.|s_{t+1}). \end{split}$$





Discrete distance -> OT distance -> Path Regularization

■ Upper bound of optimal transport distance

> Since the path regularization via OT can be difined as follows:

$$\mathcal{L}_{OT}(\tau) := \sum_{t=0}^{n-1} OT_{\mathbf{C}_{t;\theta}} \left(P_F(\cdot|s_t;\theta), P_F(\cdot|s_{t+1};\theta) \right).$$

> The path regularization via OT can be upper bound by:

$$\mathcal{L}_{\textit{UB}}(\tau) := \sum_{t=0}^{n-1} \left[\sum_{u \in \textit{Child}(s_t)} P_F(u|s_t) \log(P_B(s_t|u)) - \log(P_F(s_{t+1}|s_t)) + \mathbf{H}(P_F(\cdot|s_{t+1})) \right].$$

$$\sum_{t=0}^{n-1} -\log(P_F(s_{t+1}|s_t)) = -\log\left(\prod_{t=0}^{n-1} P_F(s_{t+1}|s_t)\right) = -\log(P(\tau))$$



- ➤ Background: GFlowNets & Optimal Transport Distance
- > Method: Path Regularization via Optimal Transport
- > Experiment
- Conclusion





■ Hyper-grid Environment

This task aims to evaluates the **generalization ability** of the GFlowNet to guess and sample unvisited modes of the interested distribution.




Figure 2: Results on the 4-D (upper) and 8-D (lower) hyper-grid environment. Left: Number of modes found during training. Right: KL divergence between the true and empirical distribution.

The GFlowNet model trained by minimizing the path regularization via OT and the upper bound both performer well in improving generalization ability.





■ Synthetic Discrete Probabilistic Modeling tasks

Training the GFlowNet with either **minimizing** the path regularization via OT (Min OT) or via the **upper bound** (UB OT) gains the better **NLL** and **MMD** scores than the baseline and Max OT.

Metrix	Method	2spirals	8gaussians	circles	moons	pinwheel	swissroll	checkerboard
NLL ↓	PCD	20.094	19.991	20.565	19.763	19.593	20.172	21.214
	ALOE	20.295	20.350	20.565	19.287	19.821	20.160	54.653
	ALOE +	20.062	19.984	20.570	19.743	19.576	20.170	21.142
	EB-GFN (paper)	20.050	19.982	20.546	19.732	19.554	20.146	20.696
	EB-GFN	20.0679	19.9862	20.5598	19.7324	19.5735	20.1599	20.6839
	EB-GFN + Max OT	20.0673	19.9857	20.5599	19.7319	19.5714	20.1597	20.6837
	EB-GFN + UB OT	20.0651	19.9854	20.5600	19.7305	19.5707	20.1596	20.6836
	EB-GFN + Min OT	20.0640	19.9855	20.5598	19.7308	19.5699	20.1595	20.6831
MMD↓	PCD	2.160	0.954	0.188	0.962	0.505	1.382	2.831
	ALOE	21.926	107.320	0.497	26.894	39.091	0.471	61.562
	ALOE +	0.149	0.078	0.636	0.516	1.746	0.718	12.138
	EB-GFN (paper)	0.583	0.531	0.305	0.121	0.492	0.274	1.206
	EB-GFN	0.3012	0.0408	-0.1724	-0.1744	0.2056	0.1555	-0.0986
	EB-GFN + Max OT	0.3258	0.0197	-0.1919	-0.0456	0.1377	0.0763	-0.0903
	EB-GFN + UB OT	0.2902	0.0102	-0.2819	-0.1253	0.1561	0.0257	-0.0923
	EB-GFN + Min OT	0.1816	0.0343	-0.2775	-0.1966	0.1220	0.1334	-0.1071

Table 4: Results on the Synthetic EB-GFN tasks. The negative log-likelihood (NLL) and MMD are displayed in units of 1×10^{-4} . ALOE+ uses a 30 larger parametrization than ALOE and EB-GFN. We only take into account the the reproduce results of EB-GFN when comparing with our methods (Min OT, Max OT, and UB OT).

^{*} Zhang D, Malkin N, Liu Z, et al. Generative flow networks for discrete probabilistic modeling[C]//International Conference on Machine Learning. PMLR, 2022: 26412-26428.





■ Biological Sequences Design

The experiments are conducted in the multi-round active learning setting, with the goal of generating a diverse set of useful candidates after evaluation rounds.

	Performance	Diversity	Novelty
DynaPPO COMs GFlowNet-AL (paper)	$\begin{array}{c} 0.938 \pm 0.009 \\ 0.761 \pm 0.009 \\ 0.932 \pm 0.002 \end{array}$	$\begin{array}{c} 12.12 \pm 1.71 \\ 19.38 \pm 0.14 \\ 22.34 \pm 1.24 \end{array}$	$\begin{array}{c} 9.31 \pm 0.69 \\ 26.47 \pm 1.30 \\ 28.44 \pm 1.32 \end{array}$
GFlowNet-AL GFlowNet+Min OT-AL GFlowNet+UB OT-AL GFlowNet+Max OT-AL	0.874 ± 0.022 0.847 ± 0.033 0.828 ± 0.022 0.917 ± 0.003	31.98 ± 2.27 20.32 ± 7.38 29.89 ± 2.80 31.56 ± 2.43	23.91 ± 1.87 23.63 ± 1.66 24.16 ± 1.75 28.86 ± 0.96

Table 1: Results on the AMP task with K = 100.

	Performance	Diversity	Novelty
DynaPPO COMs BO-qEI CbAS MINs CMA-ES AmortizedBO GFlowNet-AL (paper)	$\begin{array}{c} 0.58 \pm 0.02 \\ 0.74 \pm 0.04 \\ 0.44 \pm 0.05 \\ 0.45 \pm 0.14 \\ 0.40 \pm 0.14 \\ 0.47 \pm 0.12 \\ 0.62 \pm 0.01 \\ 0.84 \pm 0.05 \end{array}$	$\begin{array}{c} 5.18 \pm 0.04 \\ 4.36 \pm 0.24 \\ 4.78 \pm 0.17 \\ 5.35 \pm 0.16 \\ 5.57 \pm 0.15 \\ 4.89 \pm 0.01 \\ 4.97 \pm 0.06 \\ 4.53 \pm 0.46 \end{array}$	$\begin{array}{c} 0.83 \pm 0.03 \\ 1.16 \pm 0.11 \\ 0.62 \pm 0.23 \\ 0.46 \pm 0.04 \\ 0.36 \pm 0.00 \\ 0.64 \pm 0.21 \\ 1.00 \pm 0.57 \\ 2.12 \pm 0.04 \end{array}$
GFlowNet-AL GFlowNet+Min OT-AL GFlowNet+UB OT-AL GFlowNet+Max OT-AL	$\begin{array}{c} 0.83 \pm 0.01 \\ 0.82 \pm 0.01 \\ 0.83 \pm 0.01 \\ 0.85 \pm 0.02 \end{array}$	$\begin{array}{c} 4.66 \pm 0.08 \\ 4.72 \pm 0.10 \\ 4.68 \pm 0.10 \\ 4.52 \pm 0.18 \end{array}$	$\begin{array}{c} 1.14 \pm 0.03 \\ 1.13 \pm 0.04 \\ 1.14 \pm 0.05 \\ 1.21 \pm 0.10 \end{array}$

Table 2: Results on the TF Bind 8 task with K = 128.

^{*} Jain M, Bengio E, Hernandez-Garcia A, et al. Biological sequence design with gflownets[C]//International Conference on Machine Learning. PMLR, 2022: 9786-9801.





■ Biological Sequences Design

The experiments are conducted in the multi-round active learning setting, with the goal of generating a diverse set of useful candidates after evaluation rounds.

	Performance	Diversity	Novelty
DynaPPO	0.794 ± 0.002	206.19 ± 0.19	203.20 ± 0.47
COMs	0.831 ± 0.003	204.14 ± 0.14	201.64 ± 0.42
BO-qEI	0.045 ± 0.003	139.89 ± 0.18	203.60 ± 0.06
CbAS	0.817 ± 0.012	5.42 ± 0.18	1.81 ± 0.16
MINs	0.761 ± 0.007	5.39 ± 0.00	2.42 ± 0.00
CMA-ES	0.063 ± 0.003	201.43 ± 0.12	203.82 ± 0.09
AmortizedBO	0.051 ± 0.001	205.32 ± 0.12	202.34 ± 0.25
GFlowNet-AL (paper)	0.853 ± 0.004	211.51 ± 0.73	210.56 ± 0.82
GFlowNet-AL	0.8232 ± 0.0001	218.54 ± 7.88	222.05 ± 5.49
GFlowNet+Min OT-AL	0.8231 ± 0.0001	182.03 ± 0.25	220.56 ± 2.02
GFlowNet+UB OT-AL	0.8232 ± 0.0001	221.64 ± 0.11	218.02 ± 0.79
GFlowNet+Max OT-AL	0.8233 ± 0.0001	225.00 ± 3.76	242.11 ± 1.44

Table 3: Results on the GFP task with K = 128.

The GFlowNet-AL model trained by maximizing the path regularization via OT performs well in generating more diverse and novel candidates.



- ➤ Background: GFlowNets & Optimal Transport Distance
- > Method: Path Regularization via Optimal Transport
- > Experiment
- > Conclusion







- ➤ We propose to train the GFlowNet with an additional path regularization via Optimal Transport that places prior constraints on the underlying structure of the GFlowNet.
- We derive an efficient implementation of the regularization by finding its closedform solutions in specific cases and a meaningful upper bound that can be used as an approximation when we want to minimize the regularization term.
- Experiments have shown that minimizing the path regularization via OT improves the GFlowNet's generalization while maximizing the path regularization via OT enhances the exploration ability of the GFlowNet.







Fanmeng Wang 2023-6-21