

# Mechanisms for Model Consistency: A Comparative Analysis of Guideline Implementation in SysML v1 and SysML v2

1<sup>st</sup> Nassim Awabdy

*Fachbereich 5*

*Aachen University of Applied Sciences*

Aachen, Germany

nassim.awabdy@alumni.fh-aachen.de

**Abstract**—TODO

**Index Terms**—cyber-physical systems, model-based systems engineering, sysml, modeling guidelines, model validation, model verification, systems engineering

## I. INTRODUCTION

Modern Cyber-Physical Systems (CPS) are technical systems that combine mechanical, electronic, and software subsystems with physical elements embedded in the real world. The development of CPSs is becoming increasingly complex and challenging, due to their interdisciplinary nature and the need to ensure seamless integration between their physical and computational components [2], [3].

Model-Based Systems Engineering (MBSE) is a methodology for the development and management such complex systems, that addresses issues arising from the complexity and interdisciplinary nature of CPS, and provides the agility required to adapt to changing requirements and technologies. MBSE incorporates a centralized system model as the primary source of information, throughout the system lifecycle [2]–[5], [7], [8].

SysML v1 has been widely adopted as the standard for modelling CPS and served as a key enabler MBSE. SysML v1 is a graphical, general purpose modelling language that is defined as an extension of the Unified Modeling Language (UML). Because it was built on top of UML, SysML v1 inherited several limitations from UML, that limited its expressiveness and usability for CPS modelling. However, it still provided a solid foundation for specifying and analyzing a systems' behavior, structure and requirements [3], [4], [8].

The release of SysML v2 represents the next generation of the Systems Modeling Language, designed as an overhaul of SysML v1 that addresses its limitations and enhance the efficacy of MBSE practices. Unlike its predecessor, SysML v2 is built upon the Kernel Modeling Language (KerML), this approach ensures that SysML v2 inherits a formal semantic foundation, that is crucial for enhanced precision and automation in MBSE workflows. [3], [4], [8], [12].

While these advancements introduced by SysML v2 are promising, the abstract nature of the language still presents

challenges for ensuring consistent modeling practices across diverse engineering teams. Model inconsistencies creates a high risk of redundant effort, potential modeling errors, and lack of reuse of system elements, preventing them from being aggregated into a coherent overall system model. Therefore, mechanisms for implementing and enforcing modeling guidelines must evolve to leverage the native formal capabilities of SysML v2, that enable effective model verification processes throughout the development lifecycle [2]–[4], [12], [14].

Within the context of model analysis, a distinct differentiation between model validation and model verification is necessary. Following the ISO 15288 standard, this work adopts the following definitions:

- *Verification* is the process of proving that a design solution conforms to defined architectural and technical standards. This includes *requirements traceability* and *syntactic verification* [6].
- *Validation*, conversely, aims to prove that the system fulfills its business objectives and stakeholder requirements in its intended operational environment. This is achieved through *behavioral simulation* and the execution of *operational scenarios* [6].

This work addresses the following research question: **How do the mechanisms for implementing modeling guidelines differ between SysML v1 and SysML v2, and how do these differences impact the capabilities automated verification?**

To answer this, we conduct a comparative analysis of the underlying implementation mechanisms, specifically contrasting the profile-based constraints of SysML v1 with the metamodel-driven and formal semantic capabilities of SysML v2. We analyze the implications of this shift by examining specific scenarios where these mechanisms facilitate structural verification, rather than providing a holistic overview of all available commercial tools.

## II. THEORETICAL BACKGROUND

### A. Model-Based Systems Engineering (MBSE)

Model-Based Systems Engineering (MBSE) is defined by the International Council on Systems Engineering (INCOSE)

as "The formalized application of modeling to support system requirements, design, analysis, verification, and validation activities beginning in the concept stage and continuing throughout development and later life cycle stages." [9].

Unlike traditional document-based approaches, where system's information is scattered across various files, MBSE is a methodology that centralizes system's information within a unified model, which serves as the primary source of information that is managed throughout the system lifecycle [8]. This approach enhances collaboration among multidisciplinary teams, reduces errors from manual synchronization, and enables system architects to respond more quickly and effectively to numerous changes in requirements that occur during the development process [1], [7], [16].

### B. SysML v1 Foundations

SysML v1 is a graphical, general purpose modeling language that is widely recognized as the standard language for MBSE, serving as a foundational tool for specifying, analyzing, designing and verifying complex multidisciplinary systems [1], [4], [10].

SysML v1, adopted by the Object Management Group (OMG) in 2007, was essential in advancing MBSE practice by providing capabilities for formally capturing system requirements, structure, behavior, and parametric [8]. The language is defined as an extension of the Unified Modeling Language (UML), allowing it to adopt established modeling concepts [4].

SysML v1 organizes its modeling constructs into four main categories:

- **Structure:** This aspect is modeled using Block Definition Diagrams (BDDs) and Internal Block Diagrams (IBDs). BDDs are used to define components, interfaces, and relationships at black-box level, while IBDs offer a white-box perspective by outlining the internal structure of a single block [10].
- **Behavior:** SysML v1 provides several behavioral diagrams, including State Machine Diagrams, Sequence Diagrams, and Activity Diagrams [10], [16]. These diagrams capture distinct uses for modeling system behavior.
- **Requirements:** System requirements are specified in Requirement Diagrams, that largely rely on natural language representation, although they can be linked logically to other model elements [10], [12].
- **Parametric:** Parametric Diagrams define mathematical constraints and equations between system elements. They support preliminary calculations and analysis within the model, though they often require external tools for complex evaluations [10].

SysML v1 allows the restriction of modeling practices through UML profiling mechanism, enabling the construction of specialized extensions. The central element for customization is the *stereotype*, which functions as a distinct metaclass within UML [1]. Stereotypes enable the customization of existing metaclasses by associating them with specific properties

and constraints, thereby tailoring the modeling language to meet domain-specific requirements [1], [15].

The *Object Constraint Language (OCL)* function as a specialized textual specifications language that enables formally defining rules, constraints and queries on models especially those created using UML [14]. It was developed to overcome the limitations of graphical modeling by allowing precise specification of rules that cannot be easily represented visually [1].

### C. SysML v2 Foundations

SysML v2 represents a major evolution over its predecessor, having been engineered independently from UML to overcome the limitations inherited from it [4], [8]. It aims to enhance MBSE adoption and effectiveness by focusing on improving precision, expressiveness, consistency, usability, interoperability, and extensibility. [8] The foundation of SysML v2 is built upon a new general-purpose modeling language called the *Kernel Modeling Language (KerML)* [12].

The mechanism of KerML is built upon a hierarchical, three-layered architecture, successively progressing from general to specific constructs [13].

- The **Root Layer** establishes the essential syntactic scaffolding for constructing models. The main focus of this layer is to define organizational constructs, such as *Elements*, *Namespace*s, and *Relationship*s, leaving out model-level semantic interpretation relative to the modeled system [12], [13].
- The **Core Layer** introduces the language's semantic foundation based on classification, defined in first-order logic axioms. The central primitive is *Type*, which is divided into *Classifiers*, *Features*. It also defines key relationships necessary for organizing classification hierarchies [12], [13].
- The **Kernel Layer** finalizes the language specification by adding specialized constructs used in common modeling applications, such as *Data Types*, *Classes*, *Structures*, and *Behaviors* [12], [13].

KerML achieves its consistent semantics through formal mathematical logic and library-based ontological modeling that maintain a precise interpretation of complex models. Since the semantics in the *Core Layer* are defined using first-order logic, a consistent basis for mathematical reasoning about models is established [12], [13].

For comprehensive concepts introduced in the *Kernel Layer*, KerML extends its semantics through the reuse of elements found in the *Kernel Semantic Library*. This library is itself expressed in KerML, meaning that all concepts in the language are ultimately grounded in the same formal semantic framework [12], [13].

SysML v2 introduces several key features for further enhancing modeling capabilities, accessibility, and tool integration.

- **Textual Notations:** In addition to graphical notation, SysML v2 features a standardized textual syntax that

provides advantages for interoperability with external tools and exchange of models [12], [13].

- **Standardized API:** The language includes the new Systems Modeling API (SysML API), which enables full access to the model and general Model as Code workflows [12], [13].
- **Metadata Definitions:** In SysML v2, *Metadata Definitions* (metadata def) serve as the primary mechanism for annotating model elements with domain-specific semantics, analogous to Stereotypes in SysML v1. They define a specific schema (properties and constraints) that extends the language’s metaclasses, enabling the creation of domain-specific modeling languages (DSMLs) [3], [12].
- **Formal Requirements:** Requirements in SysML v2, are constructs that can formally specify a *constraint*, declare their *subject*, and have defined *attributes*, moving beyond natural language representation [12], [13].
- **Cases:** SysML v2 introduced a generic *Case* construct which is essentially a calculation that can declare a subject and an objective to provide a formal and executable way to check model correctness and evaluate system properties. Two specialized cases are provided *Analysis Case* (Quantitative Analysis) and *Verification Case* (Qualitative Analysis), further enhancing model analysis capabilities [12].

### III. RESULTS

The comparative analysis of the literature reveals a fundamental shift in the role of modeling guidelines between SysML v1 and SysML v2. While v1 utilized guidelines primarily as external constraints to enforce structural consistency, SysML v2 integrates them as foundational semantic requirements. Consequently, the relationship between *modeling guideline*, *validation*, and *verification* can be conceptualized as a hierarchical dependency.

#### A. Implementing Guidelines in SysML v1

In SysML v1, the implementation of domain-specific guidelines is achieved through the construction of a custom *Domain-Specific Modeling Language (DSML)* profile overlaying the base UML metamodel [1]. Because the language lacks a native formal semantics foundation for domain-specific rules, guidelines are enforced through the combination of stereotypes and the attachment of *Object Constraint Language (OCL)* constraints [1].

1) *Semantic Extension via Stereotypes:* : System engineers utilize the profiling mechanism to introduce domain-specific terminology that does not exist in the native SysML v1 metamodel. Guidelines are then enforced by restricting the application of elements to a specific palette of stereotyped elements, ensuring that the model structure reflects domain-specific semantics rather than generic block definitions [1]. A concrete application of this mechanism is demonstrated by Beers et al. in the development of a DSML for formal process description. To enforce the guideline that system functions

must be standardized, the author extends the metaclass *CallBehaviorAction* to create a specific *Process Operator* stereotype. This ensures that an element cannot be designated as a *Process Operator* unless it inherits the specific meta-attributes defined by the stereotype [1].

2) *Topological Enforcement via OCL:* : While stereotypes provide semantic labeling, they are insufficient for enforcing complex topological guidelines regarding the interaction between elements. To validate that the model structure adheres to the guidelines, OCL constraints must be layered onto the profile to restrict valid connections [1].

Beers et al. show the necessity of this mechanism when enforcing the VDI/VDE 3682 standard that provides the rules to implement the “Product-Process-Resource” (PPR) concept. This concept mandates that production systems are modeled through the strict interconnection of the *Process*, the *Product*, and the *Resource* [1].

In their implementation, a “State” (e.g., a Product or Energy) cannot legally connect directly to another “State” without an intermediary process. Since standard SysML v1 syntax permits the connection of any two compatible nodes, the guideline is enforced through an OCL invariant attached to the *Flow* stereotype, that prevents two state-describing elements from being connected together [1].

#### B. Implementing Guidelines in SysML v2

In contrast to the profile-based approach of SysML v1, SysML v2 implements modeling guidelines through intrinsic semantic definitions rather than extrinsic constraints.

1) *Metadata Definition:* In SysML v2, Boelsen et al. demonstrates how to use the *Metadata Definitions* to construct a domain-specific metamodel hierarchies directly within the language architecture by specializing standard KerML constructs [3]. In his work, the author aimed to implement modeling guidelines for reusable mechanical system elements based on the *motego* methodology.

The structural foundation is built by defining an abstract metadata definition for a general *solution*, which is set up as a specialization of the standard *SysML::PartDefinition* (see Fig. 1). From this abstract base, concrete domain-specific types *SolutionElement* and *SystemSolution* are derived [3].

The guidelines further mandate specific structural and behavioral components. The *ActiveSurface* and *ActiveSurfaceSet* are defined as specializations of *SysML::PartDefinition* to represent geometrical structure, while the *Material* is integrated as a reusable structural part within these surfaces.

Crucially, the behavioral logic is enforced by defining the *PhysicalEffect* not as a block, but as a specialization of the *SysML::ConstraintDefinition* meta type. Corresponding metadata definitions are also derived for *PartUsage* to enable the instantiation of these elements within the system model [3].

The enforcement of these guidelines is demonstrated in the modeling of a specific component, such as a “Lubricated Mechanical Line Rolling Contact”. The component is instantiated using the *#SolutionElementDef* metadata definition (see Fig. 2). By using this specific definition, the modeler is guided

```

1 // 1. Structural Definitions
2 metadata def SolutionElementDef :> PartDefinition;
3 metadata def ActiveSurfaceSetDef :> PartDefinition;
4 metadata def ActiveSurfaceDef :> PartDefinition;
5
6 // 2. Behavioral Definitions
7 // Enforces behavior as constraints, not blocks
8 metadata def PhyEffectDef :> ConstraintDefinition;
9
10 // 3. Usage Definitions
11 metadata def SolutionElement :> PartUsage;
12 metadata def ActiveSurfaceSet :> PartUsage;
13 metadata def ActiveSurface :> PartUsage;
14 metadata def PhyEffect :> ConstraintUsage;
15
16 metadata def Material :> PartUsage;

```

Listing 1. Definition of the domain-specific metamodel for mechanical elements in SysML v2 (adapted from Boelsen et al. [3])

to explicitly include the required sub-elements defined in the meta model, specifically the *ActiveSurface* and *Physical-Effect* [3]. Within this structure, the *ActiveSurface* integrates essential parameters via attribute definition and references the material using the *#Material* command [3]. Simultaneously, the *PhysicalEffect* is completed by adding input and output attributes and defining the calculation specification as expression, thereby ensuring that the relationship between the physical effect and the functional flows are strictly quantified accordingly [3].

```

1 // Specific component using custom metadata def
2 #SolutionElementDef def LubMechLineRollingContact {
3   // Guideline mandates specific sub-elements:
4
5   // 1. Behavioral Layer
6   #PhyEffect pe1 : SurfacePressure;
7   #PhyEffect pe2 : CurvedCurvedKinematics {
8     in omega : Real;
9     out v_out : Real = r * omega;
10  }
11
12   // 2. Structural Layer
13   #ActiveSurfaceSet ass : CylindricalLatSurfaces {
14     #ActiveSurface as1 : CylindricLatSurface {
15       attribute radius : Real;
16     }
17     #ActiveSurface as2 : CylindricLatSurface {
18       #Material mat : Steel;
19     }
20  }
21
22   // 3. Binding Parameters
23   bind pe2.radius = ass.as1.radius;
24 }

```

Listing 2. Implementation of a "Lubricated Mechanical Line Rolling Contact" using the enforced metadata definitions (adapted from Boelsen et al. [3])

Hard to integrate with external solvers without complex model transformations.

## 2) SysML v2 Verification:

2) *Libraries and Usage Definition Separation*: SysML v2 enforces guidelines through strict separation of Definition (Type) and Usage (Instance).

SysML v2 is built on KerML, which has native constraint support, reducing the need for add-on languages like OCL.

## C. Verification Methods

1) *SysML v1 Verification*: - Relies heavily on proprietary tool features (e.g., Cameo Validation Suite) to execute OCL. - Verification is often "static" (checking structure). - Limitation:

## IV. DISCUSSION AND IMPLICATIONS

### A. *Stereotypes vs. Metadata*

SysML v1 required a "trust but verify" approach, where users were trusted to apply stereotypes correctly, and scripts verified compliance later. SysML v2 sought to invert this paradigm. By integrating the definition of metadata and constraints into the core language kernel, SysML v2 aims to make non-compliant modeling physically impossible—or at least syntactically invalid—within the tool environment. The shift is from "compliance upon inspection" to "compliance by definition". [4]

## V. CONCLUSION AND OUTLOOK

### ACKNOWLEDGMENT

The author would like to express sincere gratitude to Professor Sebastian Voss for his supervision and guidance throughout the preparation of this work. His support in defining the research scope regarding SysML modeling guidelines was fundamental to the direction of this comparative analysis.

### REFERENCES

- [1] L. Beers, H. Nabizada, M. Weigand, F. Gehlhoff, and A. Fay, "A sysml profile for the standardized description of processes during system development," in 2024 IEEE International Systems Conference (SysCon). IEEE, 2024, pp. 1–8.
- [2] S. Bergemann, "Challenges in multi-view model consistency management for systems engineering," in Modellierung 2022 Satellite Events. Bonn: Gesellschaft für Informatik e.V., 2022, pp. 77–89.
- [3] K. Boelsen, M. May, G. Jacobs, and et al., "Sysml v2 based modelling guidelines for mechanical system elements," *Forsch Ingenieurwes*, vol. 89, no. 60, 2025.
- [4] E. Cibrián, J. Olivert-Iserte, C. Díez-Fenoy, R. Mendieta, J. Llorens, and J. M. Álvarez Rodríguez, "Ensuring semantic consistency in sysml v2 models through metamodel-driven validation," *IEEE Access*, vol. 13, pp. 121 444–121 457, 2025.
- [5] S. Dehn, G. Jacobs, P. Höck, and G. Höpfner, "Enhancing model-based development with formalized requirements: integrating temporal logic and sysml v2 for comprehensive state and transition modeling," *Forschung im Ingenieurwesen*, vol. 89, no. 1, p. 53, 2025.
- [6] Systems and software engineering — System life cycle processes, ISO/IEC/IEEE Standard 15288:2023, May 2023.
- [7] P. Dukić, "Generating sysmlv2 models from structured natural language," 2025.
- [8] S. Friedenthal, "Future directions for mbse with sysml v2," in MODEL-SWARD, 2023, pp. 5–9.
- [9] D. D. Walden, G. J. Roedler, K. J. Forsberg, R. D. Hamelin, and T. M. Shortell, Eds., *INCOSE Systems Engineering Handbook: A Guide for System Life Cycle Processes and Activities*, 4th ed. Hoboken, NJ, USA: John Wiley & Sons, 2015.
- [10] N. Jansen, J. Pfeiffer, B. Rumpe, D. Schmalzing, and A. Wortmann, "The language of sysml v2 under the magnifying glass," *J. Object Technol.*, vol. 21, no. 3, pp. 3–1, 2022.
- [11] H. Kausch, M. Pfeiffer, D. Raco, B. Rumpe, and A. Schweiger, "Model-driven development for functional correctness of avionics systems: a verification framework for sysml specifications," *CEAS Aeronautical Journal*, vol. 16, no. 1, pp. 33–48, 2025.
- [12] V. Molnár, B. Graics, A. Vörös, S. Tonetta, L. Cristoforetti, G. Kimberly, P. Dyer, K. Giammarco, M. Koethe, J. Hester et al., "Towards the formal verification of sysml v2 models," in Proceedings of the ACM/IEEE 27th International Conference on Model Driven Engineering Languages and Systems, 2024, pp. 1086–1095.
- [13] Object Management Group, "Kernel Modeling Language (KerML), Version 1.0," Object Management Group, Specification formal/25-09-01, Sep. 2025. [Online]. Available: <https://www.omg.org/spec/KerML/1.0/PDF>
- [14] A. Ratzke, J. Koch, and C. Grimm, "Modeling and analysis of system models with constraints in sysml v2," in 2025 20th Annual System of Systems Engineering Conference (SoSE), 2025, pp. 1–6.
- [15] S. Raedler, J. Mangler, and S. Rinderle-Ma, "Model-driven engineering method to support the formalization of machine learning using sysml," *arXiv preprint arXiv:2307.04495*, 2023.
- [16] U. Yildirim, F. Campean, A. Korsunovs, and A. Doikin, "Flow heuristics for functional modelling in model-based systems engineering," *Proceedings of the Design Society*, vol. 3, pp. 1895–1904, 2023.
- [17] Zavada, G. Kulcsár, V. Molnár, and Horváth, "Towards a configurable verification and validation framework for critical cyber-physical systems," in 2025 IEEE 8th International Conference on Industrial Cyber-Physical Systems (ICPS), 2025, pp. 1–6.
- [18] Z. Li, F. Faheem, and S. Husung, "Collaborative model-based systems engineering using dataspace and sysml v2," *Systems*, vol. 12, no. 1, 2024. [Online]. Available: <https://www.mdpi.com/2079-8954/12/1/18>