

INCIDENT REPORT |Oluwaseun Quadri

Title: Network Attack Detection Using Cowrie Honeypot

1. Introduction

This report documents a simulated network attack detected and analyzed using a Cowrie SSH honeypot in a controlled lab environment. The objective of the exercise was to identify malicious scanning activity, capture network traffic, and analyze attacker behavior using standard cybersecurity tools.

2. Lab Environment

The experiment was conducted in a virtualized environment using Oracle VirtualBox.

- **Honeypot System:** Ubuntu Linux
- **Attacker System:** Kali Linux
- **Honeypot Tool:** Cowrie SSH Honeypot
- **Attack Tools:** Nmap, SSH
- **Traffic Capture Tool:** tcpdump (PCAP analyzed with Wireshark)
- **Network Configuration:** VirtualBox NAT / Host-only network
- **Honeypot IP Address:** 192.168.56.102
- **Listening Port:** TCP 2222

3. Incident Description

During the lab exercise, the Cowrie honeypot was configured to listen on TCP port 2222, simulating an SSH service. An attacker machine (Kali Linux) performed reconnaissance activities against the honeypot using Nmap service and version detection scans.

The scanning activity triggered interactions with the honeypot, which logged the connection attempts. Simultaneously, network traffic was captured in PCAP format for further analysis.

4. Attack Detection and Evidence

4.1 Network Scanning

The attacker system executed the following command:

```
nmap -sV -p 2222 192.168.56.102
```

5. Honeypot Logs

Cowrie successfully logged the attack attempt, confirming that the honeypot was active and able to record malicious interactions.

6. Analysis

Analysis of the captured traffic in Wireshark revealed:

- TCP connection attempts to port 2222
- Service/version detection probes from the attacker
- Response packets generated by the Cowrie honeypot

These indicators confirm reconnaissance activity consistent with the early stages of a network attack

7. Impact Assessment

No real systems were compromised as the target was a honeypot designed to safely capture malicious behavior. However, the activity demonstrates how exposed SSH services can be discovered and probed by attackers during reconnaissance.

8. Conclusion

This lab successfully demonstrated the use of a Cowrie honeypot for detecting and logging network-based attacks. By combining honeypot technology with packet capture and analysis tools, malicious activity was effectively identified and documented. Such techniques are essential for improving network visibility and strengthening defensive security measures.

```


Requirement already satisfied: automat==24.0.0 in ./cowrie-env/lib/python3.12/site-packages (from twisted==25.5.0->twisted[conch]==25.5.0->cowrie==2.9.10.dev3+gc2b722be0) (25.4.16)
Requirement already satisfied: constantly==15.1 in ./cowrie-env/lib/python3.12/site-packages (from twisted==25.5.0->twisted[conch]==25.5.0->cowrie==2.9.10.dev3+gc2b722be0) (23.10.4)
Requirement already satisfied: zope-interface==5 in ./cowrie-env/lib/python3.12/site-packages (from twisted==25.5.0->twisted[conch]==25.5.0->cowrie==2.9.10.dev3+gc2b722be0) (8.2)
Requirement already satisfied: appdirs==1.4.0 in ./cowrie-env/lib/python3.12/site-packages (from twisted[conch]==25.5.0->cowrie==2.9.10.dev3+gc2b722be0) (1.4.4)
Requirement already satisfied: pycparser in ./cowrie-env/lib/python3.12/site-packages (from cffi==2.0.0->cryptography==46.0.4->cowrie==2.9.10.dev3+gc2b722be0) (3.0)
Requirement already satisfied: pyopenssl==21.0.0 in ./cowrie-env/lib/python3.12/site-packages (from twisted[tls]==22.10.0->treq==25.5.0->cowrie==2.9.10.dev3+gc2b722be0) (25.3.0)
Building wheels for collected packages: cowrie
  Building editable for cowrie (pyproject.toml) ... done
  Created wheel for cowrie: filename=cowrie-2.9.10.dev3+gc2b722be0-0.editable-py3-none-any.whl size=6085 sha256=26b4c610adfc48ae8def7b9b71542802a52af33172b1a860eeb0f4b97c9fbb49
  Stored in directory: /tmp/pip-ephem-wheel-cache-kq3rnf5f/wheels/ed/83/07/ad6d1a039accd848de15ae06f4fbf09862dcacf1ab7c814a6b
Successfully built cowrie
Installing collected packages: cowrie
Successfully installed cowrie-2.9.10.dev3+gc2b722be0
(cowrie-env) cowrie@cowrie-server:~/cowrie$ python3 -m cowrie
/home/cowrie/cowrie/cowrie-env/bin/python3: No module named cowrie.__main__; 'cowrie' is a package and cannot be directly executed
(cowrie-env) cowrie@cowrie-server:~/cowrie$ python3 -m cowrie
/home/cowrie/cowrie/cowrie-env/bin/python3: No module named cowrie.__main__; 'cowrie' is a package and cannot be directly executed
(cowrie-env) cowrie@cowrie-server:~/cowrie$ which cowrie
/home/cowrie/cowrie/cowrie-env/bin/cowrie
(cowrie-env) cowrie@cowrie-server:~/cowrie$ cowrie start

Join the Cowrie community at: https://www.cowrie.org/slack/

Starting cowrie: [twistd --umask=0022 --pidfile /home/cowrie/cowrie/var/run/cowrie.pid --logger cowrie.python.logfile.logger cowrie]...
/home/cowrie/cowrie/cowrie-env/lib/python3.12/site-packages/twisted/conch/ssh/transport.py:110: CryptographyDeprecationWarning: TripleDES has been moved to cryptography.hazmat.decrepit.ciphers.algorithms.TripleDES and will be removed from cryptography.hazmat.primitives.ciphers.algorithms in 48.0.0.
  b"3des-cbc": (algorithms.TripleDES, 24, modes.CBC),
/home/cowrie/cowrie/cowrie-env/lib/python3.12/site-packages/twisted/conch/ssh/transport.py:117: CryptographyDeprecationWarning: TripleDES has been moved to cryptography.hazmat.decrepit.ciphers.algorithms.TripleDES and will be removed from cryptography.hazmat.primitives.ciphers.algorithms in 48.0.0.
  b"3des-ctr": (algorithms.TripleDES, 24, modes.CTR),
(cowrie-env) cowrie@cowrie-server:~/cowrie$ ss -tulnp | grep 2222
tcp    LISTEN 0      50          0.0.0.0:2222      0.0.0.0:*        users:(("twistd",pid=1986,fd=11))
(cowrie-env) cowrie@cowrie-server:~/cowrie$ tail -f var/log/cowrie/cowrie.log
2026-02-06T23:08:20.339083Z [-] Python Version 3.12.3 (main, Jan 22 2026, 20:57:42) [GCC 13.3.0]
2026-02-06T23:08:20.339118Z [-] Twisted Version 25.5.0
2026-02-06T23:08:20.339130Z [-] Cowrie Version 2.9.10.dev3+gc2b722be0
2026-02-06T23:08:20.339139Z [-] Sensor UUID: ba7d3044-03b0-11f1-abc1-08002705f2bb
2026-02-06T23:08:20.341974Z [-] Loaded output engine: jsonlog
2026-02-06T23:08:20.343099Z [twisted.scripts.twistd_unix.UnixAppLogger#Info] twistd 25.5.0 (/home/cowrie/cowrie/cowrie-env/bin/python3 3.12.3) starting up.
2026-02-06T23:08:20.343214Z [twisted.scripts.twistd_unix.UnixAppLogger#Info] reactor class: twisted.internet.epollreactor.EPollReactor.
2026-02-06T23:08:20.350022Z [-] CowrieSSHFactory starting on 2222
2026-02-06T23:08:20.351173Z [cowrie.ssh.factory.CowrieSSHFactory#Info] Starting factory <cowrie.ssh.factory.CowrieSSHFactory object at 0x7d93457c8000>
2026-02-06T23:08:20.472411Z [-] Ready to accept SSH connections

```

Fig.1 Image indicating cowrie starting



The image shows a Kali Linux terminal window with a dark background and a cityscape wallpaper. The terminal displays the results of a ping and an nmap scan. The ping command shows successful communication with 192.168.56.102. The nmap scan identifies the host as running OpenSSH 9.2p1 on a Debian 2+deb12u3 system, with a MAC address of 08:00:27:05:F2:8B. The terminal output is as follows:

```
kali@kali: ~  
$ ping 192.168.56.102  
PING 192.168.56.102 (192.168.56.102) 56(84) bytes of data:  
64 bytes from 192.168.56.102: icmp_seq=1 ttl=64 time=1.36 ms  
64 bytes from 192.168.56.102: icmp_seq=2 ttl=64 time=1.19 ms  
^C  
--- 192.168.56.102 ping statistics ---  
2 packets transmitted, 2 received, 0% packet loss, time 1011ms  
rtt min/avg/max/mdev = 1.193/1.274/1.355/0.081 ms  
  
kali@kali: ~  
$ nmap -sV -p 2222 192.168.56.102  
  
Starting Nmap 7.95 ( https://nmap.org ) at 2026-02-07 02:37 EST  
Nmap scan report for 192.168.56.102  
Host is up (0.0021s latency).  
  
PORT      STATE SERVICE VERSION  
2222/tcp  open  ssh      OpenSSH 9.2p1 Debian 2+deb12u3 (protocol 2.0)  
MAC Address: 08:00:27:05:F2:8B (PCS Systemtechnik/Oracle VirtualBox virtual NIC)  
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/.  
Nmap done: 1 IP address (1 host up) scanned in 14.86 seconds  
  
kali@kali: ~  
$
```

Fig.2 image indicating Nmap scan result on kali linux