




Vulnerability Assessment & Triage Report

Task 2: Host & Network Vulnerability Assessment Lab

Prepared By:
Daaniya Absar

Date: August 31, 2026

Target: 192.168.56.101 (Metasploitable 2)

Tools: Nmap, NSE Scripts, Nikto

Progree Internship Program

Confidential – For Internal Review Only

Contents

1	Executive Summary	3
1.1	Overview	3
1.2	Key Findings	3
1.3	Top 5 Critical Findings	3
1.4	Risk Impact	3
1.5	Recommendations	4
2	Assessment Methodology	5
2.1	Introduction	5
2.2	Scope Definition	5
2.3	Tools Used	5
2.4	Assessment Phases	5
2.5	Testing Limitations	6
3	Practical Scan Results	7
3.1	Phase 1: Host Discovery - Identifying the Target	7
3.1.1	Command Executed	7
3.1.2	Analysis	7
3.2	Phase 2: Service Enumeration - Identifying Open Ports and Services	7
3.2.1	Command Executed	7
3.2.2	Analysis of Findings	8
3.3	Phase 3: Vulnerability Scanning - Identifying Known Vulnerabilities	8
3.3.1	Full Vulnerability Scan Command	8
3.3.2	Critical Vulnerability: vsftpd Backdoor	9
3.3.3	Critical Vulnerability: UnrealIRCd Backdoor	10
3.3.4	Web Application Vulnerabilities	10
3.4	Phase 4: Web Application Scanning with Nikto	11
3.4.1	Nikto Scan Command and Results	11
3.4.2	Analysis of Nikto Findings	12
4	Detailed Findings	13
4.1	Complete Service Enumeration Results	13
4.2	Detailed Critical Vulnerability Analysis	13
4.2.1	vsftpd 2.3.4 Backdoor (CVE-2011-2523)	14
4.2.2	UnrealIRCd Backdoor (CVE-2010-4344)	14
4.2.3	Samba Command Injection (CVE-2007-2447)	14
4.2.4	SSL/TLS CCS Injection (CVE-2014-0224)	15
4.2.5	SSL POODLE (CVE-2014-3566)	15
4.3	Web Application Vulnerabilities Analysis	15
4.4	High Vulnerabilities	15
4.4.1	Apache 2.2.8 Outdated	16

4.4.2	PHP 5.2.4 Outdated	16
4.4.3	HTTP TRACE Method Enabled	16
5	Remediation Plan	17
5.1	Priority 1 – Immediate (24-72 Hours)	17
5.2	Priority 2 – Short Term (7-10 Days)	17
5.3	Priority 3 – Long Term (30 Days)	17
5.4	Priority 4 – Ongoing	18
5.5	Recommended Security Hardening Checklist	18
6	Appendices	19
6.1	Appendix A: Complete Vulnerability List with CVSS Scores	19
6.2	Appendix B: Complete Scan Outputs	19
6.3	Appendix C: Sample Exploit Output with Explanation	19
6.4	Appendix D: Risk Prioritization Matrix	20
6.5	Appendix E: Tool Installation Commands	20

1 Executive Summary

1.1 Overview

This report presents the findings of a comprehensive vulnerability assessment conducted against the target system **192.168.56.101** (Metasploitable 2). The assessment was performed as part of Task 2 of the ProGree Internship Program, focusing on identifying structural service configuration flaws within an isolated environment.

The assessment involved running network reconnaissance utilities (Nmap, NSE Scripts, and Nikto) against the target virtual machine. A total of **22 open ports** were discovered, revealing multiple critical vulnerabilities that pose significant security risks to the organization.

1.2 Key Findings

The assessment identified **28 distinct vulnerabilities** across various severity levels:

Severity Level	Count
Critical	5
High	6
Medium	8
Low	9
Total Vulnerabilities	28

1.3 Top 5 Critical Findings

The following critical vulnerabilities require immediate attention:

Vulnerability	CVSS	Impact
vsftpd 2.3.4 Backdoor (CVE-2011-2523)	10.0	Remote root access without authentication
UnrealIRCd Backdoor (CVE-2010-4344)	9.8	Remote code execution vulnerability
Samba Command Injection (CVE-2007-2447)	9.3	Unauthenticated remote code execution
SSL/TLS CCS Injection (CVE-2014-0224)	7.5	Session hijacking and MITM attacks
SSL POODLE (CVE-2014-3566)	7.5	Information disclosure via SSLv3

1.4 Risk Impact

If exploited, these vulnerabilities could allow attackers to:

- Gain root-level access to the system without any credentials
- Execute arbitrary code remotely
- Exfiltrate sensitive data from the organization

- Use the compromised system as a pivot point for lateral movement
- Install ransomware or persistent backdoors
- Perform man-in-the-middle attacks to intercept communications

1.5 Recommendations

Based on the findings, the following high-level recommendations are made:

1. Immediately disable or patch the five critical vulnerabilities identified
2. Implement a formal patch management policy
3. Conduct regular vulnerability scans on a quarterly basis
4. Review and harden all service configurations
5. Remove unnecessary services and applications

2 Assessment Methodology

2.1 Introduction

The vulnerability assessment followed a structured methodology to ensure comprehensive coverage of the target system. The approach was designed to identify, classify, and prioritize vulnerabilities based on their potential impact and exploitability.

2.2 Scope Definition

The scope of this assessment was clearly defined to ensure focused and efficient testing:

- **Target System:** 192.168.56.101 (Metasploitable 2)
- **Network Environment:** Isolated host-only network (192.168.56.0/24)
- **Assessment Type:** Internal vulnerability assessment
- **Assessment Date:** August 31, 2026
- **Assessment Duration:** Approximately 2 hours
- **Network Architecture:** VirtualBox host-only adapter configuration

2.3 Tools Used

The following tools were utilized during the assessment:

Tool	Purpose
Nmap 7.99	Network discovery, service enumeration, and vulnerability scanning
NSE (Nmap Scripting Engine)	Vulnerability detection, CVE correlation, and exploit validation
Nikto 2.6.0	Web server vulnerability scanning and security misconfiguration detection

2.4 Assessment Phases

The assessment was conducted in five distinct phases:

Phase 1: Host Discovery

The first phase involved identifying active hosts on the target network. This was accomplished using Nmap's ping sweep functionality (`-sn` flag). The goal was to confirm that the target system was reachable and to identify its IP address within the network.

Phase 2: Service Enumeration

Once the target was confirmed alive, the next phase involved identifying all open ports and running services. This was performed using Nmap's service version detection (`-sV`) and default

script scanning (`-sC`). This phase provided detailed information about service versions, enabling correlation with known vulnerabilities.

Phase 3: Vulnerability Scanning

The third phase involved active vulnerability scanning using Nmap's NSE scripts (`-script vuln`) and Nikto for web application testing. These tools automatically probe for known vulnerabilities, misconfigurations, and security weaknesses.

Phase 4: CVE Correlation

During this phase, identified vulnerabilities were mapped to Common Vulnerabilities and Exposures (CVE) identifiers. Each vulnerability was assigned a Common Vulnerability Scoring System (CVSS) score to facilitate prioritization.

Phase 5: Triage and Reporting

The final phase involved analyzing the scan results, prioritizing vulnerabilities based on severity, and documenting findings in this comprehensive report. Each finding was assigned a priority level based on its CVSS score and potential business impact.

2.5 Testing Limitations

The following limitations should be noted:

- Testing was limited to network-layer vulnerabilities; application-layer testing was not conducted
- Denial of Service (DoS) testing was not performed to maintain system availability
- Social engineering and physical security testing were out of scope
- The assessment was conducted in an isolated lab environment, not a production system

3 Practical Scan Results

3.1 Phase 1: Host Discovery - Identifying the Target

3.1.1 Command Executed

The following command was used to discover active hosts on the network:

```
# On Kali Linux Terminal
kali@kali:~$ nmap -sn 192.168.56.0/24

Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-31 10:00 -0400
Nmap scan report for 192.168.56.1
Host is up (0.00031s latency).
Nmap scan report for 192.168.56.101
Host is up (0.00087s latency).
Nmap scan report for 192.168.56.102
Host is up (0.00054s latency).
Nmap done: 256 IP addresses (3 hosts up) scanned in 2.32 seconds
```

3.1.2 Analysis

The host discovery scan successfully identified three active hosts on the network:

- **192.168.56.1** – VirtualBox host-only gateway
- **192.168.56.101** – Metasploitable 2 target system
- **192.168.56.102** – Kali Linux attacker machine

The target system (192.168.56.101) was confirmed alive and reachable with a latency of 0.87 milliseconds. This confirmed that the network configuration was correct and the target was ready for further assessment.

3.2 Phase 2: Service Enumeration - Identifying Open Ports and Services

3.2.1 Command Executed

The following command was used to enumerate services on the target:

```
# On Kali Linux Terminal
kali@kali:~$ nmap -p 21,22,23,25,80,443,445,3306 192.168.56.101 -sV -sC
-oN nmap_fast.txt

Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-29 10:14 -0400
Nmap scan report for 192.168.56.101
Host is up (0.0021s latency).

PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
```



```
22/tcp    open    ssh      OpenSSH 4.7p1 Debian 8ubuntu1 (protocol
2.0)
23/tcp    open    telnet    Linux telnetd
25/tcp    open    smtp      Postfix smtpd
80/tcp    open    http      Apache httpd 2.2.8 ((Ubuntu) DAV/2)
443/tcp   closed  https
445/tcp   open    netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
3306/tcp  open    mysql     MySQL 5.0.51a-3ubuntu5
MAC Address: 08:00:27:A0:C3:AA (Oracle VirtualBox virtual NIC)
Service Info: Host: metasploitable.localdomain; OSs: Unix, Linux; CPE:
cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at
https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 8.99 seconds
```

3.2.2 Analysis of Findings

The service enumeration revealed several critical security issues:

vsftpd 2.3.4 (Port 21) This version of vsftpd contains a well-known backdoor that was introduced in the 2.3.4 release. The backdoor allows remote attackers to gain root-level access to the system without authentication. This is considered a CRITICAL vulnerability.

OpenSSH 4.7p1 (Port 22) OpenSSH 4.7p1 was released in 2007, making it over 16 years old. This version contains numerous security vulnerabilities that have been patched in subsequent releases. Attackers could exploit known vulnerabilities to gain unauthorized access.

Telnet (Port 23) Telnet is an inherently insecure protocol that transmits all data, including usernames and passwords, in plain text. Attackers with network access can easily intercept and steal credentials.

Samba 3.x (Ports 139, 445) Samba 3.x contains a critical command injection vulnerability (CVE-2007-2447) that allows unauthenticated remote code execution. This vulnerability is well-documented and has public exploits available.

MySQL 5.0.51a (Port 3306) MySQL 5.0.51a was released in 2008 and is no longer supported. This version contains numerous security vulnerabilities that have been patched in newer releases. Using unsupported software poses significant security risks.

3.3 Phase 3: Vulnerability Scanning - Identifying Known Vulnerabilities

3.3.1 Full Vulnerability Scan Command

```
# On Kali Linux Terminal
kali@kali:~$ nmap --script vuln 192.168.56.101 -oN nmap_vuln.txt
```

```
Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-29 10:17 -0400
Nmap scan report for 192.168.56.101
Host is up (0.00087s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1099/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
8009/tcp  open  ajp13
8180/tcp  open  unknown
MAC Address: 08:00:27:A0:C3:AA (Oracle VirtualBox virtual NIC)
```

3.3.2 Critical Vulnerability: vsftpd Backdoor

```
| ftp-vsftpd-backdoor:
|   VULNERABLE:
|     vsFTPD version 2.3.4 backdoor
|       State: VULNERABLE (Exploitable)
|       IDs:   BID:48539   CVE:CVE-2011-2523
|       Disclosure date: 2011-07-03
|       Exploit results:
|         Shell command: id
|         Results: uid=0(root) gid=0(root)
|       References:
|         https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2523
```

Explanation: This vulnerability is particularly dangerous because the backdoor was intentionally placed in the source code. When a connection is made to the FTP server with a specific

username containing the ":" character, the server spawns a root shell that can be accessed by the attacker. The scan confirmed this by successfully executing the `id` command and receiving output showing root privileges.

3.3.3 Critical Vulnerability: UnrealIRCd Backdoor

```
|_irc-unrealircd-backdoor: Looks like trojaned version of unrealircd.  
See http://seclists.org/fulldisclosure/2010/Jun/277
```

Explanation: UnrealIRCd 3.2.8.1 contains a backdoor that was introduced through a compromise of the official source code distribution. This backdoor allows remote attackers to execute arbitrary commands on the server with the privileges of the IRC daemon. The Nmap script detected this vulnerability, confirming the system is at risk.

3.3.4 Web Application Vulnerabilities

```
| http-enum:  
|   /tikiwiki/: Tikiwiki  
|   /test/: Test page  
|   /phpinfo.php: Possible information file  
|   /phpMyAdmin/: phpMyAdmin  
|   /doc/: Potentially interesting directory w/ listing on 'apache  
|           /2.2.8 (ubuntu) dav/2'  
|   /icons/: Potentially interesting folder w/ directory listing  
|   /index/: Potentially interesting folder
```

Explanation: The web enumeration script discovered several sensitive directories and files that pose security risks:

- `/phpinfo.php` exposes detailed system configuration information
- `/phpMyAdmin/` provides a web interface to the MySQL database
- Directory listings on `/doc/`, `/icons/`, and `/test/` allow attackers to browse directory structures

3.4 Phase 4: Web Application Scanning with Nikto

3.4.1 Nikto Scan Command and Results

```
# On Kali Linux Terminal
kali@kali:~$ nikto -h http://192.168.56.101 -o nikto_report.txt

- Nikto v2.6.0
-----

+ Target IP:          192.168.56.101
+ Target Hostname:    192.168.56.101
+ Target Port:       80
+ Platform:          Unknown
+ Start Time:        2026-08-31 07:25:17 (GMT-4)
-----

+ Server: Apache/2.2.8 (Ubuntu) DAV/2
+ ERROR: Failed to check for updates:
+ [999986] /: Retrieved x-powered-by header: PHP/5.2.4-2ubuntu5.10.
+ [750500] /icons/: Directory indexing found.
+ [013587] /: Suggested security header missing: referrer-policy.
+ [013587] /: Suggested security header missing: content-security-policy.
+ [013587] /: Suggested security header missing: strict-transport-security.
+ [013587] /: Suggested security header missing: permissions-policy.
+ [013587] /: Suggested security header missing: x-content-type-options
+ [999100] /index: Uncommon header(s) 'tcn' found, with contents: list.
+ [999965] /index: Apache mod_negotiation is enabled with MultiViews,
which allows attackers to easily brute force file names.
+ [600625] PHP/5.2.4-2ubuntu5.10 appears to be outdated (current is at
least 8.5.1).
+ [600050] Apache/2.2.8 appears to be outdated (current is at least
2.4.66).
+ [000434] /: HTTP TRACE method is active and replies which suggests
the host
is vulnerable to Cross-Site Tracing (XST).
+ [750510] /phpinfo.php: Output from the phpinfo() function was found.
+ [750500] /doc/: Directory indexing found.
+ [001213] /doc/: The /doc/ directory is browsable. This may be /usr/
doc.
+ [001384] /?=PHPB8B5F2A0-3C92-11d3-A3A9-4C7B08C10000: PHP Easter Eggs
reveal
potentially sensitive information.
+ [001795] /phpMyAdmin/changelog.php: phpMyAdmin is for managing MySQL
databases,
and should be protected or limited to authorized hosts.
```

```
+ [001796] /phpMyAdmin/ChangeLog: phpMyAdmin is for managing MySQL
databases.
+ [750500] /test/: Directory indexing found.
+ [002989] /phpinfo.php: PHP is installed, and a test script which runs
phpinfo() was found.
+ [003584] /icons/README: Apache default file found.
```

3.4.2 Analysis of Nikto Findings

The Nikto scan revealed critical web security issues:

Outdated Software The web server is running Apache 2.2.8 (released in 2008) and PHP 5.2.4 (released in 2007). Both are significantly outdated and contain hundreds of known vulnerabilities. Modern versions (Apache 2.4.66 and PHP 8.5.1) are available and should be deployed immediately.

HTTP TRACE Method Enabled The HTTP TRACE method is enabled, which allows Cross-Site Tracing (XST) attacks. Attackers can use this to obtain sensitive information such as cookies, which could lead to session hijacking.

Information Disclosure The presence of `phpinfo.php` and PHP Easter eggs reveals detailed system configuration information. This information can be used by attackers to identify vulnerable components and plan attacks.

phpMyAdmin Exposure phpMyAdmin provides a web interface to the MySQL database. If accessed by attackers, they could attempt to brute force credentials, exploit known vulnerabilities in phpMyAdmin, or directly access the database.

Directory Indexing Multiple directories (`/icons/`, `/doc/`, `/test/`) have directory indexing enabled, allowing anyone to browse the contents of these folders. This can lead to information leakage and identification of sensitive files.

Missing Security Headers The server does not implement critical security headers:

- Content-Security-Policy (CSP) – Prevents XSS and data injection
- Strict-Transport-Security (HSTS) – Enforces HTTPS
- X-Content-Type-Options – Prevents MIME type sniffing
- Referrer-Policy – Controls referrer information
- Permissions-Policy – Restricts browser features

4 Detailed Findings

4.1 Complete Service Enumeration Results

The following table presents all open ports discovered during the assessment:

Port	Service	Version / Information	
21	FTP	vsftpd 2.3.4	(CRITICAL)
22	SSH	OpenSSH 4.7p1	(HIGH)
23	Telnet	Linux telnetd	(CRITICAL)
25	SMTP	Postfix smtpd	
53	DNS	ISC BIND 9.4.2	
80	HTTP	Apache 2.2.8	(HIGH)
111	RPC	rpcbind	
139	NetBIOS	Samba 3.x	(CRITICAL)
445	SMB	Samba 3.x	(CRITICAL)
512	exec	r-exec	(MEDIUM)
513	login	rlogin	(MEDIUM)
514	shell	rshell	(MEDIUM)
1099	RMI	Java RMI Registry	(HIGH)
1524	ingreslock	Unknown	
2049	NFS	NFS	
2121	FTP	CCProxy FTP	
3306	MySQL	MySQL 5.0.51a	(HIGH)
5432	PostgreSQL	PostgreSQL 8.3	(HIGH)
5900	VNC	VNC	
6000	X11	X Window System	
6667	IRC	UnrealIRCd	(CRITICAL)
8180	Tomcat	Apache Tomcat	

4.2 Detailed Critical Vulnerability Analysis

4.2.1 vsftpd 2.3.4 Backdoor (CVE-2011-2523)

CRITICAL – CVSS: 10.0

Description: vsftpd 2.3.4 contains a backdoor that allows remote attackers to execute arbitrary commands with root privileges. The backdoor was introduced through a compromise of the vsftpd source code distribution.

Attack Vector: When a username containing the ":" character is provided, the server spawns a root shell on port 6200.

Exploit Available: Yes, publicly available in Metasploit Framework.

Impact: Full root access to the system without any authentication.

Proof: Nmap script successfully executed id command and received uid=0(root) gid=0(root).

Remediation: Upgrade to vsftpd 3.0.0 or newer, or disable the FTP service entirely.

References: <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2523>

4.2.2 UnrealIRCd Backdoor (CVE-2010-4344)

CRITICAL – CVSS: 9.8

Description: A backdoor was introduced in UnrealIRCd 3.2.8.1 through a compromise of the official source code distribution.

Attack Vector: Remote attackers can execute arbitrary commands on the server with the privileges of the IRC daemon.

Exploit Available: Yes, public exploit available.

Impact: Complete system compromise, potentially leading to further network attacks.

Remediation: Disable the UnrealIRCd service immediately.

References: <http://seclists.org/fulldisclosure/2010/Jun/277>

4.2.3 Samba Command Injection (CVE-2007-2447)

CRITICAL – CVSS: 9.3

Description: Samba 3.x contains a vulnerability in the username map script functionality that allows remote command injection.

Attack Vector: An attacker can inject arbitrary commands through the username map script parameter.

Exploit Available: Yes, publicly available in Metasploit Framework.

Impact: Unauthenticated remote code execution with root privileges.

Remediation: Upgrade Samba to version 4.x or apply security patches.

References: <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2447>

4.2.4 SSL/TLS CCS Injection (CVE-2014-0224)

CRITICAL – CVSS: 7.5

Description: OpenSSL before 0.9.8za, 1.0.0 before 1.0.0m, and 1.0.1 before 1.0.1h does not properly restrict processing of ChangeCipherSpec messages.

Attack Vector: Man-in-the-middle attackers can trigger use of a zero-length master key.

Impact: Session hijacking and sensitive information disclosure.

Remediation: Update OpenSSL to version 1.0.1h or newer.

References: <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-0224>

4.2.5 SSL POODLE (CVE-2014-3566)

CRITICAL – CVSS: 7.5

Description: The SSL protocol 3.0 uses nondeterministic CBC padding, which makes it easier for man-in-the-middle attackers to obtain cleartext data.

Attack Vector: Padding-oracle attack on SSLv3 connections.

Impact: Information disclosure, potentially exposing sensitive data.

Remediation: Disable SSLv3 support and use TLS 1.2 or higher exclusively.

References: <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-3566>

4.3 Web Application Vulnerabilities Analysis

Finding	Severity	Impact
Apache 2.2.8 Outdated	High	Over 100 known vulnerabilities, including RCE and DoS
PHP 5.2.4 Outdated	High	Over 300 known vulnerabilities, unpatched
HTTP TRACE Enabled	High	Cross-Site Tracing (XST) attacks possible
phpinfo.php Exposed	Medium	System configuration information disclosure
phpMyAdmin Exposed	Medium	Database access risk and potential compromise
Directory Indexing	Low	Information leakage through directory browsing
Missing Security Headers	Low	Various attack vectors (XSS, clickjacking)

4.4 High Vulnerabilities

4.4.1 Apache 2.2.8 Outdated

HIGH

Current Version: 2.2.8 (Released: January 2008)

Latest Stable: 2.4.66 (Released: August 2024)

Years Outdated: 16+ years

Known CVEs: Over 100 documented vulnerabilities

Impact: Remote code execution, denial of service, information disclosure

Remediation: Upgrade to Apache 2.4.x immediately

4.4.2 PHP 5.2.4 Outdated

HIGH

Current Version: 5.2.4 (Released: September 2007)

Latest Stable: 8.5.1 (Released: August 2024)

Years Outdated: 17+ years

Known CVEs: Over 300 documented vulnerabilities

Impact: Remote code execution, denial of service, information disclosure, SQL injection

Remediation: Upgrade to PHP 8.x immediately

4.4.3 HTTP TRACE Method Enabled

HIGH

Vulnerability: Cross-Site Tracing (XST)

Impact: Credential theft through Cross-Site Scripting (XSS) attacks

Attack Vector: TRACE requests reveal cookies and authentication headers

Remediation: Disable TRACE method in Apache configuration (TraceEnable Off)

5 Remediation Plan

5.1 Priority 1 – Immediate (24-72 Hours)

These vulnerabilities pose an immediate threat to the organization and must be addressed as a matter of urgency.

Action	Implementation Details
vsftpd 2.3.4	<code>sudo systemctl stop vsftpd</code> – Disable or upgrade to 3.0.0+
UnrealIRCd	<code>sudo systemctl stop unrealircd</code> – Disable service permanently
Telnet	<code>sudo systemctl stop telnetd</code> – Disable and use SSH exclusively
Samba 3.x	<code>sudo apt update && sudo apt upgrade samba</code> – Upgrade to 4.x
SSL/TLS	<code>sudo apt update && sudo apt upgrade openssl</code> – Update OpenSSL and disable SSLv3

5.2 Priority 2 – Short Term (7-10 Days)

These vulnerabilities should be addressed within the next week to reduce the attack surface.

Action	Implementation Details
Apache 2.2.8	<code>sudo apt update && sudo apt upgrade apache2</code> – Upgrade to 2.4.x
PHP 5.2.4	<code>sudo apt update && sudo apt upgrade php</code> – Upgrade to PHP 8.x
HTTP TRACE	Add <code>TraceEnable Off</code> to <code>/etc/apache2/apache2.conf</code>
phpinfo.php	<code>sudo rm /var/www/phpinfo.php</code> – Remove or restrict access
phpMyAdmin	Restrict with <code>.htaccess</code> or remove if not needed
OpenSSH 4.7p1	<code>sudo apt update && sudo apt upgrade openssh-server</code>

5.3 Priority 3 – Long Term (30 Days)

These vulnerabilities require planning and should be addressed within the next month.

Action	Implementation Details
Network Segmentation	Isolate vulnerable services on separate network segments
Firewall Configuration	Implement iptables/ufw rules to restrict unnecessary access
Patch Management	Establish a formal patch management policy and schedule
Database Upgrades	<code>sudo apt update</code> MySQL and PostgreSQL to supported versions
Directory Indexing	Disable directory indexing in Apache configuration
Security Headers	Implement CSP, HSTS, X-Content-Type-Options headers

5.4 Priority 4 – Ongoing

These are continuous security practices to maintain a secure environment.

Action	Implementation Details
CVE Monitoring	Subscribe to CVE alerts and security mailing lists
Security Assessments	Schedule quarterly vulnerability scanning
Documentation	Maintain up-to-date security documentation
Security Training	Provide security awareness training to staff
Incident Response	Develop and maintain an incident response plan

5.5 Recommended Security Hardening Checklist

1. Disable all unnecessary services (vsftpd, UnrealIRCd, Telnet, VNC, r-services)
2. Upgrade all out-of-date software (Apache, PHP, MySQL, PostgreSQL, OpenSSH)
3. Configure firewall to allow only necessary ports (22, 80, 443)
4. Implement strong password policies and multi-factor authentication
5. Enable comprehensive logging and monitoring
6. Implement security headers for web applications
7. Remove sensitive files (phpinfo.php, test pages, default files)
8. Disable directory indexing and HTTP TRACE method
9. Regularly backup system data and configurations
10. Conduct regular security assessments and penetration testing

6 Appendices

6.1 Appendix A: Complete Vulnerability List with CVSS Scores

CVE	Description	CVSS
CVE-2011-2523	vsftpd 2.3.4 Backdoor – Remote root access	10.0
CVE-2010-4344	UnrealIRCd Backdoor – Remote code execution	9.8
CVE-2007-2447	Samba Command Injection – Remote code execution	9.3
CVE-2014-0224	SSL/TLS CCS Injection – Session hijacking	7.5
CVE-2014-3566	SSL POODLE – Information disclosure	7.5
CVE-2015-4000	Logjam Attack – MITM downgrade attack	7.5
CVE-2008-0166	Debian Weak PRNG – Weak cryptographic keys	7.5
CVE-2004-2687	OpenSSL Weak Ciphers – Weak encryption	5.0

6.2 Appendix B: Complete Scan Outputs

The following files contain the complete output of the scans performed:

- **Service Scan:** `nmap_fast.txt` – Contains open ports and service versions
- **Vulnerability Scan:** `nmap_vuln.txt` – Contains all discovered vulnerabilities
- **Full Scan:** `nmap_full_scan.txt` – Contains complete port scan (65,535 ports)
- **Web Vulnerability Scan:** `nikto_report.txt` – Contains web application vulnerabilities

6.3 Appendix C: Sample Exploit Output with Explanation

The following output demonstrates successful exploitation of the vsftpd backdoor vulnerability:

```
# From nmap vulnerability scan - demonstrating exploitation
$ nmap --script vuln 192.168.56.101

| ftp-vsftpd-backdoor:
|   VULNERABLE:
|     vsFTPD version 2.3.4 backdoor
|       State: VULNERABLE (Exploitable)
|       IDs:   BID:48539   CVE:CVE-2011-2523
|       Disclosure date: 2011-07-03
|       Exploit results:
|         Shell command: id
|         Results: uid=0(root) gid=0(root)
|       References:
|         https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2523

# Explanation of the exploit:
# This output shows that the backdoor successfully executed the 'id'
#   command
# and returned 'uid=0(root) gid=0(root)' which confirms:
```

```
# 1. The backdoor is present and functional
# 2. Commands can be executed with root privileges
# 3. NO authentication is required to exploit this vulnerability
# 4. An attacker would have FULL SYSTEM ACCESS
```

6.4 Appendix D: Risk Prioritization Matrix

The following matrix defines how vulnerabilities were prioritized based on CVSS scores:

Priority	CVSS Range	Action Required
P1 – Critical	9.0 - 10.0	Immediate fix required within 24-72 hours
P2 – High	7.0 - 8.9	Scheduled upgrade within 7-10 days
P3 – Medium	4.0 - 6.9	Planned remediation within 30 days
P4 – Low	0.0 - 3.9	Monitor and maintain as part of ongoing security


6.5 Appendix E: Tool Installation Commands

```
# Install Nmap
sudo apt update
sudo apt install nmap -y

# Install Nikto
sudo apt install nikto -y

# Install Metasploit (optional, for exploit testing)
sudo apt install metasploit-framework -y

# Install dependencies for scanning
sudo apt install python3-pip -y
```



Thank You

Prepared with diligence by

Daaniya Absar

ProGree Internship Program

Confidential – For Internal Review Only