

RWorksheet_Labanero-3.R

r2249529

2023-10-08

```
#Number 1:
```

```
#A.
```

```
LETTERS
```

```
## [1] "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X"
letters
```

```
## [1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x"
first_11_letters <- LETTERS[1:11]
first_11_letters
```

```
## [1] "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K"
```

```
#B.
```

```
odd_numbers <- seq(1, 26, by = 2)
odd_letters <- LETTERS[odd_numbers]
odd_letters
```

```
## [1] "A" "C" "E" "G" "I" "K" "M" "O" "Q" "S" "U" "W" "Y"
```

```
#C.
```

```
vowels <- LETTERS[LETTERS %in% c("A", "E", "I", "O", "U")]
vowels
```

```
## [1] "A" "E" "I" "O" "U"
```

```
#D.
```

```
last_5_low <- tail(letters, 5)
last_5_low
```

```
## [1] "v" "w" "x" "y" "z"
```

```
#E.
```

```
letters15to24 <- letters[15:24]
letters15to24
```

```
## [1] "o" "p" "q" "r" "s" "t" "u" "v" "w" "x"
```

```
#Number 2:
```

```
#A. The result is that city is a vector with specified city.
```

```
city <- c("Tuguegarao City", "Manila", "Iloilo City", "Tacloban", "Samal Island", "Davao City")
city
```

```
## [1] "Tuguegarao City" "Manila" "Iloilo City" "Tacloban" "Samal Island" "Davao"
```

#B. The result is that temp is a vector with specified temperatures

```
temp <- c(42, 39, 34, 34, 30, 27)
temp
```

```
## [1] 42 39 34 34 30 27
```

#C. The result is now a data frame which it combines the city and temp

```
data <- data.frame(City = city, Temperature = temp)
data
```

```
##           City Temperature
## 1 Tuguegarao City         42
## 2      Manila           39
## 3   Iloilo City           34
## 4    Tacloban           34
## 5  Samal Island           30
## 6   Davao City           27
```

#D. The column names now changed to City and Temperature

```
names(data) <- c("City", "Temperature")
names(data)
```

```
## [1] "City"      "Temperature"
```

#Number 3:

#E The result the str() function will display the structure of dataframe "data"
`str(data)`

```
## 'data.frame':   6 obs. of  2 variables:
##  $ City      : chr  "Tuguegarao City" "Manila" "Iloilo City" "Tacloban" ...
##  $ Temperature: num  42 39 34 34 30 27
```

#F it will retrieve the content of row 3 and row 4

```
data[3, ]
```

```
##           City Temperature
## 3 Iloilo City           34
```

```
data[4, ]
```

```
##           City Temperature
## 4 Tacloban           34
```

#G The result will Display that City with the highest and lowest temperature

```
max_temp_city <- data[data$Temperature == max(data$Temperature), "City"]
min_temp_city <- data[data$Temperature == min(data$Temperature), "City"]
max_temp_city
```

```
## [1] "Tuguegarao City"
```

```
min_temp_city
```

```
## [1] "Davao City"
```

USING MATRIX

#Number 2:

#row = 2

```
dab <- matrix(c(5,6,7,4,3,2,1,2,3,7,8,9), nrow = 2)
dab
```

```
##      [,1] [,2] [,3] [,4] [,5] [,6]
```

```
## [1,] 5 7 3 1 3 8
## [2,] 6 4 2 2 7 9
```

#row = 3 and column = 2

```
matrix(data = c(3,4,5,6,7,8),3,2)
```

```
##      [,1] [,2]
## [1,] 3    6
## [2,] 4    7
## [3,] 5    8
```

```
matrix (data)
```

```
##      [,1]
## [1,] character,6
## [2,] numeric,6
```

#creating a diagonal matrix where value will always be 1

```
diag(1,nrow=6,ncol = 5)
```

```
##      [,1] [,2] [,3] [,4] [,5]
## [1,] 1    0    0    0    0
## [2,] 0    1    0    0    0
## [3,] 0    0    1    0    0
## [4,] 0    0    0    1    0
## [5,] 0    0    0    0    1
## [6,] 0    0    0    0    0
```

```
diag(6)
```

```
##      [,1] [,2] [,3] [,4] [,5] [,6]
## [1,] 1    0    0    0    0    0
## [2,] 0    1    0    0    0    0
## [3,] 0    0    1    0    0    0
## [4,] 0    0    0    1    0    0
## [5,] 0    0    0    0    1    0
## [6,] 0    0    0    0    0    1
```

#Number 2:

#A.

```
matrix(c(1:8, 11:14), nrow = 3, ncol = 4)
```

```
##      [,1] [,2] [,3] [,4]
## [1,] 1    4    7    12
## [2,] 2    5    8    13
## [3,] 3    6    11   14
```

#RESULT: [,1] [,2] [,3] [,4]

#[1,] 1 4 7 12

#[2,] 2 5 8 13

#[3,] 3 6 11 14

#B.

```
matrix(c(1:8, 11:14), nrow = 3, ncol = 4) * 2
```

```
##      [,1] [,2] [,3] [,4]
## [1,] 2    8    14   24
## [2,] 4   10   16   26
## [3,] 6   12   22   28
```

```

#Result is value is multiplied by 2:
#      [,1] [,2] [,3] [,4]
#[1,]    2    8   14   24
#[2,]    4   10   16   26
#[3,]    6   12   22   28
#C: Result content of row to = 2 5 8 13
matrix_data <- matrix(c(1:8, 11:14), nrow = 3, ncol = 4)
matrix_data[2, ]

```

```
## [1]  2  5  8 13
```

```

#D
matrix_data <- matrix(c(1:8, 11:14), nrow = 3, ncol = 4)
matrix_data[1:2, 3:4]

```

```

##      [,1] [,2]
## [1,]    7   12
## [2,]    8   13

```

```

#OUTPUT:      [,1] [,2]
# [1,]      7   12
# [2,]      8   13

```

```

#E
matrix_data <- matrix(c(1:8, 11:14), nrow = 3, ncol = 4)
matrix_data[3, 2:3]

```

```
## [1]  6 11
```

```
#OUTPUT: 6 11
```

```

#F
matrix_data <- matrix(c(1:8, 11:14), nrow = 3, ncol = 4)
matrix_data[, 4]

```

```
## [1] 12 13 14
```

```
#OUTPUT: 12 13 14
```

```

#G
matrix_data <- matrix(c(1:8, 11:14), nrow = 3, ncol = 4)
matrix_data

```

```

##      [,1] [,2] [,3] [,4]
## [1,]    1    4    7   12
## [2,]    2    5    8   13
## [3,]    3    6   11   14

```

```

#OUTPUT:      [,1] [,2] [,3] [,4]
# [1,]      1    4    7   12
# [2,]      2    5    8   13
# [3,]      3    6   11   14
rownames(matrix_data) <- c("isa", "dalawa", "tatlo")
rownames(matrix_data)

```

```
## [1] "isa"      "dalawa" "tatlo"
```

```

#OUTPUT: "isa"      "dalawa" "tatlo"
colnames(matrix_data) <- c("uno", "dos", "tres", "quattro")
colnames(matrix_data)

```

```
## [1] "uno"      "dos"      "tres"     "quattro"
```

```

#OUTPUT: "uno"      "dos"      "tres"      "quatro"
#H
library(dplyr)
matrix_data <- matrix(c(1:8, 11:14), nrow = 3, ncol = 4)
new_matrix <- matrix_data %>% t() %>% as.vector() %>% matrix(ncol = 2)

#USING ARRAYS

#Number 3: # B: result array has 3 dimensions: 2 rows, 4 columns, and 2 "layers" (depth). So, it is a t
# Given numeric values
values <- c(1, 2, 3, 6, 7, 8, 9, 0, 3, 4, 5, 1)

matrix_data <- matrix(rep(values, each = 2), nrow = 2)

array_data <- array(matrix_data, dim = c(2, 4, 2))

rownames(array_data) <- c("a", "b")
colnames(array_data) <- c("A", "B", "C", "D")

# Assign names to the dimensions
dimnames(array_data) <- list(
  "1st-Dimensional Array" = rownames(array_data),
  "2nd-Dimensional Array" = colnames(array_data),
  "3rd-Dimensional Array" = NULL
)
print(array_data)

## , , 1
##
##                2nd-Dimensional Array
## 1st-Dimensional Array A B C D
##                a 1 2 3 6
##                b 1 2 3 6
##
## , , 2
##
##                2nd-Dimensional Array
## 1st-Dimensional Array A B C D
##                a 7 8 9 0
##                b 7 8 9 0

```