

# Lab Notebook

## Pupil Reconstruction

Daniel Carmona

## Contents

<b>1</b>	<b>Amplitude and Phase Reconstruction</b>	<b>2</b>
<b>2</b>	<b>PSF Reconstruction</b>	<b>8</b>

# 1 Amplitude and Phase Reconstruction

16 February 2024

- Create new github branch: `AmpPhaseReconstructionRetraining`
  - Download the following the files from Morgana:
    - `superK_slmcube_20230625_complsines-01sp_07`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file00`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file01`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file02`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file03`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file04`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file05`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file06`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file07`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file08`
    - `slmcube_20230625_complsines-01sp_07_PSFWFs_file09`
  - Data processing for Fully Convolutional NN training
  - One fast experiment for each file: very good results, around 0.05 validation mse
-

**19 February 2024**

- Remove normalization from amplitude and phase for the fully connected experiments

---

## **EXPERIMENT NewFC10000-Processed 2**

HYPERPARAMETERS:

**\*ARCHITECTURE HYPERPARAMETERS:**

- Fully Connected
- Input shape: 1320
- Output shape: (2, 96, 96)
- Hidden layers: [2000, 2000, 2000, 2000]
- Regularizer: None
- Hidden Layers Activation: relu
- Output Layer Activation: linear
- Batch Normalization: False
- Dropout: False, 0.2

**\*COMPILE HYPERPARAMETERS:**

- Optimizer: ADAM lr=0.001, beta\_1=0.9, beta\_2=0.999
- Loss Function: MSE
- Metric: MSE

**\*TRAINING HYPERPARAMETERS :**

- Epochs: 200
- Batch size: 64
- Callbacks:
  - ReduceLROnPlateau: MSE 10 x0.1
  - Early Stop: MSE 25

**VISUALIZATION:****\*RESULTS :**

- Train MSE: 0.035130929201841354
- Validation MSE: 0.0786573588848114




Figure 1: Results of training the model NewFC10000-Processed 2

**EXPERIMENT NewFC30000-Processed-1**

## HYPERPARAMETERS:

**\*ARCHITECTURE HYPERPARAMETERS:**

- Fully Connected
- Input shape: 1320
- Output shape: (2, 96, 96)
- Hidden layers: [2000, 2000, 2000, 2000]
- Regularizer: None
- Hidden Layers Activation: relu
- Output Layer Activation: linear
- Batch Normalization: False
- Dropout: False, 0.2

**\*COMPILE HYPERPARAMETERS:**

- Optimizer: ADAM lr=0.001, beta\_1=0.9, beta\_2=0.999
- Loss Function: MSE
- Metric: MSE

**\*TRAINING HYPERPARAMETERS:**

- Epochs: 200
- Batch size: 64
- Callbacks:
  - ReduceLROnPlateau: MSE 10 x0.1
  - Early Stop: MSE 25

## VISUALIZATION:

**\*RESULTS :**

-Train MSE: 0.0357743538916111

-Validation MSE: 0.057852283120155334




Figure 2: Results of training the model NewFC30000-Processed-1

**EXPERIMENT NewFC80000-Processed-1**

## HYPERPARAMETERS:

**\*ARCHITECTURE HYPERPARAMETERS :**

- Fully Connected
- Input shape: 1320
- Output shape: (2, 96, 96)
- Hidden layers: [2000, 2000, 2000, 2000]
- Regularizer: None
- Hidden Layers Activation: relu

```
-Output Layer Activation: linear
```

```
-Batch Normalization: False
```

```
-Dropout: False, 0.2
```

```
*COMPILATION HYPERPARAMETERS:
```

```
-Optimizer: ADAM lr=0.001, beta_1=0.9, beta_2=0.999
```

```
-Loss Function: MSE
```

```
-Metric: MSE
```

```
*TRAINING HYPERPARAMETERS:
```

```
-Epochs: 200
```

```
-Batch size: 64
```

```
-Callbacks:
```

```
-ReduceLROnPlateau: MSE 10 x0.1
```

```
-Early Stop: MSE 25
```

## VISUALIZATION:

```
*RESULTS:
```

```
-Train MSE: 0.03301804140210152
```

```
-Validation MSE: 0.04487497732043266
```






Figure 3: Results of training the model NewFC80000-Processed-1

## 2 PSF Reconstruction