

Lab Notebook

Pupil Reconstruction

Daniel Carmona

Contents

1	Amplitude and Phase Reconstruction	2
2	PSF Reconstruction	10

1 Amplitude and Phase Reconstruction

16 February 2024

- Create new github branch: `AmpPhaseReconstructionRetraining`
 - Download the following the files from Morgana:
 - `superK_slmcube_20230625_complsines-01sp_07`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file00`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file01`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file02`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file03`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file04`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file05`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file06`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file07`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file08`
 - `slmcube_20230625_complsines-01sp_07_PSFWFs_file09`
 - Data processing for Fully Convolutional NN training
 - One fast experiment for each file: very good results, around 0.05 validation mse
-

19 February 2024

- Remove normalization from amplitude and phase for the fully connected experiments
-

EXPERIMENT NewFC10000-Processed 2

HYPERPARAMETERS:

***ARCHITECTURE HYPERPARAMETERS:**

- Fully Connected
- Input shape: 1320
- Output shape: (2, 96, 96)
- Hidden layers: [2000, 2000, 2000, 2000]
- Regularizer: None
- Hidden Layers Activation: relu
- Output Layer Activation: linear
- Batch Normalization: False
- Dropout: False, 0.2

***COMPILE HYPERPARAMETERS:**

- Optimizer: ADAM lr=0.001, beta_1=0.9, beta_2=0.999
- Loss Function: MSE
- Metric: MSE

***TRAINING HYPERPARAMETERS :**

- Epochs: 200
- Batch size: 64
- Callbacks:
 - ReduceLROnPlateau: MSE 10 x0.1
 - Early Stop: MSE 25

VISUALIZATION:***RESULTS :**

- Train MSE: 0.035130929201841354
- Validation MSE: 0.0786573588848114




Figure 1: Results of training the model NewFC10000-Processed 2

EXPERIMENT NewFC30000-Processed-1

HYPERPARAMETERS:

***ARCHITECTURE HYPERPARAMETERS:**

- Fully Connected
- Input shape: 1320
- Output shape: (2, 96, 96)
- Hidden layers: [2000, 2000, 2000, 2000]
- Regularizer: None
- Hidden Layers Activation: relu
- Output Layer Activation: linear
- Batch Normalization: False
- Dropout: False, 0.2

***COMPILE HYPERPARAMETERS:**

- Optimizer: ADAM lr=0.001, beta_1=0.9, beta_2=0.999
- Loss Function: MSE
- Metric: MSE

***TRAINING HYPERPARAMETERS:**

- Epochs: 200
- Batch size: 64
- Callbacks:
 - ReduceLROnPlateau: MSE 10 x0.1
 - Early Stop: MSE 25

VISUALIZATION:

***RESULTS :**

-Train MSE: 0.0357743538916111

-Validation MSE: 0.057852283120155334




Figure 2: Results of training the model NewFC30000-Processed-1

EXPERIMENT NewFC80000-Processed-1

HYPERPARAMETERS:

***ARCHITECTURE HYPERPARAMETERS :**

- Fully Connected
- Input shape: 1320
- Output shape: (2, 96, 96)
- Hidden layers: [2000, 2000, 2000, 2000]
- Regularizer: None
- Hidden Layers Activation: relu

```
-Output Layer Activation: linear
```

```
-Batch Normalization: False
```

```
-Dropout: False, 0.2
```

```
*COMPILATION HYPERPARAMETERS:
```

```
-Optimizer: ADAM lr=0.001, beta_1=0.9, beta_2=0.999
```

```
-Loss Function: MSE
```

```
-Metric: MSE
```

```
*TRAINING HYPERPARAMETERS:
```

```
-Epochs: 200
```

```
-Batch size: 64
```

```
-Callbacks:
```

```
-ReduceLROnPlateau: MSE 10 x0.1
```

```
-Early Stop: MSE 25
```

VISUALIZATION:

```
*RESULTS:
```

```
-Train MSE: 0.03301804140210152
```

```
-Validation MSE: 0.04487497732043266
```





Figure 3: Results of training the model NewFC80000-Processed-1

- Normalize and split fluxes in train, validation and test files
- Stack amplitude and phase arrays and save in train, validation and test files

EXPERIMENT NewConv10000-1

HYPERPARAMETERS:

*ARCHITECTURE HYPERPARAMETERS :

-Convolutional

-Input shape: (55, 24, 1)

-Output shape: (96, 96, 2)

-Convolutional Layers: [128, 256, 512]

-Convolutonal Kernels: [(3, 3), (3, 3), (3, 3)]

```
-Fully Connected Hidden layers: [4096, 2048, 2048, 1024, 1024, 1024]
-Regularizer: None
-Convolutional Activation: relu
-Hidden Layers Activation: relu
-Output Layer Activation: linear
-Batch Normalization: True
```

***COMPILATION HYPERPARAMETERS:**

```
-Optimizer: ADAM lr=0.001, beta_1=0.9, beta_2=0.999
-Loss Function: MSE
-Metric: MSE
```

*** TRAINING HYPERPARAMETERS:**

```
-Epochs: 200
-Batch size: 32
-Callbacks:
  -ReduceLROnPlateau: MSE 15 x0.1
  -Early Stop: MSE 50
```

VISUALIZATION:

***RESULTS:**

```
-Train MSE: 0.031087761744856834
-Validation MSE: 0.09376049041748047
```




Figure 4: Results of training the model NewConv10000-1

2 PSF Reconstruction