VECTOR

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

VECTOR

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

VECTOR

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

VECTOR

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

VECTOR

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER
A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION
A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION
A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

VECTOR

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

VECTOR

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER
   A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.
   B. DO NOT TWIST, KINK, or otherwise mishandle this belt.
2. DURING INSTALLATION
   A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.
3. TENSION
   A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.
   B. DO NOT OVER TENSION.
   C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

VECTOR

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER
A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION
A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION
A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.

VECTOR

Keilrippenriemen
Ribbed V-belt
Courroie striée
Multi V-riem
Cinghia trapezoidale nervata
Correa nervada
Correia estriada
Fortandet rem
Поликлиновой ремень
Oluklu V kayışı
Pasek wieloklinowy

1 Pc

REGISTERED COMPANY ISO 9001: 2000

EAC

VECTOR

SUGGESTIONS:

1. UPON REMOVAL FROM CONTAINER

A. DO NOT BEND OR FOLD THE BELT IN ANY RADIUS smaller than the smallest pulley in the drive.

B. DO NOT TWIST, KINK, or otherwise mishandle this belt.

2. DURING INSTALLATION

A. If the belt will not load into the pulley positions without force or prying, recheck procedures for proper slack to allow a smooth, unforced installation.

3. TENSION

A. Due to the varying requirements of precision synchronous drives, belt tension should always be set according to car manufacturer's specifications.

B. DO NOT OVER TENSION.

C. Once properly tensioned, retensioning is usually not necessary, consult vehicle manufacturer's service manual.