

TWO-TAC LLC DBA

AMERI ECANS

SELECT EQUIPMENT OVERVIEW



Doing whatever it takes,



To stand unrivaled in our field



BOOTWASH STATION



DESCRIPTION

- Total Functional Areas: 1 open bootwash and gear-rinse station.
- Stall Types & Features: 4 handheld washdown lines co-located with a stability bar to support thorough rinse from all angles.
- Interior Features: Climate-controlled container interior designed for rugged, wet, muddy environments.
- Comfort & Climate Control: Temperature-regulated
- Accessibility Features: Two ingress/egress points supporting one-way foot-traffic flowthrough from one side to the other.
- AMERI-CANS Build Notes: Helps prevent “goop creep” by stopping mud, grime, and jobsite mess from reaching common areas, break tents, offices, or parking lots; supports site cleanliness, safety, and professionalism.

CRITICAL SPECIFICATIONS

- Power Requirements: 1x50A/240v CS6364C inlet.
- Fresh Water Capacity: 400 gallons onboard water storage.
- Waste Capacity: Dependent on site drainage or collection design.
- Footprint (Required Pad): 20' L x 10' W level, packed surface.
- Additional Technical Notes: Requires grounding once permanent electrical service is connected and improved road access within 20' of entry doors.



CRITICAL SPECS



Type	Nomenclature	Total Compartments	Total Women's Compartment Toilets	Total Men's Compartment Toilets	Individual Compartment Toilets	Urinals	Sinks	Overall Length (w/Tongue)	Overall Width (stairs down)	Overall Height	Tare Weight	Onboard Water Capacity (gal)	Onboard Waste Capacity (gal)	Evacuation / Dump Valve Size	City Fill Size	Power Supply	Minimum Functional Power (without heat)	MOCP Rating
Restroom Trailer	8-Stall	8	N/A	N/A	8	8	8	35	11ft	11.5ft	12,940 lbs	400 (2x200)	1000	3"	Std. Garden Hose	1x50A/240v Cali-Standard (CS6364C) Inlet or 3x 20A/120v	2x 20A/120v	50A
Restroom Trailer	10-Station	2	5	2	N/A	3	4	29	11ft	11.5ft	11,900 lbs	200	1000	3"	Std. Garden Hose	1x50A/240v Cali-Standard (CS6364C) Inlet or 3x 20A/120v	2x 20A/120v	50A
Seacan Restroom	10-Stall	10	N/A	N/A	10	8	10	40ft	8.5ft	9.5ft	22,000 lbs	1000	1100	3"	N/A	1x100A/240v direct to panel or Series 16 Cam connections	1x100A/240v	100A
Restroom Trailer	10-Station	2	5	2	N/A	3	4	30ft	12.6ft	11.8ft	9,800 lbs	200	950	2"	Std. Garden Hose	4x30A/120v NEMA L5-30 Twist Lock 120v or 4x 15A/120v	2x 15A/120v	30A
Restroom Trailer	4-Stall	4	N/A	N/A	4	0	4	19ft	7.6ft	11.3	5,280 lbs	200	440	2"	Std. Garden Hose	3x30A/120v NEMA L5-30 Twist Lock 120v or 3x 15A/120v	2x15A/120v	30A
Restroom Trailer	4-Stall	4	N/A	N/A	4	2	4	23ft	11ft	11.3	6,960 lbs	200	480	3"	Std. Garden Hose	1x50A/240v Cali-Standard (CS6364C) Inlet or 3x 20A/120v	2x 20A/120v	50A
Seacan Restroom	10-Station-F (Flushing)	2	2	6	N/A	2	3	40ft	8.5ft	9.5ft	26,000 lbs	850	1000	2"	N/A	1x100A/240v direct to panel or Series 16 Cam connections	1x100A/240v	100A
Seacan Restroom	12-Station-Handwash (non-Flushing)	2	2	8	N/A	2	3	40ft	8.5ft	9.5ft	22,000 lbs	270 (3x90gal)	250	2"	N/A	1x100A/240v direct to panel or Series 16 Cam connections	1x100A/240v	100A
Seacan Restroom	15-Station (non-Flushing)	2	3	10	N/A	2	0	40ft	8.5ft	9.5ft	20,000 lbs	N/A	N/A	N/A	N/A	1x100A/240v direct to panel or Series 16 Cam connections	1x100A/240v	100A
Seacan Utility	Bootwash	1	N/A	N/A	N/A	N/A	N/A	20ft	8ft	9.5ft	8,000 lbs	400 (x2 200)	N/A	N/A	N/A	1x50A/240v Cali-Standard (CS6364C) Inlet	1x50A/240v	30A
Restrom Shower	8-Stall	8	N/A	N/A	N/A	N/A	8	32ft	10.5ft	11.6ft	12,500 lbs	200	1100	2"	Std. Garden Hose	4x30A/120v NEMA L5-30 Twist Lock 120v or 4x 15A/120v	2x 15A/120v	30A