

Two-Tac LLC dba



SELECT EQUIPMENT OVERVIEW



Doing whatever it takes,



To stand unrivaled in our field



MARK IV – 10-STALL FLUSHING SEACAN w/ HOT WATER SINKS



DESCRIPTION

- Total Functional Areas: 10 private, exterior-entry stalls.
- Stall Types & Features: 8 stalls with urinals and 2 without; all equipped with flushing toilets, hot handwash, and hand dryers; access-enabled entry compatible with connected jobsite systems.
- Interior Features: Dedicated supply and return HVAC per stall; wall-mounted fixtures; water-proof, reinforced industrial flooring; winterized.
- Comfort & Climate Control: Full climate control in each stall
- Accessibility Features: Exterior-entry private stalls for flexible user flow.
- AMERI-CANS Build Notes: ~1,000 flushed uses per service cycle*; engineered to raise the standard, reduce cleaning time and exposure.
* Use capacity will increase with urinal use instead of toilet.

CRITICAL SPECIFICATIONS

- Power Requirements: 100A(per leg)/240v/Single Phase Series 16 camlocks or bypass to panel
- Fresh Water Capacity: 1000 gallons
- Waste Capacity: 1100 gallons
- Footprint (Required Pad): 40' L x 10' W level, packed surface.
- Additional Technical Notes: Requires grounding and improved road access within 20' of entry doors.



CRITICAL SPECS



Type	Nomenclature	Total Compartments	Total Women's Compartment Toilets	Total Men's Compartment Toilets	Individual Compartment Toilets	Urinals	Sinks	Overall Length (w/Tongue)	Overall Width (stairs down)	Overall Height	Tare Weight	Onboard Water Capacity (gal)	Onboard Waste Capacity (gal)	Evacuation / Dump Valve Size	City Fill Size	Power Supply	Minimum Functional Power (without heat)	MOC Rating
Modular Drinking Water Station	Water Station	N/A	N/A	N/A	N/A	N/A	4	5.5ft	9ft	7.25ft	4,000 lbs	300	N/A	N/A	Std. Garden Hose	1x50A/240v or 1-320A/120v	2x 20A/120v	50A
Modular Restroom - 10-stall Private Entry Full Plumbing	MARK IV	10	N/A	N/A	10	8	10	40ft	8.5ft	9.5ft	22,000 lbs	1000	1100	3"	N/A	100A(per leg)/240v/Single Phase Series 16 camlocks or bypass to panel	1x100A/240v	100A
Modular Restroom - 10-Station Shared Entry Full Plumbing	MARK III	2	2	6	N/A	2	3	40ft	8.5ft	9.5ft	26,000 lbs	850	1000	2"	N/A	1x100A/240v direct to panel or Series 16 Cam connections	1x100A/240v	100A
Modular Restroom - 12-Station Shared Entry non-Flush w/Sinks	MARK II	2	2	8	N/A	2	3	40ft	8.5ft	9.5ft	22,000 lbs	270	250	2"	N/A	1x100A/240v direct to panel or Series 16 Cam connections	1x100A/240v	100A
Modular Restroom - 15-Station non-Flush no Sinks	MARK I	2	3	10	N/A	2	0	40ft	8.5ft	9.5ft	20,000 lbs	N/A	N/A	N/A	N/A	1x100A/240v direct to panel or Series 16 Cam connections	1x100A/240v	100A
Shower Trailer	8-Stall	8	N/A	N/A	N/A	N/A	8	32ft	10.5ft	11.6ft	12,500 lbs	200	1100	2"	Std. Garden Hose	4x30A/120v NEMA L5-30 Twist Lock 120v or 4x 15A/120v	2x 15A/120v	30A
Restroom Trailer	8-Stall	8	N/A	N/A	8	8	8	35ft	11ft	11.5ft	12,940 lbs	400	1000	3"	Std. Garden Hose	1x50A/240v Cali-Standard (CS6364C) Inlet or 3x 20A/120v	2x 20A/120v	50A
Restroom Trailer	10-Station	2	5	2	N/A	3	4	29ft	11ft	11.5ft	11,900 lbs	200	1000	3"	Std. Garden Hose	1x50A/240v Cali-Standard (CS6364C) Inlet or 3x 20A/120v	2x 20A/120v	50A
Restroom Trailer	10-Station	2	5	2	N/A	3	4	30ft	12.6ft	11.8ft	9,800 lbs	200	950	2"	Std. Garden Hose	4x30A/120v NEMA L5-30 Twist Lock 120v or 4x 15A/120v	2x 15A/120v	30A
Restroom Trailer	4-Stall	4	N/A	N/A	4	0	4	19ft	7.6ft	11.3	5,280 lbs	200	440	2"	Std. Garden Hose	3x30A/120v NEMA L5-30 Twist Lock 120v or 3x 15A/120v	2x15A/120v	30A
Restroom Trailer	4-Stall	4	N/A	N/A	4	2	4	23ft	11ft	11.3	6,960 lbs	200	480	3"	Std. Garden Hose	1x50A/240v Cali-Standard (CS6364C) Inlet or 3x 20A/120v	2x 20A/120v	50A
Modular Bootwash	Bootwash	1	N/A	N/A	N/A	N/A	N/A	20ft	8ft	9.5ft	8,000 lbs	400	N/A	N/A	N/A	1x50A/240v Cali-Standard (CS6364C) Inlet	1x50A/240v	30A