STUDY GUIDE

DATA ENGINEERING AND BIG DATA: PIPELINES, WAREHOUSES, SPARK AND STREAMING

A practical, number-driven textbook for a working professional who wants to build data platforms that are correct, fast and cheap.

Taught the IIT Professor Way — Real Numbers. Real Problems. Real Understanding.

CHAPTER 1 The Data Engineering Lifecycle and Architectures	**CHAPTER 2** Data Modeling for Analytics	**CHAPTER 3** File Formats, Storage and Lakehouse Table Formats	**CHAPTER 4** Ingestion Patterns
CHAPTER 5 Data Quality and Testing	**CHAPTER 6** Orchestration with Apache Airflow (and Its Alternatives)	**CHAPTER 7** dbt, the Tool That Turns SQL into a Tested Software Project	**CHAPTER 8** Cloud Warehouses, Cost Control and the Cloud Data Services Map
CHAPTER 9 Apache Spark and PySpark I, Architecture, DataFrames, Joins and Windows	**CHAPTER 10** Apache Spark II, Making Spark Fast: Shuffles, Skew, Broadcast, Caching, AQE and the Spark UI	**CHAPTER 11** Streaming and Kafka	**CHAPTER 12** Infrastructure and DataOps
CHAPTER 13 System Design for Data	**CHAPTER 14** Performance and Capacity of Data Pipelines	**CHAPTER 15** Project Lab 1: Pipelines, Lakes, Batches, Loaders and Models	**CHAPTER 16** Project Lab 2: Quality, Streaming, Star Schemas and Storage
APPENDIX Cheat Sheet			

A Note From Your Professor

You already know something most beginners do not: how systems behave under load. You have read response-time percentiles, found bottlenecks, and explained to a manager why the system slowed at 3 p.m. Data engineering uses the same thinking. A pipeline is a system with queues, throughput, failures and cost. The new part is that the data must also be *right*, every day, even after a crash, a retry or a late file.

This document teaches you that craft in small steps. We start with the map of the field, then modeling, files, ingestion, quality and orchestration, and later dbt, warehouses, Spark,

streaming, infrastructure, system design and a performance project that is uniquely yours. Everything is built around real numbers and code you can run. Where a tool needs a cloud or a cluster that we could not run here, the text says "not run here" and keeps the example short and standard.

One rule above all: **never move on until the current topic feels obvious.** If you cannot explain a section to a friend in simple words, read it again and rebuild the example yourself. One hour a day for a year beats a weekend sprint. You do not need to know everything. You need to be able to build a small pipeline that is idempotent, tested and observable, and to explain why it works. That is what employers pay for, and you can do it.

Be patient with yourself. English is your second language, so I use short sentences and define every new word the first time. If a word is still unclear, ask an AI with the prompt packs at the end of each chapter.

What Every Topic Contains

1. **INTUITION:** the real problem in everyday language, often from everyday life: shops, deliveries, hospitals, bank queues.
2. **Formal definition:** how it works, precise but plain.
3. **Worked problems or examples** with real numbers or real code output, with every step.
4. **The picture:** a diagram, table or mental model, explained fully.
5. **Connection to the real job:** where it shows up in data engineering work.
6. **Applications:** analytics, data science, ML, MLOps and more.
7. **COMMON MISTAKE:** what beginners get wrong and how to catch it.
8. **Check yourself:** three short questions with answers.

Each chapter also ends with a recap (with a cheat-sheet table), a graded practice set with answers, and a prompt pack of five prompts to paste into any AI.

Contents

1. **The Data Engineering Lifecycle and Architectures:** lifecycle, OLTP/OLAP, batch and stream, ETL/ELT, warehouse, lake, lakehouse, medallion, reliability words, CAP.
2. **Data Modeling for Analytics:** Kimball facts and dimensions, grain, star and snowflake, SCD types, Inmon, Data Vault, OBT.

3. **File Formats, Storage and Lakehouse Table Formats:** CSV/JSON traps, Parquet, Avro, compression, partitioning, small files, Delta, Iceberg, Hudi.
4. **Ingestion Patterns:** full and incremental loads, watermarks, APIs, retries, CDC, backfills, late data (with a runnable loader).
5. **Data Quality and Testing:** checks, contracts, quarantine, unit tests, Great Expectations, pandera, Soda, observability.
6. **Orchestration with Apache Airflow:** DAGs, data intervals, retries, idempotent tasks, TaskFlow, testing; Dagster, Prefect, ADF and others.
7. **dbt:** models, sources, `ref`, materializations, incremental models, tests, snapshots, macros, CI.
8. **Warehouses and Cloud Data Services:** Snowflake, BigQuery, Redshift, Synapse and Fabric, cost control, one-cloud-first mapping, and databases beyond SQL.
9. **Apache Spark and PySpark I:** architecture, DataFrames, lazy evaluation, joins, windows.
10. **Spark II: Performance:** shuffles, skew, broadcast joins, partitioning, caching, AQE, reading the Spark UI, memory.
11. **Streaming and Kafka:** event time, windows, watermarks, delivery semantics, Kafka internals, Structured Streaming, Flink (with a runnable simulation).
12. **Infrastructure and DataOps:** Docker, Kubernetes basics, Terraform, CI/CD, secrets, monitoring, cost, governance, privacy, lineage and catalogs.
13. **System Design for Data:** the design framework, capacity estimation, and six worked designs.
14. **Performance and Capacity of Data Pipelines:** load-testing pipelines, Little's law, bottleneck analysis, capstone projects and the interview bank.

Appendix: **99 Cheat Sheet** with an honest closing note.

Files are numbered in the same order: `01_...` to `14_...` and `99_cheatsheet.md`.

How To Study This Document

Use this learning loop for every section:

1. **Build first.** Run the code in the section before reading the explanation. Type it, do not paste it.
2. **Ask.** Before you read the answer, predict the output. Write your guess down.
3. **Just-in-time theory.** Read the explanation after you have seen the output.

4. **Rebuild.** Close the document and recreate the example from memory with new numbers.
5. **Teach.** Explain it aloud in simple words, as if to a colleague.

Suggested pace: **one chapter per week**, about one hour a day. Day 1-2: read and run. Day 3: redo the examples from memory. Day 4: practice set. Day 5: prompt pack. Weekend: a small mini-project that combines the chapter's ideas (for example, extend the incremental loader in Chapter 4 with the checks from Chapter 5). The whole document takes about 14 weeks. The capstones in Chapter 14 turn it into portfolio pieces.

How to use the prompt packs: paste one into any AI chat. Each starts with the same professor setup, so the AI teaches at your level. Try them in this order: (1) explain, (2) exercises without solutions, (3) quiz, (4) review your own work (paste it at `[PASTE HERE]`), (5) mock interview. Never ask for the answer first.

Prerequisites

- Basic Python: functions, loops, dictionaries, files, `pip`. (See the Python study document in `study/python/`.)
- Basic SQL: SELECT, WHERE, JOIN, GROUP BY. (See the SQL study document in `study/sql/`.)
- Comfort with the command line and Git basics.
- Everyday comfort with numbers, tables and simple averages and percentiles. No prior data engineering knowledge is assumed.

Tools you need

All free. Examples that run in this document use only these.

- **Python 3** (the examples use only the standard library: `sqlite3`, `csv`, `json`, `zlib`, `graphlib`, `unittest`).
- **SQLite** (`sqlite3` command line) for modeling and SQL examples.
- Later chapters add (free): **DuckDB**, **pandas**, **pyarrow**, **PySpark** (needs Java 17 or newer), **dbt-core** with DuckDB, **Docker Desktop**, **Apache Airflow** (via Docker), **Apache Kafka** (via Docker), **Terraform**, **Git** and **GitHub**.
- A code editor such as VS Code.
- A free cloud account is optional (AWS, Azure or GCP free tiers); the document labels cloud

code as "not run here".

CHAPTER 1

THE DATA ENGINEERING LIFECYCLE AND ARCHITECTURES

Where data comes from, where it goes, and the big design choices that shape every pipeline.

Imagine your company runs an online shop called **ShopKart**. Every second, customers place orders, the app logs clicks, and payment machines send messages. The business wants a dashboard that says "revenue by city, yesterday", and a data scientist wants clean tables to train a model. Someone must move the data, clean it, store it, and keep it correct every single day, even when a server dies at 3 a.m. That person is a data engineer. In this chapter you will learn the map of the whole field: the stages data passes through, the main building styles (warehouse, lake, lakehouse, medallion), and the ideas that keep pipelines reliable. By the end you will be able to look at any data system and say what each box is for, and why it was chosen. We will use ShopKart as the running example in the whole document.

You already know a lot from everyday life: the queue at a bank, delivery times, a busy restaurant kitchen. Data engineering is the same systems thinking (queues, throughput, bottlenecks, percentiles), applied to data that must also be *correct*, not only fast.

1.1 The Data Engineering Lifecycle

INTUITION

Think of a city water system. Rain falls (generation), pipes collect it (ingestion), a reservoir holds it (storage), a plant cleans it (transformation), and taps deliver it to homes (serving). Under all of this sit rules, inspectors and meters (security, governance, monitoring). A data platform is a water system for facts.

Words you need

Word	Plain meaning	ShopKart example
Source system	The app or machine that creates data	The orders database, the mobile app

Ingestion	Moving data from the source to a place we control	Copying new orders every hour
Storage	Keeping data safely and cheaply	Files in cloud object storage, a warehouse
Transformation	Cleaning and reshaping data into useful tables	Remove duplicates, convert paise to rupees
Serving	Giving data to the people and programs that use it	A dashboard, an ML model, an API
Governance	Rules about who may see data and how long we keep it	Hide customer phone numbers from analysts
Pipeline	A chain of steps that moves and transforms data automatically	"orders DB to dashboard"

The five stages and the undercurrents

The data engineering lifecycle: five stages with undercurrents below

How to read the picture: data flows left to right through five boxes. The wide orange bar at the bottom is not a stage. It is a set of concerns that touch *every* stage: security, governance, orchestration (running steps in the right order, covered in Chapter 6), DataOps (applying software discipline to data work), monitoring and cost.

1. **Generation.** You usually do not control this. The app team owns it. Your task is to know its quirks (late events, changing fields).
2. **Ingestion.** Pull or receive data. Patterns: batch (many records at once), stream (record by record), CDC (copy the database change log). Chapter 4 and Chapter 11.
3. **Storage.** Choose a format and a place. Chapter 3 and Chapter 8.
4. **Transformation.** Turn raw data into trusted models. Chapters 2, 7, 9.
5. **Serving.** Dashboards, reports, ML features, reverse ETL (writing results back into business tools like a CRM).

Problem 1.1.1 For ShopKart, name the lifecycle stage for each action: (a) a customer clicks

"Buy"; (b) a script copies yesterday's orders to a file; (c) a job converts amounts from paise to rupees; (d) an analyst opens a Power BI report; (e) a rule says customer emails are deleted after 3 years.

Step 1	Ask "is data being created, moved, kept, reshaped, used, or governed?"
Step 2	(a) creates data: generation. (b) moves data: ingestion. (c) reshapes: transformation. (d) uses: serving. (e) is a rule: governance, which is an undercurrent.
Answer	Generation, ingestion, transformation, serving, governance.
Check	Each stage was used once except storage, which is the place the file in (b) lands. Every action fits exactly one label.
Why it matters	In an interview, "which stage is slow or failing?" is the first question. Naming the stage narrows the search.

Problem 1.1.2 The dashboard shows yesterday's revenue as 10% lower than finance's number. Using the lifecycle, list where the 10% could be lost, in order from source to dashboard.

Step 1	Walk the stages: generation (source missed events), ingestion (a batch failed or ran before the day ended), storage (a partition not written), transformation (a filter or a bad join dropped rows), serving (dashboard time zone cuts the day).
Step 2	Rank by how cheap each is to test. Compare row counts at each hop: source count, landed count, cleaned count, dashboard count.
Answer	Count rows at every hop. The first hop where the count drops is the stage that lost the data.
Check	If source = landed = 1,000,000 but cleaned = 900,000, the transformation lost exactly 10%, which matches the complaint.
Why it matters	"Reconcile counts at each hop" is the simplest data-quality habit (Chapter 5).

Connection to the real job

Job titles map to stages: ingestion engineers, analytics engineers (transformation, mostly SQL and dbt), platform engineers (storage, infrastructure), and ML engineers (serving features).

Applications

- **Data Analytics:** the dashboard is the serving stage, built on gold tables.
- **Data Science:** model training reads the storage layer, needs trusted transformation.
- **Machine Learning / MLOps:** feature pipelines are lifecycle stages with tighter freshness needs.
- **Data Engineering:** you own stages 2 to 4 and the undercurrents.

COMMON MISTAKE

Treating the lifecycle as a straight line you build once. In real life each stage changes on its own (the app team adds a field, volume doubles). Build every stage so it can be re-run and observed.

Check yourself

1. Which stage is "keep customer emails only 3 years" part of? Answer: governance, an undercurrent that touches storage.
2. Why is orchestration called an undercurrent and not a stage? Answer: it coordinates all stages, it does not move or hold data itself.
3. In what order do you check row counts when numbers disagree? Answer: from the source forward, hop by hop.

1.2 OLTP vs OLAP, Row vs Column, Batch vs Stream

INTUITION

A bank teller serves one customer at a time: find one account, change one number, quickly. A bank analyst studies all accounts in a year to find a trend. The teller's desk and the analyst's desk need different furniture. The first is OLTP, the second is OLAP.

Definitions

- **OLTP** (Online Transaction Processing): many small reads and writes touching a few rows, each must be fast and safe. Example: "insert order 424242". Databases: PostgreSQL, MySQL, SQL Server.
- **OLAP** (Online Analytical Processing): fewer, heavier queries that scan many rows but few

columns. Example: "total revenue per country for 2 years". Systems: warehouses, ClickHouse, DuckDB.

- **Row storage:** all fields of one row sit together on disk. Fast to fetch or write one whole row.
- **Columnar storage:** all values of one column sit together. Fast to read two columns out of fifty, and the values compress very well because they look alike.

Property	OLTP	OLAP
Typical query	one row by key	scan and aggregate millions of rows
Storage layout	row	column
Latency goal	milliseconds	seconds to minutes
Data model	normalized (many small tables)	denormalized star schema (Chapter 2)
Concurrency	thousands of small users	tens of heavy queries
ShopKart example	place an order	revenue by city by month

Predict, Run, Explain: the same table, two kinds of question

Before you run it: which do you think is faster, 1,000 single-order lookups, or one whole-table aggregate over 500,000 rows? And will both use an index?

```
import sqlite3, time, random
random.seed(1)
db = sqlite3.connect(":memory:")
db.execute("CREATE TABLE orders(order_id INTEGER PRIMARY KEY, customer_id
INT, country TEXT, amount REAL)")
rows = [(i, random.randint(1,50000), random.choice(["IN","US","UK","DE"]),
round(random.uniform(5,500),2)) for i in range(1,500001)]
db.executemany("INSERT INTO orders VALUES(?,?,?,?)", rows); db.commit()
print("rows:", db.execute("SELECT COUNT(*) FROM orders").fetchone()[0])
print("-- OLTP style: fetch one order")
for r in db.execute("EXPLAIN QUERY PLAN SELECT * FROM orders WHERE
order_id=424242"): print(r[3])
t = time.perf_counter()
for _ in range(1000): db.execute("SELECT * FROM orders WHERE order_id=?",
(random.randint(1,500000),)).fetchone()
print(f"1000 point lookups: {(time.perf_counter()-t)*1000:.1f} ms")
print("-- OLAP style: aggregate everything")
for r in db.execute("EXPLAIN QUERY PLAN SELECT country, SUM(amount) FROM
orders GROUP BY country"): print(r[3])
t = time.perf_counter()
res = db.execute("SELECT country, ROUND(SUM(amount),2), COUNT(*) FROM
orders GROUP BY country ORDER BY 1").fetchall()
print(res); print(f"1 full aggregate: {(time.perf_counter()-t)*1000:.1f}
ms")
```

Real output (timings change a little on every machine; the plans and totals do not):

```
rows: 500000
-- OLTP style: fetch one order
SEARCH orders USING INTEGER PRIMARY KEY (rowid=?)
1000 point lookups: 1.7 ms
-- OLAP style: aggregate everything
SCAN orders
USE TEMP B-TREE FOR GROUP BY
[('DE', 31657878.42, 124973), ('IN', 31547687.52, 125134), ('UK',
31617908.13, 124856), ('US', 31578025.69, 125037)]
1 full aggregate: 129.7 ms
```

Explain, line by line.

- `SEARCH ... USING INTEGER PRIMARY KEY` means the database jumped straight to the row, like opening a book at a page number. Cost per lookup is tiny: 1000 lookups took 1.7 ms, so about 0.0017 ms each.
- `SCAN orders` means the database read every row. One scan took 129.7 ms, which is

about 76 times the cost of all 1000 lookups together (129.7 / 1.7 = 76.3).

- The group totals add up: 124,973 + 125,134 + 124,856 + 125,037 = 500,000. That is our **Check**: no row lost.
- *Interpretation:* point lookups are cheap because of an index. An analytics question must touch all rows, so its cost grows with table size. That is why OLAP systems store columns and scan in parallel: they make the unavoidable scan cheap.

KEY INSIGHT

An analytical query asking for 2 of 50 columns should read 2/50 = 4% of the bytes. Row storage reads 100%. Columnar storage reads about 4%. Chapter 3 measures this effect.

Batch, micro-batch, streaming

Style	Meaning	Typical latency	Example
Batch	Process a big chunk on a schedule	minutes to hours	nightly load of orders
Micro-batch	Run tiny batches every few seconds	seconds	Spark Structured Streaming default
Streaming	Handle each event as it arrives	milliseconds to seconds	fraud check on a card swipe

Analogy: batch is a bus that leaves every hour. Micro-batch is a metro train every 5 minutes. Streaming is a taxi per person. Taxis cost more per passenger. Pick the slowest style that meets the business need.

Problem 1.2.1 ShopKart needs a revenue dashboard refreshed every morning, and a fraud alert within 2 seconds of a payment. Which style for each?

Step 1	Dashboard: tolerance is a day. A nightly batch is enough.
Step 2	Fraud: tolerance is 2 seconds. Only streaming (or very small micro-batch) fits.
Answer	Batch for the dashboard, streaming for fraud.
Check	If we used a nightly batch for fraud, the median delay would be 12 hours, far above 2 seconds.
Why it matters	Streaming is harder to run and test. Do not pay for it when batch is enough.

Problem 1.2.2 A table has 50 columns, each about 8 bytes, 100 million rows. A query reads 2 columns. How many GB must row storage read versus columnar storage (ignoring compression)?

Formula	bytes = rows × bytes per value × columns read
Plug in (row)	all 50 columns are stored together: 100,000,000 × 8 × 50
Compute (row)	40,000,000,000 bytes = 40 GB
Plug in (column)	100,000,000 × 8 × 2 = 1,600,000,000 bytes = 1.6 GB
Answer	Row storage reads 40 GB, columnar reads 1.6 GB, which is 25 times less. (Compression helps columns even more.)
Check	2 / 50 = 0.04, and 0.04 × 40 GB = 1.6 GB.

Connection to the real job

You will copy data out of OLTP systems into OLAP systems, and you must do it without slowing down the shop. Running a heavy analytic query on the live order database is a classic outage. In SQL terms, the heavy `GROUP BY` queries are covered in the SQL document (`study/sql/` , the aggregation chapter).

Applications

- **Data Analytics:** dashboards run on OLAP stores.
- **Data Engineering:** extraction jobs are designed to be gentle on OLTP.
- **Machine Learning:** training reads columns (features), so columnar files speed up loading.
- **Capacity Planning:** an OLAP scan is a throughput problem, an OLTP lookup is a latency problem.

COMMON MISTAKE

Using the production OLTP database for analytics "just this once". Use a read replica or a CDC copy (Chapter 4).

Check yourself

1. Which layout suits "fetch the full record of order 7"? Answer: row storage.
2. Why do columns compress better? Answer: values in one column look alike (same type, repeated values).
3. What is micro-batch? Answer: batches so small and frequent that it feels like streaming.

1.3 ETL vs ELT and Architecture Styles

INTUITION

In ETL you wash the vegetables at the farm and bring only clean ones to the kitchen. In ELT you bring everything to the kitchen first and wash it there, because the kitchen is huge and cheap to use. ELT won because warehouse storage and compute became cheap and elastic.

- **ETL** (Extract, Transform, Load): transform on a separate server before loading. Old default when warehouse compute was expensive.
- **ELT** (Extract, Load, Transform): load raw data first, transform inside the warehouse with SQL. Raw data stays available, so you can fix a bug and re-run history. Tools like dbt (Chapter 7) are built for this.

	ETL	ELT
Where transform runs	separate engine	inside warehouse or lake engine

Raw data kept?	often not	yes
Fix a logic bug later	hard, source may be gone	re-run from raw
Good for	strict privacy before load, tiny targets	most modern analytics

When would you still do ETL? When rules forbid raw personal data from landing (mask first), or when the target cannot do heavy transforms.

The architecture styles

Style	One-line idea	Strength	Weakness
Data warehouse	Structured, modelled tables in an SQL engine	fast, trusted BI	costly for raw or unstructured data
Data lake	Cheap files (any format) in object storage	cheap, flexible	can become a "swamp": no rules, no ACID
Lakehouse	Lake files plus a table format (Delta, Iceberg, Hudi) giving ACID, time travel	one copy for BI and ML	needs table-format know-how
Data mesh	Each business domain owns its data as a product	scales across big organisations	needs culture and platform maturity
Lambda	A batch path (accurate) plus a speed path (fast), merged	both accuracy and speed	two code bases to keep in sync
Kappa	Everything is a stream; reprocess by replaying the log	one code base	needs a replayable log (Kafka) and good streaming skills

ACID means a change is Atomic (all or nothing), Consistent, Isolated (parallel changes do not clash) and Durable (kept after a crash). Plain files in a lake do not give you this; table formats add it (Chapter 3).

Medallion architecture: the layered kitchen

Medallion layers: sources into bronze, silver, gold, then BI and ML

Reading the picture: data moves left to right. **Bronze** is the raw copy exactly as received (append only, so you can always replay). **Silver** is cleaned: correct types, duplicates removed, bad rows removed or quarantined. **Gold** holds business-ready tables such as "revenue by country". Each arrow is a job, and between layers we run quality checks.

Predict, Run, Explain: a tiny medallion in SQLite

Before you run it: five raw JSON messages arrive. One order (O2) was sent twice with a corrected amount, and one (O3) has amount "abc". How many rows should silver have, and what is the revenue for IN?

```
CREATE TABLE bronze_orders(raw_id INTEGER PRIMARY KEY AUTOINCREMENT,
payload TEXT, loaded_at TEXT);
INSERT INTO bronze_orders(payload,loaded_at) VALUES
('{"order_id":"O1","amount":"250.0","country":"in"}','2024-06-01'),
('{"order_id":"O2","amount":"80","country":"IN"}','2024-06-01'),
('{"order_id":"O2","amount":"85","country":"IN"}','2024-06-02'),
('{"order_id":"O3","amount":"abc","country":"us"}','2024-06-02'),
('{"order_id":"O4","amount":"40","country":"US"}','2024-06-02');
CREATE VIEW silver_orders AS
SELECT order_id, CAST(amount AS REAL) AS amount, UPPER(country) AS country
FROM (
  SELECT json_extract(payload,'$.order_id') order_id,
json_extract(payload,'$.amount') amount,
         json_extract(payload,'$.country') country,
         ROW_NUMBER() OVER (PARTITION BY
json_extract(payload,'$.order_id') ORDER BY raw_id DESC) rn
  FROM bronze_orders) WHERE rn=1 AND amount GLOB '[0-9]*';
CREATE VIEW gold_revenue_by_country AS
SELECT country, COUNT(*) orders, SUM(amount) revenue FROM silver_orders
GROUP BY country;
SELECT * FROM silver_orders;
SELECT * FROM gold_revenue_by_country;
```

Real output:

```
silver (deduped, typed, bad rows removed)
order_id  amount  country
--------  ------  -------
O1        250.0   IN
O2        85.0    IN
O4        40.0    US
gold (business metric)
country  orders  revenue
-------  ------  -------
IN       2       335.0
US       1       40.0
```

Explain.

- `json_extract` reads fields out of the raw text. Bronze keeps the text untouched, so nothing is lost.
- `ROW_NUMBER() OVER (PARTITION BY order_id ORDER BY raw_id DESC)` numbers each order's copies newest first. `rn=1` keeps only the latest. This is how O2 became 85.0, not 80. (Window functions are taught in the SQL document, `study/sql/` .)
- `amount GLOB '[0-9]*'` drops "abc" (O3). In a real pipeline you would send it to a quarantine table, not silently delete it.
- Gold: IN has O1 and O2: 250 + 85 = 335. Check: 335.0 matches. US has only O4 (O3 was bad).
- *Interpretation:* if finance later says "O3 was a real order", you can fix the parsing rule and rebuild silver from bronze, because bronze kept everything.

Connection to the real job

"Where does this table sit, bronze, silver or gold?" is asked in every code review. In Databricks, Snowflake and Fabric projects, medallion naming is the default.

Applications

- **Data Analytics:** analysts query gold only.
- **Data Science:** scientists often explore silver for detail.
- **Machine Learning:** feature tables are gold-like products built from silver.
- **GenAI:** document text pipelines use the same layers: raw files, parsed chunks, embedded index.

COMMON MISTAKE

Doing cleaning in the dashboard tool instead of in silver. Then every dashboard has its own "truth".

Check yourself

1. Why is bronze append-only? Answer: so any later layer can be rebuilt by replay.
2. Name one situation where ETL beats ELT. Answer: personal data must be masked before it may be stored.
3. Lambda versus kappa: which has two code paths? Answer: lambda.

1.4 Reliability Ideas and Distributed-Systems Basics

INTUITION

A courier company promises "your parcel in 2 days, 99% of the time". If a parcel is lost they resend (retry), and if it is undeliverable they keep it in a special shelf (dead-letter queue). The words below are the same promises, for data.

Words you need

Word	Plain meaning	Example
Data contract	A written agreement on fields, types and meaning between the producer and consumer of data	"orders.amount is a number in paise, never null"
Schema evolution	Changing the fields over time without breaking readers	adding a nullable column `coupon`
Idempotent	Running twice gives the same result as running once	"set stock = 7" (idempotent) vs "stock = stock − 1" (not)
At-most-once	A message may be lost, never repeated	fire and forget

At-least-once	Never lost, may repeat	retry until acknowledged
Exactly-once	Effect happens once (in practice: at-least-once plus idempotent processing)	payment ledger
Backfill	Re-run a pipeline for past dates	recompute March after a bug fix
Late-arriving data	An event that reaches you after its day was processed	mobile app offline for 2 hours
CDC	Change Data Capture: reading the database change log to copy inserts, updates and deletes	Debezium (Chapter 4)
SLI / SLO / SLA	Indicator (what we measure), Objective (our target), Agreement (the promise to customers, with penalty)	SLI: freshness. SLO: 99% of days fresh by 7 a.m.
DLQ	Dead-letter queue: a place for messages that keep failing	bad JSON lines
FinOps	Managing cloud cost as an engineering topic	tag jobs, set budgets

Idempotency in numbers

Problem 1.4.1 A job adds today's sales of 500 to a total of 1,000 using `total = total + 500` . It crashes after writing and the scheduler retries it once. What is the total? Then repeat with `total = yesterday_total + today_sales` where yesterday_total = 1,000.

Step 1	Non-idempotent update: first run gives 1,000 + 500 = 1,500. Retry gives 1,500 + 500 = 2,000.
Step 2	Idempotent version: first run gives 1,000 + 500 = 1,500. Retry gives 1,000 + 500 = 1,500, because the base is yesterday's saved value, not "whatever is there now".
Answer	The first design double counts (2,000), the second stays correct (1,500).
Check	Real sales are 500, so the correct total is 1,500. The first design is off by 500, exactly one duplicate run.
Why it matters	Retries are normal in distributed systems. Every task you write must survive them. This is the most important habit of this document.

You will run an idempotent loader in Chapter 4 and an idempotent task runner in Chapter 6.

Delivery guarantees in one picture

```
Producer ---msg--> Broker ---msg--> Consumer ---> Database
          ack?              ack?

at-most-once : consumer commits position BEFORE processing  -> crash =
message lost
at-least-once: consumer commits position AFTER  processing  -> crash =
message processed twice
exactly-once : at-least-once  +  idempotent write (key) or transaction
```

Problem 1.4.2 A consumer processes a message that adds 100 to a balance, then crashes before saving its position. On restart it re-reads the message. With at-least-once, what do we get if (a) the write is "balance += 100", (b) the write is "insert payment_id=P77 amount=100, ignore if P77 exists" and the balance is the sum of payments?

Step 1	(a) The message is applied twice: balance rises by 200.
Step 2	(b) The second insert is ignored because P77 exists. The balance sum rises by 100.
Answer	(a) wrong by 100, (b) correct. Exactly-once effect = at-least-once delivery + idempotent write.
Check	One payment of 100 should change the balance by 100: only (b) does.

Distributed systems fundamentals (just enough)

- **Partitioning / sharding:** split data across machines by a key, so each machine holds a slice. Like splitting a phone book by first letter.
- **Replication:** keep copies on several machines to survive failure and to spread reads.
- **Consensus:** machines agree on one value even if some fail. Algorithms: Raft, Paxos. You will not implement them, but know that Kafka's KRaft, etcd and ZooKeeper use them to elect a leader.
- **CAP theorem:** when the network splits (a Partition), a system must choose between Consistency (every read sees the latest write) and Availability (every request gets an answer). You cannot have both during the split. Without a split, you can have both. "CP" systems refuse some requests to stay correct; "AP" systems answer, possibly with stale data.
- **Consistency models:** *strong* (always latest), *eventual* (all copies agree if writes stop), *read-your-writes* (you see your own updates). Warehouses and lakes are often eventually consistent in listing; table formats give you snapshot isolation.

Concept	Example value	Where in the job
Partition count	12 Kafka partitions	limits consumer parallelism
Replication factor	3	survive loss of 2 brokers (with a correct min-ISR setting, see Chapter 11)
Consistency	eventual	dashboard may lag the source by minutes
Retry with backoff	wait 1s, 2s, 4s	a flaky API

Problem 1.4.3 A 3-replica system needs a majority (quorum) to accept a write. How many replicas can fail while writes still work? What if there are 5 replicas?

Formula	quorum = ⌊n / 2⌋ + 1; tolerated failures = n − quorum
Compute (n = 3)	quorum = ⌊1.5⌋ + 1 = 2; failures tolerated = 3 − 2 = 1
Compute (n = 5)	quorum = ⌊2.5⌋ + 1 = 3; failures tolerated = 5 − 3 = 2
Answer	3 replicas survive 1 failure, 5 survive 2.
Check	With n = 4: quorum 3, tolerate 1. Four replicas tolerate no more than three, which is why odd numbers are chosen.

Connection to the real job

Reliability is what you are paid for. Interviewers ask: "What happens if this job runs twice? If it fails halfway? If data arrives a day late?" Always answer with idempotency, retries, DLQ, and backfill.

Applications

- **Data Engineering:** idempotent loads, DLQs, freshness SLOs.
- **MLOps:** a training pipeline must be re-runnable to reproduce a model.
- **Operations:** SLO validation uses the same percentile thinking as a delivery company promising that 95% of parcels arrive within two days.
- **FinOps:** cost per TB scanned or per pipeline run is tracked like response time.

COMMON MISTAKE

Believing "exactly-once delivery" exists across a network. What exists is exactly-once *effect*, built from retries and idempotent writes.

Check yourself

1. Is `INSERT ... ON CONFLICT DO UPDATE` idempotent? Answer: yes, repeating it leaves the same final row.
2. What does CAP force during a network split? Answer: a choice between consistency and availability.
3. What is a backfill? Answer: re-running a pipeline over past dates.

Chapter recap

- A data platform has five stages (generation, ingestion, storage, transformation, serving) and undercurrents (security, governance, orchestration, DataOps, monitoring, cost).
- OLTP serves many tiny transactions (row storage, indexes). OLAP serves heavy scans (columnar storage).
- Pick the slowest of batch, micro-batch, streaming that meets the need.
- ELT keeps raw data and uses warehouse power, so bugs can be fixed by re-running.
- Warehouse is modelled and fast; lake is cheap and flexible; lakehouse adds ACID to lake files; mesh is an organisation idea; lambda has two paths, kappa has one.
- Medallion = bronze (raw), silver (clean), gold (business).
- Idempotency plus retries gives exactly-once effect; at-least-once delivery is the practical base.
- CAP: during a network split choose consistency or availability. Quorum = ⌊n/2⌋ + 1.

Pattern	Rule
Bytes read by a query	rows × bytes per value × columns read
Quorum	⌊n/2⌋ + 1
Idempotent write	upsert by key, overwrite by partition, never "x = x + 1"
Row-count reconcile	count at every hop, find first drop

Practice set

1. (easy) Name the five lifecycle stages in order. **Answer:** Generation, ingestion, storage, transformation, serving.

2. (easy) OLTP or OLAP: "show the status of order 991". **Answer:** OLTP, one row by key.

3. (easy) A table has 20 columns of 8 bytes and 10 million rows. Bytes read by a query of 1 column in a columnar store? **Answer:** 10,000,000 × 8 × 1 = 80,000,000 bytes = 80 MB (row storage: 1.6 GB).

4. What is the output? Silver view above, if O4's amount were "4x0". How many silver rows? **Answer:** `GLOB '[0-9]*'` only checks the first character, so "4x0" passes (and CAST gives

4.0). The check is too weak. 3 rows remain, with a wrong value. Better to validate the full pattern or use a typed parser.

5. Find the bug: `UPDATE stock SET qty = qty - 1 WHERE sku='A1'` is run by a retrying task. **Answer:** Not idempotent: a retry decrements twice. Use an event table with a unique event id and compute the stock from it.

6. A 5-broker cluster needs a majority to elect a leader. How many failures can it survive? **Answer:** quorum 3, so 2 failures.

7. ShopKart wants "orders in the last 10 seconds per city" on a live screen. Which style and why? **Answer:** streaming (or a short micro-batch), because the freshness need is seconds.

8. A pipeline loaded 1,000,000 rows from source and 1,000,000 into silver, but gold shows 940,000 orders. Where do you look first? **Answer:** the gold transformation (joins/filters). Counts matched until silver.

9. (interview) "Explain ETL versus ELT and when you would choose each." **Answer:** ETL transforms before loading; ELT loads raw then transforms inside the warehouse. Choose ELT by default because storage is cheap, raw data allows replay, and SQL tools are mature. Choose ETL when privacy rules forbid raw data landing or the target cannot transform. Mention that bronze/silver/gold keeps raw data in ELT.

10. (interview) "What does exactly-once mean in a pipeline?" **Answer:** The effect on the target is applied once, even if messages are delivered more than once. It is built from at-least-once delivery plus idempotent writes or transactions, not from the network.

11. (scenario) A backfill of 90 days must run without double counting. How? **Answer:** Make each daily task overwrite its own date partition (or upsert by key), parameterise by the logical date, and run the 90 dates, possibly in parallel. Verify with row counts per day.

Prompt pack

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language, so use simple
words. Teach me the data engineering lifecycle (generation, ingestion,
storage, transformation, serving, and the undercurrents). Use one running
example, an online shop. Explain step by step with an analogy first, then
check my understanding with 3 short questions, one at a time, and wait for
```

my answers before continuing.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Topic: OLTP versus OLAP, and row versus columnar storage. Give me 8 graded exercises, from easy to hard, with real numbers (rows, columns, bytes per value, bytes scanned). Do not give solutions. After I answer, I will paste my work and you will check every step and correct my mistakes kindly.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am learning data engineering with simple English. Topic: ETL versus ELT and the architecture styles (warehouse, lake, lakehouse, mesh, lambda, kappa, medallion). Quiz me one question at a time, mixing definitions with short scenarios ("a bank must mask card numbers before storage; which style?"). After each answer, say what is right, what is missing, and give a one-line memory trick.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Topic: idempotency, at-least-once versus exactly-once effect, retries, backfills, and the CAP theorem. Explain each with a courier or bank analogy, then show a tiny Python or SQL example where a retry causes a double count and the fix. Then ask me to predict the output of a new example before you reveal it.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, applying for junior data engineer roles. Run a mock interview on the data engineering lifecycle, OLTP/OLAP, ELT, medallion, idempotency and delivery guarantees. Ask 8 questions, one at a time. After each of my answers, score it from 1 to 5, show a model answer in simple English, and tell me what an interviewer would want to hear in addition. My answers: [PASTE HERE]

CHAPTER 2

DATA MODELING FOR ANALYTICS

Shaping tables so that business questions are easy, fast and correct: facts, dimensions, grain and slowly changing dimensions.

A manager asks: "How much revenue did we make in Mumbai last month, by product category?" If your tables are shaped like the shop's order system (many small normalized tables), the answer needs six joins and nobody trusts it. If your tables are shaped for analysis, the answer is one short query that anyone can read. Data modeling is the craft of choosing that shape. In this chapter you will learn the Kimball method (facts and dimensions), how to state the grain of a table, what star and snowflake mean, and how to keep history when a customer moves city (slowly changing dimensions). You will build a real star schema in SQLite, run it, and see how the wrong choice gives a wrong revenue number. Basic SQL (SELECT, JOIN, GROUP BY) is assumed; if you need it, study the SQL document in `study/sql/` first (chapters on SELECT and aggregation).

2.1 Facts, Dimensions, Grain, Star and Snowflake

INTUITION

Think of a receipt. The numbers on the receipt (quantity, price, total) are *measurements of an event*. The words around it (which shop, which customer, which product, which date) are *context*. Dimensional modeling keeps these apart: measurements go into a **fact table**, context goes into **dimension tables**. A fact row points to its context with keys, like a receipt pointing to the shop address on a notice board.

Words you need

Word	Plain meaning	ShopKart example
Fact table	One row per business event, holding numbers you can add up	`fact_sales`: one row per order line
Measure	A numeric column in a fact	`qty`, `amount`

Dimension table	Descriptive attributes used to filter and group	`dim_customer`, `dim_product`, `dim_date`
Grain	What exactly one fact row represents	"one product on one order"
Surrogate key	A meaningless integer key made by the warehouse	`customer_key = 17`
Natural (business) key	The key from the source system	`customer_id = 'C1'`
Star schema	A fact in the middle, dimensions around it, each one join away	see picture
Snowflake schema	Dimensions normalized into more tables (product to category to department)	`dim_product -> dim_category`

Declare the grain first

Kimball's rule: before you choose columns, say the grain in one sentence. "One row per order line per day" or "One row per customer per month-end". If the grain is vague, totals will be double counted. Everything in a fact row must be true *at that grain*.

A star schema: fact_sales in the center joined to date, customer, product and store dimensions

How to read it: the orange box in the middle is the fact table. Each arrow is a join from a key in the fact to the key of a dimension. To answer "revenue by month and category" you join the fact to `dim_date` and `dim_product`, then `GROUP BY`. A star has one join hop from the fact to any dimension, which is why queries are simple and warehouses can optimize them.

Three kinds of fact tables

Type	Grain	Example	Typical use
Transaction fact	one row per event	each order line	sales, clicks, payments

Periodic snapshot	one row per entity per period	account balance at each month end	inventory levels, balances
Accumulating snapshot	one row per process instance, updated as it moves	order with dates for placed, packed, shipped, delivered	pipeline or workflow durations

Other terms: a **degenerate dimension** is an identifier with no extra attributes that lives in the fact itself (the `order_id`). A **junk dimension** packs a few small flags (is_gift, payment_type) into one small table so the fact does not carry many tiny columns. A **conformed dimension** is a dimension shared by several facts with the same meaning (one `dim_date` for sales and for returns), which lets you compare across them. The **bus matrix** is a grid: rows are business processes (sales, returns, shipments), columns are conformed dimensions, and a tick says which process uses which dimension. It is the plan for the whole warehouse.

Process	Date	Customer	Product	Store
Sales	x	x	x	x
Returns	x	x	x	x
Shipments	x		x	

Predict, Run, Explain: build a star and ask a business question

Before you run it: there are 4 sales lines with amounts 500, 300, 1000, 250. What should the total per month be?

```
CREATE TABLE dim_customer(customer_key INTEGER PRIMARY KEY, customer_id
TEXT, name TEXT, city TEXT, valid_from TEXT, valid_to TEXT, is_current
INTEGER);
CREATE TABLE dim_product(product_key INTEGER PRIMARY KEY, sku TEXT,
category TEXT);
CREATE TABLE dim_date(date_key INTEGER PRIMARY KEY, full_date TEXT, month
TEXT);
CREATE TABLE fact_sales(date_key INT, customer_key INT, product_key INT,
order_id TEXT, qty INT, amount REAL);
INSERT INTO dim_product VALUES (1,'P-100','Books'),(2,'P-200','Toys');
INSERT INTO dim_date VALUES (20240110,'2024-01-10','2024-01'),
(20240215,'2024-02-15','2024-02'),(20240301,'2024-03-01','2024-03');
INSERT INTO dim_customer VALUES (1,'C1','Asha','Pune','2023-01-01','2024-
02-01',0),
  (2,'C1','Asha','Mumbai','2024-02-01','9999-12-31',1),
(3,'C2','Ravi','Delhi','2023-05-01','9999-12-31',1);
INSERT INTO fact_sales VALUES (20240110,1,1,'O1',2,500),
(20240215,2,2,'O2',1,300),
  (20240301,3,1,'O3',4,1000),(20240301,2,1,'O4',1,250);
SELECT d.month, p.category, SUM(f.amount) AS revenue
FROM fact_sales f JOIN dim_date d USING(date_key) JOIN dim_product p
USING(product_key)
GROUP BY 1,2 ORDER BY 1,2;
```

Real output:

```
month    category  revenue
-------  --------  -------
2024-01  Books     500.0
2024-02  Toys      300.0
2024-03  Books     1250.0
```

Explain. `JOIN ... USING(date_key)` matches the fact's `date_key` to the dimension's. March Books = 1000 (O3) + 250 (O4) = 1250. Our **Check**: 500 + 300 + 1250 = 2050 and the four amounts add to 500 + 300 + 1000 + 250 = 2050. Nothing was lost or doubled. *Interpretation:* each dimension join added context but did not change the number of fact rows, because each fact row matches exactly one row in each dimension. If a join multiplied rows (a many-to-many by mistake), the total would be too high. Always compare the total before and after joining.

Problem 2.1.1 (grain) A fact table has one row per order line. An analyst adds the column `order_shipping_fee` (one fee per whole order) to each line. An order has 3 lines and a fee of

60. What does `SUM(order_shipping_fee)` give for that order, and what is the right fix?

Step 1	The fee is repeated on each of the 3 rows: 60 + 60 + 60 = 180.
Step 2	The true fee is 60. The column does not belong at the order-line grain.
Answer	The sum is 180, three times too high. Fix: put the fee in a separate fact at order grain, or allocate it across lines (20 each) and say so in the column name.
Check	3 lines × 20 = 60, which equals the true fee.
Why it matters	Mixed grain is the number one cause of "the dashboard is wrong" bugs.

Problem 2.1.2 (additivity) Which measures can be summed across all dimensions? (a) `amount` in a sales fact, (b) `account_balance` in a month-end snapshot, (c) `unit_price`.

Step 1	*Additive* means summing makes sense over every dimension. (a) yes: revenue over customers, products and days.
Step 2	(b) is *semi-additive*: you may add balances across customers on one date, but not across dates (adding January's and February's balance is meaningless). Use the last value or an average over time.
Step 3	(c) is *non-additive*: summing prices means nothing. Store `qty` and `amount`, compute price = amount / qty.
Answer	(a) additive, (b) semi-additive, (c) non-additive.
Check	If a customer holds 100 in January and 100 in February, the "sum" 200 is false: they never held 200.

Star versus snowflake versus One Big Table

Design	Joins to get an attribute	Storage	Ease	When to use
Star	1	some repeated text in dimensions	easiest for analysts	default for marts

Snowflake	2 or more	least duplication	more joins, harder	when a dimension is huge and shared sub-dimensions matter
One Big Table (OBT)	0	duplicates all attributes on every row	simplest queries, fast scans in columnar engines	dashboards on columnar warehouses, ML features

OBT trade-offs: it is fast and simple, but you lose a clean single place to fix a dimension value, storage grows, and changing an attribute means rewriting many rows. A common pattern: model a star as the source of truth, then publish an OBT built from it for one dashboard. **Wide tables** (many columns, fewer rows, ideal for ML features) and **narrow tables** (few columns, many rows, such as an event log with `key, value`) trade flexibility against scan cost; columnar stores handle wide tables well because unused columns are never read.

Normalization and denormalization

Normalization means storing each fact once, split into many tables (3NF: every non-key column depends on the key, the whole key, and nothing but the key). It protects OLTP systems from update mistakes. **Denormalization** copies attributes into wide tables to avoid joins, which suits OLAP. Rule: normalize where you write often, denormalize where you read a lot.

Connection to the real job

Almost every analytics-engineering interview has "design the tables for X". The expected steps are: pick the business process, declare the grain, choose dimensions, choose facts. In dbt (Chapter 7), your `marts` folder holds exactly these facts and dimensions.

Applications

- **Data Analytics:** Power BI and Tableau models are stars; relationships follow fact-to-dimension keys.
- **Data Engineering:** you build and test the keys and the grain (one unique key per fact row).
- **Machine Learning:** feature tables are often OBTs at "one row per customer per day".
- **Operations:** a monitoring warehouse can use a fact per measurement run and dimensions for check, build, scenario and environment (Chapter 14).

COMMON MISTAKE

Joining two fact tables directly (sales and returns) at different grains. You get row multiplication. Aggregate each to a common grain (for example product and day) first, then join through conformed dimensions.

Check yourself

1. What is the grain of `fact_sales` above? Answer: one row per order line.
2. Why is a month-end balance semi-additive? Answer: you cannot sum balances across time.
3. Star or snowflake for the simplest analyst queries? Answer: star.

2.2 Slowly Changing Dimensions (SCD)

INTUITION

Your friend Asha lived in Pune and moved to Mumbai. A photo album that only shows today's address would say her 2023 birthday party was in Mumbai, which is wrong. A *slowly changing dimension* decides how the warehouse remembers that people and products change, slowly, over time.

The types

Type	What it does	History kept?	Cost
0	Never change (attribute fixed, like birth date)	n/a	none
1	Overwrite the old value	no	cheapest
2	Add a new row with validity dates	full	more rows, join by key or date
3	Add a column for the previous value	one step back	a column per tracked attribute

6	Hybrid of 1+2+3: new row per change (type 2) plus a column holding the current value on all rows (type 1 style)	full, plus easy "current" view	most complex

Type 2 columns: `valid_from`, `valid_to` (use a far-future date like `9999-12-31` for the open row so range filters work), and `is_current`. The fact table stores the **surrogate key** of the version that was true when the event happened. That is the reason we need surrogate keys: the natural key `C1` now has two rows.

Predict, Run, Explain: why SCD2 changes the answer

Customer C1 lived in Pune until 2024-02-01 and then in Mumbai. Order O1 (500) was in January, O2 (300) in February, O4 (250) in March. C2 (Delhi) bought O3 (1000). Using the star from 2.1, before you run it: how much revenue belongs to Pune, Mumbai and Delhi "as it was at the time"?

```
SELECT c.city, SUM(f.amount) AS revenue
FROM fact_sales f JOIN dim_customer c USING(customer_key)
GROUP BY 1 ORDER BY 1;
```

```
city    revenue
------  -------
Delhi   1000.0
Mumbai  550.0
Pune    500.0
```

Now the same question if we had used Type 1 (overwrite): every C1 order is attributed to the current city.

```
SELECT x.city, SUM(f.amount) AS revenue
FROM fact_sales f JOIN dim_customer c USING(customer_key)
JOIN (SELECT customer_id, city FROM dim_customer WHERE is_current=1) x ON
x.customer_id=c.customer_id
GROUP BY 1 ORDER BY 1;
```

```
city    revenue
------  -------
Delhi   1000.0
Mumbai  1050.0
```

Explain. With Type 2, O1 (500, January) points to customer_key 1 (Pune) and O2 and O4 point to key 2 (Mumbai): Mumbai = 300 + 250 = 550, Pune = 500. With Type 1, Pune disappears and Mumbai absorbs 500 + 300 + 250 = 1050. **Check:** both versions total 2550 (1000 + 550 + 500 and 1000 + 1050). *Interpretation:* Pune really did generate 500 of revenue in January, but Type 1 erased it. Use Type 2 when the business asks questions "as it was". Use Type 1 for corrections (a typo in a name) where history has no value.

Doing SCD2 in two steps (and proving it is idempotent)

A snapshot of the source arrives daily (`stg_customer`). Step A closes the current row when a tracked attribute changed. Step B inserts a new current row for changed or new customers. We run it for day 1, day 2, and then day 2 *again* to check idempotency.

```
CREATE TABLE stg_customer(customer_id TEXT, name TEXT, city TEXT);
CREATE TABLE dim_customer(customer_key INTEGER PRIMARY KEY AUTOINCREMENT,
customer_id TEXT, name TEXT, city TEXT,
                          valid_from TEXT, valid_to TEXT, is_current
INTEGER);
-- Day 1 load
INSERT INTO stg_customer VALUES('C1','Asha','Pune'),('C2','Ravi','Delhi');
INSERT INTO
dim_customer(customer_id,name,city,valid_from,valid_to,is_current)
SELECT customer_id,name,city,'2024-01-01','9999-12-31',1 FROM
stg_customer;
-- Day 2: Asha moved to Mumbai, Meena is new
DELETE FROM stg_customer;
INSERT INTO stg_customer VALUES('C1','Asha','Mumbai'),
('C2','Ravi','Delhi'),('C3','Meena','Chennai');
-- Step A: close changed rows
UPDATE dim_customer SET valid_to='2024-01-02', is_current=0
WHERE is_current=1 AND EXISTS (SELECT 1 FROM stg_customer s
      WHERE s.customer_id=dim_customer.customer_id AND
s.city<>dim_customer.city);
-- Step B: insert new current rows for changed or new customers
INSERT INTO
dim_customer(customer_id,name,city,valid_from,valid_to,is_current)
SELECT s.customer_id,s.name,s.city,'2024-01-02','9999-12-31',1 FROM
stg_customer s
LEFT JOIN dim_customer d ON d.customer_id=s.customer_id AND d.is_current=1
WHERE d.customer_id IS NULL;
SELECT * FROM dim_customer ORDER BY customer_key;
```

```
customer_key  customer_id  name   city     valid_from  valid_to
is_current
------------  -----------  -----  -------  ----------  ----------  -------
---
1             C1           Asha   Pune     2024-01-01  2024-01-02  0
2             C2           Ravi   Delhi    2024-01-01  9999-12-31  1
3             C1           Asha   Mumbai   2024-01-02  9999-12-31  1
4             C3           Meena  Chennai  2024-01-02  9999-12-31  1
```

After running steps A and B a second time:

```
rows_after_rerun  current_rows
----------------  ------------
4                 3
```

Explain. Step A matches only rows that are current and differ, so a re-run finds nothing to close (the Pune row is no longer current). Step B inserts only when no current row exists, so a re-run inserts nothing. Row count stays 4 and there are 3 current rows (one per customer). **Check:** exactly one current row per customer is the invariant you test in Chapter 5. *Interpretation:* a retry cannot create duplicate versions. This is idempotency applied to a dimension.

Type 3 and the point-in-time lookup:

```
CREATE TABLE dim_cust3(customer_id TEXT PRIMARY KEY, city TEXT, prev_city
TEXT);
INSERT INTO dim_cust3 VALUES('C1','Pune',NULL);
UPDATE dim_cust3 SET prev_city=city, city='Mumbai' WHERE customer_id='C1';
SELECT * FROM dim_cust3;
-- which city was C1 in on 2024-01-01 (SCD2 table above)?
SELECT city FROM dim_customer WHERE customer_id='C1' AND '2024-01-01' >=
valid_from AND '2024-01-01' < valid_to;
```

```
customer_id  city    prev_city
-----------  ------  ---------
C1           Mumbai  Pune
city
----
Pune
```

In the `UPDATE`, the right side `prev_city=city` uses the *old* value of `city` (SQL evaluates the right sides with the row's old values), so Pune moves to `prev_city` and then city becomes Mumbai. Note the half-open range `>= valid_from AND < valid_to`: a date equal to the change date belongs to the new row only, so ranges never overlap.

Problem 2.2.1 Ravi (C2) moves to Goa on 2024-04-01. Write the two SCD2 changes and say how many rows C2 has afterwards.

Step 1	Close the current row: `valid_to = '2024-04-01'`, `is_current = 0`.
Step 2	Insert a new row: Goa, `valid_from = '2024-04-01'`, `valid_to = '9999-12-31'`, `is_current = 1`.
Answer	C2 has 2 rows: Delhi (2023-05-01 to 2024-04-01) and Goa (from 2024-04-01). One is current.
Check	The Delhi row ends exactly where the Goa row begins, so there is no gap and no overlap.

Problem 2.2.2 A fact row for an order on 2024-03-15 must get the right `customer_key` for C1 (Pune until 2024-02-01, Mumbai after). Which key and why? Use the SCD2 table from 2.1 (keys 1 and 2).

Step 1	Find the version whose range contains 2024-03-15: key 1 covers 2023-01-01 to 2024-02-01, key 2 covers 2024-02-01 to 9999-12-31.
Step 2	2024-03-15 is inside key 2's range.
Answer	`customer_key = 2` (Mumbai).
Check	The date is after 2024-02-01, the move date, so Mumbai is correct. This lookup is done while loading the fact (a "surrogate key lookup").

Connection to the real job

dbt snapshots (Chapter 7) generate SCD2 for you. Late-arriving dimension rows (a fact arrives before its customer) are handled with an "unknown" placeholder row (key −1) and a later fix-up.

Applications

- **Data Analytics:** "revenue by the customer's segment *at purchase time*".
- **Data Science:** training sets must use attribute values valid at event time to avoid *leakage* (using future information).
- **Machine Learning:** point-in-time correct feature joins use exactly the `valid_from` / `valid_to` idea.
- **Compliance:** audit queries ("who had access on that date").

COMMON MISTAKE

Choosing `9999-12-31` for open rows and then forgetting that `valid_to` is exclusive in one query and inclusive in another. Pick one convention (we use `>= from AND < to`) and document it.

Check yourself

1. Which SCD type loses history? Answer: Type 1.
2. Why does Type 2 need a surrogate key? Answer: the natural key repeats across versions.
3. What makes SCD2 load idempotent? Answer: it only closes current rows that differ and only inserts when no current row exists.

2.3 Inmon, Data Vault, and Choosing a Model

INTUITION

Kimball builds many small shops (marts) designed around customers' questions. Inmon first builds one clean central warehouse (like a central kitchen) and delivers from it. Data Vault is an insurance policy against change: it stores raw facts with full audit trail, and you build marts on top.

- **Inmon (corporate information factory):** a normalized (3NF) enterprise warehouse first, then departmental marts. Strong consistency, slower to deliver.
- **Kimball (dimensional):** build business-process marts directly as stars with conformed dimensions. Faster to value, the most common style in analytics today.
- **Data Vault:** three table types.
  - **Hub:** a list of business keys only (`hub_customer` : customer_id, load date, record source).
  - **Link:** a relationship between hubs (`link_order` : customer hub key + product hub key).
  - **Satellite:** descriptive attributes of a hub or link, with load date, so history is kept by insertion (`sat_customer_details` : name, city, load date).

```
hub_customer (customer_hk, customer_id, load_dts, rec_src)
sat_customer (customer_hk, load_dts, name, city, hash_diff)     <- new row
on every change
link_order   (order_hk, customer_hk, product_hk, load_dts)
```

`hash_diff` is a hash of the descriptive columns; if today's hash differs from the latest one, insert a new satellite row. Data Vault loads are highly parallel and easy to audit, but queries need joins and you normally build a star (the "business vault" or marts) on top. Treat it as awareness-to-working level: know the three table types and when it is chosen (many source systems, strict audit, frequent source change).

Aspect	Kimball star	Inmon 3NF	Data Vault
Built for	analysts	enterprise integration	integration and audit
Query ease	high	medium	low (needs marts)
Handling source change	rework	rework	add satellites easily
Typical size of team	small to medium	large	large, regulated

Problem 2.3.1 The source adds a new attribute `loyalty_tier` to customers. What changes in (a) a Kimball dimension, (b) a Data Vault?

Step 1	(a) Add a column to `dim_customer`, backfill it, decide Type 1 or 2 for it, test.
Step 2	(b) Add a new satellite `sat_customer_loyalty` hanging off the existing hub. No existing table changes.
Answer	Kimball alters a table; Data Vault adds a table, which is why vault is called change-tolerant.
Check	In (b), existing loads and history are untouched, so nothing can break.

Problem 2.3.2 Pick a model: a 3-person startup wants dashboards in 4 weeks from one app database. Pick for a bank merging 14 legacy systems with audit rules.

Step 1	Startup: speed and simplicity matter. Kimball star (or OBT) with dbt.
Step 2	Bank: many sources, audit trail, constant change. Data Vault for the integration layer, stars for reporting.
Answer	Kimball for the startup, Data Vault plus marts for the bank.
Check	The startup has one source and no audit rule, so the extra layers of Data Vault would only slow it down.

Applications

- **Data Engineering:** choosing the model is a design-review topic.
- **Analytics Engineering:** marts in dbt are Kimball-style.
- **Regulated industries (banking, insurance, healthcare):** Data Vault is common.

COMMON MISTAKE

Treating the model choice as religion. Real teams mix: vault-like raw layer, star marts, OBT for one dashboard. Choose per layer by the question "who reads this and how often does it change?"

Check yourself

1. Name the three Data Vault tables. Answer: hub, link, satellite.
2. What does a satellite store? Answer: descriptive attributes with load dates (history).
3. Which style is fastest to first dashboard? Answer: Kimball.

Chapter recap

- Model for the question: facts hold measurements, dimensions hold context.
- Always state the grain in one sentence before adding columns. Mixed grain double counts.
- Fact types: transaction, periodic snapshot, accumulating snapshot. Additive, semi-additive, non-additive measures.
- Conformed dimensions and the bus matrix let different facts be compared.
- Star is the default; snowflake saves space but adds joins; OBT is fastest to query and costly to maintain.

- SCD Type 1 overwrites, Type 2 versions rows (valid_from, valid_to, is_current), Type 3 keeps one previous value, Type 6 combines.
- Surrogate keys let one business key have many versions. The fact stores the version key valid at event time.
- Inmon is normalized first, Kimball is marts first, Data Vault uses hubs, links and satellites.

Pattern	Rule
Revenue check after join	total before join = total after join
SCD2 columns	`valid_from`, `valid_to` (exclusive), `is_current`
Point in time	`d >= valid_from AND d < valid_to`
SCD2 invariant	exactly one current row per business key
Additivity	sum yes / semi (not over time) / no

Practice set

1. (easy) What is the grain of a table with one row per customer per month-end balance?
Answer: one customer at one month end (a periodic snapshot).

2. (easy) Put these into fact or dimension: `qty`, `city`, `amount`, `product_category`.
Answer: facts: qty, amount. Dimensions: city, product_category.

3. Fact total is 2050 before joining three dimensions and 4100 after. What went wrong?
Answer: a join multiplied rows (duplicate dimension keys, or many-to-many). Total doubled, so each fact row matched two dimension rows. Check dimension key uniqueness.

4. What does this output? `SELECT city FROM dim_customer WHERE customer_id='C1' AND '2024-02-01' >= valid_from AND '2024-02-01' < valid_to;` using the 2.1 data.
Answer: `Mumbai` because 2024-02-01 is not < the Pune row's `valid_to` (equal), but is >= the Mumbai row's `valid_from`.

5. Find the bug: an SCD2 load inserts a new current row for every staging row without closing the old one. **Answer:** several current rows per customer, and facts join twice. Close the old row first, insert only when changed.

6. A fact table keeps `unit_price`. Why is `SUM(unit_price)` wrong, and what to store?

Answer: price is non-additive. Store `qty` and `amount`; derive price as amount / qty (or a weighted average).

7. A table has Type 3 columns `city`, `prev_city`. A customer moves twice (Pune, Mumbai, Delhi). What is stored? **Answer:** city = Delhi, prev_city = Mumbai. Pune is lost, which is the limit of Type 3.

8. Design: "average delivery time per warehouse". Which fact type and why? **Answer:** an accumulating snapshot with ordered, shipped, delivered dates per order. Durations are differences between its date columns.

9. (interview) "Walk me through designing a warehouse for a food-delivery app." **Answer:** Choose a process (order delivery). Declare grain (one row per order). Dimensions: date, customer, restaurant, courier, location. Facts: item total, fee, discount, tip, delivery minutes. Use SCD2 for restaurant and customer attributes that affect reporting. Add a periodic snapshot for courier hours. Build a bus matrix and conform date and location.

10. (interview) "When would you use SCD Type 2 rather than Type 1?" **Answer:** When the business needs history "as it was", for example revenue by customer region at purchase time, audit, or ML features without leakage. Use Type 1 for corrections.

11. (scenario) A fact arrives for customer `C9`, but `dim_customer` has no `C9` yet. What do you do? **Answer:** Use the unknown-member key (for example −1) or insert a placeholder dimension row marked inferred, and update it when the real row arrives. Never drop the fact.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me
Kimball dimensional modeling: facts, dimensions, grain, star and snowflake
schemas. Use an online shop with real numbers. Show a small SQLite example
with output, then ask me 3 questions about grain and additivity, one at a
time, and correct my answers kindly.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Topic: slowly changing dimensions Type 1, 2, 3 and
```

6. Walk me step by step through an SCD2 load with a staging table and the SQL that closes old rows and inserts new ones. Then give me 8 graded exercises with different change scenarios, no solutions, and wait for my answers before checking them.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am applying for data engineering jobs. Topic: choosing between Kimball star, Inmon 3NF, Data Vault (hubs, links, satellites) and One Big Table. Make a comparison with real project examples and ask me to choose a model for 5 business cases. Explain each correct choice in simple English and name when I would NOT use it.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Topic: finding double counting caused by wrong grain or bad joins in a star schema. Give me 6 broken SQL queries on fact and dimension tables (with small sample data), ask me to predict the wrong total, find the bug and fix it. Do not give answers until I reply. Review my answers: [PASTE HERE]

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Topic: designing a performance-results warehouse (test runs, builds, scenarios, transactions) as a star schema. Ask me to state the grain, pick facts and dimensions, and decide where SCD2 is needed. Then run a mock interview of 6 questions about dimensional modeling, scoring each answer 1 to 5 with a model answer.

CHAPTER 3

FILE FORMATS, STORAGE AND LAKEHOUSE TABLE FORMATS

How data is written to disk decides how fast, how cheap and how safe everything after it is.

You will meet a surprising number of data problems that are not about SQL or Spark at all. They are about the file. A CSV with a comma inside a name breaks a load at 2 a.m. A folder with 50,000 tiny files makes a job ten times slower than it should be. A query scans 2 TB when it needed 20 GB because the files were not partitioned. In this chapter you will learn what CSV and JSON get wrong, why Parquet is the default for analytics, how compression and partitioning save money, why the small-file problem hurts, and how table formats such as Delta Lake and Iceberg add safe updates on top of plain files. We will measure effects with real code you can run, and one toy table format you can read in 20 lines.

3.1 Text Formats: CSV and JSON, and Their Traps

INTUITION

A CSV file is a letter written by hand: anyone can read it, but there is no agreed handwriting. Is a blank an empty text or a missing value? Is `07` a number or a pin code? Text formats are friendly for humans and risky for machines.

Words you need

Word	Plain meaning
Delimiter	The character that separates fields (comma, tab, pipe)
Quoting	Wrapping a field in `"` so special characters inside are safe
Encoding	How characters become bytes (UTF-8 is the safe default)
Schema	The names and types of the columns

JSON Lines (NDJSON)	One JSON object per line; can be split and streamed

Predict, Run, Explain: what breaks in CSV and JSON

Before you run it: if you split a CSV text on newlines, how many lines do two records give when one record has a line break inside a field?

```
import csv, io, json
tricky = [("1","Doe, John",'said "hi"',"007"),
("2","line\nbreak","x","1.50")]
b = io.StringIO(); csv.writer(b).writerows(tricky);
print(repr(b.getvalue()))
naive = b.getvalue().split("\n"); print("naive split gives", len(naive)-1,
"lines for 2 records")
print("csv module read:", list(csv.reader(io.StringIO(b.getvalue()))))
print("leading zero lost if cast to int:", int("007"))
print("json float:", 0.1+0.2, "| big int:", json.loads('{"x":
12345678901234567890}')["x"])
```

Real output:

```
'1,"Doe, John","said ""hi""",007\r\n2,"line\nbreak",x,1.50\r\n'
naive split gives 3 lines for 2 records
csv module read: [['1', 'Doe, John', 'said "hi"', '007'], ['2',
'line\nbreak', 'x', '1.50']]
leading zero lost if cast to int: 7
json float: 0.30000000000000004 | big int: 12345678901234567890
```

Explain.

- The CSV writer put quotes only where needed: around `Doe, John` (a comma), around `said "hi"` (and doubled the inner quotes to `""`), and around the field with a line break. It left `007` alone.
- Splitting on `\n` found 3 pieces for 2 records, because the line break inside "line\nbreak" is data, not a record end. A real parser (the `csv` module) reads it correctly. Never parse CSV with `split(",")`.
- `int("007")` is 7: the leading zeros are gone. Pin codes, phone numbers and IDs should stay as text. Spark's `inferSchema` and pandas guess types and can make this mistake.
- Python's JSON parser kept the 20-digit integer, but many other tools (JavaScript, some warehouses) convert it to a float and lose digits. `0.1 + 0.2` shows binary float noise:

store money as integers (paise) or decimals.

- *Interpretation:* text formats carry no types, no null rule, no guarantee. You must defend against all three.

Common CSV and JSON pitfalls

Pitfall	Example	Defence
Delimiter in data	`Doe, John`	proper quoting; use a real parser
Embedded newline	address with line break	parser with quote support
Encoding	`Ã©` instead of `é`	declare UTF-8, test with non-English names
Type guessing	`007` becomes 7, `1e5` becomes 100000.0	explicit schema
Null vs empty	`,,` could be empty text or missing	agree on a null token
Date formats	`03/04/2024` is March or April?	ISO 8601: `2024-04-03`
Header drift	a column is added in the middle	read by name, validate header
JSON nesting	arrays and objects inside objects	flatten or keep as struct
JSON array file	one giant `[...]` must be fully read	use JSON Lines
No schema	a field is a string today, a number tomorrow	schema check on ingest (Chapter 5)

JSON Lines looks like this, and each line is a complete record:

```
{"id": 0, "city": "Delhi"}
{"id": 1, "city": "Pune"}
{"id": 2, "city": "Pune"}
```

Problem 3.1.1 A CSV has 3 columns. The row `101,Sharma, Raj,450` is read. How many fields does a naive split give, and what is the bug?

Step 1	Splitting on commas gives `101`, `Sharma`, `Raj`, `450`: 4 fields.
Step 2	The schema has 3 columns, so the row looks like it has one too many. The source forgot to quote the name.
Answer	4 fields; the source file is malformed, so reject or quarantine it rather than guess.
Check	If the name were quoted (`101,"Sharma, Raj",450`), the parser would give 3 fields.
Why it matters	Guessing silently corrupts columns (the amount lands in the wrong column).

Problem 3.1.2 A phone number `0987654321` is loaded as an integer and then exported. What is lost, and how many digits remain?

Step 1	As a number: 987654321 (the leading 0 is not part of the value).
Step 2	Original had 10 digits, the exported one has 9.
Answer	One digit is lost; phone numbers, pin codes and account numbers are identifiers, not numbers, so use a string type.
Check	`len("0987654321")` is 10 and `len(str(int("0987654321")))` is 9.

Connection to the real job

Most ingestion code starts with CSV or JSON from partners and APIs. The first thing a good pipeline does is write them to a typed format (Parquet) with an explicit schema, and reject bad lines to a quarantine folder.

Applications

- **Data Engineering:** landing zones receive CSV/JSON, then convert.
- **Data Analytics:** Excel exports are CSV; know the encoding issues.
- **GenAI:** JSON Lines is the standard format for fine-tuning and evaluation datasets.
- **API integration:** JSON is the language of REST APIs.

COMMON MISTAKE

Letting `inferSchema` decide types in production. Today's sample file says the column is an integer; tomorrow one row has "N/A" and the job fails, or worse, silently becomes null. Always give an explicit schema.

Check yourself

1. Why not `line.split(",")` ? Answer: commas and newlines can appear inside quoted fields.
2. Which format can be split and streamed line by line, JSON array or JSON Lines? Answer: JSON Lines.
3. How should an account number be stored? Answer: as text.

3.2 Columnar Formats: Parquet, ORC, Avro, Arrow

INTUITION

Row storage is a stack of index cards, each card holding everything about one customer. Columnar storage is a set of drawers, one drawer per attribute: all cities in one drawer, all amounts in another. To total all amounts you open one drawer, not every card.

How the formats differ

Format	Layout	Best for	Notes
Parquet	columnar, files split into row groups	analytics, data lakes, ML	default in Spark, DuckDB, Athena, BigQuery loads
ORC	columnar	Hive and older Hadoop ecosystems	similar ideas to Parquet
Avro	row-based, schema stored with data	streaming (Kafka), schema evolution	pairs with a Schema Registry

Arrow	in-memory columnar	passing data between tools without copying	not a storage file format by itself (the file form is called Feather / Arrow IPC)
CSV / JSON	text rows	exchange with humans and APIs	see 3.1

Inside a Parquet file

Parquet file layout: row groups containing column chunks, plus a footer with statistics

How to read it: the file is cut into **row groups** (a block of rows, often around 128 MB). Inside each group, every column has its own **column chunk**, which is split into pages and compressed. The **footer** at the end holds the schema and, for every column chunk, the minimum value, maximum value and null count. A reader first reads the footer (the last bytes of the file), then fetches only the column chunks it needs.

Two big tricks come from this layout:

- **Column pruning:** `SELECT amount` reads only the `amount` chunks.
- **Predicate pushdown:** for `WHERE amount > 450` , if a row group's max is 300, the whole group is skipped using the footer statistics, without reading it.

Values in one column are alike, so Parquet also uses **dictionary encoding** (store each distinct city once, then a small number per row), **run-length encoding** (store "A, repeated 500 times") and then a general **compression** codec.

Predict, Run, Explain: why columns compress better

We do not have pyarrow installed here (the sandbox cannot download packages), so we simulate the idea with plain Python and `zlib` (the same family of compression as gzip). We make 20,000 rows, write them as CSV rows, then as column blocks, and compress both.

Before you run it: will the column layout compress smaller than the row layout? Which single column will compress best?

```
import csv, io, zlib, random
random.seed(7)
N = 20000
cities = ['Pune','Mumbai','Delhi','Chennai','Kolkata']
rows = [(i, random.choice(cities), random.choice(['A','B','C']),
         round(random.uniform(10,500),2), f"2024-01-
{random.randint(1,28):02d}") for i in range(N)]
csv_buf = io.StringIO(); csv.writer(csv_buf).writerows(rows); row_bytes =
csv_buf.getvalue().encode()
cols = list(zip(*rows))
col_bytes = b"".join(("\n".join(map(str, c)) + "\n").encode() for c in
cols)
print("raw row-layout bytes   :", len(row_bytes))
print("raw column-layout bytes:", len(col_bytes))
print("zlib row-layout        :", len(zlib.compress(row_bytes, 6)))
print("zlib column-layout     :", len(zlib.compress(col_bytes, 6)))
for n, c in zip(['id','city','tier','amount','day'], cols):
    b = ("\n".join(map(str, c)) + "\n").encode()
    print(f"  col {n:7s} raw {len(b):7d} zlib
{len(zlib.compress(b,6)):7d}")
```

Real output:

```
raw row-layout bytes   : 658869
raw column-layout bytes: 638869
zlib row-layout        : 159095
zlib column-layout     : 141110
  col id      raw  108890 zlib   43755
  col city    raw  135625 zlib   10963
  col tier    raw   40000 zlib    5756
  col amount  raw  134354 zlib   54869
  col day     raw  220000 zlib   21266
```

Explain.

- The raw sizes differ by 20,000 bytes (658,869 − 638,869) because the row layout carries one extra comma or newline per row and the column layout only a newline.
- After compression the row layout is 159,095 bytes and the column layout 141,110 bytes. Savings: (159,095 − 141,110) / 159,095 = 17,985 / 159,095 = 11.3%.
- Per column: `city` shrank from 135,625 to 10,963 bytes (8.1% of its raw size), `tier` from 40,000 to 5,756. `amount` , which is random decimals, compressed least (54,869 of 134,354, 41%). **Check:** adding the five separate column sizes gives 43,755 + 10,963 +

5,756 + 54,869 + 21,266 = 136,609 bytes, within 3% of the 141,110 bytes for the one-stream compression (the gap comes from how the compressor behaves on one long stream; we did not investigate it further). Low-variety columns win big.

- *Interpretation:* real Parquet uses dictionary and run-length encoding before compression, so it does far better than plain zlib on columns like `city`: a dictionary of 5 cities needs about 3 bits per row, which for 20,000 rows is 7.5 KB (20,000 × 3 / 8 = 7,500 bytes) against 135,625 bytes of text.

KEY INSIGHT

For analytics, you pay for bytes scanned (in time on a lake, in money on serverless engines). Columnar layout plus compression plus pruning can cut bytes read by 10 to 100 times compared with CSV.

Parquet with pyarrow looks like this. **Not run here** (pyarrow could not be installed in this sandbox); the calls are standard:

```
import pyarrow as pa, pyarrow.parquet as pq
table = pa.Table.from_pylist([{"id": 1, "city": "Pune", "amount": 250.0}])
pq.write_table(table, "orders.parquet", compression="zstd")
print(pq.ParquetFile("orders.parquet").metadata)        # row groups,
rows, footer info
only_amount = pq.read_table("orders.parquet", columns=["amount"])   #
column pruning
filtered = pq.read_table("orders.parquet", filters=[("amount", ">", 100)])
# predicate pushdown
```

And with DuckDB, which can query a Parquet file with SQL (also **not run here**):

```
SELECT city, SUM(amount) FROM 'orders.parquet' GROUP BY city;
COPY (SELECT * FROM 'orders.csv') TO 'orders.parquet' (FORMAT PARQUET,
COMPRESSION ZSTD);
```

Avro and schema evolution

Avro is *row* oriented and stores its schema (a JSON description) with the data. That suits a stream of whole messages. With a **Schema Registry** (a service that stores versions of each schema), a Kafka message carries only a small schema id. Rules for safe evolution: adding a field **with a default** is backward compatible (new readers can read old data); removing a field

that had no default breaks readers. Parquet also allows adding columns (old files simply return null for them), but renaming and changing types need care.

Problem 3.2.1 A Parquet file has 10 row groups. A query has `WHERE order_date = '2024-03-15'`. The footer shows that only 1 row group has min ≤ 2024-03-15 ≤ max. How much data is read versus a full scan, if each group is 128 MB and the query reads 2 of 20 columns?

Formula	bytes read ≈ matching groups × group size × (columns read / total columns)
Plug in	1 × 128 MB × (2 / 20)
Compute	128 × 0.1 = 12.8 MB
Answer	About 12.8 MB, against 10 × 128 = 1,280 MB for a full scan of all columns, which is 100 times less. (This assumes equal column sizes. Real columns differ.)
Check	1/10 of the groups times 2/20 of the columns is 1/100.
Why it matters	Sorting data by the filter column before writing makes min/max ranges narrow, so pushdown works. Unsorted data has every group span the full range and nothing is skipped.

Problem 3.2.2 A column `city` has 5 distinct values over 1,000,000 rows. Roughly how many bits per row does dictionary encoding need, and how many bytes in total (ignoring the dictionary)?

Step 1	5 values need $\lceil \log_2 5 \rceil = 3$ bits (2 bits cover only 4 values).
Step 2	1,000,000 × 3 bits = 3,000,000 bits = 375,000 bytes.
Answer	About 375 KB, against about 6.8 MB as text (average 6.8 bytes per city name, per our sample above).
Check	135,625 bytes for 20,000 rows is 6.78 bytes per row; × 1,000,000 = 6.78 MB.

Connection to the real job

Typical rule: land raw files as they come (bronze), but store everything downstream as Parquet (or Delta/Iceberg, which use Parquet inside) with zstd or snappy compression. Kafka topics use Avro or Protobuf with a registry.

Applications

- **Data Engineering:** Parquet in the lake, Avro on Kafka.
- **Data Analytics:** Athena or BigQuery external tables over Parquet are cheaper than CSV.
- **Machine Learning:** training reads feature columns only; Parquet gives fast loading into pandas or Spark.
- **MLOps:** Arrow moves data between pandas, Spark and model servers without copies.

COMMON MISTAKE

Expecting Parquet to speed up a query that reads all columns of unsorted data. Gains come from pruning, pushdown and compression. If you read everything, you get only the compression benefit.

Check yourself

1. What does the Parquet footer hold? Answer: schema plus min/max/null stats per column chunk.
2. Which format fits Kafka messages with a schema registry? Answer: Avro (or Protobuf).
3. What is predicate pushdown? Answer: skipping row groups using min/max statistics before reading data.

3.3 Compression, Partitioning and the Small-File Problem

INTUITION

A library has books (data), a catalogue (metadata) and shelves labelled by year (partitions). If you want 2024 books, you walk to the 2024 shelf. If every page of every book is a separate sheet in a separate envelope (small files), you spend all day opening envelopes.

Compression codecs

Codec	Speed	Size	Splittable alone?	Typical use
snappy	very fast	medium	not by itself, but fine inside Parquet	default for Parquet in Spark

zstd	fast	smaller than snappy	inside Parquet yes	good modern default for cold and warm data
gzip	slow	small	no (a single .gz file cannot be split for parallel read)	archives, final delivery
lz4	extremely fast	larger	inside Parquet yes	real-time, Kafka

"Splittable" matters: a 5 GB `.csv.gz` file must be read by one task, so a cluster of 100 cores waits for one core. Inside Parquet, compression is applied per column page, so the file is still splittable at row-group boundaries.

Hive-style partitioning

Store data in folders named by a column value:

```
orders/
  day=2024-01-01/part-0000.parquet
  day=2024-01-02/part-0000.parquet
  ...
```

A query with `WHERE day = '2024-01-05'` opens only that folder. This is **partition pruning**.

Predict, Run, Explain: partitions and the small-file problem

We write 20,000 rows split by day (28 days), and read one day. Then we compare one 20,000-line file against the same lines split across 2,000 tiny files. Before you run it: how many folders and rows will the day query read? Will 2,000 files be 2,000 times slower than one?

```
import os, tempfile, time, random
random.seed(7)
N = 20000
rows = [(i, random.choice(['Pune','Mumbai','Delhi']),
random.randint(1,28)) for i in range(N)]
# partition by day
base = tempfile.mkdtemp()
for i, city, d in rows:
    p = f"{base}/day=2024-01-{d:02d}"; os.makedirs(p, exist_ok=True)
    with open(p + "/part.csv", "a") as f: f.write(f"{i},{city},{d}\n")
parts = sorted(os.listdir(base)); print("partitions:", len(parts),
parts[:3])
n = sum(1 for _ in open(f"{base}/day=2024-01-05/part.csv"))
print(f"query day=2024-01-05 reads 1 of {len(parts)} folders, {n} of {N}
rows")
# small files: same lines, 1 file vs 2000 files
lines = [f"{i},{c},{d}\n" for i, c, d in rows]
d1 = tempfile.mkdtemp(); open(d1 + "/one.csv", "w").writelines(lines)
d2 = tempfile.mkdtemp()
for k in range(2000): open(f"{d2}/p{k}.csv", "w").writelines(lines[k*10:
(k+1)*10])
def readall(d):
    t = time.perf_counter(); n = 0
    for fn in os.listdir(d):
        with open(os.path.join(d, fn)) as f: n += sum(1 for _ in f)
    return n, time.perf_counter() - t
for lab, d in (("1 file", d1), ("2000 files", d2)):
    n, t = readall(d); print(f"{lab:11s} lines={n} read_time={t*1000:.1f}
ms")
```

Real output of exactly this code:

```
partitions: 28 ['day=2024-01-01', 'day=2024-01-02', 'day=2024-01-03']
query day=2024-01-05 reads 1 of 28 folders, 716 of 20000 rows
1 file      lines=20000 read_time=5.6 ms
2000 files  lines=20000 read_time=3395.1 ms
```

Explain.

- The day query touched 716 of 20,000 rows: 716 / 20,000 = 3.58%, close to the 1/28 = 3.57% you expect from 28 equal days. Pruning avoids reading the rest.
- The same 20,000 lines took 5.6 ms from one file and 3,395.1 ms from 2,000 files: 3,395.1 / 5.6 = 606 times slower. The data size is identical. Every file costs an open, a metadata

lookup and a task. On this laptop each file costs about 1.7 ms (3,395.1 / 2,000 = 1.70 ms); your machine will differ, but the pattern holds. On cloud object storage each file costs a network request of tens of milliseconds, and Spark schedules a task per file, so the damage is far worse.

- *Interpretation:* total work is `files × cost per file + bytes / throughput`. With tiny files the first term dominates. Aim for files of roughly 128 MB to 1 GB.

Fixing small files (compaction): periodically run a job that reads many small files and writes fewer large ones (Spark `repartition` / `coalesce`, Delta `OPTIMIZE`, Iceberg `rewrite_data_files`). Prevent them by batching writes, not writing every minute into 1,000 partitions, and by tuning the number of output files.

Choosing a partition column. Good: low cardinality (few distinct values), used in filters, and gives files of decent size, such as date. Bad: `customer_id` (millions of folders), or a column no one filters on.

Problem 3.3.1 Daily data is 200 GB. You partition by `day` and `country` (50 countries). How big is an average file if each partition writes one file? Is it good?

Formula	average file = daily size / (number of partitions that day)
Plug in	200 GB / 50
Compute	4 GB per file
Answer	4 GB average. Skew matters, but this is large, so split each partition into several files (for example 8, giving 512 MB each: 4 GB / 8 = 0.5 GB). That is fine.
Check	50 × 8 × 0.5 GB = 200 GB.
Why it matters	If instead you partition by `day`, `country`, `city` (about 5,000 pairs), then each file is 200 GB / 5,000 = 40 MB, and you have the small-file problem.

Problem 3.3.2 An hourly job writes 1 file per partition into 24 hourly folders, each folder gets 500 MB a day in total. How many files per day, and what size each? After one year, how many files?

Step 1	24 files per day, each 500 MB / 24 = 20.8 MB if volume is even.
Step 2	24 × 365 = 8,760 files in a year in this single table.
Answer	24 files/day of about 21 MB (too small) and 8,760 per year. Compact each day into 1 file of 500 MB: 365 files per year.
Check	365 × 500 MB = 182.5 GB a year of data either way; only the file count changes.

Object storage: S3, ADLS, GCS

Cloud lakes live in **object storage**: Amazon S3, Azure Data Lake Storage Gen2 (ADLS), Google Cloud Storage (GCS). An object is a file plus metadata, addressed by a key (path). They are cheap, durable, and scale without limit, but are not a file system: renaming a "folder" is really copy-and-delete of every object, and listing millions of keys is slow.

Topic	Practice
Layout	`s3://company-lake/bronze/orders/ingest_date=2024-06-01/` (zone, dataset, partition)
Naming	lowercase, no spaces, stable; avoid millions of tiny files per prefix
Lifecycle policy	move to cheaper storage class after N days, delete temp data, expire old versions
Permissions	least privilege via IAM (AWS), RBAC (Azure), IAM (GCP); separate raw and curated buckets; no public buckets
Durability	built in; turn on versioning for accident recovery

Connection to the real job

You will tune file sizes and partition columns on almost every lake project, and cost reports often point to "one table scans too much". Ask "is this table partitioned by what people filter on?"

Applications

- **Data Engineering:** compaction jobs, lifecycle rules, layout conventions.
- **Data Analytics:** queries on Athena/BigQuery external tables become cheaper with partition

filters.

- **FinOps:** serverless engines bill per bytes scanned, so partition pruning is cost control.
- **Machine Learning:** reading training data by date range uses the same partitions.

COMMON MISTAKE

Partitioning by a high-cardinality column such as `user_id`, creating millions of folders and tiny files. Partition by date (or similar), and use clustering or sorting inside files for the rest.

Check yourself

1. Why is a single 5 GB .gz CSV slow on a cluster? Answer: gzip text cannot be split, so one task reads it all.
2. Ideal file size range? Answer: about 128 MB to 1 GB.
3. What is partition pruning? Answer: reading only the folders that match the filter.

3.4 Table Formats: Delta Lake, Iceberg, Hudi

INTUITION

Plain files in a lake are like paper pages in a folder: you can add pages, but to change one sentence you must reprint the page, and if two people do it at once you get a mess. A table format adds a **ledger** (a log of "page added, page removed") so that changes are all-or-nothing and you can see the folder as it looked yesterday.

Why they exist

A lake of Parquet files has no transactions. A job that writes 100 files and fails at 60 leaves a half-written table that readers can see. You cannot do `UPDATE`, `DELETE` or `MERGE` safely. Table formats fix this by keeping **immutable data files** plus a **commit log** (metadata). A reader first reads the log to find which files make up the current version.

Feature	Meaning
ACID on lakes	a commit becomes visible all at once
Time travel	read the table as of a version or timestamp

Schema evolution	add, rename, drop columns tracked in metadata
Upserts / MERGE	update rows by rewriting affected files (or writing delete files)
Compaction	merge small files, remove old ones

The three main formats: **Delta Lake** (born at Databricks; `_delta_log` folder of JSON and checkpoint files), **Apache Iceberg** (metadata tree of manifest files; engine-neutral; hidden partitioning), **Apache Hudi** (strong for incremental upserts and streaming ingestion). All three store data in Parquet. A **catalog** is the directory that maps a table name to its current metadata: Hive Metastore, Unity Catalog, AWS Glue, Nessie (Git-like versions), and the Iceberg REST catalog.

Predict, Run, Explain: a toy table format

This toy is **not** Delta Lake. It shows the core idea in a few lines: data files never change, and an ordered log of `add` / `remove` actions defines each version. Before you run it: after the UPDATE of id 2 from Delhi to Mumbai, which files make up the table? Can we still read version 0?

```
import json, os, tempfile
root = tempfile.mkdtemp(); os.makedirs(root + "/_log")
def write_file(name, rows): json.dump(rows, open(f"{root}/{name}", "w"))
def commit(version, actions): json.dump(actions, open(f"
{root}/_log/{version:03d}.json", "w"))
def snapshot(as_of=None):
    files = set()
    for fn in sorted(os.listdir(root + "/_log")):
        v = int(fn[:3])
        if as_of is not None and v > as_of: break
        for a in json.load(open(f"{root}/_log/{fn}")):
            (files.add if a["op"] == "add" else files.discard)(a["file"])
    rows = []
    for f in sorted(files): rows += json.load(open(f"{root}/{f}"))
    return sorted(files), rows
write_file("f1.json", [{"id":1,"city":"Pune"}, {"id":2,"city":"Delhi"}]);
commit(0, [{"op":"add","file":"f1.json"}])
write_file("f2.json", [{"id":3,"city":"Goa"}]);
commit(1, [{"op":"add","file":"f2.json"}])
# UPDATE id=2 -> Mumbai: never edit a file. Rewrite f1 without id 2, write
f3, commit both together.
write_file("f1b.json", [{"id":1,"city":"Pune"}])
write_file("f3.json",  [{"id":2,"city":"Mumbai"}])
commit(2, [{"op":"remove","file":"f1.json"},
{"op":"add","file":"f1b.json"}, {"op":"add","file":"f3.json"}])
for v in (0, 1, 2, None):
    files, rows = snapshot(v); print("version", v, "files", files, "rows",
[(r['id'], r['city']) for r in rows])
```

Real output (from running the same logic):

```
version 0 files ['f1.json'] rows [(1, 'Pune'), (2, 'Delhi')]
version 1 files ['f1.json', 'f2.json'] rows [(1, 'Pune'), (2, 'Delhi'),
(3, 'Goa')]
version 2 files ['f1b.json', 'f2.json', 'f3.json'] rows [(1, 'Pune'), (3,
'Goa'), (2, 'Mumbai')]
version None files ['f1b.json', 'f2.json', 'f3.json'] rows [(1, 'Pune'),
(3, 'Goa'), (2, 'Mumbai')]
```

Explain.

- Version 2's single commit removes `f1.json` and adds two files. Readers who read the log up to version 1 still see `f1.json`, which was never deleted from disk. That is **time travel**: version 0 still shows Delhi.

- A crash between `write_file` calls and `commit(2, ...)` leaves orphan files that no version references. The table is unchanged: that is **atomicity**. Orphans are removed later by a cleanup job (Delta `VACUUM`, Iceberg `expire_snapshots`).
- The final snapshot (`None` = latest) equals version 2. **Check:** the row count is 3 in versions 1 and 2, as expected for 1 update and 0 inserts after version 1.
- *Interpretation:* real formats add checkpoints (a summary of the log so that readers do not replay thousands of commits), statistics per file for skipping, and optimistic concurrency (two writers both try to write commit N; one wins, the other retries).

In Spark with Delta it looks like this (**not run here**):

```
MERGE INTO silver.customers t USING updates s ON t.id = s.id
WHEN MATCHED THEN UPDATE SET *
WHEN NOT MATCHED THEN INSERT *;
SELECT * FROM silver.customers VERSION AS OF 3;        -- time travel
OPTIMIZE silver.customers;                             -- compaction
```

Problem 3.4.1 A table has 1,000 files after 1,000 commits and each commit adds 1 file. A reader replays the log. How many log entries without a checkpoint, and with a checkpoint every 10 commits when the latest commit is number 1,000?

Step 1	Without a checkpoint the reader replays all 1,000 commits.
Step 2	With a checkpoint at commit 1,000 (a multiple of 10), the reader reads the checkpoint (1 file) and zero later commits.
Answer	1,000 entries versus about 1 checkpoint read (at most 9 extra commits in other cases).
Check	The worst case is 9 commits after the latest checkpoint, since checkpoints come every 10.

Problem 3.4.2 Choose a format: (a) streaming upserts from a database into a lake with a Databricks team; (b) a multi-engine setup using Spark, Trino and Snowflake reading the same tables; (c) heavy record-level updates on a large lake with incremental pulls.

Step 1	(a) Delta Lake is the native fit.
Step 2	(b) Iceberg is designed for engine neutrality.
Step 3	(c) Hudi's design focuses on record-level upserts and incremental queries.
Answer	(a) Delta, (b) Iceberg, (c) Hudi. In practice all three keep converging, and many platforms can read more than one, so check what your engine supports.
Check	These are the usual associations, not rules. Verify features in the current documentation, since all three move fast.

Query engines over lake data

Engine	What it is	Use
Spark SQL	distributed engine (Chapter 9)	big ETL
Trino / Presto	distributed SQL on many sources, no storage of its own	interactive queries over lakes
Athena	serverless Presto/Trino on S3, pay per bytes scanned	ad-hoc lake queries on AWS
DuckDB	in-process analytic engine (like SQLite for analytics)	local work, learning, tests, small to medium data
ClickHouse	columnar OLAP database	fast aggregations, logs, product analytics
Druid / Pinot	real-time OLAP stores	user-facing dashboards with sub-second queries on streams

Applications

- **Data Engineering:** MERGE-based CDC apply, GDPR deletes, compaction.
- **Machine Learning:** time travel gives reproducible training sets ("the table as of model v7 training").
- **Analytics:** one governed copy for BI and ML.
- **MLOps:** dataset versioning without copying data.

COMMON MISTAKE

Forgetting maintenance. Without compaction and cleanup, a table format accumulates small files and old versions, and queries slow down while storage cost grows. Schedule `OPTIMIZE` / `VACUUM` (Delta) or rewrite/expire (Iceberg).

Check yourself

1. What two things make a table format? Answer: immutable data files plus a commit log.
2. Why can readers still see old data after an update? Answer: old files stay until cleanup; the log lets you read an earlier version.
3. What is a catalog? Answer: the directory mapping table names to their current metadata.

Chapter recap

- CSV and JSON have no types and many traps: quoting, encoding, leading zeros, nulls. Always give an explicit schema and parse with a real parser.
- Parquet is columnar with row groups, column chunks and a footer of min/max stats, enabling column pruning and predicate pushdown.
- Avro is row-based with a schema, ideal for Kafka plus a Schema Registry.
- Column layouts compress better because neighbours are alike (dictionary and run-length encoding).
- Partition by low-cardinality filter columns (like date). Prune partitions to cut bytes scanned.
- Small files are slow: cost is files × per-file overhead. Compact to roughly 128 MB to 1 GB.
- Object storage is cheap and durable but not a file system. Use layout conventions, lifecycle rules and least-privilege permissions.
- Delta, Iceberg and Hudi add ACID, time travel and MERGE to lake files via a commit log; run compaction and cleanup.

Pattern	Rule
Bytes read	matching groups × group size × (columns read / total columns)
Files cost	files × per-file overhead + bytes / throughput
Target file size	128 MB to 1 GB

Dictionary bits	$\lceil \log_2 \text{distinct values} \rceil$ per row
Partition column	low cardinality, used in filters (date)
Maintenance	OPTIMIZE / VACUUM (Delta), rewrite / expire (Iceberg)

Practice set

1. (easy) Which format is human readable and has no types: Parquet, CSV, Avro? **Answer:** CSV.

2. (easy) A column has 4 distinct values. How many bits per row for dictionary encoding? **Answer:** $\lceil \log_2 4 \rceil = 2$ bits.

3. What is printed? `int("0042")` **Answer:** 42. The leading zeros disappear.

4. A table is 1.2 TB in Parquet with 60 columns of similar size. A query reads 3 columns. About how much is read (ignoring pruning by rows)? **Answer:** 1.2 TB × 3 / 60 = 0.06 TB = 60 GB.

5. Find the bug: `df.write.partitionBy("customer_id").parquet(path)` on 5 million customers. **Answer:** 5 million folders and tiny files. Partition by date; use sorting or bucketing for customer_id.

6. A daily job writes 400 GB across 1,600 files. Average file size? **Answer:** 400 GB / 1,600 = 0.25 GB = 250 MB. Healthy.

7. The same job after a change writes 400 GB across 80,000 files. Size and problem? **Answer:** 400,000 MB / 80,000 = 5 MB each: small-file problem. Compact or reduce output partitions.

8. Why does Parquet min/max skipping fail on unsorted data? **Answer:** each row group then contains values across the full range, so min/max cannot exclude any group.

9. (interview) "What is the difference between a data lake and a lakehouse?" **Answer:** A lake is files in object storage with no transactions or table semantics. A lakehouse adds a table format (Delta, Iceberg, Hudi) giving ACID, schema enforcement, time travel and MERGE, so one copy of data serves both BI and ML.

10. (interview) "Explain Parquet internals." **Answer:** Columnar file made of row groups; each has one chunk per column, split into compressed pages with dictionary or run-length encoding; the footer has schema and min/max/null stats. Readers prune columns, push predicates down to skip groups, and read in parallel by row group.

11. (scenario) A nightly Spark job on 3 TB of `.csv.gz` takes 5 hours on 100 cores although most cores are idle. Why and what do you do? **Answer:** gzip text is not splittable, so each file is read by one task and a few huge files cause a long tail. Convert once to Parquet (zstd/snappy), partition by date, target 128 MB to 1 GB files, and read the Parquet in later jobs.

Prompt pack

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Explain the
traps of CSV and JSON files (quoting, encoding, leading zeros, null versus
empty, type guessing) with small Python examples. Show the wrong version
and its result, then the fix. Then give me 6 practice problems with a
corrupted CSV, no solutions, and review my answers one by one.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles. Explain how a Parquet file is laid out (row
groups, column chunks, pages, footer statistics, dictionary and run-length
encoding) with an analogy first. Then give me a calculation exercise about
column pruning and predicate pushdown with real numbers, and wait for my
answer before showing the steps.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles. Topic: partitioning strategy, file sizes and the
small-file problem in a data lake on S3 or ADLS. Describe a realistic
scenario with daily volume and cardinalities, ask me to choose partition
columns and compute file sizes, then critique my choice and explain
compaction, lifecycle policies and cost.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Topic: Delta
Lake, Apache Iceberg and Apache Hudi table formats (commit log, time
travel, MERGE, compaction, catalogs). Explain with a ledger analogy, walk
me through what happens on an UPDATE and on a failed write, then quiz me
```

one question at a time on when to choose which format.

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional moving into data roles, and I am applying for data engineering roles. Run a mock interview about file formats and lakehouse storage: Parquet internals, Avro and schema registry, compression and splittability, partitioning, small files, Delta versus Iceberg, DuckDB and Athena. Ask 8 questions one at a time, grade each answer 1 to 5, and show a model answer in simple English. My answers: [PASTE HERE]
```

CHAPTER 4

INGESTION PATTERNS

How to copy data from the outside world into your platform: completely, incrementally, safely, and again after a failure.

Every pipeline starts with a hard question: "How do I get the data in without missing anything, without duplicating anything, and without hurting the source?" A new order arrives, an old order is changed, a customer is deleted, an API returns page 3 twice, a job crashes halfway. This chapter gives you the patterns that answer those cases: full load, incremental load with a watermark, change data capture (CDC), API pagination and retries, file drops and webhooks. You will write and run a working incremental loader in Python and SQLite, break it on purpose, and fix it. By the end you will be able to design an ingestion job that you can re-run at any time and trust.

Our running example is the ShopKart `orders` table: it has `id`, `amount` and `updated_at`.

4.1 Full Load vs Incremental Load and the Watermark

INTUITION

You keep a diary of your friend's bank statement. The *full load* way is to photocopy the whole statement every night. The *incremental* way is to write down only the lines after the last line you already have. The "last line you already have" is the **watermark**.

Words you need

Word	Plain meaning
Full load	Copy everything, replace the target
Incremental load	Copy only new or changed rows since last time
Watermark (high-water mark)	The largest `updated_at` (or id) already loaded; the next run starts after it
Upsert	Insert if the key is new, update if it exists

State table	A small table that remembers the watermark between runs
Page	One chunk of results from an API

Pattern	When it fits	Cost	Risk
Full load	small tables (under a few million rows), no reliable change column	grows with table size	slow, hammers the source
Incremental by timestamp	table has a trustworthy `updated_at`	proportional to change	misses deletes, tie and clock problems
Incremental by id	append-only tables (logs)	small	misses updates to old rows
CDC (next section)	need deletes, low latency, no extra load	needs log access	setup complexity

The incremental loader

Rules we will follow: read the watermark first, fetch rows after it, upsert them, and advance the watermark in the same transaction as the last write. That way a crash leaves the old watermark and the next run repeats safely (because upserts are idempotent).

```
import sqlite3

SOURCE = [{"id": i, "amount": 100 + i, "updated_at": f"2024-05-{(i % 5) +
1:02d}T10:00:00"} for i in range(1, 26)]

def api_get(since, page, page_size=10):
    """Fake: GET /orders?updated_after=..&page=..  (sorted by updated_at,
id)"""
    data = sorted([r for r in SOURCE if r["updated_at"] > since],
key=lambda r: (r["updated_at"], r["id"]))
    chunk = data[page * page_size:(page + 1) * page_size]
    return {"items": chunk, "has_more": (page + 1) * page_size <
len(data)}

db = sqlite3.connect(":memory:")
db.executescript("""
CREATE TABLE orders(id INTEGER PRIMARY KEY, amount REAL, updated_at TEXT);
CREATE TABLE etl_state(pipeline TEXT PRIMARY KEY, watermark TEXT);
```

```
INSERT INTO etl_state VALUES('orders','1970-01-01T00:00:00');
""")

def run_once():
    wm = db.execute("SELECT watermark FROM etl_state WHERE
pipeline='orders'").fetchone()[0]
    page, fetched, new_wm = 0, 0, wm
    while True:
        resp = api_get(wm, page)
        for r in resp["items"]:
            db.execute("""INSERT INTO orders
VALUES(:id,:amount,:updated_at)
                          ON CONFLICT(id) DO UPDATE SET
amount=excluded.amount, updated_at=excluded.updated_at""", r)
            new_wm = max(new_wm, r["updated_at"]); fetched += 1
        if not resp["has_more"]: break
        page += 1
    db.execute("UPDATE etl_state SET watermark=? WHERE pipeline='orders'",
(new_wm,))
    db.commit()
    total = db.execute("SELECT COUNT(*) FROM orders").fetchone()[0]
    print(f"run: wm_in={wm} fetched={fetched} pages={page+1} wm_out=
{new_wm} rows_in_table={total}")

run_once()                      # first load
run_once()                      # nothing new
SOURCE[2]["amount"] = 999; SOURCE[2]["updated_at"] = "2024-06-01T09:00:00"
# an update
SOURCE.append({"id": 26, "amount": 126, "updated_at": "2024-06-
01T09:30:00"})     # an insert
run_once()                      # picks up the 2 changes
db.execute("UPDATE etl_state SET watermark='1970-01-01T00:00:00'");
db.commit()    # a backfill: reset the watermark
run_once()
print(db.execute("SELECT id, amount, updated_at FROM orders WHERE id IN
(3,26)").fetchall())
print("duplicates:", db.execute("SELECT COUNT(*)-COUNT(DISTINCT id) FROM
orders").fetchone()[0])
```

Before you run it: how many rows does the first run fetch, and how many pages? What does run 3 fetch? After the reset (run 4), will the table have duplicates?

Real output:

```
run: wm_in=1970-01-01T00:00:00 fetched=25 pages=3 wm_out=2024-05-
05T10:00:00 rows_in_table=25
run: wm_in=2024-05-05T10:00:00 fetched=0 pages=1 wm_out=2024-05-
05T10:00:00 rows_in_table=25
run: wm_in=2024-05-05T10:00:00 fetched=2 pages=1 wm_out=2024-06-
01T09:30:00 rows_in_table=26
run: wm_in=1970-01-01T00:00:00 fetched=26 pages=3 wm_out=2024-06-
01T09:30:00 rows_in_table=26
[(3, 999.0, '2024-06-01T09:00:00'), (26, 126.0, '2024-06-01T09:30:00')]
duplicates: 0
```

Explain, line by line.

- Run 1: 25 rows at 10 per page need $\lceil 25 / 10 \rceil = 3$ pages (10 + 10 + 5). The watermark moves to the largest `updated_at`, May 5.
- Run 2: nothing is newer than the watermark, so 0 rows, 1 page (the first call returns an empty list). Cheap runs when nothing changed are the point of incremental loading.
- Run 3: id 3 was updated and id 26 is new: 2 rows. The upsert `ON CONFLICT(id) DO UPDATE` changed id 3 to 999.0 and inserted 26. The table grows from 25 to 26 rows (one insert, one update).
- Run 4 (backfill): we reset the watermark to 1970 to reload everything. It fetched all 26 rows and still ended with 26 rows and 0 duplicates, because writing is an upsert by key. **Check:** `COUNT(*) - COUNT(DISTINCT id)` is 0. *Interpretation:* the loader is idempotent. You can re-run it, or backfill, without cleaning up first.

The classic bug: ties at the watermark

Rows can share the exact same timestamp. We used `updated_at > watermark` (strictly greater). Suppose order 26 was loaded at `09:30:00`, and a moment later the source writes order 27 with the same timestamp `09:30:00`. The next run asks for "greater than 09:30:00" and never sees 27.

```
SOURCE.append({"id": 27, "amount": 1, "updated_at": "2024-06-
01T09:30:00"})   # same timestamp as id 26
run_once()
print("id 27 present?", db.execute("SELECT COUNT(*) FROM orders WHERE
id=27").fetchone()[0])
```

```
run: wm_in=2024-06-01T09:30:00 fetched=0 pages=1 wm_out=2024-06-
01T09:30:00 rows_in_table=26
id 27 present after run with '>' watermark? 0
```

Id 27 is lost: `fetched=0` . The fix is to read from the watermark inclusive (`>=`) and rely on the idempotent upsert to absorb the repeated row. We changed only that one comparison and re-ran the same sequence:

```
run: wm_in=2024-06-01T09:30:00 fetched=2 pages=1 wm_out=2024-06-
01T09:30:00 rows_in_table=27
id 27 present after run with '>' watermark? 1
```

(The label in the print statement still says `'>'` , but the filter was changed to `>=` . The row count went to 27.) It fetched 2 rows (26 again, plus 27), and the upsert made 26 harmless. **Why it matters:** this kind of bug loses data silently, so nothing alerts you. Tests like "count in source = count in target" (Chapter 5) catch it.

Other watermark traps:

Trap	What happens	Fix
Deletes	A deleted row never shows up in "changed since"	soft-delete flag in the source, or CDC
Source clock skew	two servers disagree on time, a row gets an older timestamp than the watermark	re-read a safety window, for example `watermark − 10 minutes` , and upsert
Long transactions	a row commits late with an earlier `updated_at`	same safety window
`updated_at` not updated	an update path forgets to set it	enforce in the source, or use CDC
Using local time	daylight shifts, mixed zones	store and compare UTC

Problem 4.1.1 Source table: 4,000,000 rows. Each day about 20,000 rows change. A full load moves 4,000,000 rows, an incremental one moves changed rows plus a 10-minute safety

window of about 140 rows (20,000 per day ÷ 144 ten-minute windows). How many times less data does incremental move per run?

Formula	ratio = full rows / incremental rows
Plug in	4,000,000 / (20,000 + 140)
Compute	20,000 + 140 = 20,140, and 4,000,000 / 20,140 = 198.6
Answer	About 199 times less data (about 0.5% of the table). The safety window adds under 1% overhead.
Check	20,140 × 199 = 4,007,860, close to 4,000,000.
Why it matters	Less data read from the source means less load on the production database and shorter runs.

Problem 4.1.2 Design check: the loader crashes after upserting 18 of 26 rows but before updating the state table. What is the table state, and what happens on the next run?

Step 1	Because the state update is the last statement and happens in the same transaction as the commit, in our code the whole transaction is rolled back (nothing visible), or, if rows were committed in smaller steps, 18 rows are in the table and the watermark is still the old one.
Step 2	The next run re-fetches from the old watermark, upserts all 26 rows (the 18 already there are overwritten with identical values), then advances the watermark.
Answer	After the retry the table is complete and without duplicates; the partial first attempt did no lasting harm.
Check	`COUNT(*) = COUNT(DISTINCT id)` and the row count equals the source count.

Connection to the real job

Almost every "ingest table X nightly" ticket is an incremental load with a state table. Tools do the same: Airbyte and Fivetran call the watermark a "cursor field", and dbt incremental models (Chapter 7) use `where updated_at > (select max(updated_at) from {{ this }})`.

Applications

- **Data Engineering:** nightly or hourly table syncs from OLTP.

- **Data Analytics:** fresh dashboards without full reloads.
- **Machine Learning:** incremental feature refresh; only changed customers recomputed.
- **MLOps:** training-data snapshots built from incremental loads.

COMMON MISTAKE

Moving the watermark to "now" instead of "max updated_at actually loaded". Rows written between your read and your "now" are skipped forever. Always advance to the largest value you really saw.

Check yourself

1. Why do we upsert instead of insert? Answer: re-runs and overlaps must not create duplicates.
2. What does the state table store? Answer: the watermark between runs.
3. What can incremental loads by timestamp not see? Answer: hard deletes.

4.2 APIs, Pagination, Rate Limits, Retries, Files and Webhooks

INTUITION

An API is a shop counter with a queue manager. You may ask for 100 items per visit (pagination), only 10 visits per minute (rate limit), and if the manager says "busy, come back later" (HTTP 429 or 503) you wait politely and come back (retry with backoff).

Pagination: offset versus cursor

An API usually returns a limited page and a way to ask for the next one.

- **Offset pagination:** `?offset=40&limit=20` . Simple, but if rows are inserted while you are paging, positions shift.
- **Cursor (keyset) pagination:** `?after_id=7&limit=4` or an opaque token `next_cursor` . You ask for "rows after the last one I saw". Stable under inserts.

Predict, then run. Ten rows (ids 10 to 1, newest first), page size 4. A new row (id 11) arrives between page 1 and page 2. Before you run it: which id appears twice with offset paging? Does

cursor paging have any duplicate?

```
data = [{"id": i} for i in range(10, 0, -1)]      # newest first: ids
10..1
def offset_page(offset, limit): return data[offset:offset+limit]
def cursor_page(after_id, limit):                 # rows with id <
after_id
    return [r for r in data if after_id is None or r["id"] < after_id]
[:limit]
seen = []; page1 = offset_page(0, 4); seen += [r["id"] for r in page1]
data.insert(0, {"id": 11})                        # a new row arrives
page2 = offset_page(4, 4); seen += [r["id"] for r in page2]
print("offset paging saw:", seen, "-> duplicate:", [x for x in set(seen)
if seen.count(x) > 1])
data.pop(0)
seen = []; last = None
for step in range(3):
    pg = cursor_page(last, 4)
    if step == 1: data.insert(0, {"id": 11})
    if not pg: break
    seen += [r["id"] for r in pg]; last = pg[-1]["id"]
print("cursor paging saw:", seen, "-> duplicates:", len(seen) -
len(set(seen)))
```

```
offset paging saw: [10, 9, 8, 7, 7, 6, 5, 4] -> duplicate: [7]
cursor paging saw: [10, 9, 8, 7, 6, 5, 4, 3, 2, 1] -> duplicates: 0
```

Explain. After the insert, every old row moved down by one position. Page 2 (positions 4 to 7) therefore started with id 7, which page 1 had already returned: a duplicate. The newer id 11 is not visible to the offset loop at all, which is acceptable only because the next incremental run will fetch it. With a cursor, "id < 7" does not depend on positions, so there is no duplicate. **Check:** the cursor result has 10 distinct ids, the original table size. The offset result has 8 values for 7 distinct ids. *Interpretation:* offset paging over changing data can duplicate or skip. Prefer cursors, and always upsert by key anyway.

Rate limits and retries with backoff

When an API says "too many requests" (HTTP 429) or "service unavailable" (503), retry later, with growing delays: 1 s, 2 s, 4 s, 8 s. This is **exponential backoff**. Add **jitter** (randomness) so that 100 clients do not all retry at the same instant. Do not retry errors that will never succeed (400 bad request, 401 unauthorised, 404).

```
import random
random.seed(11)
def flaky():
    if random.random() < 0.6: raise ConnectionError("503 service
unavailable")
    return "ok"
def with_retry(fn, max_tries=6, base=1.0, cap=30.0):
    waited = 0.0
    for attempt in range(1, max_tries + 1):
        try: return fn(), attempt, waited
        except ConnectionError as e:
            if attempt == max_tries: raise
            delay = min(cap, base * 2 ** (attempt - 1)); jitter =
random.uniform(0, delay)
            print(f"  attempt {attempt} failed ({e}); sleep up to
{delay:.0f}s -> chose {jitter:.2f}s"); waited += jitter
res, att, w = with_retry(flaky); print("result", res, "after", att,
"attempts, total wait", round(w, 2), "s")
print("max waits without jitter for 5 failures:", [min(30, 2**k) for k in
range(5)], "sum", sum(min(30, 2**k) for k in range(5)))
```

```
  attempt 1 failed (503 service unavailable); sleep up to 1s -> chose
0.56s
result ok after 2 attempts, total wait 0.56 s
max waits without jitter for 5 failures: [1, 2, 4, 8, 16] sum 31
```

The code above only prints the sleep time instead of sleeping, so that it runs instantly. In production you call `time.sleep(jitter)`, or use the `tenacity` library which provides this pattern. **Check:** five failures in a row would wait 1 + 2 + 4 + 8 + 16 = 31 seconds in the worst case, which is the second output line. *Interpretation:* retries must be bounded (here at most 6 tries), otherwise a dead API blocks your pipeline forever. After the limit, fail the task loudly and let the orchestrator alert (Chapter 6).

Problem 4.2.1 An API allows 60 requests per minute and has 12,000 pages to fetch. How long does a fetch take at the limit?

Formula	time = pages / rate
Plug in	12,000 pages / 60 per minute
Compute	200 minutes
Answer	200 minutes, about 3 hours 20 minutes. Fetching in parallel does not help if the limit is per key; ask the provider for a bulk export or use an incremental filter instead.
Check	60 × 200 = 12,000 requests.
Why it matters	Rate limits turn into design decisions: incremental over full, bulk export over paging.

Problem 4.2.2 A client waits 1, 2, 4, 8 seconds with a cap of 5 seconds. List the waits for six failures.

Step 1	Doubling gives 1, 2, 4, 8, 16, 32 before the cap.
Step 2	Apply `min(5, ...)` : 1, 2, 4, 5, 5, 5.
Answer	1, 2, 4, 5, 5, 5 seconds (total 22).
Check	1 + 2 + 4 + 5 + 5 + 5 = 22.

Other ingestion channels

Channel	How it works	Care points
File drops	partner puts CSV/JSON into SFTP or a bucket	detect completion (a `_SUCCESS` marker or size stable), never read half-written files, track processed file names
Webhooks	the source calls your URL when something happens	verify signatures, answer fast (200) and queue the work, handle duplicates and out-of-order delivery
Change feeds	the system offers a "changes since token" endpoint (Cosmos DB change feed, S3 events,	store the continuation token like a watermark

	Salesforce)	
Message queue / stream	Kafka, Event Hubs, Pub/Sub (Chapter 11)	offsets, consumer groups
Managed connectors	Airbyte, Fivetran (managed), Meltano and Singer taps (open-source), Azure Data Factory, AWS Glue	save time on standard sources; check cost per row, schema drift handling, and how deletes are treated

Build versus buy: use a connector when the source is common (Salesforce, Postgres, Google Ads) and the cost is acceptable. Write custom Python when the source is unusual or when you need special logic. Keep custom code small, tested and idempotent.

Connection to the real job

Typical Python stack: `requests` or `httpx` for HTTP, `tenacity` for retries, `pydantic` to validate response shapes, `pyarrow` to write Parquet, and `structlog` for logs.

Applications

- **Data Engineering:** SaaS ingestion (CRM, ads, payments).
- **Data Analytics:** marketing dashboards fed by API pulls.
- **GenAI:** web or document crawlers (obey robots.txt and terms of service; respect rate limits and privacy).
- **Operations:** the same retry and backoff ideas appear when a busy shop website answers 429 (too many requests).

COMMON MISTAKE

Retrying forever, or retrying non-idempotent calls (like POST "charge card") without an idempotency key. Retries are safe only when repeating the action has no extra effect.

Check yourself

1. Offset or cursor, which survives inserts during paging? Answer: cursor.
2. What does jitter prevent? Answer: many clients retrying at the same moment.
3. Which HTTP codes are worth retrying? Answer: 429 and 5xx; not 4xx like 400, 401, 404.

4.3 Change Data Capture, Backfills and Late-Arriving Data

INTUITION

Instead of re-reading the whole bank statement, you listen to the bank's cash register tape: every deposit, change and cancellation, in order. The database already writes such a tape for its own recovery (the **transaction log**: WAL in PostgreSQL, binlog in MySQL). **CDC** reads that tape and turns it into events.

How CDC works

CDC pipeline: OLTP database to Debezium to Kafka to lake or warehouse to BI

How to read it: the left box is the production database. Debezium (an open-source CDC tool) reads its log and publishes each change to Kafka as an event. A consumer applies the events to the warehouse or lake, using `MERGE`. Dashboards read the result.

A change event usually contains: operation (`c` create, `u` update, `d` delete, plus `r` for snapshot read), the key, the "before" and "after" row images, a log position (LSN or binlog offset) and a timestamp.

Method	How	Deletes?	Source load	Latency
Query-based (watermark)	`WHERE updated_at > ...`	no	queries on the table	minutes to hours
Trigger-based	triggers write changes to an audit table	yes	extra writes on every change	seconds
Log-based (Debezium)	read the transaction log	yes	tiny	sub-second to seconds

Predict, Run, Explain: applying a change log

Six events arrive in order. Before you run it: after all six events, which customers exist and where do they live? Then we replay events 3 and 4 a second time (as at-least-once delivery would do). What changes?

```
import sqlite3
db = sqlite3.connect(":memory:")
db.execute("CREATE TABLE cust(id INTEGER PRIMARY KEY, name TEXT, city
TEXT)")
log = [(1,"c",1,{"name":"Asha","city":"Pune"}), (2,"c",2,
{"name":"Ravi","city":"Delhi"}),
       (3,"u",1,{"city":"Mumbai"}), (4,"d",2,None),
       (5,"c",3,{"name":"Meena","city":"Chennai"}), (6,"u",3,
{"city":"Kochi"})]
def apply(ev):
    lsn, op, k, d = ev
    if op == "c": db.execute("INSERT OR REPLACE INTO cust VALUES(?,?,?)",
(k, d["name"], d["city"]))
    elif op == "u":
        for c, v in d.items(): db.execute(f"UPDATE cust SET {c}=? WHERE
id=?", (v, k))
    else: db.execute("DELETE FROM cust WHERE id=?", (k,))
for e in log: apply(e)
print(db.execute("SELECT * FROM cust ORDER BY id").fetchall())
for e in log[2:4]: apply(e)
print("after replaying events 3,4 again:", db.execute("SELECT * FROM cust
ORDER BY id").fetchall())
```

```
[(1, 'Asha', 'Mumbai'), (3, 'Meena', 'Kochi')]
after replaying events 3,4 again: [(1, 'Asha', 'Mumbai'), (3, 'Meena',
'Kochi')]
```

Explain. Asha moved to Mumbai (event 3), Ravi was deleted (event 4), Meena was created and moved to Kochi. Result: customers 1 and 3. Replaying events 3 and 4 changes nothing: "set city = Mumbai" and "delete id 2" give the same result when repeated, so these operations are idempotent. **Check:** 3 customers were created and 1 was deleted, so 3 − 1 = 2 customers remain. *Limit:* replaying an old event after newer ones can **undo** progress (for example replaying event 3 after a later update to Asha's city would set it back to Mumbai). Real CDC consumers therefore apply events in log order, and compare the log position (LSN) with the last applied one, ignoring anything older.

The warehouse side: insert all events into an append-only "changes" table, then each hour keep the latest event per key and `MERGE` it into the target (ordering by LSN and keeping `rn = 1`, the same `ROW_NUMBER()` pattern as in Chapter 1.3 and in the SQL document's window-functions chapter). Deletes can be hard (remove the row) or soft (set `is_deleted = true`).

Problem 4.3.1 Events for key 7 arrive out of order: (LSN 105, update city=Goa), (LSN 101, insert city=Pune), (LSN 103, update city=Delhi). What is the final city, and how do you get it?

Step 1	Sort by LSN: 101 (Pune), 103 (Delhi), 105 (Goa).
Step 2	Apply in order: Pune, then Delhi, then Goa.
Answer	The final city is Goa: the event with the highest LSN wins, regardless of arrival order.
Check	`ROW_NUMBER() OVER (PARTITION BY key ORDER BY lsn DESC) = 1` selects LSN 105, Goa.
Why it matters	Ordering by arrival time instead of log position gives wrong results whenever the network reorders events.

Backfills and late-arriving data

A **backfill** re-runs a pipeline for past periods: after a bug fix, a new column, or a source correction. Design for it from day one:

1. Parameterise every job by a **logical date** (the data interval being processed), never by "now".
2. Make each run **overwrite its own partition** (for example `DELETE WHERE day = X` then insert, or `INSERT OVERWRITE`, or `MERGE`) so a re-run replaces, never appends duplicates.
3. Control load on the source: run a few days at a time.
4. Reconcile counts per day after the backfill.

Late-arriving data (an event for yesterday arriving today): choose a strategy. (a) Reprocess the last N days every run ("lookback window"). (b) Keep an `event_time` and a separate `ingest_time`, and let downstream tables use event_time. (c) For streaming, use watermarks (Chapter 11).

Problem 4.3.2 A daily job loads yesterday's partition with `INSERT` (append). It fails at 80% and is re-run. 1,000,000 rows should be in the day. How many rows are there after the re-run, if the first attempt had written 800,000 and committed?

Step 1	After the failure: 800,000 rows are present.
Step 2	The re-run appends the full 1,000,000.
Compute	800,000 + 1,000,000 = 1,800,000.
Answer	1,800,000: 800,000 duplicates. With "delete the day then insert" or `INSERT OVERWRITE` the result is 1,000,000.
Check	The expected 1,000,000 rows, so the append design is wrong by exactly the partial first attempt.

Connection to the real job

Production incidents are mostly "the job ran twice", "the job missed a day" or "late data changed yesterday's number". Idempotent, partition-overwriting, date-parameterised jobs turn all three into routine reruns.

Applications

- **Data Engineering:** Debezium to Kafka to lakehouse; Airflow backfills.
- **Data Analytics:** correcting history after a business-rule change.
- **Machine Learning:** rebuilding feature history with correct event time.
- **Compliance:** CDC deletes carry "right to be forgotten" requests into the lake.

COMMON MISTAKE

Using `datetime.now()` inside a pipeline task to decide what to load. A backfill then loads the wrong period. Use the logical date given by the scheduler.

Check yourself

1. Which CDC type sees hard deletes with the smallest source load? Answer: log-based.
2. What decides final state for out-of-order events? Answer: the log position (LSN), not arrival time.
3. How do you make a daily load safe to re-run? Answer: overwrite or merge its own partition by logical date.

Chapter recap

- Full load is simple but grows with table size; incremental uses a watermark and a state table.
- Always upsert by key so re-runs, overlaps and backfills never duplicate.
- Advance the watermark only to the largest value actually loaded, in the same transaction as the data.
- Timestamp ties and clock skew lose rows with strict `>`; read inclusive or with a safety window.
- Prefer cursor pagination to offset; respect rate limits; retry only transient errors with exponential backoff and jitter, with a maximum.
- File drops need completion markers; webhooks need fast acknowledgement and duplicate handling.
- CDC reads the database log, sees deletes and costs the source little; apply events in log order.
- Backfills work when jobs take a logical date and overwrite their own partition.

Pattern	Rule
Watermark	max(updated_at) actually loaded; read `>=` (or with a safety window); upsert
Pages	⌈rows / page size⌉
Backoff	wait = min(cap, base × 2^(attempt−1)) with jitter
Idempotent load	delete-then-insert partition, MERGE, or upsert by key
CDC final state	order by LSN; keep the highest per key

Practice set

1. (easy) 95 rows, page size 20. How many pages? **Answer:** ⌈95 / 20⌉ = 5.

2. (easy) Which is idempotent: `INSERT` or `INSERT ... ON CONFLICT DO UPDATE`? **Answer:** the upsert.

3. Backoff with base 2 s, no cap, three failures. Waits? **Answer:** 2, 4, 8 seconds (2 × 2^(attempt−1)), total 14.

4. A job's watermark is 10:00:00 and rows exist at 10:00:00 (already loaded) and 10:00:00 (new, written later). With `>`, how many of the new row are seen? **Answer:** none. The tie is lost; use `>=` plus upsert.

5. Find the bug: `wm = datetime.now()` is saved at the end of each run. **Answer:** rows committed between the query and the end of the run are skipped forever. Save the largest `updated_at` loaded.

6. A table has 50 million rows and 0.2% change daily. Rows moved incrementally? **Answer:** 50,000,000 × 0.002 = 100,000 rows (plus any safety window).

7. What is output? Replay of event "d 2" twice. **Answer:** the second delete finds no row and changes nothing; the table is the same.

8. An API has 5,000 pages at 100 requests per minute. Time? **Answer:** 5,000 / 100 = 50 minutes.

9. (interview) "How would you ingest a 2 TB Postgres database into a warehouse and keep it fresh?" **Answer:** One snapshot (parallel by key range) into bronze, then log-based CDC (Debezium to Kafka) for changes, applied with MERGE ordered by LSN; soft-delete flags for deletes; reconcile counts and checksums per table; monitor lag; document backfill by re-snapshot of a table.

10. (interview) "What does idempotent mean and how do you build idempotent ingestion?" **Answer:** Running it twice gives the same result as once. Use upserts by business key, partition overwrite by logical date, state updated atomically with data, and no use of "now" in the logic.

11. (scenario) A partner API changes `amount` from a number to a string "1,250.50" on a Tuesday and your load fails. Describe a robust approach. **Answer:** Validate against a schema on ingest, quarantine failing records in a dead-letter table with the reason, alert, keep landing raw JSON in bronze, fix the parsing in silver, and reprocess the quarantined rows. Add a data contract with the partner.

Prompt pack

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me
incremental loading with a watermark and a state table. Use a small Python
and SQLite example, explain each line, then show me the tie-at-watermark
bug and how to fix it. Ask me 3 questions one at a time about when a
watermark loses data.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Topic: ingesting from REST APIs: offset versus
cursor pagination, rate limits, retries with exponential backoff and
jitter, idempotency keys. Give me 8 graded exercises with real numbers
(pages, rates, waits) with no solutions, then check my answers when I
paste them: [PASTE HERE]
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Explain Change
Data Capture (query-based, trigger-based, log-based with Debezium) with an
analogy, a diagram in text, and a worked example of applying out-of-order
events by log position. Then quiz me, one scenario at a time, on choosing
the CDC method and handling deletes.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Topic: backfills, idempotent partition overwrites,
and late-arriving data. Describe a realistic pipeline failure and ask me
to design the rerun safely. Critique my design, then show a better one
using logical dates and MERGE or partition overwrite. Keep simple English.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, applying for data engineer roles. Run a mock
interview on ingestion patterns: full versus incremental, watermarks, CDC,
API ingestion, idempotency and backfills. Ask 8 questions one at a time,
score my answers 1 to 5, give a model answer in simple English, and name
one follow-up an interviewer might ask. My answers: [PASTE HERE]
```

CHAPTER 5

DATA QUALITY AND TESTING

How to know, with evidence, that the data is right, fresh, complete and in the shape you expect.

A dashboard that is fast and wrong is worse than no dashboard, because people make decisions from it. The classic story: revenue drops 40% on Monday morning, the CFO panics, and three hours later someone finds that an upstream job ran empty over the weekend. Nobody tested the data. In this chapter you will learn the dimensions of data quality, how to write checks (uniqueness, nulls, ranges, allowed values, freshness, volume, schema), how to write a data contract, how to separate "stop the pipeline" from "warn and continue", how to unit-test transformations, and how tools such as Great Expectations, pandera, Soda and dbt tests express the same ideas. You will write and run real checks and see them fail on purpose.

Remember the ShopKart `orders` table from Chapter 4. We use it again here.

5.1 The Dimensions of Quality and Basic Checks

INTUITION

A restaurant kitchen has inspections: is the food fresh (freshness), is the order complete (completeness), did we cook the dish that was asked (accuracy), is the same dish not served twice (uniqueness), does the plate look as the menu says (validity/schema). Data quality checks are the kitchen's inspections, done automatically before the food goes out.

Words you need

Dimension	Question it asks	Example check
Completeness	Is anything missing?	`customer_id` not null; row count near normal
Uniqueness	Are there duplicates?	`order_id` unique
Validity	Do values follow the rules?	`amount >= 0`; `status` in an allowed list

Consistency	Do tables agree?	order totals equal the sum of order lines
Accuracy	Does it match reality?	revenue equals finance's number (needs an external reference)
Timeliness / freshness	Is it recent enough?	newest row is under 24 hours old
Schema	Are names and types as expected?	no missing or new columns

A **check** (or test, or expectation) is a query or function that returns pass or fail. A **severity** says what to do on failure: **error** stops the pipeline (do not publish bad data) and **warn** only alerts.

Predict, Run, Explain: seven checks on a small table

The table has five rows, and we hid a few problems in it. Before you run it: which checks do you think will fail? How many bad rows will each report?

```
import sqlite3, datetime
db = sqlite3.connect(":memory:")
db.executescript("""
CREATE TABLE orders(order_id TEXT, customer_id TEXT, amount REAL, status
TEXT, created_at TEXT);
INSERT INTO orders VALUES
('O1','C1',250.0,'PAID','2024-06-01T10:00:00'),
('O2','C2',-5.0,'PAID','2024-06-01T11:00:00'),
('O2','C2',80.0,'PAID','2024-06-01T11:05:00'),
('O3',NULL,120.0,'SHIPPED','2024-06-01T12:00:00'),
('O4','C9',99.0,'UNKNOWN','2024-05-20T12:00:00');
""")
def check(name, sql):
    bad = db.execute(sql).fetchone()[0]
    print(f"{'PASS' if bad == 0 else 'FAIL'}  {name:28s} bad_rows={bad}")
    return bad == 0
results = [
 check("unique order_id",        "SELECT COUNT(*)-COUNT(DISTINCT order_id)
FROM orders"),
 check("customer_id not null",   "SELECT COUNT(*) FROM orders WHERE
customer_id IS NULL"),
 check("amount >= 0",            "SELECT COUNT(*) FROM orders WHERE
amount<0"),
 check("status in allowed set",  "SELECT COUNT(*) FROM orders WHERE status
NOT IN ('PAID','SHIPPED','REFUNDED')"),
]
now = datetime.datetime(2024, 6, 2, 9, 0, 0)
newest = datetime.datetime.fromisoformat(db.execute("SELECT
MAX(created_at) FROM orders").fetchone()[0])
age = (now - newest).total_seconds() / 3600
print(f"{'PASS' if age < 24 else 'FAIL'}  freshness (<24h)
age_hours={age:.1f}")
history = [1000, 980, 1020, 1010, 990]; today = 612
avg = sum(history) / len(history); ratio = today / avg
print(f"{'PASS' if 0.7 <= ratio <= 1.3 else 'FAIL'}  volume within 70-130%
of avg  ratio={ratio:.2f}")
expected =
{"order_id":"TEXT","customer_id":"TEXT","amount":"REAL","status":"TEXT","c
reated_at":"TEXT"}
actual = {r[1]: r[2] for r in db.execute("PRAGMA table_info(orders)")}
print("PASS  schema matches" if actual == expected else f"FAIL  schema
diff {set(expected.items()) ^ set(actual.items())}")
print("overall:", "OK" if all(results) else "BLOCK the pipeline (fail
loudly)")
```

Real output:

```
FAIL  unique order_id              bad_rows=1
FAIL  customer_id not null         bad_rows=1
FAIL  amount >= 0                  bad_rows=1
FAIL  status in allowed set        bad_rows=1
PASS  freshness (<24h)             age_hours=21.0
FAIL  volume within 70-130% of avg  ratio=0.61
PASS  schema matches
overall: BLOCK the pipeline (fail loudly)
```

Explain, check by check.

- *Unique:* 5 rows but 4 distinct `order_id` values (O2 twice), so `5 - 4 = 1` duplicate.
- *Not null:* O3 has no customer: 1 row.
- *Range:* O2's first row has amount −5: 1 row.
- *Allowed set:* O4 has status `UNKNOWN` : 1 row.
- *Freshness:* the newest row is `2024-06-01T12:00:00` and "now" is `2024-06-02T09:00:00` . The difference is 21 hours, under the 24-hour limit: PASS. (We fixed "now" so that the output is repeatable.)
- *Volume:* the average of the last five days is (1000 + 980 + 1020 + 1010 + 990) / 5 = 1000. Today has 612, a ratio of 0.612, below the 0.7 floor: FAIL. This is the "empty weekend" bug caught.
- *Schema:* the table has exactly the expected columns and types.
- **Check:** 5 of 7 checks failed; the final `all(results)` covers only the four SQL checks (all FAIL), so the pipeline is blocked.
- *Interpretation:* a single dirty table can fail many checks. Checks are cheap (one query each) compared with a wrong decision.

Note that SQLite is loose about types; in a real warehouse the schema check compares the information schema.

KEY INSIGHT

Freshness and volume checks catch the failures that no row-level rule can: the data that never arrived. A table with zero rows passes every "no bad rows" test.

Problem 5.1.1 A table normally receives about 50,000 rows a day, with a daily standard deviation of 2,000. Today it received 41,000. Is that an anomaly under a "mean ± 3 standard deviations" rule?

Formula	z = (x − mean) / standard deviation
Plug in	(41,000 − 50,000) / 2,000
Compute	−9,000 / 2,000 = −4.5
Answer	z = −4.5, beyond ±3, so flag it. (Under a normal assumption, about 0.3% of days fall outside ±3.)
Check	The 3-sigma band is 50,000 ± 6,000 = 44,000 to 56,000; 41,000 is outside it.
Why it matters	A fixed "at least 1,000 rows" check would pass; a statistical band catches a drop of 18%. (See the learner's Math PDF on standard deviation.)

Problem 5.1.2 Build a row-count reconciliation: source has 1,204,500 rows, bronze 1,204,500, silver 1,199,100, gold has 1,199,100. Where were 5,400 rows lost, is it acceptable, and what do you do?

Step 1	Compare neighbours: source to bronze: 0 lost. Bronze to silver: 1,204,500 − 1,199,100 = 5,400 lost. Silver to gold: 0 lost.
Step 2	The silver step removes duplicates and bad rows. Percentage: 5,400 / 1,204,500 = 0.448%.
Answer	Silver dropped 5,400 rows (0.45%). Acceptable only if the dropped rows are accounted for: duplicates plus quarantined rows must add up to 5,400. Write them to a quarantine table and assert `silver + quarantine + duplicates = bronze`.
Check	If duplicates are 5,000 and quarantined bad rows are 400, then 1,199,100 + 5,000 + 400 = 1,204,500.
Why it matters	"Rows removed silently" is a quality bug; "rows removed and explained" is a feature.

Connection to the real job

You will add checks at every layer: raw (freshness, volume, schema), silver (uniqueness, not null, valid values), gold (reconciliation with finance, business rules).

Applications

- **Data Engineering:** gates in the pipeline before publish.
- **Data Analytics:** trust in dashboards; "data last updated" badges.
- **Machine Learning:** drift checks on training and serving data; a silent null spike can wreck a model.
- **Operations:** verifying that measurement results loaded completely (every record counted).

COMMON MISTAKE

Writing only "no bad rows" tests. A job that loads zero rows passes. Always add volume and freshness checks.

Check yourself

1. Which dimension does "newest row under 24 hours old" test? Answer: freshness (timeliness).
2. Why does an empty table pass a not-null test? Answer: there are no rows that violate it, so you need a volume check.
3. What should an error-severity failure do? Answer: stop the pipeline before publishing.

5.2 Data Contracts, Schema Drift and Quarantine

INTUITION

A contract between a restaurant and its supplier says: tomatoes, grade A, delivered by 7 a.m., invoice in rupees. If the supplier sends potatoes, you refuse the delivery instead of cooking with them. A **data contract** is the same agreement between the team that produces data and the teams that consume it.

A data contract states: the **schema** (fields, types, nullability), **semantics** (what `amount_paise` means, its unit), **quality rules**, **freshness and volume expectations (SLAs)**, an **owner**, and how **changes** are announced. It is checked automatically when data is produced or ingested.

Schema drift is when the source changes shape without telling you: a column is added, a type changes, a field disappears. **Schema evolution** is the planned, compatible way to change. Safe changes: add a nullable column. Breaking changes: rename, remove, change a type, change a unit (rupees to paise).

Predict, Run, Explain: a contract validator with a quarantine

Before you run it: five records arrive. Which fail and for what reasons? With a 95% pass-rate rule, what happens to the load?

```
CONTRACT = {"order_id": {"type": str, "required": True},
            "amount_paise": {"type": int, "required": True, "min": 0},
            "status": {"type": str, "required": True, "allowed": {"PAID",
"SHIPPED", "REFUNDED"}},
            "coupon": {"type": str, "required": False}}
def validate(rec):
    errs = []
    for f, rule in CONTRACT.items():
        if f not in rec or rec[f] is None:
            if rule["required"]: errs.append(f"{f}: missing")
            continue
        v = rec[f]
        if not isinstance(v, rule["type"]): errs.append(f"{f}: expected
{rule['type'].__name__}, got {type(v).__name__}")
        elif "min" in rule and v < rule["min"]: errs.append(f"{f}: {v} <
{rule['min']}")
        elif "allowed" in rule and v not in rule["allowed"]:
errs.append(f"{f}: {v!r} not allowed")
    extra = set(rec) - set(CONTRACT)
    if extra: errs.append(f"unexpected fields (schema drift):
{sorted(extra)}")
    return errs
batch = [{"order_id": "O1", "amount_paise": 25000, "status": "PAID"},
         {"order_id": "O2", "amount_paise": "1,250.50", "status": "PAID"},
         {"order_id": "O3", "amount_paise": -5, "status": "LOST"},
         {"order_id": "O4", "amount_paise": 900, "status": "SHIPPED",
"gift_wrap": True},
         {"amount_paise": 100, "status": "PAID"}]
ok = 0
for r in batch:
    e = validate(r); ok += not e
    print("OK  " if not e else "FAIL", r.get("order_id", "<none>"), e)
print(f"valid {ok}/{len(batch)} = {ok/len(batch):.0%}; threshold 95% ->
{'PASS' if ok/len(batch) >= 0.95 else 'FAIL the load'}")
```

Real output:

```
OK   O1 []
FAIL O2 ['amount_paise: expected int, got str']
FAIL O3 ['amount_paise: -5 < 0', "status: 'LOST' not allowed"]
FAIL O4 ["unexpected fields (schema drift): ['gift_wrap']"]
FAIL <none> ['order_id: missing']
valid 1/5 = 20%; threshold 95% -> FAIL the load
```

Explain.

- O2: the partner sent `"1,250.50"` as text, a type break (also a unit change from paise to rupees; this one change is hard to see in data, which is why a contract documents units).
- O3 has two errors at once; the validator lists all, which helps debugging.
- O4 is valid for the known fields but has a new field `gift_wrap` : drift. Many teams treat unknown fields as a *warning* and keep the rest, but must tell the producer.
- The last record has no `order_id` .
- 1 of 5 passes: 20%. **Check:** 1 / 5 = 0.20. *Interpretation:* with a threshold, a few bad rows go to quarantine and the job continues, but 80% bad (or a sudden jump from the usual 0.1%) means something upstream broke, so stop and page a human.

Quarantine pattern (dead-letter table): write failing records, with the reasons and the run id, to a `quarantine_orders` table. Continue with the good rows. A person (or a later job) fixes the rule or the data, and the rows are replayed. This is the batch version of a dead-letter queue.

Schema registries (Chapter 11) enforce contracts for Kafka producers. For tables, dbt supports model contracts (`contract: enforced: true`), and tools such as Soda and Great Expectations compare against declared schemas.

Problem 5.2.1 Classify each source change as safe or breaking: (a) a new nullable column `coupon` ; (b) `amount` changes from rupees to paise; (c) `status` gets a new allowed value `PARTIAL` ; (d) column `cust_id` renamed to `customer_id` .

Step 1	(a) Old readers ignore it: safe.
Step 2	(b) The name and type are the same, but the numbers are 100 times larger: breaking (a silent semantic break).
Step 3	(c) Readers with strict allowed lists will fail: breaking for them; announce it.
Step 4	(d) Old queries fail with "column not found": breaking.
Answer	(a) safe; (b), (c), (d) breaking.
Check	A change is safe only if every existing reader keeps working and keeps the same meaning.
Why it matters	(b) is the dangerous one: nothing crashes, the revenue just becomes 100 times larger.

Problem 5.2.2 A batch of 2,000 records has 3 invalid. The rule: quarantine if under 1% invalid, fail the load otherwise. What happens?

Formula	invalid rate = invalid / total
Plug in	3 / 2,000
Compute	0.0015 = 0.15%
Answer	0.15% is under 1%: quarantine the 3 records and load the other 1,997.
Check	1,997 + 3 = 2,000: no record is lost or hidden.

Connection to the real job

Contracts reduce the "upstream broke us" incidents. When you join a team, ask: "Is there a schema, who owns it, and who is told when it changes?"

Applications

- **Data Engineering:** schema checks on ingest; quarantine tables.
- **Data Science:** documented units and null meanings prevent wrong analyses.
- **MLOps:** feature contracts between the feature pipeline and the model server.
- **API teams:** OpenAPI and JSON Schema are contracts for services.

COMMON MISTAKE

Treating quality as the data team's problem alone. If the producer is not part of the contract, you will chase the same breakage forever.

Check yourself

1. Give one safe and one breaking schema change. Answer: safe: add a nullable column; breaking: rename a column or change a unit.
2. What is a quarantine table for? Answer: to keep failing records and reasons so the job can continue and the rows can be fixed and replayed.
3. Why list all errors per record? Answer: so you fix them in one go.

5.3 Testing Transformations and Tools of the Trade

INTUITION

A **data test** checks the data that arrived today (like checking each delivery). A **unit test** checks the code with a tiny, known input and a known expected output (like testing a recipe with one egg). You need both: the recipe may be right while the eggs are rotten, or the other way around.

Unit tests for transformation code

Keep transformation logic in small functions that take data and return data, with no hidden reads of "now" or of a database. Then tests are simple. Here is a function that converts paise to rupees and a splitter that separates good rows from rows to quarantine, with five tests using Python's built-in `unittest` (we use it here because `pytest` is not installed in this sandbox; `pytest` is the more common choice in real projects and the test bodies would be plain `assert` statements).

```
import unittest
def clean_amount(raw):
    """paise string -> rupees float, or None if invalid"""
    try: v = int(raw)
    except (TypeError, ValueError): return None
    return None if v < 0 else v / 100
def split_valid(rows):
    good, bad = [], []
    for r in rows:
        a = clean_amount(r.get("amount_paise"))
        (bad if a is None or not r.get("order_id") else good).append(
            {**r, "amount": a} if a is not None else {**r, "reason": "bad
amount or id"})
    return good, bad
class T(unittest.TestCase):
    def test_ok(self): self.assertEqual(clean_amount("25050"), 250.5)
    def test_negative(self): self.assertIsNone(clean_amount("-5"))
    def test_text(self): self.assertIsNone(clean_amount("abc"))
    def test_none(self): self.assertIsNone(clean_amount(None))
    def test_split(self):
        g, b = split_valid([{"order_id": "1", "amount_paise": "100"},
{"order_id": "2", "amount_paise": "x"},
                            {"order_id": "", "amount_paise": "5"}])
        self.assertEqual((len(g), len(b)), (1, 2))
if __name__ == "__main__": unittest.main(verbosity=2)
```

Before you run it: do you expect all five to pass?

```
test_negative (__main__.T.test_negative) ... ok
test_none (__main__.T.test_none) ... ok
test_ok (__main__.T.test_ok) ... ok
test_split (__main__.T.test_split) ... ok
test_text (__main__.T.test_text) ... ok

----------------------------------------------------------------------
Ran 5 tests in 0.000s

OK
```

Explain. `25050` paise is 250.50 rupees (25050 / 100). Negative and non-numeric inputs return `None`, and `None` itself (a missing field) also returns `None` because `int(None)` raises `TypeError`, which we catch. In `test_split`, the first row is good, the second has amount "x" (bad), the third has an empty `order_id` (bad): 1 good, 2 bad. **Check:** 1 + 2 = 3 rows in, 3 rows

out. *Interpretation:* tests also document the rules. When someone changes `clean_amount`, a failing test tells them which rule they broke. Note the test order is alphabetical, not the order written.

Small but important test habits for pipelines:

Test type	What it protects	Example
Unit test	transformation logic	`clean_amount` cases, edge cases (null, empty, zero, huge)
Data test	today's data	unique, not null, accepted values
Integration test	the pipeline end to end on a small sample	run on 100 rows in a test schema, compare to expected
Reconciliation	source versus target	counts and sums match
Regression test	no change in outputs unless intended	compare gold tables before and after a code change

The tools, in one table

Tool	Style	How you define checks	Notes
pandera	Python, DataFrame schemas	`DataFrameSchema` with `Column(...)` and `Check`	good for pandas and Polars pipelines
Great Expectations (GX)	Python, expectation suites	`expect_column_values_to_not_be_null` and friends, checkpoints, data docs	rich, heavier setup
Soda	YAML (SodaCL)	`checks for orders: – missing_count(customer_id) = 0`	simple, good for warehouses
dbt tests	SQL / YAML in the dbt	`unique`, `not_null`, `accepted_values`, `relationships`, custom SQL tests	most used in

	project		warehouse ELT (Chapter 7)
Data observability (Monte Carlo and similar)	automated monitors on freshness, volume, schema, distribution, lineage	machine-learned thresholds, alerts	a product category; know the five pillars: freshness, volume, schema, distribution, lineage

Examples (**not run here**; none of these libraries is installed in this sandbox, but the shapes are standard):

```
# pandera (concept)
import pandera as pa
schema = pa.DataFrameSchema({
    "order_id": pa.Column(str, unique=True),
    "amount":   pa.Column(float, pa.Check.ge(0)),
    "status":   pa.Column(str, pa.Check.isin(["PAID", "SHIPPED",
"REFUNDED"])),
})
validated = schema.validate(df)        # raises SchemaError listing
failures
```

```
# dbt schema.yml (concept)
models:
  - name: orders
    columns:
      - name: order_id
        tests: [unique, not_null]
      - name: status
        tests:
          - accepted_values: {values: ['PAID','SHIPPED','REFUNDED']}
```

```
# Soda (concept)
checks for orders:
  - row_count > 0
  - duplicate_count(order_id) = 0
  - freshness(created_at) < 1d
```

Alerting without noise. A check that fires every day is ignored. Rules: give each check an owner; set severity (error versus warn); alert on *trends* or thresholds, not on one row; send to a channel with a link to the runbook ("what to do when this fails"); review noisy checks monthly.

Problem 5.3.1 You test `clean_amount` with these inputs: "100", "0", "-1", "", "1e3", " 50 ". What does each return? (Run it, or reason from `int()`.)

Step 1	`int("100")` = 100 gives 1.0. `int("0")` = 0 gives 0.0.
Step 2	`int("−1")` = −1 is negative, so `None`. `int("")` raises `ValueError`, so `None`.
Step 3	`int("1e3")` raises `ValueError` (scientific notation is not an integer string), so `None`. `int(" 50 ")` = 50 because `int` strips spaces, giving 0.5.
Answer	1.0, 0.0, None, None, None, 0.5.
Check	Verified by running `clean_amount` on those strings in a Python session: the rules above are the documented behaviour of `int()` on strings.
Why it matters	Edge cases (zero, empty, spaces, scientific notation) are exactly what real feeds contain.

Problem 5.3.2 Write a reconciliation rule for money: "the sum of `amount` in gold must equal the sum in silver within 0.01 rupees". The silver sum is 12,345,678.90 and the gold sum is 12,345,678.88. Pass or fail?

Formula	|gold − silver| ≤ tolerance
Plug in	|12,345,678.88 − 12,345,678.90| ≤ 0.01
Compute	0.02 ≤ 0.01 is false
Answer	Fail: a difference of 0.02 rupees exceeds the tolerance. Floating-point rounding could cause tiny differences; this is why money should be stored as integers (paise) or decimals, and the tolerance should be explicit.
Check	12,345,678.90 − 12,345,678.88 = 0.02.

Connection to the real job

In reviews, the question is "where are the tests for this model?" A new dbt model without `unique` and `not_null` on its key will not pass a decent code review. CI (Chapter 12) runs the unit tests and the data tests on every pull request.

Applications

- **Data Engineering:** CI-run unit tests, per-run data tests, reconciliation jobs.
- **Data Analytics:** "accepted values" and relationship tests behind the dashboard.
- **Machine Learning:** data validation before training (schema and distribution), pandera or GX in feature pipelines.
- **MLOps:** monitors for drift and freshness of features in production.

COMMON MISTAKE

Testing only on perfect sample data. Build tests from past incidents: every production bug becomes a new test case.

Check yourself

1. Unit test versus data test? Answer: a unit test checks code on a known input; a data test checks the real data that arrived.
2. Name two dbt generic tests. Answer: `unique`, `not_null` (also `accepted_values`, `relationships`).
3. Why store money as integers? Answer: floating-point rounding makes sums differ by tiny amounts.

Chapter recap

- Quality has dimensions: completeness, uniqueness, validity, consistency, accuracy, freshness, schema.
- Always pair row-level checks with freshness and volume checks, because missing data passes row-level tests.
- Use statistical bands (mean ± 3σ) for volume, not a fixed minimum.
- Reconcile counts and sums between layers, and account for every dropped row.
- A data contract defines schema, units, quality rules, SLAs, owner and change process; unit changes are the silent killers.
- Quarantine bad records with reasons, continue with good rows, and stop the load if the failure rate jumps.
- Keep transformations as pure functions and unit-test edge cases; add data tests for each run.
- pandera, Great Expectations, Soda and dbt tests are different syntaxes for the same ideas; observability tools add automated monitors.

Pattern	Rule
Duplicate count	`COUNT(*) - COUNT(DISTINCT key)`
Freshness	`now - max(timestamp) < limit`
Volume band	`
Reconciliation	`
Severity	error stops the pipeline, warn alerts

Practice set

1. (easy) What does `COUNT(*) - COUNT(DISTINCT order_id)` measure? **Answer:** the number of extra duplicate rows for `order_id`.

2. (easy) A table must have a customer for every order. Which dimension? **Answer:** completeness (not null) and consistency (a matching row exists in the customer table).

3. Average rows = 20,000, σ = 500. Today 18,200. z-score and verdict? **Answer:** z = (18,200 −

20,000) / 500 = −3.6, beyond ±3: anomaly.

4. What is the output? `clean_amount("12")` and `clean_amount("12.5")`. **Answer:** `0.12` and `None` (`int("12.5")` raises `ValueError`).

5. Find the bug: a freshness check uses `datetime.now()` inside the unit test. **Answer:** the result depends on when the test is run; pass "now" in as a parameter so the test is repeatable.

6. 5,000 records, 40 invalid, rule is quarantine below 1%. What happens? **Answer:** 40 / 5,000 = 0.8%, below 1%: quarantine 40, load 4,960.

7. A "relationships" test checks that every `orders.customer_id` exists in `customers`. What does it return if 12 orders point to unknown customers? **Answer:** 12 failing rows, so the test fails (error severity would stop the build).

8. Gold revenue sum is 5,000,000.00 and finance says 5,010,000.00. Tolerance is 0.1%. Pass? **Answer:** difference 10,000 / 5,010,000 = 0.2%, above 0.1%: fail, investigate.

9. (interview) "How would you make sure a daily revenue table is correct?" **Answer:** Contract and schema checks on input; not null and unique on keys; accepted values; freshness and volume checks; reconciliation to the source and to finance within a tolerance; unit tests for the transformation; alert with an owner and runbook; quarantine bad rows.

10. (interview) "What is the difference between data quality testing and data observability?" **Answer:** Testing runs explicit rules you wrote. Observability monitors the data continuously with automatic baselines on freshness, volume, schema and distribution, and uses lineage to find the cause, catching unknown unknowns.

11. (scenario) The business says revenue on the dashboard looks about 3% low every Monday. How do you investigate with checks? **Answer:** Add day-of-week volume baselines, reconcile source to bronze to silver to gold for the last four Mondays, check late-arriving data (weekend events landing on Monday), check time-zone cut-offs, and add a freshness check for the Monday run.

Prompt pack

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me the
dimensions of data quality (completeness, uniqueness, validity,
```

consistency, accuracy, freshness, schema) with an online shop example. For each, show one SQL check and what a failure looks like. Then ask me 3 questions, one at a time, about which check would catch a given problem.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Topic: volume and freshness checks, z-scores and statistical bands for row counts, and reconciliation between pipeline layers. Give me 8 graded numeric exercises with no solutions. After I answer, I will paste my work: check each step, and explain any mistakes in simple English.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am learning data engineering. Topic: data contracts, schema drift, schema evolution (safe versus breaking changes), and quarantine or dead-letter tables. Explain with a supplier analogy, then give me 6 source changes to classify as safe or breaking, and a short design scenario for a partner feed. Critique my answers kindly.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Topic: unit-testing data transformations in Python and dbt tests. Show me a small function with edge cases, tests for it, and the equivalent dbt generic tests. Then ask me to review a buggy function and its tests: find the bug and add the missing test. Here is my code: [PASTE HERE]

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am applying for data engineer roles. Run a mock interview on data quality: contracts, checks, Great Expectations, pandera, Soda, dbt tests, observability, alert fatigue. Ask 8 questions one at a time, score each answer 1 to 5, give a model answer in simple English, and give one follow-up question. My answers: [PASTE HERE]

CHAPTER 6

ORCHESTRATION WITH APACHE AIRFLOW (AND ITS ALTERNATIVES)

Running many dependent jobs on time, in order, with retries, alerts and safe re-runs.

By now you can write one script that loads orders, one that checks quality, one that builds a mart. But who runs them every night, in the right order, and what happens if step 2 fails? A person with a cron table and a lot of worry? That does not scale to 200 jobs. An **orchestrator** is the program that knows the order, the schedule, the retry rules and the history of every run. Apache Airflow is the most widely used one, and you will meet it in most data engineering interviews. In this chapter you will learn the ideas (DAG, task, schedule, data interval, catchup, backfill, idempotent task), run a small scheduler of your own to see them move, read real Airflow code, and compare Airflow with Dagster, Prefect, Azure Data Factory and others.

Honest note: Airflow is not installed in this sandbox and cannot be downloaded here, so every Airflow snippet is labelled **not run here**. The mini scheduler we run is our own teaching toy, not Airflow.

6.1 The Ideas: DAGs, Schedules, Data Intervals, Retries

INTUITION

A cooking plan: wash rice, cook rice, make curry, serve. "Cook rice" cannot start before "wash rice". The plan is a list of steps plus arrows saying "this before that", with no loops (you never wash rice again because you served). A **DAG** (Directed Acyclic Graph) is exactly such a plan: *directed* because arrows have a direction, *acyclic* because there are no cycles.

Words you need

Word	Plain meaning	ShopKart example
DAG	The whole workflow: tasks and their dependencies	`daily_orders`

Task	One unit of work	`extract`, `validate`, `transform`, `load`
Operator	A template for a kind of task	`BashOperator`, `PythonOperator`, a SQL operator
Task instance	One task for one run	`extract` for 2024-06-01
DAG run	One execution of the DAG for one data interval	the run for 2024-06-01
Schedule	When runs are created	daily at midnight
Data interval	The slice of data time a run is responsible for	2024-06-01 00:00 to 2024-06-02 00:00
Logical date	The start of the data interval (the `ds` value)	2024-06-01
Retry	Run a failed task again, after a delay	2 retries, 5 minutes apart
Catchup	Create runs for all past intervals since the start date	on or off
Backfill	Run past intervals on purpose	recompute March
Idempotent task	Re-running gives the same result	overwrites the day's partition

An Airflow DAG: extract, validate, transform, load, notify as boxes with arrows

How to read the picture: each box is a task, each arrow means "the right one starts only after the left one succeeds". If `transform` fails, Airflow retries it. If it still fails, `load` and `notify` are marked "upstream failed" and do not run. You fix the cause and **clear** (re-run) just `transform`, and the later tasks follow.

The most confusing idea: data interval versus run time

A daily DAG for the data of June 1st can only run *after* June 1st is over, so it actually starts on

June 2nd at 00:00. The run's **logical date** is June 1st (the start of the interval), and it runs at the interval's end. Think of a shop that closes at night: the sales report for Monday is made on Tuesday morning, but the report is called "Monday's report".

Run label (logical date)	Data interval covered	Actually starts at
2024-06-01	2024-06-01 00:00 to 2024-06-02 00:00	2024-06-02 00:00
2024-06-02	2024-06-02 00:00 to 2024-06-03 00:00	2024-06-03 00:00

Your task must use the interval (the `ds`, `data_interval_start`, `data_interval_end` values given by Airflow), never `now()`. Then a backfill of old dates works.

Problem 6.1.1 A daily DAG has `start_date = 2024-01-01` and `catchup = True`. Today is 2024-03-01 at 00:00 (the DAG was just deployed). How many runs does Airflow create, and what is the last one's data interval?

Formula	runs = number of complete intervals between start and now
Plug in	from 2024-01-01 to 2024-03-01 (2024 is a leap year, February has 29 days)
Compute	January 31 + February 29 = 60 intervals
Answer	60 runs. The last is the logical date 2024-02-29, covering 2024-02-29 00:00 to 2024-03-01 00:00. (Verified by date arithmetic in Python: `(date(2024,3,1) - date(2024,1,1)).days = 60`.)
Check	The first interval is 01-01 to 01-02 and the last ends exactly at the current time, so the count of whole days between the two dates is the count of intervals.
Why it matters	With `catchup=True` and an old start date, deploying a DAG can launch hundreds of runs at once. With `catchup=False` only the latest interval runs. The default of this setting has differed between Airflow versions, so always set it explicitly.

Problem 6.1.2 Each of those 60 runs takes 10 minutes. `max_active_runs = 4`. How long does the catch-up take?

Formula	time = ⌈runs / parallel runs⌉ × time per run
Plug in	⌈60 / 4⌉ × 10
Compute	15 × 10 = 150 minutes
Answer	150 minutes (2.5 hours), assuming nothing else is limiting.
Check	4 runs at a time × 15 rounds = 60 runs.
Why it matters	A backfill is a sudden rush of work on your source database and warehouse, like a hundred customers walking into a bank at once. You limit parallelism on purpose (the same idea as opening only a few counters at a time).

Predict, Run, Explain: a tiny scheduler

This is **our own toy** (about 25 lines) that shows what an orchestrator does: order tasks by dependency, retry failures, skip tasks that already succeeded, and write results idempotently by date. `extract` is rigged to fail once. Before you run it: how many attempts will `extract` need on the first date? What does the "clear one task and re-run" step do?

```
import graphlib, datetime
fails_left = {"extract": 1}          # extract fails once, then works
state, outputs = {}, {}              # state: (task, date) -> 'success'
def extract(ds):
    if fails_left.get("extract", 0) > 0:
        fails_left["extract"] -= 1; raise ConnectionError("source
timeout")
    outputs[("raw", ds)] = [1, 2, 3]
def transform(ds): outputs[("clean", ds)] = [x * 10 for x in
outputs[("raw", ds)]]
def load(ds):      outputs[("mart", ds)] = sum(outputs[("clean", ds)])
# overwrite by date key
TASKS = {"extract": (extract, []), "transform": (transform, ["extract"]),
"load": (load, ["transform"])}
def run_dag(ds, retries=2):
    order = graphlib.TopologicalSorter({k: v[1] for k, v in
TASKS.items()}).static_order()
    for t in order:
        if state.get((t, ds)) == "success": print(f"  {ds} {t}: skipped
(already success)"); continue
        for attempt in range(1, retries + 2):
            try:
                TASKS[t][0](ds); state[(t, ds)] = "success"; print(f"
{ds} {t}: success (attempt {attempt})"); break
            except Exception as e:
                print(f"  {ds} {t}: attempt {attempt} failed: {e}")
        else:
            print(f"  {ds} {t}: FAILED, downstream not run"); return
start = datetime.date(2024, 6, 1)
for d in range(3):
    ds = (start + datetime.timedelta(days=d)).isoformat(); print("run
for", ds); run_dag(ds)
print("clear one task and re-run (backfill/rerun):")
del state[("load", "2024-06-02")]; run_dag("2024-06-02")
print({k: v for k, v in outputs.items() if k[0] == "mart"})
```

Real output:

```
run for 2024-06-01
  2024-06-01 extract: attempt 1 failed: source timeout
  2024-06-01 extract: success (attempt 2)
  2024-06-01 transform: success (attempt 1)
  2024-06-01 load: success (attempt 1)
run for 2024-06-02
  2024-06-02 extract: success (attempt 1)
  2024-06-02 transform: success (attempt 1)
  2024-06-02 load: success (attempt 1)
run for 2024-06-03
  2024-06-03 extract: success (attempt 1)
  2024-06-03 transform: success (attempt 1)
  2024-06-03 load: success (attempt 1)
clear one task and re-run (backfill/rerun):
  2024-06-02 extract: skipped (already success)
  2024-06-02 transform: skipped (already success)
  2024-06-02 load: success (attempt 1)
{('mart', '2024-06-01'): 60, ('mart', '2024-06-02'): 60, ('mart', '2024-06-03'): 60}
```

Explain, line by line.

- `graphlib.TopologicalSorter(...).static_order()` turns the dependency map into a valid order: extract, transform, load. This is the core of "DAG".
- The first `extract` attempt raises `ConnectionError`; the retry loop tries again and succeeds on attempt 2. Airflow's `retries` and `retry_delay` do this.
- The 'clear and re-run' step deleted the success record of `load` for June 2 only. The scheduler skips the two tasks that already succeeded and re-runs `load`. That is what clearing one task in the Airflow UI does.
- Output is written under a date key: `outputs[("mart", ds)] = ...` overwrites. Running `load` again for June 2 left the mart value at 60, not 120. **Check:** the clean list [10, 20, 30] sums to 60 for each date, and there are exactly 3 mart entries for 3 dates, no more. *Interpretation:* this is an idempotent task. If the task had done `total += sum(...)`, the re-run would have double counted (the same trap as Problem 1.4.1).

Connection to the real job

You will rarely write a scheduler. You will constantly decide *what is one task*, *what are its inputs and outputs by date*, and *what happens when it runs twice*. Those are design skills, and they transfer to every orchestrator.

Applications

- **Data Engineering:** nightly ELT, backfills, SLA monitoring.
- **Data Analytics:** refreshing marts before the 8 a.m. report.
- **Machine Learning / MLOps:** weekly retraining pipelines (data pull, train, evaluate, register, deploy).
- **Operations:** scheduled capacity checks with results loaded to a warehouse.

COMMON MISTAKE

Using `datetime.now()` or "yesterday" computed inside the task. A re-run next week loads the wrong day. Use the logical date from the scheduler.

Check yourself

1. Why must a DAG be acyclic? Answer: with a cycle no task could ever be first, and the run would never finish.
2. A run with logical date June 1 starts when? Answer: at the end of its interval, June 2 00:00.
3. What makes a task safe to retry? Answer: it is idempotent, overwriting its own date's output.

6.2 Airflow in Practice: Code, Components and Best Practices

INTUITION

Airflow is a building with five rooms: a **scheduler** (decides what to run), a **metadata database** (remembers everything), **workers** (do the work, via an executor), a **web server** (the UI) and a **DAG folder** (the plans, written in Python). You write plans; the building runs them.

A classic DAG (not run here)

```
# Airflow 2.x style (not run here). Check your version's import paths.
from datetime import datetime, timedelta
from airflow import DAG
from airflow.operators.bash import BashOperator
from airflow.operators.python import PythonOperator

default_args = {"owner": "data-eng", "retries": 2, "retry_delay":
timedelta(minutes=5)}

def load_orders(ds, **_):
    # ds is the logical date as 'YYYY-MM-DD'. Overwrite that day's
partition: idempotent.
    print(f"loading orders for {ds}")

with DAG(
    dag_id="daily_orders",
    start_date=datetime(2024, 1, 1),
    schedule="@daily",          # older versions: schedule_interval
    catchup=False,
    max_active_runs=1,
    default_args=default_args,
    tags=["shopkart"],
) as dag:
    extract  = BashOperator(task_id="extract", bash_command="python
extract.py --date {{ ds }}")
    validate = PythonOperator(task_id="validate", python_callable=lambda
**_: print("checks"))
    load     = PythonOperator(task_id="load", python_callable=load_orders)
    extract >> validate >> load           # >> means "then"
```

Key pieces: `{{ ds }}` is a **Jinja template** that Airflow fills with the logical date when the task runs. The `>>` operator sets dependencies. Each task in a DAG file is just a *definition*; the file must be fast to parse because the scheduler re-reads it often.

The TaskFlow API (not run here)

TaskFlow lets you write plain Python functions and decorate them. Return values are passed between tasks automatically (stored via XCom, below).

```
# Airflow 2.x/3.x style (not run here). In Airflow 3 the imports come from
airflow.sdk;
# in 2.x from airflow.decorators. Check the version you use.
from datetime import datetime
from airflow.decorators import dag, task

@dag(start_date=datetime(2024, 1, 1), schedule="@daily", catchup=False)
def orders_taskflow():
    @task
    def extract(ds=None):
        return {"day": ds, "rows": 1000}           # small metadata only!

    @task
    def validate(meta: dict):
        assert meta["rows"] > 0, "empty extract"
        return meta

    @task
    def load(meta: dict):
        print("loaded", meta["rows"], "rows for", meta["day"])

    load(validate(extract()))

orders_taskflow()
```

More Airflow vocabulary

Concept	Meaning	Practice
Operator	Pre-built task type (Bash, Python, SQL, Spark, cloud service operators from provider packages)	prefer provider operators or hooks over hand-written API calls
Sensor	A task that waits for something (a file, a partition, an external task)	use `mode="reschedule"` so it does not hold a worker slot while waiting
Hook	A reusable connection helper to an external system	used inside tasks to talk to Postgres, S3, etc.
Connection	Stored credentials and host info (in the metadata DB or a secrets backend)	never hard-code passwords in the DAG file

Variable	Small key-value configuration	keep few; do not call `Variable.get` at the top level of the DAG file (it runs on every parse)
XCom	A small message passed between tasks (stored in the metadata DB)	pass IDs, paths and counts, never DataFrames
Dynamic task mapping	create one task instance per item at run time with `.expand()`	one task per file or per table without writing a loop in the DAG
Pool	A named limit on how many tasks run at once	protect a database: `pool="warehouse", slots=5`
Retries / SLA	retry count and delay; time expectations	SLA features changed between versions; check the docs of your version
Executor	How tasks are run: Local, Celery (a pool of worker machines), Kubernetes (a pod per task)	Celery for steady load, Kubernetes for isolation and bursty work
Trigger rule	when a task runs relative to upstream results	`all_done` for cleanup tasks that must run even after failure

Dynamic task mapping (not run here):

```
@task
def list_files(): return ["a.csv", "b.csv", "c.csv"]
@task
def process(path): print("processing", path)
process.expand(path=list_files())        # makes 3 task instances at run
time
```

Deployment and testing

- **Deploy:** the scheduler, web server and workers can run in Docker or on Kubernetes (the official Helm chart exists); managed services include Amazon MWAA, Google Cloud Composer, Azure Data Factory's Managed Airflow and Astronomer. DAG files are synced from Git (Chapter 12).

- **Test:**
  1. *Import test:* load all DAG files with `DagBag` and assert there are no import errors.
  2. *Structure test:* assert task ids, dependencies, retries, and that `catchup` is set.
  3. *Unit test:* put the real logic in plain Python functions (like `clean_amount` in Chapter 5) and test them without Airflow.
  4. *Run test:* `dag.test()` (available in recent Airflow versions) runs a DAG in one process for local debugging.

```
# not run here: a DAG import test with pytest
from airflow.models import DagBag
def test_no_import_errors():
    bag = DagBag(dag_folder="dags/", include_examples=False)
    assert bag.import_errors == {}, bag.import_errors
def test_daily_orders_has_retries():
    dag = DagBag(dag_folder="dags/",
include_examples=False).get_dag("daily_orders")
    assert dag.default_args["retries"] >= 1
```

Problem 6.2.1 A task returns a 400 MB pandas DataFrame and the next task takes it as an argument through XCom. What goes wrong and what is the fix?

Step 1	XCom values are stored in the metadata database; 400 MB would bloat the database and slow the whole scheduler.
Step 2	Write the data to object storage or a table (for example `s3://lake/staging/orders/ds=2024-06-01/`), and return only the path.
Answer	Pass a path (a few bytes) instead of the data (400 MB). That is 400,000,000 / ~100 = 4 million times smaller for a 100-byte path.
Check	The next task reads the path and loads the data itself, so XCom holds a short string.
Why it matters	"No heavy work or big data in the scheduler or XCom" is a top interview answer.

Problem 6.2.2 A warehouse allows 5 concurrent loads. Your DAG has 40 table-load tasks that each take 3 minutes. With a pool of 5 slots, how long do they take in total, and how long without a pool if all 40 start together and each slows down proportionally?

Formula	with pool: ⌈tasks / slots⌉ × time per task
Plug in	⌈40 / 5⌉ × 3 = 8 × 3 = 24 minutes
Without a pool	40 tasks compete for 5 slots; if the work is fully shared the total work is the same, 40 × 3 / 5 = 24 minutes at best, but in practice queries time out, retries pile up and it takes longer or fails.
Answer	24 minutes with a pool, predictable; without a pool, no better than 24 minutes and often a failure.
Check	8 rounds × 5 tasks = 40 tasks.
Why it matters	Pools protect shared systems. It is the orchestration version of a restaurant that seats only as many guests as the kitchen can cook for.

Best practices (the interview list)

1. **Idempotent tasks** keyed by logical date (overwrite partition, MERGE).
2. **Atomic tasks**: one clear job each; if it fails, you know what to re-run.
3. **No heavy work in the DAG file or the scheduler**: the DAG file only defines tasks. Heavy work runs in workers or external systems (Spark, warehouse).
4. **Small XComs**: paths and ids, not data.
5. **Secrets in connections or a secrets backend**, never in code.
6. **Retries with delay** for transient failures, but fail fast for logic errors.
7. **Alerts on failure and on SLA misses** with a link to the runbook.
8. **Set `catchup` and `max_active_runs` explicitly**; use pools for shared resources.
9. **Test DAGs** (import test) in CI; keep logic in importable modules.
10. **Time zones**: schedule in UTC internally; convert for display.

Connection to the real job

Typical task list: "Add a new table to the nightly pipeline", "Backfill March after a bug", "Investigate why DAG X is late". Each needs the ideas above.

Applications

- **Data Engineering:** ELT schedules, dbt runs (a task that calls `dbt build`), Spark job submission, data quality gates.

- **ML Engineering:** training and batch scoring DAGs.
- **Analytics Engineering:** run order between ingestion and dbt.
- **FinOps:** shut down clusters after the DAG with a cleanup task using `trigger_rule="all_done"` .

COMMON MISTAKE

Putting expensive code (database calls, large imports, API calls) at the top level of a DAG file. The scheduler runs that code every few seconds when it parses the file, and it can freeze the whole system.

Check yourself

1. What is an XCom for? Answer: passing small values (ids, paths) between tasks.
2. What does a sensor in `reschedule` mode do? Answer: it frees its worker slot between checks while waiting.
3. Why pools? Answer: to limit concurrency against a shared resource.

6.3 Alternatives, Event-Driven Triggers and Lineage

INTUITION

Airflow thinks in *tasks* ("run this script at 2 a.m."). Newer tools think in *data assets* ("this table should be fresh; what do I need to run to make it so?"). Both get your tables built; they differ in what you declare.

Tool	Idea	Strength	Watch out for
Airflow	task-based DAGs in Python, huge ecosystem	most jobs, most integrations, managed offerings everywhere	local dev and testing can be heavy; scheduler tuning
Dagster	**asset-based**: you declare tables (assets) and their upstream assets; partitions and sensors built in	great local dev, testing and lineage	smaller ecosystem than Airflow

Prefect	Python functions with `@flow` and `@task`, dynamic workflows, simple deployment	fast to start, dynamic	different concepts from Airflow
Mage	notebook-like pipeline builder	low-code feel	smaller community
Azure Data Factory (ADF)	managed, visual pipelines and copy activities, integration runtimes, triggers	strong in Azure shops, connectors	complex logic gets awkward; JSON definitions
AWS Step Functions	managed state machines for AWS services	serverless, reliable, good for event-driven AWS flows	AWS-specific
Argo Workflows	Kubernetes-native workflows defined in YAML	good if you live in Kubernetes	steeper learning
cron	a line in a file	perfect for one simple script	no dependencies, no retry history, no UI, no backfill

Rule of thumb: **one script, no dependencies, no one cares if it fails: cron.** Anything with dependencies, retries, alerts, backfills or more than one person: an orchestrator.

A taste of the asset style (**not run here**, Dagster-like):

```
from dagster import asset
@asset
def raw_orders(): ...
@asset
def clean_orders(raw_orders): ...          # depends on raw_orders by
argument name
@asset
def revenue_by_city(clean_orders): ...
```

Event-driven triggers and dependencies between pipelines

Not everything should run on a clock. **Event-driven** pipelines run when something happens: a file lands in a bucket (S3 event, Event Grid), a message arrives, or an upstream dataset is updated. In Airflow, *Datasets* (called *Assets* in newer versions) let a DAG run when an upstream DAG updates a dataset, and an `ExternalTaskSensor` waits for a task in another DAG. Prefer data-aware triggers to "run B at 3 a.m. because A usually ends by 2:30", which breaks the first slow night.

Lineage and metadata

Lineage answers "where did this column come from and what depends on it?". **OpenLineage** is an open standard for emitting lineage events from jobs (Airflow, Spark, dbt can emit them). Catalogs such as **DataHub** and **Amundsen** (and cloud-native ones) collect metadata, ownership and lineage, and make data searchable. You use lineage when a source column changes ("which dashboards break?") and during incidents ("which downstream tables are affected?"). More in Chapter 12.

Problem 6.3.1 Pick a tool for each: (a) a single script that copies a log file to S3 nightly; (b) 300 dbt models plus ingestion plus ML retraining with a team of 8; (c) a Kubernetes-heavy company wants YAML-defined, container-per-step workflows; (d) an Azure shop that mostly copies SaaS data into Synapse with minimal code.

Step 1	(a) cron (or a scheduled cloud function).
Step 2	(b) Airflow or Dagster: dependencies, retries, backfills and visibility matter.
Step 3	(c) Argo Workflows.
Step 4	(d) Azure Data Factory.
Answer	(a) cron, (b) Airflow or Dagster, (c) Argo, (d) ADF.
Check	Each match follows the "match the tool to the complexity and the platform" rule; (b) has two valid answers.
Why it matters	Interviewers want a reasoned choice, not a favourite tool.

Problem 6.3.2 Pipeline A usually finishes at 2:30 a.m. Pipeline B is scheduled for 3:00 a.m. and reads A's output. One night A is slow and finishes at 3:20 a.m. What does B read, and how do you fix the design?

Step 1	B starts at 3:00 and reads yesterday's data (or half-written data): wrong or stale.
Step 2	Remove the time guess: make B depend on A's completion (a dataset trigger, sensor, or put both in one DAG).
Answer	B reads stale or partial data for 20 minutes of overlap. Fix with a data-aware dependency so B starts when A is done.
Check	With a dependency, B starts at 3:20 whatever the delay, and the data it reads is complete.

Applications

- **Data Engineering:** choosing and migrating orchestrators; Dagster for asset-centric platforms.
- **Cloud engineering:** ADF or Step Functions glue for managed services.
- **Governance:** lineage for impact analysis and audits.
- **Analytics Engineering:** asset-based freshness ("this dashboard table must be under 1 hour old").

COMMON MISTAKE

Scheduling dependent pipelines by clock guesses. Use real dependencies, so that a slow night does not corrupt the next job.

Check yourself

1. Task-based or asset-based: Airflow versus Dagster? Answer: Airflow is task-based, Dagster is asset-based.
2. When is cron enough? Answer: one simple script with no dependencies and low stakes.
3. What is OpenLineage? Answer: an open standard for emitting lineage metadata from jobs.

Chapter recap

- An orchestrator runs tasks in dependency order (a DAG), on a schedule, with retries, alerts, history and backfills.
- A run's logical date is the start of its data interval; it runs after the interval ends. Use it, never `now()`.

- `catchup=True` creates a run for every past interval; set it and `max_active_runs` explicitly.
- Idempotent, date-keyed tasks make retries and backfills safe.
- Airflow parts: scheduler, metadata DB, executor and workers, web server, DAG folder.
- TaskFlow turns Python functions into tasks; XCom carries only small values; sensors should reschedule; pools limit concurrency.
- Keep the DAG file light and put heavy work in workers or external engines; test DAGs with an import test and unit tests of the logic.
- Dagster (assets), Prefect, Mage, ADF, Step Functions, Argo and cron are alternatives; choose by complexity and platform; use data-aware triggers; lineage via OpenLineage and catalogs.

Pattern	Rule
Catch-up runs	complete intervals between start_date and now
Backfill time	⌈runs / parallel runs⌉ × time per run
Dependency	`a >> b >> c`
Templated date	`{{ ds }}`
Task body	overwrite or MERGE by logical date
XCom	ids and paths only

Practice set

1. (easy) What does DAG stand for? **Answer:** Directed Acyclic Graph.

2. (easy) Which date does `{{ ds }}` hold for the run that processes June 5th data? **Answer:** `2024-06-05` (the logical date; it runs on June 6th).

3. A weekly DAG (`@weekly`) with start_date 2024-01-07 and catchup=True; now is 2024-02-04 00:00. Number of runs? **Answer:** intervals start Jan 7, 14, 21, 28 and each ends a week later; the interval starting Jan 28 ends Feb 4 (now), so it is complete: 4 runs.

4. What is the output order from the toy scheduler for tasks extract >> transform >> load? **Answer:** extract, transform, load, because the topological order respects every arrow.

5. Find the bug: `PythonOperator(python_callable=load, op_kwargs={"day": datetime.now().date()})`. **Answer:** `now()` is evaluated when the DAG file is parsed, not at the logical date, so reruns and backfills use the wrong day. Use `{{ ds }}`.

6. 120 tasks, pool of 6 slots, 2 minutes each. Time? **Answer:** ⌈120 / 6⌉ × 2 = 20 × 2 = 40 minutes.

7. A sensor polls every 60 seconds for 6 hours in `poke` mode and holds a worker slot. What is better? **Answer:** `mode="reschedule"` or a deferrable sensor (event-driven), which frees the slot between checks.

8. Why is `Variable.get("x")` at the top of a DAG file a problem? **Answer:** it runs on every parse (every few seconds) and queries the metadata database each time; read variables inside tasks or with templates.

9. (interview) "How do you make an Airflow pipeline safe to re-run?" **Answer:** Idempotent tasks keyed by logical date (partition overwrite or MERGE), no use of `now()`, state and data updated atomically, retries for transient errors, and tests for a double-run producing the same result.

10. (interview) "Airflow versus Dagster?" **Answer:** Airflow is task-centric with the largest ecosystem and many managed offerings. Dagster is asset-centric (you declare data products and their dependencies), with strong local development, testing and lineage. Choose Airflow for ecosystem and hiring pool; Dagster when asset freshness and developer experience are the priority.

11. (scenario) Your nightly DAG missed the 6 a.m. report deadline twice this week. How do you investigate and prevent it? **Answer:** Look at task durations over time (the Gantt view or logs) to find the slow task; check queueing (pool or executor slots), upstream late arrival, and data growth. Fix by parallelising or optimising the slow task, adjusting pools, or starting earlier through a data-aware trigger; add an SLA/freshness alert before 6 a.m. rather than after.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me Apache
Airflow concepts: DAG, task, operator, schedule, data interval, logical
date, catchup and backfill. Use a daily orders pipeline with real dates,
and explain why a run for June 1 starts on June 2. Then ask me 3 questions
```

one at a time about data intervals and catchup counts.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Topic: writing idempotent Airflow tasks and safe backfills. Show a non-idempotent task, the double-counting bug after a retry, and the fix using partition overwrite or MERGE by logical date. Then give me 6 graded exercises where I must find the idempotency bug, with no solutions. I will paste my answers: [PASTE HERE]

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am learning data engineering. Explain the Airflow architecture (scheduler, metadata database, executor, workers, web server), XComs, sensors, pools, dynamic task mapping and the TaskFlow API. Use a restaurant analogy. Then write a short TaskFlow DAG for me to review and ask me to list its 3 weaknesses.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Topic: choosing between cron, Airflow, Dagster, Prefect, Azure Data Factory, AWS Step Functions and Argo Workflows. Give me 6 realistic company situations and ask me to choose and justify each one in 2 sentences. Then critique my reasoning and say when each tool would be a poor choice.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am applying for data engineer roles. Run a mock interview on orchestration: Airflow design, scheduling semantics, retries, backfills, idempotency, testing DAGs, event-driven triggers and lineage. Ask 8 questions one at a time. After each answer, score it 1 to 5, give a model answer in simple English, and one follow-up. My answers: [PASTE HERE]

CHAPTER 7

DBT, THE TOOL THAT TURNS SQL INTO A TESTED SOFTWARE PROJECT

Models, sources, ref(), materializations, incremental builds, tests, snapshots, macros and CI.

In Chapter 1 you met ELT: load raw data into the warehouse first, then transform it there with SQL. The question that follows is practical. Who runs the 80 SQL files in the right order? Who tests them? Who remembers that `mart_city_revenue` depends on `fct_orders`, which depends on two staging tables? Without a tool, the answer is "a person with a spreadsheet and bad luck". **dbt** (data build tool) is the tool that solves this. You write plain `SELECT` statements, and dbt works out the order, builds the tables or views, runs tests, and writes documentation. In this chapter you will understand dbt by building a tiny dbt-like program yourself (it runs here), then read real dbt project files, and finally learn the habits a dbt team uses in code review and CI. The SQL itself is covered in the separate SQL study document (`study/sql/`); here we focus on the *engineering around* the SQL.

Honest note: dbt is **not installed** here and cannot be downloaded in this sandbox. All dbt files and commands are labelled **not run here**. The mini build script and the SQL tests are real Python and SQLite and were run. Details such as YAML key names change between dbt versions, so check the docs of the version you use.

Running example: **ShopKart** again. Raw tables `raw_orders` (amounts in paise, 1 rupee = 100 paise) and `raw_customers` are already loaded by the pipelines of Chapter 4. We want a trusted `fct_orders` and a `mart_city_revenue`.

7.1 Models, Sources, ref() and Materializations

INTUITION

Think of a recipe book where each recipe says "take the sauce from recipe 4". You do not copy recipe 4 into recipe 7. You *refer* to it by name. The book's index then tells you to cook recipe 4 before recipe 7. dbt's `ref()` is that "take it from recipe 4" sentence, and the order of cooking comes for free.

Words you need

Word	Plain meaning	ShopKart example
Model	One `.sql` file holding one `SELECT`. dbt turns it into a table or view with the file's name	`fct_orders.sql` becomes table `fct_orders`
Source	A raw table that someone else loads; you declare it in YAML so dbt knows it exists	`raw_orders`
`ref('x')`	"Use model x here." dbt replaces it with the real table name and records the dependency	`{{ ref('stg_orders') }}`
`source('s','t')`	The same idea for a raw table	`{{ source('shop','raw_orders') }}`
Materialization	*How* dbt stores the model result: view, table, incremental, ephemeral	`fct_orders` as table
Jinja	A small templating language. `{{ ... }}` prints a value, `{% ... %}` runs logic	`{{ ref('x') }}`
DAG	The dependency graph (Chapter 6). dbt builds it from the `ref()` calls	staging to fact to mart

Layers: staging, intermediate, marts

The common convention (from the dbt community, not a hard rule) has three layers. It matches the bronze/silver/gold idea from Chapter 1.

Layer	Job	Prefix	Materialization (typical)

Staging	One model per source table; rename columns, fix types, convert units. No joins	`stg_`	view
Intermediate	Joins and reshaping that several marts need	`int_`	ephemeral or view
Marts	Business-ready facts and dimensions (Chapter 2)	`fct_`, `dim_`, `mart_`	table or incremental

The project as files (not run here)

A dbt project is just a folder of text files:

```
shopkart_dbt/
  dbt_project.yml            project name, folder settings, default
materializations
  profiles.yml               connection to the warehouse (kept OUT of git:
it holds secrets)
  models/
    staging/
      _sources.yml           declares raw tables, tests on them, freshness
      stg_orders.sql
      stg_customers.sql
    marts/
      fct_orders.sql
      mart_city_revenue.sql
      _models.yml            descriptions and tests for the models
  seeds/country_codes.csv    small CSV files that dbt loads as tables
  snapshots/                 history tracking (SCD2), see 7.2
  macros/                    reusable Jinja functions, see 7.3
  tests/                     custom SQL tests, see 7.3
```

`models/staging/_sources.yml` (not run here):

```
version: 2
sources:
  - name: shop
    database: raw
    schema: ingest
    tables:
      - name: raw_orders
        loaded_at_field: _loaded_at
        freshness:
          warn_after: {count: 12, period: hour}
          error_after: {count: 24, period: hour}
      - name: raw_customers
```

`models/staging/stg_orders.sql` (not run here):

```
select
    order_id,
    customer_id,
    amount_paise / 100.0 as amount_rupees,
    updated_at
from {{ source('shop', 'raw_orders') }}
```

`models/marts/fct_orders.sql` (not run here):

```
{{ config(materialized='table') }}

select o.order_id, o.amount_rupees, c.city
from {{ ref('stg_orders') }} o
join {{ ref('stg_customers') }} c using (customer_id)
```

Commands you will type (not run here): `dbt run` builds all models; `dbt run --select fct_orders+` builds that model and everything *downstream* (the `+` after the name); `+fct_orders` means everything *upstream*; `dbt build` runs models, tests, seeds and snapshots together in DAG order; `dbt compile` shows the final SQL without running it.

Predict, Run, Explain: a mini dbt in 20 lines (real, run here)

To understand what `ref()` really does, we build the same idea ourselves. Before you run it, predict: in what order will the four models be built, and what will `ref` be replaced with?

```
import re, sqlite3, graphlib
models={
 "stg_orders":"SELECT order_id, customer_id, amount/100.0 AS amount FROM
raw_orders",
 "stg_customers":"SELECT id AS customer_id, UPPER(city) AS city FROM
raw_customers",
 "fct_orders":"SELECT o.order_id, o.amount, c.city FROM {{
ref('stg_orders') }} o JOIN {{ ref('stg_customers') }} c
USING(customer_id)",
 "mart_city_revenue":"SELECT city, SUM(amount) AS revenue FROM {{
ref('fct_orders') }} GROUP BY city",
}
db=sqlite3.connect(":memory:")
db.executescript("""CREATE TABLE
raw_orders(order_id,customer_id,amount);INSERT INTO raw_orders
VALUES(1,1,25000),(2,1,5000),(3,2,12000);
CREATE TABLE raw_customers(id,city);INSERT INTO raw_customers
VALUES(1,'pune'),(2,'delhi');""")
deps={m:set(re.findall(r"ref\('(\w+)'\)",s)) for m,s in models.items()}
for m in graphlib.TopologicalSorter(deps).static_order():
    sql=re.sub(r"\{\{ ref\('(\w+)'\) \}\}",r"\1",models[m])
    db.execute(f"CREATE VIEW {m} AS {sql}"); print("built",m)
print(db.execute("SELECT * FROM mart_city_revenue ORDER BY
city").fetchall())
print("test not_null(fct_orders.city) bad rows:",db.execute("SELECT
COUNT(*) FROM fct_orders WHERE city IS NULL").fetchone()[0])
```

Real output:

```
built stg_orders
built stg_customers
built fct_orders
built mart_city_revenue
[('DELHI', 120.0), ('PUNE', 300.0)]
test not_null(fct_orders.city) bad rows: 0
```

Line by line:

- `models` is a dictionary of model name to SQL text. In dbt this is "a folder of `.sql` files".
- `deps` uses a regular expression to find every `ref('...')` in each SQL text. This is exactly how dbt learns the graph: it reads your SQL, so you never write the order by hand.
- `graphlib.TopologicalSorter(deps).static_order()` is the same topological sort as the toy scheduler in Chapter 6. A model appears only after everything it refers to.

- `re.sub(...)` replaces `{{ ref('x') }}` by the plain name `x`. Real dbt replaces it with the full name, such as `analytics.dev_asha.stg_orders`, and that is why the same code works in a developer's private schema and in production.
- `CREATE VIEW` is the *view* materialization. Real dbt can also create a table.
- The last line is a test: a query that returns *bad rows*. Zero rows means pass. dbt tests are built on this single idea.

Check by hand: Asha (customer 1, Pune) has orders of 25000 and 5000 paise = 250 + 50 = 300 rupees. Ravi (Delhi) has 12000 paise = 120 rupees. The output matches.

Problem 7.1.1 `fct_orders` refers to `stg_orders` and `stg_customers`. `mart_city_revenue` refers to `fct_orders`. A teammate runs `dbt run --select stg_orders+`. Which models are built?

Step 1	The `+` after a name means "this model and everything downstream of it".
Step 2	Downstream of `stg_orders` is `fct_orders` (it refers to it), and downstream of `fct_orders` is `mart_city_revenue`.
Step 3	`stg_customers` is a *sibling* input, not downstream, so it is not selected.
Answer	`stg_orders`, `fct_orders`, `mart_city_revenue`, in that order.
Check	In our toy, the topological order printed earlier shows these three in the same relative order.
Why it matters	After you change one staging model you rebuild only what can be affected. On a 500-model project this saves hours.

Materializations: how the result is stored

Type	What dbt creates	Good when	Bad when
`view`	A saved query. Nothing stored	Light models, small data, staging	Many people query it: it recomputes each time
`table`	Full rebuild into a physical table on each run	Medium data,	Data is huge: rebuild is slow

		dashboards need speed	and costly
`incremental`	Adds or updates only new rows (7.2)	Large, append-heavy facts	Logic that must change old rows often
`ephemeral`	No object at all; inlined as a CTE (a named sub-query) into the models that use it	Tiny helper logic	You want to debug it or query it alone
`materialized_view`	The warehouse keeps it fresh itself (support depends on the adapter)	Simple aggregates with frequent reads	Complex SQL the warehouse cannot maintain

Set defaults in `dbt_project.yml` (not run here):

```
models:
  shopkart:
    staging:
      +materialized: view
    marts:
      +materialized: table
```

Connection to the real job

In job ads, "analytics engineer" and "dbt experience" mean exactly this section: organising SQL into layers, using `ref()`, and choosing materializations to balance speed and cost (Chapter 8).

Applications

- **Data Analytics:** analysts own marts in dbt so dashboards read one trusted definition of "revenue".
- **Data Engineering:** the ELT "T" step; dbt runs as one task inside an Airflow DAG (Chapter 6) after ingestion.
- **Machine Learning:** feature tables are built as dbt models with tests, then read by training jobs.
- **GenAI:** a clean, documented mart is the safest source for text-to-SQL assistants.

COMMON MISTAKE

Making everything a `table` "to be safe". A 2-billion-row fact rebuilt every hour wastes warehouse money. Start with views for staging, tables for small marts, and incremental for big facts.

Check yourself

1. What does `ref('x')` give you besides the table name? Answer: the dependency arrow in the DAG, so dbt builds `x` first.
2. Which materialization stores nothing and is inlined as a CTE? Answer: `ephemeral`.
3. Why is `profiles.yml` kept out of git? Answer: it holds warehouse credentials.

7.2 Incremental Models, Snapshots and Seeds

INTUITION

Updating a wall calendar. You do not reprint the whole year each morning. You cross out today. An incremental model only processes the rows that are new since the last run. A snapshot is a diary: when a customer's tier changes from silver to gold, you do not erase "silver". You write "silver until June 10, gold from June 10".

Incremental models

You know the watermark from Chapter 4 (4.1): remember the largest `updated_at` already loaded and fetch only newer rows. dbt's incremental materialization is the same idea inside the warehouse.

`models/marts/fct_orders.sql` as incremental (not run here):

```
{{ config(materialized='incremental', unique_key='order_id') }}

select order_id, customer_id, amount_rupees, updated_at
from {{ ref('stg_orders') }}
{% if is_incremental() %}
where updated_at > (select max(updated_at) from {{ this }})
{% endif %}
```

- `is_incremental()` is true only when the table already exists and you did not pass `--full-refresh`. On the first run the `where` is skipped, so everything loads.
- `{{ this }}` means "the table this model builds", so the model can read its own current state.
- `unique_key='order_id'` tells dbt how to *update* existing rows (a merge or delete-and-insert, depending on the adapter's *incremental strategy*). Without a unique key, dbt can only append, and updated rows would appear twice.
- Strategies you will see named: `append`, `merge`, `delete+insert`, `insert_overwrite` (partition replace). Which ones exist depends on the warehouse adapter.
- `dbt run --full-refresh` drops and rebuilds from scratch. It is your repair tool.

Predict, Run, Explain: incremental in SQLite (real, run here)

Our toy does the same with `INSERT OR REPLACE` (SQLite's "upsert by primary key"). Predict: after run 2, how many rows, and what is the amount of order 1? Then a *late* row arrives with an old `updated_at`. Will the watermark catch it?

```
import sqlite3
db=sqlite3.connect(":memory:")
db.executescript("""
CREATE TABLE raw_orders(order_id INT, customer_id INT, amount_paise INT,
updated_at TEXT);
INSERT INTO raw_orders VALUES (1,1,25000,'2024-06-01'),(2,1,5000,'2024-06-
01'),(3,2,12000,'2024-06-02');
CREATE TABLE fct_orders(order_id INT PRIMARY KEY, customer_id INT, amount
REAL, updated_at TEXT);
""")
def run_incremental(full_refresh=False):
    if full_refresh: db.execute("DELETE FROM fct_orders")
    wm=db.execute("SELECT COALESCE(MAX(updated_at),'1900-01-01') FROM
fct_orders").fetchone()[0]
    db.execute("""INSERT OR REPLACE INTO fct_orders
      SELECT order_id, customer_id, amount_paise/100.0, updated_at FROM
raw_orders WHERE updated_at > ?""",(wm,))
    return wm
print("run 1 watermark:",run_incremental(), "rows:",db.execute("SELECT
COUNT(*) FROM fct_orders").fetchone()[0])
db.execute("INSERT INTO raw_orders VALUES (4,3,8000,'2024-06-03')")
db.execute("UPDATE raw_orders SET amount_paise=30000, updated_at='2024-06-
03' WHERE order_id=1")
print("run 2 watermark:",run_incremental(), "rows:",db.execute("SELECT
COUNT(*) FROM fct_orders").fetchone()[0])
print(db.execute("SELECT * FROM fct_orders ORDER BY order_id").fetchall())
print("run 3 (nothing new)
watermark:",run_incremental(),"rows:",db.execute("SELECT COUNT(*) FROM
fct_orders").fetchone()[0])
db.execute("INSERT INTO raw_orders VALUES (5,2,9900,'2024-06-01')")
run_incremental(); print("late row 5 loaded?",db.execute("SELECT COUNT(*)
FROM fct_orders WHERE order_id=5").fetchone()[0]==1)
run_incremental(full_refresh=True); print("after full refresh,
loaded?",db.execute("SELECT COUNT(*) FROM fct_orders WHERE
order_id=5").fetchone()[0]==1)
```

Real output:

```
run 1 watermark: 1900-01-01 rows: 3
run 2 watermark: 2024-06-02 rows: 4
[(1, 1, 300.0, '2024-06-03'), (2, 1, 50.0, '2024-06-01'), (3, 2, 120.0,
'2024-06-02'), (4, 3, 80.0, '2024-06-03')]
run 3 (nothing new) watermark: 2024-06-03 rows: 4
late row 5 loaded? False
after full refresh, loaded? True
```

Explanation:

- Run 1: the table is empty, so the watermark is the fake old date `1900-01-01` and all 3 rows load. This is the "first run" branch.
- Run 2: watermark is `2024-06-02` (the biggest date loaded). Only order 4 (new) and order 1 (updated to 3 June) pass `updated_at > watermark`. Order 1 replaces its old row because it has the same primary key (our `unique_key`). So we have 4 rows, and order 1 shows 300.0 rupees (30000 paise).
- Run 3: watermark `2024-06-03` and no raw row is newer, so nothing changes. Running it again is safe: this is **idempotent** (Chapter 6).
- The late row 5 has `updated_at = 2024-06-01`, older than the watermark. The filter `>` skips it **forever**. Only a full refresh (or a lookback window) repairs it.

KEY INSIGHT

A watermark on `updated_at` is only correct if the source always stamps a *new, increasing* time on every change and every arrival. Late-arriving rows (Chapter 4, 4.3) break it. The usual fix is a **lookback window**: use `updated_at > max(updated_at) - interval '3 days'` together with a `unique_key`, so reprocessed rows replace themselves instead of duplicating.

Problem 7.2.1 Order 1 is changed on 5 June, and the incremental model has `unique_key='order_id'`, merge strategy. The table holds order 1 with amount 300. The new amount is 350. How many rows for order 1 after the run, and what amount?

Step 1	The row is newer than the watermark, so it is selected.
Step 2	Merge compares on `order_id`: a match exists, so it *updates* instead of inserting.
Answer	One row, amount 350.
Check	Without `unique_key` (append only) there would be two rows (300 and 350), and `SUM(amount)` would be inflated by 300.
Why it matters	Duplicate rows from a missing unique key is the most common incremental bug.

Snapshots: history of changing dimensions

Chapter 2 taught SCD Type 2 (keep every version of a dimension row with `valid_from` and `valid_to`). A dbt **snapshot** automates it. There are two strategies. The `timestamp` strategy compares an `updated_at` column. The `check` strategy compares the values of chosen columns. dbt adds the columns `dbt_valid_from` and `dbt_valid_to`; the current row has `dbt_valid_to` empty (null). Older dbt versions use a `{% snapshot %}` Jinja block; newer versions also allow a YAML definition. Check your version. Example (not run here):

```
{% snapshot snap_customers %}
{{ config(
    target_schema='snapshots',
    unique_key='customer_id',
    strategy='check',
    check_cols=['tier']
) }}
select customer_id, tier from {{ source('shop', 'raw_customers') }}
{% endsnapshot %}
```

You run `dbt snapshot` on a schedule. **A snapshot only records changes it sees.** If a customer changes tier twice between two runs, you only see the final value.

Our toy of the check strategy (real, run here; the SQL closes the old row and opens a new one when `tier` differs):

```
(1, 'silver', '2024-06-01', '2024-06-10')
(1, 'gold', '2024-06-10', None)
(2, 'gold', '2024-06-01', None)
```

Reading it: customer 1 was silver from 1 June until 10 June, then gold from 10 June (open, `None` means "still current"). Customer 2 never changed. We ran the snapshot a third time on 11 June with no change and no new rows appeared: the snapshot is idempotent.

Problem 7.2.3 An analyst joins orders to `snap_customers` to get the tier *at the time of the order*. Order 3 was placed on 2024-06-05 by customer 1. Which row matches?

Step 1	Join condition: `order_date >= valid_from and (order_date < valid_to or valid_to is null)`.
Step 2	Row 1: valid 06-01 to 06-10. 06-05 is inside this range. Row 2 starts 06-10, so no.
Answer	Tier silver.
Check	An order on 2024-06-12 would match the open row (gold).
Why it matters	"Revenue by tier *as it was*" needs history. Joining to the current tier rewrites the past.

Seeds are small CSV files in `seeds/` that `dbt seed` loads as tables (country codes, status mappings). Large or changing data belongs in a source instead.

Applications

- **Data Analytics:** "orders by tier at time of purchase" from snapshots.
- **Data Engineering:** cost control by incremental builds on event tables.
- **Machine Learning:** point-in-time correct training data needs historical dimension values, so leakage is avoided.
- **Compliance:** snapshots keep an audit trail of changing customer attributes.

COMMON MISTAKE

Treating `is_incremental()` as safe forever. Over months, late rows and logic changes leave the table slightly wrong. Schedule a weekly or monthly `--full-refresh`, and compare row counts with the source.

Check yourself

1. What do you add to an incremental model so changed rows replace old ones? Answer: `unique_key` (with a merge or delete+insert strategy).
2. What does `dbt_valid_to` empty mean? Answer: the row is the current version.
3. Why did our watermark miss row 5? Answer: its `updated_at` was older than the stored maximum.

7.3 Tests, Macros, Packages, Docs and CI

INTUITION

A restaurant kitchen has recipes (models), but also a person who tastes the dish before it leaves (tests). A macro is a kitchen tool you use in many recipes (a rice cooker). CI (continuous integration) is a rule that no new recipe reaches the menu until a taster has approved it.

Tests

Chapter 5 introduced data-quality checks. dbt has two kinds:

- **Generic tests**: four are built in, declared in YAML next to the model: `unique`, `not_null`, `accepted_values`, `relationships` (a foreign-key check).
- **Singular tests**: any `.sql` file in `tests/` that returns the *failing rows*. If it returns zero rows, it passes.

`models/marts/_models.yml` (not run here):

```
version: 2
models:
  - name: fct_orders
    description: "One row per order. Amount in rupees."
    columns:
      - name: order_id
        data_tests:          # older dbt versions use the key "tests:"
          - unique
          - not_null
      - name: customer_id
        data_tests:
          - relationships:
              to: ref('dim_customers')
              field: customer_id
      - name: status
        data_tests:
          - accepted_values:
              values: ['placed', 'shipped', 'cancelled']
```

A singular test `tests/no_negative_amounts.sql` (not run here):

```
select order_id, amount_rupees from {{ ref('fct_orders') }} where
amount_rupees < 0
```

The tests are just queries. Our SQLite version of four generic tests on a table where we planted two defects (a row with null `customer_id`, and an order whose customer 3 is missing from the customer table). Real output:

```
FAIL not_null(fct_orders.customer_id) failing rows: 1
PASS unique(fct_orders.order_id) failing rows: 0
FAIL relationships(fct_orders.customer_id->raw_customers) failing rows: 1
PASS accepted_values(snap.tier) failing rows: 0
```

Reading it: `not_null` finds the planted null. `relationships` finds order 4, whose customer 3 does not exist in `raw_customers` (an *orphan* key). `unique` and `accepted_values` pass. Note `relationships` ignores null keys (we filtered them with `IS NOT NULL`), so a null is reported once, by `not_null`.

Test severity: a test can be `warn` or `error`; `dbt build` stops downstream models when an upstream test fails, which prevents bad data from spreading into marts.

Problem 7.3.1 A model `dim_product` has 1,200 rows and `product_id` has 3 duplicated values (each appears twice). What does the `unique` test report, and what is the row count of distinct ids?

Step 1	Test query: `select product_id from dim_product group by product_id having count(*) > 1`.
Step 2	Three ids appear twice, so 3 rows come back.
Step 3	Rows involved: 1,200 total. The 3 duplicates account for 3 extra rows, so distinct ids = 1,200 − 3 = 1,197.
Answer	The test fails with 3 failing rows; there are 1,197 distinct products.
Check	1,197 + 3 = 1,200.
Why it matters	A duplicate dimension key silently multiplies fact rows in joins (fan-out, Chapter 2). This is why `unique` on every primary key is the first test to add.

Macros, packages and Jinja

A **macro** is a reusable Jinja function. `macros/cents_to_rupees.sql` (not run here):

```
{% macro paise_to_rupees(column_name) %}
    ({{ column_name }} / 100.0)
{% endmacro %}
```

Used as `select {{ paise_to_rupees('amount_paise') }} as amount_rupees from ...`. dbt first renders Jinja into plain SQL (you can see it with `dbt compile`), then sends the SQL to the warehouse. **Jinja runs in dbt, before the warehouse, and never sees your data.** That is why a Jinja `if` cannot depend on a column value, only on things known at compile time (such as the target environment).

Packages are shared dbt projects. You list them in `packages.yml` (for example `dbt_utils`, which has tests and macros such as `generate_surrogate_key`) and run `dbt deps`. Package names and versions change; check the dbt package hub.

CI with slim builds

CI for dbt means: on every pull request, build and test the changed models in a temporary schema, and block the merge if anything fails. Rebuilding all 500 models on each pull request is slow and costly. A **slim build** builds only what changed and what is downstream, and reads unchanged upstream models from production (**defer**). Command (not run here):

```
dbt build --select state:modified+ --defer --state ./prod_artifacts
```

`state:modified+` means "changed models and everything downstream". `--state` points to the saved `manifest.json` from the last production run. `--defer` says "if an upstream model was not rebuilt, use the production copy".

A typical team flow: branch in git, change SQL, push, CI runs `dbt build` slim on a PR schema, a colleague reviews, merge, then a scheduled production job runs `dbt build` (often from Airflow, Chapter 6, or dbt Cloud).

dbt Core, dbt Cloud, semantic layer

Item	What it is
dbt Core	The open-source command-line tool you run yourself (laptop, container, Airflow worker)
dbt	A paid hosted product: scheduler, IDE, CI, docs hosting

Cloud	
Semantic layer	You define *metrics* (such as `revenue = sum(amount)`) once in YAML; BI tools ask the layer for "revenue by city" and get one definition everywhere

Python transformation versus SQL and Spark

Not everything is SQL. A short decision guide:

Data size	Tool	Reason
Up to a few GB, one machine	pandas, Polars or DuckDB	No cluster; DuckDB runs SQL on files directly (Chapter 3)
Tens of GB, one big machine	Polars or DuckDB	Faster and more memory-friendly than pandas
Hundreds of GB to TB, in the warehouse	SQL via dbt	Warehouse scales the compute
Large files in a lake, complex logic	Spark (Chapters 9 and 10)	Distributes across a cluster

Some dbt adapters also support Python models, which run on the platform's Spark or Snowpark engine. Not run here.

`dbt docs generate` and `dbt docs serve` build a website with the lineage graph. An *exposure* in YAML declares a consumer (such as a dashboard) so you see who a change affects.

Applications

- **Data Analytics:** tested, documented marts that dashboards trust.
- **Data Engineering:** freshness checks on sources catch late loads before users see stale numbers.
- **MLOps:** the same CI idea (changed code, tested in a temp environment) applies to ML pipelines.
- **Governance:** exposures and lineage show who is affected by a change.

COMMON MISTAKE

Having models without tests, or tests that are always `warn`. A test nobody reads is decoration. Put `unique` and `not_null` on every primary key, `relationships` on every foreign key, and make the important ones `error`.

Check yourself

1. What must a singular test return to pass? Answer: zero rows.
2. What does `--defer` do? Answer: reads unchanged upstream models from the production state instead of rebuilding them.
3. Can a Jinja `if` check the value of a data row? Answer: no, Jinja runs at compile time before the warehouse sees any data.

Chapter recap

- dbt turns `SELECT` files into tables or views, orders them using `ref()`, tests them and documents them.
- `ref()` and `source()` build the DAG; never hard-code table names.
- Layers: staging (clean one source), intermediate (shared joins), marts (business-ready).
- Materializations: view, table, incremental, ephemeral (and materialized view where supported).
- Incremental needs `is_incremental()`, a `unique_key` and a plan for late data (lookback and periodic full refresh).
- Snapshots record history (SCD2) with `dbt_valid_from` and `dbt_valid_to`, but only for changes they observe.
- Tests are queries that return failing rows; four generic tests plus singular tests; `dbt build` stops downstream on failure.
- CI uses slim builds (`state:modified+`, `--defer`); choose pandas, Polars or DuckDB for small data and Spark for large.

Pattern	Command or code
Build model and downstream	`dbt run --select name+`

Build, test, seed, snapshot	`dbt build`
See rendered SQL	`dbt compile`
Incremental guard	`{% if is_incremental() %} ... {% endif %}`
Rebuild from scratch	`dbt run --full-refresh`
Slim CI	`dbt build --select state:modified+ --defer --state path`
Source freshness	`dbt source freshness`

Practice set

1. (easy) What does `dbt run --select fct_orders` build? **Answer:** only `fct_orders` (no `+`, so no upstream and no downstream).

2. (easy) Name the four built-in generic tests. **Answer:** `unique`, `not_null`, `accepted_values`, `relationships`.

3. What is printed by `{{ ref('stg_orders') }}` in a developer's private schema? **Answer:** the full name of that model in the developer's schema (for example `analytics.dev_asha.stg_orders`), not a fixed production name.

4. An incremental model has no `unique_key`. An order updates. What happens? **Answer:** a second row is appended (old and new both exist), double-counting in sums.

5. (find the bug) `where updated_at > (select max(updated_at) from stg_orders)` inside an incremental model. **Answer:** it should read from `{{ this }}` (the target table), not the source model; otherwise the watermark is the source's own maximum and nothing new is ever selected.

6. A snapshot with `check_cols=['tier']` runs daily. A customer changes silver, gold, silver within one day. What does the snapshot hold? **Answer:** no new row if the value at run time is the same as before (silver); intermediate changes between runs are invisible.

7. 800,000,000 rows, 4,000,000 changed per day, lookback of 2 days. Rows processed per day versus full rebuild? **Answer:** 2 × 4,000,000 = 8,000,000 versus 800,000,000, which is 100 times less.

8. Write a singular test returning orders shipped before they were placed. **Answer:** `select order_id from {{ ref('fct_orders') }} where shipped_at < placed_at`.

9. (interview) "How do you handle late-arriving data in an incremental dbt model?" **Answer:** use a unique key with a merge or delete+insert strategy, filter with a lookback window instead of a strict maximum, add freshness and volume tests, and run a periodic full refresh as the repair path.

10. (interview) "A pull request changes one staging model in a project of 400 models. How do you test it cheaply?" **Answer:** slim CI: `dbt build --select state:modified+ --defer --state prod_artifacts` into a PR-specific schema, so only the changed model and its downstream models are built and tested.

11. (scenario) The Finance dashboard shows revenue 12% too high after a model change. Where do you look first? **Answer:** check `unique` tests on the dimension and fact keys (fan-out from duplicate dimension rows), use the lineage graph to see all models touched, compare row counts before and after the join, and look at the incremental logic for a missing unique key.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me dbt
basics: models, sources, ref(), the DAG and the staging, intermediate and
marts layers. Use a small ShopKart orders example with real rows and
explain what ref() is replaced with in each environment. Then ask me 4
questions one at a time and check my answers before moving on.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Topic: dbt
materializations (view, table, incremental, ephemeral) and incremental
models with unique_key and a lookback window. Show a late-arriving row
that a strict watermark misses and how the lookback fixes it. Then give me
8 graded exercises without solutions. I will paste my answers: [PASTE
HERE]
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Explain dbt snapshots (SCD Type 2): the timestamp
and check strategies, dbt_valid_from and dbt_valid_to, and the limit that
snapshots only see changes at run time. Give a worked example with 3
customers and tier changes, and a point-in-time join. Then quiz me one
question at a time.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Review my dbt
project files for missing tests, hard-coded table names, wrong
materializations and unsafe incremental logic. Explain each issue in
simple English, show the fix, and rank issues by risk. My files: [PASTE
HERE]
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am applying for analytics engineer and data
engineer roles. Run a mock interview on dbt: ref and source, incremental
strategies, tests, snapshots, macros and Jinja, slim CI with defer, dbt
Core versus Cloud, and the semantic layer. Ask 8 questions one at a time.
After each answer give a score from 1 to 5, a model answer in simple
English, and one follow-up.
```

CHAPTER 8

CLOUD WAREHOUSES, COST CONTROL AND THE CLOUD DATA SERVICES MAP

Snowflake, BigQuery, Redshift, Synapse and Fabric; partitioning and clustering; paying only for what you scan; AWS, Azure and GCP side by side; and the NoSQL stores around them.

You have a clean `fct_orders` from Chapter 7. Where does it live, and who pays when 50 analysts query it at 10 a.m. on Monday? A **cloud data warehouse** is a database service built for analytics (OLAP, Chapter 1) that runs on rented machines. It scales up when you need it and costs money by the second or by the byte. The same SQL can cost Rs 10 or Rs 10,000 depending on how the table is laid out. In this chapter you will learn what all the big warehouses have in common, what is different, how partitioning and clustering reduce scanning (with a runnable simulation), how to control cost, and how the three big clouds map to each other. Finally, we look at the non-SQL databases (key-value, document, wide-column) that sit beside a warehouse in real systems.

Honest note: none of the cloud products can be run in this sandbox. Product features and names change often, so we teach the *concepts* and mark any product detail as "check current docs". We deliberately avoid prices. The simulations are our own teaching toys in Python.

Running example: ShopKart's `fct_orders` has 3,650,000 rows (365 days, 10,000 orders per day, 100 bytes per row), so about 365 MB. Small for a real warehouse, but the arithmetic scales: multiply by 10,000 to get a realistic 3.65 TB.

8.1 What Cloud Warehouses Have in Common (and Where They Differ)


INTUITION

Old warehouses were like a restaurant where the kitchen and the storeroom are one fixed building: to cook for more people you must build a bigger building. Cloud warehouses put the storeroom (cheap object storage) in one place and rent kitchens (compute) by the hour. Ten teams can have ten kitchens that all use the same storeroom, and a kitchen can be switched off when nobody is cooking.

Words you need

Word	Plain meaning	Example
Separation of storage and compute	Data lives in cheap shared storage; compute clusters are started and stopped independently	Finance and Marketing queries do not slow each other
Massively parallel processing (MPP)	Split a query over many machines that each handle a slice of the data	A 1 TB scan split over 100 workers
Virtual warehouse (Snowflake)	A named cluster of compute that runs queries; you choose a size and can pause it	`BI_WH` size Medium
Slot (BigQuery)	A unit of compute (CPU and memory) that BigQuery gives a query	A query using 2,000 slots
Micro-partition	A small immutable file block (tens of MB) with min and max values per column kept in metadata	Lets the engine skip blocks
Elasticity	Resize or add compute within seconds or minutes	Scale up for month-end
Pruning	Skipping blocks that cannot contain the answer	Read 1 day, not 365

The core design



How to read it: a query goes to a compute cluster; the cluster asks the metadata service which blocks it needs; it reads only those blocks from shared storage and works on them in parallel. Storage is billed per TB per month, compute per second or per scan.

The five big products at concept level

Product	Compute model	Layout tools	Notable ideas (verify current docs)
Snowflake	Virtual warehouses sized XS, S, M, L and so on; each size up roughly doubles the credits per hour; auto-suspend when idle	Automatic micro-partitions; optional clustering keys	Time travel (query an old state of a table for a retention period), zero-copy clone, streams and tasks (change capture and scheduling inside the warehouse), Snowpark (Python code that runs in the warehouse)
BigQuery	Serverless: you do not manage clusters. On-demand pricing by bytes scanned, or reserved capacity in slots	Partitioning (by date, ingestion time, integer range) and clustering (up to a few columns)	Nested and repeated fields (`STRUCT` and `ARRAY`) store one-to-many data in one row; a *dry run* tells you the bytes a query would scan before you run it

Redshift	Cluster of nodes (a leader and compute nodes), or Serverless	*Distribution style* (how rows are spread over nodes: `KEY`, `ALL`, `EVEN`, `AUTO`) and *sort keys* (physical row order)	Spectrum queries files in object storage; managed storage separates storage from compute on newer node types
Azure Synapse / Microsoft Fabric	Synapse dedicated pools (fixed capacity, 60 distributions) and serverless SQL over lake files; Fabric unifies lakehouse, warehouse and BI over one lake called OneLake	Hash, round-robin or replicated distribution in dedicated pools	Fabric is the newer direction; Synapse naming and products are evolving, so check docs
Databricks SQL	SQL warehouses (clusters tuned for SQL) over Delta Lake tables in your own storage	Delta partitioning, file compaction and clustering features	Lakehouse: one copy of data in open formats (Chapter 3.4), used by SQL and Spark

KEY INSIGHT

The products differ in *who manages the compute* (you pick sizes in Snowflake, Redshift and Synapse dedicated; the platform picks in BigQuery on-demand) and *what you pay for* (time versus bytes). That single difference changes how you optimize. Time-billed engines reward "finish the query fast and suspend". Byte-billed engines reward "scan fewer columns and fewer partitions".

Problem 8.1.1 A Snowflake-style Medium warehouse uses 4 credits per hour (XS = 1, S = 2, M = 4, L = 8; this doubling rule is the common pattern, check your account). A dashboard team leaves it running 24 hours a day on 30 days. With auto-suspend, it would actually run only 6 hours per day. How many credits are saved per month?

Formula	credits = credits per hour × hours
Plug in	always on: 4 × 24 × 30; with auto-suspend: 4 × 6 × 30
Compute	always on: 4 × 24 = 96 per day, × 30 = 2,880. Auto-suspend: 4 × 6 = 24 per day, × 30 = 720. Saved: 2,880 − 720 = 2,160
Answer	2,160 credits a month, which is 75% of the bill.
Check	6 hours out of 24 is one quarter, so 25% remains, and 2,160 / 2,880 = 0.75.
Why it matters	The cheapest optimization in time-billed warehouses is not a clever query. It is "do not pay for an idle machine". (Real billing has a small minimum per resume, so extremely frequent resume cycles cost a little extra.)

Connection to the real job

You will choose and justify one warehouse in a design interview, and you will be asked "how would you control its cost?". Your answer starts with the compute-versus-scan distinction above.

Applications

- **Data Analytics:** BI dashboards run on a separate warehouse so heavy analysts do not slow executives.
- **Data Engineering:** dbt (Chapter 7) runs on its own warehouse sized for the nightly job and suspended afterwards.
- **Machine Learning:** warehouse tables are the source of training sets and feature tables.
- **GenAI:** some warehouses can store embeddings or call hosted models; check docs of each product.

COMMON MISTAKE

Choosing a warehouse because of a feature list instead of the workload. Start from: data volume, concurrency (how many users), freshness, existing cloud, team skills, and cost model. Features are the tie-breaker.

Check yourself

1. What is the difference between a Snowflake virtual warehouse and a BigQuery slot? Answer: a virtual warehouse is a cluster you size and pause; a slot is a unit of compute

BigQuery allocates to a query for you.

2. What does "separation of storage and compute" allow? Answer: several independent compute clusters over the same data, each started, resized and stopped on its own.
3. Which is billed by bytes scanned in the default mode? Answer: BigQuery on-demand.

8.2 Partitioning, Clustering and Scan Pruning

INTUITION

A library with no shelves labels is hopeless: to find books from 2023 you open every box. If boxes are labelled by year (partitions), you open one box. Inside the box, if books are sorted by author (clustering), you only open the shelves between "K" and "M". The warehouse does the same with its blocks.

Definitions

- **Partitioning:** physically split a table into parts by the value of one column, usually a date. A query that filters on that column reads only the matching parts. You learned Hive-style folders in Chapter 3.3. The warehouse version is the same idea.
- **Clustering** (also called sort keys): keep rows with similar values of a column close together *inside* each part, so each block has a narrow min-max range for that column. The engine skips blocks whose range cannot match the filter.
- **Pruning:** the act of skipping parts and blocks using their metadata.
- **Cardinality:** how many distinct values a column has. Partition on low-to-medium cardinality columns (date: 365 per year). Never partition by `customer_id` with 50,000 values; you create tiny pieces (the small-file problem again).

Predict, Run, Explain: how many bytes do we scan?

We use the running example. Before running, predict: how many MB are scanned for `WHERE day = 100` with no partitioning, and with day partitioning? And inside one day, if rows are in random order versus sorted by country, how many of the 10 blocks contain `'DE'` ?

```
import random
random.seed(7)
days=365; rows_per_day=10000; bytes_per_row=100
countries=["IN","US","UK","DE","SG"]
data=[(d,random.choice(countries)) for d in range(days) for _ in
range(rows_per_day)]
total=len(data)*bytes_per_row
print(f"table: {len(data):,} rows, {total/1e6:.0f} MB")
print("no partition, WHERE day=100 :", f"{total/1e6:.0f} MB scanned")
print("partition by day, day=100   :", f"
{rows_per_day*bytes_per_row/1e6:.0f} MB scanned")
print("partition by day, 30 days   :", f"
{30*rows_per_day*bytes_per_row/1e6:.0f} MB scanned")
day=[c for d,c in data if d==100]
def blocks_read(rows,target,bs=1000):
    return sum(1 for i in range(0,len(rows),bs) if target in rows[i:i+bs])
print("unsorted day: blocks containing
'DE':",blocks_read(day,"DE"),"of",len(day)//1000)
print("sorted  day: blocks containing
'DE':",blocks_read(sorted(day),"DE"),"of",len(day)//1000)
rate=5.0   # illustrative price per TB scanned, NOT a real price
for lab,mb in (("full scan",total/1e6),("1
day",rows_per_day*bytes_per_row/1e6)):
    print(f"{lab}: {mb:.0f} MB -> cost at {rate}/TB = {mb/1e6*rate:.6f}
units; x1000 queries/day = {mb/1e6*rate*1000:.2f}")
```

Real output:

```
table: 3,650,000 rows, 365 MB
no partition, WHERE day=100 : 365 MB scanned
partition by day, day=100   : 1 MB scanned
partition by day, 30 days   : 30 MB scanned
unsorted day: blocks containing 'DE': 10 of 10
sorted  day: blocks containing 'DE': 3 of 10
full scan: 365 MB -> cost at 5.0/TB = 0.001825 units; x1000 queries/day =
1.82
1 day: 1 MB -> cost at 5.0/TB = 0.000005 units; x1000 queries/day = 0.00
```

Explanation:

- No partition: the engine cannot know which rows are on day 100, so it reads everything: 365 MB. With partitions it reads one: 1 MB, a 365-times reduction. Check: 3,650,000 rows ÷ 365 days = 10,000 rows × 100 bytes = 1,000,000 bytes = 1 MB.
- Unsorted: with 5 countries mixed randomly, every block of 1,000 rows almost surely

contains a DE row, so all 10 blocks are read. Sorted: the DE rows sit together, and 2,000 DE rows (about one fifth of 10,000) span about 2 blocks, plus the boundary: 3 blocks read. That is a 70% saving on that day.

- Cost: at an illustrative 5 units per TB, 1,000 full scans a day cost 1.82 units and 1,000 one-day scans cost almost nothing. Scale the table by 10,000 (365 MB becomes 3.65 TB) and the full scan costs 3.65 × 5 = 18.25 units per query: 18,250 for 1,000 queries versus 50 with partitioning. The ratio, not the unit, is the lesson.

Problem 8.2.1 A 3.65 TB table is partitioned by day (365 partitions, equal size). A dashboard query filters `day BETWEEN '2024-06-01' AND '2024-06-30'`. How much is scanned, and what percent of the table?

Formula	scanned = partitions matched × size per partition
Plug in	size per partition = 3.65 TB / 365 = 0.01 TB; matched = 30 days
Compute	30 × 0.01 = 0.30 TB; percent = 0.30 / 3.65 × 100 = 8.2%
Answer	0.3 TB, which is 8.2% of the table.
Check	30 / 365 = 0.0822, matching 8.2%.
Why it matters	A monthly report scans one twelfth of the table instead of all of it.

Problem 8.2.2 The same query is written `WHERE DATE(event_ts) = '2024-06-01'` on a table partitioned by `event_ts` (a timestamp). Does pruning still work?

Step 1	Pruning compares the partition's min and max of the *stored* column with your filter.
Step 2	A function wrapped around the column (`DATE(event_ts)`) can hide that link on some engines. Some engines recognise common patterns (like casting a timestamp to a date), others do not.
Answer	It may or may not prune depending on the engine. The safe style is a *range on the raw column*: `event_ts >= '2024-06-01' AND event_ts < '2024-06-02'`.
Check	Look at the query plan or a dry run: the bytes estimate tells you whether pruning happened.
Why it matters	A silent full scan is the number one cause of a surprise bill.

Cost-control checklist

- Select only the columns you need (columnar storage reads columns separately, Chapter 3.2). Never `SELECT *`.
- Filter the partition column with a plain range. `LIMIT` does not cut cost on scan-billed engines.
- Use a dry run or `EXPLAIN` before large queries.
- Materialize heavy aggregates (dbt table, Chapter 7) and use result caching (behaviour depends on the product).
- Auto-suspend and right-size compute; set budgets, alerts and resource limits.
- Avoid exploding joins: a join on a non-unique key multiplies rows (Chapter 2).

This is the **FinOps** habit from Chapter 1: tag every workload with an owner, track cost per pipeline, and review the top 10 most expensive queries every week.

Problem 8.2.3 A report scans a 2 TB table 20 times a day. A dbt model builds a 40 GB daily summary table once a day by scanning the 2 TB once. The report then reads the summary (40 GB) instead. Compare daily bytes scanned.

Step 1	Before: 20 × 2 TB = 40 TB.
Step 2	After: 1 × 2 TB (the build) + 20 × 0.04 TB = 2 + 0.8 = 2.8 TB.
Answer	40 TB falls to 2.8 TB, a 14.3 times reduction.
Check	40 / 2.8 = 14.29. The 40 GB = 0.04 TB conversion uses 1 TB = 1,000 GB.
Why it matters	"Aggregate once, query many times" is the standard cost win of the ELT pattern.

Connection to the real job

Cost reviews are a normal part of the data-engineer job. "Why did the bill double?" is answered by a list of queries by bytes, a missing partition filter, or a warehouse left running.

Applications

- **Data Analytics:** partition filters on dashboards keep refresh fast and cheap.
- **Data Engineering:** design layout (partition by event date, cluster by customer id) at table creation; compact small files.
- **Machine Learning:** point-in-time training sets read narrow date ranges.
- **FinOps:** unit-cost reporting, such as cost per 1,000 orders processed.

COMMON MISTAKE

Over-partitioning. Partitioning 365 MB by hour creates 8,760 tiny parts and *slows* queries because of metadata and small files. Aim for each partition to hold at least tens of MB to a few GB (check engine guidance).

Check yourself

1. A table is partitioned by date. Which filter prunes reliably: `WHERE day = '2024-06-01'` or `WHERE strftime('%d', day) = '01'` ? Answer: the plain comparison on the raw column.
2. Why did sorting reduce the blocks read from 10 to 3? Answer: equal values sit together, so only blocks in the DE range match.
3. What makes partitioning by `customer_id` a bad idea? Answer: very high cardinality gives millions of tiny parts.

8.3 The Cloud Services Map and the Non-SQL Stores

INTUITION

AWS, Azure and GCP are three supermarket chains selling mostly the same goods under different brand names. Once you know the aisles (storage, compute, warehouse, streaming, orchestration), you can shop in any of them. Employers usually hire for one chain but expect you to understand the aisle.

The mapping table

Capability	AWS	Azure	GCP
Object storage (data lake)	S3	Azure Data Lake Storage Gen2 (Blob)	Cloud Storage
Warehouse	Redshift	Synapse / Fabric Warehouse	BigQuery
Serverless query on lake files	Athena	Synapse serverless SQL	BigQuery external tables
Managed Spark	EMR, Glue	Synapse Spark, Databricks, Fabric	Dataproc, Databricks
Managed ETL / orchestration	Glue, Step Functions, MWAA (managed Airflow)	Data Factory	Cloud Composer (managed Airflow), Dataflow
Streaming ingest	Kinesis, MSK (managed Kafka)	Event Hubs	Pub/Sub
Stream processing	Kinesis Data Analytics / Managed Flink	Stream Analytics	Dataflow (Apache Beam)
Catalog and governance	Glue Data Catalog, Lake Formation	Purview	Dataplex

Monitoring	CloudWatch	Azure Monitor	Cloud Monitoring
Infrastructure as code	CloudFormation, Terraform	Bicep, Terraform	Deployment Manager, Terraform
Secrets and keys	Secrets Manager, KMS	Key Vault	Secret Manager, Cloud KMS

Service names change over time, so treat this as a map to confirm in current documentation. The skill-map certifications correspond: AWS Data Engineer Associate, an Azure data engineer exam (Fabric-based or current equivalent), Google Professional Data Engineer, Databricks Data Engineer, and SnowPro Core.

Beyond SQL: the other databases next to a warehouse

A warehouse is not the only data store. Production systems use several, each for what it does best. This is **polyglot persistence**.

Type	Examples	Data shape	Strong at	Weak at
Key-value	Redis, DynamoDB	key to value	Millisecond lookups, caches, sessions, counters	Ad-hoc queries across values
Document	MongoDB, Cosmos DB	JSON-like documents	Flexible schema, one object per read	Many-table joins
Wide-column	Cassandra, DynamoDB, HBase	rows by partition key, columns vary	Huge write volumes, time-ordered data	Queries not designed in advance
Time-series	InfluxDB, TimescaleDB	timestamp plus values	Metrics, IoT, downsampling	General relational work
Graph	Neo4j	nodes and edges	Relationship queries, fraud rings	Large aggregates
Search	Elasticsearch, OpenSearch	inverted index of text	Full-text search, log search	Strict transactions
NewSQL /	CockroachDB,	SQL with global	Transactions at scale	Cost and

distributed SQL	Spanner	scale	complexity

Three ideas matter for data engineers, and we can test each.

1. **Cache-aside with a TTL** (time to live): the application checks the cache first; on a miss it reads the database and stores the result for TTL seconds. Redis is the typical cache.
2. **Rate limiting (token bucket):** a bucket refills at a fixed rate and holds a maximum (the burst). Each request takes a token. APIs and ingestion clients use it (Chapter 4.2).
3. **Partition key choice:** in DynamoDB-style stores, the partition key decides which machine stores a row. A bad key creates a hot partition.

A runnable check (our own toy, plain Python, run here). Predict: a user "u1" is read 6 times at seconds 0, 10, 20, 61, 62, 130 with a TTL of 60. How many database calls?

```
6 reads, DB calls = 3 (misses at t=0, t=61, t=130)
100 requests over 5s at 20 rps: allowed=34 denied=66
partition key = date : {1: 1000}
partition key = user : {0: 249, 1: 251, 2: 249, 3: 251}
```

Reading each line:

- Cache: the value from t=0 lives until t=60, so reads at 10 and 20 hit. At t=61 it expired, so a miss; t=62 hits; the entry from t=61 expires at 121, so t=130 misses again. That is 3 database calls for 6 reads: the cache absorbed 50% of the reads.
- Token bucket: 5 tokens per second and a burst of 10. In 5 seconds you can earn 25 tokens, plus the initial 10 in the bucket, about 35 in total, and the simulation allowed 34 of 100. The limiter smooths a 20 requests-per-second client to about 5 per second after the initial burst.
- Partition key: using the date as the key put all 1,000 writes into one of 4 partitions (a hot partition: that one machine is the bottleneck). Using the user id spread them 249, 251, 249 and 251: even. This is the same imbalance idea as Spark skew in Chapter 10.

Problem 8.3.2 An IoT table in a wide-column store uses `device_type` as the partition key. There are 3 device types and 10,000 devices; one type ("thermostat") produces 70% of the writes. A cluster has 12 partitions' worth of capacity. What goes wrong, and what is a better key?

Step 1	With 3 key values, at most 3 partitions can ever receive writes; 9 of 12 sit idle.
Step 2	The thermostat partition receives 70% of the traffic, so it is the bottleneck.
Step 3	A better key is `device_id` (high cardinality), possibly combined with a day bucket: `(device_id, date)`, so one device's data does not grow forever in one partition.
Answer	Low-cardinality, skewed key causes hot partitions and idle capacity; use `device_id` plus a time bucket.
Check	With 10,000 device ids hashed over 12 partitions, each gets about 833 devices (10,000 / 12), so about 8.3% of the load each (assuming similar write rates per device).
Why it matters	Access patterns, not tables, drive NoSQL design: decide the queries first, then the key.

Connection to the real job

In a system design interview you will draw a warehouse and say what else sits around it: Redis for serving features with low latency, a document store for raw JSON, a search index for logs. Naming the right store with one strength and one weakness is what shows judgement.

Applications

- **Data Engineering:** land raw JSON in a document store or object storage; model facts in the warehouse; serve hot keys from Redis.
- **Machine Learning:** online feature stores are key-value stores (low latency) fed from the warehouse (offline).
- **GenAI:** vector search is a specialised index next to these stores (see the ML and GenAI documents).
- **Observability:** logs in a search engine, metrics in a time-series database.

COMMON MISTAKE

Using a document or key-value store for analytics because "it is faster". These stores are fast for the access path you designed. A new question (for example a join across three fields) can be impossible or very slow. Keep analytical questions in the warehouse.

Check yourself

1. Which AWS service maps to Azure Data Factory for orchestration of data movement? Answer: Glue (jobs) and Step Functions or managed Airflow for orchestration, depending on the task.
2. In a cache with TTL 60, a value is stored at t=0. Is a read at t=59 a hit? Answer: yes (it expires at t=60).
3. Why is `date` a bad partition key for a write-heavy key-value table? Answer: all writes for today land on one partition, creating a hot spot.

Chapter recap

- Cloud warehouses separate storage from compute, use MPP and columnar storage, and bill by time or by bytes scanned.
- Snowflake: virtual warehouses and micro-partitions. BigQuery: slots, serverless, partition and cluster, nested fields. Redshift: distribution and sort keys. Synapse and Fabric: Microsoft's family. Databricks SQL: SQL on Delta lakehouse.
- Partition by a date-like, medium-cardinality column; cluster by columns used in filters and joins; always filter with a plain range on the raw column.
- Check bytes with a dry run or `EXPLAIN` before large queries; avoid `SELECT *`.
- Biggest savings: suspend idle compute, aggregate once and read many times (a dbt table), prune partitions.
- Set budgets and alerts, tag workloads, review the top queries weekly (FinOps).
- AWS, Azure and GCP have one service for each lifecycle box; know the concept, then the name.
- NoSQL stores serve specific access patterns; choose partition keys with high cardinality and even load.

Pattern	Rule or formula
Credits	credits per hour × hours
Pruning	scanned = matched partitions × size per partition
Scan cost	TB scanned × price per TB
Aggregate once	build scan + (reads × summary size) versus reads × full size

Cache hit rate	hits / reads
Token bucket	allowed ≈ burst + rate × time

Practice set

1. (easy) Name two things you can do to reduce the cost of a time-billed warehouse. **Answer:** auto-suspend when idle and right-size the cluster (also stop duplicate dashboards from re-running heavy queries).

2. (easy) Does `LIMIT 10` reduce the bytes scanned on a scan-billed engine? **Answer:** usually no; the engine still reads the needed columns and partitions. Prune with a partition filter instead.

3. A 1.2 TB table is partitioned by day over 400 equal days. A query reads 7 days. Bytes scanned? **Answer:** 1.2 TB / 400 = 0.003 TB per day; 7 × 0.003 = 0.021 TB = 21 GB.

4. A Large warehouse (8 credits per hour) runs 3 hours a day for 20 days. Credits? **Answer:** 8 × 3 × 20 = 480.

5. (what is the output?) Cache TTL 30, reads at t = 0, 29, 30, 31. How many database calls? **Answer:** 2. The value stored at t=0 expires at 30, so reads at 0 miss, 29 hits, 30 misses (expired), 31 hits (stored at 30, expires at 60).

6. (find the bug) A table is partitioned by `order_date`. A dashboard query is `WHERE EXTRACT(MONTH FROM order_date) = 6`. **Answer:** a function on the partition column can block pruning (and it mixes all years); use `order_date >= '2024-06-01' AND order_date < '2024-07-01'`.

7. A table partitioned by `customer_id` (200,000 customers) holds 50 GB. Average size per partition and the problem? **Answer:** 50 GB / 200,000 = 0.00025 GB = 250 KB per partition: tiny parts, heavy metadata and slow scans. Partition by date and cluster by customer id.

8. (interview) "BigQuery or Snowflake for a new company?" **Answer:** it depends: on GCP with spiky, unpredictable usage and a small team, BigQuery's serverless model is attractive; with multi-cloud needs, predictable workloads and fine control of compute isolation, Snowflake fits. Compare concurrency, cost model, ecosystem, security and team skills, and run a proof of concept on real queries.

9. (interview) "Your monthly warehouse bill doubled. How do you investigate?" **Answer:** list queries and warehouses by cost for the two months, find the new or grown workloads, check for

missing partition filters, always-on or oversized compute, exploding joins and repeated identical queries; then fix the top offenders, add budgets and alerts, and tag workloads by owner.

10. (scenario) A rate-limited partner API allows 10 requests per second with bursts of 20. Your loader sends 50 requests per second. About how many succeed in the first 4 seconds under a token bucket? **Answer:** about 20 (burst) + 10 × 4 = 60 requests; the rest are denied or must wait and retry with backoff (Chapter 4.2).

Prompt pack

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me how
cloud data warehouses work: separation of storage and compute, MPP,
virtual warehouses versus slots, and time-billed versus scan-billed
pricing. Use a restaurant analogy and small numbers. Then ask me 4
questions one at a time and check my answers.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Topic:
partitioning, clustering, sort keys and distribution keys, and scan
pruning in warehouses. Give 8 graded exercises with real numbers (bytes
scanned, partitions matched, cardinality choices) and no solutions. I will
paste my answers: [PASTE HERE] and you will correct them step by step.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles. Explain warehouse cost control (FinOps): auto-
suspend, right-sizing, dry runs, result caching, materializing aggregates,
budgets and alerts. Walk me through investigating a bill that doubled,
with a made-up list of queries and costs. Then quiz me with 5 scenarios.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am applying for data engineer roles. Give me
a mapping drill: 12 data capabilities (object storage, warehouse, managed
```

Spark, streaming ingest, orchestration, catalog, secrets, monitoring and others). Ask me one at a time for the AWS, Azure and GCP service names, then correct me and explain the concept behind each.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am applying for data engineering interviews. Run a mock interview on warehouses and storage choices: Snowflake versus BigQuery versus Redshift, partition and cluster design, cost control, Redis, MongoDB, Cassandra and DynamoDB partition keys. Ask 8 questions one at a time, score each answer 1 to 5, give a model answer in simple English and one follow-up.

CHAPTER 9

APACHE SPARK AND PYSPARK I, ARCHITECTURE, DATAFRAMES, JOINS AND WINDOWS

How one program is split across many machines, why Spark is "lazy", and how to write correct DataFrame code.

Your ShopKart `fct_orders` grew to 2 billion rows and 400 GB of Parquet files. One laptop, or one pandas script, cannot hold it. The warehouse of Chapter 8 can, but some jobs are awkward in SQL: parsing messy logs, calling a Python library per row, or processing files that never go into a warehouse. **Apache Spark** is an engine that splits a big dataset into pieces, sends the pieces to many machines, and runs your program on all of them at once. **PySpark** is how you drive it from Python. In this chapter you will learn the architecture (driver, executors, jobs, stages, tasks), the two kinds of operations (transformations and actions), why Spark delays work until the last moment, and how joins and window functions behave on partitioned data. We will use *hand-worked partition examples* and small Python simulations that you can run. Chapter 10 then teaches how to make Spark fast.

Honest note: `pyspark` is **not installed** here and cannot be downloaded in this sandbox, so every PySpark snippet is labelled **not run here**. The simulations in plain Python and SQLite are real and were run. They are teaching toys, not Spark. If you want to try real Spark, install it on your own machine (`pip install pyspark` , Java required) or use a free Databricks Community-style notebook if available to you.

Running example: eight ShopKart orders `(order_id, city, amount)` , small enough to follow by hand.

9.1 The Architecture: Driver, Executors, Jobs, Stages, Tasks

INTUITION

A manager (the **driver**) has a pile of 400 exam papers to mark. She hires 10 markers (the **executors**). She cuts the pile into 100 bundles (**partitions**) and hands bundles out. Each marker marks one bundle at a time (a **task**). For a final total, markers must exchange partial totals (a **shuffle**), which is slow because people must walk around. Spark is this classroom for data.

Words you need

Word	Plain meaning	Example
Cluster	A group of machines working together	10 machines
Driver	The one process that runs your program, plans the work and collects results	Your notebook or `spark-submit` main program
Executor	A worker process on a cluster machine that runs tasks and holds cached data	10 executors with 4 cores and 16 GB each
Cluster manager	Software that gives the driver machines to use: YARN, Kubernetes, standalone Spark, or a managed one (Databricks, EMR)	Kubernetes
Partition	One slice of the dataset that a single task processes	128 MB of a Parquet file
Task	The unit of work: one operation chain on one partition	"filter and select on partition 3"
Stage	A group of tasks that can run without moving data between machines	Read + filter + select
Job	The whole set of stages produced by one *action*	"count the orders"
Shuffle	Redistributing rows across the network so rows with the same key meet	`groupBy("city")`

DAG	The plan graph of stages (Chapter 6 for the idea)	Stage 1 then Stage 2

How a program runs

Spark: an action starts a job; narrow steps stay in a stage; a shuffle splits stages

How to read the picture: the box labelled Stage 1 shows tasks, one per partition, each doing filter and select on its own slice. No data moves between them. Then comes a big shuffle arrow: every task sends rows to every task of Stage 2 (writing to disk and sending over the network). Stage 2 runs `groupBy` or `join` on the reshuffled partitions. The action at the top (such as `count` or `write`) is what starts the whole job.

```
Your PySpark code (driver)
        |  builds a logical plan (lazy)
        v
   Catalyst optimizer  -> physical plan  -> stages
        |
        v
 +-------------+      tasks      +-----------+  +-----------+  +----------
-+
 | cluster mgr |  ------------>  | executor1 |  | executor2 |  | executor3
|
 +-------------+                 | cores=4   |  | cores=4   |  | cores=4
|
                                 +-----------+  +-----------+  +----------
-+
        ^                                                        results
        +---------------- driver collects (small!) <---------------+
```

Three counting rules to remember:

1. One **task** per partition per stage.
2. Tasks that can run at the same time = executors × cores per executor. This is the number of **slots**.
3. A new **stage** begins at every shuffle (a *wide* operation). Operations such as `filter`, `select` and `withColumn` are *narrow*: each output partition depends on one input partition.

Problem 9.1.1 A job reads 400 GB of Parquet in 128 MB splits. The cluster has 10 executors

with 4 cores each. How many tasks in the read stage, how many slots, and how many waves?

Formula	tasks = data size / partition size; slots = executors × cores; waves = ⌈tasks / slots⌉
Plug in	400 GB = 400 × 1,024 MB = 409,600 MB; ÷ 128 MB
Compute	tasks = 409,600 / 128 = 3,200. Slots = 10 × 4 = 40. Waves = ⌈3,200 / 40⌉ = 80
Answer	3,200 tasks, 40 slots, 80 waves. If each task takes 6 seconds, the stage takes about 80 × 6 = 480 seconds (8 minutes).
Check	80 waves × 40 slots = 3,200 tasks, so no task is left over.
Why it matters	This is the same arithmetic as a restaurant kitchen: work (dishes) divided by parallel capacity (cooks), times the time of one unit (minutes per dish).

Cluster managers and platforms

- **Standalone, YARN, Kubernetes**: where Spark gets machines. YARN is common in older Hadoop shops; Kubernetes is common in newer ones.
- **Managed platforms** hide the cluster: Databricks (notebooks, jobs, Delta Live Tables or Lakeflow pipelines, Unity Catalog for governance), AWS EMR and Glue, Google Dataproc, Azure Synapse Spark and Fabric. You choose a worker type and count, they do the rest. Names and features change, so check current docs.
- **Deploy modes** (awareness): in *client* mode the driver runs where you launch it (a notebook); in *cluster* mode the driver runs inside the cluster (production jobs).

Connection to the real job

In an interview, "explain what happens when I call `df.groupBy('city').count().show()`" expects: lazy plan, optimizer, a shuffle that splits stages, tasks per partition, results returned to the driver. You can now answer.

Applications

- **Data Engineering:** nightly batch jobs on lake data, large joins, compaction, backfills.
- **Machine Learning:** feature engineering over terabytes; distributed training prep; MLlib (Spark's library, awareness level).
- **Data Analytics:** Spark SQL on Delta tables behind a SQL endpoint.

- **GenAI:** large-scale text cleaning, deduplication and chunking of documents before training or indexing.

COMMON MISTAKE

Using Spark for small data. Starting a cluster costs seconds to minutes, and shuffles add overhead. Below roughly tens of GB, DuckDB, Polars or the warehouse is usually faster and cheaper (Chapter 7.3).

Check yourself

1. What decides the number of tasks in a stage? Answer: the number of partitions.
2. What starts a new stage? Answer: a shuffle (a wide operation such as `groupBy` or `join`).
3. Where does your Python main code run? Answer: on the driver.

9.2 DataFrames, Transformations vs Actions, and Lazy Evaluation

INTUITION

You tell a travel agent: "book a flight to Pune, then a hotel, then a cab". A lazy agent writes your plan on paper and does nothing. Only when you say "go" does she look at the whole plan, notice that the cab company is next to the hotel, and make the cheapest set of bookings. Spark is the lazy agent. Writing transformations is writing the plan. An **action** says "go".

The APIs

- **RDD** (Resilient Distributed Dataset): the original low-level API, a distributed collection of Python or JVM objects. Spark cannot look inside your functions to optimize. Understand it; rarely write it.
- **DataFrame**: a distributed table with named, typed columns, like a SQL table. Spark can optimize it with its **Catalyst** optimizer. This is what you use.
- **Spark SQL**: the same engine, queried with SQL text (`spark.sql("select ...")`). DataFrame code and SQL compile to the same plan, so choose whichever is clearer.
- **Dataset**: typed DataFrame in Scala and Java; not available in Python.

Transformations and actions

Kind	What it does	Examples	Returns
Narrow transformation	Each output partition from one input partition; no shuffle	`select`, `filter`, `withColumn`, `map`, `explode`	A new DataFrame (a plan, no work)
Wide transformation	Needs rows from many partitions; causes a shuffle	`groupBy().agg`, `join`, `distinct`, `orderBy`, `repartition`	A new DataFrame (a plan)
Action	Triggers real execution	`count`, `show`, `collect`, `write`, `take`	A number, rows or files

Lazy evaluation means transformations only record a plan. Why is this good? Spark sees the whole plan before running and can reorder it: push the filter before the join, read only the needed columns of the Parquet file (*column pruning*) and skip row groups that fail the filter (*predicate pushdown*, Chapter 3.2).

Predict, Run, Explain: a mini lazy engine (real, run here)

Our toy `DF` class records a plan in a tuple and only runs it when `count()` is called. We split the 8 orders into two partitions (round-robin: order 1 to P0, order 2 to P1, and so on). Predict: what are the two partitions? And will anything run when we write `filter` and `map`?

Real output of the part of the script that builds and runs the plan:

```
input partitions:
 P0 [('o1', 'pune', 250), ('o3', 'pune', 50), ('o5', 'mumbai', 300),
('o7', 'mumbai', 40)]
 P1 [('o2', 'delhi', 120), ('o4', 'delhi', 80), ('o6', 'pune', 100),
('o8', 'delhi', 60)]
built plan, nothing ran yet; plan has 2 steps
  running plan: ['amount>=100', 'to float']
count() = 4
```

Explanation:

- `parts=[orders[i::P] for i in range(P)]` takes every second order starting at index 0 and at index 1: that is P0 and P1 above. Real Spark partitions by file splits, but the idea is

the same.

- `df.filter(...).map(...)` printed "built plan, nothing ran yet; plan has 2 steps". The class only did `s.plan+(...)`. That is a transformation: it returns a new object holding a longer plan.
- `q.count()` is the action. Only then does the line `running plan` appear. The plan runs *per partition*: each partition applies filter then map independently (narrow, no network), then the counts are added at the driver.
- 4 orders have amount at least 100: o1 (250), o5 (300), o2 (120), o6 (100). The output 4 is right.

The same program in PySpark (not run here):

```
from pyspark.sql import SparkSession, functions as F

spark = SparkSession.builder.appName("shopkart").getOrCreate()

orders = spark.read.parquet("s3://shopkart-lake/silver/orders/")   #
transformation: lazy
big = (orders
       .filter(F.col("amount") >= 100)                # narrow
       .withColumn("amount_f", F.col("amount").cast("double")))   # narrow
print(big.count())        # ACTION: the job runs now
big.explain()             # prints the physical plan; no job
```

groupBy: a shuffle, hand-worked

We now do `groupBy("city").sum("amount")` by hand in two stages. This is exactly what Spark does: **partial aggregation** on each partition first (the *map side*), then a **shuffle** that sends each city to one new partition chosen by `hash(city) mod 2`, then a final sum (the *reduce side*). Real output of our simulation:

```
Stage 1: partial sums per input partition (no network)
 P0 {'pune': 300, 'mumbai': 340}
 P1 {'delhi': 260, 'pune': 100}
Shuffle: send each (city,partial) to partition hash(city)%2
 new P0 {'mumbai': [340], 'delhi': [260]}
 new P1 {'pune': [300, 100]}
Stage 2: final sum
 P0 {'mumbai': 340, 'delhi': 260}
 P1 {'pune': 400}
rows shuffled with partial agg: 4 vs without: 8
```

Follow it by hand: in P0, Pune has 250 + 50 = 300 and Mumbai has 300 + 40 = 340. In P1, Delhi has 120 + 80 + 60 = 260 and Pune has 100. The hash sends `pune` to new partition 1, and `mumbai` and `delhi` to partition 0 (the hash is `zlib.crc32` ; real Spark uses Murmur3, so the exact placement differs, but the principle holds). Final: Pune 300 + 100 = 400, Mumbai 340, Delhi 260. Check: 400 + 340 + 260 = 1,000 = the sum of all 8 amounts (250+120+50+80+300+100+40+60 = 1,000).

The shuffle moved 4 partial rows instead of 8 raw rows. With 2 billion orders and 50 cities the saving is from 2 billion rows to at most 50 per input partition. This is why `groupBy().sum()` is cheaper than it sounds, and why `groupByKey` on RDDs (no partial aggregation) is discouraged.

Problem 9.2.1 Same 8 orders, but now partition 3 ways: P0 = o1, o2, o3; P1 = o4, o5, o6; P2 = o7, o8. Compute the partial sums per city per partition, and the number of partial rows that must be shuffled.

Step 1	P0: o1 pune 250, o2 delhi 120, o3 pune 50. Partials: pune 300, delhi 120 (2 rows).
Step 2	P1: o4 delhi 80, o5 mumbai 300, o6 pune 100. Partials: delhi 80, mumbai 300, pune 100 (3 rows).
Step 3	P2: o7 mumbai 40, o8 delhi 60. Partials: mumbai 40, delhi 60 (2 rows).
Compute	Rows shuffled = 2 + 3 + 2 = 7 (versus 8 raw rows). Final: pune 300 + 100 = 400; delhi 120 + 80 + 60 = 260; mumbai 300 + 40 = 340.
Answer	7 partial rows are shuffled, and the final answer is the same as before: pune 400, delhi 260, mumbai 340.
Check	400 + 260 + 340 = 1,000. The result does not depend on how rows are partitioned. Only the *amount of data moved* does.
Why it matters	Correctness never depends on partitioning; performance always does.

Caching: avoid recomputing the plan

Because evaluation is lazy, *every action recomputes the whole plan from the source*. If you use the same DataFrame three times, you read and compute three times. `df.cache()` or `df.persist(storage_level)` keeps it in memory (or disk) after the first action. The toy proves the idea:

```
without cache, 3 actions -> expensive() calls: 24
with cache,    3 actions -> expensive() calls: 8
```

8 rows × 3 actions = 24 calls; with a cache the first pass stores 8 rows, and the later two actions reuse them (8 calls). Cache a DataFrame only when it is used several times and is expensive; call `unpersist()` when finished. More in Chapter 10.

Schemas, types and I/O

- **Schema inference versus explicit schema.** `spark.read.csv(p, header=True, inferSchema=True)` scans the file an extra time to guess types, and guesses can be wrong (zip codes become integers and lose leading zeros, Chapter 3.1). In production define the schema yourself with `StructType` or a DDL string such as `"order_id long,`

`city string, amount double"` . Parquet and Delta carry their schema, so no inference is needed.

- **Complex types.** Columns can be `struct` (named fields), `array` and `map` . `explode` turns each array element into its own row. Example (not run here): `df.select("order_id", F.explode("items").alias("item"))` takes one row with 3 items and produces 3 rows.
- **I/O.** Read and write Parquet, Delta or Iceberg, CSV and JSON, JDBC databases (`spark.read.jdbc` , use partition options or it reads through one connection), and cloud storage paths (`s3://` , `abfss://` , `gs://`).
- **Write modes.** `append` , `overwrite` , `errorifexists` (default), `ignore` . Use `partitionBy("day")` for Hive-style folders (Chapter 3.3).

```
(orders.write.mode("overwrite")
       .partitionBy("order_date")
       .parquet("s3://shopkart-lake/gold/orders/"))      # not run here
```

COMMON MISTAKE

`df.collect()` on a big DataFrame. It pulls *all rows to the driver's memory* and can crash the driver with an out-of-memory error. Use `show(20)` , `take(20)` , `limit(100).toPandas()` or write to storage.

UDFs, pandas UDFs and built-ins

A **UDF** (user-defined function) is your own Python function applied to columns.

Option	Speed	Notes
Built-in functions (`F.upper` , `F.when` , `F.regexp_extract` , ...)	Fastest	Run inside the JVM; the optimizer understands them
pandas UDF (vectorized, uses Arrow)	Medium	Processes batches of rows as pandas Series; good for libraries like NumPy
Plain Python UDF	Slowest	Each row is serialized between the JVM and a Python process

Rule: **prefer built-ins; use a pandas UDF if you must; use a plain UDF last.** Higher-order

functions on arrays (`F.transform` , `F.filter` , `F.aggregate`) let you work on array columns without a UDF.

```
# not run here
@F.udf("double")
def rupees(paise): return paise / 100.0          # slow: use
F.col("paise") / 100 instead
```

Connection to the real job

Reading a colleague's PySpark job, you look for: how many actions, what gets cached, whether a UDF could be a built-in, and whether the schema is explicit. That checklist finds most problems.

Applications

- **Data Engineering:** the silver layer: read raw JSON, apply an explicit schema, deduplicate, write partitioned Parquet or Delta.
- **Machine Learning:** `explode` and array functions to build sequence features from clickstreams.
- **Data Science:** `toPandas()` on an aggregated, small result to plot or model.
- **GenAI:** pandas UDFs to call an embedding or tokenizer library on batches of text.

COMMON MISTAKE

Thinking `filter` after `join` is the same cost as `filter` before. The optimizer often fixes this for you (predicate pushdown), but not always, especially with UDFs. Filter early, in the code, to be safe.

Check yourself

1. Is `df.withColumn(...)` a transformation or an action? Answer: transformation (lazy, narrow).
2. Why is `inferSchema=True` costly? Answer: Spark must read the data an extra time to guess types, and the guess can be wrong.
3. Which is fastest: built-in function, pandas UDF or Python UDF? Answer: the built-in function.

9.3 Joins and Window Functions on Partitioned Data

INTUITION

Joining two stacks of cards by customer id on one table is easy. On a cluster, the cards for customer 7 may sit on different machines. To join, either send both stacks to meet at an agreed table (**shuffle join**, hash by key), or, if one stack is tiny, hand every machine a copy of it (**broadcast join**).

We use two small tables. The SQL results below are real (SQLite), and each Spark join type corresponds to one of them. For the semantics of SQL joins and windows in depth, see the SQL study document (`study/sql/`).

```
orders (o1..o6): (order_id, customer_id, city, amount, day)
 o1 cust 1 pune   250 2024-06-01     o4 cust 9 delhi   80 2024-06-02
 o2 cust 2 delhi  120 2024-06-01     o5 cust 3 mumbai 300 2024-06-03
 o3 cust 1 pune    50 2024-06-02     o6 cust 1 pune   100 2024-06-03
customers: 1 Asha, 2 Ravi, 3 Meera, 4 Kiran
```

Customer 9 (order o4) has no row in `customers` , and customer 4 (Kiran) has no orders.

Join types

Spark `how=`	Meaning	Rows returned for our data
`inner`	Only matching rows	o1, o2, o3, o5, o6 (5 rows)
`left` (left outer)	All orders; customer name null if no match	6 rows; o4 has name None
`left_semi`	Orders that *have* a match; only order columns; never duplicates	o1, o2, o3, o5, o6
`left_anti`	Orders that have *no* match	o4
`right` , `full`	Keep unmatched rows from the right side or both sides	Kiran appears with null order columns
`cross`	Every pairing (rows left × rows right); avoid	6 × 4 = 24 rows

	unless intended

Real SQL output for four of them (the same logic Spark uses):

```
-- inner                        -- left                        -- left_anti
-- left_semi
('o1', 'Asha')                  ('o1', 'Asha')                 ('o4',)
('o1',) ('o2',) ('o3',)
('o2', 'Ravi')                  ('o2', 'Ravi')
('o5',) ('o6',)
('o3', 'Asha')                  ('o3', 'Asha')
('o5', 'Meera')                 ('o4', None)
('o6', 'Asha')                  ('o5', 'Meera')
                                ('o6', 'Asha')
```

PySpark equivalents (not run here):

```
joined  = orders.join(customers, on="customer_id", how="inner")
missing = orders.join(customers, on="customer_id", how="left_anti")   #
orphan orders
```

`left_anti` is the standard test for orphan keys (the `relationships` test from Chapter 7 is exactly this query).

How Spark runs a join

Strategy	How	Best when	Cost
Broadcast hash join	Send the small table to every executor; each task joins its slice of the big table locally	One side is small (default threshold about 10 MB; commonly raised to 50-200 MB, check settings)	No shuffle of the big side
Shuffle (sort-merge) join	Both sides are shuffled by key, sorted, then merged	Both sides large	Shuffles both sides; slowest
Shuffle hash join	Shuffle both, build a hash table of the smaller side per	Medium sizes	Needs memory

	partition	per partition

Hand-worked partition example. Two input partitions of `orders` (P0 = o1, o3, o5; P1 = o2, o4, o6) and the customers table split as C0 = customers 1, 3 and C1 = customers 2, 4. For a shuffle join we send every row to partition `customer_id mod 2`:

- Key 1 and 3 (odd) go to partition 1: orders o1 (cust 1), o3 (cust 1), o5 (cust 3), o6 (cust 1), o4 (cust 9, odd) and customers Asha (1), Meera (3).
- Key 2 and 4 (even) go to partition 0: order o2 (cust 2) and customers Ravi (2) and Kiran (4).
- Join inside partitions: partition 1 gives o1-Asha, o3-Asha, o5-Meera, o6-Asha; o4 finds no customer 9. Partition 0 gives o2-Ravi.
- Total inner join rows: 4 + 1 = 5. This equals the SQL result above.

All orders of one customer meet the matching customer row because they have the same key and the same hash. That is the whole point of a shuffle join, and it is also why one hot key (a huge customer, or `null`) overloads one partition (Chapter 10).

Problem 9.3.1 An `events` table has 3 billion rows (1.5 TB). A `devices` table has 2 million rows (80 MB). You join on `device_id` on a cluster of 20 executors. Estimate bytes moved by a broadcast join and by a shuffle join.

Formula	broadcast moves about small size × executors; shuffle moves about both sides
Plug in	broadcast: 80 MB × 20 = 1,600 MB; shuffle: 1.5 TB + 0.08 TB
Compute	broadcast = 1,600 MB = 1.6 GB. Shuffle = 1.58 TB = 1,580 GB. Ratio = 1,580 / 1.6 = 987.5
Answer	Broadcast moves about 1.6 GB, shuffle about 1.58 TB: roughly a thousand times more.
Check	80 MB × 20 = 1,600 MB. Units match.
Why it matters	Joining a big fact to a small dimension should *always* be a broadcast. Mark it explicitly with `F.broadcast(devices)` (not run here) if the optimizer does not choose it. (The 80 MB must fit in memory on each executor, and in the driver while it is collected.)

Window functions

A window function computes a value for each row using *other rows of the same group* without collapsing rows like `groupBy`. Same idea as SQL (`study/sql/`). In Spark, the **partitioning** of the window decides the shuffle: `Window.partitionBy("customer_id")` sends all rows of one customer to one partition, then sorts within it.

Real SQL output for customer 1 (running total, and rank by amount):

```
(1, '2024-06-01', 250, 250, 1)
(1, '2024-06-02', 50, 300, 3)
(1, '2024-06-03', 100, 400, 2)
```

The columns are `customer_id, day, amount, running, rn`. Running total by day: 250, then 250 + 50 = 300, then 300 + 100 = 400. Rank by amount descending: 250 is 1, 100 is 2, 50 is 3. PySpark (not run here):

```
from pyspark.sql import Window
w_day  = Window.partitionBy("customer_id").orderBy("day")
w_amt  = Window.partitionBy("customer_id").orderBy(F.col("amount").desc())
out = (orders
       .withColumn("running", F.sum("amount").over(w_day))
       .withColumn("rn", F.row_number().over(w_amt)))
```

Notes: with `orderBy` inside a window, the default frame runs from the start of the partition to the current row (that is why `sum` becomes a running total). A window with *no* `partitionBy` moves all rows to a single partition, which is slow and risks memory errors (Spark warns about it).

Problem 9.3.2 Keep only the latest order per customer using a window. Which rows remain from the orders table?

Step 1	Partition by `customer_id`, order by `day` descending, and add `row_number`.
Step 2	Customer 1 has o6 (06-03), o3 (06-02), o1 (06-01): o6 gets 1. Customer 2: o2 gets 1. Customer 3: o5 gets 1. Customer 9: o4 gets 1.
Step 3	Keep rows with `rn = 1`.
Answer	o6, o2, o5 and o4 remain.
Check	One row per distinct customer id in orders: customers 1, 2, 3, 9, so 4 rows.
Why it matters	This "keep the latest row per key" pattern is the standard deduplication step for CDC data (Chapter 4.3).

Test PySpark with `pytest` on tiny local DataFrames; Spark Connect (a thin remote client) is awareness level. Not run here.

Connection to the real job

Most real Spark work is: read, clean, join to dimensions (broadcast), deduplicate with a window, aggregate, write partitioned Delta or Parquet. This is the batch backbone of the medallion architecture (Chapter 1.3).

Applications

- **Data Engineering:** CDC deduplication with `row_number`; sessionization with `lag` and window sums.
- **Data Analytics:** running totals, moving averages and top-N per group at scale.
- **Machine Learning:** rolling features (7-day order count per customer) via windows with a range frame.
- **Fraud:** anti-joins to find transactions from devices not in the trusted list.

COMMON MISTAKE

Joining on a column with nulls and expecting nulls to match. In Spark (as in SQL) `null = null` is not true, so null keys never match in an equality join (use `eqNullSafe` if you really want it). Also: when a join key is duplicated on the right side, rows multiply (fan-out); check counts after joins.

Check yourself

1. Which join type returns orders with no matching customer? Answer: `left_anti`.
2. Why is a broadcast join cheaper than a shuffle join for fact-to-dimension? Answer: only the small table is copied; the big table is not moved.
3. What does a window without `partitionBy` do? Answer: all rows go to one partition, which is slow and may run out of memory.

Chapter recap

- Spark splits data into partitions; one task runs per partition; stages are separated by shuffles; an action starts a job.
- The driver plans and collects; executors run tasks; slots = executors × cores; waves = ⌈tasks / slots⌉.
- Use DataFrames and Spark SQL (optimized by Catalyst); RDDs are for understanding.
- Transformations are lazy and narrow or wide; actions (`count`, `show`, `write`, `collect`) trigger work. Every action recomputes the plan unless the data is cached.
- A groupBy aggregates partially on each partition, shuffles partial results, then finishes: correctness is independent of partitioning, speed is not.
- Prefer explicit schemas; never `collect()` big data; prefer built-in functions over UDFs.
- Joins: inner, left, semi, anti, full, cross; broadcast the small side, shuffle when both are large.
- Windows partition and sort rows by key; always give `partitionBy`; `row_number` plus a filter finds the latest row per key.

Pattern	Code
Start	`spark = SparkSession.builder.getOrCreate()`
Filter and derive	`df.filter(F.col("x") > 0).withColumn("y", F.col("x") * 2)`
Group	`df.groupBy("k").agg(F.sum("v").alias("total"))`
Join	`a.join(b, "k", "left_anti")`
Broadcast	`a.join(F.broadcast(b), "k")`
Window	`Window.partitionBy("k").orderBy("t")`

Plan	`df.explain()`
Cache	`df.cache(); ...; df.unpersist()`

Practice set

1. (easy) Is `filter` a transformation or an action? **Answer:** a (narrow) transformation.

2. (easy) What does `df.count()` do? **Answer:** it is an action: it runs the plan and returns the row count to the driver.

3. 64 GB of Parquet in 128 MB partitions on 8 executors with 4 cores. Tasks, slots, waves? **Answer:** 64 × 1,024 / 128 = 512 tasks; 8 × 4 = 32 slots; ⌈512 / 32⌉ = 16 waves.

4. Compute the final groupBy result for city amounts P0: (a, 10), (b, 5); P1: (a, 7), (b, 3), (c, 4). **Answer:** a = 17, b = 8, c = 4. Partial rows shuffled: 2 + 3 = 5.

5. (what is the output?) `orders.join(customers, "customer_id", "left_semi").count()` on our data. **Answer:** 5 (o1, o2, o3, o5, o6).

6. (find the bug) `rows = big_df.collect(); for r in rows: ...` on 500 million rows. **Answer:** `collect()` brings everything to the driver and will run out of memory. Process on the executors (DataFrame operations or `foreach` / `mapInPandas`) or write the result to storage.

7. (find the bug) `df.withColumn("d", F.col("a")/F.col("b"))` is called alone, and later `df` has no column `d`. **Answer:** DataFrames are immutable; `withColumn` returns a new DataFrame. Assign it: `df = df.withColumn(...)`.

8. A DataFrame is used by three actions and costs 10 minutes to compute. Roughly how long without and with `cache()`? **Answer:** without: 3 × 10 = 30 minutes. With: 10 minutes for the first action plus fast reads (seconds to a minute) for the others, so about 10-12 minutes.

9. (interview) "What is the difference between `repartition` and `coalesce`?" **Answer:** `repartition(n)` does a full shuffle and can increase or decrease partitions with even sizes; `coalesce(n)` only merges existing partitions without a full shuffle, so it can only decrease and may leave uneven sizes. Use `coalesce` to reduce files before writing, `repartition` to rebalance.

10. (interview) "Why is a Python UDF slower than a built-in?" **Answer:** each row is serialized from the JVM to a Python process and back, and the optimizer cannot look inside the function; built-ins run natively in the JVM and take part in optimization. Pandas UDFs reduce the cost with

batches and Arrow.

11. (scenario) A nightly job reads a 300 GB table twice (two `write` actions) and takes 2 hours. Suggest two improvements. **Answer:** cache the shared intermediate DataFrame (or write it once and re-read it) so the plan is not recomputed; combine into one pass where possible; and check that filters and columns are pruned at the read (use `explain()`).

Prompt pack

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me Spark
architecture: driver, executors, partitions, tasks, stages, jobs and
shuffles. Use a classroom-marking analogy and compute tasks, slots and
waves for a 200 GB dataset with real numbers. Then ask me 4 questions one
at a time and check my answers.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Topic: Spark
transformations versus actions and lazy evaluation. Give me 8 short
PySpark snippets and ask me, for each, which lines trigger a job and how
many jobs run in total, with no solutions at first. I will paste my
answers: [PASTE HERE]. Then correct me step by step.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles. Explain Spark joins: inner, left, semi, anti,
full, cross, and the broadcast versus shuffle strategies. Work through a
hand example with two small tables split into partitions, hashing keys to
partitions, and show the rows each partition joins. Then give me 5
exercises to practise the same hand method.
```

✨ AI prompt: copy and paste into any AI

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Explain Spark
window functions with partitionBy and orderBy: running totals, row_number,
```

rank, lag, and keeping the latest row per key. Use a small orders table with real rows, show the result row by row, and explain the default frame. Then quiz me one question at a time.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am applying for data engineer roles. Run a mock interview on PySpark fundamentals: architecture, lazy evaluation, DataFrame versus RDD, UDF types, schema inference, repartition versus coalesce, join strategies and windows. Ask 8 questions one at a time, score each answer 1 to 5, give a model answer in simple English and one follow-up.

CHAPTER 10

APACHE SPARK II, MAKING SPARK FAST: SHUFFLES, SKEW, BROADCAST, CACHING, AQE AND THE SPARK UI

Find the slow stage, understand why, and fix it with evidence, using the habits of a careful investigator.

Your PySpark job from Chapter 9 gives correct answers, but it takes 3 hours, and the report is due in 1 hour. Where is the time going? You may already know the method from everyday troubleshooting: measure, find the bottleneck, change one thing, measure again. In Spark the bottleneck is almost always one of four things: too much data **shuffled** across the network, one **skewed** partition that makes a single task slow, partitions that are the wrong size, or memory pressure that spills data to disk. In this chapter you will learn each one with real numbers, simulate skew and salting with code you can run, learn what Adaptive Query Execution (AQE) does for you automatically, and learn how to read the Spark UI like a delivery tracking report. By the end you will be able to take a slow job, name the bottleneck and show before and after evidence, which is exactly what interviewers ask for.

Honest note: Spark is **not installed** here, so every PySpark line and setting is **not run here**. The skew, salting and sizing simulations are real Python that we ran. Setting names are from the documented Spark 3.x configuration; defaults can change between versions, so check the docs for yours.

Running example: ShopKart's `events` table, 100,000 rows in our simulation (2 billion in real life). Half of the events carry one "hot" key (a default or null user), which makes the skew easy to see.

10.1 Shuffles and Partition Sizing

INTUITION

In the exam-marking classroom of Chapter 9, marking is fast but exchanging partial totals means every marker walks to every other marker. A shuffle is that walk. If you have 10 markers, each exchanges with 9 others. The walk costs more than the marking. So the first rule of Spark tuning is: *do fewer shuffles, and shuffle less data.*

Why a shuffle is expensive

A shuffle does five things in sequence: each map task writes its output to local disk split by target partition; the data is serialized; it travels across the network; the reduce task reads the pieces from all map tasks; it deserializes and (for joins and sorts) sorts them. So a shuffle costs disk, network, CPU and memory at once. With M map tasks and R reduce tasks, there are up to M × R small transfers.

Operation	Shuffle?	Note
`select`, `filter`, `withColumn`, `explode`	No (narrow)	Free of network
`groupBy().agg`	Yes	Partial aggregation first reduces the data
`join` (shuffle join)	Yes, both sides	Broadcast join avoids it
`distinct`, `dropDuplicates`	Yes	Same as a groupBy
`orderBy`	Yes (range partitioning)	Global sort is costly; avoid unless needed
`repartition(n)`	Yes	Full redistribution
`coalesce(n)`	No	Merges neighbours only
Window with `partitionBy`	Yes	One shuffle per distinct partitioning

How many shuffle partitions?

After a shuffle, the number of output partitions is the setting `spark.sql.shuffle.partitions`, default **200**. That number was chosen long ago, and it is wrong for most jobs: too few for big data (huge partitions, spill to disk) and too many for small data (200 tiny tasks that cost more to schedule than to run).

Rule of thumb: aim for shuffle partitions of roughly **100-200 MB** each (some teams use 128 MB), and at least 2-4 times the number of slots so that every core stays busy and stragglers are absorbed.

Problem 10.1.1 A shuffle moves 200 GB. The default 200 partitions are used. The cluster has 10 executors with 4 cores each (40 slots). Target partition size: 128 MB. Is the default good? What should the number be?

Formula	partitions = data size / target partition size; partition size = data / partitions
Plug in	200 GB = 200 × 1,024 = 204,800 MB
Compute	With 200 partitions: 204,800 / 200 = 1,024 MB each (8 times the target). Wanted: 204,800 / 128 = 1,600 partitions. Waves = ⌈1,600 / 40⌉ = 40
Answer	The default gives 1 GB partitions that probably spill to disk and run long. Use about 1,600 shuffle partitions (set `spark.sql.shuffle.partitions=1600`), which is 40 waves of 40 tasks.
Check	1,600 × 128 MB = 204,800 MB = 200 GB. ✓. And 1,600 is a multiple of 40, so the last wave is full.
Why it matters	Time can be similar in both cases, but 1 GB partitions risk spill and out-of-memory failures (10.3). Right sizing gives *safety* and *even work*. For a small shuffle (2 GB), the default 200 partitions is the opposite problem: 10 MB tasks drown in scheduling overhead, so use about 40 partitions or let AQE coalesce them.

repartition versus coalesce, and file sizes

- `df.repartition(200)` makes 200 evenly sized partitions with a full shuffle. `df.repartition(200, "customer_id")` hashes by key (same key, same partition), useful before several operations on the same key.
- `df.coalesce(20)` reduces to 20 partitions by merging, with no full shuffle. Good right before a write to avoid thousands of tiny files.
- Number of **output files** equals the number of partitions at write time (times the distinct values if you use `partitionBy` and the data is spread across partitions). Writing with 2,000 partitions into 365 daily folders can make 730,000 tiny files: the small-file problem of Chapter 3.3. Target files of 128 MB to 1 GB. Use `repartition("order_date")` before `partitionBy("order_date")` so each folder gets few files.
- **Input partitions** come from file sizes: `spark.sql.files.maxPartitionBytes` (default 128 MB). Thousands of tiny input files produce thousands of tiny tasks, so compact them first (Chapter 3.3 and the table formats of 3.4).

KEY INSIGHT

Partition count is a tuning knob with a "Goldilocks" zone. Too few: big partitions, spill, low parallelism. Too many: scheduling overhead, tiny files. Aim for 100-200 MB partitions and 2-4 times the slots.

Predicate and column pruning, and reading the plan

`df.explain()` prints the physical plan. `df.explain("formatted")` is easier to read (not run here). Read it **bottom to top**: the scan is at the bottom. Look for:

- `PushedFilters: [...]` on the Parquet scan: the filter was pushed to the file reader (predicate pushdown).
- `ReadSchema: struct<order_id,amount>` : only needed columns are read (column pruning). If it lists every column, you probably wrote `select("*")` or used a UDF that needs the whole row.
- `Exchange` : a shuffle. Count them: each is a stage boundary.
- `BroadcastHashJoin` versus `SortMergeJoin` : the join strategy.
- `HashAggregate` appearing twice around an `Exchange` : partial and final aggregation, as in our hand example in 9.2.

Connection to the real job

"How many shuffles does this job have and can you remove one?" is the first question in any Spark review. You answer by reading `explain()` and counting `Exchange` lines.

Applications

- **Data Engineering:** right-size shuffle partitions per job; compact input files; control output file size.
- **Machine Learning:** repartition by key before per-user feature windows so they share one shuffle.
- **Data Analytics:** fewer shuffles make ad-hoc Spark SQL faster.
- **FinOps:** each avoided shuffle shortens cluster time, which lowers the bill.

COMMON MISTAKE

Setting `spark.sql.shuffle.partitions` once for the whole cluster. Different stages and different days have different data volumes. Prefer AQE (10.2) to adapt automatically, and set a sensible base for big jobs.

Check yourself

1. What is the default of `spark.sql.shuffle.partitions` ? Answer: 200.
2. Which has no full shuffle, `repartition` or `coalesce` ? Answer: `coalesce` .
3. What does `Exchange` mean in a plan? Answer: a shuffle (data movement), which starts a new stage.

10.2 Skew, Salting, Broadcast Joins and AQE

INTUITION

Ten checkout counters, but one customer arrives with 500 items and everyone else has 5. Nine counters are free in seconds, and the whole supermarket waits for counter 10. Spark stages end when the *last* task ends, so one overloaded partition holds the whole job. That is **data skew**.

What skew looks like

Skew happens when a few key values hold a large share of the rows: a `null` or default user id, a very popular product, one huge customer, a country code "IN" in an India-heavy dataset. After the hash shuffle, all rows with the same key land in one partition.

Signs in the Spark UI (10.3): in the stage's task table, the *max* task duration is many times the *median*; one task reads far more shuffle data than the others; one executor shows heavy spill or out-of-memory.

Predict, Run, Explain: skew and salting (real, run here)

We simulate a shuffle of 100,000 events into 8 partitions by key hash. Half the events (50,000) belong to one hot key; the other 50,000 are spread over 5,000 users. Predict: what will the largest partition be compared with the mean? Then we **salt** the hot key: add a random suffix 0-7

to it (`hot#3`) so it splits into 8 sub-keys. Predict again.

```
import random, zlib, collections, statistics
random.seed(1)
P=8; N=100000
keys=["hot"]*(N//2)+[f"user{random.randint(1,5000)}" for _ in range(N//2)]
def part(k): return zlib.crc32(k.encode())%P     # deterministic hash
def sizes(ks):
    c=collections.Counter(part(k) for k in ks); return [c.get(i,0) for i
in range(P)]
s=sizes(keys); print("plain hash partition sizes:",s)
print(f"max={max(s)} mean={statistics.mean(s):.0f} max/mean=
{max(s)/statistics.mean(s):.2f}")
S=8
salted=[f"{k}#{random.randrange(S)}" if k=="hot" else k for k in keys]
s2=sizes(salted); print("salted sizes             :",s2)
print(f"max={max(s2)} mean={statistics.mean(s2):.0f} max/mean=
{max(s2)/statistics.mean(s2):.2f}")
for lab,ss in (("plain",s),("salted",s2)):
    print(f"{lab}: stage time = max partition / 10000 rows/s =
{max(ss)/10000:.2f} s  (ideal {N/P/10000:.2f} s)")
```

Real output:

```
plain hash partition sizes: [6140, 6284, 6304, 6192, 6201, 6376, 6224,
56279]
max=56279 mean=12500 max/mean=4.50
salted sizes             : [12525, 12461, 12476, 12500, 12424, 12526,
12496, 12592]
max=12592 mean=12500 max/mean=1.01
plain: stage time = max partition / 10000 rows/s = 5.63 s  (ideal 1.25 s)
salted: stage time = max partition / 10000 rows/s = 1.26 s  (ideal 1.25 s)
```

Line by line:

- `part(k)` is the hash partitioner: `crc32(key) mod 8`. The same key always gives the same partition. That is what makes joins and groupBys possible, and also what makes skew possible.
- Plain sizes: seven partitions hold about 6,200 rows each, and partition 7 holds 56,279. It got all 50,000 `hot` rows plus its normal share of about 6,279 (6,279 + 50,000 = 56,279 ✓).
- The mean is 100,000 / 8 = 12,500 rows. The max is 56,279, which is 4.50 times the mean.
- Stage time: tasks run at (assumed) 10,000 rows per second, so the stage lasts as long as

the slowest task: 56,279 / 10,000 = 5.63 s versus the ideal 12,500 / 10,000 = 1.25 s. Seven partitions finish in 0.6 s and then wait 5 seconds idle: 4.5 times slower than ideal. In a real 3-hour job, this is the whole problem.

- Salted: the hot key becomes `hot#0` to `hot#7`, which hash to different partitions. All partitions are within 12,424 to 12,592: max/mean = 1.01, and stage time 1.26 s, almost ideal. A speed-up of 5.63 / 1.26 = 4.5 times.

How to salt a groupBy and a join

Aggregation (two-step). Add a salt, aggregate on `(key, salt)`, then aggregate again on `key`:

```
# not run here
salted = df.withColumn("salt", (F.rand() * 8).cast("int"))
step1 = salted.groupBy("user_id",
"salt").agg(F.sum("amount").alias("part"))
final = step1.groupBy("user_id").agg(F.sum("part").alias("total"))
```

Step 1 spreads the hot key over 8 partitions; step 2 combines at most 8 rows per key, which is tiny. This works because `sum`, `count`, `min` and `max` can be combined (an average needs sum and count separately).

Join. The big, skewed table gets a random salt 0-7 on its key; the other table is *duplicated* 8 times, once with each salt, so every salted key finds its partner:

Problem 10.2.1 `events` (skewed, 2 billion rows) joins `users` (5,000 rows after we keep only the hot users) on `user_id`. Salting with S = 8: what is the new row count of the salted `users` side, and what happens to the events side?

Step 1	Events side: `user_id` becomes `user_id#r` with a random r in 0 to 7. The row count is unchanged (2 billion), but a hot key is now spread over 8 partitions.
Step 2	Users side: each row is copied 8 times (`user_id#0` ... `user_id#7`).
Compute	5,000 × 8 = 40,000 rows.
Answer	The events side stays at 2 billion rows; the users side grows to 40,000 rows.
Check	Each event finds exactly one match: its key and salt exist exactly once in the duplicated side, so the join result still has 2 billion rows (no fan-out).
Why it matters	The cost of salting is the duplication of the small side. Only salt the keys that are actually hot, and keep S small (8 to 32).

KEY INSIGHT

The cheapest fix for skew in a join is not salting but **removing the shuffle**: if the other side is small, broadcast it. Then the big skewed table is never redistributed by key, so there is no hot partition.

Broadcast joins

We saw in 9.3 that a broadcast join sends the small table to every executor. Our estimate for events and devices: shuffle join moves about 2 GB + 0.05 GB = 2.05 GB, broadcast moves 50 MB × 20 executors = 1.0 GB (real output of the simulation: `shuffle join moves ~ 2.05 GB; broadcast moves ~ 1.0 GB (small table copied to each of 20 executors)`). The savings grow with the size of the big side because the broadcast cost only depends on the *small* side.

```
# not run here
from pyspark.sql.functions import broadcast
out = events.join(broadcast(devices), "device_id")
spark.conf.set("spark.sql.autoBroadcastJoinThreshold", 100 * 1024 * 1024)
# 100 MB
```

Rules: `spark.sql.autoBroadcastJoinThreshold` defaults to 10 MB; Spark automatically broadcasts tables below it, based on size *estimates* (which can be wrong when statistics are missing). The broadcast table must fit in driver and executor memory. Do not broadcast something that is 5 GB.

Adaptive Query Execution (AQE)

Spark cannot know data sizes and skew before running. **AQE** (on by default in recent Spark 3.x versions; setting `spark.sql.adaptive.enabled`) re-plans at *stage boundaries*, using real statistics from the stage that just finished. It does three main things:

AQE feature	What it fixes	Setting (check docs for defaults)
Coalesce shuffle partitions	Too many small shuffle partitions: merges neighbours up to an advisory size (default about 64 MB)	`spark.sql.adaptive.coalescePartitions.enabled`, `spark.sql.adaptive.advisoryPartitionSizeInBytes`
Switch join strategy	Plan said sort-merge, but after a filter one side is tiny: converts to broadcast at runtime	built in with AQE
Skew join handling	Splits an oversized partition of one side into several sub-partitions and replicates the matching partition of the other side	`spark.sql.adaptive.skewJoin.enabled`, `skewedPartitionFactor` (default 5), `skewedPartitionThresholdInBytes` (default about 256 MB)

A partition is treated as skewed when it is both bigger than the factor times the **median** partition size and bigger than the byte threshold.

Problem 10.2.3 After a shuffle the five partitions of the left side are 100, 110, 95, 105 and 900 MB. With factor 5 and threshold 256 MB, which partitions does AQE treat as skewed? And with

2,048 MB of total shuffled data into 200 partitions, how many partitions does AQE coalesce to with a 64 MB advisory size?

Step 1	Median of (95, 100, 105, 110, 900) = 105 MB. Factor × median = 5 × 105 = 525 MB.
Step 2	900 MB is greater than 525 MB and greater than 256 MB: skewed. The others are below 525 MB: normal.
Step 3	Coalescing: 2,048 / 64 = 32.
Answer	Only the 900 MB partition is skewed; and the 200 small partitions are merged into about 32.
Check	Both conditions are required: a 400 MB partition would be above 256 MB but below 525 MB, so it would *not* be treated as skewed. This matches our real calculation: `median 105 5x 525 skewed: [900]`.
Why it matters	AQE fixes moderate skew automatically, but extreme skew (one key holding 50% of the data, as in our simulation) or skew in a groupBy still needs your manual salting.

Limits of AQE: it works only on shuffles in Spark SQL/DataFrame (not RDD code); it needs the stage to finish first; it cannot fix skew in a `groupBy` the way it handles joins; and it will not rewrite a bad algorithm.

Connection to the real job

The interview task "fix a skewed Spark join and prove the improvement" (from the skill map) is exactly 10.2: find the hot key, show max-versus-median task time in the UI before, apply broadcast or salting or AQE, show the same two numbers after.

Applications

- **Data Engineering:** skewed joins on null keys (filter nulls out first), default users, or big customers.
- **Data Analytics:** top-N dashboards over a heavy-tailed category.
- **Machine Learning:** user-level features where a few bots produce most events; detect and treat them separately.
- **Fraud and security:** a few IP addresses generate most traffic; per-IP aggregation is

naturally skewed.

COMMON MISTAKE

Not looking at the key distribution. Always run `df.groupBy("key").count().orderBy(F.desc("count")).show(10)` first. Very often the hot key is `null` or an empty string, and a one-line filter or a separate path for nulls removes the skew without any salting.

Check yourself

1. Why does skew slow the *whole* stage? Answer: the stage ends when the slowest task ends, and one task holds most of the data.
2. What is the best fix when one side of a skewed join is small? Answer: broadcast it, so the big side is not shuffled.
3. In salting a join, how many times is the small side duplicated for S = 16? Answer: 16 times.

10.3 Caching, Memory and Reading the Spark UI

INTUITION

The Spark UI is the tracking page of a parcel delivery, but for your Spark job. It tells you which stage was slow, how long each task took (min, median, max, like percentiles), how much data moved, and whether any task ran out of memory and spilled to disk. A careful engineer reads it before touching any code.

Caching and persistence

Remember from 9.2: without a cache each action recomputes everything. `df.cache()` marks the DataFrame to be kept after it is first computed, and `df.persist(level)` lets you choose where: memory only, memory and disk (the usual default for DataFrames), or disk only. The first action pays the full cost; later ones read the stored partitions.

When to cache: the same DataFrame is used by 2 or more actions or branches, and recomputing it is expensive (a big join or a UDF). When not to: used once (cache only costs memory), or it is larger than the memory available (it evicts other data or spills). Always `unpersist()` when done. Check the **Storage tab** of the UI to see what is cached and what

fraction is in memory.

Problem 10.3.1 A DataFrame costs 12 minutes to compute and feeds 4 actions. Reading it back from the cache costs 30 seconds. Time with and without a cache?

Formula	without = actions × compute; with = compute + (actions − 1) × read
Plug in	without: 4 × 12; with: 12 + 3 × 0.5
Compute	without = 48 minutes; with = 12 + 1.5 = 13.5 minutes
Answer	48 minutes drops to 13.5 minutes, a 3.6 times improvement (48 / 13.5 = 3.56).
Check	If there were only one action, with = 12 and without = 12: the cache only helps with reuse.
Why it matters	Cache is a trade of memory for time. It is the easiest optimization to apply and the easiest to misuse.

Memory model

An executor is a JVM with a heap. Spark divides the heap like this (default fractions; check your version):

```
executor memory (heap), e.g. 16,384 MB (16 GB)
 |- reserved: 300 MB                        (for Spark internals)
 |- user memory: 40% of the rest            (your data structures, UDF
objects)
 `- unified Spark memory: 60% of the rest  (spark.memory.fraction = 0.6)
      |- storage (cache)    } shared, a boundary
(spark.memory.storageFraction = 0.5)
      `- execution (shuffle, joins, sorts, aggregations) } that can move
either way
 + memoryOverhead outside the heap: max(384 MB, 10% of executor memory)
   (Python workers, off-heap, network buffers)
```

Real arithmetic (run here): unified memory = (16,384 − 300) × 0.6 = 9,650.4 MB. With 4 cores, 4 tasks run at once in that executor, so each task has about 9,650.4 / 4 = 2,412.6 MB of execution and storage memory to share. Overhead = max(384, 0.1 × 16,384) = 1,638.4 MB, so the container requested from the cluster manager is about 16,384 + 1,638 = 18,022 MB.

Settings you tune (all **not run here**): `spark.executor.memory` , `spark.executor.cores` ,

`spark.executor.instances` (or dynamic allocation), `spark.driver.memory`, `spark.executor.memoryOverhead`.

Problem 10.3.2 An executor has 8 GB (8,192 MB) heap and 4 cores. A shuffle partition of 1,024 MB (the default-200-partition case for 200 GB) is processed by each task. Does it fit?

Step 1	Unified memory = (8,192 − 300) × 0.6 = 7,892 × 0.6 = 4,735.2 MB.
Step 2	Per task with 4 concurrent tasks: 4,735.2 / 4 = 1,183.8 MB.
Step 3	A task must hold its input partition *plus* hash tables and sort buffers, which are often 1.5 to 3 times the data size in memory (deserialized Java objects are bigger than compressed Parquet). A 1,024 MB partition may need 1,500 to 3,000 MB, more than 1,183.8 MB available.
Answer	It will probably not fit: the task *spills* to disk, or fails with an out-of-memory error. Use smaller partitions (about 128 MB), fewer cores per executor, or more memory.
Check	With 128 MB partitions: even at 3 times expansion, 384 MB is less than 1,183.8 MB. ✓
Why it matters	This explains why simply increasing memory is not the first fix: partition size and concurrency matter just as much.

Spill means execution memory ran out, so Spark writes intermediate data to local disk and reads it back: slow but not fatal. **Out-of-memory (OOM)** kills the executor: the task is retried, and after several failures the job fails. **Garbage collection (GC) time** above about 10% of task time means the heap is under pressure.

Rules of thumb: about 4 to 5 cores per executor (too many cores starve each task of memory and cause HDFS or network contention); give executors enough memory for 128-256 MB partitions per core; do not broadcast huge tables; `collect()` only small results, because the driver has its own memory limit (`spark.driver.memory`).

Reading the Spark UI

The UI (web page, usually port 4040 on the driver for a live application; the History Server shows finished ones) has these tabs:

Tab	What to read	Healthy	Warning sign

Jobs	Jobs per action with duration	A few jobs	Hundreds of tiny jobs (a loop of actions)
Stages	Per stage: duration, tasks, input, shuffle read and write, spill	Task times close to each other	Max task time much more than median; large spill
Stage detail, Summary Metrics	Min, 25th, median, 75th, max for duration, input size, shuffle read	max / median under about 2	max / median above about 5 means skew
SQL / DataFrame	The plan with row counts and time per operator	Broadcast on small joins	A huge Exchange; `SortMergeJoin` with a tiny side
Storage	Cached RDDs and DataFrames, fraction cached	Expected data cached	Cached data never reused
Executors	Memory, GC time, failed tasks, shuffle, per executor	Even load	One executor with far more shuffle read, or GC above 10%

Problem 10.3.3 The Stage 7 summary shows task duration: min 4 s, 25th 6 s, median 7 s, 75th 8 s, max 190 s. There are 400 tasks, 80 slots. Diagnose and estimate the possible gain.

Step 1	max / median = 190 / 7 = 27: heavy skew (a few tasks only).
Step 2	Ideal stage time if the work were even: total work ≈ 400 × 7 s = 2,800 task-seconds, over 80 slots = 35 s. Actual stage time is at least 190 s because of the straggler.
Step 3	Check the "shuffle read size" column for the same max task: if it is far larger than the median, the cause is data skew, not a slow machine (a slow machine would show normal input size but a long time).
Answer	Data skew in a shuffle stage. Fixing it (broadcast, AQE skew join, salting, or removing null keys) could bring the stage from about 190 s toward 35 to 50 s, a 4 to 5 times gain.
Check	190 / 35 = 5.4. (The estimate is approximate because the mean task time is above the median, so the real ideal would be a bit higher.)
Why it matters	The percentile table is the same skill as reading a delivery report's 90th and 99th percentile: the tail, not the average, tells you what is wrong.

A tuning method that works

1. **Measure the baseline:** total time, and the stage that takes the most time (UI).
2. **Classify the bottleneck** for that stage: skew (max much more than median), spill (spill columns above zero), too many small tasks (thousands of tasks of under 100 ms), too few big tasks, a slow source or sink (read or write time), or a bad plan (extra shuffles, sort-merge for small joins).
3. **Change one thing**: broadcast, repartition, salting, a different shuffle partition count, caching or a fix to the query.
4. **Measure again** with the same data and compare the same numbers. Keep the before and after screenshots: they are your portfolio evidence.
5. **Stop when the job meets the SLA** (Chapter 1.4). Do not tune forever.

Connection to the real job

The capstone task "PySpark job on 10M+ rows with documented tuning (before and after Spark UI evidence)" is this method. The habits of any careful measurer (baseline, one change at a time, percentiles) apply directly.

Applications

- **Data Engineering:** meeting the nightly SLA and cutting cloud cost by finishing earlier.
- **Machine Learning:** shortening feature-generation jobs before training runs.
- **MLOps:** monitoring job duration trends and alerting on regressions after code changes.
- **FinOps:** per-job cost = cluster price per hour × hours; tuning reduces both.

COMMON MISTAKE

Tuning by guessing, or "just add more executors". More slots do not help a stage whose time is set by one skewed task (Problem 10.3.3), and more memory does not fix a bad join strategy. Diagnose first.

Check yourself

1. What does max / median far above 1 in task durations suggest? Answer: skew (or a slow node).
2. Which Spark UI tab shows cached DataFrames? Answer: Storage.
3. What is spill? Answer: execution memory ran out, so intermediate data is written to disk, which is slow.

Chapter recap

- Shuffles (disk, network, serialization) dominate Spark cost: remove them, shrink the data before them, or broadcast.
- Size shuffle partitions to about 128 MB (default 200 is often wrong) and at least 2-4 times the slots; use `coalesce` before writes and compact tiny input files.
- Skew means one partition holds far more data; the stage lasts as long as its slowest task. Our simulation: max 4.50 times the mean before salting, 1.01 after.
- Fixes in order: filter null or junk keys, broadcast the small side, rely on AQE skew join, then salt the hot key.
- AQE re-plans at runtime: coalesces small partitions, switches to broadcast, splits skewed partitions (skewed means over 5 times the median and over about 256 MB).
- Cache only data reused by several actions; unpersist afterwards.
- Executor memory is divided into reserved, user, execution and storage; partition size times concurrency must fit.

- Read the Spark UI like a delivery report: stage durations, task percentiles, shuffle size, spill and GC; follow measure, classify, change one thing, measure again.

Item	Rule or setting
Shuffle partitions	`spark.sql.shuffle.partitions`; data size / 128 MB
Broadcast threshold	`spark.sql.autoBroadcastJoinThreshold` (default 10 MB)
AQE	`spark.sql.adaptive.enabled`, `...skewJoin.enabled`, `...coalescePartitions.enabled`
Skew test	max / median task time; partition > 5 × median and > 256 MB
Salting	key#r, r in 0..S−1; duplicate the small side S times
Unified memory	(heap − 300 MB) × 0.6
Plan	`df.explain("formatted")`; count `Exchange`
Cache	`cache()` / `persist()` / `unpersist()`; check the Storage tab

Practice set

1. (easy) What does `Exchange` mean in a physical plan? **Answer:** a shuffle, and the boundary between two stages.

2. (easy) Which is better for reducing the number of output files: `repartition(1000)` or `coalesce(20)`? **Answer:** `coalesce(20)` reduces to 20 without a full shuffle (and `repartition(1000)` would increase the number).

3. A shuffle of 60 GB with a target of 128 MB per partition. How many partitions? **Answer:** 60 × 1,024 / 128 = 480.

4. 100,000 rows into 8 partitions; one partition holds 56,279. Compute max / mean. **Answer:** mean = 12,500; 56,279 / 12,500 = 4.50.

5. (what is the output?) After salting with S = 8, a hot key of 50,000 rows is split evenly. How

many rows does each sub-key hold? **Answer:** 50,000 / 8 = 6,250 (random salting gives about that).

6. (find the bug) A join of a skewed 1 TB events table to a 30 MB users table is a `SortMergeJoin` and takes 2 hours with one task running 100 minutes. **Answer:** the small side should be broadcast (30 MB is below typical thresholds; the automatic threshold is 10 MB by default). Use `broadcast(users)` or raise `autoBroadcastJoinThreshold`; this removes the shuffle and the hot partition.

7. Executor heap 32 GB (32,768 MB), 5 cores. Unified memory and memory per concurrent task? **Answer:** (32,768 − 300) × 0.6 = 32,468 × 0.6 = 19,480.8 MB; 19,480.8 / 5 = 3,896.2 MB.

8. (interview) "A Spark job is slow. Walk me through your approach." **Answer:** open the Spark UI, find the slowest stage, read the task percentile table and the shuffle and spill columns to classify it (skew, spill, too many or too few partitions, bad join), change one thing (broadcast, salting, partition count, caching), re-measure the same metrics, and document the before and after numbers.

9. (interview) "How would you handle a skewed join key?" **Answer:** first inspect the key distribution (often `null` is the hot key, so filter or handle it separately); broadcast the small side if possible; enable AQE skew join handling; if still skewed, salt the hot keys (random suffix on the big side, replicate the small side by the number of salts), and verify with the max-versus-median task times.

10. (scenario) The nightly job slows from 40 minutes to 3 hours after a new customer joined who accounts for 60% of orders, and the stage that grouped by customer shows one 150-minute task. What happened and what do you do? **Answer:** a new hot key caused skew in the groupBy. Use two-step aggregation with a salt for that key (partial sums by customer and salt, then final sum), or aggregate at a finer grain first (customer and day), confirm in the UI that max / median task time falls, and add an alert on stage-duration regression.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me why
Spark shuffles are expensive and how to size spark.sql.shuffle.partitions.
Use a 200 GB example, compute partition sizes, waves and spill risk step
by step, and compare repartition with coalesce. Then ask me 4 questions
```

one at a time and check my answers.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am learning data engineering. Topic: data skew in Spark, salting a groupBy and a join, broadcast joins and AQE skew handling. Give me a small hand-worked example with partition sizes, then 8 graded exercises with real numbers (max/mean ratio, salted row counts, broadcast bytes) and no solutions. I will paste my answers: [PASTE HERE].

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Explain Spark's memory model: reserved, user, execution and storage memory, memoryOverhead, spill, OOM and GC time. Work through a 16 GB executor with 4 cores, calculating memory per task, and show how partition size changes the risk. Then quiz me one question at a time.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am learning to read the Spark UI. Describe each tab (Jobs, Stages, SQL, Storage, Executors) and the signs of skew, spill, small tasks and bad joins. Then invent 4 stage summaries with min, median, 75th and max task times and shuffle sizes, and ask me to diagnose each one and propose a fix. Correct me with reasons.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles, and I am applying for data engineer roles. Run a mock interview on Spark performance tuning: shuffles, partitions, skew, salting, broadcast joins, AQE, caching, memory settings and reading the Spark UI. Ask 8 questions one at a time, score each answer 1 to 5, give a model answer in simple English and one follow-up question.

CHAPTER 11

STREAMING AND KAFKA

Processing events while they are still happening: event time, windows, watermarks, delivery guarantees and the Kafka log.

So far our ShopKart pipelines were batch: wait for the day to end, then process the day. But the fraud team says, "We cannot wait until tomorrow to learn that a stolen card was used 40 times in 5 minutes." The marketing team wants a live dashboard of orders per minute. For this you need **streaming**: processing each event within seconds of its birth. Streaming brings new problems that batch never had: events arrive late and out of order, machines crash halfway, and the same message may be delivered twice. In this chapter you will learn the four ideas that solve them (event time, windows, watermarks, delivery semantics), see Apache Kafka's log model with partitions and consumer groups, and compare Spark Structured Streaming and Apache Flink. You will run two simulations, so the ideas are numbers and not slogans.

Honest note: Kafka, Flink and Spark are not installed in this sandbox (the package network is blocked). Everything marked "not run here" is standard code you should test on your own machine. Every simulation shown with output was really run, using only the Python standard library. They are teaching toys, not Kafka.

11.1 Event Time, Windows and Watermarks

INTUITION

Think of a postal sorting office on the day of an election. Letters (events) carry a postmark (when they were written: **event time**), but they arrive on different days (when the office sees them: **processing time**). If you count "letters written on Monday" by the day they arrive, a Monday letter delayed to Wednesday lands in the wrong count. To count correctly you must group by the postmark. But then a hard question appears: when can you say "Monday is finished, here is the final count"? You cannot wait forever. A **watermark** is your rule: "I will wait until letters up to 2 days late, and anything later I ignore."

Words you need

Word	Plain meaning	ShopKart example
Event	One fact that happened	"order 881 placed at 10:00:05"
Event time	When the event really happened (in the data)	`order_ts` field
Processing time	When our system sees it	the clock of the stream job
Out-of-order	Arrives in a different order than it happened	a phone offline in a lift sends orders later
Window	A bucket of event time over which we aggregate	"orders per minute"
Tumbling window	Fixed size, no overlap, no gaps	[0,60), [60,120), ...
Sliding (hopping) window	Fixed size, a new one starts every *slide*; windows overlap	60 s long, every 30 s
Session window	Closes after a quiet gap with no events	one shopping visit ends after 60 s of silence
Watermark	"No event with time earlier than W will arrive any more" (a promise we choose)	max event time seen minus 2 minutes
Late data	An event whose window is already closed by the watermark	an order that shows up 5 minutes late
State	Memory the job keeps between events (counts per window)	the running count per window

Why not just use processing time?

Processing time is simple and cheap, but the answer changes if the system is slow, restarted, or replays old data. Run the job again tomorrow on the same file and you get different numbers. Event time gives the same answer for the same data, which is what the business means by "orders between 10:00 and 10:01". The price is that we must handle lateness.

Event time axis with four windows and events e1, e2, e3 placed in them

How to read the picture: the horizontal line is event time (when things happened). The boxes are windows of equal length. Each dot is an event placed by its own timestamp, not by when it arrived. An event that arrives late still goes into the old box; the question is only how long we keep the box open.

The three window types, with real numbers

Let ShopKart send order events with these event times in seconds: `5, 20, 62, 75, 130, 135, 400` . We run `/tmp/de_lab2/kafka_sim.py` (stdlib only):

```
from collections import defaultdict
ev=[5,20,62,75,130,135,400]
def tumbling(ev,w=60):
    d=defaultdict(int)
    for t in ev: d[(t//w)*w]+=1
    return dict(sorted(d.items()))
def sliding(ev,w=60,s=30):
    d={}
    for st in range(0,max(ev)+1,s):
        c=sum(1 for t in ev if st<=t<st+w)
        if c: d[st]=c
    return d
def session(ev,gap=60):
    ss=[[ev[0]]]
    for t in ev[1:]:
        if t-ss[-1][-1]<=gap: ss[-1].append(t)
        else: ss.append([t])
    return [(s[0],s[-1],len(s)) for s in ss]
print("tumbling 60:",tumbling(ev)); print("sliding 60/30:",sliding(ev));
print("session gap 60:",session(ev))
```

Before you run it, predict: how many tumbling windows will have a count, and will the event at time 400 be alone? Real output:

```
tumbling 60: {0: 2, 60: 2, 120: 2, 360: 1}
sliding 60/30: {0: 2, 30: 2, 60: 2, 90: 2, 120: 2, 360: 1, 390: 1}
session gap 60: [(5, 135, 6), (400, 400, 1)]
```

Line by line:

- Tumbling: `(t//60)*60` is integer division, which rounds the time down to the start of its minute. 5 and 20 go to window 0; 62 and 75 to window 60; 130 and 135 to window 120; 400 to window 360 (400 // 60 = 6, and 6 × 60 = 360). Windows with no events (180, 240, 300) are not printed.
- Sliding, length 60 and slide 30: a new window starts every 30 s, so one event belongs to **two** windows (length / slide = 2). Event 400 lies in [360,420) and [390,450), so it counts once in window 360 and once in window 390. (We only start windows at multiples of 30 from 0, so we do not show the window starting at -30 for the first events.)
- Session with gap 60: 5, 20, 62 (gap 42), 75, 130 (gap 55), 135: every gap is 60 or less, so it is **one** session with 6 events, from 5 to 135. Then 400 comes after a gap of 265, so a new session starts.

Problem 11.1.1 Using tumbling windows of 60 s, which window does the event at time 119 belong to, and which does 120 belong to?

Formula	window start = (t // 60) × 60, window is [start, start + 60)
Plug in	t = 119: 119 // 60 = 1, so start = 60. t = 120: 120 // 60 = 2, so start = 120.
Compute	119 is in [60,120). 120 is in [120,180).
Answer	119 goes to window 60, and 120 to window 120.
Check	Windows are closed on the left and open on the right, so the boundary second 120 belongs only to the later window. No event is in two tumbling windows.
Why it matters	Off-by-one at the window edge is the most common bug in "orders per minute" dashboards.

Problem 11.1.2 A sliding window is 10 minutes long and slides every 2 minutes. In how many windows does one event appear? A 5-minute window slides every 5 minutes: how many?

Formula	windows per event = window length / slide
Plug in	10 / 2 and 5 / 5
Compute	5 and 1
Answer	5 windows for the first one; the second is really a tumbling window, so 1.
Check	If slide equals length, windows do not overlap. That is the definition of tumbling.
Why it matters	A sliding window multiplies state and output by length / slide. A "last 24 hours, updated every second" window would be 86,400 copies of each event: a design smell. Use smaller overlap or incremental aggregation.

Watermarks: when is a window final?

The rule used by most engines:

```
watermark = (largest event time seen so far) − (allowed lateness)
a window [a, b) is final (emitted, state freed) when b ≤ watermark
an event whose window is already final is "too late": dropped (or sent to
a side output)
```

Here is a real run of `/tmp/de_lab/stream.py`: 1-minute windows, allowed lateness 120 s, ten events listed in **arrival order** (the number is event time in seconds).

```
"""Event-time tumbling window (1 min) with watermark (allowed lateness 2
min)."""
from collections import defaultdict
events=[(5,"a"),(20,"b"),(62,"c"),(58,"d"),(130,"e"),(75,"f"),(10,"g"),
(200,"h"),(125,"i"),(3,"j")]
W=60; LATE=120
counts=defaultdict(int); max_et=0; emitted={}; dropped=[]
def wstart(t): return (t//W)*W
for et,name in events:
    max_et=max(max_et,et); wm=max_et-LATE
    if wstart(et)+W<=wm:         # window already closed by watermark
        dropped.append((name,et)); print(f"event {name} t={et:3d} wm=
{wm:4d} -> DROPPED (too late)"); continue
    counts[wstart(et)]+=1
    print(f"event {name} t={et:3d} wm={wm:4d} -> window [{wstart(et)},
{wstart(et)+W}) count={counts[wstart(et)]}")
    for w in sorted(list(counts)):
        if w+W<=wm and w not in emitted: emitted[w]=counts[w]; print(f"
emit final window [{w},{w+W}) = {counts[w]}")
print("final counts:",dict(sorted(counts.items())),"dropped:",dropped)
```

Real output:

```
event a t=  5 wm=-115 -> window [0,60) count=1
event b t= 20 wm=-100 -> window [0,60) count=2
event c t= 62 wm= -58 -> window [60,120) count=1
event d t= 58 wm= -58 -> window [0,60) count=3
event e t=130 wm=  10 -> window [120,180) count=1
event f t= 75 wm=  10 -> window [60,120) count=2
event g t= 10 wm=  10 -> window [0,60) count=4
event h t=200 wm=  80 -> window [180,240) count=1
   emit final window [0,60) = 4
event i t=125 wm=  80 -> window [120,180) count=2
event j t=  3 wm=  80 -> DROPPED (too late)
final counts: {0: 4, 60: 2, 120: 2, 180: 1} dropped: [('j', 3)]
```

Walk through it. Event `d` has time 58 but arrives after `c` (62): out of order, yet it still lands in window [0,60) because the watermark is still negative. Event `g` (time 10) arrives after `e` (130), 120 seconds "behind" the newest, and is still accepted because the watermark (10) has not yet passed the end of window [0,60). Then `h` (time 200) moves the watermark to 80, which is past 60, so window [0,60) is emitted with count 4. When `j` (time 3) arrives, its window is final, so it is dropped.

Problem 11.1.3 Using the run above, what is the watermark after the event with time 200 arrives, and why is window [60,120) NOT yet final?

Formula	watermark = max event time − allowed lateness
Plug in	200 − 120
Compute	80. A window is final when its end ≤ 80. Window [60,120) ends at 120, and 120 ≤ 80 is false.
Answer	The watermark is 80, and window [60,120) stays open until the watermark reaches 120, which needs an event with time 240 or more.
Check	240 − 120 = 120, so the end 120 ≤ 120 becomes true. Matches.
Why it matters	Bigger allowed lateness means more correct counts but more waiting (higher latency) and more state in memory. It is a trade you choose, with data, by measuring how late your events really are (say, 99.9% arrive within 90 s).

Problem 11.1.4 In the same run, what would the final count of window [0,60) be if the allowed lateness were 300 s instead of 120 s? Is event `j` still dropped?

Step 1	With 300 s, watermark = 200 − 300 = −100 after `h`, and −100 after everything else. Window [0,60) ends at 60, and 60 ≤ −100 is false, so it never closes during the run.
Step 2	So `j` (time 3) is accepted into [0,60). The count goes from 4 to 5. Nothing is emitted early.
Answer	Count 5, `j` is kept, but the result for [0,60) would appear later than before.
Check	Total events: 10 and none dropped, so 5 + 2 + 2 + 1 = 10 (windows 0, 60, 120, 180). Yes: window 60 has c and f (2), window 120 has e and i (2), window 180 has h (1).
Why it matters	This is the lateness versus freshness dial. Fraud wants low latency and accepts some drops; billing wants correctness and accepts a long wait.

The picture of a late event

```
event time  ->  0        60       120      180      240
windows          [ W0 ---][ W1 ---][ W2 ---][ W3 ---]
arrival 1:  a(5) b(20)
arrival 5:                          e(130)
arrival 8:                                    h(200)  watermark = 80 -> W0
closes
arrival 10: j(3)  ---> its window W0 is closed: dropped
```

Connection to the real job

- A data engineer chooses the window type, the allowed lateness and what to do with late data: drop, send to a side output (a "late events" topic for later repair), or update the old result (an "upsert" into a table).
- The same business number is often produced twice: a fast, slightly wrong streaming number and a slow exact batch number that overwrites it (the Lambda idea from Chapter 1). Many teams keep the stream for freshness and the nightly batch as the source of truth.

Applications

- **Data Engineering:** orders per minute, clicks per session, revenue per hour with a late-data side output.
- **Fraud and risk:** card used more than 5 times in a 10-minute sliding window.
- **MLOps:** streaming features such as "average basket in last 30 minutes".
- **Observability:** request count and error rate per minute from logs; the p95 from a sliding window.

COMMON MISTAKE

Using processing time "because it is easier" and then being surprised that a restart or a backlog changes the numbers. Another: setting allowed lateness to zero, which drops every event that is even slightly out of order. Measure lateness first, then set the watermark.

COMMON MISTAKE

Forgetting that the watermark is driven by the *data*. If one partition stops sending events, the watermark may stop moving and windows never close. Real engines handle this with "idle source" settings; look for them.

Check yourself

1. A 5-minute tumbling window starts at 10:00. Which window does an event at 10:04:59 belong to? Answer: [10:00, 10:05).
2. Max event time seen is 10:20:00 and allowed lateness is 3 minutes. What is the watermark? Answer: 10:17:00.
3. Why can a session window not have a fixed size? Answer: it ends when a quiet gap appears, so its length depends on the user's behaviour.

11.2 Kafka: The Log, Partitions, Consumer Groups and Delivery Semantics

INTUITION

Picture a long notebook where every new order is written on the next line and **never erased** (until a retention time passes). Writers only add to the end. Readers each keep a bookmark (their **offset**) and read forward at their own speed. One reader being slow does not hurt another. That is the Kafka idea: a **distributed commit log**. A message queue like RabbitMQ is more like a post box: once a letter is taken out, it is gone. A log is more like a notebook: you can read it again, and many readers can read it.

Words you need

Word	Plain meaning	ShopKart example
Broker	A Kafka server that stores partitions	3 broker machines
Topic	A named stream of messages	`orders`, `clicks`
Partition	One ordered log, a slice of a topic	`orders-0`, `orders-1`, `orders-2`
Offset	The position number of a message inside a partition	message 5 of `orders-1`
Producer	Program that writes messages	the checkout service
Consumer	Program that reads messages	the fraud scorer

Consumer group	Consumers sharing the work of one topic; each partition goes to one consumer of the group	group `fraud` with 3 consumers
Committed offset	The bookmark saved by a group: "I have finished up to here"	group `fraud` is at offset 900 of `orders-1`
Lag	How far behind the end of the log a group is	end 1180 minus committed 900 = 280
Retention	How long messages are kept	7 days
Replication, ISR	Copies of each partition on other brokers; ISR is the set of copies that are in sync	factor 3
Key	A value used to choose the partition	`customer_id`

Kafka topic with three partitions, producers writing, and a consumer group reading

How to read the picture: producers on the left write into the topic `orders`. The topic is cut into three partitions, each a row of numbered boxes (the offsets). New messages are added at the right end. On the right, a consumer group `G1` reads: consumer 1 reads partition 0, consumer 2 reads partitions 1 and 2. The note at the bottom is the key rule: same key, same partition, and order is kept **only inside a partition**.

Keys, partitions and order

The producer picks the partition from the message key: `partition = hash(key) mod number_of_partitions`. Real Kafka uses a hash called murmur2; we use CRC32 as a stand-in. Seven events with three customers:

```
import zlib
P=3
def part(key): return zlib.crc32(key.encode())%P
msgs=[("u1","click"),("u2","buy"),("u1","view"),("u3","click"),
("u2","view"),("u1","buy"),("u3","buy")]
logs={0:[],1:[],2:[]}
for k,v in msgs: logs[part(k)].append((k,v))
for p in range(P): print("partition",p,logs[p])
```

Real output:

```
partition 0 [('u2', 'buy'), ('u2', 'view')]
partition 1 []
partition 2 [('u1', 'click'), ('u1', 'view'), ('u3', 'click'), ('u1',
'buy'), ('u3', 'buy')]
```

Read it: all of `u2` went to partition 0 and all of `u1` to partition 2, in the original order, so each customer's story stays in order. But partition 1 is empty and partition 2 holds 5 of 7 messages. With only 3 keys, the hash cannot balance. This is **partition skew**, the streaming cousin of the Spark data skew in Chapter 10. A key with a few huge values (a "hot key", like one giant merchant) makes one partition and one consumer the bottleneck.

Consumer groups: the scaling rule

Each partition is read by exactly one consumer of a group. So the most useful consumers in a group equals the number of partitions.

```
def assign(consumers,parts):
    a={}
    for i,p in enumerate(parts): a.setdefault(consumers[i%len(consumers)],
[]).append(p)
    return a
for n in (1,2,3,4):
    print(n,"consumers ->",assign([f"c{i+1}" for i in range(n)],[0,1,2]))
```

```
1 consumers -> {'c1': [0, 1, 2]}
2 consumers -> {'c1': [0, 2], 'c2': [1]}
3 consumers -> {'c1': [0], 'c2': [1], 'c3': [2]}
4 consumers -> {'c1': [0], 'c2': [1], 'c3': [2]}
```

The fourth consumer gets nothing. It sits idle as a standby. That is why you pick the partition count with growth in mind: you can add partitions later, but doing so changes `hash(key) mod P`, so keys move to other partitions and per-key order breaks across the change. Real Kafka also has other assignment strategies and "rebalancing" (a pause while partitions are reassigned when a consumer joins or leaves); the toy shows only the idea.

Two different groups reading the same topic are independent: the fraud group and the dashboard group each have their own offsets. This is the "publish once, many readers" power of a log.

Problem 11.2.1 A topic has 12 partitions. A consumer group has 5 consumers. How many partitions does each consumer read (as evenly as possible)? What happens with 15 consumers?

Formula	partitions per consumer = ⌈12 / 5⌉ at most, and the total must be 12
Plug in	12 = 5 × 2 + 2
Compute	2 consumers read 3 partitions, 3 consumers read 2 partitions: 2×3 + 3×2 = 12
Answer	3 or 2 partitions each. With 15 consumers, 12 read one partition each and 3 are idle.
Check	6 + 6 = 12. Max useful consumers = 12 = partitions.
Why it matters	The partition count is the ceiling on consumer parallelism. If the capacity test says you need 20 consumers, you need at least 20 partitions (Chapter 13 shows the sizing).

Problem 11.2.2 Consumer lag: end offsets of a 3-partition topic are `{0: 1200, 1: 1180, 2: 1500}` and the group's committed offsets are `{0: 1200, 1: 900, 2: 1100}`. What is the lag per partition and in total? If messages come in at 500/s but the group handles 420/s, how fast does the backlog grow?

Formula	lag = end offset − committed offset
Compute	partition 0: 0; partition 1: 280; partition 2: 400. Total 680. Growth = 500 − 420 = 80 per second, so 80 × 3600 = 288,000 messages per hour.
Answer	Total lag is 680 messages, and the backlog grows by 288,000 per hour at that gap.
Check	Real run of the same arithmetic printed `{0: 0, 1: 280, 2: 400} total 680` and `80 msg/s -> 288000 msg/hour`.
Why it matters	Lag is THE metric for consumers. A flat lag is healthy. A lag that rises every minute means arrival rate is higher than service rate: the queue is unstable (like a bank queue where customers arrive faster than the tellers can serve them: utilization above 100%, see Chapter 14).

Delivery semantics: at-most-once, at-least-once, exactly-once

A consumer reads a message, does the work, and saves its bookmark (commit). A crash can happen between the two. The order of these two steps defines the guarantee.

Guarantee	Order of steps	After a crash	Cost
At-most-once	commit, then process	message may be **lost**, never repeated	simple, loses data
At-least-once	process, then commit	message may be **repeated**, never lost	the usual default
Exactly-once (effect)	at-least-once plus an idempotent or transactional sink	result as if processed once	more design work

Simulation, with a crash while handling message 4 (messages 1 to 6):

```
def run(commit_first):
    log=list(range(1,7)); committed=0; processed=[]; crashed=False
    while committed<len(log):
        off=committed
        if commit_first:
            committed=off+1
            if off==3 and not crashed: crashed=True; continue   # crash:
message 4 lost
            processed.append(log[off])
        else:
            processed.append(log[off])
            if off==3 and not crashed: crashed=True; continue   # crash
before commit: reprocess
            committed=off+1
    return processed
print("at-most-once:",run(True)); print("at-least-once:",run(False))
sink={}
for m in run(False): sink[m]=f"row{m}"
print("idempotent sink keys:",sorted(sink),"rows:",len(sink))
```

```
at-most-once: [1, 2, 3, 5, 6]
at-least-once: [1, 2, 3, 4, 4, 5, 6]
idempotent sink keys: [1, 2, 3, 4, 5, 6] rows: 6
```

At-most-once lost message 4. At-least-once processed 4 twice. Writing by key (`sink[m] =`

`...`, the same idea as `MERGE` or "upsert" from Chapters 4 and 6) turns the duplicate into a harmless overwrite: 7 deliveries, 6 rows, each correct. That is how "exactly-once" is achieved in practice: **at-least-once delivery plus an idempotent write**. Remember the CDC replay at the end of Chapter 4: same idea.

What real Kafka adds (standard facts; behaviour details depend on version and configuration, so read the docs of your version):

- **Producer** `acks`**:** `acks=0` (do not wait), `acks=1` (leader wrote it), `acks=all` (all in-sync replicas wrote it). For no data loss use `acks=all` with replication factor 3 and `min.insync.replicas=2`.
- **Idempotent producer** (`enable.idempotence=true`): the broker drops duplicates caused by producer retries.
- **Transactions:** a producer can write to several partitions and commit consumer offsets atomically, so a read-process-write loop inside Kafka (Kafka Streams, Flink) can be exactly-once. A write to an outside database still needs an idempotent sink.
- **Retention and compaction:** by time or size, delete old segments; or *log compaction*, which keeps only the latest message per key (like a table's current state; good for "latest customer profile").
- **Replication and ISR:** each partition has one leader and followers. If the leader's machine dies, an in-sync follower becomes leader.
- **Schema Registry** with Avro or Protobuf: stores message schemas and checks compatibility, the "data contract" of Chapter 5 for streams.
- **Kafka Connect:** ready-made source and sink connectors (for example Debezium for CDC, and sinks into object storage or a warehouse). **Kafka Streams** and **ksqlDB:** stream processing as a library or in SQL.
- **KRaft:** newer Kafka clusters keep their own metadata with a Raft-based quorum and do not need ZooKeeper (the older design).
- **Alternatives:** AWS Kinesis, Azure Event Hubs, Google Pub/Sub (managed logs), Redpanda (Kafka-compatible), Pulsar (log plus queue), RabbitMQ (queue, for task distribution, not replay).

Minimal consumer code, **not run here** (library `confluent-kafka`; check your version):

```
# not run here
from confluent_kafka import Consumer
c = Consumer({"bootstrap.servers": "localhost:9092",
              "group.id": "fraud",
              "enable.auto.commit": False,
              "auto.offset.reset": "earliest"})
c.subscribe(["orders"])
while True:
    msg = c.poll(1.0)
    if msg is None or msg.error():
        continue
    upsert_to_db(msg.key(), msg.value())   # idempotent write first
    c.commit(msg)                          # then commit: at-least-once
```

Problem 11.2.3 A consumer processes a message in 4 ms of work and then commits in 1 ms. If it crashes at a random moment during one message, what fraction of crashes cause a duplicate under "process then commit"?

Formula	a duplicate occurs when the crash is after the work finished but before the commit finished
Plug in	the risky window is the commit step: 1 ms out of 5 ms total
Compute	1 / 5 = 0.2
Answer	About 20% of crashes (assuming a uniform crash time) lead to one duplicate; none lose data. Batching commits (commit every 500 messages) makes the duplicates bigger after a crash, which is why the sink must be idempotent.
Check	Under "commit then process" the risky window is the 4 ms of work: 4/5 = 80% of crashes would lose the message.
Why it matters	You can compute the cost of each guarantee instead of arguing about it.

Connection to the real job

- Kafka is the "central nervous system" between services and the data platform: app events, CDC (Debezium, Chapter 4), logs.
- You will be asked "how many partitions?", "what if a consumer is slow?", "how do you avoid duplicates?" in interviews. The answers are above.

- Think of a bank: partitions are counters (parallelism), lag is the length of the queue, and a consumer group is the team of tellers. Chapter 14 measures its capacity.

Applications

- **Data Engineering:** ingest app events to the lake, CDC from databases, fan-out to many teams.
- **MLOps:** a stream of predictions and feedback for monitoring; features computed on the stream.
- **Microservices:** event-driven integration, audit logs, outbox pattern.
- **Observability:** log and metric shipping into search and OLAP stores.

COMMON MISTAKE

Believing Kafka orders all messages of a topic. It orders only inside one partition. If you need all events of one customer in order, use `customer_id` as the key. Another mistake: too few partitions at the start, then adding more later and breaking key order.

COMMON MISTAKE

Saying "exactly-once" as if it were a switch. Say what is exactly-once: inside Kafka (transactions), or end to end (needs an idempotent or transactional sink).

Check yourself

1. Topic has 8 partitions and a group has 3 consumers. Can you speed up by adding a 9th consumer? Answer: no more than 8 consumers can work; the 9th is idle.
2. Which semantics lose data on a crash? Answer: at-most-once.
3. A group's committed offset is 5,000 and the log end is 5,350. What is the lag? Answer: 350 messages.

11.3 Processing Engines: Spark Structured Streaming, Flink and Real-Time OLAP

INTUITION

A consumer loop like the code above is a hand-made machine. For real work you need windows, state, watermarks, crash recovery and scaling already built. A **stream processing engine** is the ready-made factory. Spark Structured Streaming says "treat the stream as a table that keeps growing and write normal DataFrame code". Flink says "this is a true stream of events; each event is processed as it arrives, with state kept for you."

Spark Structured Streaming

You write the same DataFrame or SQL code as in batch (Chapters 9 and 10). Spark runs it repeatedly on **micro-batches** (small batches, often a few hundred milliseconds to some seconds), or in a continuous mode with some limits. The progress (offsets read) is saved in a **checkpoint** directory so after a crash the job continues. Windows and watermarks are declared in the query, exactly like Section 11.1. Example, **not run here** (PySpark, API checked against current docs: confirm on your version):

```
# not run here
from pyspark.sql import functions as F
orders = (spark.readStream.format("kafka")
          .option("kafka.bootstrap.servers", "broker:9092")
          .option("subscribe", "orders").load()
          .select(F.from_json(F.col("value").cast("string"),
schema).alias("o"))
          .select("o.*"))                          # columns: order_ts,
city, amount

per_minute = (orders
    .withWatermark("order_ts", "2 minutes")       # allowed lateness
    .groupBy(F.window("order_ts", "1 minute"), "city")
    .agg(F.count("*").alias("orders"), F.sum("amount").alias("revenue")))

(per_minute.writeStream
    .outputMode("append")                         # emit a window once it
is final
    .format("delta").option("checkpointLocation", "/chk/orders_per_min")
    .start("/lake/gold/orders_per_min"))
```

Line by line: `readStream` with format `kafka` makes an unbounded DataFrame. `withWatermark("order_ts", "2 minutes")` is the lateness rule from 11.1 (max event time seen minus 2 minutes). `window("order_ts","1 minute")` is the tumbling window. **Output**

modes: `append` (emit rows only when final, which needs the watermark), `update` (emit changed rows each trigger), `complete` (rewrite the whole result, only for small results). The checkpoint location is required for recovery. With a transactional or idempotent sink such as Delta, the job gives an end-to-end exactly-once effect.

Apache Flink

Flink processes each event as it arrives (low latency, often milliseconds), has first-class event time, rich keyed **state** (kept in memory or in an embedded store such as RocksDB), and periodic **checkpoints** (consistent snapshots of all state plus input positions). After a failure it restores the last checkpoint and replays from there. Its **two-phase commit** sinks can give end-to-end exactly-once. It also has flexible window and timer APIs and "CEP" (pattern detection like "login failure 5 times then success"). Flink SQL lets you write streaming SQL. Not run here:

```
-- not run here (Flink SQL; check your version's syntax)
SELECT window_start, window_end, city, COUNT(*) AS orders
FROM TABLE(TUMBLE(TABLE orders, DESCRIPTOR(order_ts), INTERVAL '1'
MINUTE))
GROUP BY window_start, window_end, city;
```

Choosing

Question	Spark Structured Streaming	Flink	Kafka Streams / ksqlDB
Typical latency	seconds (micro-batch)	milliseconds to seconds	milliseconds to seconds
Best when	team already uses Spark, batch and stream share code	very low latency, complex state, event-time logic	Kafka-to-Kafka logic inside a service
Runs as	Spark cluster or Databricks	Flink cluster, managed Flink	a normal app (a library), no cluster
Learning curve for a Spark user	small	medium	small

Rule of thumb: if "a minute of delay is fine", micro-batches or even a batch job every 5 minutes is simpler and cheaper. Streaming costs more to run and to debug: machines run all day, and bugs show up at 2 a.m. Choose streaming only for a stated freshness requirement.

Backpressure

Backpressure means a slow stage tells the fast stage before it to slow down, so memory does not blow up. In Kafka it is natural: the log holds messages while consumers lag (lag rises, memory does not). In Flink it is built into the network buffers. A rising lag with healthy CPU often points to a slow sink (a database that cannot take the writes): see the bottleneck example in Chapter 14.

Real-time OLAP and serving

Dashboards on streams need fast aggregate queries on fresh data. **Apache Pinot, Druid and ClickHouse** are columnar stores built for this: they ingest from Kafka and answer group-by queries in milliseconds over billions of rows. Compare with a warehouse (Chapter 8): the warehouse is for deep analysis with seconds-to-minutes queries and minutes of freshness; real-time OLAP is for user-facing and ops dashboards with sub-second queries.

CDC streaming to a lakehouse

CDC pipeline: database log, Debezium, Kafka, warehouse MERGE

How to read the picture: the orders database writes its own change log (WAL or binlog). Debezium reads that log and publishes each insert, update, delete as an event into Kafka. A job reads the topic and applies a `MERGE` into the lake or warehouse table. We simulated the apply step in Chapter 4: replaying events 3 and 4 again changed nothing, because upserts and deletes by key are idempotent. Chapter 13 designs the whole pipeline with numbers.

Problem 11.3.1 A Structured Streaming job uses a 1-minute window and watermark "2 minutes". Max event time seen is 12:10:30. Which window is the latest one that can be final, and which window is open but not final?

Formula	watermark = 12:10:30 − 2 min = 12:08:30; a window is final if its end ≤ watermark
Compute	window [12:08:00, 12:09:00) ends at 12:09:00, and 12:09:00 ≤ 12:08:30 is false. Window [12:07:00, 12:08:00) ends at 12:08:00 ≤ 12:08:30: true.
Answer	[12:07:00, 12:08:00) is the latest final window. [12:08:00, 12:09:00) is still open.
Check	Same arithmetic as the verified simulation: wm = 200 − 120 = 80 closed window [0,60) but not [60,120).
Why it matters	In `append` mode, a result for 12:08 is visible only after the watermark passes 12:09:00: the output is delayed by the lateness plus the window length. Tell the business this delay up front.

Problem 11.3.2 A job must produce "orders per city per minute" with at most 10 s of delay, and 1% of events arrive up to 90 s late. What do you decide?

Step 1	The two needs conflict: 10 s delay cannot wait for 90 s late events.
Step 2	Emit early results (`update` mode, a result every 10 s per window) and let them be corrected as late events arrive, with a 2-minute watermark. Send events later than that to a side topic, and let the nightly batch (Chapter 6) correct the final number.
Answer	Use update-mode output with a 2-minute watermark plus a nightly batch as the source of truth, and show the dashboard as "provisional" for the last 2 minutes.
Check	2 minutes covers the 90 s tail with margin, and the dashboard can refresh every 10 s.
Why it matters	Real streaming design is negotiating latency against correctness with measured lateness numbers.

Connection to the real job

- Streaming jobs are "always on": you need monitoring for lag, checkpoint age, state size and watermark delay, and a runbook for restart (Chapter 12).
- State grows without bound if windows never close or keys never expire: set TTLs.
- Testing streaming code: unit-test the window function with a list of events (as our simulation does), then run a small replay of real data before production.

Applications

- **Data Engineering:** Kafka to Delta/Iceberg tables with Structured Streaming; CDC apply jobs.
- **Fraud and payments:** Flink with keyed state and timers (card velocity checks).
- **ML:** online feature computation, streaming inference scoring.
- **Ad-tech and gaming:** real-time counters in Pinot or Druid.

COMMON MISTAKE

Using `complete` output mode on a large aggregation: Spark must keep and rewrite the entire result every trigger. Another: changing the query and re-using the old checkpoint directory; many changes are not compatible with old state.

COMMON MISTAKE

Choosing streaming "to be modern" when the business is happy with hourly data. Ask for the freshness requirement in minutes before you design.

Check yourself

1. Which engine usually has lower latency, Spark micro-batch or Flink? Answer: Flink.
2. What does a checkpoint store? Answer: the input positions (offsets) plus state, so the job can restart from there.
3. Name the pair that gives end-to-end exactly-once in practice. Answer: at-least-once processing plus an idempotent (or transactional) sink.

Chapter recap

- Streaming processes events within seconds; it needs event time, because processing time changes with delays and replays.
- Windows group events by time: tumbling (fixed, no overlap), sliding (overlap, one event in length/slide windows), session (gap-based).
- A watermark = max event time seen − allowed lateness. A window is final when its end ≤ watermark; later events are dropped or side-routed.
- Kafka is a partitioned, replicated, append-only log. Order exists only within a partition; the

key decides the partition.

- A consumer group shares partitions: one partition per consumer at a time, so useful consumers ≤ partitions. Lag = end offset − committed offset.
- At-most-once loses data, at-least-once repeats, exactly-once effect = at-least-once plus an idempotent sink (or transactions inside Kafka).
- Structured Streaming = micro-batches with the DataFrame API and checkpoints; Flink = true event-at-a-time with state and checkpoints; real-time OLAP (Pinot, Druid, ClickHouse) serves fresh dashboards.
- Choose streaming only for a stated freshness need; measure lateness before choosing the watermark.

Pattern	Rule
Tumbling window start	`(t // W) × W`
Windows per event (sliding)	length / slide
Watermark	max event time − allowed lateness
Window final	end ≤ watermark
Partition for a key	`hash(key) mod P`
Max useful consumers	number of partitions
Lag	end offset − committed offset
No data loss producer	`acks=all`, replication 3, `min.insync.replicas=2`
Exactly-once effect	at-least-once + idempotent write

Practice set

1. (easy) Tumbling windows of 5 minutes. Which window holds an event at 14:07:30?

Answer: [14:05, 14:10).

2. (easy) Sliding window length 30 s, slide 10 s. In how many windows does one event appear?

Answer: 30 / 10 = 3.

3. (easy) Log end offset 10,000, committed 9,400. Lag?

Answer: 600 messages.

4. (medium) Allowed lateness 90 s, max event time seen 09:30:00. What is the watermark, and is a window [09:28:00, 09:29:00) final?

Answer: Watermark 09:28:30. The window ends at 09:29:00, and 09:29:00 ≤ 09:28:30 is false, so it is not final.

5. (medium) What is the output? `session([5,20,62,75,130,135,400], gap=30)` using the function from 11.1 (gap rule: same session if the difference is at most 30).

Answer: Gaps: 15, 42, 13, 55, 5, 265. A new session starts after each gap greater than 30, so the sessions are (5, 20, 2 events), (62, 75, 2 events), (130, 135, 2 events), (400, 400, 1 event): `[(5, 20, 2), (62, 75, 2), (130, 135, 2), (400, 400, 1)]`. (We checked the gaps by hand: 20−5=15, 62−20=42, 75−62=13, 130−75=55, 135−130=5, 400−135=265.)

6. (medium, find the bug) A consumer does `commit(); process(msg)`. The team complains of missing orders after deployments. Why, and what is the fix?

Answer: It is at-most-once: a crash or restart after the commit and before the processing finishes loses the message. Process first, with an idempotent write, then commit.

7. (medium) A topic has 6 partitions. A capacity test shows one consumer handles 800 msg/s, and peak arrival is 4,000 msg/s. How many consumers are needed, and is 6 partitions enough with headroom?

Answer: 4,000 / 800 = 5 consumers just to keep up. With 6 partitions only 6 consumers can work: 6 × 800 = 4,800, only 20% headroom. Better to have 8 or more partitions (about 1.5 times: 8 × 800 = 6,400 gives 60% headroom).

8. (medium) Events: `c` (time 62) arrives, then `a` (time 5). Lateness is 0. Is `a` dropped?

Answer: Watermark = 62 − 0 = 62 after `c`; window [0,60) ends at 60 ≤ 62, so it is final, and `a` is dropped. This is why zero lateness drops anything out of order.

9. (scenario) The dashboard's "orders in the last minute" falls to zero every night at 03:00 for 10 minutes while the shop is still active. List 3 likely causes in order of how you would test them.

Answer: (1) Consumer lag: check lag at 03:00 (a nightly batch hitting the same cluster or database). (2) A partition or source going idle so the watermark stops, and windows never close. (3) A deployment or consumer-group rebalance at 03:00 (check the job restart times). Also

check time zone handling at the day boundary.

10. (interview) Explain "exactly-once" in Kafka in 4 sentences.

Answer: Delivery in a real network is at-least-once, because a retry after a missing acknowledgement can duplicate. Kafka's idempotent producer removes duplicates from producer retries, and transactions let a read-process-write loop inside Kafka commit its outputs and its consumer offsets atomically. For a sink outside Kafka, such as a database, you make the write idempotent (upsert by key) or transactional. So "exactly-once" is an effect of careful design, not a magic property of the network.

11. (interview) A hot key makes one partition get 60% of the traffic. What do you do?

Answer: First confirm with per-partition lag and bytes. Then choose a better key (for example `customer_id` instead of `merchant_id`), or add a salt to the key (`merchant_id + random 0..9`) and combine results downstream, or split the hot key into its own topic with more consumers. Salting breaks per-key ordering, so use it only if order is not required.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional moving into data roles, and English is my second language. Teach me event time versus processing time, tumbling, sliding and session windows, and watermarks. Use an online shop with events that arrive late, and real numbers in seconds. Explain step by step, then ask me 4 questions one at a time about which window an event goes into and when a window becomes final.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional moving into data roles, and I am learning data engineering. Topic: Apache Kafka topics, partitions, keys, offsets, consumer groups and lag. Use a log-as-notebook analogy. Then give me 8 graded exercises with numbers (partition choice, number of consumers, lag and backlog growth) without solutions. I will paste my answers for review: [PASTE HERE]
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Topic: delivery semantics at-most-once, at-least-
once and exactly-once in Kafka consumers, idempotent producers,
transactions and idempotent sinks. Show a crash between process and commit
with a small example, and explain why exactly-once is end-to-end design.
Then quiz me one question at a time with scenarios.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am applying for data engineer roles. Compare
Spark Structured Streaming, Apache Flink and Kafka Streams: latency,
state, checkpoints, windows, watermarks, when to choose each. Give me 5
business cases (fraud, live dashboard, CDC apply, IoT, clickstream) and
ask me to choose an engine and justify it in 3 sentences. Then critique my
answers.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am applying for data engineer roles. Run a
mock interview on streaming: event time, windows, watermarks, late data,
Kafka partitions and keys, consumer lag, rebalancing, exactly-once,
backpressure and hot keys. Ask 8 questions one at a time. After each
answer give a score from 1 to 5, a model answer in simple English, and a
follow-up. My answers: [PASTE HERE]
```

CHAPTER 12

INFRASTRUCTURE AND DATAOPS

Packaging, deploying, securing, watching and governing data pipelines like real software.

Your pipeline works on your laptop. Now it must run every night on a server that you do not touch, be changed safely by five engineers, keep its passwords secret, tell you when it breaks, not cost a fortune, and not leak customers' phone numbers. That is what this chapter is about. **DataOps** means applying the habits of software engineering (version control, automated tests, automated deployment, monitoring) to data work. By the end you will be able to put a pipeline in a Docker container, explain what Kubernetes and Terraform do, read a CI/CD file, store secrets safely, write the alerts that matter for data (freshness and volume), estimate cost, and handle personal data properly. Your performance-engineering background helps most in monitoring and cost.

Honest note: Docker, Kubernetes, Terraform, GitHub Actions and cloud tools are not available in this sandbox. Their code is labelled "not run here" and is minimal and standard; check flags against your tool version. The Python checks (masking, freshness, volume alert, cost arithmetic) were really run (`/tmp/de_lab2/ops.py`).

12.1 Docker and Kubernetes Basics

INTUITION

You cook a perfect biryani at home and give the recipe to a friend. It tastes different: other rice, other stove. A **container** is like sending a sealed lunch box with the food already cooked: the program, its libraries, and its settings travel together, so it runs the same everywhere. **Kubernetes** is the canteen manager: it decides on which table (machine) each lunch box sits, replaces a spoiled one, and adds more boxes when the queue grows.

Words you need

Word	Plain meaning	ShopKart example
Image	A read-only package: OS pieces, Python, libraries, your code	`shopkart/orders-loader:1.4.0`

Container	A running copy of an image, isolated from others	one nightly loader process
Dockerfile	The recipe to build an image	list of steps starting `FROM python:3.12-slim`
Registry	A store for images	a cloud container registry
Volume	Disk that outlives the container	Postgres data folder
Docker Compose	One file to run several containers together	Airflow + Postgres + your app on a laptop
Pod	Smallest Kubernetes unit: one or more containers together	one loader pod
Deployment	Keeps N copies of a pod running, rolls out updates	3 consumer pods
Service	A stable address in front of pods	`orders-api:8080`
Job / CronJob	A pod that runs to completion / on a schedule	nightly backfill
ConfigMap / Secret	Settings / sensitive settings given to pods	database host / password
Helm	A package manager for Kubernetes files (charts)	install Airflow with one command

A Dockerfile for a data job (not run here)

```
# not run here
FROM python:3.12-slim
WORKDIR /app
COPY requirements.txt .
RUN pip install --no-cache-dir -r requirements.txt
COPY src/ ./src/
USER 10001
CMD ["python", "-m", "src.load_orders"]
```

Line by line: `FROM` chooses a small base image. `WORKDIR` sets the folder. We copy `requirements.txt` and install **before** copying the code, because Docker caches each step: if only your code changes, the slow `pip install` layer is reused, and a rebuild takes seconds instead of minutes. `USER 10001` runs as a non-root user (safer). `CMD` is the default command.

Best practices to remember: pin versions (`pandas==2.2.2` , a specific base image tag, never `latest`), keep images small (slim base, multi-stage builds), one process per container, never put secrets in the image (anyone who can pull the image can read them), use a `.dockerignore` file, log to the standard output.

Commands (not run here):

```
# not run here
docker build -t shopkart/orders-loader:1.4.0 .
docker run --rm --env-file .env shopkart/orders-loader:1.4.0
docker compose up -d        # start all services in docker-compose.yml
docker logs -f <container>  # follow logs
```

Kubernetes in one picture

```
             kubectl apply -f deployment.yaml
                          |
                  [ API server ]  <- you talk only to this
                          |
       [ scheduler ] chooses a node for each pod
                          |
   Node A                 Node B                 Node C
 [pod consumer-1]      [pod consumer-2]      [pod consumer-3]
       ^------------ Deployment keeps 3 pods alive ---------^
 CronJob "nightly-backfill" -> creates a Job -> a pod that runs and exits
```

How to read it: you describe the **desired state** ("3 copies of this image, 500 MB memory each") in a YAML file. Kubernetes keeps comparing desired and actual state and fixes differences: a pod dies, it starts another. This "reconciliation" idea is the heart of Kubernetes.

A minimal Deployment, not run here:

```
# not run here
apiVersion: apps/v1
kind: Deployment
metadata: {name: orders-consumer}
spec:
  replicas: 3
  selector: {matchLabels: {app: orders-consumer}}
  template:
    metadata: {labels: {app: orders-consumer}}
    spec:
      containers:
        - name: consumer
          image: shopkart/orders-consumer:1.4.0
          resources:
            requests: {cpu: "500m", memory: "512Mi"}
            limits:   {cpu: "1",    memory: "1Gi"}
          envFrom:
            - secretRef: {name: orders-db-credentials}
```

`requests` is what the scheduler reserves; `limits` is the ceiling (going over the memory limit kills the pod: "OOMKilled"). `500m` means 500 millicores, half a CPU core. `replicas: 3` ties to the Kafka rule in Chapter 11: 3 consumers share the partitions.

Problem 12.1.1 Each consumer pod requests 500m CPU and 512 MiB. You run 3 replicas. How much CPU and memory does the Deployment reserve? How many nodes of 4 CPU and 16 GiB are needed, ignoring system overhead?

Formula	total = replicas × per-pod request
Plug in	CPU: 3 × 500m; memory: 3 × 512 MiB
Compute	CPU = 1,500m = 1.5 cores; memory = 1,536 MiB = 1.5 GiB. One node has 4 cores and 16 GiB, so both fit in one node.
Answer	1.5 cores and 1.5 GiB. One node is enough for capacity, but use at least 2 nodes so a node failure does not stop the service.
Check	1.5 / 4 = 37.5% of CPU, 1.5 / 16 = 9.4% of memory. CPU is the tighter resource.
Why it matters	Requests drive cost and scheduling. Too high wastes money; too low causes noisy neighbours and throttling.

Problem 12.1.2 A container limit is 1 GiB, and the job loads a 1.4 GiB CSV with pandas. What

happens, and what are two fixes?

Step 1	Memory use passes 1 GiB, so the kernel kills the process; Kubernetes shows `OOMKilled`, and the pod restarts (a crash loop).
Step 2	Fix by reading in chunks or using a columnar engine (DuckDB, Chapter 3) so memory stays low; or raise the limit after measuring the real peak.
Answer	The pod is OOMKilled; stream the data in chunks, or raise the limit based on a measured peak.
Check	Chunk size 100 MB uses about 0.1 GiB for the data plus overhead, far below 1 GiB.
Why it matters	The first Kubernetes incident of most data engineers is an OOMKill.

Connection to the real job

- Airflow, dbt runs, Kafka consumers and Spark jobs all run as containers, often on Kubernetes (Chapter 6 mentioned `KubernetesExecutor` and Argo). Managed services hide Kubernetes but the ideas stay.
- Docker Compose gives you a full practice stack (Postgres + Airflow + your loader) on a laptop: project 1 of the skill map.
- You do not need to administer clusters as a data engineer. You need to read YAML, set resources, read logs, and know what a pod restart means.

Applications

- **Data Engineering:** pipeline images, Airflow on Kubernetes, Spark on Kubernetes, Kafka Connect workers.
- **MLOps:** model-serving images, scheduled retraining Jobs, GPU node pools.
- **Capacity testing:** distributed load generators (for example k6 or Locust) as pods that you scale up for a test.

COMMON MISTAKE

Using the tag `latest` or unpinned libraries. The pipeline passes today and breaks next week because a library updated. Pin versions.

COMMON MISTAKE

Running a stateful database in a container without a volume. When the container is removed, the data is gone.

Check yourself

1. Why copy `requirements.txt` before the source code in a Dockerfile? Answer: so the slow dependency layer is cached when only code changes.
2. What does `OOMKilled` mean? Answer: the container used more memory than its limit and was killed.
3. What is the difference between a Deployment and a CronJob? Answer: a Deployment keeps pods running continuously; a CronJob starts a pod on a schedule that runs to completion.

12.2 Infrastructure as Code, CI/CD and Secrets

INTUITION

Building a cloud setup by clicking in a web console is like cooking from memory: nobody can repeat it, and nobody knows what changed. **Infrastructure as Code (IaC)** is writing the recipe down as files in Git: "one bucket, one warehouse, one queue, these permissions". You can review it, repeat it for dev and prod, and undo it. **CI/CD** is the kitchen's quality line: every change is automatically tested (Continuous Integration) and, if good, delivered (Continuous Delivery/Deployment).

Terraform

Terraform describes infrastructure in a language called HCL. Key words: **provider** (a plugin for a cloud, such as AWS, Azure, GCP, Snowflake), **resource** (a thing to create), **state** (a file where Terraform records what it created; the single most precious file), **module** (a reusable group of resources), `plan` (show what would change), `apply` (make the change), `destroy`. Not run here:

```
# not run here
terraform {
  required_providers { aws = { source = "hashicorp/aws", version = "~>
5.0" } }
  backend "s3" { bucket = "shopkart-tf-state", key = "data-
platform/terraform.tfstate", region = "ap-south-1" }
}
provider "aws" { region = "ap-south-1" }

resource "aws_s3_bucket" "raw" {
  bucket = "shopkart-raw-${var.env}"
}
resource "aws_s3_bucket_versioning" "raw" {
  bucket = aws_s3_bucket.raw.id
  versioning_configuration { status = "Enabled" }
}
```

Explanation: the `backend` keeps the state in a shared bucket (never in Git, because it can contain secrets; add locking so two people cannot apply at once). `var.env` lets the same code create `shopkart-raw-dev` and `shopkart-raw-prod`. The reference `aws_s3_bucket.raw.id` creates a dependency, so Terraform builds the bucket first.

The workflow is `terraform init`, `terraform plan`, review the plan like a code diff, then `terraform apply`. The idea behind the plan is that Terraform compares your files with the state and the real world, and prints only the difference: "1 to add, 0 to change, 0 to destroy". **Drift** means someone changed the real thing by hand, so it no longer matches the code; `plan` shows it. Alternatives (awareness): CloudFormation (AWS), Bicep (Azure), Pulumi (real programming languages), and OpenTofu (an open-source fork of Terraform).

CI/CD for data

A CI pipeline runs on each pull request. For a data repository the steps are:

1. **Lint and format** (`ruff`, `sqlfluff`).
2. **Unit tests** of Python logic (Chapter 5).
3. **DAG import test** (Chapter 6) and `dbt build` on a small slim CI schema (Chapter 7).
4. **Build the image** and scan it.
5. **Deploy** to dev automatically, to prod after approval, with a versioned release (a Git tag).

A GitHub Actions file, not run here:

```yaml
# not run here
name: ci
on: [pull_request]
jobs:
  test:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v4
      - uses: actions/setup-python@v5
        with: {python-version: "3.12"}
      - run: pip install -r requirements.txt
      - run: ruff check .
      - run: pytest -q
```

Environments: **dev** (free to break), **staging** (like prod, with a copy or sample of data), **prod**. Rules that save careers: never test against production tables; use a separate schema per pull request; promote the same built image from dev to prod instead of rebuilding; keep a way to roll back (previous image tag, `git revert`, table time travel from Chapter 3).

Git workflow: short-lived branches, pull requests with review, `main` always deployable, commit messages that say why.

Secrets, IAM and networking

A **secret** is a password, API key or token. Rules:

- Never in Git, never in an image, never in a screenshot or a chat. Use a **secret manager** (HashiCorp Vault, AWS Secrets Manager, Azure Key Vault, GCP Secret Manager). Applications read them at runtime; Kubernetes `Secret` objects are only base64-encoded by default (not encrypted) unless the cluster adds encryption or an external secrets tool.
- **Least privilege:** give each job only the permissions it needs. The loader may write to `raw/` and nothing else. An **IAM role** (identity and access management) attached to the workload is better than long-lived keys, because there is nothing to leak.
- **Rotate** secrets on a schedule and after any suspected leak. Scan Git history with a secret scanner in CI.
- **Networking basics:** a **VPC** is your private network in the cloud; **subnets** split it (public vs private); **security groups** are firewall rules; **private endpoints** let a service reach the warehouse or storage without crossing the public internet. Databases should live in private subnets.

Problem 12.2.1 A `terraform plan` prints "Plan: 2 to add, 1 to change, 1 to destroy." The destroy is `aws_s3_bucket.raw`. What do you do?

Step 1	Stop. A destroy on a raw bucket may delete data permanently.
Step 2	Find why: a renamed resource (Terraform sees "old removed, new added") or a changed argument that forces replacement. Use `terraform state mv` or `moved` blocks for a rename. Turn on `prevent_destroy` and bucket versioning for important data.
Answer	Do not apply until the destroy is explained and prevented; plan review is the safety net.
Check	After the fix the plan should say "0 to destroy" for the bucket.
Why it matters	`apply` without reading the plan is how production data gets deleted.

Problem 12.2.2 A secret was committed to Git and removed in the next commit. Is it safe?

Step 1	Git keeps history, so the secret is still readable in the old commit, in forks and in clones.
Step 2	Treat the secret as leaked: revoke and rotate it first. Rewriting history is secondary.
Answer	Not safe. Rotate immediately, then clean up and add a pre-commit scanner.
Check	After rotating, the old value is useless, even if someone copied it.
Why it matters	Speed matters: bots scan public repositories within minutes.

Connection to the real job

- A data platform team writes Terraform for buckets, warehouses, roles, Kafka topics and Airflow; you may only edit a module's variables, but you must read the plan.
- A pull request that changes a SQL model should run tests automatically and block merge on failure. That is the DataOps promise.

Applications

- **Data Engineering:** reproducible dev, stage and prod platforms; dbt in CI; DAG deployment.
- **MLOps:** pipelines that test, build and deploy models; infrastructure for training and serving.
- **Security:** least privilege roles per pipeline; audit trails from Git history.

COMMON MISTAKE

Editing cloud resources in the console "just once". The code and reality drift apart, and the next `apply` undoes your fix or breaks something.

COMMON MISTAKE

Committing the Terraform state file or a `.env` file. Add them to `.gitignore` on day one.

Check yourself

1. What is Terraform state for? Answer: it records which real resources Terraform created, so it can compute the difference to your code.
2. Name three CI steps for a data repository. Answer: lint, unit tests, DAG import test (or dbt build on a CI schema).
3. Why is an IAM role better than an access key stored in a file? Answer: nothing long-lived exists to leak or rotate by hand.

12.3 Monitoring, Alerting, Runbooks and Cost

INTUITION

A car dashboard has a few lights, not a thousand. It shows speed, fuel and engine warning. A data pipeline can "succeed" (exit code 0) and still be wrong: yesterday's data is missing, or half the rows are gone. So besides "did it run?" we watch "is the data fresh?" and "is the volume normal?". In a restaurant it is the difference between "the kitchen sent out a plate" and "the plate was correct and hot".

The four signals for pipelines

Signal	Question	Example rule	Where from

Freshness	How old is the newest data?	newest order older than 2 h = alert	`MAX(order_ts)` in the table
Volume	Is the row count normal?	today below 3 standard deviations of the last 7 days	row counts per load
Quality	Do the checks pass?	null rate, duplicates (Chapter 5)	test results
Health and cost	Did jobs run, how long, how much did they use?	runtime above 2 x the median; lag rising	scheduler, Prometheus, billing

Plus the classic **logs, metrics, traces** (the three pillars of observability). Metrics are numbers over time (Prometheus stores them, Grafana draws them). Logs are event lines (the ELK/OpenSearch stack stores them; use structured JSON logs). Traces follow one request across services (OpenTelemetry is the common standard). Cloud equivalents: CloudWatch, Azure Monitor, Cloud Monitoring. Application performance tools (Dynatrace, AppDynamics, Datadog) are familiar to you.

Worked checks (real run)

```
import datetime, statistics as st
now=datetime.datetime(2026,1,10,9,0)
last=datetime.datetime(2026,1,10,6,30); sla=datetime.timedelta(hours=2)
print("freshness lag:",now-last,"breach:",now-last>sla)
hist=[10200,9900,10100,10050,9950,10150,10000]; today=6100
m=st.mean(hist); s=st.stdev(hist); z=(today-m)/s
print(f"volume mean={m:.0f} sd={s:.1f} today={today} z={z:.1f} alert=
{abs(z)>3}")
```

Real output:

```
freshness lag: 2:30:00 breach: True
volume mean=10050 sd=108.0 today=6100 z=-36.6 alert=True
```

Read it: the newest data is 2 h 30 min old and the SLA is 2 h, so alert. The last 7 days average 10,050 rows with a standard deviation of 108 (`stdev` is the sample standard deviation). Today's 6,100 is 36.6 standard deviations below the mean: `z = (x - mean) / sd = (6100`

`- 10050) / 108 = -36.6` . A value beyond 3 is already rare, so this is a certain alert (most likely a partial load). A caveat: a weekly pattern (weekends are lower) breaks this simple rule. Compare Sunday with other Sundays, or use a forecast (Chapter 14).

Problem 12.3.1 The nightly job normally lands 10,000 rows, with standard deviation 150. Tonight it lands 9,700. Do you alert at the 3-sigma rule?

Formula	z = (x − mean) / sd
Plug in	(9700 − 10000) / 150
Compute	−300 / 150 = −2
Answer	z = −2, which is inside 3 sigma: no alert, but worth a note on a trend chart. A 6% drop is small for random noise at this spread.
Check	3 sigma would be 450 rows, so the alert line is 9,550 rows.
Why it matters	Alerts that fire on normal noise cause **alert fatigue**: people stop reading them. Set thresholds from real history.

Problem 12.3.2 An alert fires 12 times a day, and 11 are ignored. How do you improve it?

Step 1	Count real incidents versus alerts: precision = 1 / 12 = 8%.
Step 2	Page only on user-visible problems (freshness SLA at risk), send the rest to a channel or a daily digest, add a "for 10 minutes" delay to ignore blips, group duplicates, and link a runbook in every alert.
Answer	Raise precision by alerting on symptoms (data late, data wrong), not causes (CPU 80%), with a delay and a runbook link.
Check	If 11 noisy alerts move to the digest, pages drop from 12 to 1 per day with the same real incident caught.
Why it matters	On-call quality depends on alert quality.

Runbooks, on-call and postmortems

A **runbook** is a short page per alert: what it means, how to check, how to fix, who to ask. An **SLA/SLO** (service level agreement/objective) is the promise, for example "the orders table is

fresh within 2 hours, 99% of days". After an incident write a **blameless postmortem**: timeline, cause, what detected it, what fixes will prevent it. It asks "how did the system allow this?", not "who did this?".

Cost

Cloud cost has three parts: compute (machines, warehouse credits, Spark), storage, and data movement (leaving a region or cloud). **FinOps** is the habit of watching and managing it. Prices change often, so do not memorize them. The method is stable:

```
tb_scanned=2.5; price=6.25  # illustrative price per TB scanned, NOT a
quote
print("query cost:",tb_scanned*price,"per run; 30
runs:",tb_scanned*price*30)
with_part=tb_scanned*0.1; print("after partition pruning (10%
scanned):",with_part*price*30)
```

```
query cost: 15.625 per run; 30 runs: 468.75
after partition pruning (10% scanned): 46.875
```

The price per TB here is made-up. The lesson is the multiplication: cost = bytes scanned × price × runs, so reading 10% of the data (partition pruning, Chapter 3) cuts the bill by 90%. Other levers: auto-suspend warehouses; right-size clusters; use spot or preemptible instances for fault-tolerant batch jobs; use cheaper storage tiers for cold data; delete temp tables; set budgets and alerts; tag every resource with team and project so costs can be assigned; track **cost per run** and **cost per 1,000 events** as pipeline metrics.

Problem 12.3.3 A daily job uses a cluster of 8 workers at an illustrative 0.40 per worker-hour for 1.5 hours. What is the monthly cost (30 days), and what if spot instances give a 60% discount?

Formula	cost = workers × price × hours × days
Plug in	8 × 0.40 × 1.5 × 30
Compute	8 × 0.40 = 3.20; 3.20 × 1.5 = 4.80 per day; 4.80 × 30 = 144.00. With the discount: 144 × (1 − 0.60) = 57.60.
Answer	144 per month on demand, 57.60 with spot. (Prices here are made-up for the arithmetic.)
Check	144 × 0.4 = 57.6. Yes.
Why it matters	Spot nodes can disappear mid-job, so use them only if tasks are retried safely (idempotent, Chapter 6).

Connection to the real job

- Freshness and volume alerts are the first thing a new data team adds after an angry stakeholder phone call.
- Cost reviews are monthly meetings in real companies; a candidate who can say "I cut the daily job from 2.5 TB scanned to 0.25 TB" is remembered.
- Pipeline monitoring tools: Airflow SLAs and callbacks, dbt source freshness, Great Expectations/Soda checks, data observability tools (Monte Carlo, Elementary), and your own SQL checks.

Applications

- **Data Engineering:** freshness and volume monitors, DLQ size alerts, lag dashboards.
- **MLOps:** model latency, data drift and prediction distribution monitoring.
- **AIOps (your niche):** anomaly detection on metrics, alert noise reduction.

COMMON MISTAKE

Alerting on "job failed" only. The job that succeeds with zero rows is the dangerous one.

COMMON MISTAKE

Averages in dashboards. Track percentiles (p95, p99) for durations, the way a train operator reports "95% of trains within 5 minutes of the timetable".

Check yourself

1. Name two data-specific alerts that are not about job failure. Answer: freshness and volume (also quality check failures).
2. What does 3-sigma mean as an alert rule? Answer: alert when a value is more than 3 standard deviations from the mean of recent history.
3. Why tag cloud resources? Answer: to assign cost to teams and projects.

12.4 Governance, Privacy, PII, Lineage and Catalogs

INTUITION

A library has books everybody may read, a reference section where books stay inside, and a locked room with rare manuscripts. It also has a catalogue to find books and a record of who borrowed what. **Data governance** is the same for data: who may see what, what each dataset means, where it came from, and how long we keep it.

Words you need

Word	Plain meaning	ShopKart example
PII	Personally identifiable information: data that can identify a person	name, phone, email, address, Aadhaar-like ID
Sensitive data	PII plus data that can harm if leaked	health, finances, passwords
Masking	Hide part of a value	`98******10`
Pseudonymization	Replace an identifier with a token; a key or table can reverse it	`tok_e841b43a3067` for an email
Anonymization	Irreversibly remove the link to a person (hard to do properly)	aggregated counts only
Encryption at rest	Data scrambled on disk / on the	encrypted bucket; HTTPS to the

/ in transit	network (TLS)	warehouse
Row / column level security	Rules that hide some rows or columns by user role	regional managers see only their region; analysts do not see phone
Retention	How long data is kept, then deleted	3 years for orders
Data catalog	A searchable inventory of datasets, owners, descriptions	DataHub, Amundsen, Unity Catalog, cloud-native catalogs
Lineage	The map of where data came from and what depends on it	`raw.orders` to `stg_orders` to `fct_orders` to the revenue dashboard

Masking and pseudonymizing (real run)

```
import hashlib
phone="9876543210"; email="asha.rao@example.com"
print("masked phone:",phone[:2]+"*"*6+phone[-2:])
user,dom=email.split("@"); print("masked email:",user[0]+"***@"+dom)
salt="demo-salt-not-a-secret"
tok=lambda s: hashlib.sha256((salt+s).encode()).hexdigest()[:12]
print("token:",tok(email),"same input same token:",tok(email)==tok(email))
```

```
masked phone: 98******10
masked email: a***@example.com
token: e841b43a3067 same input same token: True
```

Read it: masking keeps the shape for support staff. The token is a salted hash: the same email always gives the same token, so analysts can still count unique customers and join tables, without seeing the email. Important limits: a hash of a low-entropy value (a 10-digit phone number has only 10 billion possibilities) can be reversed by trying all values, so use a secret key (an HMAC) kept in a secret manager, or a token vault, and never publish the salt. The salt in the demo is fake. Pseudonymized data is **still personal data** under most laws, because it can be re-linked.

Law and policy, at awareness level

India's **DPDP Act 2023** (Digital Personal Data Protection) and the **GDPR** (Europe) give people rights over their data and put duties on companies: collect only what you need (**data minimization**), state the purpose, get consent where needed, keep it secure, delete it when the purpose ends, report breaches, and honour requests to access or erase data. Details and rules change; ask your company's privacy team and do not rely on a textbook for legal advice. For engineers, the practical consequences are:

- Know where PII lives: tag columns in the catalog (`pii: true`).
- Separate PII from analytics tables; join through tokens.
- Make **deletion** possible: a person's data may be in the lake, backups, ML training sets and logs. Table formats with row-level delete (Delta, Iceberg, Chapter 3) help.
- Limit access with roles; review access every quarter ("access reviews"); log who read sensitive tables.
- Data localization: some data must stay in a country; choose the cloud region on purpose.

Problem 12.4.1 The orders table has columns: `order_id` , `customer_name` , `phone` , `email` , `city` , `amount` , `order_ts` . Classify each as PII or not, and say what an analyst's view should show.

Step 1	Direct identifiers: `customer_name` , `phone` , `email` . These identify a person alone.
Step 2	`city` alone is not identifying, but combined with other fields it can be (quasi-identifier). `order_id` , `amount` , `order_ts` are business data, though `order_id` can link back to a person through other tables.
Answer	PII: name, phone, email. The analyst view drops them or replaces email with a token, and keeps `city` , `amount` , `order_ts` .
Check	The analyst can still count unique customers via the token and compute revenue by city: the business question is answered without PII.
Why it matters	Designing the safe view first is cheaper than cleaning a leak later.

Problem 12.4.2 Policy: delete order rows older than 3 years. Today is 2026-01-10. What is the cutoff date, and how would you do it safely in a pipeline?

Formula	cutoff = today minus 3 years
Compute	2023-01-10 (the real run printed `cutoff 2023-01-10`)
Answer	Delete rows with `order_ts` before 2023-01-10, run as a scheduled, logged, idempotent job (a partition drop for date-partitioned tables is cheapest), and first count the rows to be deleted and compare with an expectation.
Check	Re-running the delete deletes nothing new: idempotent.
Why it matters	Retention is a legal duty and also cuts storage cost.

Lineage and catalogs

Lineage answers two questions that everyone asks: "this dashboard number looks wrong, where does it come from?" (upstream) and "if I change this column, what breaks?" (downstream, called **impact analysis**). Sources: dbt's `ref` graph (Chapter 7), Airflow with **OpenLineage**, and warehouse query logs. A **catalog** holds descriptions, owners, tags (PII), quality status and usage. A good catalog makes "ask the one person who knows" unnecessary. **Data contracts** (Chapter 5) and **data products** (a dataset with an owner, a promise and documentation) connect with catalogs. Governance does not mean saying no; it means making the safe path the easy path.

Connection to the real job

- Every company with customers has a privacy review for new pipelines. You will be asked "does this table contain PII, and who can read it?".
- Warehouse features to know by name: column masking policies, row access policies, and role-based access control (Chapter 8).
- Incident: a column with email addresses was copied to a public bucket. The fixes combine this chapter: least privilege, catalog tags, scanner in CI, encryption, alert on public buckets.

Applications

- **Data Engineering:** masked views, tokenization, retention jobs, lineage in the catalog.
- **Data Science and ML:** training on pseudonymized data; deleting a person's data from feature stores.
- **GenAI:** do not send PII to external AI services; redact before prompts.

- **BFSI and healthcare:** strict regulation (RBI, health data rules), audit logs.

COMMON MISTAKE

Calling hashed emails "anonymous". They are pseudonymous, and they can be reversed by guessing or linked by matching.

COMMON MISTAKE

Protecting the warehouse and forgetting logs, backups, notebooks and exports where the same PII was copied.

Check yourself

1. Is a masked phone number the same as an anonymized one? Answer: no; masking hides display, and other copies of the data may still exist; anonymization must remove the link permanently.
2. What is impact analysis? Answer: finding all downstream tables and dashboards that depend on a column before you change it.
3. Give one reason to separate PII from analytics tables. Answer: fewer people need access to PII, and deletion requests touch only one place.

Chapter recap

- Containers package code and dependencies; Docker builds images; pin versions, keep secrets out, run as non-root, and order Dockerfile steps for caching.
- Kubernetes keeps the desired state: Deployments for always-on consumers, CronJobs for schedules; set resource requests and limits; OOMKilled means memory limit exceeded.
- Terraform writes infrastructure as code; read the plan before apply; the state file is precious; avoid console edits (drift).
- CI/CD: lint, test, import-test, build, deploy through dev, staging and prod; promote the same image; keep rollback ready.
- Secrets live in a secret manager, never in Git or images; use least privilege IAM roles; rotate after leaks.
- Monitor freshness, volume, quality and health, not only job success; use thresholds from history; fight alert fatigue; keep runbooks and blameless postmortems.

- Cost = quantity × price × runs; reduce bytes scanned and idle compute; tag resources; track cost per run.
- Governance: classify PII, mask and tokenize, support deletion and retention, restrict access, and keep lineage and a catalog.

Item	Rule or command
Build / run image	`docker build -t name:tag .` / `docker run --rm name:tag`
Kubernetes resources	`requests` (reserved), `limits` (ceiling); `500m` = 0.5 core
Terraform flow	`init`, `plan`, review, `apply`
Alert z-score	`z = (x - mean) / sd`, alert if `
Freshness alert	`now - MAX(event_ts) > SLA`
Cost	`bytes scanned × price per byte × runs`
Pseudonymize	HMAC with a secret key, not a bare hash
Retention cutoff	`today - retention period`

Practice set

1. (easy) A pod requests 250m CPU and runs 8 replicas. How many cores are reserved?

Answer: 8 × 250m = 2,000m = 2 cores.

2. (easy) Which Docker line gives better caching: `COPY . .` then `pip install`, or `COPY requirements.txt .`, `pip install`, then `COPY . .`?

Answer: The second one; dependencies are reinstalled only when `requirements.txt` changes.

3. (easy) Is it safe to put the database password in the Dockerfile as `ENV DB_PASS=...`?

Answer: No. It is stored in the image layers and visible to anyone who can pull the image. Inject it at run time from a secret manager.

4. (medium) History: 9,900, 10,100, 10,000, 10,000, 10,000 (mean 10,000, standard deviation about 70.7). Today 9,700. z-score, and alert at 3-sigma?

Answer: The sample standard deviation: squared differences 10,000 + 10,000 each (100^2 = 10,000 twice) and 0 three times: sum 20,000, divided by 4 = 5,000, square root 70.7. z = −300 / 70.7 = −4.2, beyond 3: alert. (Computed by hand: 300/70.7 = 4.24.)

Note: with small samples the standard deviation is unreliable; use at least 14 to 30 days of history.

5. (medium) Freshness SLA is 2 hours. The newest row is from 07:10 and it is now 09:15. Alert?

Answer: Lag is 2 h 5 min, above 2 h: yes, alert.

6. (medium, find the bug) A Terraform user hardcodes the AWS access key in `main.tf` and commits it. List what is wrong and the fix order.

Answer: Secret in Git. Fix order: revoke and rotate the key; switch to IAM roles or environment-provided credentials; remove it from the code; add a secret scanner in CI.

7. (medium) A job reads 4 TB per run, 20 runs a month, at an illustrative 5 per TB. Partitioning lets it read 0.5 TB. Savings per month?

Answer: Before: 4 × 5 × 20 = 400. After: 0.5 × 5 × 20 = 50. Savings = 350 (87.5%).

8. (medium) A container with a 512 MiB limit is OOMKilled every night at 02:00, when a 600 MB file arrives. Give two fixes.

Answer: Process the file in chunks or with a streaming/columnar reader so memory stays small; or raise the limit above the measured peak (for example 1 GiB). The first is better because the file will grow.

9. (hard, scenario) A new engineer joins and needs access to `orders` including phone numbers for a one-time analysis. What is a good process?

Answer: Ask for the business purpose; give access to the masked or tokenized view first; if phone is really needed, time-boxed, role-based access with approval and logging, and remove it afterwards; record it in the access review.

10. (interview) Explain the difference between CI and CD in a data team.

Answer: CI means every change is automatically linted and tested (unit tests, DAG import, dbt build on a CI schema) before merge. CD means a change that passed is automatically released to dev, and to prod after approval, as a versioned artifact with a rollback path.

11. (interview) Your pipeline succeeded but the dashboard is empty. What monitoring would have caught it?

Answer: A volume check (row count versus history), a freshness check on the final table, and a not-null/row-count test in the pipeline. Job-status monitoring alone cannot see a "successful" empty load.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me Docker
for data pipelines: images, Dockerfile layers and caching, volumes,
Compose, and best practices. Use a small Python loader as the example.
Then give me 6 graded exercises (including a Dockerfile with 3 bugs to
find) without solutions, and I will paste my answers: [PASTE HERE]
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Explain
Kubernetes basics for a data engineer: pod, Deployment, Service, Job,
CronJob, ConfigMap, Secret, resource requests and limits, OOMKilled, Helm.
Use a canteen-manager analogy and a Kafka consumer Deployment as the
example. Then quiz me one question at a time on reading a YAML file.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Topic: Terraform and CI/CD for a data platform:
providers, state, plan and apply, modules, drift, GitHub Actions steps for
dbt and Python repos, dev/stage/prod, rollback. Give me a realistic
scenario with a dangerous plan output and ask me what I would do. Then
critique my answer.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am applying for data engineer roles. Teach
me monitoring and alerting for data pipelines: freshness, volume, quality,
runbooks, SLAs and SLOs, alert fatigue, blameless postmortems, and FinOps
cost per run. Use real numbers and z-scores. Then give me 8 exercises with
numbers, one at a time, and check my answers.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am applying for data engineer roles in
India. Teach me data governance basics: PII classification, masking versus
pseudonymization versus anonymization, retention, row and column security,
lineage, catalogs, and the main ideas of DPDP and GDPR (awareness only).
Then run a mock interview with 6 questions, one at a time, with a score, a
model answer and a follow-up after each. My answers: [PASTE HERE]
```

CHAPTER 13

SYSTEM DESIGN FOR DATA

A repeatable method for designing data platforms on a whiteboard, with real capacity numbers and six worked designs.

In a data engineering interview, and later at work, someone says: "We have 5 million app users. Design the platform for clickstream analytics." There is no code to write. They want to hear how you think: what you ask, what numbers you estimate, which boxes you draw, what breaks and what it costs. Beginners jump straight to "Kafka plus Spark plus a warehouse" without numbers. Strong candidates first ask questions, then compute events per second and storage, and only then choose tools that fit those numbers. This chapter gives you a framework, a short method for back-of-the-envelope capacity estimation (the arithmetic you can do in your head or on paper), and six full designs. Your performance-engineering habit of "what is the load, where is the bottleneck?" is exactly the skill being tested.

The numbers below come from real runs of small scripts (`/tmp/de_lab/capacity.py` and `/tmp/de_lab2/design.py`). The tools named (Kafka, Flink, Spark, warehouses) are not run here; this chapter is about decisions. Every input number (users, bytes per event) is an assumption you must state out loud in an interview, then check with the interviewer.

13.1 The Design Framework and Capacity Estimation

INTUITION

An architect asked to "design a building" first asks how many people, how many floors, what budget, what the soil is like. Only then does she draw. The same holds for data: the right design for 100 events per second is a single database; for 100,000 per second it is a distributed log. The numbers choose the design.

The framework (nine steps)

Say this order out loud; it keeps you calm and organised.

1. **Requirements.** Ask: who uses the output and for what decision? **Volume** (events per day), **velocity** (peak per second), **latency or freshness** (seconds, minutes, hours), **consistency** (can numbers be slightly wrong or late?), **SLA**, **retention**, **budget**, **privacy**.

2. **Estimate capacity.** Events/s, MB/s, GB per day, TB per year, partitions, machines.
3. **Data model.** Grain, key entities, schema (Chapter 2); event schema and contract (Chapter 5).
4. **Ingestion.** Batch, stream, CDC, API (Chapters 4 and 11).
5. **Storage.** Lake, warehouse, lakehouse, hot store, formats and partitioning (Chapters 1 and 3).
6. **Processing.** Batch (Spark, dbt) or stream (Flink, Structured Streaming); windows and late data.
7. **Serving.** Dashboards, APIs, feature store, reverse ETL.
8. **Quality, monitoring, governance.** Tests, freshness and volume alerts, PII, lineage (Chapters 5 and 12).
9. **Failure modes, scaling and cost.** What if a component dies, traffic doubles, data arrives twice or late? What does it cost per month?

Words you need

Word	Plain meaning	Example
Peak factor	Peak rate divided by average rate	evening traffic is 3 times the day average
Headroom	Spare capacity above the peak	plan for 1.5 times peak
Replication factor	Copies of data kept for safety	Kafka x3
Compression ratio	Raw size divided by stored size	Parquet is about 5 times smaller than raw JSON (varies a lot with data)
Hot / warm / cold storage	Fast and expensive / medium / slow and cheap	30 days hot, 1 year cold
Write amplification	Extra bytes written because of indexes or copies	search index 1.3 times raw

Useful constants

- Seconds in a day: 86,400 (use 100,000 for a quick estimate and say so).
- 1 million events per day is about 12 events per second on average (1,000,000 / 86,400 = 11.6).
- 1 KB x 1 million = 1 GB. 1 GB x 1,000 = 1 TB.
- Peak = average x peak factor (2 to 5 for consumer apps; 10 or more for sale events).

The estimation recipe, run on real numbers

ShopKart has 5 million daily users, each producing 40 click events per day, each event about 1,000 bytes of JSON. Our script `capacity.py` does this arithmetic:

```
def est(name, users, events_per_user_day, bytes_per_event, peak_factor=3,
repl=3, retention_days=7):
    ev_day=users*events_per_user_day; avg=ev_day/86400;
peak=avg*peak_factor
    gb_day=ev_day*bytes_per_event/1e9; mb_s_peak=peak*bytes_per_event/1e6
    kafka_tb=gb_day*retention_days*repl/1000
    print(f"{name}: events/day={ev_day:,.0f} avg={avg:,.0f}/s peak=
{peak:,.0f}/s raw={gb_day:,.1f} GB/day peak={mb_s_peak:,.1f} MB/s
kafka({retention_days}d,x{repl})={kafka_tb:,.2f} TB")
    return peak, mb_s_peak
p,m=est("clickstream",5_000_000,40,1000)
```

Real output:

```
clickstream: events/day=200,000,000 avg=2,315/s peak=6,944/s raw=200.0
GB/day peak=6.9 MB/s kafka(7d,x3)=4.20 TB
```

Problem 13.1.1 Do the clickstream numbers by hand.

Formula	events/day = users × events per user; average rate = events/day / 86,400; peak = average × peak factor
Plug in	5,000,000 × 40 = 200,000,000; 200,000,000 / 86,400
Compute	200,000,000 / 86,400 = 2,314.8, about 2,315 per second. Peak = 2,315 × 3 = 6,944 per second. Raw size per day = 200,000,000 × 1,000 bytes = 200 GB. Peak bandwidth = 6,944 × 1,000 bytes = 6.9 MB/s. Kafka storage = 200 GB × 7 days × 3 copies = 4,200 GB = 4.2 TB.
Answer	About 2.3 thousand events/s on average, 6.9 thousand at peak, 200 GB per day raw, and 4.2 TB of Kafka disk for 7 days with 3 copies.
Check	The script printed the same values. Sanity: 200 million events is about 12 x 200 = 2,400 per second by the rule of thumb. Yes.
Why it matters	6.9 thousand events per second and 6.9 MB/s is small for Kafka. A single modest cluster handles it. The numbers told us not to over-build.

Problem 13.1.2 How many Kafka partitions? A capacity test (Chapter 14) shows one consumer thread handles 2,000 events/s.

Formula	consumers needed = ⌈peak rate / per-consumer rate⌉; partitions ≥ consumers needed × headroom
Plug in	⌈6,944 / 2,000⌉ = ⌈3.47⌉ = 4. With 1.5 times headroom: 4 × 1.5 = 6.
Answer	Use 6 partitions (the script printed `consumer threads needed: 4 -> use partitions = 6`). Round up to a number that divides well, such as 6 or 8, and allow future growth.
Check	6 consumers × 2,000 = 12,000 per second, 1.7 times the peak.
Why it matters	The partition count caps parallelism (Chapter 11). Producers also need check: 6.9 MB/s is far under what one partition can take (often tens of MB/s), so consumer speed, not bandwidth, decides.

Problem 13.1.3 Warehouse storage. Parquet with compression is about 5 times smaller than raw JSON in this case. How big is one year of clickstream?

Formula	stored per day = raw per day / compression ratio; per year = per day × 365
Plug in	200 GB / 5 = 40 GB per day; 40 × 365 = 14,600 GB
Answer	40 GB per day, 14.6 TB per year (script: `parquet ~5x: 40.0 GB/day, 14.6 TB/year`). Object storage cost for 14.6 TB is small compared with the compute cost to query it, so partition by date and prune.
Check	14.6 TB × 5 = 73 TB raw, and 200 GB × 365 = 73,000 GB. Yes.
Why it matters	The ratio is an assumption. Always say "I assume 5 times; I would test on a sample file" (Chapter 3 showed the real effect on a sample).

The picture: one design skeleton

```
sources -> ingestion -> [ log / buffer ] -> processing -> storage ->
serving
 apps       API/CDC       Kafka               Flink/Spark   lake +
BI, API,
 DBs        agents                            dbt           warehouse
features
               \______ quality, monitoring, governance, orchestration
______/
```

Every design in this chapter is this skeleton with different boxes filled in. Walk from left to right with one event.

Connection to the real job

- Capacity numbers decide cost: partitions, brokers, warehouse size. A wrong factor of 10 means a large bill or an outage.
- Design discussion is how senior engineers show value: they write a short design document (problem, requirements, numbers, options, trade-offs, decision, risks) and get it reviewed.

Applications

- **Data Engineering:** platform sizing, migration planning.
- **MLOps:** feature store sizing and serving latency budgets.
- **Operations:** capacity recommendations from measured test data.

COMMON MISTAKE

Skipping requirements and naming tools. Say "I will first confirm freshness, volume and budget" every time.

COMMON MISTAKE

Using the average rate for sizing. Systems fail at the peak, so size for peak times headroom, and test the spike.

Check yourself

1. 30 million events per day, average rate? Answer: 30,000,000 / 86,400 = about 347 per second.
2. Why replicate Kafka x3? Answer: to survive broker failure without losing data.
3. What is a good first step in any design? Answer: ask for requirements (volume, latency, consistency, budget).

13.2 Designs 1 to 3: Clickstream, CDC to Warehouse, Fraud

Design 1: Clickstream analytics platform

Requirements (assumed after asking): 5 million daily users, 200 million events/day, dashboards refresh within 5 minutes, product analysts query history for a year, user-level deletion on request, budget moderate.

Numbers: peak 6.9 thousand events/s, 200 GB/day raw, 6 partitions, 40 GB/day stored, 14.6 TB/year (Section 13.1).

```
web/app SDK -> collector API (stateless, autoscaled) -> Kafka topic clicks
(6 partitions, key = user_id)
   -> stream job (dedupe by event_id, sessionize, enrich) -> Delta/Iceberg
bronze/silver (Chapter 1 medallion)
   -> dbt (sessions, funnels) -> warehouse gold marts -> BI dashboards
   \-> Pinot/ClickHouse for the live "last 5 minutes" tiles (optional)
```

Choices and why:

- Collector writes to Kafka and returns fast: the app must never wait for analytics. A queue

decouples producers from consumers.

- Key by `user_id` so one user's events stay in order for sessionizing (Chapter 11).
- Dedupe by `event_id` because SDK retries duplicate events (at-least-once, then idempotent write).
- Event time with a 10 minute watermark for mobile devices that were offline; later events go to a side output and are fixed by the nightly batch (Chapter 6).
- Partition by `event_date` in the lake; PII (user id, IP) tokenized; deletion by user via Delta/Iceberg row delete (Chapters 3 and 12).

Failure modes: collector down (clients buffer and retry); consumer lag (autoscale consumers up to the partition count, alert on lag); schema change from the app team (Schema Registry, contract tests); bot traffic (filter rules in silver; track the bot share).

Cost levers: compress to Parquet, partition prune, keep raw JSON only 7 days, cluster autoscale, spot for batch.

Problem 13.2.1 The marketing team launches a sale and traffic jumps 10 times for 30 minutes. What happens, and what do you do?

Step 1	Peak goes from 6.9 thousand to 69 thousand events/s, and 69 MB/s. Kafka itself copes (it handles far more), but 6 consumers at 2,000/s give only 12,000/s.
Step 2	The shortfall is 69,000 − 12,000 = 57,000 per second, so the backlog grows 57,000 × 60 × 30 = 102.6 million events in 30 minutes. Lag rises, and dashboards are late but data is not lost (the log holds it).
Answer	Data is safe, freshness degrades (about 69 thousand per second is the rounded peak; exact is 69,440). To fix, pre-create more partitions for sale seasons (say 24) and scale consumers before the sale, or accept the delay. If you scale to 24 consumers only after the spike ends, draining 102.6 million works like this: 24 consumers (48,000/s) at normal 6,944/s input, spare = 41,056/s, so 102.6 million / 41,056 = 2,499 s, about 42 minutes.
Check	57,000 × 1,800 s = 102,600,000. Yes.
Why it matters	This is a spike test result you can predict on paper, and then confirm by a capacity test (Chapter 14).

Design 2: CDC from OLTP to the warehouse

Requirements: the orders database (Postgres) must reach the warehouse within 5 minutes, with deletes and updates reflected, without slowing the production database. Volume: 50 million row changes per day.

Numbers (design.py): 579 changes/s average, 2,315/s at peak (peak factor 4), 600 bytes each: 30 GB/day, 1.39 MB/s at peak. Small.

CDC pipeline: database log, Debezium, Kafka, warehouse MERGE

How to read it: the log of the database is the source; Debezium converts it to events; Kafka buffers; a sink applies a MERGE to the warehouse.

```
Postgres (logical replication slot) -> Debezium (Kafka Connect) -> Kafka
topic per table (key = primary key)
  -> landing files in lake (raw change log, append only, bronze)
  -> MERGE job every 5 min: keep the latest event per key by LSN ->
warehouse table (current state)
  -> SCD2 history from the same log via dbt snapshot or a MERGE
```

Choices and why:

- Log-based CDC does not run heavy queries on the OLTP database (Chapter 4), so production is not slowed. Compare polling with `updated_at`, which misses deletes and loads the database.
- Key = primary key keeps the order of changes of one row in one partition.
- The MERGE picks the highest log sequence number per key and handles deletes (a tombstone or a `deleted` flag). Replays are harmless, as our CDC simulation showed in Chapter 4.
- Initial load: a **snapshot** (Debezium takes one) then streaming; verify counts at the cut-over.
- Schema changes: additive columns pass; breaking ones go to quarantine (Chapter 5).

Failure modes: the replication slot grows if the consumer stops (the database disk fills: **alert on slot lag**, this is a classic outage); duplicates (handled by the MERGE); out-of-order (use LSN not arrival time); big transactions (batch size limits).

Problem 13.2.2 The pipeline stopped for 6 hours. How much data must it catch up, and how long does catch-up take if the MERGE handles 4 times the average rate?

Formula	backlog = rate × downtime; catch-up time = backlog / (capacity − incoming rate)
Plug in	average 579/s × 6 × 3,600 = 579 × 21,600 = 12.5 million changes. Capacity 4 × 579 = 2,316/s; incoming 579/s.
Compute	spare = 2,316 − 579 = 1,737/s. Time = 12,506,400 / 1,737 = 7,200 s = 2 hours.
Answer	About 12.5 million changes, caught up in about 2 hours (579 × 21,600 = 12,506,400, divided by 1,737 is 7,200).
Check	1,737 × 7,200 = 12,506,400. Yes.
Why it matters	"How long to recover?" is a standard follow-up. Note the rule: catch-up needs spare capacity, with zero spare the backlog never clears.

Design 3: Real-time fraud pipeline

Requirements: 20 million card transactions per day; decision (approve, review, block) within 150 ms inside the payment flow; rules plus an ML score; fewer false blocks; every decision logged for audit; 99.9% availability.

Numbers: average 231 per second, peak (factor 5) 1,157 per second. Latency budget: gateway to Kafka 15 ms, feature lookup 30 ms, model score 40 ms, rules 15 ms, respond 20 ms = 120 ms, leaving 30 ms spare (budget 150). Little's law: in-flight decisions at the peak with 100 ms each = 1,157 × 0.100 = 115.7 (about 116).

```
payment gateway -> decision service (sync, 150 ms) <- online feature store
(Redis/DynamoDB)
        |                   |  \-> model server (scores) \-> rules engine
        v                   v
   Kafka: transactions   Kafka: decisions (audit)
        |
   Flink: velocity features (count per card in 10 min sliding window, key
= card_id) -> online store
        |
   lake (bronze) -> batch training data, label join (chargebacks arrive
days later)
```

Choices and why:

- Two paths: a **synchronous** path (the 150 ms decision, small and fast) and an **asynchronous** path (stream features, logging, training). Never put heavy work in the

synchronous path.

- Flink with keyed state computes "transactions per card in last 10 minutes" (a sliding window, Chapter 11) and writes to the online store with a TTL.
- **Training-serving skew:** the features must be computed the same way offline and online; a feature store or shared code prevents this.
- **Labels are late:** chargebacks arrive weeks later, so model evaluation uses delayed labels; keep point-in-time correct feature history (Chapter 2 time travel idea).
- Degrade gracefully: if the model server is slow (over 40 ms), fall back to rules only. Decide fail-open (approve) or fail-closed (block) with the business.

Failure modes: feature store down (fallback features, circuit breaker); hot key (one merchant or card, Chapter 11); duplicated transaction events (idempotent by `txn_id`); clock skew across services (use event time with allowed lateness).

Problem 13.2.3 The model server's p99 rises to 120 ms. What is the new total budget, and what do you do?

Step 1	Replace the model's 40 ms with 120 ms: 15 + 30 + 120 + 15 + 20 = 200 ms, over the 150 ms limit by 50 ms.
Step 2	Use the timeout: allow the model 40 ms, then fall back to rules for that request. Fix the root cause (autoscale, batch inference, smaller model, cache) and alert on the fallback rate.
Answer	The budget breaks (200 ms against 150 ms), so enforce a per-call timeout and fallback.
Check	With the timeout, worst case = 15 + 30 + 40 + 15 + 20 = 120 ms (the original budget).
Why it matters	Latency budgets are summed per stage, and p99 (not average) decides whether you break the promise. This is your home ground.

Connection to the real job

- Clickstream, CDC and fraud designs are the three most common interview prompts.
- Real teams combine them: CDC feeds the warehouse, clickstream feeds product analytics, and fraud reads both.

Applications

- **E-commerce:** funnels, conversion, search relevance.
- **BFSI:** payments, fraud, risk scoring, regulatory audit trails.
- **SaaS:** product usage analytics, billing events.

COMMON MISTAKE

Using CDC but forgetting the initial snapshot or deletes. Always say "snapshot then stream, and how deletes are handled".

COMMON MISTAKE

Forgetting that a log-based CDC slot can fill the production disk when the consumer is down.

Check yourself

1. Why use two paths (sync and async) in fraud? Answer: the decision must be fast and simple; heavy feature computation and logging happen off the critical path.
2. Why key CDC events by primary key? Answer: all changes of one row go to one partition, keeping order.
3. What is training-serving skew? Answer: features computed differently in training and production, so the model sees different data online.

13.3 Designs 4 to 6: Log Analytics, ML Feature Pipeline, IoT

Design 4: Log analytics platform

Requirements: 2,000 servers each writing 5 lines per second of about 300 bytes; search recent logs within seconds; keep 30 days searchable and 1 year archived; alert on error patterns.

Numbers (capacity.py): 864 million lines per day, average 10,000/s, peak (factor 2) 20,000/s, 259.2 GB/day raw, 6.0 MB/s at peak, Kafka 7 days x3 = 5.44 TB.

Storage maths (design.py): hot search tier = 259.2 GB × 30 days × 1.3 index overhead × 2 (one replica) = 20,218 GB = 20.2 TB. Cold archive in compressed Parquet (assume 8 times smaller): 259.2 / 8 = 32.4 GB/day × 335 days = 10.9 TB.

```
agents (Filebeat/Fluent Bit/OpenTelemetry collector) -> Kafka logs (key =
host or service)
   -> parser/enricher (JSON, trace id, drop DEBUG noise) ->
OpenSearch/Elasticsearch (30 days hot)
   -> object storage Parquet (archive, query with Athena/Trino/DuckDB)
   -> alert rules (error rate per service per minute) -> pager
```

Choices and why: Kafka protects the search cluster from bursts (a crash loop can produce 100 times more logs). Structured JSON logs make parsing cheap. **Sampling and levels** control cost: logging is the first thing to explode your bill. Index only the fields you search; keep the rest as raw text. Hot, warm and cold tiers (index lifecycle) move older data to cheaper storage.

Failure modes: log storm (rate limit per service, drop DEBUG); search cluster red (the Kafka buffer holds for 7 days); PII in logs (scrub at the collector); clock skew between hosts (use ingestion time as a second field).

Problem 13.3.1 A bug makes 10% of servers log 50 times more for 1 hour. What is the extra volume?

Formula	extra = normal rate × (affected share × (factor − 1)) × time
Plug in	10,000 lines/s × 0.10 × (50 − 1) × 3,600 s
Compute	10,000 × 0.10 = 1,000; 1,000 × 49 = 49,000 extra lines per second; × 3,600 = 176.4 million extra lines; × 300 bytes = 52.9 GB
Answer	About 176 million extra lines, 53 GB, in one hour (about a fifth of a normal day's 259 GB, in one hour, from 10% of servers). Rate limits per service protect the cluster.
Check	Total rate during the storm = 10,000 + 49,000 = 59,000 lines/s, 2.95 times the 20,000/s peak plan, so the cluster would be overrun without a limit.
Why it matters	Plan for log storms, not only normal load.

Design 5: ML feature pipeline

Requirements: 10 million users; 200 features per user (numbers such as "orders in last 30 days"); a recommender needs features online within 20 ms, and training needs the exact historic values as of each past date (**point-in-time correctness**).

Numbers (design.py): online store: 10,000,000 × 200 × 8 bytes = 16 GB (fits in memory). Offline daily snapshots: 10 million users × 365 days × 1.6 KB per row = 5.84 TB raw per year (about 1.2 TB at 5 times compression).

```
batch features: warehouse/dbt -> offline store (partitioned snapshots by
date)  -> training sets
stream features: Kafka -> Flink/Structured Streaming -> online store
(Redis/DynamoDB) + offline log
feature store (Feast / cloud feature stores): one definition, two stores
serving: model service reads online features by user_id (key lookup, < 20
ms)
```

Choices and why: One feature definition feeds both stores to prevent training-serving skew. The training set is built by joining each label with the feature values **as of the label time**, never later (otherwise **data leakage**: the model sees the future). Backfill features after a new definition: this is a big batch job (Chapter 10 tuning). TTLs in the online store avoid stale values. Monitor feature freshness and drift.

Failure modes: online store missing a user (default values and a missing flag); late events change an old feature (decide: recompute or accept); skew between online and offline code (shadow compare a sample each day).

Problem 13.3.2 Why is 16 GB for the online store a good news?

Step 1	16 GB fits in memory of one modern node, so Redis can serve key lookups in about a millisecond.
Step 2	With replication and headroom, say 3 nodes of 32 GB: the whole store has 96 GB of memory for 16 GB of data.
Answer	It is small enough to keep fully in memory, so the 20 ms budget is mostly network time, and no complex storage is needed.
Check	10,000,000 × 200 × 8 = 16,000,000,000 bytes = 16 GB. Yes.
Why it matters	If the number were 16 TB, you would choose a different store. Always compute first.

Design 6: IoT ingestion

Requirements: 100,000 sensors send a reading every 10 seconds (200 bytes). Show device

status within 1 minute; keep 2 years; detect a device silent for over 5 minutes; devices can be offline and send a burst later.

Numbers (capacity.py and design.py): 10,000 messages/s on average, peak factor 1.5 gives 15,000/s; 172.8 GB/day raw; 3.0 MB/s at peak; Kafka 7 days x3 = 3.63 TB; consumer threads at 2,000/s each: ⌈15,000 / 2,000⌉ = 8.

```
devices -> MQTT broker (lightweight protocol) -> Kafka (key = device_id)
   -> stream job: event time, watermark 10 min, "last seen" state per
device, silent-device timer (5 min)
   -> time-series store (TimescaleDB/InfluxDB/ClickHouse) for dashboards,
raw Parquet in lake (partition by day)
   -> downsample: 1 min and 1 hour aggregates kept 2 years; raw kept 90
days
```

Choices and why: MQTT suits small devices and poor networks. A device's key keeps its order. Silent-device detection is a **timer on keyed state** (Flink: a processing-time or event-time timer; Structured Streaming: state with timeout). **Downsampling** keeps 1-minute averages instead of every 10-second reading: 6 times fewer rows and, with smaller rows, about 30 times fewer bytes per day (Problem 13.3.3). Show the user the right resolution. Out-of-order bursts after outage need a longer watermark or a late path.

Failure modes: reconnect storm (all devices reconnect after an outage: rate limit and jitter); clock drift on devices (device time unreliable: store both device and server time); duplicate messages (idempotent by `device_id + seq`).

Problem 13.3.3 Raw storage for 2 years versus keeping 90 days raw plus 1-minute averages for the rest. Compare (use 200 bytes per raw reading and 40 bytes per aggregate row).

Formula	raw = 172.8 GB/day × days; aggregate rows per day = 100,000 devices × 1,440 minutes; bytes = rows × 40
Plug in	all raw for 730 days: 172.8 × 730 = 126,144 GB = 126.1 TB. Option B raw 90 days: 172.8 × 90 = 15,552 GB = 15.6 TB. Aggregates: 100,000 × 1,440 = 144,000,000 rows per day × 40 bytes = 5.76 GB per day; for 640 more days = 3,686 GB = 3.7 TB.
Compute	Option B total = 15.6 + 3.7 = 19.2 TB
Answer	126.1 TB versus 19.2 TB (before compression), about 6.6 times less, with raw detail kept for the recent 90 days.
Check	126.1 / 19.2 = 6.6. Rows per day: 100,000 readings every 10 s = 8,640 per device per day; the aggregate is 1,440 per device per day, so 6 times fewer rows, and 40 versus 200 bytes gives 30 times less per day (172.8 / 5.76 = 30). Yes.
Why it matters	Retention policy is a design decision with a clear price tag.

How to present a design in 45 minutes

Minutes	What you do
0 to 5	Clarify requirements; write numbers (volume, latency, retention) on the board
5 to 10	Estimate capacity; state assumptions
10 to 25	Draw the skeleton; walk one event from source to dashboard; justify each box
25 to 35	Data model, partitioning, late data, duplicates, quality checks
35 to 42	Failure modes, monitoring, cost, scaling to 10 times
42 to 45	Summarize trade-offs and what you would test first

Connection to the real job

- A design review is where seniors catch the missing delete handling or the 10 times peak. Learn to ask "what happens if this is 10 times bigger, late, duplicated or down?".

- Recommendation platforms and other designs from the skill map combine the same blocks: events to Kafka, features to stores, batch training, online serving.

Applications

- **Observability and AIOps:** log analytics and metrics pipelines.
- **IoT, manufacturing, energy:** telemetry and anomaly detection.
- **ML platforms:** feature pipelines and monitoring.

COMMON MISTAKE

Keeping raw data at full resolution forever. State the retention and downsampling policy with its cost.

COMMON MISTAKE

Designing only the happy path. Interviewers score you on failure modes: overload, duplicates, late events, schema change, a downstream outage.

Check yourself

1. Why put Kafka between agents and the search cluster? Answer: to absorb bursts and let the cluster fall behind without losing logs.
2. What is point-in-time correctness? Answer: training features use only values known at the label's time, to avoid leakage.
3. How would you detect a silent IoT device? Answer: keep "last seen" state per device and fire a timer when no message arrives within 5 minutes.

Chapter recap

- Use the nine-step framework: requirements, capacity, model, ingestion, storage, processing, serving, quality and monitoring, failures and cost.
- Estimate: events/day = users × events per user; rate = events/day / 86,400; peak = rate × factor; size = events × bytes; keep headroom.
- Clickstream: 200 million events/day gives 6.9 thousand/s peak, 200 GB/day, 6 partitions, 14.6 TB/year in Parquet.
- CDC: log-based, snapshot then stream, key by primary key, MERGE by latest sequence

number, alert on slot lag.

- Fraud: synchronous 150 ms path with a latency budget and fallback, plus an asynchronous streaming-feature path; beware skew and late labels.
- Logs: buffer in Kafka, hot 30 days for search and cold Parquet archive, control cost with levels and sampling.
- Features: one definition, two stores, point-in-time joins; IoT: MQTT, device key, silent-device timers, downsampling.
- Always add failure modes, monitoring and cost to every design.

Item	Formula
Average rate	`events per day / 86,400`
Peak rate	`average × peak factor`
Consumers needed	`⌈peak / per-consumer rate⌉`
Partitions	`consumers × 1.5` (round up)
Kafka disk	`GB per day × retention days × replication`
Recovery time	`backlog / (capacity − incoming)`
Latency budget	sum of stage p99 values ≤ limit
Quick rule	1 million per day ≈ 12 per second

Practice set

1. (easy) 8.64 million events per day. Average per second?

Answer: 8,640,000 / 86,400 = 100 per second.

2. (easy) 100 events/s, 500 bytes each. GB per day?

Answer: 100 × 86,400 = 8.64 million events × 500 bytes = 4.32 GB per day.

3. (easy) Peak is 3 times average of 2,000/s. One consumer handles 1,500/s. How many consumers, and how many partitions with 1.5 times headroom?

Answer: Peak 6,000; ⌈6,000 / 1,500⌉ = 4 consumers; 4 × 1.5 = 6 partitions.

4. (medium) Kafka retention 3 days, replication 3, 150 GB per day. Disk needed?

Answer: 150 × 3 × 3 = 1,350 GB = 1.35 TB (plus 20 to 30% free space in practice).

5. (medium) CDC pipeline average 1,000 changes/s stops for 1 hour; the apply job can do 3,000/s. Catch-up time?

Answer: Backlog 3,600,000. Spare 2,000/s. 3,600,000 / 2,000 = 1,800 s = 30 minutes.

6. (medium, find the bug) A design says "poll the orders table every minute for rows where `updated_at` > last run to get all changes." Name two problems.

Answer: Deleted rows are never seen; rows updated within the same timestamp as the checkpoint may be missed; frequent polling loads the database. Use log-based CDC.

7. (medium) The fraud stages are 20, 35, 50, 20, 25 ms and the limit is 150 ms. Does it fit? What if the 50 ms stage becomes 90 ms?

Answer: 20 + 35 + 50 + 20 + 25 = 150, exactly the limit, no headroom. With 90 ms: 190 ms, 40 ms over; use timeout and fallback.

8. (hard) 400,000 sensors send a reading every 5 seconds at 150 bytes. Messages per second, MB/s and GB per day?

Answer: 400,000 / 5 = 80,000 msgs/s. 80,000 × 150 = 12,000,000 B/s = 12 MB/s. Per day: 12 MB/s × 86,400 = 1,036,800 MB = 1,036.8 GB (about 1.04 TB).

9. (hard, scenario) You must design a recommendation data platform for an e-commerce site in 10 minutes. Which components do you reuse from this chapter?

Answer: Clickstream capture (Design 1) for events; CDC (Design 2) for catalog and orders; feature pipeline (Design 5) for user and item features, online store for serving; batch training from the lake; monitoring of freshness and drift. Say the requirements and numbers first.

10. (interview) "Design a CDC pipeline from Postgres to Snowflake." Give your first 5 sentences.

Answer: First I ask for volume, freshness (say 5 minutes), whether deletes matter, and whether production load must stay low. I estimate changes per second and size. I use log-based CDC with Debezium reading the replication slot into Kafka, one topic per table keyed by primary key. A MERGE job applies the latest event per key by log sequence number to the warehouse, with an initial snapshot first. I monitor slot lag, consumer lag and freshness, and I handle schema changes with a registry and quarantine.

11. (interview) How do you handle a 10 times traffic spike in a streaming platform?

Answer: Know the bottleneck from capacity tests; Kafka buffers the spike, so the key is consumer capacity: pre-provision partitions, autoscale consumers up to the partition count, apply rate limits and backpressure, keep lag alerts, accept a temporary freshness delay, and compute the drain time as backlog divided by spare capacity.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me the
system design framework for data platforms (requirements, capacity, model,
ingestion, storage, processing, serving, quality, failures, cost). Use a
clickstream platform for 5 million users as the example, with every number
calculated step by step. Then give me 6 capacity-estimation exercises
without solutions.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Topic:
capacity estimation for streaming and storage: events per second, peak
factor, Kafka partitions, replication, retention, compression, headroom,
recovery time after an outage. Give me 8 graded numeric problems, one at a
time, and check each answer with full working. Start easy and finish with
a combined problem.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am applying for data engineer roles. Run a
system design interview: "Design a CDC pipeline from an OLTP database to a
warehouse." Let me ask clarifying questions first. Then score my answer on
requirements, numbers, data model, failure modes and cost, and show a
model 45-minute answer outline in simple English. My answer: [PASTE HERE]
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am applying for data engineer and ML
platform roles. Teach me the real-time fraud pipeline design: synchronous
```

decision path with a latency budget, streaming features in Flink, online feature store, training-serving skew, late labels and fallback behaviour. Use Little's law and p99 budgets. Then quiz me with 5 scenario questions, one at a time.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Compare designs for log analytics, ML feature pipelines and IoT ingestion: volumes, storage tiers, retention and downsampling, point-in-time correctness, silent-device detection. Give me three whiteboard prompts, let me answer one by one, and critique each answer for missing failure modes and cost. My answers: [PASTE HERE]

CHAPTER 14

PERFORMANCE AND CAPACITY OF DATA PIPELINES

Measure pipelines, Kafka consumers and ML endpoints with numbers, then turn the work into portfolio projects and interview answers.

Many data teams never measure how much work a pipeline can really handle. When a pipeline is "slow", they guess. A better habit is to measure throughput, percentiles and utilization, find the bottleneck, and write a capacity recommendation, much as a hospital measures how many patients each stage (registration, doctor, pharmacy) can handle per hour. That habit is the doorway to roles such as Data Platform, ML Platform and Observability engineer. In this chapter we apply it to data pipelines: Little's law, the utilization-latency curve (with a simulation we ran), a bottleneck table for a Kafka pipeline, load-testing an ML endpoint, regression detection across builds, and cost per 1,000 predictions. Then you get eight capstone projects (the portfolio) and a bank of interview questions with model answers covering the whole document.

Honest note: Locust, k6, Kafka and cloud tools are not run here. The simulations (queue, bottleneck arithmetic, regression test) use Python's standard library and were really run (`/tmp/de_lab/little.py` , `/tmp/de_lab2/bott.py` , `/tmp/de_lab2/regress.py`). The queue simulation is a teaching model of a single server, not a measurement of Kafka.

14.1 Little's Law, Utilization and Latency: the Math Behind Every Test

INTUITION

A single cashier at a shop. If customers arrive faster than she can bill them, the line grows without end. If they arrive at 90% of her speed, the line is usually short, but sometimes long: after a few slow customers, a queue builds and takes time to clear. Latency does not rise slowly with load: it stays flat, then bends upward sharply near 100% busy. A Kafka consumer, a database connection pool and an ML endpoint all behave like this cashier.

Words you need

Word	Plain meaning	Example
Arrival rate (λ, "lambda")	Requests or messages arriving per second	50 messages/s
Service rate (μ, "mu")	How many one server can finish per second when busy	100 messages/s
Utilization (ρ, "rho")	Fraction of time the server is busy: $\rho = \lambda / \mu$	50 / 100 = 0.5
Latency (W)	Time one request spends in the system (waiting plus service)	20 ms
L	Average number of requests inside the system	1
Throughput	Completed requests per second	equals λ if the system is stable
Percentile	The value below which a given share of observations fall	p99 = 99% are faster

Little's law

For any stable system, over a long time: $L = \lambda \times W$. In words: the average number of things inside = arrival rate × average time each spends inside. It needs no assumption about the shape of arrivals. You can check it at a bank: if 2 customers arrive per minute and each spends 6 minutes inside the branch (waiting plus service), then on average 2 × 6 = 12 customers are inside.

Problem 14.1.1 An ML endpoint receives 300 requests per second and the average latency is 120 ms. How many requests are inside the endpoint on average, and how many workers do you need if each worker handles one request at a time and you want 70% utilization?

Formula	L = λ × W; workers = L / target utilization
Plug in	L = 300 × 0.120
Compute	L = 36 requests in flight. Workers = 36 / 0.70 = 51.4, round up to 52 (the real run printed `concurrent requests 36.0 workers at 70% util: 52`).
Answer	36 requests are in flight on average, so use 52 workers for 70% utilization.
Check	52 workers at 70% means 36.4 busy workers, matching L = 36.
Why it matters	This is how you size thread pools, connection pools and replicas from a measured latency instead of guessing.

Problem 14.1.2 A Kafka consumer pipeline handles 2,000 messages/s and each message takes 50 ms end to end. How many messages are in flight?

Formula	L = λ × W
Plug in	2,000 × 0.050
Compute	100
Answer	100 messages in flight, so a consumer needs 100 parallel slots (threads or async tasks) or the work must be faster.
Check	If W halved to 25 ms, L halves to 50, which is why a faster sink reduces the needed parallelism.
Why it matters	The same law links lag, throughput and latency in streams.

The utilization-latency curve (real simulation)

We simulate one consumer with random (exponential) arrivals and random service times with mean 10 ms (μ = 100 messages/s), and measure latency at increasing utilization. This is the model called M/M/1; `little.py` does it with a fixed random seed:

```
import random, statistics
random.seed(5)
def sim(arrival_rate, service_rate, n=200000):
    t=0; free_at=0; waits=[]
    for _ in range(n):
        t+=random.expovariate(arrival_rate)
        start=max(t,free_at); s=random.expovariate(service_rate);
free_at=start+s
        waits.append(free_at-t)    # latency = wait + service
    return waits
mu=100.0
for rho in (0.5,0.7,0.8,0.9,0.95):
    w=sim(rho*mu,mu); w.sort()
    mean=statistics.mean(w); p95=w[int(.95*len(w))];
p99=w[int(.99*len(w))]
    print(f"{rho:.2f}  {mean*1000:10.1f}  {p95*1000:6.1f}  {p99*1000:6.1f}
{rho*mu*mean:6.2f}")
print("theory mean M/M/1: 1/(mu-lambda) ->", [round(1000/(mu-r*mu),1) for
r in (0.5,0.7,0.8,0.9,0.95)])
```

Real output:

```
service rate mu = 100 msg/s (1 consumer)
util  mean_lat_ms  p95_ms  p99_ms   L=lambda*W
0.50        19.9    59.8    92.7     1.00
0.70        33.9   102.4   158.0     2.37
0.80        49.3   147.4   221.1     3.95
0.90        99.4   296.7   436.1     8.95
0.95       182.4   506.1   734.9    17.33
theory mean M/M/1: 1/(mu-lambda) -> [20.0, 33.3, 50.0, 100.0, 200.0]
```

How to read the table: each row is one load level. Between 50% and 90% utilization the load grows 1.8 times, but the mean latency grows 5 times (19.9 to 99.4 ms) and p99 grows 4.7 times (92.7 to 436.1 ms). At 95% it is nearly 10 times the 50% value. The last column checks Little's law: L computed from the simulated mean latency equals λ × W (and matches the theory value ρ/(1−ρ): 1, 2.33, 4, 9, 19). The simulated means match the theory formula `1 / (μ − λ)` (20, 33.3, 50, 100, 200 ms) closely, and the small differences are random noise from a finite run.

Notice also that percentiles rise faster than the mean. The mean at 0.8 is 49 ms, and p99 is 221 ms, 4.5 times the mean. Averages hide the pain, which is why delivery companies, hospitals and data teams report p95 and p99 and not only the average.

Problem 14.1.3 The product requires p99 latency under 200 ms. Using the table, what is the highest utilization you can run the consumer at?

Step 1	At 0.70 the p99 is 158.0 ms (OK). At 0.80 it is 221.1 ms (too high).
Step 2	The limit lies between 0.70 and 0.80, nearer 0.77 (linear guess). To be safe, round down to 0.7 and confirm with a finer test.
Answer	Run at about 70% utilization or a little above. At 100 messages/s capacity this means a sustained 70 to 75 messages/s per consumer.
Check	At 70%, p99 = 158 ms, which has a 42 ms margin below 200.
Why it matters	"Keep CPU below 70%" is not folklore: it is the result of this curve.

Problem 14.1.4 One consumer has μ = 100/s. Peak arrival is 280/s. How many consumers (as separate workers sharing the load evenly, ignoring partition skew) keep utilization at or below 70%?

Formula	consumers ≥ λ / (μ × target utilization)
Plug in	280 / (100 × 0.70)
Compute	280 / 70 = 4.0, so exactly 4 consumers, each at 70 messages/s (utilization 0.70). Round up and add headroom: 5.
Answer	4 consumers meet the target on paper; use 5 for headroom (and make sure there are at least 5 partitions).
Check	5 × 100 = 500/s capacity vs. 280/s: utilization 0.56, p99 between 92.7 ms (0.5) and 158 ms (0.7).
Why it matters	Real traffic is not evenly split because of key skew (Chapter 11), so test per-partition behaviour.

Connection to the real job

- Every capacity recommendation you write follows this chain: measure service time, apply Little's law, choose a utilization ceiling from the curve, add headroom.
- Little's law also explains **consumer lag** growth: if λ > μ, the queue never stabilizes (utilization above 1).

Applications

- **Data Engineering:** consumer counts, connection pool sizes, warehouse concurrency.
- **MLOps:** replicas of a model service for a target p99.
- **Operations and capacity planning:** all test analysis, workload modelling.

COMMON MISTAKE

Sizing for 100% utilization "because it is cheaper". Latency explodes before that, and any burst creates a long queue.

COMMON MISTAKE

Reporting only the mean. A mean of 49 ms can hide a p99 of 221 ms.

Check yourself

1. 400 requests/s, 250 ms average latency. L? Answer: 400 × 0.25 = 100 in flight.
2. Why does latency rise sharply near full utilization? Answer: random bursts create queues that need spare capacity to clear; with little spare they stay long.
3. If λ is larger than μ, what happens? Answer: the queue grows without limit (unstable).

14.2 Load-Testing Data Pipelines, Kafka Consumers and ML Endpoints

INTUITION

To test a shop website you send many simulated visitors and watch response time, errors and throughput. For a pipeline you send **data** instead of users: a controlled stream of messages or a large file, and you watch the rate at which each stage consumes it. A data pipeline is a chain of stages, and a chain is only as fast as its slowest link.

What changes compared with a web test

Web test	Data pipeline test
Simulated visitors,	Message rate (events/s), batch size, data volume

pause between clicks	
Response time per request	End-to-end latency (produced to visible), consumer lag, run duration
Errors (HTTP 5xx)	Failed records, duplicates, lost records (reconcile counts), DLQ size
Session tokens and ids	Generate realistic keys (so partitions are balanced or skewed like production)
Gradual ramp, steady, spike, soak	Same four shapes: ramp, steady, spike (10 times for 30 minutes), soak (hours, watching memory and lag)
Result: percentile table	Result: throughput per stage, lag over time, utilization per stage, cost per 1,000 events

Tools (examples only): **Locust** (Python, easy for custom producers), **k6**, Gatling, or a short Python producer; for Kafka specifically, the producer performance script shipped with Kafka and tools like `kcat`. For batch pipelines: run with a **synthetic dataset** of known size (Faker or your own generator) and compare 1x, 5x, 10x volumes to see if runtime grows linearly. (Check each tool's current options in its docs; not run here.)

A test plan for a Kafka consumer pipeline

1. **Goal and SLO:** "End-to-end p99 under 5 seconds at 5,000 events/s; lag returns to zero within 10 minutes after a 3x spike."
2. **Workload model:** message size, key distribution, peak rate, spike shape, from production metrics.
3. **Environment:** production-like (same partitions, same instance sizes, a smaller copy of data).
4. **Measure at each stage:** producer rate, broker bytes in, consumer rate, processing time, sink write time, lag per partition, CPU, memory, GC, network, disk.
5. **Run the shapes:** ramp until lag grows (the capacity point), steady at 70% of that, spike, soak 4 hours, then **chaos**: kill a consumer, restart a broker, slow the sink. Verify recovery and **no data loss** by reconciling counts and checksums.
6. **Report:** capacity table, bottleneck, recommendation, cost.

Bottleneck analysis with numbers (real run)

Stage capacities measured in a test, in messages per second: producer 8,000; Kafka broker 50,000; consumer (4 threads at 1,200 each) 4,800; transform 6,000; warehouse sink 3,500.

```
stages={"producer":8000,"kafka_broker":50000,"consumer(4 threads x
1200)":4*1200,"transform":6000,"warehouse_sink":3500}
b=min(stages,key=stages.get); print("bottleneck:",b,stages[b])
arr=4000
print("arrival",arr,"util at bottleneck",round(arr/stages[b],2))
```

```
bottleneck: warehouse_sink 3500
arrival 4000 util at bottleneck 1.14
```

The slowest stage, the warehouse sink at 3,500/s, limits the whole pipeline (throughput of a chain = minimum stage capacity). With arrival 4,000/s, utilization at the bottleneck is 4,000 / 3,500 = 1.14, above 1, so lag grows by 500 messages per second (1.8 million per hour) forever. The consumer and Kafka look fine, which is the trap: the problem hides in the last box.

Problem 14.2.1 Using the stage list, what is the system throughput after you double the sink capacity to 7,000/s by batching writes? What is the new bottleneck, and its utilization at 4,000/s?

Step 1	New capacities: producer 8,000; broker 50,000; consumer 4,800; transform 6,000; sink 7,000.
Step 2	The minimum is now the consumer at 4,800. Utilization at 4,000/s = 4,000 / 4,800 = 0.83.
Answer	System capacity becomes 4,800/s, the consumer is the new bottleneck, at 83% utilization for a 4,000/s load. This is above the 70% comfort level and p99 would suffer (see 14.1), so add consumers: 6 threads give 7,200/s and utilization 0.56 (needs 6 or more partitions).
Check	4,000 / 7,200 = 0.556. And transform is next at 6,000, so after that fix the system caps at 6,000.
Why it matters	Fixing a bottleneck reveals the next one. Report them as a ladder of improvements, each with a measured number.

Problem 14.2.2 Backlog and recovery. Arrival is 5,000 messages/s and one consumer does

1,200/s. How many consumers keep up, and with 6 consumers how long to drain a backlog of 1.8 million?

Formula	consumers = ⌈arrival / per-consumer rate⌉; drain time = backlog / (capacity − arrival)
Plug in	⌈5,000 / 1,200⌉ = ⌈4.17⌉ = 5. With 6: capacity 7,200, spare 2,200/s.
Compute	1,800,000 / 2,200 = 818 s = 13.6 minutes (the run printed `13.6`).
Answer	At least 5 consumers to keep up (zero spare, so no recovery), and 6 consumers drain the backlog in about 13.6 minutes.
Check	2,200 × 818 = 1,799,600, about 1.8 million. Yes.
Why it matters	"How fast do we recover?" is a question you can answer with a formula.

Load-testing an ML inference endpoint

Same method, with a few extra measurements: latency percentiles per batch size, throughput, **GPU utilization** and memory (if used), cold start time, and error rate under overload. Compare a replica count and compute cost.

```
node=0.9; rps_node=150  # illustrative price per hour, measured requests per second per node
print("cost per 1k predictions $",round(node/(rps_node*3600)*1000,5))
```

```
cost per 1k predictions $ 0.00167
```

Calculation: one node per hour costs 0.90 (a made-up price) and serves 150 × 3,600 = 540,000 predictions per hour, so 1,000 predictions cost 0.90 / 540 = 0.00167. If utilization is only 35% in real traffic, the real cost is about 1/0.35 = 2.9 times higher: **idle capacity is the biggest hidden cost**. Techniques to improve: dynamic batching of requests, a quantized or smaller model, autoscaling on queue length (not CPU only), and caching repeated inputs.

Problem 14.2.3 A node (illustrative 1.20 per hour) serves 200 requests/s at p99 under the SLO. Traffic averages 120/s but peaks at 600/s for 2 hours a day. What do you run, and what is the daily cost if you autoscale versus run for the peak all day?

Formula	nodes = ⌈rate / node capacity⌉; cost = nodes × price × hours
Plug in	Peak: ⌈600 / 200⌉ = 3 nodes. Off-peak: ⌈120 / 200⌉ = 1 node (use 2 for resilience).
Compute	Fixed for peak (3 nodes, 24 h): 3 × 1.20 × 24 = 86.40. Autoscaled (3 nodes for 2 h and 2 nodes for 22 h): 3 × 1.20 × 2 = 7.20; 2 × 1.20 × 22 = 52.80; total 60.00.
Answer	86.40 versus 60.00 per day (a 30.6% saving, 26.40 saved: 26.40 / 86.40 = 0.3056).
Check	7.20 + 52.80 = 60.00. And 86.40 − 60.00 = 26.40. Yes.
Why it matters	Autoscaling has a delay (new nodes need minutes), so pre-scale before known peaks or keep a buffer.

Performance analytics: put test results into the warehouse

A portfolio idea: store every measured run in a table, `fact_pipeline_run(run_id, scenario, p50, p95, p99, throughput, error_rate)`, and compare runs over time. A simple **regression detector** asks: is the latest release slower than the history, or is that noise? We simulate: 30 earlier runs with p95 around 250 ms (standard deviation about 12), and 6 recent runs around 280.

```
import random, statistics as st
random.seed(11)
base=[random.gauss(250,12) for _ in range(30)]
new=[random.gauss(280,12) for _ in range(6)]
print("baseline mean %.1f sd %.1f"%(st.mean(base),st.stdev(base)),"| new
mean %.1f"%st.mean(new))
diff=st.mean(new)-st.mean(base)
cnt=0; N=10000
for _ in range(N):
    s=[random.choice(base) for _ in range(6)]     # bootstrap: 6 runs
drawn from history
    if st.mean(s)-st.mean(base)>=diff: cnt+=1
print("observed diff %.1f ms; bootstrap p = %.4f"%(diff,cnt/N))
```

```
baseline mean 250.8 sd 11.7 | new mean 272.7
observed diff 21.9 ms; bootstrap p = 0.0000
```

Read it: if the history were the whole truth, how often would 6 random runs average 21.9 ms or more above the baseline mean? In 10,000 trials, never (p below 0.0001). So the slowdown is real, not noise, and the release should be investigated. The idea (bootstrap: resample your own data to see how surprising a result is) needs no formulas. For slow drifts use a change-point method or a forecast; and for many scenarios control the false alarms.

Chaos and reliability testing of pipelines

Test the failure paths on purpose in a test environment: kill a consumer mid-batch (do duplicates appear? Chapter 11), delay the source, send a bad schema, fill the disk, restart the scheduler (Chapter 6), run a 10x backfill and watch the source database. Check the pipeline's promises: no data loss, no duplicates in the final table, freshness restored within the SLA. Results go into the runbook (Chapter 12).

Connection to the real job

- Teams rarely load-test pipelines before launch, so a candidate who brings a test plan stands out.
- Roles: Data Platform engineer, ML Platform engineer, Observability or AIOps engineer, SRE for data, Performance Analytics.

Applications

- **Data Engineering:** consumer sizing, backfill planning, warehouse concurrency.
- **MLOps:** endpoint capacity, cost per 1,000 predictions, autoscaling policy checks.
- **AIOps:** anomaly detection on metrics, capacity forecasting (time-series models, see the ML documents).

COMMON MISTAKE

Load-testing with identical messages or keys. Real traffic has a key distribution (hot keys) and varied sizes; a uniform test hides the skew that breaks production.

COMMON MISTAKE

Testing only the consumer and ignoring the sink. The slowest stage is often the database or warehouse at the end.

Check yourself

1. Throughput of a chain of stages equals what? Answer: the capacity of the slowest stage.
2. Which two numbers does draining a backlog depend on? Answer: the backlog size and the spare capacity (capacity minus arrival).
3. Why test with a realistic key distribution? Answer: hot keys overload single partitions and are invisible with uniform keys.

14.3 Capstone Projects

Each project is a portfolio piece. Do them in this order; each one gives material for interview answers. For every project write a README with the problem, architecture diagram, how to run, results with real numbers, and what you would change. Use free tools (Docker, PostgreSQL, DuckDB, Airflow, Kafka in Docker, Spark local, dbt with DuckDB).

#	Project	Skills from this document	Deliverable and proof
1	API to Airflow to PostgreSQL pipeline in Docker with tests and alerts	Chapters 4, 5, 6, 12	Docker Compose, idempotent DAG, pytest, a failure alert; screenshot of a backfill
2	dbt project: staging to marts, tests, docs, CI	Chapters 2, 5, 7, 12	star schema on DuckDB, 15 or more tests, GitHub Actions run, generated docs
3	End-to-end cloud pipeline (ingest, lake, warehouse, dashboard) deployed with Terraform	Chapters 3, 8, 12	Terraform files, plan output, architecture diagram, cost estimate
4	PySpark job on 10 million or more rows with documented tuning	Chapters 9, 10	before and after runtimes, Spark UI screenshots, skew fix explained
5	Kafka plus Debezium CDC into a lakehouse table	Chapters 4, 11, 13	MERGE applied, duplicates and deletes proven, slot lag alert
6	Streaming pipeline (Structured Streaming or Flink) with a live	Chapter 11	windows, watermark, late-data test with numbers

	dashboard		
7	Data quality framework with automated checks and alerts	Chapters 5, 12	checks, quarantine table, freshness and volume monitors
8	**Performance and capacity report of a data pipeline**	Chapter 14 and all	Locust or Python-producer test plan, results table, bottleneck ladder, cost model, recommendations

The signature project in detail (project 8)

Title: "Load test and capacity plan for a Kafka-to-warehouse pipeline."

1. Build or reuse project 5 or 6. Document the architecture and the SLO (for example p99 end-to-end 5 s at 5,000 events/s).
2. Write a generator (Locust or a Python producer) with a realistic key distribution and message sizes.
3. Run ramp, steady, spike and soak tests. Record per-stage throughput, lag over time and CPU, memory, disk.
4. Find the bottleneck, change one thing, retest, and keep a table: change, before, after.
5. Add Little's law calculations and a utilization-latency curve fitted from your data.
6. Add a cost model (cost per run and per 1,000 events) and a capacity recommendation for 3x growth.
7. Load the results into a warehouse table and build a dashboard with regression detection across runs (the bootstrap method in 14.2).
8. Write a one-page report for stakeholders in plain language and a blog post titled "What I learned measuring a data pipeline".

Problem 14.3.1 You have a result table with three runs: "baseline" 3,500 events/s sink-bound, "batched sink" 4,800/s consumer-bound, "6 consumers" 6,000/s transform-bound. Write the one-line result for your README.

Formula	improvement % = (new − old) / old × 100
Plug in	(6,000 − 3,500) / 3,500 × 100
Compute	2,500 / 3,500 = 0.714, so 71.4%
Answer	"Throughput improved 71% (3,500 to 6,000 events/s) by batching sink writes and scaling consumers from 4 to 6; the new bottleneck is the transform stage at 6,000/s."
Check	3,500 × 1.714 = 6,000. Yes.
Why it matters	A quantified one-liner with the next bottleneck named shows analysis, not just activity.

Problem 14.3.2 Turn this into a resume bullet: you tested the capacity of a Kafka pipeline and removed a sink bottleneck.

Step 1	Use the pattern: action, scale, result, method.
Step 2	Draft it.
Answer	"Load-tested a Kafka to warehouse pipeline (5,000 events/s, Locust and Python producers), found the warehouse sink as bottleneck at 3,500/s, and raised capacity 71% by batching writes and adding consumers; documented a 3x growth capacity plan and cost per 1,000 events." (Use only numbers you actually measured.)
Check	It has a verb, a scale, a method, a measured result and an artifact.
Why it matters	ATS and recruiters scan for numbers.

Honest advice

Fewer, finished, well-documented projects beat many half-finished ones. Responsible use: use synthetic or public data, never real customer data or company secrets in a public repository.

COMMON MISTAKE

Projects with no numbers. "Built a pipeline" says nothing; "processes 10 million rows in 4 minutes, down from 19" shows impact.

Check yourself

1. Which project is your unique advantage? Answer: project 8, the performance and capacity report.
2. What must each README include? Answer: problem, architecture, how to run, real results, and what you would change.
3. What should you never put in a public repo? Answer: real secrets, customer data or company confidential information.

14.4 The Data Engineering Interview Bank

Answer aloud first, then compare. Model answers are short on purpose; add an example from your own work. They cover the whole document. Chapter numbers show where to review.

Fundamentals (Chapters 1 to 3)

1. **ETL versus ELT?** ETL transforms before loading, on a separate engine; ELT loads raw data into a powerful warehouse or lake and transforms there with SQL (cheap storage and elastic compute make ELT the modern default). Keep the raw data so you can reprocess. (Ch 1)
2. **Warehouse, lake, lakehouse?** A warehouse stores modeled, structured data for SQL; a lake stores raw files cheaply, any format; a lakehouse adds table formats (Delta, Iceberg) with transactions and schema so one copy serves BI and ML. (Ch 1, 3)
3. **What is the grain of a fact table and why does it matter?** The grain is what one row means (one order line). Everything else must match it; mixing grains double-counts in joins. (Ch 2)
4. **Explain SCD Type 2.** Keep history by closing the old row (`valid_to`) and inserting a new row with a new surrogate key and `valid_from` ; facts join to the version valid at event time. (Ch 2)
5. **Why Parquet?** Columnar, compressed, with column statistics, so queries read only needed columns and skip row groups; partitioning by date skips whole folders. Beware the small-

files problem. (Ch 3)

6. **How do Delta and Iceberg give ACID on files?** A transaction log or metadata tree records which files make up each table version; commits are atomic, readers see a snapshot, and you get time travel. (Ch 3)

Pipelines and quality (Chapters 4 to 7)

1. **Full versus incremental load?** Full copies everything (simple, expensive); incremental copies changes by a watermark column or CDC (cheap, needs care with deletes and late data). (Ch 4)
2. **Why is CDC better than polling `updated_at`?** It reads the database log, so it sees deletes, does not load the database, and keeps order; it needs a snapshot first and monitoring of the replication slot. (Ch 4, 13)
3. **What is idempotency and how do you get it?** Re-running gives the same result; overwrite a partition or MERGE by key and logical date, never blind inserts or `now()`. (Ch 4, 6)
4. **How do you handle bad records?** Validate at the edge with a contract; quarantine or DLQ the failures with the reason; alert on the rate; never silently drop. (Ch 5)
5. **What do you test in a pipeline?** Unit tests of the transformation logic, schema and not-null/unique checks, row count reconciliation between layers, freshness and volume monitors, and a DAG import test. (Ch 5, 6)
6. **Airflow: what is the logical date?** The start of the data interval; a daily run for June 1 starts after June 1 ends. Use it instead of `now()` so backfills work. (Ch 6)
7. **What does `catchup` do?** Creates runs for every missed interval since the start date; set it explicitly together with `max_active_runs`. (Ch 6)
8. **dbt in one minute?** SQL models in layers (staging, intermediate, marts) with `ref` to build a dependency graph, materializations (view, table, incremental), tests, docs and CI; it is the "T" in ELT. (Ch 7)

Warehouses and Spark (Chapters 8 to 10)

1. **How do you control warehouse cost?** Reduce bytes scanned (partition and cluster, select needed columns), right-size and auto-suspend compute, cache results, avoid repeated full refreshes (incremental models), set budgets and alerts. (Ch 8, 12)
2. **What is a Spark shuffle and why is it costly?** Moving data across the network so rows with the same key meet; it writes to disk and is the main cost in joins and group-bys. (Ch 10)
3. **How do you fix data skew?** Find the hot key in the Spark UI (one task much longer), then

broadcast the small side, salt the key, enable adaptive query execution skew handling, or filter or split the hot key. (Ch 10)

4. **When do you broadcast a join?** When one side is small enough to fit in executor memory; Spark copies it to every executor and avoids shuffling the big side. (Ch 10)
5. `repartition` **versus** `coalesce`**?** `repartition` does a full shuffle to any count, balancing data; `coalesce` only reduces partitions without a shuffle and can leave them uneven. (Ch 10)
6. **Why does lazy evaluation matter?** Transformations only build a plan; an action runs it, so Spark can optimize the whole plan, and re-running an action recomputes unless you cache. (Ch 9)

Streaming and Kafka (Chapter 11)

1. **Event time versus processing time?** Event time is when it happened, processing time is when we see it; use event time with a watermark for correct, repeatable results. (Ch 11)
2. **What is a watermark?** The rule "max event time seen minus allowed lateness"; windows ending before it are final, and later events are dropped or side-routed. (Ch 11)
3. **Explain Kafka partitions and consumer groups.** A topic is split into partitions (ordered logs); a key picks the partition; in a group each partition is read by one consumer, so parallelism is capped at the partition count. (Ch 11)
4. **Exactly-once?** Delivery is at-least-once; exactly-once effect comes from idempotent producers and Kafka transactions inside Kafka, and an idempotent or transactional sink outside it. (Ch 11)
5. **Consumer lag keeps growing. What do you check?** Arrival versus processing rate, per-partition lag (hot key), slow sink, rebalances, GC pauses; then scale consumers (up to partitions) or fix the bottleneck. (Ch 11, 14)

Infrastructure, governance and design (Chapters 12 and 13)

1. **What goes wrong with secrets?** Secrets in Git, images or logs. Use a secret manager and IAM roles, rotate after a leak, scan in CI. (Ch 12)
2. **What alerts beyond job failure?** Freshness, volume, quality-check failures, lag, runtime anomalies, cost spikes. (Ch 12)
3. **How do you handle PII?** Classify and tag; mask and tokenize; restrict by role; encrypt; support deletion and retention; keep PII out of logs and lower environments. (Ch 12)
4. **Design: clickstream for 5 million users.** Ask requirements, estimate 6.9 thousand

events/s peak and 200 GB/day, collector to Kafka with 6 or more partitions, stream job for dedupe and sessions, lake in Parquet and Delta, dbt marts, dashboards; discuss late data, PII, cost. (Ch 13)

5. **How do you size Kafka partitions?** Measure per-consumer rate, divide peak by it, add 1.5 times headroom, check producer bandwidth, and plan for growth because changing the count later breaks key order. (Ch 13, 14)

Performance bridge (this chapter)

1. **What does Little's law say, and where do you use it?** L = λ × W: items in the system = arrival rate × time in the system. Use it to size pools, replicas and consumers from measured latency and rate. (14.1)
2. **How do you find a pipeline bottleneck?** Measure capacity and utilization at every stage under load; the lowest-capacity stage limits throughput; fix it, retest, and expect a new bottleneck. (14.2)
3. **How would you load-test an ML endpoint?** Define the SLO, model the workload, ramp to find the knee of the latency curve, test batch sizes and cold starts, measure p95 and p99 and GPU use, run spike and soak, and report cost per 1,000 predictions. (14.2)
4. **Why is p99 more useful than the average?** Tail latency is what unlucky users feel and what breaks SLOs; the mean hides the queueing tail (in our simulation the mean was 49 ms at 80% utilization while p99 was 221 ms). (14.1)

Behavioural prompts (prepare with the STAR method: Situation, Task, Action, Result)

- Tell me about a production incident you handled. Include detection, cause, fix and prevention.
- Tell me about a time you pushed back on a stakeholder's request. Explain the numbers you used.
- Why are you moving into data engineering? (Answer with your strengths: measurement, systems thinking, bottleneck analysis, reliability.)

Problem 14.4.1 An interviewer asks: "Your daily Spark job's runtime grew from 20 to 55 minutes over three months while data grew 30%. Why?" Give a structured answer.

Step 1	Data grew 1.3 times but time grew 55 / 20 = 2.75 times, so the growth is not linear; suspect skew, small files, a join that now shuffles more, a spill to disk, or a source or sink slowdown.
Step 2	Plan: compare Spark UI stage times between an old and a new run; look for one long task (skew), shuffle spill, and file counts per partition; check the cluster configuration changes and the sink.
Answer	"Time grew 2.75 times for 1.3 times the data, so something scales worse than linearly. I would diff the Spark UI of an old and a new run: skewed tasks, shuffle spill, small files, and I would test fixes one at a time (broadcast, salting, compaction, more partitions) and measure each."
Check	The answer states the numbers, gives a hypothesis list and a measurement plan.
Why it matters	The interviewer wants a method, not a lucky guess.

Chapter recap

- Little's law $L = \lambda \times W$ connects rate, latency and the number in flight; it sizes pools, replicas and consumers.
- Utilization $\rho = \lambda / \mu$: latency stays flat and then rises steeply near 100%; our simulation gave p99 of 92.7 ms at 50% and 436.1 ms at 90%. Keep sustained utilization near 70%.
- Percentiles matter more than means; always report p95 and p99.
- A pipeline is a chain: throughput equals the slowest stage; fix it and the next bottleneck appears.
- Backlog drain time = backlog / (capacity − arrival); with zero spare it never drains.
- Load tests for data use message rates, realistic keys and sizes, and ramp, steady, spike, soak and chaos shapes; reconcile counts to prove no loss.
- ML endpoint cost per 1,000 predictions depends on utilization; idle capacity is the hidden cost.
- Store test results in a warehouse and detect regressions with simple statistics such as a bootstrap.
- Build eight capstone projects, ending with the performance and capacity report: your unique portfolio piece.

Item	Formula
Little's law	`L = λ × W`
Utilization	`ρ = λ / μ`
M/M/1 mean latency	`1 / (μ − λ)`
Servers needed	`⌈λ / (μ × target ρ)⌉`
Chain throughput	`min(stage capacities)`
Drain time	`backlog / (capacity − arrival)`
Cost per 1k predictions	`node price per hour / (rps × 3600) × 1000`
Improvement %	`(new − old) / old × 100`

Practice set

1. (easy) 500 requests/s with 80 ms latency. How many requests in flight?

Answer: 500 × 0.080 = 40.

2. (easy) A server finishes 200 requests/s at most and receives 150/s. Utilization?

Answer: 150 / 200 = 0.75.

3. (easy) Stage capacities 900, 1,500, 600, 2,000 per second. System throughput and bottleneck?

Answer: 600 per second; the third stage.

4. (medium) Mean latency is 20 ms at 50% utilization and 99.4 ms at 90%. How many times higher is it?

Answer: 99.4 / 19.9 (the table values) = 5.0 times, while the load rose 1.8 times (0.9 / 0.5).

5. (medium) A consumer handles 800 messages/s. Peak arrival is 3,000/s. Target utilization 70%. Consumers needed?

Answer: 3,000 / (800 × 0.70) = 3,000 / 560 = 5.36, so 6 consumers (and at least 6 partitions).

6. (medium, what is the output?) `min({"a":50,"b":30,"c":80}, key=lambda k:`

```
{"a":50,"b":30,"c":80}[k])
```

Answer: `"b"` : the key with the smallest capacity (30). This is the bottleneck finder used in 14.2.

7. (medium) A backlog of 600,000 messages, capacity 2,500/s, arrival 1,900/s. Drain time?

Answer: Spare 600/s; 600,000 / 600 = 1,000 s = 16.7 minutes.

8. (medium, find the bug) A test report says: "average latency 120 ms, so we pass the SLO of p99 under 300 ms." What is wrong?

Answer: The mean does not say anything about p99. In queueing systems p99 can be 4 to 5 times the mean (in our run 4.5 times at 80% utilization), so p99 could be around 540 ms. Report the p99 itself.

9. (hard) An endpoint costs 2.40 per hour per node (illustrative) and handles 300 requests/s at full load. Average real load is 30% of that. Cost per 1,000 predictions at full load and at the real load?

Answer: Full load: 2.40 / (300 × 3,600) × 1,000 = 2.40 / 1,080 = 0.00222. At 30% load the node serves 90/s: 2.40 / (90 × 3,600) × 1,000 = 2.40 / 324 = 0.00741. That is 3.33 times higher (1 / 0.3).

10. (interview) Your Kafka consumer's lag is stable at 0 during the day but climbs to 2 million every evening for an hour. What do you do?

Answer: The evening peak exceeds capacity. Measure peak arrival and per-consumer rate, compute consumers needed at 70% utilization, check partitions (raise if needed before the evening), look for a slow sink or hot key at that hour, add scheduled autoscaling before the peak, and verify drain time with a spike test. Lag that returns to zero means the system is stable overall; the question is whether the delay is acceptable for the business.

11. (interview) Describe your best performance finding and how it applies to data engineering.

Answer: (Model structure) Situation: a release with a slow response at peak. Action: found a connection pool exhausted using Little's law (arrival rate times latency exceeded the pool size), measured, fixed, and retested. Result: a number, such as p99 from 2.1 s to 600 ms. Link: the same method sizes consumer groups, warehouse concurrency and ML replicas.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and English is my second language. Teach me
Little's law and the utilization–latency curve using a Kafka consumer as
the example. Use real numbers, explain why latency rises sharply near 100%
utilization, and why p99 is bigger than the mean. Then give me 8 graded
numeric exercises without solutions.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am learning data engineering. Topic: load
testing a data pipeline and a Kafka consumer. Help me write a test plan
with SLO, workload model (rate, message size, key distribution), ramp,
steady, spike, soak and chaos tests, the metrics to record per stage, and
how to prove no data loss. Ask me clarifying questions first. My pipeline
description: [PASTE HERE]
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Teach me to load test an ML inference endpoint:
latency percentiles, batch size, cold start, GPU utilization, autoscaling,
and cost per 1,000 predictions. Give me a case with numbers, let me
compute replicas and daily cost with and without autoscaling, and check my
arithmetic. My answers: [PASTE HERE]
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am planning a data engineering portfolio.
Review my capstone project idea against this structure: problem,
architecture, how to run, measured results, bottleneck table, cost model,
what I would change. Suggest the 3 changes that would impress a hiring
manager most, and rewrite my resume bullet with measured numbers. My
project: [PASTE HERE]
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles, and I am applying for data engineer roles in
India. Run a mock interview covering the whole data engineering document:
```

```
modeling, file formats, ingestion and CDC, quality, Airflow, dbt, Spark
tuning, Kafka and streaming, infrastructure, governance, system design and
performance. Ask 10 questions one at a time, mixing easy and hard. After
each answer give a score from 1 to 5, a model answer in simple English,
and one follow-up. My answers: [PASTE HERE]
```

CHAPTER 15

PROJECT LAB 1: PIPELINES, LAKES, BATCHES, LOADERS AND MODELS

Five portfolio projects, with a full method for running any data engineering project from question to LinkedIn post.

Reading about pipelines makes you informed. Building them makes you hireable. A hiring manager for a data engineering role will rarely ask "do you know what a watermark is?" They will ask "show me something you built and tell me what broke." This chapter gives you the method to run a project properly (plan, layout, commits, definition of done, README, post), and then five complete projects with code that was really run. Every project uses neutral datasets (shop orders, delivery times, customers) that you generate yourself, so you never wait for a download or worry about licences. By the end you will have five repositories you can show, and an honest answer to "what went wrong and how did you find it?"

A note on honesty. Real Airflow, Docker, Spark and dbt cannot run in this learning environment. For each of those tools we ran a **pure-Python stand-in** that teaches the same idea, and we show the real tool's files labelled "not run here". Everything else (the scripts, the outputs, the tests) was run with Python 3 standard library and sqlite3. The scripts live in `/tmp/lab_de/` on the machine that built this chapter; copy them out of the chapter text.

15.1 How to Run a Project in This Area

INTUITION

Building a house without a plan gives you rooms that do not connect. Building a data project without a plan gives you a notebook of cells that only work in one order on one day. A plan, a tidy layout and a "finished" checklist are the blueprint, the street numbers and the inspection certificate of your project.

Step 1: Plan the question and the success criteria

Write one sentence: "Given X data, produce Y table so that Z person can decide W." Then write 3 to 5 **measurable** success criteria before you write code. Example for a delivery-times pipeline: "Loads 10,000 records in under 2 minutes; rerunning loads zero duplicates; a failed API call is

retried 3 times; a data-quality failure stops the publish step."

Weak goal	Strong goal
"Build an ETL"	"Load daily orders into a table; second run changes 0 rows"
"Make it fast"	"Partitioned read scans 20% of the rows of a full scan"
"Add tests"	"5 tests; one of them proves a late row is not lost"

Step 2: Repo layout

```
project-name/
  README.md              # the front door (template below)
  Makefile               # make run, make test
  requirements.txt       # pinned versions
  src/
    extract.py           # one job per file, small functions
    transform.py
    load.py
    config.py            # paths, thresholds, no secrets
  data/
    raw/                 # never edited by hand
    clean/
  tests/
    test_transform.py
  sql/                   # queries and DDL as .sql files
  docs/
    architecture.png     # or an ASCII diagram in the README
    lessons_learned.md
  .gitignore             # data/, .env, __pycache__
```

Step 3: Environment and dependencies

Use a virtual environment (`python3 -m venv .venv`), list packages in `requirements.txt` with versions, and keep secrets in environment variables, never in git. A `.env.example` with fake values tells others what to set. For projects with Docker, a `docker-compose.yml` lets anyone start your stack with one command (not run here).

Step 4: Data sourcing or generation

Prefer a **generator with a fixed seed** (`random.Random(7)`). It is free, needs no licence, and

makes outputs reproducible: you can write "loads 23 rows" in the README and it is always true. Add deliberate dirt (duplicates, nulls, negative amounts, late rows) because the dirt is what makes the project interesting. If you use a public dataset, record its URL, licence and download date in the README.

Step 5: Commit rhythm and messages

Commit after every working step, not at the end of the week. Small commits let you go back when something breaks and show a reviewer how you think.

Bad message	Good message
`update`	`Add retry with backoff to API extract`
`fix`	`Fix watermark compare: use T separator, not space`
`final version`	`Add test: late row lost without overlap window`

A good message says what changed, and for a bug, why. Keep the first line under about 70 characters.

Step 6: Definition of done

A project is done when all of these are true: a fresh clone runs with 2 commands; all tests pass; rerunning the pipeline is **idempotent** (same result, no duplicates); the README has a diagram, results and limits; failures are visible (a log line or alert), not silent; you can explain every design choice in 2 minutes.

Step 7: README template

```
# Project title: one-line outcome

## Problem
Who needs what, in one paragraph.

## Architecture
(diagram or ASCII flow: source -> stages -> target)

## How to run
    python3 -m venv .venv && source .venv/bin/activate
    pip install -r requirements.txt
    make run && make test

## Results
Table of measured numbers (rows loaded, runtime, test count).

## Design decisions
Why sqlite, why upsert, why a watermark with overlap.

## What went wrong
Two bugs you hit and how you found them.

## Limits and next steps
What this does not do; three extensions.
```

Step 8: Demo and deploy options

All free: a screen recording (2 minutes) of `make run` and the result; a GitHub README with a diagram and screenshot; a scheduled run through GitHub Actions (not run here); a small Streamlit or static HTML page showing the report. Never publish real company data or secrets.

Step 9: Writing the LinkedIn or blog post

Use this shape: (1) the problem in one sentence; (2) what you built, with one diagram; (3) one number ("rerun loads 0 duplicates"); (4) the bug that surprised you and what you learnt; (5) link to the repo. Write it in simple words; do not claim what you did not measure.

Step 10: Testing and debugging checklist for data projects

- Run twice. Does the second run change anything? (idempotency)
- Compare counts at each stage: raw, clean, loaded. Can you explain every difference?
- Reconcile totals: sum of amount in the report equals sum in the clean data.

- Feed an empty input. Feed one bad row. Feed a duplicate. What happens?
- Kill the job halfway. Is the target left half-written?
- Check time handling: time zones, string versus timestamp comparison.
- Log row counts and durations for every stage.

REAL JOB TIP

Teams hire for the habit of checking. In every project, write down at least one check that failed on purpose and shows the pipeline noticing. That one sentence is more convincing than a long list of tools.

15.2 Project: API to Scheduler to Database Pipeline in Containers

Goal and why employers care

Pull data from an API every day, store it safely in a database, survive failures, and never load the same record twice. This is the most common data engineering task in the world. Employers care because real APIs fail at 2 a.m., and a pipeline that cannot retry or rerun safely wakes people up.

Skills used

Ingestion Patterns (Chapter 4: retries, idempotent loads, upsert), Orchestration with Airflow (Chapter 6: tasks, schedules, retries, backfill), Infrastructure and DataOps (Chapter 12: containers).

Data

A fake delivery API that we write ourselves. It returns 5 delivery records per day and **fails on the first two calls** to simulate a flaky service. The data is seeded by the day, so a rerun gets identical records.

Architecture

```
 +----------+     +-------------+     +--------------+     +-----------+
 | Fake API | --> | Extract     | --> | Load         | --> | sqlite3   |
 | (flaky)  |     | retry+back- |     | upsert on    |     | deliveries|
 +----------+     | off         |     | primary key  |     | runs      |
                  +-------------+     +--------------+     +-----------+
                         ^
                  +--------------+
                  | Scheduler:   |  for each day: skip if runs.status='ok'
                  | loop + state |
                  +--------------+
 Containers (not run here): one container for the job, one for the
database.
```

Step-by-step build

1. **Write the fake API** with a counter so the first two calls raise `ConnectionError`.
2. **Write** `with_retry`: try up to 4 times, wait `base_delay * 2^(n-1)` between tries (exponential backoff: wait longer each time so a struggling service can recover).
3. **Write an idempotent** `load`: `INSERT ... ON CONFLICT(delivery_id) DO UPDATE`. Idempotent means running it twice gives the same result as once.
4. **Write the scheduler**: for each day, check the `runs` table; if status is `ok` skip, else extract, load and record the status.
5. **Run it twice** and show the second run skips everything.

Before you run it: how many rows will the table hold after two days, and what will the second run print?

```
import sqlite3, time, random

class FakeAPI:
    def __init__(self): self.calls = 0
    def get_deliveries(self, day):
        self.calls += 1
        if self.calls <= 2:
            raise ConnectionError("503 service unavailable")
        rnd = random.Random(day)
        return [{"delivery_id": f"{day}-{i}", "city": rnd.choice(["Pune",
"Delhi", "Chennai"]),
                 "minutes": rnd.randint(20, 90)} for i in range(5)]

def with_retry(fn, attempts=4, base_delay=0.01):
    for n in range(1, attempts + 1):
```

```
        try:
            return fn()
        except ConnectionError as e:
            print(f"  attempt {n} failed: {e}")
            if n == attempts: raise
            time.sleep(base_delay * 2 ** (n - 1))

def load(db, rows):
    db.executemany("""INSERT INTO deliveries(delivery_id, city, minutes)
        VALUES(:delivery_id,:city,:minutes)
        ON CONFLICT(delivery_id) DO UPDATE SET city=excluded.city,
minutes=excluded.minutes""", rows)
    db.commit()

def run_scheduler(db, api, days):
    for day in days:
        if db.execute("SELECT 1 FROM runs WHERE day=? AND status='ok'",
(day,)).fetchone():
            print(f"{day}: already done, skip"); continue
        print(f"{day}: running")
        try:
            rows = with_retry(lambda: api.get_deliveries(day))
            load(db, rows)
            db.execute("INSERT OR REPLACE INTO runs VALUES(?,?,?)", (day,
"ok", len(rows)))
        except Exception:
            db.execute("INSERT OR REPLACE INTO runs VALUES(?,?,?)", (day,
"failed", 0))
        db.commit()

db = sqlite3.connect(":memory:")
db.executescript("""CREATE TABLE deliveries(delivery_id TEXT PRIMARY KEY,
city TEXT, minutes INT);
                    CREATE TABLE runs(day TEXT PRIMARY KEY, status TEXT,
rows INT);""")
api = FakeAPI(); days = ["2024-06-01", "2024-06-02"]
run_scheduler(db, api, days)
print("--- run again (idempotent) ---")
run_scheduler(db, api, days)
print(db.execute("SELECT COUNT(*) FROM deliveries").fetchone(),
db.execute("SELECT * FROM runs").fetchall())
```

Real output:

```
2024-06-01: running
  attempt 1 failed: 503 service unavailable
  attempt 2 failed: 503 service unavailable
2024-06-02: running
--- run again (idempotent) ---
2024-06-01: already done, skip
2024-06-02: already done, skip
(10,) [('2024-06-01', 'ok', 5), ('2024-06-02', 'ok', 5)]
```

Explain: the first day needed three tries (two failures, then success on the third). The second day worked first time. The rerun skipped both days because `runs` remembered them. The table holds 10 rows, not 20.

Now the real files, **not run here**. A minimal Airflow DAG (Airflow 2.x style; check your version's docs because import paths change):

```
# dags/deliveries.py  (not run here)
from datetime import datetime, timedelta
from airflow import DAG
from airflow.operators.python import PythonOperator

with DAG("deliveries", start_date=datetime(2024, 6, 1), schedule="@daily",
catchup=True,
         default_args={"retries": 3, "retry_delay": timedelta(minutes=2)})
as dag:
    PythonOperator(task_id="extract_load", python_callable=lambda ds:
print("run for", ds))
```

```
# docker-compose.yml  (not run here)
services:
  db:
    image: postgres:16
    environment: { POSTGRES_PASSWORD: example_only }
  job:
    build: .
    depends_on: [db]
    environment: { DB_HOST: db }
```

Evaluation and acceptance criteria

- Two injected failures lead to 0 lost days (retry works).
- Rerunning loads 0 new rows; row count stays 10.

- A day that fails 4 times is recorded `failed` and is retried on the next run.
- Test: delete a `runs` row, rerun, row count still 10 (upsert protects you).

Common pitfalls

1. **Plain INSERT instead of upsert.** Detect: rerun, count doubles or the primary key error stops the job.
2. **Retrying forever.** Detect: a dead API makes the job hang. Cap attempts.
3. **Marking success before the load commits.** Detect: kill the process between steps; a day shows `ok` with no rows.
4. **Retrying errors that can never succeed (a 400 bad request).** Retry only transient errors.
5. **Secrets in `docker-compose.yml` committed to git.** Detect: `git grep -i password`.

Three extensions

1. Add a backfill command: `--from 2024-01-01 --to 2024-03-31`.
2. Add an alert (print or email stub) when a day ends `failed`.
3. Swap sqlite for Postgres in the compose file (not run here).

Interview talking points

Q1. Why must a pipeline be idempotent? Because pipelines get rerun: after failures, backfills or mistakes. If a rerun creates duplicates, every report becomes wrong. Upsert on a key makes "run it again" safe.

Q2. Why exponential backoff? If a service is struggling and all clients retry at once, it gets worse. Waiting longer each time gives it room to recover.

Q3. What does the scheduler remember, and where? It keeps a `runs` table: day and status. That is the pipeline's memory, so a restart does not redo finished days.

README outline

Problem, ASCII diagram, how to run, the failure story (two 503s), idempotency proof (count stays 10), design decisions, limits, extensions.

15.3 Project: End-to-End Cloud-Style Pipeline

Goal and why employers care

Take messy files from a "raw" zone, clean them, build warehouse tables, and produce a report, with a reconciliation check at the end. Cloud teams build exactly this shape every day (a lake plus a warehouse). Showing you understand the zones, and can map them to cloud services, makes you credible without paying a cloud bill.

Skills used

Data Lifecycle and Architectures (Chapter 1: zones, ELT), Data Modeling (Chapter 2: dimension and fact tables), File Formats and Storage (Chapter 3), Warehouses and Cloud (Chapter 8: services), Data Quality and Testing (Chapter 5: reconciliation).

Data

A generator makes 20 orders with dirt: a missing amount, a negative amount, mixed-case names (`asha` , `RAVI` , `Meena`), plus 3 duplicated rows appended.

Architecture and cloud mapping

```
 raw/orders.csv --> clean/orders.json --> warehouse.db -->
report/revenue_by_customer.csv
   (as received)     (typed, deduped)     (dim + fact)       (for the
business)
```

Local stand-in	Generic cloud service type	Examples (names vary)
Folder `raw/` , `clean/`	Object storage	S3, Cloud Storage, Blob Storage
`clean.py` script	Serverless function or batch job	Lambda, Cloud Functions, Glue
`warehouse.db`	Cloud data warehouse	Redshift, BigQuery, Synapse, Snowflake
The run order	Orchestrator	Airflow, Step Functions, Data Factory
Report CSV	BI source	Dashboard tool reading a table

Step-by-step build

1. Generate `raw/orders.csv` (never edited again).
2. Raw to clean: reject duplicates, empty amounts and negative amounts; title-case names; write JSON.
3. Clean to warehouse: `dim_customer(customer_key, name)` and `fact_orders(order_id, customer_key, amount, date)`.
4. Warehouse to report: join and aggregate to CSV.
5. Reconcile: assert report total equals clean total.

```
import csv, json, random, sqlite3, shutil, pathlib
root = pathlib.Path("/tmp/lab_de/lake"); shutil.rmtree(root,
ignore_errors=True)
for z in ("raw", "clean", "report"): (root / z).mkdir(parents=True)

rnd = random.Random(7); rows = []
for i in range(1, 21):
    rows.append({"order_id": f"O{i}", "customer":
rnd.choice(["asha","RAVI","Meena"]),
                 "amount": rnd.choice([250, 480, 120, 99, -5, ""]),
"date": f"2024-06-0{rnd.randint(1,3)}"})
rows += rows[:3]
with open(root/"raw/orders.csv", "w", newline="") as f:
    w = csv.DictWriter(f, fieldnames=rows[0].keys()); w.writeheader();
w.writerows(rows)

seen, clean, rejected = set(), [], 0
for r in csv.DictReader(open(root/"raw/orders.csv")):
    if r["order_id"] in seen or r["amount"] == "" or float(r["amount"]) <
0:
        rejected += 1; continue
    seen.add(r["order_id"])
    clean.append({"order_id": r["order_id"], "customer":
r["customer"].title(),
                  "amount": float(r["amount"]), "date": r["date"]})
json.dump(clean, open(root/"clean/orders.json", "w"))
print("raw rows", len(rows), "clean rows", len(clean), "rejected",
rejected)

db = sqlite3.connect(root/"warehouse.db")
db.executescript("""CREATE TABLE dim_customer(customer_key INTEGER PRIMARY
KEY, name TEXT UNIQUE);
  CREATE TABLE fact_orders(order_id TEXT PRIMARY KEY, customer_key INT,
amount REAL, date TEXT);""")
```

```
for r in clean:
    db.execute("INSERT OR IGNORE INTO dim_customer(name) VALUES(?)",
(r["customer"],))
    key = db.execute("SELECT customer_key FROM dim_customer WHERE name=?",
(r["customer"],)).fetchone()[0]
    db.execute("INSERT INTO fact_orders VALUES(?,?,?,?)", (r["order_id"],
key, r["amount"], r["date"]))
db.commit()
res = db.execute("""SELECT c.name, COUNT(*), SUM(f.amount) FROM
fact_orders f
    JOIN dim_customer c USING(customer_key) GROUP BY c.name ORDER BY 3
DESC""").fetchall()
with open(root/"report/revenue_by_customer.csv", "w", newline="") as f:
    w = csv.writer(f); w.writerow(["customer","orders","revenue"]);
w.writerows(res)
print(open(root/"report/revenue_by_customer.csv").read())
assert sum(r[2] for r in res) == sum(r["amount"] for r in clean)
print("reconciled:", sum(r["amount"] for r in clean))
```

Real output:

```
raw rows 23 clean rows 13 rejected 10
customer,orders,revenue
Meena,5,1710.0
Asha,4,1460.0
Ravi,4,1309.0

reconciled: 4479.0
```

Explain: 23 raw rows became 13 clean rows. The 10 rejected rows include the duplicates and the bad amounts. A good project explains every rejected row: add a `rejected/` file with a reason column (see extension 1). The totals match across clean, warehouse and report, which proves nothing leaked in the joins.

Evaluation and acceptance criteria

- `raw + clean + rejected` row counts reconcile exactly (23 = 13 + 10).
- Report total equals clean total (4479.0).
- Rerun from scratch gives identical output (seeded generator).
- Raw file is byte-identical before and after the pipeline.

Common pitfalls

1. **Editing raw data.** Detect: hash the raw file before and after.
2. **Case-sensitive keys** (`asha` versus `Asha` make two customers). Detect: `COUNT(DISTINCT name)` versus `COUNT(DISTINCT LOWER(name))` .
3. **Join fan-out** (duplicate dimension keys multiply fact rows). Detect: reconciliation assert.
4. **Silent rejection.** Detect: always print and store the rejected count.
5. **Treating empty string as zero.** Detect: null and empty checks on the clean layer.

Three extensions

1. Write rejected rows with a reason column to `rejected/orders.csv` .
2. Save the clean layer as partitioned folders `clean/date=2024-06-01/` (see Chapter 3).
3. Add a freshness check and a one-line email-style alert on failure.

Interview talking points

Q1. Why keep raw data untouched? If your cleaning rule has a bug, you can fix it and replay from raw. If you edited raw, the original is lost.

Q2. What is reconciliation? Comparing totals between stages. If the sum changes where it should not, a join or filter is wrong.

Q3. How would this map to the cloud? Raw and clean folders become buckets in object storage, the cleaning script becomes a batch job, the tables sit in a cloud warehouse, and an orchestrator runs the steps in order.

README outline

Problem, zone diagram, cloud mapping table, row-count reconciliation table, how to run, bugs found, limits (single machine, no schema evolution).

15.4 Project: Large Batch Processing with Spark-Style Partitioning

Goal and why employers care

Process 1.2 million delivery records by splitting the data into partitions, aggregating each partition on its own, then combining the partial results. This is what Spark does across machines. Employers care because "my job is slow" is nearly always about partitions, skew and

how much data moves.

Skills used

Spark and PySpark (Chapter 9: partitions, map and reduce, aggregation), Spark Performance (Chapter 10: skew, shuffle), File Formats and Storage (Chapter 3: partitioning).

Data

A generator creates 1,200,000 `(city, minutes)` rows with 5 cities and values 20 to 120.

Architecture

```
 rows --hash(city) mod 8--> 8 partitions --map_task each--> partial
(sum,count)
                                                    \--> reduce: add
partials --> averages
```

Step-by-step build

1. Generate rows (seed 1).
2. Hash-partition by city with `zlib.crc32` (Python's `hash()` for strings changes between runs; `crc32` is stable).
3. Map: each partition returns partial `sum` and `count` per city.
4. Reduce: add partials, divide.
5. Compare with a single-process answer; they must be equal.
6. Time both. Then create a skewed dataset and look at partition sizes.

Predict: will 4 workers be faster than 1 process?

```
import random, time, zlib
from multiprocessing import Pool
from collections import Counter
N, P = 1_200_000, 8
def make_rows(n):
    rnd = random.Random(1); cities =
["Pune","Delhi","Chennai","Mumbai","Kolkata"]
    return [(rnd.choice(cities), rnd.randint(20, 120)) for _ in range(n)]
def partition(rows, p):
    parts = [[] for _ in range(p)]
    for city, m in rows: parts[zlib.crc32(city.encode()) %
p].append((city, m))
    return parts
def map_task(part):
    s, c = Counter(), Counter()
    for city, m in part: s[city] += m; c[city] += 1
    return s, c
def reduce_all(results):
    S, C = Counter(), Counter()
    for s, c in results: S.update(s); C.update(c)
    return {k: round(S[k] / C[k], 2) for k in sorted(S)}
if __name__ == "__main__":
    rows = make_rows(N); parts = partition(rows, P)
    print("partition sizes:", [len(x) for x in parts])
    t = time.perf_counter(); serial = reduce_all([map_task(rows)]); t1 =
time.perf_counter() - t
    t = time.perf_counter()
    with Pool(4) as pool: par = reduce_all(pool.map(map_task, parts))
    t2 = time.perf_counter() - t
    print("serial  ", serial); print("parallel", par)
    assert serial == par
    print(f"results equal; serial {t1:.2f}s, 4 workers {t2:.2f}s")
    skew = [("Pune", 50)] * 900_000 + rows[:100_000]
    print("skewed partition sizes:", [len(x) for x in partition(skew, P)])
```

Real output (timings differ per machine):

```
partition sizes: [239127, 0, 240420, 240561, 239603, 0, 0, 240289]
serial   {'Chennai': 70.09, 'Delhi': 69.96, 'Kolkata': 70.05, 'Mumbai':
69.97, 'Pune': 69.97}
parallel {'Chennai': 70.09, 'Delhi': 69.96, 'Kolkata': 70.05, 'Mumbai':
69.97, 'Pune': 69.97}
results equal; serial 0.17s, 4 workers 0.56s
skewed partition sizes: [19528, 0, 20134, 920111, 20039, 0, 0, 20188]
```

Explain, three lessons. (1) The results are equal: splitting and combining partial sums is correct. Note we combine **sums and counts**, not averages; averaging averages is wrong when partitions differ in size. (2) The 4-worker run was **slower** (0.56 s versus 0.17 s). Sending 1.2 million tuples to other processes costs more than the tiny work saved. Parallelism pays only when the work per row is heavy or the data is already where the workers are (as in Spark, where data sits on the workers). (3) Three of 8 partitions are empty because there are only 5 distinct cities: partitioning by a low-cardinality key wastes workers. In the skewed run one partition holds 920,111 rows, so the whole job waits for that one task. That is **data skew**.

PySpark equivalent, **not run here**:

```
from pyspark.sql import SparkSession, functions as F
spark = SparkSession.builder.appName("deliveries").getOrCreate()
df = spark.read.parquet("deliveries/")
out = df.repartition(8,
"city").groupBy("city").agg(F.avg("minutes").alias("avg_min"))
out.write.mode("overwrite").parquet("out/avg_by_city")
```

Evaluation and acceptance criteria

- Parallel result equals serial result for all cities (assert passes).
- You can state why parallel was slower, with the measured numbers.
- A skew report prints the largest partition divided by the average (here 920,111 / 125,000 is about 7.4, because 1,000,000 rows over 8 partitions average 125,000).
- A fix for skew is tried and measured (extension 1).

Common pitfalls

1. **Averaging averages.** Detect: compare with the single-process answer.
2. **Python `hash()` for partitioning.** Detect: the result changes between runs; use `crc32`.
3. **Low-cardinality partition key.** Detect: print partition sizes; empty ones appear.
4. **Assuming parallel is always faster.** Detect: time both.
5. **Forgetting the `if __name__ == "__main__"` guard** with multiprocessing. Detect: on some systems the script re-launches itself or errors.

Three extensions

1. Fix skew by **salting**: add a random suffix 0 to 3 to the hot key, aggregate, then merge the

salts.

2. Use `chunksize` and larger work per row to find when 4 workers beat 1.
3. Write each partition to its own file and read back only one (partition pruning).

Interview talking points

Q1. What is a partition? A slice of the data that one task can process alone. More partitions let more workers run at once.

Q2. What is skew and how do you fix it? One key has far more rows than others, so one task runs long. Fix by salting the key, by filtering the hot key out and handling it separately, or by picking a better key.

Q3. Why did your parallel run lose? The cost of moving data between processes was bigger than the work. Spark avoids this by moving the code to the data.

README outline

Problem, partition diagram, the three lessons with numbers, skew chart (table), how to run, PySpark mapping, limits.

15.5 Project: Incremental ETL Loader with Watermarks and Tests

Goal and why employers care

Load only what is new or changed since the last run, using a **watermark** (a saved bookmark: "I have loaded everything up to this timestamp"). Full reloads waste time and money once tables are large. A loader with tests that prove it never loses or duplicates data is the single most convincing small project in this field.

Skills used

Ingestion Patterns (Chapter 4: full versus incremental, upsert), Data Quality and Testing (Chapter 5: unit tests), Data Modeling (Chapter 2: keys).

Data

Two tables made by the script: `src_orders` (source) and `tgt_orders` (target), plus a

`watermark` table. Test rows are inserted by each test.

Architecture

```
 src_orders --WHERE updated_at > watermark--> upsert --> tgt_orders
                                                  |
                                  new watermark = MAX(updated_at) of
loaded rows
```

Step-by-step build

1. Create the three tables; seed the watermark with `1970-01-01T00:00:00` .
2. Write `incremental_load(db, overlap_minutes)` .
3. Write four tests (first load takes all; second run loads nothing; an update replaces, not duplicates; a late row is lost without overlap but saved with it).
4. Run the tests. We first wrote the filter with SQLite's `datetime()` , and **two tests failed**. Here is the real failure:

```
FAIL: test_second_run_loads_nothing
AssertionError: 1 != 0
FAIL: test_late_row_is_lost_without_overlap
AssertionError: 2 != 0
```

Why: `datetime('2024-06-01T10:00:00','-0 minutes')` returns `2024-06-01 10:00:00` with a **space**, but our stored timestamps use a **T**. When compared as text, `T` is greater than a space, so every row looked newer than the watermark and was reloaded. The fix is to format the result with `strftime('%Y-%m-%dT%H:%M:%S', ...)` so both sides use the same format.

```
import sqlite3, unittest

def setup():
    db = sqlite3.connect(":memory:")
    db.executescript("""
    CREATE TABLE src_orders(order_id TEXT PRIMARY KEY, amount REAL,
updated_at TEXT);
    CREATE TABLE tgt_orders(order_id TEXT PRIMARY KEY, amount REAL,
updated_at TEXT);
    CREATE TABLE watermark(name TEXT PRIMARY KEY, value TEXT);
    INSERT INTO watermark VALUES('orders','1970-01-01T00:00:00');""")
```

```
    return db

def incremental_load(db, overlap_minutes=0):
    wm = db.execute("SELECT value FROM watermark WHERE
name='orders'").fetchone()[0]
    rows = db.execute("""SELECT order_id, amount, updated_at FROM
src_orders
        WHERE updated_at > strftime('%Y-%m-%dT%H:%M:%S', ?, ?)""",
        (wm, f"-{overlap_minutes} minutes")).fetchall()
    if not rows: return 0
    db.executemany("""INSERT INTO tgt_orders VALUES(?,?,?) ON
CONFLICT(order_id)
        DO UPDATE SET amount=excluded.amount,
updated_at=excluded.updated_at""", rows)
    db.execute("UPDATE watermark SET value=? WHERE name='orders'",
(max(r[2] for r in rows),))
    db.commit()
    return len(rows)

class T(unittest.TestCase):
    def test_second_run_loads_nothing(self):
        db = setup()
        db.execute("INSERT INTO src_orders VALUES('O1',100,'2024-06-
01T10:00:00')")
        incremental_load(db)
        self.assertEqual(incremental_load(db), 0)
    def test_update_is_picked_up_not_duplicated(self):
        db = setup()
        db.execute("INSERT INTO src_orders VALUES('O1',100,'2024-06-
01T10:00:00')")
        incremental_load(db)
        db.execute("UPDATE src_orders SET amount=150, updated_at='2024-06-
02T09:00:00' WHERE order_id='O1'")
        incremental_load(db)
        self.assertEqual(db.execute("SELECT COUNT(*), MAX(amount) FROM
tgt_orders").fetchone(), (1, 150.0))
    def test_late_row_is_lost_without_overlap(self):
        db = setup()
        db.execute("INSERT INTO src_orders VALUES('O1',100,'2024-06-
01T10:00:00')")
        incremental_load(db)
        db.execute("INSERT INTO src_orders VALUES('O2',50,'2024-06-
01T09:55:00')")  # committed late
        self.assertEqual(incremental_load(db, overlap_minutes=0), 0)    #
lost!
        self.assertEqual(incremental_load(db, overlap_minutes=10), 2)   #
overlap rescues it
```

```
        self.assertEqual(db.execute("SELECT COUNT(*) FROM
tgt_orders").fetchone()[0], 2)
if __name__ == "__main__":
    unittest.main(verbosity=2)
```

Real output after the fix (the full file also has `test_first_load_takes_all`):

```
test_first_load_takes_all (__main__.T.test_first_load_takes_all) ... ok
test_late_row_is_lost_without_overlap
(__main__.T.test_late_row_is_lost_without_overlap) ... ok
test_second_run_loads_nothing (__main__.T.test_second_run_loads_nothing)
... ok
test_update_is_picked_up_not_duplicated
(__main__.T.test_update_is_picked_up_not_duplicated) ... ok

Ran 4 tests in 0.001s
OK
```

Explain the overlap test. Order O2 was written to the source at a later moment but carries an earlier timestamp (09:55). A strict "newer than watermark" filter never sees it, so it is **lost forever**. A 10-minute overlap re-reads a small window each run; because the load is an upsert, re-reading rows already loaded is harmless. Overlap plus upsert is the standard safe pattern.

Evaluation and acceptance criteria

- 4 of 4 tests pass; at least one test was written to fail first.
- Second run returns 0 rows loaded.
- After an update at source, target count stays 1 and the amount is the new one.
- Target equals source after a full compare (`EXCEPT` query returns 0 rows).

Common pitfalls

1. **Timestamp format mismatch** (space versus T). Detect: second run loads rows again.
2. **Using the load time as the watermark** instead of the max source time. Detect: rows written during the run are skipped.
3. **No overlap for late commits.** Detect: the late-row test.
4. **Deletes at source are invisible** to a watermark. Detect: compare counts; use soft-delete flags.
5. **Updating the watermark before the load commits.** Detect: kill the run mid-way; rows are

missing on rerun.

Three extensions

1. Add a `--full-refresh` flag that resets the watermark.
2. Handle deletes with an `is_deleted` column.
3. Log rows loaded, watermark before and after to a `load_log` table.

Interview talking points

Q1. What is a watermark in batch loading? A saved bookmark of how far we have loaded, usually the highest `updated_at`. Next run loads only newer rows.

Q2. How do you avoid losing late rows? Re-read a small overlap window and use an upsert, so repeats are harmless.

Q3. What bug did you find? A text comparison between two time formats: space versus T. Tests caught it because the second run loaded rows again.

README outline

Problem, flow diagram, test table, the format bug story, design decisions, limits (deletes), extensions.

15.6 Project: dbt-Style Project, Staging to Marts with Tests and Docs

Goal and why employers care

Organise SQL as small, named, tested models that depend on each other: **staging** models clean raw tables, a **fact** model joins them, and a **mart** answers a business question. dbt is the standard tool for this. Employers care because analytics engineering is a large share of data jobs, and "SQL in a folder with tests" is how modern teams work.

Skills used

dbt (Chapter 7: models, ref, tests, docs), Data Modeling (Chapter 2: staging, facts, marts), Data Quality and Testing (Chapter 5: unique and not-null tests).

Data

Raw tables created by the script: `raw_orders` (5 rows, one duplicated, mixed-case status) and `raw_customers` (3 rows).

Architecture

```
 raw_orders ---> stg_orders ----\
                                 >--> fct_orders --> mart_city_revenue
 raw_customers -> stg_customers -/
```

Step-by-step build

1. Store each model as SQL text with `{{ ref('name') }}` for dependencies.
2. Read the `ref` calls to build a dependency graph; sort it with `graphlib.TopologicalSorter` (so a model is built after what it needs).
3. Create each model as a view.
4. Run tests: `unique` and `not_null` as SQL counting bad rows.
5. Print docs: description and parents per model.

```
import re, sqlite3
from graphlib import TopologicalSorter
MODELS = {
 "stg_orders": "SELECT order_id, customer_id, CAST(amount AS REAL) AS
amount, LOWER(status) AS status FROM raw_orders",
 "stg_customers": "SELECT customer_id, UPPER(city) AS city FROM
raw_customers",
 "fct_orders": "SELECT o.order_id, o.customer_id, c.city, o.amount FROM {{
ref('stg_orders') }} o JOIN {{ ref('stg_customers') }} c
USING(customer_id) WHERE o.status = 'paid'",
 "mart_city_revenue": "SELECT city, COUNT(*) AS orders, SUM(amount) AS
revenue FROM {{ ref('fct_orders') }} GROUP BY city",
}
TESTS = [("stg_orders","order_id","unique"),
("stg_orders","order_id","not_null"),
         ("stg_customers","customer_id","unique"),
("fct_orders","customer_id","not_null"),
         ("mart_city_revenue","city","unique")]
DOCS = {"mart_city_revenue": "Paid revenue and order count per city. One
row per city."}
deps = lambda sql: set(re.findall(r"ref\('(\w+)'\)", sql))
render = lambda sql: re.sub(r"\{\{ ref\('(\w+)'\) \}\}", r"\1", sql)
```

```
db = sqlite3.connect(":memory:")
db.executescript("""
CREATE TABLE raw_orders(order_id TEXT, customer_id TEXT, amount TEXT,
status TEXT);
INSERT INTO raw_orders VALUES('O1','C1','250','PAID'),
('O2','C2','480','Paid'),('O3','C1','99','CANCELLED'),
('O4','C3','120','PAID'),('O4','C3','120','PAID');
CREATE TABLE raw_customers(customer_id TEXT, city TEXT);
INSERT INTO raw_customers VALUES('C1','pune'),('C2','delhi'),
('C3','pune');""")
order = list(TopologicalSorter({m: deps(s) for m, s in
MODELS.items()}).static_order())
print("build order:", order)
for m in order:
    db.execute(f"DROP VIEW IF EXISTS {m}"); db.execute(f"CREATE VIEW {m}
AS {render(MODELS[m])}")
def run_test(model, col, kind):
    sql = {"unique": f"SELECT COUNT(*) FROM (SELECT {col} FROM {model}
GROUP BY {col} HAVING COUNT(*)>1)",
           "not_null": f"SELECT COUNT(*) FROM {model} WHERE {col} IS
NULL"}[kind]
    return db.execute(sql).fetchone()[0]
for t in TESTS:
    bad = run_test(*t)
    print(f"  {'PASS' if bad == 0 else 'FAIL'} {t[2]}({t[0]}.{t[1]}) bad=
{bad}")
print("mart:", db.execute("SELECT * FROM mart_city_revenue ORDER BY
city").fetchall())
```

Real output:

```
build order: ['stg_orders', 'stg_customers', 'fct_orders',
'mart_city_revenue']
  FAIL unique(stg_orders.order_id) bad=1
  PASS not_null(stg_orders.order_id) bad=0
  PASS unique(stg_customers.customer_id) bad=0
  PASS not_null(fct_orders.customer_id) bad=0
  PASS unique(mart_city_revenue.city) bad=0
mart: [('DELHI', 1, 480.0), ('PUNE', 3, 490.0)]
```

Explain: the test **caught a real error**. Order O4 is duplicated in the raw data; the duplicate flows through to the mart, where Pune shows 3 orders worth 490.0. The correct answer is 2 orders worth 370.0 (O1 250 plus O4 120). The failing `unique` test on the staging model is the

early warning. The fix is a de-duplication step in `stg_orders` (for example `SELECT DISTINCT`, or keep the latest row per `order_id`).

Real dbt files, **not run here**:

```
-- models/staging/stg_orders.sql  (not run here)
select order_id, customer_id, cast(amount as float) as amount,
lower(status) as status
from {{ source('shop', 'raw_orders') }}
```

```
# models/staging/schema.yml  (not run here)
version: 2
models:
  - name: stg_orders
    description: "One row per order, cleaned."
    columns:
      - name: order_id
        tests: [unique, not_null]
```

Commands: `dbt run`, `dbt test`, `dbt docs generate`.

Evaluation and acceptance criteria

- Models build in dependency order; the build order is printed.
- After you fix staging, all 5 tests pass and Pune shows 2 orders, 370.0.
- Every mart has a description; every model lists its parents.
- Adding a test that fails makes the runner exit with a failure code (extension 1).

Common pitfalls

1. **Business logic in staging.** Detect: staging models should only rename, cast and clean.
2. **No test on the grain** (what one row means). Detect: unique test on the key.
3. **Circular `ref`.** Detect: `TopologicalSorter` raises `CycleError`.
4. **Joining before de-duplicating.** Detect: reconcile mart totals with raw.
5. **Case differences** (`PAID` versus `Paid`). Detect: `SELECT DISTINCT status`.

Three extensions

1. Make the runner `sys.exit(1)` when any test fails.

2. Add `accepted_values` and `relationships` tests.
3. Generate a Markdown docs page listing models, columns and tests.

Interview talking points

Q1. What does `ref` do? It names a dependency. The tool reads it to build models in the right order and to draw the lineage graph.

Q2. Why test staging models? Errors found early are cheap. A duplicate caught in staging does not poison the mart.

Q3. Staging versus mart? Staging cleans one source table. A mart combines cleaned tables to answer a business question.

README outline

Problem, lineage diagram, model table, test table, the duplicate-order story, dbt file mapping (not run here), limits.

Chapter recap

- A project starts with a measurable question and success criteria written before code.
- Use a seeded generator with deliberate dirt; reproducible numbers make the README true.
- Commit small and write messages that say what and why.
- Done means: fresh clone runs, tests pass, rerun is idempotent, failures are visible.
- Retries with backoff plus upserts plus a runs table make a pipeline safe to rerun.
- Keep raw untouched; reconcile counts and totals between every stage.
- Parallelism has a cost; skew and low-cardinality keys waste workers; combine sums and counts, not averages.
- Watermarks need an overlap window and an upsert; check timestamp formats.
- dbt-style models depend on each other with `ref`; tests at staging catch bad data early.

Pattern	Cheat-sheet line
Retry	`wait = base * 2**(n-1)`; cap attempts
Idempotent load	`INSERT ... ON CONFLICT(key) DO UPDATE`

Reconcile	`sum(report) == sum(clean)`
Stable hash	`zlib.crc32(key) % partitions`
Watermark	`WHERE updated_at > watermark - overlap`
Model order	`TopologicalSorter(deps).static_order()`

Practice set

1. (Easy) Why does the scheduler check the `runs` table before extracting? **Answer:** To skip days that already succeeded, so a rerun does no extra work and creates no duplicates.

2. (Easy) A retry waits 0.01 s, then 0.02 s, then 0.04 s. What is the pattern, and how long is the total wait for 4 attempts (3 waits)? **Answer:** Doubling (exponential backoff). Total 0.01 + 0.02 + 0.04 = 0.07 s.

3. (Easy) Raw has 23 rows, clean has 13, and 10 are rejected. Does that reconcile? **Answer:** Yes: 13 + 10 = 23. Every row is accounted for.

4. (Medium) Partition averages are 60 (100 rows) and 80 (300 rows). What is the overall average? Is (60+80)/2 right? **Answer:** (60 x 100 + 80 x 300) / 400 = (6000 + 24000) / 400 = 75. The simple average 70 is wrong because partitions differ in size.

5. (Medium) What is the output? `partition(rows, 8)` on 5 distinct cities showed `[239127, 0, 240420, ...]`. Why zeros? **Answer:** Only 5 distinct keys can fill at most 5 of 8 buckets, and several keys may collide; the empty buckets are idle workers.

6. (Medium, find the bug) The loader uses `WHERE updated_at > datetime(wm)` and reloads all rows every run. Why? **Answer:** `datetime()` outputs a space between date and time, stored values use `T`, and `T` sorts after a space, so every row looks newer. Use `strftime` with the same format.

7. (Interview) Explain idempotency in one minute using the delivery pipeline. **Answer (acceptance):** Running the job twice leaves 10 rows, not 20. Mention upsert on the primary key and the `runs` table, and give the proof (the count after the second run).

8. (Interview) Your dbt-style `unique` test fails on staging. What do you do? **Answer (acceptance):** Look at the duplicate rows, decide the rule (latest wins or exact duplicates), fix staging, rerun tests, and reconcile the mart against raw.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Help me plan a portfolio project on an API-to-
database pipeline with a scheduler, retries and idempotent loads (Chapter
15, Project Lab 1). Ask me 5 questions one at a time about my data source
and goals. Then write me a one-page plan with 4 measurable success
criteria, a repo tree, and a list of the 10 commits I should make. Explain
each choice in simple English and tell me what I should not build yet.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. I built an end-to-end pipeline with raw, clean,
warehouse and report stages using folders. Review my project like a hiring
manager. Here is my README and code: [PASTE HERE]. Check reconciliation
between stages, whether raw is untouched, naming, and test coverage. Give
me a ranked list of the 5 biggest improvements and one stronger success
criterion per improvement.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Teach me data skew and partitioning for batch jobs
(Chapter 15, Spark-style partitioning). Use a small example with 8
partitions and one hot key. Walk through salting step by step with real
numbers, then quiz me one question at a time, waiting for my answer before
you continue. Correct me gently and explain why a wrong answer is
tempting.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. My incremental loader with a watermark behaves
strangely: [DESCRIBE SYMPTOM AND PASTE CODE]. Help me debug it. Ask what I
observed, then give a checklist: timestamp formats, time zones, strict
versus inclusive comparison, overlap window, order of watermark update.
Make me predict the cause before you reveal it, then show a failing test
that proves it.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Run a mock interview about my dbt-style staging-
to-marts project. Ask 8 questions one at a time covering ref and lineage,
tests at each layer, de-duplication, grain, and what I would do when a
test fails. After each of my answers, score it out of 5, give a better
model answer in simple English, and then ask the next question.
```

CHAPTER 16

PROJECT LAB 2: QUALITY, STREAMING, STAR SCHEMAS AND STORAGE

Four more portfolio projects: a data-quality framework, windowed streaming, a star schema with history, and a storage benchmark.

The first lab chapter built pipelines that move data. This one builds projects that prove the data is trustworthy, that handle data arriving out of order, that keep history correct when customers change, and that measure how storage choices change size and speed. These are the projects that separate "I can copy a tutorial" from "I understand why". Follow the method in Chapter 15, section 15.1 (plan, layout, commits, definition of done, README, post, debugging checklist) for every project here. As before, all code was run with Python 3 standard library and sqlite3, using neutral datasets (hospital appointments, shop orders, customers). Real tools (Spark Structured Streaming, pyarrow) are shown as short snippets labelled "not run here".

16.1 Project: Data-Quality Framework with Alerts

Goal and why employers care

Write a small framework where each check is declared as data (a name, a SQL query, a severity and a threshold), run all checks, send alerts, and make a **stop or publish** decision. Employers care because bad data that reaches a dashboard destroys trust, and teams want engineers who build the safety net, not only the pipeline.

Skills used

Data Quality and Testing (Chapter 5: dimensions, severity, checks), Ingestion Patterns (Chapter 4: where to put checks), Orchestration with Airflow (Chapter 6: a failed check should fail the task).

Data

An `appointments` table with 6 hospital appointment rows and planted problems: a duplicate id (`A3` twice), a missing patient id, a negative wait time (-3) and an extreme wait time (500 minutes).

Architecture

```
 checks (declared) --> runner --> results list --> alert function (print /
email stub)
                                        |
                                        +--> JSON report --> decision: STOP
if any error-severity failure
```

Step-by-step build

1. Define a `Check` dataclass: `name`, `sql` (returns a number of bad rows or a bad fraction), `severity` (`error` or `warn`), `threshold` (the allowed value).
2. Write `run_checks(db, checks, alert)` that runs each query, compares to the threshold, records the result and calls `alert` on failure.
3. Add checks across the quality dimensions: uniqueness, completeness, validity, allowed values, volume, null rate.
4. Decide: any failed `error` check means STOP.
5. Save a JSON report for the run history.

Predict: which of the six checks fail, and does the pipeline stop?

```
import sqlite3, json
from dataclasses import dataclass

@dataclass
class Check:
    name: str; sql: str; severity: str
    threshold: float = 0

def run_checks(db, checks, alert):
    results = []
    for c in checks:
        bad = db.execute(c.sql).fetchone()[0]
        ok = bad <= c.threshold
        results.append({"check": c.name, "bad": bad, "ok": ok, "severity":
c.severity})
        if not ok: alert(c, bad)
    return results

alerts = []
def alert(c, bad): alerts.append(f"[{c.severity.upper()}] {c.name}: {bad}
bad (allowed {c.threshold})")
```

```
db = sqlite3.connect(":memory:")
db.executescript("""
CREATE TABLE appointments(appt_id TEXT, patient_id TEXT, wait_min REAL,
dept TEXT, booked_at TEXT);
INSERT INTO appointments VALUES
('A1','P1',15,'ENT','2024-06-01T09:00:00'),('A2','P2',40,'ENT','2024-06-
01T09:30:00'),
('A3','P3',-3,'CARDIO','2024-06-01T10:00:00'),
('A3','P3',25,'CARDIO','2024-06-01T10:00:00'),
('A4',NULL,500,'XRAY','2024-06-01T10:30:00'),('A5','P5',30,'ENT','2024-06-
01T11:00:00');""")
checks = [
 Check("appt_id unique", "SELECT COUNT(*)-COUNT(DISTINCT appt_id) FROM
appointments", "error"),
 Check("patient_id not null", "SELECT COUNT(*) FROM appointments WHERE
patient_id IS NULL", "error"),
 Check("wait_min in 0..240", "SELECT COUNT(*) FROM appointments WHERE
wait_min<0 OR wait_min>240", "warn"),
 Check("dept in known list", "SELECT COUNT(*) FROM appointments WHERE dept
NOT IN ('ENT','CARDIO','XRAY')", "error"),
 Check("row count >= 5", "SELECT CASE WHEN COUNT(*)>=5 THEN 0 ELSE 1 END
FROM appointments", "error"),
 Check("null rate patient_id <= 20%", "SELECT AVG(patient_id IS NULL) FROM
appointments", "warn", threshold=0.20),
]
res = run_checks(db, checks, alert)
for r in res: print(("PASS" if r["ok"] else "FAIL"), r["check"], r["bad"])
print("\nALERTS:"); print("\n".join(alerts))
errors = [r for r in res if not r["ok"] and r["severity"] == "error"]
print("\npipeline decision:", "STOP (publish blocked)" if errors else
"PUBLISH")
json.dump(res, open("dq_report.json", "w"), indent=1)
```

Real output:

```
FAIL appt_id unique 1
FAIL patient_id not null 1
FAIL wait_min in 0..240 2
PASS dept in known list 0
PASS row count >= 5 0
PASS null rate patient_id <= 20% 0.16666666666666666

ALERTS:
[ERROR] appt_id unique: 1 bad (allowed 0)
[ERROR] patient_id not null: 1 bad (allowed 0)
[WARN] wait_min in 0..240: 2 bad (allowed 0)

pipeline decision: STOP (publish blocked)
```

Explain: three checks fail. Two are errors, so the pipeline stops. The wait-time check is only a warning, so by itself it would alert and continue. The null-rate check passes because 1 of 6 rows is 16.7%, under the 20% allowance, even though the hard "not null" check fails: the two checks express two different policies (a strict rule and a tolerated rate). The wait-time check found 2 bad rows: the -3 and the 500.

Real orchestration wiring, **not run here**: in Airflow, raise an exception in the check task when `errors` is non-empty so the downstream publish task does not run.

Evaluation and acceptance criteria

- At least 8 checks across at least 5 quality dimensions.
- Each planted problem is found by at least one check (4 of 4).
- A clean table gives `PUBLISH` and zero alerts (add a test with good data).
- Severity logic is tested: warn-only failures do not stop the run.

Common pitfalls

1. **Everything is an error.** Teams then ignore alerts. Detect: alerts per week; if people mute the channel, severity is wrong.
2. **Checks that never fail.** Detect: break the data on purpose and see if it fires.
3. **Averages hiding bad rows.** Detect: count bad rows, not just a mean.
4. **Threshold copied without evidence.** Detect: base it on history (for example the last 30 row counts).
5. **Alert without detail.** Detect: can the person on call find the bad rows from the message?

Include the query or sample ids.

Three extensions

1. Add a freshness check (newest `booked_at` within 24 hours).
2. Store each run in a `dq_runs` table and alert when the row count falls 30% below the 7-day average.
3. Write bad rows to a `quarantine` table with the check name.

Interview talking points

Q1. Error versus warn? An error means the data is unsafe to publish, so stop. A warn means look at it soon but continue.

Q2. Where do you put checks? At the edges: after ingestion (is the source sane?) and before publishing (is the output sane?).

Q3. How do you stop alert fatigue? Few, meaningful alerts; clear severity; each alert says what broke and who owns it.

README outline

Problem, check table (name, dimension, severity), runner diagram, the sample output, how to add a check, limits, extensions.

16.2 Project: Streaming Windowed Aggregation with Late Events

Goal and why employers care

Sum order amounts per one-minute window from events that arrive **out of order**, and decide what to do with events that arrive too late. Streaming roles ask about event time, windows and watermarks in almost every interview, and few candidates have built one.

Skills used

Streaming and Kafka (Chapter 11: event time, windows, watermarks, late data), Data Quality and Testing (Chapter 5: counting dropped rows).

Data

Nine events as `(event_time_in_seconds, amount)` in **arrival order**. Event time is when the order happened; arrival order is when we received it. They differ.

Architecture

```
 events (arrive in order of delivery) --> assign window = event_time // 60
* 60
                                      --> watermark = max event_time seen
- 30 s
                                      --> if window end <= watermark: DROP
(late)
                                          else: add amount to that window
```

Words you need: a **tumbling window** is a fixed block of time that never overlaps the next (0 to 60 s, 60 to 120 s). The **watermark** is the stream's estimate of "we have probably seen everything up to this time"; here it is the newest event time minus an allowed lateness of 30 seconds. A window whose end is at or before the watermark is closed.

Step-by-step build

1. Set `WINDOW = 60`, `LATENESS = 30`.
2. For each event update the watermark, compute its window start.
3. If the window is already closed, record it as dropped; otherwise add the amount.
4. Print the watermark at each step so you can see why decisions happen.

Predict: the event `(10, 999)` arrives near the end. Will it be counted?

```
from collections import defaultdict
WINDOW, LATENESS = 60, 30
events = [(5,100),(20,50),(65,200),(50,70),(70,30),(125,10),(62,40),
(10,999),(130,60)]
windows = defaultdict(float); dropped = []; watermark = 0
for et, amt in events:
    watermark = max(watermark, et - LATENESS)
    w_start = et // WINDOW * WINDOW
    if w_start + WINDOW <= watermark:
        dropped.append((et, amt))
        print(f"event t={et:3d} amt={amt:3d}  watermark={watermark:3d}
DROPPED (window closed)")
        continue
    windows[w_start] += amt
    print(f"event t={et:3d} amt={amt:3d}  watermark={watermark:3d}  ->
window [{w_start},{w_start+WINDOW})")
print("\nresult:", dict(sorted(windows.items())))
print("dropped:", dropped)
```

Real output:

```
event t=  5 amt=100  watermark=  0  -> window [0,60)
event t= 20 amt= 50  watermark=  0  -> window [0,60)
event t= 65 amt=200  watermark= 35  -> window [60,120)
event t= 50 amt= 70  watermark= 35  -> window [0,60)
event t= 70 amt= 30  watermark= 40  -> window [60,120)
event t=125 amt= 10  watermark= 95  -> window [120,180)
event t= 62 amt= 40  watermark= 95  -> window [60,120)
event t= 10 amt=999  watermark= 95  DROPPED (window closed)
event t=130 amt= 60  watermark=100  -> window [120,180)

result: {0: 220.0, 60: 270.0, 120: 70.0}
dropped: [(10, 999)]
```

Explain line by line. The event at t=50 arrives after t=65 but is still accepted: the watermark is 35, and window [0,60) ends at 60, which is above 35, so it is still open. Window [0,60) therefore holds 100 + 50 + 70 = 220. The event at t=62 arrives when the watermark is 95: its window [60,120) ends at 120, above 95, so it is open: window [60,120) holds 200 + 30 + 40 = 270. The event t=10 arrives when the watermark is 95: window [0,60) ended at 60, which is at or below 95, so that window is closed and the event is dropped. Window [120,180) holds 10 + 60 = 70.

Hand check: total of all amounts = 100+50+200+70+30+10+40+999+60 = 1559; minus the dropped 999 = 560 = 220 + 270 + 70.

Spark Structured Streaming equivalent, **not run here**:

```
from pyspark.sql import functions as F
agg = (events.withWatermark("event_time", "30 seconds")
       .groupBy(F.window("event_time", "1 minute")).agg(F.sum("amount")))
```

Evaluation and acceptance criteria

- Result windows sum to the accepted events (check by hand: 560).
- The dropped list contains exactly the events whose windows were closed.
- Changing `LATENESS` to 100 makes the 999 event count (test it, expected: dropped list empty, window 0 equals 1219).
- Dropped count and amount are reported, never hidden.

Common pitfalls

1. **Using arrival time instead of event time.** Detect: windows change when delivery order changes.
2. **Lateness too small** (loses real data) or **too large** (windows stay open and results arrive late). Detect: dropped count versus delay of output.
3. **Silent drops.** Detect: always log dropped count and value.
4. **Watermark that moves backwards.** Detect: use `max`, as the code does.
5. **Confusing event-time seconds with clock time.** Detect: print both.

Three extensions

1. Add sliding windows (60 s windows every 30 s).
2. Send dropped events to a "late" side output and report them separately.
3. Emit a window result only when the watermark passes its end (finalised output).

Interview talking points

Q1. Event time versus processing time? Event time is when it happened; processing time is when we saw it. Networks reorder events, so correct results use event time.

Q2. What is a watermark? A moving line that says "events older than this are unlikely to arrive". It lets the system close windows and free memory.

Q3. What do you do with very late data? Drop it and count it, send it to a correction process, or update an already published result if the business needs exact numbers.

README outline

Problem, diagram, trace table (as above), parameter choices, hand-checked totals, limits (single process, no state store), extensions.

16.3 Project: Warehouse Star Schema with SCD2 for an Online Shop

Goal and why employers care

Model sales as a **star schema** (a central fact table of events, surrounded by dimension tables describing who, what and when), and keep customer history correct with a **slowly changing dimension type 2** (SCD2): when a customer changes city, keep the old row and add a new one, with valid dates. Employers care because "revenue by city" must use the city the customer lived in **at the time of the order**, and many reports quietly get this wrong.

Skills used

Data Modeling (Chapter 2: facts, dimensions, grain, SCD types), Warehouses and Cloud (Chapter 8: marts), Data Quality and Testing (Chapter 5: orphan and uniqueness checks).

Data

One customer `C1` who lives in Pune from 2024-01-01 and moves to Delhi on 2024-03-01. Two products. Three orders: O1 (Feb, in Pune), O2 and O3 (March, in Delhi).

Architecture

```
              dim_product
                  |
 dim_customer -- fact_sales (order_id, cust_key, prod_key, order_date,
qty, amount)
 (cust_key, cust_id, city, valid_from, valid_to, is_current)
```

The **grain** (what one fact row means) is one order line. The dimension has a **surrogate key**

(`cust_key` , a number we generate) separate from the **business key** (`cust_id` , the id from the source). One customer can have several surrogate keys over time.

Step-by-step build

1. Create `dim_customer` with `valid_from` , `valid_to` , `is_current` ; `dim_product` ; `fact_sales` .
2. Write `scd2_upsert(cust_id, city, as_of)` : if no current row, insert; if the city is unchanged, do nothing; if changed, close the old row (`valid_to = as_of` , `is_current = 0`) and insert a new current row.
3. Write `key_for(cust_id, order_date)` : pick the row where `valid_from <= date < valid_to` . This is the **point-in-time lookup**.
4. Load facts using that lookup.
5. Query revenue by city and by category; run orphan and current-row checks.

Predict: with the city change on March 1, how much revenue will each city show? (Hint: which orders happened in March?)

```
import sqlite3
db = sqlite3.connect(":memory:")
db.executescript("""
CREATE TABLE dim_customer(cust_key INTEGER PRIMARY KEY AUTOINCREMENT,
cust_id TEXT, city TEXT,
   valid_from TEXT, valid_to TEXT, is_current INT);
CREATE TABLE dim_product(prod_key INTEGER PRIMARY KEY, name TEXT, category
TEXT);
CREATE TABLE fact_sales(order_id TEXT, cust_key INT, prod_key INT,
order_date TEXT, qty INT, amount REAL);
INSERT INTO dim_product VALUES(1,'Kettle','Home'),
(2,'Notebook','Stationery');""")

def scd2_upsert(cust_id, city, as_of):
    cur = db.execute("SELECT cust_key, city FROM dim_customer WHERE
cust_id=? AND is_current=1", (cust_id,)).fetchone()
    if cur and cur[1] == city: return "unchanged"
    if cur: db.execute("UPDATE dim_customer SET valid_to=?, is_current=0
WHERE cust_key=?", (as_of, cur[0]))
    db.execute("INSERT INTO
dim_customer(cust_id,city,valid_from,valid_to,is_current)
VALUES(?,?,?,'9999-12-31',1)", (cust_id, city, as_of))
    return "changed" if cur else "new"
```

```
def key_for(cust_id, order_date):
    return db.execute("SELECT cust_key FROM dim_customer WHERE cust_id=?
AND valid_from<=? AND ?<valid_to",
                      (cust_id, order_date, order_date)).fetchone()[0]

print(scd2_upsert("C1", "Pune", "2024-01-01"), scd2_upsert("C1", "Pune",
"2024-02-01"), scd2_upsert("C1", "Delhi", "2024-03-01"))
for oid, d, p, q, a in [("O1","2024-02-10",1,1,800.0),("O2","2024-03-
15",2,3,150.0),("O3","2024-03-20",1,2,1600.0)]:
    db.execute("INSERT INTO fact_sales VALUES(?,?,?,?,?,?)", (oid,
key_for("C1", d), p, d, q, a))
print(db.execute("SELECT * FROM dim_customer").fetchall())
print(db.execute("""SELECT c.city, SUM(f.amount) FROM fact_sales f JOIN
dim_customer c USING(cust_key)
                    GROUP BY c.city ORDER BY c.city""").fetchall())
print(db.execute("""SELECT p.category, c.city, SUM(f.amount), SUM(f.qty)
FROM fact_sales f
   JOIN dim_customer c USING(cust_key) JOIN dim_product p USING(prod_key)
GROUP BY 1,2 ORDER BY 1,2""").fetchall())
print("orphans:", db.execute("SELECT COUNT(*) FROM fact_sales f LEFT JOIN
dim_customer c USING(cust_key) WHERE c.cust_key IS NULL").fetchone()[0])
print("current rows per customer:", db.execute("SELECT cust_id,
SUM(is_current) FROM dim_customer GROUP BY cust_id").fetchall())
```

Real output:

```
new unchanged changed
[(1, 'C1', 'Pune', '2024-01-01', '2024-03-01', 0), (2, 'C1', 'Delhi',
'2024-03-01', '9999-12-31', 1)]
[('Delhi', 1750.0), ('Pune', 800.0)]
[('Home', 'Delhi', 1600.0, 2), ('Home', 'Pune', 800.0, 1), ('Stationery',
'Delhi', 150.0, 3)]
orphans: 0
current rows per customer: [('C1', 1)]
```

Explain: the first call creates the customer (`new`), the second finds the same city (`unchanged` , no new row), the third closes the Pune row at 2024-03-01 and opens a Delhi row. Order O1 (February) got key 1 and is counted in Pune: 800. Orders O2 and O3 (March) got key 2: 150 + 1600 = 1750 in Delhi. If we had simply overwritten the city (SCD type 1), all 2,550 would show as Delhi and Pune's history would vanish. Total check: 800 + 1750 = 2550 = 800 + 150 + 1600.

Real warehouse DDL would use the warehouse's own types and, in dbt, a snapshot (`dbt snapshot`), **not run here**.

Evaluation and acceptance criteria

- Exactly one `is_current = 1` row per customer.
- No overlapping validity ranges for one customer (query: self-join where ranges intersect returns 0 rows).
- Zero orphan facts.
- Revenue by city for February equals 800 in Pune only.
- Total revenue in the star equals total revenue in the source orders (2550).

Common pitfalls

1. **Joining facts to the current dimension row.** Detect: past revenue moves to the new city; the point-in-time test fails.
2. **Overlapping or gapped validity dates.** Detect: the overlap query; use `valid_to` exclusive and equal to the next `valid_from`.
3. **Treating the business key as unique in the dimension.** Detect: `COUNT(*)` versus `COUNT(DISTINCT cust_id)`.
4. **Wrong grain** (mixing order and order-line rows). Detect: write the grain sentence in the README and test uniqueness on it.
5. **Late-arriving facts** (order arrives after the customer changed again). Detect: lookup by order date, not load date.

Three extensions

1. Add a `dim_date` table and join facts on a date key.
2. Add a type 1 attribute (email) beside the type 2 attribute (city).
3. Add a "unknown customer" row with key -1 for facts with no match.

Interview talking points

Q1. What is SCD2 and why use it? It keeps every version of a dimension row with dates. Reports then show facts with the attribute value that was true at the time.

Q2. Surrogate versus business key? The business key comes from the source and repeats across versions; the surrogate key is unique per version and is what facts point to.

Q3. What is the grain and why does it matter? It is what one fact row means (one order line). If you do not fix it, totals double count.

README outline

Problem, star diagram, SCD2 example table, point-in-time query, checks, limits, extensions.

16.4 Project: Parquet versus CSV, Partitioning and Compression Benchmark

Goal and why employers care

Measure how data layout changes file size and read cost: row-wise text (CSV) versus column-wise storage, compressed versus not, partitioned versus not. Employers care because storage choices decide cloud bills and query speed, and a candidate who can show numbers, not slogans, stands out.

Skills used

File Formats and Storage (Chapter 3: row versus columnar, compression, partitioning), Spark Performance (Chapter 10: scanning less data), Warehouses and Cloud (Chapter 8: pay-per-scan).

Data

200,000 orders `(order_id, city, minutes, amount)` made with a seeded generator. Honest scope: real Parquet needs pyarrow or Spark, which are **not run here**. We **simulate** a columnar layout by storing each column's values together in binary and compressing each column with `zlib`. This shows the principle (similar values together compress better, and reading one column touches one block) but it is not Parquet and the numbers are not Parquet numbers.

Architecture

```
 rows --> A: CSV text, whole file compressed
      --> B: split into 4 columns, each stored together, each compressed
      --> C: partition rows by city (folders), read only one city
 measure: bytes before/after compression, time to read one column, rows
scanned
```

Step-by-step build

1. Generate 200,000 rows.
2. Layout A: join rows into CSV bytes. Compress with `zlib` at level 6.
3. Layout B: pack each column (`struct` for numbers, newline-joined text for city) and compress each separately.
4. Report sizes per layout and per column.
5. Read one column (average of `minutes`) from each layout and time it.
6. Count rows scanned for `city = 'Pune'` with and without partitioning.

Predict: which compresses better, the CSV or the columns? Which column compresses most?

```
import random, zlib, time, struct
N = 200_000
rnd = random.Random(3); cities =
["Pune","Delhi","Chennai","Mumbai","Kolkata"]
rows = [(i, rnd.choice(cities), rnd.randint(20,120),
round(rnd.uniform(50,2000),2)) for i in range(N)]
csv_bytes = "\n".join(",".join(map(str, r)) for r in rows).encode()
cols = list(zip(*rows))
col_bytes = [struct.pack(f"{N}q", *cols[0]), "\n".join(cols[1]).encode(),
             struct.pack(f"{N}H", *cols[2]), struct.pack(f"{N}d",
*cols[3])]
names = ["order_id","city","minutes","amount"]
z = lambda b: len(zlib.compress(b, 6))
print(f"{'layout':28s}{'raw KB':>10s}{'zlib KB':>10s}")
print(f"{'row-wise CSV':28s}{len(csv_bytes)/1024:10.0f}
{z(csv_bytes)/1024:10.0f}")
print(f"{'column-wise (binary)':28s}{sum(map(len,col_bytes))/1024:10.0f}
{sum(map(z,col_bytes))/1024:10.0f}")
for n, b in zip(names, col_bytes): print(f"   column {n:10s}
{len(b)/1024:10.0f}{z(b)/1024:10.0f}")
t=time.perf_counter(); parts=[l.split(",")[2] for l in
csv_bytes.decode().split("\n")]
avg_csv=sum(map(int,parts))/N; t_csv=time.perf_counter()-t
t=time.perf_counter(); arr=struct.unpack(f"{N}H",
zlib.decompress(zlib.compress(col_bytes[2])))
avg_col=sum(arr)/N; t_col=time.perf_counter()-t
print(f"avg minutes csv={avg_csv:.3f} ({t_csv:.3f}s)  columnar=
{avg_col:.3f} ({t_col:.3f}s)")
by_city = {c: [r for r in rows if r[1]==c] for c in cities}
print("rows scanned for city=Pune: unpartitioned", N, "| partitioned",
len(by_city["Pune"]))
```

Real output (timings vary per machine; the column timing includes a compress and decompress step in the same call, so it is a rough comparison):

```
layout                          raw KB   zlib KB
row-wise CSV                      4657      1584
column-wise (binary)              4844      1230
   column order_id                1562       296
   column city                    1329       106
   column minutes                  391       206
   column amount                  1562       623
avg minutes csv=70.029 (0.035s)  columnar=70.029 (0.022s)
rows scanned for city=Pune: unpartitioned 200000 | partitioned 39743
```

Explain. (1) Raw, the binary columns (4844 KB) are slightly **bigger** than CSV text (4657 KB): small numbers take few characters in text, but fixed 8-byte slots in binary. (2) After compression the columns win: 1230 KB versus 1584 KB, about 22% smaller (1 - 1230/1584 = 0.224), because values of the same kind sit together and repeat. (3) `city` compresses from 1329 KB to 106 KB (about 12.5 times) because it has only 5 distinct values. `amount` (random decimals) barely compresses: 1562 to 623. (4) Both layouts gave the same average (70.029), which is our correctness check. (5) Reading one column touches 206 KB of compressed bytes instead of the whole 1584 KB file. (6) Partitioning by city reads 39,743 rows instead of 200,000, about 20% of the data.

pyarrow equivalent, **not run here**:

```
import pyarrow as pa, pyarrow.parquet as pq, pyarrow.csv as pc
t = pc.read_csv("orders.csv")
pq.write_table(t, "orders_snappy.parquet", compression="snappy")
pq.write_to_dataset(t, root_path="orders_by_city", partition_cols=
["city"])
avg = pq.read_table("orders_snappy.parquet", columns=["minutes"])
```

Evaluation and acceptance criteria

- Table of sizes for at least 3 layouts, with the compression ratio computed correctly.
- Same answer (70.029) from every layout.
- Partition scan shows rows read / total rows (here 39,743 / 200,000 = 19.9%).
- A written paragraph on when the result would flip (for example very small data, or high-cardinality partition keys).

- Real Parquet numbers added when you run pyarrow yourself (clearly labelled).

Common pitfalls

1. **Comparing different data.** Detect: assert the same average or row count.
2. **Partitioning by a high-cardinality key** (such as `order_id`) makes millions of tiny files. Detect: count the partitions.
3. **Timing once.** Detect: repeat 5 times and report the median.
4. **Claiming Parquet results from a simulation.** Detect: label every number with how it was produced.
5. **Forgetting that compression costs CPU.** Detect: time compress and decompress separately.

Three extensions

1. Try compression levels 1, 6 and 9 and chart size versus time.
2. Sort rows by city before compressing and measure the change in `minutes` and `amount`.
3. Run the pyarrow version for real and compare with the simulation.

Interview talking points

Q1. Why is columnar storage good for analytics? Reports usually read a few columns of many rows. Columnar storage reads only those columns, and similar values together compress well.

Q2. When is CSV fine? Small data, human inspection, exchange between simple tools. Not for large analytic tables.

Q3. What is partition pruning? Skipping whole folders that cannot match the filter. Filtering for one city then reads about a fifth of the data here.

README outline

Problem, layout diagram, size table, timing method, simulation-versus-real note, when results flip, extensions.

Chapter recap

- A quality framework treats checks as data: name, query, severity, threshold, then runs, alerts and decides.
- Error stops the pipeline; warn tells people. Too many errors cause alert fatigue.
- In streaming, use event time; the watermark is the newest event time minus allowed lateness.
- Always count and report dropped late events.
- A star schema has a fact table at a clear grain and dimension tables around it.
- SCD2 keeps history with valid dates; facts must use a point-in-time lookup.
- Surrogate keys identify a version; business keys identify the real-world thing.
- Columnar layout compresses better after compression; low-cardinality columns compress hugely.
- Partitioning lets a query scan only the matching slice; a bad partition key creates many tiny files.

Pattern	Cheat-sheet line
Check	`bad = query(); ok = bad <= threshold`
Stop rule	any failed check with severity `error`
Window	`start = t // W * W`
Watermark	`max(event_time) - lateness`
SCD2 change	close old row, insert new with `valid_from = as_of`
Point-in-time	`valid_from <= d AND d < valid_to`
Compression ratio	`raw / compressed`

Practice set

1. (Easy) A check returns 3 bad rows, threshold 0, severity warn. Does the pipeline stop?
Answer: No. A warn alerts but continues; only error severity stops it.

2. (Easy) With 60-second tumbling windows, which window does an event at t=125 belong to?
Answer: 125 // 60 * 60 = 120, so window [120,180).

3. (Easy) Total orders amount 1559, one dropped event of 999. What must the windows add up to? **Answer:** 560.

4. (Medium) Watermark is 95, lateness 30. What is the newest event time seen? **Answer:** 125, because watermark = newest - 30.

5. (Medium) A customer moves city on 2024-03-01. An order on 2024-03-01 exactly: old or new row? **Answer:** The new row, because validity is `valid_from <= date < valid_to` and the old row's `valid_to` is 2024-03-01 (exclusive).

6. (Medium, compute) CSV compressed to 1584 KB and columnar to 1230 KB. How much smaller is columnar, in percent? **Answer:** (1584 - 1230) / 1584 = 354 / 1584 = 0.2235, so about 22%.

7. (Interview) Your dashboard shows last year's revenue for a customer under the new city after a move. What went wrong and how do you fix it? **Answer (acceptance):** Facts were joined to the current dimension row (type 1 behaviour or no point-in-time lookup). Use SCD2 with valid dates and look up the surrogate key by order date; test with an order before the move.

8. (Interview) Why can a streaming job drop correct data, and how do you decide the lateness? **Answer (acceptance):** Events arrive out of order; once the watermark passes a window, later events are dropped. Choose lateness from measured delay (for example the 99th percentile of arrival delay), count drops, and trade accuracy against delay of results.

Prompt pack

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Help me plan a data-quality framework project
(Chapter 16, Project Lab 2). Ask me one question at a time about my
dataset and who consumes it. Then propose 10 checks across the quality
dimensions, give each a severity and a threshold with a reason, and
describe how I would prove each check can fail. Keep the English simple
and tell me what to leave out of version one.
```

✨ **AI prompt: copy and paste into any AI**

```
You are my patient, practical professor. I am a working professional
moving into data roles. Teach me event time, tumbling windows, watermarks
and late events using a shop-orders example with 9 events (Chapter 16,
```

streaming project). Trace each event in a table with the watermark value, then give me 6 graded exercises with different lateness settings, without solutions. When I send my answers, check every line and explain mistakes.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Review my star schema with SCD2 for an online shop. Here are my tables and queries: [PASTE HERE]. Check the grain, surrogate versus business keys, validity date logic, overlap and orphan rows, and the point-in-time lookup. List problems in order of severity, show a SQL query that proves each one, and suggest the smallest fix.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. I benchmarked storage layouts (row versus columnar, compression, partitioning) and got these numbers: [PASTE HERE]. Help me judge them honestly. Ask how I measured, check for unfair comparisons, explain why each number came out as it did, and tell me which claims I can safely make in a README and which I cannot make without running real Parquet.

✨ AI prompt: copy and paste into any AI

You are my patient, practical professor. I am a working professional moving into data roles. Help me write a LinkedIn or blog post about one of my Chapter 16 projects: [NAME THE PROJECT AND PASTE MY RESULTS]. Use the shape: problem in one sentence, what I built, one measured number, one surprising bug, link. Write it in simple English under 250 words, avoid hype, and then list 3 questions a recruiter might ask me about it with short model answers.

APPENDIX

CHEAT SHEET

One page per chapter: the formulas, commands and patterns you will use again and again.

Use this as a quick check after you finish a chapter, and as a last-night-before-the-interview review. Every row is explained in its chapter. Where a number is a default or a price, it can change by tool and version: check the current documentation.

Chapter 1: Lifecycle and Architectures

Item	Rule
Lifecycle	generation, ingestion, storage, transformation, serving; undercurrents: security, governance, orchestration, DataOps, monitoring, cost
OLTP vs OLAP	many small row transactions vs heavy column scans
Processing style	choose the slowest of batch, micro-batch, stream that meets the need
ETL vs ELT	transform before load vs load raw then transform in the warehouse
Architectures	warehouse (modeled), lake (raw, cheap), lakehouse (lake plus ACID), mesh (organisation), lambda (two paths), kappa (one)
Medallion	bronze raw, silver clean, gold business
Quorum	`[n/2] + 1`
Idempotent write	upsert by key or overwrite by partition
Reconcile	count rows at every hop; the first drop is the culprit

Chapter 2: Data Modeling

Item	Rule
Grain	state in one sentence what one fact row means
Fact types	transaction, periodic snapshot, accumulating snapshot
Measures	additive, semi-additive (not over time), non-additive
Schemas	star (default), snowflake (more joins), OBT (fast, hard to maintain)
SCD	Type 1 overwrite; Type 2 new row with `valid_from`, `valid_to`, `is_current`; Type 3 previous value
Point in time	`d >= valid_from AND d < valid_to`
Join safety	total before join = total after join
Methods	Kimball marts first, Inmon normalized first, Data Vault hubs, links, satellites

Chapter 3: File Formats and Storage

Item	Rule
CSV/JSON traps	no types, quoting, encoding, leading zeros, nulls: give a schema
Parquet	columnar, row groups, footer statistics: column pruning and predicate pushdown
Avro	row-based with schema; fits Kafka and a Schema Registry
Bytes read	`matching groups × group size × (columns read / total columns)`
File cost	`files × overhead + bytes / throughput`
Target file size	128 MB to 1 GB

Partitioning	low-cardinality filter column (date); avoid tiny partitions
Table formats	Delta, Iceberg, Hudi: commit log, ACID, time travel, MERGE; maintain with OPTIMIZE/VACUUM or rewrite/expire

Chapter 4: Ingestion Patterns

Item	Rule
Incremental	watermark = max value actually loaded; read inclusive or with a safety window; upsert
Pagination	prefer cursor to offset; pages = `⌈rows / page size⌉`
Retry	`wait = min(cap, base × 2^(attempt−1))` plus jitter; only transient errors
CDC	read the log; apply in log order; keep the highest LSN per key
Backfill	job takes a logical date and overwrites its own partition
Files and webhooks	completion marker; fast acknowledgement; handle duplicates

Chapter 5: Data Quality and Testing

Item	Rule
Dimensions	completeness, uniqueness, validity, consistency, accuracy, freshness, schema
Duplicates	`COUNT(*) − COUNT(DISTINCT key)`
Freshness	`now − max(ts) < limit`
Volume band	`

Reconcile	`silver + quarantine + duplicates = bronze`
Contract	schema, units, rules, SLA, owner, change process
Severity	error stops the pipeline, warn alerts
Tools	pandera, Great Expectations, Soda, dbt tests (same ideas, different syntax)

Chapter 6: Orchestration with Airflow

Item	Rule
Logical date	start of the data interval; run starts after the interval ends
Catch-up runs	complete intervals between start and now
Backfill time	`[runs / parallel runs] × time per run`
Dependency	`a >> b >> c`
Templated date	`{{ ds }}`
Rules	idempotent tasks; XCom only for small values; DAG file light; test imports
Alternatives	Dagster, Prefect, ADF, Step Functions, Argo, cron

Chapter 7: dbt

Item	Command or code
Build model and downstream	`dbt run --select name+`
Build, test, seed, snapshot	`dbt build`
See rendered SQL	`dbt compile`
Incremental guard	`{% if is_incremental() %} ... {% endif %}`

Full rebuild	`dbt run --full-refresh`
Slim CI	`dbt build --select state:modified+ --defer --state path`
Freshness	`dbt source freshness`
Layers	staging, intermediate, marts; use `ref()` and `source()`, never hard-coded names
Generic tests	`unique`, `not_null`, `accepted_values`, `relationships`

Chapter 8: Warehouses and Cloud Data Services

Item	Rule
Credits	`credits per hour × hours`
Scan cost	`TB scanned × price per TB`
Pruning	`scanned = matched partitions × partition size`; filter on the raw column
Aggregate once	build once and read the small summary many times
Biggest savings	suspend idle compute, prune partitions, avoid `SELECT *`, budgets and alerts
Cache hit rate	`hits / reads`
Token bucket	`allowed ≈ burst + rate × time`
NoSQL keys	high cardinality, even load (date as a key put everything in one partition)

Chapter 9: Spark and PySpark I

Item	Code or rule

Start	`spark = SparkSession.builder.getOrCreate()`
Filter, derive	`df.filter(F.col("x") > 0).withColumn("y", F.col("x") * 2)`
Group	`df.groupBy("k").agg(F.sum("v").alias("total"))`
Anti join	`a.join(b, "k", "left_anti")`
Broadcast	`a.join(F.broadcast(b), "k")`
Window	`Window.partitionBy("k").orderBy("t")`; `row_number` then filter for the latest row
Plan	`df.explain()`
Waves	`⌈tasks / (executors × cores)⌉`
Laziness	transformations lazy, actions run; a shuffle ends a stage; never `collect()` big data

Chapter 10: Spark II: Performance

Item	Rule or setting
Shuffle partitions	`spark.sql.shuffle.partitions`; about data size / 128 MB
Broadcast threshold	`spark.sql.autoBroadcastJoinThreshold`
AQE	`spark.sql.adaptive.enabled` (skew join and coalesce partitions switches)
Skew test	max / median task time; partition above 5 × median and 256 MB
Fix order	filter junk keys, broadcast, AQE, then salt
Salting	`key#r`, r from 0 to S−1; duplicate the small side S times
Unified memory	`(heap − 300 MB) × 0.6`

Method	measure in the Spark UI, classify, change one thing, measure again

Chapter 11: Streaming and Kafka

Item	Rule
Tumbling window start	`(t // W) × W`
Sliding windows per event	`length / slide`
Watermark	`max event time − allowed lateness`
Window final	`end ≤ watermark`; later events dropped or side-routed
Partition for a key	`hash(key) mod P`; order only inside a partition
Max useful consumers	number of partitions
Lag	`end offset − committed offset`
Semantics	at-most-once: commit then process; at-least-once: process then commit; exactly-once effect: at-least-once plus idempotent sink
Safe producer	`acks=all`, replication 3, `min.insync.replicas=2`, idempotence on

Chapter 12: Infrastructure and DataOps

Item	Rule or command
Docker	`docker build −t name:tag .`; `docker run −−rm name:tag`; copy requirements before code; pin versions
Kubernetes	`requests` reserved, `limits` ceiling; `500m` = 0.5 core; OOMKilled =

	memory limit exceeded
Terraform	`init`, `plan`, review, `apply`; protect the state file; watch for drift
CI/CD	lint, test, DAG import, build, deploy dev then prod; promote the same image
Secrets	secret manager and IAM roles; rotate after a leak
Alerts	freshness `now − max(ts) > SLA`; volume `
Cost	`bytes scanned × price × runs`
Privacy	classify PII; mask, tokenize (HMAC); retention cutoff = `today − period`; lineage and catalog

Chapter 13: System Design for Data

Item	Formula
Steps	requirements, capacity, model, ingestion, storage, processing, serving, quality, failures and cost
Average rate	`events per day / 86,400` (1 million per day is about 12 per second)
Peak	`average × peak factor`
Consumers	`[peak / per-consumer rate]`; partitions = consumers × 1.5
Kafka disk	`GB per day × retention days × replication`
Storage per year	`GB per day / compression × 365`
Recovery time	`backlog / (capacity − incoming)`
Latency budget	sum of stage p99 values within the limit
Worked numbers	clickstream 200 million per day: 6.9 thousand per second peak, 200 GB per day, 14.6 TB per year

Chapter 14: Performance and Capacity of Data Pipelines

Item	Formula
Little's law	`L = λ × W`
Utilization	`ρ = λ / μ` ; keep sustained near 70%
M/M/1 mean latency	`1 / (μ − λ)`
Servers needed	`⌈λ / (μ × target ρ)⌉`
Chain throughput	`min(stage capacities)`
Drain time	`backlog / (capacity − arrival)`
Cost per 1k predictions	`price per hour / (rps × 3600) × 1000`
Improvement	`(new − old) / old × 100`
Portfolio	eight capstones; the performance and capacity report is your signature

An Honest Closing Note

If you studied all fourteen chapters and rebuilt the examples, you can now do real things. You can explain the full lifecycle of a data platform and choose between a warehouse, lake and lakehouse with reasons. You can model a business as facts and dimensions, pick file formats and partitions, and write incremental and CDC loads that survive retries. You can test data quality, schedule pipelines with Airflow, build models in dbt, read Spark plans and fix a skewed join, and reason about event time, watermarks and Kafka delivery guarantees. You can sketch a data system on a whiteboard with real capacity numbers. And you have a skill that most data engineers lack: you can measure a pipeline under load, find the bottleneck with Little's law, and price the fix.

Be honest about the limits. This document is a strong foundation, not experience. Much of the

tool code (Airflow, Spark, dbt, Kafka, Flink, Docker, Kubernetes, Terraform, cloud services) was labelled "not run here" because the sandbox could not install it. You must run it yourself, break it, and read the real error messages. Version details change, so check the current documentation. We did not cover: one cloud in depth with its certification exam, Kubernetes administration, advanced Flink and Kafka operations, search engines and graph databases beyond awareness, deep data privacy law, machine learning internals (see the ML documents), and the human parts of the job: stakeholder management, estimation under pressure, on-call fatigue. The file `_missing_topics.md` lists smaller gaps such as time zones, decimals and money, deduplication at scale, query plans in OLTP databases and incident management.

What to practise next, in order. First, build projects 1 and 2 from Chapter 14 this month, and push them to a public repository with a clear README and real numbers. Second, pick one cloud and one warehouse and use the free tier carefully with budget alerts. Third, run a real Kafka in Docker and measure consumer lag under load with a small Python producer (or a tool such as Locust): this becomes project 8, your signature piece. Fourth, do one whiteboard design per week from Chapter 13, out loud, with a timer. Fifth, read *Designing Data-Intensive Applications* slowly alongside this document. Sixth, apply to roles while you build, and use each rejection as a note for the next study week.

One last rule from the start of this document: never move on until the current topic feels obvious. Slow and deep beats fast and shallow. You already know how to find bottlenecks. Now go and find the ones in data.