

DaemonCore FieldOps Production Cheat Sheet

Windows 6.4.0 | Signed engagements | Evidence-first execution

Use this sheet while operating FieldOps. The order matters: bind the operator, declare exact scope, verify the permit, execute only inside that scope, seal evidence, create findings, and close the engagement. A FieldOps license unlocks the workspace; it does not authorize a target.

The 60 second operating loop

STEP	OPERATOR ACTION	PROOF CREATED
1 Bind	Confirm the device-bound operator identity shows your legal or professional name, organization, email, and role.	Ed25519 operator fingerprint
2 Declare	Create the engagement from the signed rules of engagement. Enter exact targets, ports, window, client, approver, and authorization reference.	Signed operation permit
3 Preflight	Confirm ACTIVE AUTHORIZATION, target and port allowlists, policy level, execution profile, and permit validity.	Scope and capacity record
4 Execute	Choose the workspace that matches the approved objective. Stop when the authorized proof point is reached.	Operation receipt and output
5 Seal	Promote relevant results into the evidence vault. Import external JSON or SARIF only through Evidence Intake.	SHA-256 capture digest
6 Decide	Create evidence-backed findings, record disposition, attach retests, and export the client report or case file.	Finding history and report
7 Close	Stop active jobs, campaigns, and experiments, export the record, then close the authorization boundary.	Closed immutable engagement

Hard stops

STOP IMMEDIATELY WHEN	REQUIRED RESPONSE
The target, port, endpoint, method, or test window is not explicitly authorized	Do not improvise. Pause and amend the rules of engagement.
DNS resolves to a private, loopback, link-local, reserved, or changed destination outside the declared mode	Treat it as a scope change. Preserve the event and obtain authorization.
A campaign or workload crosses its approved objective, grant, or SLO	Use the workspace stop control or emergency stop, then record the reason.
Evidence integrity or permit verification fails	Do not rely on the record. Export what is available and escalate for review.

Open a production engagement

FIELD	PRODUCTION ENTRY	CHECK
Engagement	Specific job or assessment name	No generic reusable permit
Client	Legal customer or internal owner	Matches written authorization
Authorization reference	SOW, ROE, ticket, or change record	Traceable by approver
Network mode	External or internal	Matches the operator vantage point
Targets	Exact hostnames or IP addresses	No inferred third parties
TCP ports	Exact approved port set	Includes native tool and verification ports
Policy	Observe, Validate, or Stress	Stress required for resilience authorization
Execution profile	Guarded or Professional	Professional capacity follows signed scope
Test window	Start and end timestamps	Ends within 366 days
Approver	Named authority and professional email	Independent of operator where policy requires

Policy selection

POLICY	PERMITTED OPERATION CLASSES	USE WHEN
Observe	Observation only	Inventorying and recording approved signals without active validation
Validate	Observe and validate	Confirming service, protocol, HTTP, TLS, and approved assessment evidence
Stress	Observe, validate, and resilience	Running bounded Chaos Engine checks or verifying external load authority

Before every run

- **Window.** Engagement status is active and the current clock is inside the signed test window.
- **Scope.** The selected target and every port are visible in the exact permit allowlist.
- **Permit.** The operation class is allowed by the signed policy and the permit integrity indicator passes.
- **Control plane.** No conflicting native job, campaign, or Chaos Engine experiment is already active.
- **Exit plan.** The intended proof point, abort condition, communications path, and recovery owner are known.

Choose the right workspace

WORKSPACE	USE IT FOR	PRODUCTION OUTPUT
Diagnostics	DNS, TCP, HTTP, TLS, HTTP posture, service profiling, deep inventory, surface mapping, and baselines	Sealed diagnostic capture
Execution Fabric	Managed Nmap inventory, workstation capability discovery, signed scope export, and external evidence intake	Native job capture or signed manifest
Campaigns	Repeatable multi-target DNS, inventory, and surface workflows with pause, resume, cancel, and restart recovery	Campaign task ledger and captures
Assets and evidence	Reviewing captures, service inventory, drift, imported JSON or SARIF, and promotion into findings	Digest-verified evidence chain
Findings	Writing impact, remediation, severity, disposition, and retest history from selected evidence	Client-ready finding record
Chaos Engine	Short bounded HEAD-based baseline, ramp, spike, and soak experiments with SLO abort and recovery proof	Resilience score and experiment ledger

Managed Nmap run

STAGE	WHAT TO DO
Select	Choose one exact permitted target. FieldOps uses the engagement port set.
Attest	Confirm the run remains inside the active signed permit.
Run	Start Nmap and watch the live process output. FieldOps passes a fixed argument array without a command shell.
Stop	Use STOP JOB when the objective changes, the window closes, or the target behaves unexpectedly.
Seal	A completed result becomes a native-tool capture with engine, address, timing, output, and digest.

Evidence intake

Use signed scope export for Nuclei, ZAP, k6, Locust, TShark, Hashcat, and other supported bridges. Run the specialist tool in the customer-controlled environment, then import JSON or SARIF against the exact authorized target. Imported content is treated as evidence, never executed by DaemonCore.

High intensity testing without anonymous execution

Version 6.4.0 separates the built-in bounded Chaos Engine from professional external load generation. FieldOps signs k6 or Locust workload manifests only after the exact target publishes a challenge-bound capacity grant over trusted TLS. The customer-controlled runner performs the workload and returns results for evidence sealing.

PHASE	REQUIRED ACTION	ENFORCED BOUNDARY
1 Permit	Create a new Stress-policy engagement containing the exact load target and verification port.	Operator, approver, scope, and window are signed
2 Publish	Place the JSON capacity grant at the challenge path shown in Execution Fabric.	Grant must originate from the exact target
3 Verify	Select target, port, and verified TLS, then choose Verify Target Capacity.	Challenge, target, authorization reference, and expiration must match
4 Configure	Enter path, requests per second, duration, and concurrency at or below the grant.	Values above the verified capacity are rejected
5 Export	Export the k6 or Locust signed workload manifest.	Manifest includes permit and grant digests
6 Execute	Run through customer-controlled load infrastructure with monitoring and emergency stop available.	Runner must independently enforce the manifest
7 Import	Return structured results through Evidence Intake and bind them to the target.	Source digest enters chain of custody

Capacity grant schema

JSON FIELD	MEANING	RULE
challenge	Unique value shown by the engagement	Exact match
target	Authorized hostname or IP	Exact permit target
authorizationReference	SOW, ROE, ticket, or change record	Exact engagement reference
maxRequestsPerSecond	Maximum approved arrival rate	Positive integer
maxDurationSeconds	Maximum approved load duration	At least 10 seconds
maxConcurrency	Maximum approved workers	Positive integer
validUntil	Grant expiration in ISO 8601	Inside the permit window

Emergency stop: stop the customer-controlled workers first, preserve target and runner telemetry, record the reason in the engagement, and do not resume until the approving authority confirms the remaining window and capacity.

Evidence to finding to report

ACTION	MINIMUM PRODUCTION CONTENT
Capture	Exact target, address, port or path, operation type, timestamps, duration, tool or engine, result, and digest
Finding	Specific title, severity, evidence-backed description, business impact, practical remediation, and source capture
Disposition	Open, accepted risk, resolved, or false positive, with operator note and timestamp
Retest	New capture from the same engagement, fixed or still-present verdict, note, and retained history
Report	Authorization, signed operator, approver, integrity state, campaigns, services, drift, evidence, findings, and retests
Case file	Portable engagement record retained before closure or upgrade

Fast troubleshooting

SYMPTOM	CHECK FIRST	NEXT ACTION
Operation blocked	Entitlement, active window, policy class, exact target and port	Correct the engagement; never bypass the permit
Target resolves differently	DNS answers and network mode	Stop, record drift, and obtain a scope decision
Nmap unavailable	Execution Fabric workstation rescan and Docker availability	Install the supported tool or use the signed evidence bridge
Capacity verification fails	New engagement challenge, exact JSON values, trusted TLS, HTTP 200, and grant expiration	Correct the target-hosted grant and verify again
Workload export blocked	Stress policy, current grant, and requested rate, concurrency, and duration	Stay at or below the target-issued capacity
Evidence import rejected	JSON or SARIF format, 2 MB limit, exact target, and source integrity	Export structured evidence and retry
Integrity indicator fails	Permit mutation, file corruption, interrupted write, or stale record	Stop execution and preserve the record for review

Closeout checklist

DONE	CLOSEOUT ACTION
☐	Stop all native jobs, campaigns, Chaos Engine experiments, and customer-controlled workers.
☐	Confirm evidence, capture, and signature integrity indicators pass.
☐	Finish finding dispositions and attach available retest evidence.
☐	Export the client report and case file to the approved evidence location.
☐	Record unresolved limitations, affected assets, owner, and next review date.
☐	Close the authorization boundary. Reopen work only through a new engagement.