

Dapatkan datanya

Panggilan dilakukan ke GitHub melalui modul permintaan Python untuk mengunduh file .zip dan mengekstraknya.

```
import os
import requests
import zipfile
from pathlib import Path

# Setup path to data folder
data_path = Path("data/")
image_path = data_path / "pizza_steak_sushi"

# If the image folder doesn't exist, download it and prepare it...
if image_path.is_dir():
    print(f"{image_path} directory exists.")
else:
    print(f"Did not find {image_path} directory, creating one...")
    image_path.mkdir(parents=True, exist_ok=True)

# Download pizza, steak, sushi data
with open(data_path / "pizza_steak_sushi.zip", "wb") as f:
    request = requests.get("https://github.com/mrdbourke/pytorch-deep-learning/raw/main/data/pizza_steak_sushi.zip")
    print("Downloading pizza, steak, sushi data...")
    f.write(request.content)

# Unzip pizza, steak, sushi data
with zipfile.ZipFile(data_path / "pizza_steak_sushi.zip", "r") as zip_ref:
    print("Unzipping pizza, steak, sushi data...")
    zip_ref.extractall(image_path)

# Remove zip file
os.remove(data_path / "pizza_steak_sushi.zip")

Did not find data/pizza_steak_sushi directory, creating one...
Downloading pizza, steak, sushi data...
Unzipping pizza, steak, sushi data...
```

#Buat Kumpulan Data dan DataLoader (data_setup.py)

Kami mengonversi kode pembuatan Dataset dan DataLoader yang berguna menjadi fungsi yang disebut create_data_loaders().

```
import os
```

```

from torchvision import datasets, transforms
from torch.utils.data import DataLoader

NUM_WORKERS = os.cpu_count()

def create_dataloaders(
    train_dir: str,
    test_dir: str,
    transform: transforms.Compose,
    batch_size: int,
    num_workers: int=NUM_WORKERS
):

    train_data = datasets.ImageFolder(train_dir, transform=transform)
    test_data = datasets.ImageFolder(test_dir, transform=transform)

    # Get class names
    class_names = train_data.classes

    # Turn images into data loaders
    train_dataloader = DataLoader(
        train_data,
        batch_size=batch_size,
        shuffle=True,
        num_workers=num_workers,
        pin_memory=True,
    )
    test_dataloader = DataLoader(
        test_data,
        batch_size=batch_size,
        shuffle=False, # don't need to shuffle test data
        num_workers=num_workers,
        pin_memory=True,
    )

    return train_dataloader, test_dataloader, class_names

```

Jika kita ingin membuat `DataLoader` sekarang kita dapat menggunakan fungsi di dalamnya `data_setup.py` seperti ini:

```

# Import data_setup.py
from going_modular import data_setup

# Create train/test dataloader and get class names as a list
train_dataloader, test_dataloader, class_names =
data_setup.create_dataloaders(...)

```

Membuat model (model_builder.py)

```
import torch
from torch import nn

class TinyVGG(nn.Module):

    def __init__(self, input_shape: int, hidden_units: int,
output_shape: int) -> None:
        super().__init__()
        self.conv_block_1 = nn.Sequential(
            nn.Conv2d(in_channels=input_shape,
                out_channels=hidden_units,
                kernel_size=3,
                stride=1,
                padding=0),
            nn.ReLU(),
            nn.Conv2d(in_channels=hidden_units,
                out_channels=hidden_units,
                kernel_size=3,
                stride=1,
                padding=0),
            nn.ReLU(),
            nn.MaxPool2d(kernel_size=2,
                stride=2)
        )
        self.conv_block_2 = nn.Sequential(
            nn.Conv2d(hidden_units, hidden_units, kernel_size=3,
padding=0),
            nn.ReLU(),
            nn.Conv2d(hidden_units, hidden_units, kernel_size=3,
padding=0),
            nn.ReLU(),
            nn.MaxPool2d(2)
        )
        self.classifier = nn.Sequential(
            nn.Flatten(),
            # Where did this in_features shape come from?
            # It's because each layer of our network compresses and
changes the shape of our inputs data.
            nn.Linear(in_features=hidden_units*13*13,
                out_features=output_shape)
        )

    def forward(self, x: torch.Tensor):
        x = self.conv_block_1(x)
        x = self.conv_block_2(x)
        x = self.classifier(x)
        return x
# return
```

```
self.classifier(self.conv_block_2(self.conv_block_1(x))) # <- leverage
the benefits of operator fusion
```

Sekarang alih-alih mengkodekan model TinyVGG dari awal setiap saat, kita dapat mengimpornya menggunakan:

```
import torch
# Import model_builder.py
from going_modular import model_builder
device = "cuda" if torch.cuda.is_available() else "cpu"

# Instantiate an instance of the model from the "model_builder.py"
script
torch.manual_seed(42)
model = model_builder.TinyVGG(input_shape=3,
                              hidden_units=10,

output_shape=len(class_names)).to(device)
```

#Membuat fungsi train_step() dan test_step() serta train() untuk menggabungkannya

```
import torch

from tqdm.auto import tqdm
from typing import Dict, List, Tuple

def train_step(model: torch.nn.Module,
               dataloader: torch.utils.data.DataLoader,
               loss_fn: torch.nn.Module,
               optimizer: torch.optim.Optimizer,
               device: torch.device) -> Tuple[float, float]:

    # Put model in train mode
    model.train()

    # Setup train loss and train accuracy values
    train_loss, train_acc = 0, 0

    # Loop through data loader data batches
    for batch, (X, y) in enumerate(dataloader):
        # Send data to target device
        X, y = X.to(device), y.to(device)

        # 1. Forward pass
        y_pred = model(X)

        # 2. Calculate and accumulate loss
        loss = loss_fn(y_pred, y)
        train_loss += loss.item()
```

```

# 3. Optimizer zero grad
optimizer.zero_grad()

# 4. Loss backward
loss.backward()

# 5. Optimizer step
optimizer.step()

# Calculate and accumulate accuracy metric across all batches
y_pred_class = torch.argmax(torch.softmax(y_pred, dim=1), dim=1)
train_acc += (y_pred_class == y).sum().item()/len(y_pred)

# Adjust metrics to get average loss and accuracy per batch
train_loss = train_loss / len(dataloader)
train_acc = train_acc / len(dataloader)
return train_loss, train_acc

def test_step(model: torch.nn.Module,
              dataloader: torch.utils.data.DataLoader,
              loss_fn: torch.nn.Module,
              device: torch.device) -> Tuple[float, float]:

# Put model in eval mode
model.eval()

# Setup test loss and test accuracy values
test_loss, test_acc = 0, 0

# Turn on inference context manager
with torch.inference_mode():
    # Loop through DataLoader batches
    for batch, (X, y) in enumerate(dataloader):
        # Send data to target device
        X, y = X.to(device), y.to(device)

        # 1. Forward pass
        test_pred_logits = model(X)

        # 2. Calculate and accumulate loss
        loss = loss_fn(test_pred_logits, y)
        test_loss += loss.item()

        # Calculate and accumulate accuracy
        test_pred_labels = test_pred_logits.argmax(dim=1)
        test_acc += ((test_pred_labels ==
y).sum().item()/len(test_pred_labels))

# Adjust metrics to get average loss and accuracy per batch
test_loss = test_loss / len(dataloader)

```

```

test_acc = test_acc / len(dataloader)
return test_loss, test_acc

def train(model: torch.nn.Module,
          train_dataloader: torch.utils.data.DataLoader,
          test_dataloader: torch.utils.data.DataLoader,
          optimizer: torch.optim.Optimizer,
          loss_fn: torch.nn.Module,
          epochs: int,
          device: torch.device) -> Dict[str, List]:

    # Create empty results dictionary
    results = {"train_loss": [],
               "train_acc": [],
               "test_loss": [],
               "test_acc": []
              }

    # Loop through training and testing steps for a number of epochs
    for epoch in tqdm(range(epochs)):
        train_loss, train_acc = train_step(model=model,
                                           dataloader=train_dataloader,
                                           loss_fn=loss_fn,
                                           optimizer=optimizer,
                                           device=device)

        test_loss, test_acc = test_step(model=model,
                                         dataloader=test_dataloader,
                                         loss_fn=loss_fn,
                                         device=device)

        # Print out what's happening
        print(
            f"Epoch: {epoch+1} | "
            f"train_loss: {train_loss:.4f} | "
            f"train_acc: {train_acc:.4f} | "
            f"test_loss: {test_loss:.4f} | "
            f"test_acc: {test_acc:.4f}"
        )

        # Update results dictionary
        results["train_loss"].append(train_loss)
        results["train_acc"].append(train_acc)
        results["test_loss"].append(test_loss)
        results["test_acc"].append(test_acc)

    # Return the filled results at the end of the epochs
    return results

# Import engine.py
from going_modular import engine

```

```
# Use train() by calling it from engine.py
engine.train(...)
```

1. Membuat fungsi untuk menyimpan model (utils.py)

```
import torch
from pathlib import Path

def save_model(model: torch.nn.Module,
               target_dir: str,
               model_name: str):

    # Create target directory
    target_dir_path = Path(target_dir)
    target_dir_path.mkdir(parents=True,
                          exist_ok=True)

    # Create model save path
    assert model_name.endswith(".pth") or model_name.endswith(".pt"),
    "model_name should end with '.pt' or '.pth'"
    model_save_path = target_dir_path / model_name

    # Save the model state_dict()
    print(f"[INFO] Saving model to: {model_save_path}")
    torch.save(obj=model.state_dict(),
               f=model_save_path)

# Import utils.py
from going_modular import utils

# Save a model to file
save_model(model=...,
           target_dir=...,
           model_name=...)
```

#Latih, evaluasi, dan simpan model (train.py)

Dalam file train.py , kami akan menggabungkan semua fungsi skrip Python lain yang kami miliki dibuat dan digunakan untuk melatih model.

```
import os
import torch
import data_setup, engine, model_builder, utils

from torchvision import transforms

# Setup hyperparameters
NUM_EPOCHS = 5
BATCH_SIZE = 32
```

```

HIDDEN_UNITS = 10
LEARNING_RATE = 0.001

# Setup directories
train_dir = "data/pizza_steak_sushi/train"
test_dir = "data/pizza_steak_sushi/test"

# Setup target device
device = "cuda" if torch.cuda.is_available() else "cpu"

# Create transforms
data_transform = transforms.Compose([
    transforms.Resize((64, 64)),
    transforms.ToTensor()
])

# Create DataLoaders with help from data_setup.py
train_dataloader, test_dataloader, class_names =
data_setup.create_dataloaders(
    train_dir=train_dir,
    test_dir=test_dir,
    transform=data_transform,
    batch_size=BATCH_SIZE
)

# Create model with help from model_builder.py
model = model_builder.TinyVGG(
    input_shape=3,
    hidden_units=HIDDEN_UNITS,
    output_shape=len(class_names)
).to(device)

# Set loss and optimizer
loss_fn = torch.nn.CrossEntropyLoss()
optimizer = torch.optim.Adam(model.parameters(),
                               lr=LEARNING_RATE)

# Start training with help from engine.py
engine.train(model=model,
             train_dataloader=train_dataloader,
             test_dataloader=test_dataloader,
             loss_fn=loss_fn,
             optimizer=optimizer,
             epochs=NUM_EPOCHS,
             device=device)

# Save the model with help from utils.py
utils.save_model(model=model,
                 target_dir="models",

```



```
model_name="05_going_modular_script_mode_tinyvgg_model.pth")
```