

Confluent flow and other approximations to the Pooling Problem

Dag Haugland · Eligius M.T. Hendrix ·
Ísak Páll Gestsson

Received: date / Accepted: date

Abstract About the computational challenge of the pooling problem and finding approximate solutions by means of confluent or influent flow

Keywords Pooling problem · complexity · global optimization

Mathematics Subject Classification (2000) 90C26 · 90C35 · 90C39 · 68Q25

1 Introduction

Taken from an earlier paper, to be revised: Traditional network flow models, like the minimum cost network flow problem, rely on considerations of the flow as a homogeneous commodity. Variations in composition is however relevant in many industrial and logistics applications of the models, including petroleum refining and pipeline transportation of natural gas. Crude oils supplied to a refinery have contamination levels depending on their sources of origin. Major components of natural gas are methane, ethane, butane and propane, but the proportions in which they occur are not equal for all gas wells. For environmental or technical reasons, requirements to the final composition are often imposed at the sink nodes of the flow network. Whenever constraints of this kind apply, it is therefore essential for network flow models to recognize not only the total product flow, but also how the flow composition evolves from network sources to sinks. In particular, the models must reflect updates of

Dag Haugland, Corresponding author
Department of Informatics, University of Bergen, Norway E-mail: dag.haugland@ii.uib.no

Eligius M.T. Hendrix
Department of Computer Architecture, Universidad de Málaga and Operations Research and Logistics Group, Wageningen University E-mail: eligius.hendrix@wur.nl

Ísak Páll Gestsson
Gassco

the composition at nodes where differently composed flows are pooled. This provides a computationally challenging problem referred to as the POOLING PROBLEM.

The POOLING PROBLEM exhibits strong resemblance with well-studied logistics models like the MINIMUM COST FLOW PROBLEM and the TRANSPORTATION PROBLEM. Another classical related problem is Stigler’s DIET PROBLEM [1,2], asking for the minimum cost diet requiring a certain amount of specified nutrients. The problem is easy to extend to a multi-diet version where groups of people have each their own requirements. Nutritional contents differ between sources, that is, foods of which diets can be composed, and the optimal mix must be found for each sink (group of people). Conceptually, the multi-diet version coincides with the POOLING PROBLEM in bipartite networks. Thanks to this simple network structure, with exclusively direct links between sources and sinks, diet problems are nothing but linear programs. However, when extending the problem to more general network structures, this is no longer the case. Absence of linear formulations has immediate computational consequences. While minimum cost flow instances where the network size reaches a six digit number of arcs and nodes can be solved within hours, or even minutes, exact solution of POOLING PROBLEM instances with hundreds of nodes appears to be unrealistic.

The POOLING PROBLEM has been recognized for decades as a challenge where linear programming approaches fail. Bounds on the flow composition frequently induce bilinear constraints in otherwise linear models, and require corresponding solution methods. An approach based on iterated solution of linearized model versions has gained popularity especially in the oil refining industry, and has been analyzed experimentally by Haverly [3]. A major conclusion is that methods of this kind may produce suboptimal solutions. Such observations helped establishing a consensus, already in early days of research in the POOLING PROBLEM, that global optimality is achievable only in small instances.

Owing to the anticipated intractability of the problem, early research was mainly directed towards heuristic methods [3–5], where iterative linearization is the core idea. Floudas and Visweswaran [6] reported the first exact solution algorithm for the POOLING PROBLEM. Later, algorithms based on branch-and-bound [7–11], Lagrangian relaxation [12–14], and integer programming [15] have been studied. The industrial relevance of the problem, notably in petroleum refining [4,5], the food industry [16], and in waste water processing [17,18], has been acknowledged by many authors. The POOLING PROBLEM survey by Misener and Floudas [19] has a comprehensive list of references to work in this area.

The STANDARD POOLING PROBLEM (SPP) is defined in terms of a networks with three node layers, referred to as sources, pools and sinks (sinks), respectively. Each arc links either a source to a pool or a pool to a sink. Quality constraints in terms of bounds on the composition are imposed at the sinks. Each bound relates to the relative content of a flow component, referred to as the component. After NP-hardness of the SPP was formally proved [20],

Dey and Gupte [15] showed that the problem is as hard to approximate as the maximum clique problem. The problem remains NP-hard for networks with only two sources and two sinks, and only one flow component subject to constraints [21].

The remainder of the text is organized as follows: Mathematical notation and formulation of the POOLING PROBLEM are provided in Section 2.

To be written.

2 Mathematical Notation and Problem Formulation

To be revised:

Let $D = (N, A)$ be a directed acyclic graph, where the node set $N = S \cup I \cup T$ consists of the disjoint subsets S of *sources*, I of *pools*, and T of *sinks*. Let K be a finite set, and refer to its elements as *flow components* or simply *components*. In the sequel, elements of vectors and matrices defined over the sets N and K are identified by a subscript if they correspond to N , and by a superscript if they correspond to K . Complexity analyses in later sections require that network parameters are defined as rational rather than real numbers. Define the vectors of unit arc costs $\mathbf{c} \in \mathbb{Q}^A$ and arc capacities $\mathbf{h} \in \mathbb{Q}_+^A$. For integers j and n , let $\mathbf{j}^n$ denote the vector with all its n entries equal to j , and let $\mathbf{I}^n$ denote the $(n \times n)$ -identity matrix.

At all sources $s \in S$, flow with a given concentration of each component $k \in K$ may enter D , and flow leaving the network at a sink $t \in T$ must satisfy upper concentration bounds. Define the matrices of *concentration* $\mathbf{Q} \in \mathbb{Q}^{K \times S}$ and *concentration bounds* $\mathbf{U} \in \mathbb{Q}^{K \times T}$. For $s \in S$ and $t \in T$, let $\mathbf{q}_s = (q_s^k)_{k \in K}$ and $\mathbf{u}_t = (u_t^k)_{k \in K}$ be the columns of $\mathbf{Q}$ and $\mathbf{U}$, respectively. That is, q_s^k is the concentration of component k of the flow entering D at s , and u_t^k is the upper bound on the concentration of the flow leaving D at t .

For each pool $i \in I$, the set of sources from which there exists a path to i in D is denoted S_i . Analogously, T_i is the set of sinks to which there is a path from i in D . The sets of upstream and downstream neighbors of node $j \in N$ are denoted N_j^- and N_j^+ , respectively. Without loss of relevant generality, it is assumed that $N_s^- = N_t^+ = \emptyset$ for every $s \in S$ and $t \in T$. The sets of pools adjacent to source s and sink t are denoted $I_s = \{i \in I : (s, i) \in A\}$ and $I_t = \{i \in I : (i, t) \in A\}$, respectively.

A vector $\mathbf{f} \in \mathbb{R}_+^A$ is called a *flow* in D iff it satisfies the capacity and flow conservation constraints:

$$f_{ij} \leq h_{ij} \quad (i, j) \in A, \quad (1)$$

$$\sum_{j \in N_i^-} f_{ji} - \sum_{j \in N_i^+} f_{ij} = 0 \quad i \in I. \quad (2)$$

We refer to the set $F(D, \mathbf{h}) = \{\mathbf{f} \in \mathbb{R}_+^A : (1)-(2) \text{ are satisfied}\}$ as the *flow polytope* of D . For each $\mathbf{f} \in F(D, \mathbf{h})$, define $\mathbf{W} = (\mathbf{w}_j)_{j \in N} \in \mathbb{R}^{K \times N}$ to be a

concentration matrix of $\mathbf{f}$ iff $\mathbf{w}_s = \mathbf{q}_s$ ($s \in S$),

$$\mathbf{w}_i \sum_{j \in N_i^-} f_{ji} = \sum_{j \in N_i^-} \mathbf{w}_j f_{ji}, \quad i \in I \cup T.$$

That is, the concentration $\mathbf{w}_i = (w_i^k)_{k \in K}$ of component k in the flow blended at a pool i , is a convex combination of the entering concentrations $\mathbf{w}_j$ ($j \in N_i^-$), with convexity weights $f_{ji} / \sum_{j' \in N_i^-} f_{j'i}$. These conditions on $\mathbf{w}$ are referred to as the *linear blending* property, and together with (2), they imply directly

$$\sum_{s \in S} \mathbf{q}_s \sum_{j \in N_s^+} f_{sj} = \sum_{t \in T} \mathbf{w}_t \sum_{j \in N_t^-} f_{jt}. \quad (3)$$

At sinks $t \in T$ where $\sum_{i \in I_t} f_{it} > 0$, the upper concentration bounds u_t^k apply, and linear blending yields $\mathbf{w}_t = \sum_{j \in N_t^-} \mathbf{w}_j f_{jt} / \sum_{j \in N_t^-} f_{jt} \leq \mathbf{u}_t$. Thus, $\mathbf{f} \in F(D, \mathbf{h})$ is said to be a *concentration-feasible* flow in D iff $\sum_{j \in N_t^-} \mathbf{w}_j f_{jt} \leq \mathbf{u}_t \sum_{j \in N_t^-} f_{jt}$ ($t \in T$) for any concentration matrix $\mathbf{W}$ of $\mathbf{f}$.

Problem 2.1 The POOLING PROBLEM: Find a concentration-feasible flow $\mathbf{f}$ in D minimizing the total costs $\mathbf{c} \cdot \mathbf{f}$. $\square$

3 Confluent flow and extensions

In the MINIMUM COST FLOW PROBLEM (MCFP), the flow leaving a source and the flow entering a sink are subject to bounds. Let the bounds in question, referred to as the *supply* at source $s \in S$ and the *demand* at sink $t \in T$, respectively, be denoted b_s and b_t . Traditionally in MCFP, the supply represents an upper bound, whereas demand is a *lower* bound on the sink flow. This contrasts SPP, in which both bounds are upper, with the implication that zero flow is feasible in all instances. In the current work, we will consider both these options, and state explicitly whether demand should be considered an upper or a lower bound.

Let

$$F^{\geq}(D, \mathbf{h}, \mathbf{b}) = \left\{ \mathbf{f} \in F(D, \mathbf{h}) : \sum_{j \in N_s^+} f_{sj} \leq b_s (s \in S), \sum_{j \in N_t^-} f_{jt} \geq b_t (t \in T) \right\}$$

and

$$F^{\leq}(D, \mathbf{h}, \mathbf{b}) = \left\{ \mathbf{f} \in F(D, \mathbf{h}) : \sum_{j \in N_s^+} f_{sj} \leq b_s (s \in S), \sum_{j \in N_t^-} f_{jt} \leq b_t (t \in T) \right\}$$

be the flow polytopes corresponding to the two variants of the MCFP. In the current article, the notion of *confluent* flow [22] and related concepts are extensively exploited:

Definition 3.1 A flow $\mathbf{f} \in F(D, \mathbf{h})$ is said to be *confluent* if, at all nodes $i \in S \cup I$, $f_{ij} > 0$ for at most one $j \in N_i^+$. $\square$

That is, confluence means that while flow streams are allowed to merge at pools, it has to leave the pool along a unique arc. Also all flow leaving a source must be allocated to the same arc. The inflow counterpart of confluent flow, where merging is disallowed, is defined analogously:

Definition 3.2 A flow $\mathbf{f} \in F(D, \mathbf{h})$ is said to be *influent* if, at all nodes $i \in I \cup T$, $f_{ji} > 0$ for at most one $j \in N_i^-$. $\square$

The two concepts are combined disjunctively:

Definition 3.3 A flow $\mathbf{f} \in F(D, \mathbf{h})$ is said to be *confluent-influent* if, at all nodes $i \in I$, either $f_{ij} > 0$ for at most one $j \in N_i^+$ or $f_{ji} > 0$ for at most one $j \in N_i^-$. $\square$

Observe that the condition in Definition 3.3 applies to pools only, since no flow enters sources or leaves sinks.

Problem 3.1 The MINIMUM COST CONFLUENT FLOW PROBLEM (MCCFP): Find a flow $\mathbf{f} \in F^{\geq}(D, \mathbf{h}, \mathbf{b})$ satisfying Definition 3.1 such that the cost $\mathbf{c} \cdot \mathbf{f}$ is minimized. $\square$

Analogously, in correspondence with Definitions 3.2 and 3.3, respectively, the MINIMUM COST INFLUENT FLOW PROBLEM (MCIFP) and the MINIMUM COST CONFLUENT-INFLUENT FLOW PROBLEM (MCCIFP) are defined.

3.1 Complexity of fluency-constrained extensions of MCFP

A modified version of MCCFP, in which the largest arc flow is to be minimized, is known to be NP-hard [22], and even NP-hard to approximate within a factor $\frac{4}{3}$. By a simple reduction from the SUBSET SUM PROBLEM, it is next shown that MCCFP as introduced in Definition 3.1 is NP-hard, even in a much restricted instance class.

Proposition 3.1 *MCCFP is NP-hard in instances where D is bipartite, $I = \emptyset$, and $|T| = 2$.*

Proof Consider an instance $(b_1, \dots, b_n, d)$ of the SUBSET SUM PROBLEM, where $1 \leq b_1 \leq \dots \leq b_n \leq d \in \mathbb{Z}_+$. Let D be the complete bipartite digraph with node sets $S = \{s_1, \dots, s_n\}$ and $T = \{t_0, t_1\}$. Let the supply at s_i be b_i ($i = 1, \dots, n$), while the demand at t_0 and t_1 is, respectively, $\sum_{i=1}^n b_i - d$ and d . Both arcs leaving s_i have capacity b_i and arbitrary cost. Because total supply equals total demand, $\mathbf{f} \in F^{\geq}(D, \mathbf{h}, \mathbf{b})$ only if b_i flow units leave source s_i , d units enter sink t_1 , and $\sum_{i=1}^n b_i - d$ units enter sink t_0 . Confluence implies that all the flow leaving s_i enters exactly one of the sinks t_0 or t_1 . Thus, the MCCFP instance $(D, \mathbf{b}, \mathbf{b}, \mathbf{c})$ is feasible if and only if there exists a set $S_1 \subseteq \{1, \dots, n\}$ such that $\sum_{i \in S_1} b_i = d$. $\square$

NP-hardness in restricted instance classes also applies to the influent and confluent-influent counterparts of MCCFP:

Proposition 3.2 *MCIFP is NP-hard in instances where D is bipartite, $I = \emptyset$, and $|S| = 2$.*

Proof Consider the instance of the SUBSET SUM PROBLEM introduced in the proof of Proposition 3.1. Let D be the complete bipartite digraph with node sets $S = \{s_0, s_1\}$ and $T = \{t_1, \dots, t_n\}$. Let the demand at t_i be b_i ($i = 1, \dots, n$), while the supply at s_0 and s_1 is, respectively, $\sum_{i=1}^n b_i - d$ and d . Finally, c_{st_i} is arbitrary and $h_{st_i} = b_i$ for $s \in \{s_0, s_1\}$. Following the arguments in the proof of Proposition 3.1, $(D, \mathbf{b}, \mathbf{b}, \mathbf{c})$ is a feasible MCIFP instance if and only if $\sum_{i \in S_1} b_i = d$ for some $S_1 \subseteq \{1, \dots, n\}$. $\square$

Proposition 3.1 also applies if MCCFP is defined with the demand as upper bounds. That is, if $F^\geq$ is replaced by $F^\leq$ in Problem 3.1. Consider the digraph introduced in the proof of the proposition, and let the cost $c_{st} = -2$ for all $s = s_1, \dots, s_n$ and $t = t_1$. For $t = t_0$, let $c_{st} = -1$. Hence, the minimum cost is $-t - \sum_{i=1}^n b_i$ if and only if $\sum_{i \in S_1} b_i = d$ for some $S_1 \subseteq \{1, \dots, n\}$. Analogously, Proposition 3.2 applies even if MCIFP is defined with respect to $F^\leq$ rather than $F^\geq$.

Let $\text{len}(D)$ denote the maximum length of paths from a source to a sink in D . In bipartite digraphs consisting only of sources and sinks (i.e, $\text{len}(D) = 1$), any flow is confluent-influent. Introducing an intermediate set I of nodes renders MCCIFP NP-hard, even if there are no arcs between any two nodes in I .

Proposition 3.3 *MCCIFP is NP-hard in instances where $\text{len}(D) = |T| = 2$.*

Proof Consider the instance of the SUBSET SUM PROBLEM introduced in the proof of Proposition 3.1. Let D be the complete bipartite digraph with node sets $S = \{s_1, \dots, s_n, s'_1, \dots, s'_n\}$, $I = \{p_1, \dots, p_n\}$, and $T = \{t_0, t_1\}$. All arcs of D are incident to I , where $N_{p_i}^- = \{s_i, s'_i\}$ and $N_{p_i}^+ = \{t_0, t_1\}$. Let the supply at s_i and s'_i be b_i ($i = 1, \dots, n$), while the demand at t_0 and t_1 is, respectively, $2\sum_{i=1}^n b_i - 2d$ and $2d$. Both arcs entering p_i have capacity b_i , whereas the leaving arcs have capacity $2b_i$. Arc costs are arbitrary.

Consider a feasible flow $\mathbf{f}$ in the MCCIFP instance $(D, \mathbf{h}, \mathbf{b}, \mathbf{c})$ hence defined. Then, since total supply equals both the total capacity of arcs leaving S and total demand, $f_{sp_i} = h_{sp_i} > 0$ for all $s = s_i, s'_i$ and $i = 1, \dots, n$. It follows that $\mathbf{f}$ is confluent, as it is not influent at any p_i . Hence, all $2b_i$ units of flow leaving p_i are sent to the same sink, t_0 or t_1 . Since t_1 receives $2d$ units of flow, there is a set $I_1 \subseteq \{1, \dots, n\}$ such that $\sum_{i \in I_1} f_{p_i t_1} = 2\sum_{i \in I_1} b_i = 2d$.

Coversely, if $\sum_{i \in I_1} b_i = d$ for some $I_1 \subseteq \{1, \dots, n\}$, then the flow $\mathbf{f}$, where $f_{s_i p_i} = f_{s'_i p_i} = b_i$ ($i = 1, \dots, n$), $f_{p_i t_0} = \begin{cases} 2b_i, & i \notin I_1 \\ 0, & i \in I_1, \end{cases}$ and $f_{p_i t_1} = \begin{cases} 2b_i, & i \in I_1 \\ 0, & i \notin I_1, \end{cases}$ is feasible in the MCCIFP instance. $\square$

3.2 Weak fluency conditions

Different digraphs may be equivalent in the perspective of the MCFP. Splitting any node into two new ones joined by an arc with sufficiently large capacity and zero cost, renders the MCFP instance unchanged. In contrast, the operation largely alters the MCCIFP instance, since any flow in the modified network is confluent-influent. A concept that is more resilient to likely graph alterations is introduced next.

For any flow $\mathbf{f}$ in D , let $D(\mathbf{f}) = (N(\mathbf{f}), A(\mathbf{f}))$ denote the subgraph of D , where $A(\mathbf{f}) \subseteq A$ consists of arcs $(i, j) \in A$ where $f_{ij} > 0$, and $N(\mathbf{f}) \subseteq N$ consists of nodes in N with at least one incident arc in $A(\mathbf{f})$.

Definition 3.4 A flow $\mathbf{f}$ in D is said to be *weakly confluent* if, for all $i \in N(\mathbf{f})$, $D(\mathbf{f})$ has paths from i to at most one sink $t \in T \cap N(\mathbf{f})$. If $D(\mathbf{f})$ has paths to i from at most one source $s \in S \cap N(\mathbf{f})$, then $\mathbf{f}$ is said to be *weakly influent*. If either of the conditions holds at all $i \in N(\mathbf{f})$, then $\mathbf{f}$ is *weakly confluent-influent*. $\square$

It is readily observed that if $\mathbf{f}$ is confluent, then it is also weakly confluent. Analogous claims hold for the other two fluency conditions. Further, in bipartite digraphs, weak confluence (weak influence) implies confluence (influence). Finally, if $\text{len}(D) = 2$ (see the proof of Proposition 3.3), then a weakly confluent-influent flow in D is also confluent-influent. For these reasons, Propositions 3.1-3.3 apply even if the fluency condition is to be understood in the weak sense.

Acknowledgment

The work of the second author has been funded by grants from the Spanish state (TIN2012-37483-C03-01 and TIN2015-66680), Junta de Andalucía (P11-TIC-7176), in part financed by the European Regional Development Fund (ERDF).

References

1. G. J. Stigler, The cost of subsistence, *American Journal of Agricultural Economics* 27 (2) (1945) 303–314.
2. G. B. Dantzig, The diet problem, *Interfaces* 20 (4) (1990) 43–47. doi:10.1287/inte.20.4.43.
3. C. A. Haverly, Studies of the behavior of recursion for the pooling problem, *ACM SIGMAP Bulletin* 25 (1978) 19–28.
4. T. E. Baker, L. S. Lasdon, Successive linear programming at exxon, *Management Science* 31 (3) (1985) 264–274. doi:10.1287/mnsc.31.3.264.
5. C. W. DeWitt, L. S. Lasdon, A. D. Waren, D. A. Brenner, S. A. Melhem, Omega: An improved gasoline blending system for texaco, *Interfaces* 19 (1) (1989) 85–101. doi:10.1287/inte.19.1.85.
6. C. A. Floudas, V. Visweswaran, A global optimization algorithm (gop) for certain classes of nonconvex nlp: I. theory, *Computers & Chemical Engineering* 14 (12) (1990) 1397–1417. doi:10.1016/0098-1354(90)80020-C.

7. C. Audet, J. Brimberg, P. Hansen, S. L. Digabel, N. Mladenović, Pooling problem: Alternate formulations and solution methods, *Management Science* 50 (6) (2004) 761–776. doi:10.1287/mnsc.1030.0207.
8. L. R. Foulds, D. Haugland, K. Jörnsten, A bilinear approach to the pooling problem, *Optimization* 24 (1–2) (1992) 165–180. doi:10.1080/02331939208843786.
9. R. Misener, J. P. Thompson, C. A. Floudas, Apogee: Global optimization of standard, generalized, and extended pooling problems via linear and logarithmic partitioning schemes, *Computers & Chemical Engineering* 35 (5) (2011) 876–892. doi:10.1016/j.compchemeng.2011.01.026.
10. N. V. Sahinidis, M. Tawarmalani, Accelerating branch-and-bound through a modeling language construct for relaxation-specific constraints, *Journal of Global Optimization* 32 (2) (2005) 259–280. doi:10.1007/s10898-004-2705-8.
11. V. Visweswaran, C. A. Floudas, Computational results for an efficient implementation of the gop algorithm and its variants, in: I. E. Grossmann (Ed.), *Global Optimization in Chemical Engineering*, Kluwer Academic Publishers, Dordrecht, The Netherlands, 1996, pp. 111–153.
12. N. Adhya, M. Tawarmalani, N. V. Sahinidis, A lagrangian approach to the pooling problem, *Industrial & Engineering Chemistry Research* 38 (5) (1999) 1956–1972. doi:10.1021/ie980666q.
13. H. Almutairi, S. Elhedhli, A new lagrangean approach to the pooling problem, *Journal of Global Optimization* 45 (2) (2009) 237–257. doi:10.1007/s10898-008-9371-1.
14. A. Ben-Tal, G. Eiger, V. Gershovitz, Global minimization by reducing the duality gap, *Mathematical Programming* 63 (2) (1994) 193–212. doi:10.1007/BF01582064.
15. S. S. Dey, A. Gupte, Analysis of milp techniques for the pooling problem, *Operations Research* 63 (2) (2015) 412–427. doi:10.1287/opre.2015.1357.
16. J. Kallrath, Solving planning and design problems in the process industry using mixed integer and global optimization, *Annals of Operations Research* 140 (1) (2005) 339–373. doi:10.1007/s10479-005-3976-2.
17. B. Galán, I. E. Grossmann, Optimal design of distributed wastewater treatment networks, *Industrial & Engineering Chemistry Research* 37 (10) (1998) 4036–4048. doi:10.1021/ie980133h.
18. R. Misener, C. A. Floudas, Global optimization of large-scale generalized pooling problems: Quadratically constrained minlp models, *Industrial & Engineering Chemistry Research* 49 (11) (2010) 5424–5438. doi:10.1021/ie100025e.
19. R. Misener, C. A. Floudas, Advances for the pooling problem: Modeling, global optimization, and computational studies, *Applied and Computational Mathematics* 8 (1) (2009) 3–22.
20. M. Alfaki, D. Haugland, Strong formulations for the pooling problem, *Journal of Global Optimization* 56 (3) (2013) 897–916. doi:10.1007/s10898-012-9875-6.
21. D. Haugland, The computational complexity of the pooling problem, *Journal of Global Optimization* 64 (2) (2016) 199–215. doi:10.1007/s10898-015-0335-y.
22. J. Chen, R. Rajaraman, R. Sundaram, Meet and merge: Approximation algorithms for confluent flows, *Journal of Computer and System Sciences* 72 (3) (2006) 468–489. doi:10.1016/j.jcss.2005.10.003.