

Real time messaging, file sharing and powerful search. Slack: where work happens.

Learn More x

Practice GATE CS Placements Videos Contribute  
Login/Register

## Circular Queue | Set 2 (Circular Linked List Implementation)

Prerequisite – [Circular Singly Linked List](#)

We have discussed basics and how to implement circular queue using array in set 1.

[Circular Queue | Set 1 \(Introduction and Array Implementation\)](#)

In this post another method of circular queue implementation is discussed, using Circular Singly Linked List.

Operations on Circular Queue:

- **Front:** Get the front item from queue.
- **Rear:** Get the last item from queue.
- **enqueue(value)** This function is used to insert an element into the circular queue. In a circular queue, the new element is always inserted at Rear position.

**Steps:**

1. Create a new node dynamically and insert value into it.
2. Check if front==NULL, if it is true then front = rear = (newly created node)
3. If it is false then rear=(newly created node) and rear node always contains the address of the front node.


- **dequeue()** This function is used to delete an element from the circular queue. In a queue, the element is always deleted from front position.

**Steps:**

1. Check whether queue is empty or not means front == NULL.
2. If it is empty then display Queue is empty. If queue is not empty then step 3

Real time messaging, file sharing and powerful search. Slack: where work happens.

Learn More x



**Recommended:** Please try your approach on {IDE} first, before moving on to the solution.

```
// C or C++ program for insertion and
// deletion in Circular Queue
#include <bits/stdc++.h>
using namespace std;

// Structure of a Node
struct Node
{
    int data;
    struct Node* link;
};

struct Queue
{
    struct Node *front, *rear;
};

// Function to create Circular queue
void enQueue(Queue *q, int value)
{
    struct Node *temp = new Node;
```

Real time messaging, file sharing and powerful search. Slack: where work happens.

Learn More x

```
else
    q->rear->link = temp;

q->rear = temp;
q->rear->link = q->front;
}

// Function to delete element from Circular Queue
int deQueue(Queue *q)
{
    if (q->front == NULL)
    {
        printf ("Queue is empty");
        return INT_MIN;
    }

    // If this is the last node to be deleted
    int value; // Value to be dequeued
    if (q->front == q->rear)
    {
        value = q->front->data;
        free(q->front);
        q->front = NULL;
        q->rear = NULL;
    }
    else // There are more than one nodes
    {
        struct Node *temp = q->front;
        value = temp->data;
        q->front = q->front->link;
        q->rear->link = q->front;
        free(temp);
    }

    return value ;
}

// Function displaying the elements of Circular Queue
void displayQueue(struct Queue *q)
{
    struct Node *temp = q->front;
    printf("\nElements in Circular Queue are: ");
    while (temp->link != q->front)
    {
        printf("%d ", temp->data);
        temp = temp->link;
    }
    printf("%d", temp->data);
}
```

Real time messaging, file sharing and powerful search. Slack: where work happens.

Learn More x

```
1 // Create a queue and initialize front and rear
Queue *q = new Queue;
q->front = q->rear = NULL;

// Inserting elements in Circular Queue
enqueue(q, 14);
enqueue(q, 22);
enqueue(q, 6);

// Display elements present in Circular Queue
displayQueue(q);

// Deleting elements from Circular Queue
printf("\nDeleted value = %d", dequeue(q));
printf("\nDeleted value = %d", dequeue(q));

// Remaining elements in Circular Queue
displayQueue(q);

enqueue(q, 9);
enqueue(q, 20);
displayQueue(q);

return 0;
}
```

[Run on IDE](#)

Output:

```
Elements in Circular Queue are: 14 22 6
Deleted value = 14
Deleted value = 22
Elements in Circular Queue are: 6
Elements in Circular Queue are: 6 9 20
```

**Time Complexity:** Time complexity of enqueue(), dequeue() operation is  $O(1)$  as there is no loop in any of the operation.

**Note :** In case of linked list implementation, a queue can be easily implemented without being circular. However in case of array implementation, we need a circular queue to save space.

Real time messaging, file sharing and powerful search. Slack: where work happens.

[Learn More](#) x

page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

## GATE CS Corner    Company Wise Coding Practice

[Linked Lists](#)   [Queue](#)

### Recommended Posts:

[Top 20 Linked List Interview Question](#)

[Write a program function to detect loop in a linked list](#)

[Given a linked list of line segments, remove middle points](#)

[Minimum time required to rot all oranges](#)

([Login](#) to Rate and Mark)

1

Average Difficulty : **1/5.0**  
Based on **1** vote(s)

Add to TODO List

Mark as DONE

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

Load Comments

Share this post!

@geeksforgeeks, Some rights reserved

Contact Us!

About Us!

Advertise with us!

Privacy Policy

