MASTER SOP

From source video to character remake

Greg #1 / Five-video batch / November 11, 2026

What was actually done, how the evidence was captured, and how to repeat the process with other characters.

V01 - Jupi / golden milk demonstration: 149.800s, 50 cards, 150 source stills.

V02 - Apple cider vinegar neck-cloth demonstration: 29.767s, 8 cards, 24 source stills.

V03 - Parmesan green bean fries: 34.333s, 12 cards, 36 source stills.

V04 - Purple sweet potato mochi-style bites: 52.767s, 20 cards, 60 source stills.

V05 - Turmeric coconut-oil molded bites: 32.733s, 15 cards, 45 source stills.

Production stage: breakdowns and Greg frame/motion instructions complete. Greg image and video generation remains unperformed; visual/motion QA stays pending.

What this package delivers

Five independent reverse-engineering packs, each with its source MP4, full ASR-assisted transcript, raw word timing estimates, standard SRT, exact source START/MID/END screenshots, one-second contact sheets, shot/frame manifests, visual PDF, editable Markdown and a separate copy-ready Greg prompt for every shot/beat card. The screenshots are source evidence; they are not Greg renders.

Scope completed: source analysis, extraction, production planning and documented remake instructions. Scope not executed: Greg image generation, video generation, lip-sync, music/SFX isolation or final video editing. Frame-pair and clip QA are correctly marked PENDING. This document records the actual process below and separately describes the production steps to run next.

Requested destination: Greg 1 / 2026-11 November / 2026-11-11 - Five Video Remakes - Greg 1. A separate new dated folder was created so existing November work was not overwritten.

1. Locate sources and choose identity

Used the five attached local MP4 files, not a thumbnail image as a substitute for video. Probed each file with ffprobe to read actual video dimensions, frame count, frame rate and duration. All five are vertical 9:16 at 30 fps; the neck-cloth video is only 360 x 640, while the others are 720 x 1280. Source file names and SHA-256 digests are preserved in SOURCE_PROVENANCE.json.

Searched connected Drive for the Greg #1 November hierarchy, checked the destination, and created the new dated project folder with five video subfolders. Retrieved and visually inspected the newer four-view mature-man character reference. That newer sheet is the face/body authority for these Greg #1 plans. An older Greg kitchen image was also inspected but was not blended into the chosen face.

Greg #1 means the plaid version. The selected identity sheet itself shows a white shirt; the prompts explicitly request plaid. An exact approved plaid pattern was not available in the selected reference, so the first rendered Greg frame must establish a single pattern to reuse. Do not accidentally switch to Greg #2 denim/tattoos.

2. Inspect the visual chronology

Created initial low-resolution overview sheets at about one-second intervals using ffmpeg, then inspected the full sequence of overview pages. Used OpenCV frame differences on 90 x 160 grayscale thumbnails to propose edit/action boundaries: mean absolute difference above 12, local maximum within five frames, and more than twice the nearby median. These were candidates, not automatically accepted cuts.

Extracted before/after pairs around candidate boundaries and visually compared them. Removed many false positives caused by hand movement, product pushes, face motion and camera reframing. Kept intentional brief whisk inserts, ingredient additions, prop reveals and room changes. Some continuous performance passages are divided into beat cards for production; their entry is labelled beat or continuous beat rather than claiming a hard cut.

Recorded source-specific setups, props, visual state, camera moves and continuity issues. The long Jupi source includes a staged digestive-vessel demonstration and an ingredient montage. The neck-cloth source uses two-person staging and several pushes toward the nape. Green beans use

true overhead inserts and an oven cut. Purple bites begin with a result preview. Turmeric bites switch from a camper to a cream kitchen at 00:26.933.

Camera motion was classified by visible evidence: a hand moving a mug or food toward the lens is a prop push; it is not automatically a camera dolly. Where optical/digital zoom cannot be distinguished from motion, the pack describes the framing change without inventing a lens or percentage.

3. Extract the reusable screenshot evidence

For each card, assigned a zero-based START frame and OUT-exclusive boundary. MID is floor((START + OUT - 1) / 2); END is OUT - 1. Extracted all three directly from the source at full native resolution using OpenCV. Saved JPEG at quality 94 with card ID, role and frame index in its filename. FRAME_MANIFEST.csv lists every screenshot and timestamp.

Created final contact sheets from exact frame n x 30 at each whole second, replacing the approximate initial overview samples. The delivered atlases therefore start at source frame 0 and carry exact timestamp/frame labels. They provide browsing context; the START/MID/END stills and original MP4 remain the detailed reference.

Frame time is frame index / 30. OUT is an edit boundary, not a still image. For example, a card ending at OUT frame 139 retains frames through 138. Source durations are never replaced with a generic six-second clip length. SHOT_MANIFEST.csv preserves every retained duration, entry type and planned generation target.

4. Recover dialogue and synchronize it

Extracted audio as 16 kHz mono WAV with ffmpeg. Ran faster-whisper small.en locally on CPU with int8 compute, beam size 5, word timestamps enabled and voice-activity detection enabled. Stored the complete original ASR output, including word estimates and probabilities, as ASR_RAW.json. The audio was read through Python wave/numpy for transcription after a decoder compatibility issue.

Compared targeted ambiguous terms with visible captions/product labels. In V01 corrected ASR "in a line" to "inulin", "GP/JUPY hydration" to "Jupi hydration", and "pomine" to "papain" using those on-screen references. Preserved the unmodified ASR output for audit. No claim is made that every spoken word was independently listened to and verified.

Wrote a readable transcript and standard SRT with approximate phrase timings. Each card includes dialogue from overlapping ASR segments; a sentence can therefore appear on two adjacent cards. That repetition is an alignment aid, not an instruction to speak it twice. Use the complete transcript and original MP4 when conforming the final voice track.

Before recording: listen at normal speed, check every word, verify proper names, mark breaths and emphasis, and tighten subtitle word cues against waveform/frame playback. Preserve source pace and sentence overlaps across inserts. Do not force dialogue into a six-second render by accelerating it globally. Music and incidental sound effects were not separately identified or isolated in this pass.

5. Reverse-engineer lighting, texture and skin

Use each video's source as the style and environment authority. The Greg identity sheet only establishes face/body. V01 and V04 use soft side-window light in a cream kitchen; V02 uses bright diffuse daylight and a softer low-resolution image; V03 uses neutral daylight with pronounced

marble texture; V05 uses warm wood bounce in the camper before cutting to brighter cream-kitchen light.

Keep the original shadow side, shadow-edge softness, specular highlights, window direction, exposure impression, white balance, depth of field and compression character. Skin must retain Greg's own colour and age details under that light: pores, forehead creases, moustache texture and normal shine. Match realism and texture, not the source actor's ethnicity or identity.

Do not add hard iPhone flash just because it was requested for other campaigns. These sources do not all have that look. Do not add beauty smoothing, plastic skin, HDR clarity, heavy cinematic contrast or a new kitchen. Exact Kelvin, aperture, focal length and light power cannot be recovered from these compressed sources; use reference matching, not fabricated numerical settings.

For QA, compare source and remake side-by-side at the same size. Check cabinet edges, window highlights, plate shadows, glass reflections, food colour, face brightness, relative head size and focus falloff. Then examine the face and hands at 100% for waxiness, edge halos, invented wrinkles or mismatched skin tone. A text prompt is not a guarantee of pixel stability.

6. Build START and END frames with Greg

This stage is specified but not yet executed. For each card, open its source START, source MID, source END and GREG1_IDENTITY.png. Use a controlled edit or subject mask to replace the lead presenter and associated hands while retaining the source scene. Generate the START first. Keep captions/UI out of generated image pixels; add approved captions in the editor.

Establish Greg face, plaid pattern, sleeve length, skin detail and hand appearance once, then reuse the approved frame as a character/style reference across setups. Maintain a separate environment reference per source setup. Do not use a face reference as permission to copy its studio lighting or background.

Create END by editing the actual approved Greg START. Use source END as the target for pose, camera framing and prop/food state. Keep identity, clothing, exposure and architecture consistent. For static cameras, unchanged background pixels should remain stable; for intentional zooms/reframes, projection may change while the room layout remains the same. A true cut receives a separate setup and frame pair.

Each prompts/ file gives input reference roles, planned output names, allowed changes, start/end state, camera action, retained timing and QA checks. Planned Greg filenames are not presented as existing assets. Inspect both generated frames before marking pair QA passed. Reject extra fingers, disconnected contact points, mirrored labels, changing mugs, random ingredients or disappearing props.

7. Animate and edit to source timing

This stage is not yet executed. The pack uses 6- or 8-second generation targets as planning windows, with a separately preserved source retained duration. They are not a statement that a particular current Veo/VO3 interface supports every control. Check the selected model's live duration, START/END-reference and audio options before rendering.

Short source inserts must stay short. A seven-frame whisk insert is roughly 0.233 seconds in the edit, even if its usable motion comes from a longer render. Trim the natural action window; do not fill

every shot with six seconds of slow movement. Separate each true cut into its own clip so the model cannot invent a transition between different camera setups.

For continuous talking-head beats, use compatible endpoints or a longer continuous take where supported, then conform to the original sequence. Match the source voice cadence, emphasis, forward lean and eye contact with Greg's voice identity. Do not clone the original performer's voice. Preserve source dialogue windows while recording approved remake wording.

Keep object motion distinct from camera motion: a lifted jar, mug or bite grows in frame through hand movement. Use an edit crop for a simple punch-in only when it matches the observed reference. Avoid adding orbits, lens breathing or camera travel to a locked pouring shot. Sound design and subtitles are a separate final-edit pass.

8. Continuity ledger and copy decisions

V01: preserve filled vessel -> additions -> still blocked -> orange pour -> bucket discharge -> empty vessel/residue. Do not refill the vessel in later sales shots. Timer reads a different elapsed period from the spoken hook. Product is Jupi in the source. A different brand, claims, ingredient panel, testimonial history and offer must be supplied/approved before making a branded Greg version.

V02: wet-cloth hook is followed by a later preparation demonstration. Track the stain and nape position. A second character reference is not supplied, so that role remains unassigned. The medical explanation and acid-compress schedule are analytical source material, not approved treatment guidance.

V03: raw beans -> egg -> Parmesan jar -> tray -> oven -> cooked hero. Carry cooked coating and plate quantity through the talking section. Source omits baking time and the unit for 400 degrees. V04: finished preview -> cooked potato -> mash -> milk -> starch -> rolled balls -> fryer -> cooked result. Later smooth pedestal balls do not exactly match the earlier browned batch; choose an explicit continuity correction before rendering.

V05: source alternates solid and melted oil appearances. Keep the issue visible in the source breakdown; for a cleaner remake, approve a consistent melted state before generating inserts. Preserve the camper-to-kitchen cut. Do not reproduce the stop-ibuprofen instruction or imply homemade bites are equivalent medication. Source medical assertions and personal claims across these videos are not independently verified.

9. Repeat with other characters

Duplicate a complete video pack for each approved character; preserve source IDs, source timestamps and evidence files unchanged. Add that character's actual reference sheet and wardrobe/environment decisions. Replace identity tokens in the prompts and planned render filenames. Do not rewrite the source analysis just because the character changes.

Generate and inspect one anchor START per setup, then derive its END. Replace all visible presenter hands, forearms and reflected faces consistently. Keep the same source lighting/texture and camera/prop choreography unless the user explicitly requests a new environment. Supporting performers need their own identity references.

Run pair QA and clip QA independently for each character. Keep a simple status table: reference selected, START rendered, END derived, pair inspected, clip rendered, clip inspected, edit

conformed, dialogue approved. Save the character version in its own folder so Greg #1, Greg #2, Becky, Steve and other cast cannot overwrite one another.

10. Verify and hand off

Validate source coverage: the first card starts at frame 0, each next START equals the previous OUT, and the last OUT equals the source frame count. Verify total retained frames, unique card IDs, readable image paths and existing prompts. Do not claim frame-pair or motion quality passed when no remake images/video have been generated.

Generate readable PDFs with ReportLab, render all pages with PyMuPDF, cross-check samples with Poppler and inspect representative cover, shot and transcript layouts. Keep an editable Markdown version and CSV/JSON manifests. Bundle each original MP4 plus evidence, identity reference and prompts into its own ZIP. The complete batch archive also includes the SOP and reproducibility scripts.

Upload the individual PDF, editable playbook and ZIP to each dated Drive subfolder. Put the master SOP and index at the project root. Read the destination folders back after uploading to confirm files exist. Retain the final PDF set and complete batch archive as downloadable deliverables. Upload receipts and local validation results should be checked before reporting completion.

Reproducibility

The complete batch ZIP includes the scripts named in MASTER_SOP.md. Source provenance records and raw transcripts are retained in each video folder. The scripts document the executed process; they require their listed dependencies and source paths to rerun.