Problem 08: The Last Traveler of the Clockwork Kingdom

Time limit: 1 second

In the ancient Clockwork Kingdom, time itself flows through a massive circular chain of **arcane pylons**. Each pylon contains a reservoir of **temporal essence**, and traveling from one pylon to the next consumes a certain amount of that essence.

You are the kingdom's last Temporal Traveler capable of drawing essence from the pylons to sustain your journey.

But there's a catch:
You must begin your journey at **one** of these pylons with no essence at all, and attempt to complete a full rotation around the Clockwork Ring. At every pylon:

- You **absorb** the temporal essence stored there
- You **spend** a fixed amount of essence to move to the next pylon in the ring

Your task is to determine **which pylon** can serve as the starting point that allows you to complete the entire circular journey **without your essence ever dropping below zero**.

If multiple such pylons exist, output the pylon with the **lowest index**.
If no pylon allows a full rotation, you must return **-1**, meaning the Clockwork Ring cannot be traversed.

Input:

The input consists of the following:

- First line: integer **n**, the number of pylons in the Clockwork Ring *(1 ≤ n ≤ 100000)*
- Second line: **n integers**, where the ith integer is the **essence[i]** stored in pylon *i* *(1<=essence[i]<=10^9)*
- Third line: **n integers**, where the ith integer is the **drain[i]** (1<=drain[i]<=10^9), the essence required to move from pylon ***i*** to pylon **(i+1)** (wrapping to 1 at the end)

Output:

A single integer i.e. the **lowest index** of the pylon from which a full temporal rotation is possible, or **-1** if the journey is doomed from the start.

Sample Input	**Sample Output**
5 1 2 3 4 5 3 4 5 1 2	4

Sample Input	**Sample Output**
3 2 3 4 3 4 3	-1