

Results of the GECCO 2017 Competition on Niching Methods for Multimodal Optimization

M.G. Epitropakis¹, M. Preuss², X. Li³, and A. Engelbrecht³

¹Data Science Institute, Department of Management Science, Lancaster University, UK

²ERCIS, WWU Muenster, Muenster, Germany

³School of Computer Science and Information Technology, RMIT University, Australia

⁴Department of Computer Science, University of Pretoria, South Africa

GECCO 2017 Competition on Niching Methods

m.epitropakis@lancaster.ac.uk
xiaodong.li@rmit.edu.au

mike.preuss@uni-muenster.de
engel@cs.up.ac.za

Table of contents

1. Introduction

2. Participants

3. Results

4. Winners

5. Summary

Introduction

- Many real-world problems are “multi-modal” by nature, i.e., multiple satisfactory solutions exist
- **Niching methods:** promote and maintain formation of multiple stable subpopulations within a single population
 - **Aim:** maintain diversity and locate multiple globally optimal solutions.
- **Challenge:** Find an efficient optimization algorithm, which is able to **locate multiple global optimal solutions** for multi-modal problems with various characteristics.

Competition: GECCO 2016 – CEC 2013/2015/2016/2017

Provide a common platform that encourages fair and easy comparisons across different niching algorithms.

X. Li, A. Engelbrecht, and M.G. Epitropakis, “**Benchmark Functions for CEC’2013 Special Session and Competition on Niching Methods for Multimodal Function Optimization**”, Technical Report, Evolutionary Computation and Machine Learning Group, RMIT University, Australia, 2013

- 20 benchmark multi-modal functions with different characteristics
- 5 accuracy levels: $\varepsilon \in \{10^{-1}, 10^{-2}, 10^{-3}, 10^{-4}, 10^{-5}\}$
- The benchmark suite and the performance measures have been implemented in: C/C++, Java, MATLAB, (Python soon)

Benchmark function set

X. Li, A. Engelbrecht, and M.G. Epitropakis, “[Benchmark Functions for CEC’2013 Special Session and Competition on Niching Methods for Multimodal Function Optimization](#)”, Technical Report, Evolutionary Computation and Machine Learning Group, RMIT University, Australia, 2013

Id	Dim.	# GO	Name	Characteristics
F_1	1	2	Five-Uneven-Peak Trap	Simple, deceptive
F_2	1	5	Equal Maxima	Simple
F_3	1	1	Uneven Decreasing Maxima	Simple
F_4	2	4	Himmelblau	Simple, non-scalable, non-symmetric
F_5	2	2	Six-Hump Camel Back	Simple, not-scalable, non-symmetric
F_6	2,3	18,81	Shubert	Scalable, #optima increase with D, unevenly distributed grouped optima
F_7	2,3	36,216	Vincent	Scalable, #optima increase with D, unevenly distributed optima
F_8	2	12	Modified Rastrigin	Scalable, #optima independent from D, symmetric
F_9	2	6	Composition Function 1	Scalable, separable, non-symmetric
F_{10}	2	8	Composition Function 2	Scalable, separable, non-symmetric
F_{11}	2,3,5,10	6	Composition Function 3	Scalable, non-separable, non-symmetric
F_{12}	2,3,5,10	8	Composition Function 4	Scalable, non-separable, non-symmetric

Largely follows the procedures of the 2013/2015 CEC niching competitions, adopt new performance criteria:

Improved Scenarios

- Include information on the **resources (time, function evaluations)** needed to find the global optima, not only the fraction of successes within a given time period (number of evaluations), and
- Take into account **the size of the final solution set**, and reward small sets that mostly consist of the sought optima only.

Three different Scenarios (performance evaluation):

- **Scenario I:** Adopt the CEC2013/2015 competition ranking procedure (based on average **Peak Ratio**), to facilitate straight forward comparisons with all previous competition entries.
- **Scenario II:** Adopt the **(static) F1 measure** to take into account the recall and precision of the final solution sets
- **Scenario III:** Adopt the **(dynamic) F1 measure** integral over the whole runtime to take into account the computational efficiency of the submitted algorithm

Ranking based on average values across all problems/accuracy levels of the aforementioned measures are used to decide the winner.

Participants

Submissions to the competition:

- (**SSGA-DMRTS-DDC-F: SSGA**) A Steady State Genetic Algorithm with the Dynamic Modified Restricted Tournament Selection Method, by Camila Silva de Magalhães, Lincon Onório Vidal, Matheus Muller Pereira da Silva, Raquel Gomes Gonçalves Farias, Helio José Correa Barbosa, and Laurent Emmanuel Dardenne, from UFRJ and LNCC, Brazil [3]
- (**RLSIS**): Restarted Local Search with Improved Selection of Starting Points, Simon Wessing, [1]
- (**RSCMSAES**): Benchmarking Covariance Matrix Self Adaption Evolution Strategy with Repelling Subpopulations for GECCO 2017 Competition on Multimodal Optimization, Ali Ahrari, Kalyanmoy Deb and Mike Preuss [2]

Implemented algorithms for comparisons:



- (CMA-ES) The classic CMA-ES with restarts
- (IPOP-CMA-ES) The classic IPOP-CMA-ES
- (NEA1,NEA2,NEA2+) Niching the CMA-ES via Nearest-Better Clustering

Results



Summary:

- 3 new search algorithms
- 5 comparators based on the previous competitions @ GECCO 2016
- 20 multi-modal benchmark functions
- 5 accuracy levels $\varepsilon \in \{10^{-1}, 10^{-2}, 10^{-3}, 10^{-4}, 10^{-5}\}$
- Results: **per accuracy level & over all accuracy levels**
- Latest version always in the repository:
<https://github.com/mikeagn/CEC2013>



Scenario I: Accuracy level $\varepsilon = 10^{-1}$





Scenario I: Accuracy level $\varepsilon = 10^{-2}$





Scenario I: Accuracy level $\varepsilon = 10^{-3}$




Scenario I: Accuracy level $\varepsilon = 10^{-4}$






Scenario I: Accuracy level $\varepsilon = 10^{-5}$






Scenario I: Overall performance






Scenario II: Accuracy level $\varepsilon = 10^{-1}$






Scenario II: Accuracy level $\varepsilon = 10^{-2}$






Scenario II: Accuracy level $\varepsilon = 10^{-3}$




Scenario II: Accuracy level $\varepsilon = 10^{-4}$




Scenario II: Accuracy level $\varepsilon = 10^{-5}$




Scenario II: Overall performance




Scenario III: Accuracy level $\varepsilon = 10^{-1}$




Scenario III: Accuracy level $\varepsilon = 10^{-2}$




Scenario III: Accuracy level $\varepsilon = 10^{-3}$



Scenario III: Accuracy level $\varepsilon = 10^{-4}$



Scenario III: Accuracy level $\varepsilon = 10^{-5}$



Overall performance

Alg.	Sc.I	Rank	Sc.II	Rank	Sc.III	Rank	Mean Rank	Final Rank
RLSIS	0.700	3	0.792	2	0.3938	3	2.666	2
RSCMSA	0.826	1	0.899	1	0.7915	1	1.000	1
SSGA	0.755	2	0.052	8	0.2276	6	6.000	6
cma	0.574	6	0.073	7	0.1795	7	6.666	7
ipop	0.317	8	0.245	4	0.2996	4	5.333	5
nea1	0.540	7	0.093	6	0.1145	8	7.000	8
nea2	0.647	5	0.118	5	0.2509	5	5.000	4
nea2+	0.689	4	0.721	3	0.7579	2	3.000	3

Winners

Overall ranking on all scenarios

1. (**rs-cmsa-es**): Covariance Matrix Self Adaption Evolution Strategy with Repelling Subpopulations, Ali Ahrari, Kalyanmoy Deb and Mike Preuss
2. (**rlsis**): Restarted Local Search with Improved Selection of Starting Points, Simon Wessing
3. (**nea2+**): Niching the CMA-ES via Nearest-Better Clustering: First Steps Towards an Improved Algorithm, Mike Preuss

Note: The algorithms have not been fine-tuned for the specific benchmark suite!

Summary

Summary

- Three search algorithms in new Scenarios
- **Winner: rs-cmsa-es:** Covariance Matrix Self Adaption Evolution Strategy with Repelling Subpopulations
 - Best on average performance, (CMA-ES, Repelling Sub-populations)
- Places 2 and 3:
 - **rlsis:** Restarted Local Search with Improved Selection of Starting Points
 - **nea2+:** Niching the CMA-ES via Nearest-Better Clustering (improved)

Conclusions (2)

- The competition provides a boost to the multi-modal optimization community
- New competitive and very promising approaches in new performance scenarios

Key characteristics of the algorithms:

- Methodologies: repelling, restarts, clustering, hill-valley approaches, post-processing
- Usage of local models to maintain diversity and exploit locally the neighborhoods
- Algorithms: CMA-ES, and GAs

Possible objectives:

- Re-organize the competitions from scratch
- Enhance the benchmark function set
- Introduce new performance measures

Results of the GECCO 2017 Competition on Niching Methods for Multimodal Optimization

M.G. Epitropakis¹, M. Preuss², X. Li³, and A. Engelbrecht³

¹Data Science Institute, Department of Management Science, Lancaster University, UK

²ERCIS, WWU Muenster, Muenster, Germany

³School of Computer Science and Information Technology, RMIT University, Australia

⁴Department of Computer Science, University of Pretoria, South Africa

GECCO 2017 Competition on Niching Methods

m.epitropakis@lancaster.ac.uk
xiaodong.li@rmit.edu.au

mike.preuss@uni-muenster.de
engel@cs.up.ac.za

- [1.] Simon Wessing. Two-stage methods for multimodal optimization. PhD thesis, Technische Universität Dortmund, 2015. <http://hdl.handle.net/2003/34148>
- [2.] Multimodal Optimization by Covariance Matrix Self-Adaptation Evolution Strategy with Repelling Subpopulations, Ali Ahrari, Kalyanmoy Deb and Mike Preuss, DOI: 10.1162/EVCO_a_00182, Evolutionary Computation, p.1-33
http://www.mitpressjournals.org/doi/abs/10.1162/EVCO_a_00182
- [3.] C.S. de Magalhães, D.M. Almeida, H.J.C. Barbosa, L.E. Dardenne, A dynamic niching genetic algorithm strategy for docking highly flexible ligands, Inf. Sci. 289 (2014) 206–224.