

A diagram of a 4-pin header. The pins are labeled from left to right: R, PI, UART, and 5GTR. The first pin (R) is highlighted with a yellow box.

No Wolves were harmed ... very much
in the creation of this PCB

Temp G12
Humidity

much C12 MEMS Mic

Battery Positive 25
gives here

TESTED ONCE. SEEMED FINE.

- Accelerometer
- Magnetometer



Pin	Signal
1	NC
2	NC
3	NC
4	NC
5	NC
6	NC
7	NC
8	NC
9	NC
10	NC
11	NC
12	NC
13	NC
14	NC
15	NC
16	NC
17	NC
18	NC
19	NC
20	NC
21	NC
22	NC
23	NC
24	NC
25	NC
26	NC
27	NC
28	NC
29	NC
30	NC
31	NC
32	NC

GP42
the Answer?

IF FOUND, RETURN TO JENNA



COLLAR_PET SENSOR NODE, REV A
PROTOTYPE UNIT - DO NOT PANIC
IT HAS NOT EXPLODED YET
MIC

RECOVERED FROM THE LAB
ESCAPED WITH HARDWARE
Assembled by Paw

WARNING: CONTAINS MORE GPIO THAN NECESSARY

UART 1 RX Sel TX Sel UART 0

DESIGNED WITHOUT ADULT SUPERVISION

DO NOT LICK THE PCB

PROPERTY OF FMI - PROBABLY

CERTIFIED MOSTLY SAFE

BUILT & ASSEMBLED IN QUESTIONABLE CONDITIONS
WARRANTY VOID IF OBSERVED

FIELD MODIFIED / UNAUTHORIZED