Basic Electrical Technology

Parallel Magnetic Circuits

Parallel Magnetic Circuit

- More than one path for flux
- $\Phi = \Phi_1 + \Phi_2$

$$S_{AB} = \frac{l_{AB}}{\mu_0 \, \mu_{rAB} \, A_{AB}}$$

$$S_{ADCB} = \frac{l_{ADCB}}{\mu_0 \, \mu_{rADCB} \, A_{ADCB}}$$

$$S_{AFEB} = \frac{l_{AFEB}}{\mu_0 \, \mu_{rAFEB} \, A_{AFEB}}$$





Analogous Electrical Circuit

Parallel Magnetic Circuit

- $(Mmf)_{Total} = (Mmf)_{AB} + (Mmf)_{ADCB}$

  OR

  $(Mmf)_{Total} = (Mmf)_{AB} + (Mmf)_{AFEB}$



- $(Mmf)_{Total} = \Phi S_{AB} + \Phi_1 S_{ADCB}$

  OR

  $(Mmf)_{Total} = \Phi S_{AB} + \Phi_2 S_{AFEB}$



Analogous Electrical Circuit

Parallel Magnetic Circuit with Air Gap





$$S_{AFEB} = \frac{(l_{AFEB} - l_{gleft})}{\mu_0 \, \mu_{rAFEB} \, A_{AFEB}}; \qquad S_{AB} = \frac{(l_{AB} - l_{gcenter})}{\mu_0 \, \mu_{rAB} \, A_{AB}}$$

Illustration 1

The magnetic circuit shown in Fig. is made of a material having relative permeability of 2000. The central limb is wound with 1000 turns and has an airgap of length of 2mm. The side limb airgap is 8 mm. Calculate the current required to set up a flux of 2.6 mWb in the central limb. Mean lengths of various sections are as follows: AB = 24 cm, ACDB = AFGHEB = 60 cm. Cross sectional area of the structure is 10 cm^2.



Ans: 4.98 A

Illustration 2

A coil carrying a current of 2.8 A is wound on the left limb of the cast steel symmetrical frame of uniform square cross section 16 cm^2 as shown in Fig. Calculate the number of turns in the coil to produce a flux of 1.8 mWb in the air gap of 0.2 cm length. The relative permeability of cast steel is 1200.



Ans: 1480