

S10_2

1 D - A r r a y s



Objectives

To learn and appreciate the following concepts:

- Declare, initialize and access 1D array.
- Write programs using common data structures namely arrays and strings and solve problems.



Session outcome

- At the end of session student will be able to
 - Declare, initialize and access 1D array
 - Write programs using 1D array



Arrays – recap

1D Array:

- Syntax: `type array_name[size];`
- Memory Requirement:
`Total size = size * (sizeof(data_type));`
- Initialization:
`type array-name [size]={list of values}`
- Write and Read:

<code>for(i=0;i<n;i++)</code>	<code>for(i=0;i<n;i++)</code>
<code>scanf("%d",&a[i]);</code>	<code>printf("%d\n",a[i]);</code>



WAP to insert an element to an array at a given position

```
int a[100], n,i, pos, ele;

scanf("%d",&n); // number of elements
printf("\nEnter the elements of array:");
for(i=0;i<n;i++)

    scanf ("%d" , &a[i]) ;

printf("\nEnter the element and position  of insertion:");

scanf ("%d %d" , &ele , &pos) ;

for(i=n; i>=pos; i--) //shift the elements to right

    a[i]=a[i-1];

a[pos-1] = ele; //ele is inserted at the specified pos.
n = n + 1;      // increment the count of no of elements
printf("\nThe array after insertion is:");
for(i=0;i<n; i++)    printf ("%d\n" , a[i]) ;
```

Example : insert 9 at 2nd position

a[]={1, 2, 3, 4, 5}

New array after inserting 9 :

a[]={1, 9, 2, 3, 4, 5}



WAP to delete an element from an array

```
printf("enter no of numbers");
```

```
scanf ("%d" , &n) ;
```

```
printf("enter n numbers \n");
```

```
for(i=0;i<n;i++)
```

```
    scanf ("%d" , &a[i]) ;
```

```
printf("enter the position at which the element to be deleted");
```

```
scanf ("%d" , &pos) ;
```

```
for(i=pos-1; i<n-1; i++)
```

```
    a[i] =a[i+1]; //shift the elements to left
```

```
n = n-1;      //decrement the count of no of elements
```

```
for(i=0;i<n;i++)
```

```
    printf ("%d" , a[i]) ;
```

Example : delete ele at 2nd position

a[]={1, 2, 3, 4, 5}

New array after deleting 2:

a[]={1, 3, 4, 5}



Insert an element into a sorted array

Read array elements (in sorted order) & element '**ele**' to be inserted

```
//finding position
```

```
for(i=0;i<n;i++)
```

```
    if (ele<a[i])
```

```
        break;
```

```
pos = i+1; //position of insertion
```

```
for(i=n; i>=pos; i--) //shift the elements to right
```

```
    a[i]=a[i-1];
```

```
a[pos-1] = ele; //ele is inserted at the specified pos.
```


```
n = n + 1;    // increment the count of no of elements
```

Example: insert 3 into the array

a[] = {1, 2, 4, 5, 6}

New array after inserting 3 :

a[] = {1, 2, 3, 4, 5, 6}



Go to posts/chat box for the link to the question

submit your solution in next 2 minutes

The session will resume in 3 minutes



Tutorials on Array

- Write a C program to find average of an 1-D array.
- Write a C program to find second largest element in an array.
- Write a C program to find union and intersection of two arrays.



Largest and second largest element in an array

/ assume first element of the array as the largest & second largest */*

```
largest1 = array[0];
```

```
largest2 = array[1];
```

```
for (i = 1; i < MAX; i++)  
{  
    if (array[i] >= largest1)  
    {  
        largest2 = largest1;  
        largest1 = array[i];  
    }  
    else if (array[i] > largest2)  
    {  
        largest2 = array[i];  
    }  
}
```

Example: array[] = {22,44, 34, 9, 21}

44 is largest

34 is second largest



Summary

- Problems on 1D arrays