

# Machine Intelligence II

## Online-PCA (Hebbian Learning)

### Tutorial

Neural Information Processing Group (Prof. Dr. Klaus Obermayer)

19.05.2016

# Projection Methods

- Principal Component Analysis (PCA)
- Online-PCA  $\Rightarrow$  Hebbian Learning
- Nonlinear Structure  $\Rightarrow$  Kernel PCA
- Source Separation
  - Model based  $\Rightarrow$  Independent Component Analysis (ICA)
  - Cost Function Based  $\Rightarrow$  Projection Pursuit

# Principal Components (PCs): "interesting" directions

Eigenvalue problem yields direction in feature space with max. variance

$$\underline{\mathbf{C}}\underline{\mathbf{e}}_i = \lambda_i\underline{\mathbf{e}}_i, \quad i = 1, \dots, N$$

# Principal Components (PCs): "interesting" directions

Eigenvalue problem yields direction in feature space with max. variance

$$\underline{\mathbf{C}}\underline{\mathbf{e}}_i = \lambda_i\underline{\mathbf{e}}_i, \quad i = 1, \dots, N$$

⇒ **Principal Components:** normalized eigenvector  $\underline{\mathbf{e}}_i$  of  $\underline{\mathbf{C}}$

⇒ Variance along a PC is given by the corresponding Eigenvalue

$$\sigma_i^2 = \underline{\mathbf{e}}_i^T \underline{\mathbf{C}} \underline{\mathbf{e}}_i = \lambda \underline{\mathbf{e}}_i^2 = \lambda_i$$

# Principal Components (PCs): "interesting" directions

Eigenvalue problem yields direction in feature space with max. variance

$$\underline{\mathbf{C}}\underline{\mathbf{e}}_i = \lambda_i\underline{\mathbf{e}}_i, \quad i = 1, \dots, N$$

⇒ **Principal Components**: normalized eigenvector  $\underline{\mathbf{e}}_i$  of  $\underline{\mathbf{C}}$

⇒ Variance along a PC is given by the corresponding Eigenvalue

$$\sigma_i^2 = \underline{\mathbf{e}}_i^T \underline{\mathbf{C}}\underline{\mathbf{e}}_i = \lambda \underline{\mathbf{e}}_i^2 = \lambda_i$$

⇒ ordering of principal components w.r.t. variance:


$$\begin{array}{ccccccc} \lambda_1 & > & \lambda_2 & > & \lambda_3 & > & \dots\dots\dots & > & \lambda_{N-1} & > & \lambda_N \\ \downarrow & & \downarrow & & \downarrow & & & & \downarrow & & \downarrow \\ \underline{\mathbf{e}}_1 & & \underline{\mathbf{e}}_2 & & \underline{\mathbf{e}}_3 & & & & \underline{\mathbf{e}}_{N-1} & & \underline{\mathbf{e}}_N \end{array}$$

$\underline{\mathbf{e}}_i$ : direction of largest variance in the subspace  $\text{span}\{\underline{\mathbf{e}}_i, \underline{\mathbf{e}}_{i+1}, \dots, \underline{\mathbf{e}}_N\}$

# Online-PCA

Biologically plausible implementation  
online learning

# Linear connectionist neurons



$$y = \underline{\mathbf{w}}^T \underline{\mathbf{x}}$$

observations:  $\underline{\mathbf{x}}^{(\alpha)}, \alpha = 1, \dots, p, \underline{\mathbf{x}}^{(\alpha)} \in \mathbb{R}^N$

# Hebbian (correlation-based) learning for linear neurons

The Organization of Behavior (Donald Hebb, 1949): **fire together-wire together**



# Hebbian (correlation-based) learning for linear neurons

The Organization of Behavior (Donald Hebb, 1949): **fire together-wire together**

---

initialization of weights  $\underline{\mathbf{w}}$  (e.g. sample small random numbers)

choose (small) learning rate  $\varepsilon$

**begin** loop

    Choose an observation  $\underline{\mathbf{x}}^{(\alpha)}$

    Change weights according to:

$$\Delta \mathbf{w}_j = \varepsilon y_{(\underline{\mathbf{x}}^{(\alpha)}; \underline{\mathbf{w}})} x_j^{(\alpha)} = \varepsilon \left( \underline{\mathbf{w}}^T \underline{\mathbf{x}}^{(\alpha)} \right) x_j^{(\alpha)}, \quad j = 1, \dots, N$$

**end**

---

# Hebbian (correlation-based) learning for linear neurons

The Organization of Behavior (Donald Hebb, 1949): **fire together-wire together**

---

initialization of weights  $\underline{\mathbf{w}}$  (e.g. sample small random numbers)

choose (small) learning rate  $\varepsilon$

**begin** loop

    Choose an observation  $\underline{\mathbf{x}}^{(\alpha)}$

    Change weights according to:

$$\Delta \mathbf{w}_j = \varepsilon y_{(\underline{\mathbf{x}}^{(\alpha)}; \underline{\mathbf{w}})} x_j^{(\alpha)} = \varepsilon \left( \underline{\mathbf{w}}^T \underline{\mathbf{x}}^{(\alpha)} \right) x_j^{(\alpha)}, \quad j = 1, \dots, N$$

**end**

---

⇒ weights increase (decrease) if input and output are correlated (anticorrelated)

# Hebbian (correlation-based) learning for linear neurons

The Organization of Behavior (Donald Hebb, 1949): **fire together-wire together**

---

initialization of weights  $\underline{\mathbf{w}}$  (e.g. sample small random numbers)

choose (small) learning rate  $\varepsilon$

**begin** loop

    Choose an observation  $\underline{\mathbf{x}}^{(\alpha)}$

    Change weights according to:

$$\Delta w_j = \varepsilon y_{(\underline{\mathbf{x}}^{(\alpha)}; \underline{\mathbf{w}})} x_j^{(\alpha)} = \varepsilon \left( \underline{\mathbf{w}}^T \underline{\mathbf{x}}^{(\alpha)} \right) x_j^{(\alpha)}, \quad j = 1, \dots, N$$

**end**

---

⇒ weights increase (decrease) if input and output are correlated (anticorrelated)

## Proposition

Hebb's rule extracts the PC with the largest eigenvalue:  $\underline{\mathbf{w}} \propto \underline{\mathbf{e}}_1$

Proofs: deterministic version → lecture notes; stochastic version → Haykin book

# Implications

# Implications

- model for learning of receptive fields and the resulting *neural code*

# Implications

- model for learning of receptive fields and the resulting *neural code*
- adaptive tracking of the direction of largest variance: "on-line" PCA

# Implications

- model for learning of receptive fields and the resulting *neural code*
- adaptive tracking of the direction of largest variance: "on-line" PCA

*Problem:*  $\|w\| \rightarrow \infty \Rightarrow$  requires some form of ("biological"?) normalization

# Implications

- model for learning of receptive fields and the resulting *neural code*
- adaptive tracking of the direction of largest variance: "on-line" PCA

*Problem:*  $\|w\| \rightarrow \infty \Rightarrow$  requires some form of ("biological"?) normalization

**Solution: Normalization via Oja's rule**



# Implications

- model for learning of receptive fields and the resulting *neural code*
- adaptive tracking of the direction of largest variance: "on-line" PCA

*Problem:*  $\|w\| \rightarrow \infty \Rightarrow$  requires some form of ("biological"?) normalization

**Solution: Normalization via Oja's rule**

$$\Delta w_j = \varepsilon y(\underline{x}^{(\alpha)}; \underline{w}) \left\{ \underbrace{x_j^{(\alpha)}}_{\text{Hebbian learning}} - \underbrace{y(\underline{x}^{(\alpha)}; \underline{w}) w_j}_{\text{decay term}} \right\}$$

# Implications

- model for learning of receptive fields and the resulting *neural code*
- adaptive tracking of the direction of largest variance: "on-line" PCA

*Problem:*  $\|w\| \rightarrow \infty \Rightarrow$  requires some form of ("biological"?) normalization

**Solution: Normalization via Oja's rule**

$$\Delta w_j = \varepsilon y(\underline{x}^{(\alpha)}; \underline{w}) \left\{ \underbrace{x_j^{(\alpha)}}_{\text{Hebbian learning}} - \underbrace{y(\underline{x}^{(\alpha)}; \underline{w}) w_j}_{\text{decay term}} \right\}$$

## Proposition

Oja's rule converges to the unit vector which points into the direction of the largest variance:  $\underline{w} \rightarrow \underline{e}_1$  (proof:  $\leadsto$  group presentation)