

Motorised Change-Over Switches Three Pole Type OTM



Part Number	Frame Sizes	Rated Current AC22A @ 400VAC	Rated Power AC22A @ 400VAC	Motor Voltage	Page Number	ZAR Price
1SCA022845R8110	OTM160E3CM24D	160A	110kVA	24VDC	175	R20 344
1SCA022845R8290	OTM200E3CM24D	200A	135kVA	24VDC	175	R24 888
1SCA022845R8370	OTM250E3CM24D	250A	170kVA	24VDC	175	R25 099
1SCA022847R0910	OTM315E3CM24D	315A	215kVA	24VDC	175	R35 243
1SCA022847R1390	OTM400E3CM24D	400A	275kVA	24VDC	175	R41 623
1SCA022873R1210	OTM630E3CM24D	630A	435kVA	24VDC	175	R49 884
1SCA022872R5910	OTM800E3CM24D	800A	550kVA	24VDC	175	R62 877
1SCA113672R1001	OTM1000E3CM24D	1000A	680kVA	24VDC	175	R85 595

Accessories Auxiliary contacts (AUX)

Part Number	Frame Size Range	Auxiliary Contacts
1SCA022353R4970	OTM160 to OTM3200	1 n/o
1SCA022353R4890	OTM160 to OTM3200	1 n/c



Installation Side	Page Number	ZAR Price
Right	181	R249
Right	181	R273

Depending on your electrical design, two auxiliaries may be required. One to indicate that the switch is in position I and another to indicate the switch is in position II. A maximum of 8(4 per switch) auxiliary blocks can be used on the OTM range 160A and above.

Accessories Bridging Bars (3 per Set)

Part Number	Frame Size Range
1SCA022767R6910	OTM160 to OTM250
1SCA022767R7120	OTM315 to OTM400
1SCA022785R7020	OTM630 to OTM800
1SCA022868R0710	OTM1000 to OTM1250



Buying bridging bars negates the necessity of building bus bars or making electrical links for S1, S2 and load system.

Page Number	ZAR Price
183	R701
183	R989
183	R2 059
183	R6 671

Notes:

- * OTM's with 230VAC rated motors are available on request.
- * OTM's with 4-pole option are available on request.
- * OTM's with higher and lower Amperage ratings are available on request.
- * Refer to ABB 2019-2020 Price Catalogue for specified page numbers.
- * List of T's & C's appear on page 8 of 8.