



83 Piercy Avenue Parkhill Gardens Germiston

> P.O Box 15419 Lambton 1414 South Africa

Reg. No.2009/189488/23

Issue 12 April 2022

Tel: +27 11 827 1386 Fax: +27 86 597 6836 www.hagar.co.za info@hagar.co.za

# Pluggable Interface Relays and Bases

## **CR-M Range (without LED's)**

Page 1 of 8

AUD
24 V DE MOZADCALO
FOYAC RES
1A 240 V AC
· · · · · · · · · · · · · · · · · · ·
CELLER
214 Zin Din William
1
P
9

Part	Control	Number of	Contact	Description	Order	ZAR
Number	Voltage	Contacts	Rating	•	Code	Price
CR-M012DC2	12VDC	2 c/o ( SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405611R4000	R121
CR-M024DC2	24VDC	2 c/o ( SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405611R1000	R121
CR-M230AC2	230VAC	2 c/o ( SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405611R3000	R142
CR-M012DC4	12VDC	4 c/o ( SPDT)	6A @ 250V	14 Pin Pluggable Relay	1SVR405613R4000	R129
CR-M024DC4	24VDC	4 c/o ( SPDT)	6A @ 250V	14 Pin Pluggable Relay	1SVR405613R1000	R129
CR-M230AC4	230VAC	4 c/o ( SPDT)	6A @ 250V	14 Pin Pluggable Relay	1SVR405613R3000	R151

Notes

Relays has a test flag function which can be latched. The flag is Green for DC or Orange for AC coils. Relay Bases are DIN 35 Rail Mounted. C/O can be paralleled to increase the Current Rating. Choose the CR-U Range if higher current rating is required.



#### Base for CR-M Relays

CR-M2SS CR-M4SS Standard Base for CR-M 2 c/o Relay 1SVR405651R1000 R76 Standard Base for CR-M 4 c/o Relay 1SVR405651R3000 R87

### Pluggable Interface Relays and Bases

### **CR-U Range (without LED's)**



	Part	Control	Number of	Contact	Description	Order	ZAR
	Number	Voltage	Contacts	Rating		Code	Price
Г	CR-U012DC2	12VDC	2 c/o ( SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405621R4000	R182
	CR-U024DC2	24VDC	2 c/o ( SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405621R1000	R182
	CR-U230AC2	230VAC	2 c/o ( SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405621R3000	R192
	CR-U012DC3	12VDC	3 c/o ( SPDT)	10A @ 250V	11 Pin Pluggable Relay	1SVR405622R4000	R188
	CR-U024DC3	24VDC	3 c/o ( SPDT)	10A @ 250V	11 Pin Pluggable Relay	1SVR405622R1000	R188
	CR-U230AC3	230VAC	3 c/o ( SPDT)	10A @ 250V	11 Pin Pluggable Relay	1SVR405622R3000	R200

Notes

Relays has a test flag function which can be latched. The flag is Green for DC or Orange for AC coils. Relay Bases are DIN 35 Rail Mounted. C/O can be paralleled to increase the Current Rating. Choose the CR-M Range if space is a consideration.



CR-U2S CR-U3S Standard Base for CR-U 2 c/o Relay 1SVR405670R0000 R91 Standard Base for CR-U 3 c/o Relay 1SVR405660R0000 R93

#### Notos:

- \* More options on the relays are available on request, ie; CR-M/CR-U with LED and non standard coil voltages.
- \* For accessories on the relays or sockets please enquire with us, ie; diode, varistor, gold contacts etc.
- $^{\star}$  Refer to ABB 2019-2020 Price Catalogue for the specified page numbers shown below.
- \* For CR-M type, see page 358.
- \* For CR-M accessories, see page 360.
- \* For CR-U socket/base, see page 364.
- \* List of T's & C's appear on page 8 of 8

- \* For CR-M socket/base, see page 360.
- \* For CR-U type, see page 364.
- \* For CR-U accessories, see page 366.