

# MAKE & TAKE SERIES

# PLANT STAND

IN PARTNERSHIP WITH 

Make this beautiful plant stand and learn how to build using a pocket hole jig.

[www.rockler.com](http://www.rockler.com)  
800-279-4441

## GET FROM ROCKLER

Stock #	Item
(2) 36355	Mahogany by the Piece, 3/4" X 5" X 48"
(1) 65391	Kreg Pocket Hole Jig 310
(1) 38502	Kreg® 1-1/4"L #7 Fine-Thread Washer-Head Pocket Hole Screws, 100-
(1) 51487	Kreg Automaxx 3" Wood Project Clamp
(1) 64980	General Finishes Outdoor Oil

### 1. RIP LUMBER TO WIDTH



You can purchase lumber that is 2-1/2" wide or rip your lumber into 2-1/2"-wide boards.

### 2. CUT THE PARTS TO LENGTH



Cut the legs and cross braces to length. In this case we used a miter saw to cut these parts.

### 3. POCKET HOLE SCREWS



This project is assembled with pocket hole screws. Screws are driven into an angled pocket hole that features a flat bottom.

### 4. BORE THE POCKET HOLES



Use a pocket hole jig and stepped drill bit to bore two pocket holes in each end of the crossbraces. We used the Kreg Pocket Hole Jig 310. Locate the holes 3/4" from the side edges of the crossbraces.

### 5. ASSEMBLE THE CROSS BRACES




Assemble the cross braces with 1-1/4" pocket hole screws. We used a Kreg Project Clamp to keep the faces of the cross brace parts flush with each other.


### 6. ATTACH CROSS BRACES TO LEGS




Attach the cross brace assemblies to the legs. Use a square to position the cross brace perpendicular to the leg. Finally, apply your choice of stain or top coat.



**SIDE VIEW**



**TOP VIEW**



## MATERIAL LIST

	T	x	W	x	L
<b>A</b> Legs (4)	3/4"	x	2-1/2"	x	32"
<b>B</b> Long Cross Brace (2)	3/4"	x	2-1/2"	x	13"
<b>C</b> Short Cross-Braces (4)	3/4"	x	2-1/2"	x	5-1/4"